

Question 1 of 62



Choose 1 option.

A developer notices the execution of all the test methods in a class takes a long time to run, due to the initial setup of all the test data that is needed to perform the tests.

What should the developer do to speed up test execution?

- ☐ A. Reduce the amount of test methods in the class.
- ☐ B. Ensure proper usage of test data factory in all test methods.
- ☐ C. Define a method that creates test data and annotate with `@createData`.
- ☒ D. Define a method that creates test data and annotate with `@testSetup`.



Choose 1 option.

A Salesforce Platform Developer is leading a team that is tasked with deploying a new application to production. The team has used source-driven development, and they want to ensure that the application is deployed successfully.

What tool or mechanism should be used to verify that the deployment is successful?

- ☐ A. Force.com Migration Tool
- ☐ B. Apex Test Execution
- ☒ C. Salesforce DX CLI
- ☐ D. Salesforce Inspector

Question 3 of 62

Choose 1 option.

What is a benefit of JavaScript remoting over Visualforce Remote Objects?

- ☒ A. Supports complex server-side application logic
- ☐ B. Does not require any Apex code
- ☐ C. Does not require any JavaScript code
- ☐ D. Allows for specified re-render targets

Question 4 of 62



Choose 1 option.

An org records customer order information in a custom object, `Order__c`, that has fields for the shipping address. A developer is tasked with adding code to calculate shipping charges on an order, based on a flat percentage rate associated with the region of the shipping address.

What should the developer use to store the rates by region, so that when the changes are deployed to production no additional steps are needed for the calculation to work?

- ☒ A. Custom metadata type
- ☐ B. Custom object
- ☐ C. Custom list setting
- ☐ D. Custom hierarchy setting

Question 5 of 62



Choose 1 option.

A developer is debugging an Apex-based order creation process that has a requirement to have three savepoints, SP1, SP2, and SP3 (created in order), before the final execution of the process.

During the final execution process, the developer has a routine to roll back to SP1 for a given condition. Once the condition is fixed, the code then calls a roll back to SP3 to continue with final execution. However, when the roll back to SP3 is called, a runtime error occurs.

Why does the developer receive a runtime error?

- ☒ A. SP3 became invalid when SP1 was rolled back.
- ☐ B. The developer should have called SP2 before calling SP3.
- ☐ C. The developer used too many savepoints in one trigger session.
- ☐ D. The developer has too many DML statements between the savepoints.

Question 6 of 62



Choose 1 option.

A developer needs to implement a historical Task reporting feature that allows users, assigned to a custom profile named "Auditors", to perform searches against the Tasks related to the Account object.

The developer must ensure the search is able to return Tasks that are between 12 and 24 months old. It should exclude any tasks which have been deleted, and include Tasks whether archived or not.

Given the following code, which select statement should be inserted at the placeholder as a valid way to retrieve the Tasks ranging from 12 to 24 month old?

```
Date initialDate = System.Today().addMonths(-24);  
Date endDate = System.Today().addMonths(-12);  
// Insert SELECT statement here
```

- ☒ A. [SELECT AccountId, CreatedDate, Subject
FROM Task
WHERE What.Type = 'Account' AND isArchived=true AND CreatedDate => :initialDate AND
CreatedDate <= :endDate];
- ☐ B. [SELECT AccountId, CreatedDate, Subject
FROM Task
WHERE What.Type = 'Account' AND CreatedDate => :initialDate AND CreatedDate <= :endDate
ALL ROWS];
- ☐ C. [SELECT AccountId, CreatedDate, Subject
FROM Task
WHERE What.Type = 'Account' AND isDeleted=false AND CreatedDate => :initialDate AND
CreatedDate <= :endDate ALL ROWS];
- ☐ D. [SELECT AccountId, CreatedDate, Subject
FROM Task
WHERE What.Type = 'Account' AND isArchived=true AND CreatedDate => :initialDate AND
CreatedDate <= :endDate ALL ROWS];

Question 7 of 62



Choose 1 option.

A company has code to update a Request and Request Lines and make a callout to their external ERP system's REST endpoint with the updated records.

```
public void updateAndMakeCallout(Map<Id, Request__c> reqs, Map<Id, Request_Line__c> reqLines) {  
    Savepoint sp = Database.setSavepoint();  
  
    try {  
        insert reqs.values();  
        insert reqLines.values();  
        HttpResponse response = CalloutUtil.makeRestCallout(reqs.keySet(), reqLines.keySet());  
    } catch (Exception e) {  
        Database.rollback(sp);  
        System.debug(e);  
    }  
}
```

The `CalloutUtil.makeRestCallout` fails with a 'You have uncommitted work pending. Please commit or rollback before calling out' error.

What should be done to address the problem?

- ☐ A. Move the `CalloutUtil.makeRestCallout` method call below the catch block.
- ☒ B. Change the `CalloutUtil.makeRestCallout` to an `@future` method.
- ☐ C. Remove the `Database.setSavepoint` and `Database.rollback`.
- ☐ D. Change the `CalloutUtil.makeRestCallout` to an `@InvocableMethod` method.



Choose 1 option.

A developer writes a Lightning web component that displays a dropdown list of all custom objects in the org from which a user will select. An Apex method prepares and returns data to the component.

What should the developer do to determine which objects to include in the response?

- ☐ A. Import the list of all custom objects from `@salesforce/schema`.
- ☐ B. Check the `getObjectType()` value for 'Custom' or 'Standard' on the `sObject` describe result.
- ☒ C. Check the `isCustom()` value on the `sObject` describe result.
- ☐ D. Use the `getCustomObjects()` method from the `Schema` class.

Question 9 of 62



Choose 2 options.

As part of point-to-point integration, a developer must call an external web service which, due to high demand, takes a long time to provide a response. As part of the request, the developer must collect key inputs from the end user before making the callout.

Which two elements should the developer use to implement these business requirements?

- ☐ A. Screen Flow
- ☐ B. Batch Apex
- ☒ C. Apex method that returns a Continuation object
- ☒ D. Lightning web component

Question 10 of 62



Choose 1 option.

A developer is asked to find a way to store secret data with an ability to specify which profiles and users can access which secrets.

What should be used to store this data?

- ☐ A. Static resources
- ☐ B. Custom metadata
- ☒ C. Custom settings
- ☐ D. `System.Cookie` class

Question 11 of 62



Choose 1 option.

Consider the following code snippet:

```
01 public class with sharing AccountsController{
02
03     @AuraEnabled
04     public List<Accounts> getAllAccounts() {
05         return [Select Id, Name, Industry FROM Account];
06     }
07
08 }
```

As part of the deployment cycle, a developer creates the following test class:

```
01 private class with sharing AccountsController_Test{
02
03     @TestSetup
04     private static void makeData(){
05         User user1 = [Select Id FROM User WHERE Profile.Name = 'System Administrator' and
isActive = true LIMIT 1 ];
06         User user2 = [Select Id FROM User WHERE Profile.Name = 'Standard User' and userName =
'test@test.com' and isActive = true LIMIT 1];
07
08         TestUtils.insertAccounts(10,user1.Id);
09         TestUtils.insertAccounts(20,user2.Id);
10     }
11
12     @IsTest
13     private static void getAllAccounts_StandardUser_Test(){
14
15         List<Account> result = AccountsController.getAllAccounts();
16         System.assertEquals(20,result.size());
17
18     }
```

```
11
12     @IsTest
13     private static void getAllAccounts_StandardUser_Test() {
14
15         List<Account> result = AccountsController.getAllAccounts();
16         System.assertEquals(20, result.size());
17
18     }
19
20 }
```

When the test class runs, the assertion fails.

Which change should the developer implement in the Apex test method to ensure the test method executes successfully?

- ☐ A. Add `@IsTest(seeAllData=true)` to line 12 and enclose lines 15 and 16 within `Test.startTest()` and `Test.stopTest()`.
- ☐ B. Query the Administrator user into memory and enclose lines 15 and 16 within the `System.runAs(user)` method.
- ☒ C. Query the Standard User into memory and enclose lines 15 and 16 within the `System.runAs(user)` method.
- ☐ D. Add `System.runAs(User)` to line 14 and enclose line 15 within `Test.startTest()` and `Test.stopTest()`.

Question 12 of 62

Choose 1 option.

A developer is trying to access org data from within a test class.

Which sObject type requires the test class to have the (seeAllData=true) annotation?

- ☐ A. RecordType
- ☒ B. Report
- ☐ C. User
- ☐ D. Profile



Choose 3 options.

Which three Visualforce components can be used to initiate Ajax behavior to perform partial page updates?

- ☐ A. `<apex:form>`
- ☐ B. `<apex:actionStatus>`
- ☒ C. `<apex:commandButton>`
- ☒ D. `<apex:actionSupport>`
- ☒ E. `<apex:commandLink>`

Question 14 of 62



Choose 1 option.

Universal Containers develops a Salesforce application that requires frequent interaction with an external REST API.

To avoid duplicating code and improve maintainability, how should they implement the API integration for code reuse?

- ☒ A. Create a reusable Apex class for the API integration and invoke it from the relevant Apex classes.
- ☐ B. Use a separate Apex class for each API endpoint to encapsulate the integration logic.
- ☐ C. Store the API integration code as a static resource and reference it in each Apex class.
- ☐ D. Include the API integration code directly in each Apex class that requires it.

Question 15 of 62



Choose 1 option.

A developer is asked to modify a Lightning web component so that it displays in one column on phones and in two columns on tablets, desktops, and larger devices.

Given to the code below:

```
<lightning-layout multiple-rows="true">
  <lightning-layout-item>
    <div>Example 1</div>
  </lightning-layout-item>
  <lightning-layout-item>
    <div>Example 2</div>
  </lightning-layout-item>
</lightning-layout>
```

Which should the developer add to the code to meet the requirements?

- ☐ A. Add `size="12"` `medium-device-size="6"` to the `<lightning-layout-item>` elements
- ☒ B. Add `size="6"` `small-device-size="12"` to the `<lightning-layout-item>` elements
- ☐ C. Add `small-device-size="12"` to the `<lightning-layout-item>` elements
- ☐ D. Add `medium-device-size="6"` to the `<lightning-layout-item>` elements

Question 16 of 62



Choose 1 option.

A company uses an external system to manage its custom account territory assignments. Every quarter, millions of Accounts may be updated in Salesforce with new Owners when the territory assignments are completed in the external system.

What is the optimal way to update the Accounts from the external system?

- ☐ A. Composite REST API
- ☐ B. SOAP API
- ☐ C. Bulk API
- ☒ D. Apex REST Web Service



Choose 1 option.

Consider the following code snippet:

```
public static List<Account> getAccounts(Date thisDate, Id goldenRT){  
    List<Account> accountList = [Select Id, Name, Industry FROM Account WHERE CreatedDate = :thisDate OR  
    RecordTypeId = :goldenRT];  
    return accountList;  
}
```

The Apex method is executed in an environment with a large data volume count for Accounts, and the query is performing poorly.

Which technique should the developer implement to ensure the query performs optimally, while preserving the entire result set?

- ☒ A. Break down the query into two individual queries and join the two result sets.
- ☐ B. Annotate the method with the `@Future` annotation.
- ☐ C. Use the `Database.queryLocator` method to retrieve the accounts.
- ☐ D. Create a formula field to combine the `CreatedDate` and `RecordType` value, then filter based on the formula.

Question 18 of 62

Choose 1 option.

Which use case can be performed only by using asynchronous Apex?

- ☐ A. Querying tens of thousands of records
- ☐ B. Making a call to schedule a batch process to complete in the future
- ☒ C. Calling a web service from an Apex trigger
- ☐ D. Updating a record after the completion of an insert

Question 19 of 62



Choose 1 option.

Which interface needs to be implemented by an Aura component so that it may be displayed in modal dialog by clicking a button on a Lightning record page?

- ☐ A. `lightning:editAction`
- ☐ B. `lightning:quickAction`
- ☐ C. `force:lightningEditAction`
- ☒ D. `force:lightningQuickAction`

Question 20 of 62



Choose 1 option.

A developer is asked to build a solution that will automatically send an email to the customer when an Opportunity stage changes. The solution must scale to allow for 10,000 emails per day. The criteria to send the email should be evaluated after certain conditions are met.

What is the optimal way to accomplish this?

- ☐ A. Use an Apex trigger with Batch Apex.
- ☐ B. Use `MassEmailMessage()` with an Apex trigger.
- ☐ C. Use `SingleEmailMessage()` with an Apex trigger.
- ☒ D. Use an Email Alert with Flow Builder.

Question 21 of 62



Choose 1 option.

Refer to the component code and requirements below:

```
<lightning:layout multipleRows="true">
  <lightning:layoutItem size="12">{!v.account.Name}
</lightning:layoutItem>

  <lightning:layoutItem size="12">{!v.account.AccountNumber}
</lightning:layoutItem>

  <lightning:layoutItem size="12">{!v.account.Industry}
</lightning:layoutItem>
</lightning:layout>
```

Requirements:

1. For mobile devices, the information should display in three rows.
2. For desktops and tablets, the information should display in a single row.

Requirement 2 is not displaying as desired.

Which option has the correct component code to meet the requirements for desktops and and tablets?

- ☐ A.

```
<lightning:layout multipleRows="true">
  <lightning:layoutItem size="12" mediumDeviceSize="6">{!v.account.Name}
</lightning:layoutItem>

  <lightning:layoutItem size="12" mediumDeviceSize="6">{!v.account.AccountNumber}
</lightning:layoutItem>

  <lightning:layoutItem size="12" mediumDeviceSize="6">{!v.account.Industry}
</lightning:layoutItem>
</lightning:layout>
```
- ☐ B.

```
<lightning:layout multipleRows="true">
```

```
</lightning:layout>
```

☐ C. `<lightning:layout multipleRows="true">`

```
  <lightning:layoutItem size="12" largeDeviceSize="4">{!v.account.Name}
</lightning:layoutItem>
```

```
  <lightning:layoutItem size="12" largeDeviceSize="4">{!v.account.AccountNumber}
</lightning:layoutItem>
```

```
  <lightning:layoutItem size="12" largeDeviceSize="4">{!v.account.Industry}
</lightning:layoutItem>
```

```
</lightning:layout>
```

☒ D. `<lightning:layout multipleRows="true">`

```
  <lightning:layoutItem size="12" mediumDeviceSize="6" largeDeviceSize="4">
{!v.account.Name}
  </lightning:layoutItem>
```

```
  <lightning:layoutItem size="12" mediumDeviceSize="6" largeDeviceSize="4">
{!v.account.AccountNumber}
  </lightning:layoutItem>
```

```
  <lightning:layoutItem size="12" mediumDeviceSize="6" largeDeviceSize="4">
{!v.account.Industry}
  </lightning:layoutItem>
</lightning:layout>
```

Question 22 of 62



Choose 1 option.

Consider the following code snippet:

```
<c-selected-order>
<template for:each={orders.data} for:item="order">
  <c-order orderId={order.Id}></c-order>
</template>
</c-selected-order>
```

How should the `<c-order>` component communicate to the `<c-selected-order>` component that an order has been selected by the user?

- ☒ A. Create and dispatch a custom event.
- ☐ B. Create and fire a component event.
- ☐ C. Create and fire an application event.
- ☐ D. Create and fire a standard DOM event.

Question 23 of 62



Choose 1 option.

A developer created a Lightning web component that uses a `lightning-record-edit-form` to collect information about Leads. Users complain that they only see one error message at a time about their input when trying to save a Lead record.

Which best practice should the developer use to perform the validations on more than one field, thus allowing more than one error message to be displayed simultaneously?

- ☐ A. Apex REST
- ☒ B. Client-side validation
- ☐ C. Next Best Action
- ☐ D. Custom validation rules

Question 24 of 62



Choose 2 options.

A Salesforce org has more than 50,000 contacts. A new business process requires a calculation that aggregates data from all of these contact records. This calculation needs to run once a day after business hours.

Which two steps should a developer take to accomplish this?

- ☒ A. Implement the `Schedulable` interface.
- ☒ B. Implement the `Queueable` interface.
- ☐ C. Use the `@future` annotation.
- ☐ D. Implement the `Database.Batchable` interface.



Choose 1 option.

Refer to the Aura component below:

Component markup:

```
<aura:component>
    <aura:attribute name="contactInfo" type="Object"/>
    <aura:attribute name="showContactInfo" type="boolean" default="true"/>
    <aura:handler name="init" value="{!this}" action="{!c.init}"/>

    <!-- ... other code ... -->
    <aura:if isTrue="{!v.showContactInfo}">
        <c:contactInfo value="{!v.contactInfo}"/>
    </aura:if>
</aura:component>
```

Controller JS:

```
((
    init: function(cmp, helper) {
        // ...other code ...
        var show = helper.getShowContactInfo();
        cmp.set("v.showContactInfo", show);
    },
    // other code...
})
```

A developer receives complaints that the component loads slowly.

Which change can the developer implement to make the component perform faster?

- ☐ A. Move the contents of `<c:contactInfo>` into the component.
- ☐ B. Change the type of `contactInfo` to "Map".
- ☒ C. Change the default for `showContactInfo` to "false".

Question 26 of 62

Choose 1 option.

Which technique can run custom logic when a Lightning web component is loaded?

- ☐ A. Use an `<aura:handler>` `init` event to call a function.
- ☒ B. Use the `connectedCallback()` method.
- ☐ C. Use the `renderedCallback()` method.
- ☐ D. Call `$A.enqueueAction` and pass in the method to call.

Question 27 of 62



Choose 1 option.

Which Salesforce feature allows a developer to see when a user last logged in to Salesforce if real-time notification is not required?

- ☐ A. Asynchronous Data Capture Events
- ☐ B. Calendar Events
- ☒ C. Event Monitoring Log
- ☐ D. Developer Log

Question 28 of 62



Choose 3 options.

Refer to the Lightning component below:

```
<lightning:button label="Save" onclick="{!c.handleSave}" />

({
  handleSave : function (component, event, helper) {
    helper.saveAndRedirect(component);
  }
})
```

The Lightning Component allows users to click a button to save their changes and then redirects them to a different page. Currently when the user hits the Save button, the records are getting saved, but they are not redirected.

Which three techniques can a developer use to debug the JavaScript?

- ☒ A. Use the browser's dev tools to debug the JavaScript.
- ☐ B. Use Developer Console to view the debug log.
- ☒ C. Use console.log() messages in the JavaScript.
- ☐ D. Use Developer Console to view checkpoints.
- ☒ E. Enable Debug Mode for Lightning components for the user.

Question 29 of 62



Choose 2 options.

A developer created a Lightning web component that allows users to input a text value that is used to search for Accounts by calling an Apex method. The Apex method returns a list of `AccountWrappers` and is called imperatively from a JavaScript event handler.

```
01:
02: public class AccountSearcher {
03:
04:     public static List<AccountWrapper> search(String term) {
05:         List<AccountWrapper> wrappers = getMatchingAccountWrappers(term);
06:         return wrappers;
07:     }
08:
09:
10:     public class AccountWrapper {
11:         public Account { get; set; }
12:         public Decimal matchProbability { get; set; }
13:     }
14:     // ...other methods, including getMatchingAccountWrappers implementation...
15: }
```

Which two changes should the developer make so the Apex method functions correctly?

- ☐ A. Add `@AuraEnabled` to line 01.
- ☒ B. Add `@AuraEnabled` to lines 11 and 12.
- ☒ C. Add `@AuraEnabled` to line 03.
- ☐ D. Add `@AuraEnabled` to line 09.



Choose 1 option.

A company wants to run different logic based on an Opportunity's record type.

Which code segment handles this request and follows best practices?

- ☐ A.

```
RecordType recType_New = [SELECT Id, Name FROM RecordType WHERE SObjectType =
'Opportunity' AND IsActive = True And DeveloperName = 'New' LIMIT 1];

RecordType recType_Renewal = [SELECT Id, Name FROM RecordType WHERE SObjectType =
'Opportunity' AND IsActive = True And DeveloperName = 'Renewal' LIMIT 1];

for(Opportunity o : Trigger.new) {
if(o.RecordTypeId == recType_New ) {
    // do some logic Record Type 1
}
else if (o.RecordTypeId == recType_Renewal ) {
    // do some logic for Record Type 2
}
}
```
- ☒ B.

```
List<RecordType> recTypes = [SELECT Id, Name FROM RecordType WHERE SObjectType =
'Opportunity' AND IsActive = True];

Map<String, Id> recTypeMap = new Map<String, Id>();
for(RecordType rt : recTypes) {
    recTypeMap.put(rt.Name, rt.Id);
}

for(Opportunity o : Trigger.new) {
    if(o.RecordTypeId == recTypeMap.get('New') ) {
        // do some logic Record Type 1
    }
    else if (o.RecordTypeId == recTypeMap.get('Renewal') ) {
        // do some logic for Record Type 2
    }
}
```


Question 31 of 62



Choose 2 options.

The Account object has a field, `Audit_Code__c`, that is used to specify what type of auditing the Account needs and a Lookup to User, `Auditor__c`, that is the assigned auditor.

When an Account is initially created, the user specifies the `Audit_Code__c`. Each User in the org has a unique text field, `Audit_Code__c`, that is used to automatically assign the correct user to the Account's `Auditor__c` field.

```
trigger AccountTrigger on Account(before insert) {  
    AuditAssigner.setAuditor(trigger.new);  
}  
  
public class AuditAssigner {  
    public static void setAuditor(List<Account> accounts) {  
        for (User u : [SELECT Id, Audit_Code__c FROM User]) {  
            for (Account a : accounts) {  
                if (u.Audit_Code__c == a.Audit_Code__c) {  
                    a.Auditor__c = u.Id;  
                }  
            }  
        }  
    }  
}
```

What should be changed to most optimize the code's efficiency?

- ☒ A. Add a `WHERE` clause to the SOQL query to filter on audit codes.
- ☐ B. Build a `Map<String, List<Account>>` of audit code to accounts.
- ☒ C. Build a `Map<Id, List<String>>` of Account Id to audit codes.
- ☐ D. Add an initial SOQL query to get all distinct audit codes.

A developer is working with existing functionality that tracks how many times a stage has changed for an Opportunity. When the Opportunity's stage is changed, a workflow rule is fired to increase the value of a field by one. The developer wrote an after trigger to create a child record when the field changes from 4 to 5.

A user changes the stage of an Opportunity and manually sets the count field to 4. The count field updates to 5, but the child record is not created.

What is the reason this is happening?

- ☐ A. After triggers fire before workflow rules.
- ☐ B. After triggers are not fired after field updates.
- ☐ C. Trigger.new does not change after a field update.
- ☒ D. Trigger.old does not contain the updated value of the count field.

Question 33 of 62



Choose 1 option.

A developer created and tested a Visualforce page in their developer sandbox, but now receives reports that user encounter view state errors when using it in production.

What should the developer ensure to correct these errors?

- ☐ A. Ensure profiles have access to the Visualforce page.
- ☐ B. Ensure properties are marked as `private`.
- ☒ C. Ensure variables are marked as `transient`.
- ☐ D. Ensure queries do not exceed governor limits.

Question 34 of 62



Choose 2 options.

Consider the below trigger intended to assign the Account to the manager of the Account's region:

```
trigger AssignOwnerByRegion on Account ( before insert, before update )
{
    List<Account> accountList = new List<Account>();
    for( Account anAccount : trigger.new )
    {
        Region__c theRegion = [
            SELECT Id, Name, Region_Manager__c
            FROM Region__c
            WHERE Name = :anAccount.Region_Name__c
        ];
        anAccount.OwnerId = theRegion.Region_Manager__c;

        accountList.add( anAccount );
    }

    update accountList;
}
```

Which two changes should a developer make in this trigger to adhere to best practices?

- ☒ A. Remove the last line that updates `accountList` because it is not needed.
- ☐ B. Add `if (!accountList.isEmpty())` before `update accountList`.
- ☐ C. Use a Map to cache the results of the `Region__c` query by Id.
- ☒ D. Move the `Region__c` query to outside the loop.

Question 35 of 62



Choose 1 option.

In an organization that has multi-currency enabled, a developer is tasked with building a Lightning component that displays the top ten Opportunities most recently accessed by the logged in user. The developer must ensure the Amount and LastModifiedDate field values are displayed according to the user's locale.

What is the most effective approach to ensure values displayed respect the user's locale settings?

- ☐ A. Use a wrapper class to format the values retrieved via SOQL.
- ☒ B. Use the `FORMAT ()` function in the SOQL query.
- ☐ C. Use the `FOR VIEW` clause in the SOQL query.
- ☐ D. Use `REGEX` expressions to format the values retrieved via SOQL.

Question 36 of 62



Choose 1 option.

Universal Containers develops a Visualforce page that requires the inclusion of external JavaScript and CSS files. They want to ensure efficient loading and caching of the page.

Which feature should be utilized to achieve this goal?

- ☒ A. Static resources
- ☐ B. RemoteAction
- ☐ C. PageBlockTable
- ☐ D. ActionFunction

Question 37 of 62



Choose 1 option.

Refer to the test method below:

```
Line 1: @isTest
Line 2: static void testMyTrigger()
Line 3: {
Line 4:     //Do a bunch of data setup
Line 5:     DataFactory.setupDataForMyTriggerTest();
Line 6:
Line 7:     List<Account> acctsBefore = [SELECT Is_Customer__c FROM Account WHERE Id IN
:DataFactory.accounts];
Line 8:
Line 9:     //Utility to assert all accounts are not customers before the update
Line 10:    AssertUtil.assertNotCustomers(acctsBefore);
Line 11:
Line 12:    //Set accounts to be customers
Line 13:    for(Account a : DataFactory.accounts)
Line 14:    {
Line 15:        a.Is_Customer__c = true;
Line 16:    }
Line 17:
Line 18:    update DataFactory.accounts;
Line 19:
Line 20:    List<Account> acctsAfter = [SELECT Number_Of_Transfers__c FROM Account WHERE Id IN
:DataFactory.accounts];
Line 21:
Line 22:    //Utility to assert Number_Of_Transfers__c is correct based on test data
Line 23:    AssertUtil.assertNumberOfTransfers(acctsAfter);
Line 24: }
```

The test method tests an Apex trigger that the developer knows will make a lot of queries when a lot of Accounts are simultaneously updated to be customers.

```
Line 18:      update DataFactory.accounts;  
Line 19:  
Line 20:      List<Account> acctsAfter = [SELECT Number_Of_Transfers__c FROM Account WHERE Id IN  
:DataFactory.accounts];  
Line 21:  
Line 22:      //Utility to assert Number_Of_Transfers__c is correct based on test data  
Line 23:      AssertUtil.assertNumberOfTransfers(acctsAfter);  
Line 24: }
```

The test method tests an Apex trigger that the developer knows will make a lot of queries when a lot of Accounts are simultaneously updated to be customers.

The test method fails at the Line 20 because of too many SOQL queries.

What is the correct way to fix this?

- ☐ A. Use `Limits.getLimitQueries()` to find the total number of queries that can be issued.
- ☐ B. Change the `DataFactory` class to create fewer Accounts so that the number of queries in the trigger is reduced.
- ☐ C. Add `Test.startTest()` before and add `Test.stopTest()` after both Line 7 and Line 20 of the code.
- ☒ D. Add `Test.startTest()` before and add `Test.stopTest()` after Line 18 of the code.

Question 38 of 62



Choose 1 option.

A company accepts orders for customers in their enterprise resource planning (ERP) system that must be integrated into Salesforce as `Order__c` records with a lookup field to Account. The Account object has an external ID field, `ERP_Customer_ID__c`.

What should the integration use to create new `Order__c` records that will automatically be related to the correct Account?

- ☒ A. Upsert on the `Order__c` object and specify the `ERP_Customer_ID__c` for the Account relationship.
- ☐ B. Upsert on the Account and specify the `ERP_Customer_ID__c` for the relationship.
- ☐ C. Merge on the `Order__c` object and specify the `ERP_Customer_ID__c` for the Account relationship.
- ☐ D. Insert on the `Order__c` object followed by an update on the `Order__c` object.

Question 39 of 62



Choose 1 option.

Universal Containers analyzes a Lightning web component and its Apex controller class that retrieves a list of contacts associated with an account. The code snippets are as follows:

Lightning web component (accountContacts.html):

```
<template>
  <lightning-card title=""Account Contacts"">
    <lightning-datatable data={contacts} columns={columns} key-field=""Id""></lightning-datatable>
  </lightning-card>
</template>
```

Apex controller class (AccountContactsController.cls):

```
public with sharing class AccountContactsController {
    @AuraEnabled
    public static List<Contact> getAccountContacts(String accountId) {
        return [SELECT Id, Name, Email, Phone FROM Contact WHERE AccountId = :accountId];
    }
}
```

Based on the code snippets, what change should be made to display the contacts' mailing addresses in the Lightning web component?

- ☐ A. Add a new method in the Apex controller class to retrieve the mailing addresses separately and modify the Lightning web component to invoke this method.
- ☐ B. Modify the SOQL query in the getAccountContacts method to include the MailingAddress field.
- ☐ C. Extend the lightning-datatable component in the Lightning web component to include a column for the MailingAddress field.
- ☒ D. Modify the SOQL query in the getAccountContacts method to include the MailingAddress field and update the columns attribute in javascript file to add Mailing address fields.

Question 40 of 62



Choose 1 option.

A developer created an Apex class that updates an Account based on input from a Lightning web component that is used to register an Account. The update to the Account should only be made if it has not already been registered.

```
account = [SELECT Id, Is_Registered__c FROM Account WHERE Id = :accountId];

if (!account.Is_Registered__c) {
    account.Is_Registered = true;
    // ...set other account fields...
    update account;
}
```

What should the developer do to ensure that users do not overwrite each other's updates to the same Account if they make updates at the same time?

- ☐ A. Add a try/catch block around the update.
- ☐ B. Use upsert instead of update.
- ☐ C. Use FOR UPDATE in the SOQL query.
- ☒ D. Include LastModifiedDate in the query to make sure it wasn't recently updated.



Choose 1 option.

A developer is asked to develop a new AppExchange application. A feature of the program creates Survey records when a Case reaches a certain stage and is of a certain Record Type. This feature needs to be configurable, as different Salesforce instances require Surveys at different times. Additionally, the out-of-the-box AppExchange app needs to come with a set of best practice settings that apply to most customers.

What should the developer use to store and package the custom configuration settings for the app?

- ☐ A. Custom settings
- ☐ B. Custom objects
- ☒ C. Custom metadata
- ☐ D. Custom labels

Question 42 of 62



Choose 1 option.

Universal Containers implements a private sharing model for the `Convention_Attendee__c` custom object. As part of a new quality assurance effort, the company created an `Event_Reviewer__c` user lookup field on the object. Management wants the event reviewer to automatically gain Read/Write access to every record they are assigned to.

What is the best approach to ensure the assigned reviewer obtains Read/Write access to the record?

- ☒ A. Create an after insert trigger on the Convention Attendee custom object, and use Apex Sharing Reasons and Apex Managed Sharing.
- ☐ B. Create a before insert trigger on the Convention Attendee custom object, and use Apex Sharing Reasons and Apex Managed Sharing.
- ☐ C. Create criteria-based sharing rules on the Convention Attendee custom object to share the records with the Event Reviewers.
- ☐ D. Create a criteria-based sharing rule on the Convention Attendee custom object to share the records with a group of Event Reviewers.

Question 43 of 62



Choose 1 option.

The head of recruiting at Universal Containers (UC) wants to provide all internal users the ability to search for open positions by role, department, and location via a new recruiting app. In addition to search, users of the app should be able to refer a friend, apply for a position, and review the status of their current submissions.

The app will be surfaced to UC's existing iOS and Android users via the standard mobile app that Salesforce provides. It has a custom user interface design and offline access is not required.

Given these requirements, what is the recommended approach to develop the app?

- ☐ A. Salesforce SDK
- ☒ B. Lightning Web Components
- ☐ C. Lightning Experience Builder
- ☐ D. Visualforce

Question 44 of 62



Choose 1 option.

A developer is inserting, updating, and deleting multiple lists of records in a single transaction and wants to ensure that any error prevents all execution.

How should the developer implement error exception handling in their code to handle this?

- ☐ A. Use `Database` methods to obtain lists of `Database.SaveResults`.
- ☒ B. Use `Database.setSavepoint()` and `Database.rollback()` with a try-catch statement.
- ☐ C. Use a try-catch statement and handle DML cleanup in the catch statement.
- ☐ D. Use a try-catch and use `sObject.addError()` on any failures.

Question 45 of 62



Choose 2 options.

A developer created an Opportunity trigger that updates the account rating when an associated opportunity is considered high value. Current criteria for an opportunity to be considered high value is an amount greater than or equal to \$1,000,000. However, this criteria value can change over time.

There is a new requirement to also display high value opportunities in a Lightning web component.

Which two actions should the developer take to meet these business requirements, and also prevent the business logic that obtains the high value opportunities from being repeated in more than one place?

- ☒ A. Create a helper class that fetches the high value opportunities.
- ☐ B. Leave the business logic code inside the trigger for efficiency.
- ☐ C. Call the trigger from the Lightning web component.
- ☒ D. Use custom metadata to hold the high value amount.

Question 46 of 62



Choose 1 option.

A company has an Apex process that makes multiple extensive database operations and web service callouts. The database processes and web services can take a long time to run and must be run sequentially.

How should the developer write this Apex code without running into governor limits and system limitations?

- ☒ A. Use Queueable Apex to chain the jobs to run sequentially.
- ☐ B. Use Limits class to stop entire process once governor limits are reached.
- ☐ C. Use multiple `@future` methods for each process and callout.
- ☐ D. Use Apex Scheduler to schedule each process.

Question 47 of 62



Choose 1 option.

A developer used custom settings to store some configuration data that changes occasionally. However, tests are now failing in some of the sandboxes that were recently refreshed.

What should be done to eliminate this issue going forward?

- ☒ A. Replace custom settings with custom metadata.
- ☐ B. Set the setting type on the custom setting to Hierarchy.
- ☐ C. Replace custom settings with static resources.
- ☐ D. Set the setting type on the custom setting to List.

Question 48 of 62



Choose 1 option.

A developer is asked to look into an issue where a scheduled Apex is running into DML limits. Upon investigation, the developer finds that the number of records processed by the scheduled Apex has recently increased to more than 10,000.

What should the developer do to eliminate the limit exception error?

- ☐ A. Use platform events.
- ☐ B. Implement the `Queueable` interface.
- ☒ C. Implement the `Batchable` interface.
- ☐ D. Use the `@future` annotation.

- ☐ B. `<lightning:layout multipleRows="false">`
 `<lightning:layoutItem size="12" largeDeviceSize="6">{!v.rec.Name}`
 `</lightning:layoutItem>`

 `<lightning:layoutItem size="12" largeDeviceSize="6">{!v.rec.Description__c}`
 `</lightning:layoutItem>`
`</lightning:layout>`
- ☒ C. `<lightning:layout multipleRows="true">`
 `<lightning:layoutItem smallDeviceSize="12" largeDeviceSize="6">{!v.rec.Name}`
 `</lightning:layoutItem>`

 `<lightning:layoutItem smallDeviceSize="12" largeDeviceSize="6">`
 `{!v.rec.Description__c}`
 `</lightning:layoutItem>`
`</lightning:layout>`
- ☐ D. `<lightning:layout multipleRows="false">`
 `<lightning:layoutItem smallDeviceSize="12" largeDeviceSize="6">{!v.rec.Name}`
 `</lightning:layoutItem>`

 `<lightning:layoutItem smallDeviceSize="12" largeDeviceSize="6">`
 `{!v.rec.Description__c}`
 `</lightning:layoutItem>`
`</lightning:layout>`

Question 49 of 62



Choose 1 option.

An Aura component has a section that displays some information about an Account and it works well on the desktop, but users have to scroll horizontally to see the description field output on their mobile devices and tablets.

```
<lightning:layout multipleRows="false">
  <lightning:layoutItem size="6">{!v.rec.Name}
</lightning:layoutItem>

  <lightning:layoutItem size="6">{!v.rec.Description__c}
</lightning:layoutItem>
</lightning:layout>
```

How should a developer change the component to be responsive for mobile and tablet devices?

- ☐ A.

```
<lightning:layout multipleRows="true">
  <lightning:layoutItem size="12" largeDeviceSize="6">{!v.rec.Name}
</lightning:layoutItem>

  <lightning:layoutItem size="12" largeDeviceSize="6">{!v.rec.Description__c}
</lightning:layoutItem>
</lightning:layout>
```
- ☐ B.

```
<lightning:layout multipleRows="false">
  <lightning:layoutItem size="12" largeDeviceSize="6">{!v.rec.Name}
</lightning:layoutItem>
```

Question 50 of 62



Choose 1 option.

A developer has a test class that creates test data before making a mock callout but now receives a 'You have uncommitted work pending. Please commit or rollback before calling out' error.

Which step should be taken to resolve the error?

- ☐ A. Ensure both the insertion and mock callout occur after the `Test.startTest()`.
- ☐ B. Ensure both the insertion and mock callout occur after the `Test.stopTest()`.
- ☒ C. Ensure the records are inserted before the `Test.startTest()` statement and the mock callout occurs after the `Test.startTest()`.
- ☐ D. Ensure the records are inserted before the `Test.startTest()` statement and the mock callout occurs within a method annotated with `@testSetup`.

Question 51 of 62



Choose 1 option.

How should a developer verify that a specific Account record is being tested in a test class for a Visualforce controller?

- ☐ A. Insert the Account into Salesforce, instantiate the page reference in the test class, then use `System.setParentRecordId().get()` to set the Account ID.
- ☒ B. Insert the Account in the test class, instantiate the page reference in the test class, then use `System.currentPageReference().getParameters().put()` to set the Account ID.
- ☐ C. Instantiate the page reference in the test class, insert the Account in the test class, then use `seeAllData=true` to view the Account.
- ☐ D. Instantiate the page reference in the test class, insert the Account in the test class, then use `System.setParentRecordId().get()` to set the Account ID.

Question 52 of 62

Choose 1 option.

Which method should be used to convert a `Date` to a `String` in the current user's locale?

- ☐ A. `Date.parse`
- ☐ B. `String.format`
- ☐ C. `String.valueOf`
- ☒ D. `Date.format`



Choose 1 option.

Universal Containers uses Salesforce to track orders in an `Order__c` object.

The `Order__c` object has private organization-wide defaults. The `Order__c` object has a custom field, `Quality_Controller__c`, that is a Lookup to User and is used to indicate that the specified User is performing quality control on the `Order__c`.

What should be used to automatically give read only access to the User set in the `Quality_Controller__c` field?

- ☐ A. Criteria-based sharing
- ☐ B. Record ownership
- ☐ C. User managed sharing
- ☒ D. Apex managed sharing

Question 54 of 62



Choose 2 options.

A business currently has a process to manually upload orders from its external Order Management System (OMS) into Salesforce.

This is a labor intensive process since accounts must be exported out of Salesforce to get the IDs. The upload file must be updated with the correct account IDs to relate the orders to the corresponding accounts.

Which two recommendations should make this process more efficient?

- ☐ A. Use the insert wizard in the Data Loader to import the data.
- ☐ B. Ensure the data in the file is sorted by the order ID.
- ☒ C. Use the upsert wizard in the Data Loader to import the data.
- ☒ D. Identify unique fields on Order and Account and set them as External IDs.

Question 55 of 62



Choose 1 option.

A developer is responsible for formulating the deployment process for a Salesforce project. The project follows a source-driven development approach, and the developer wants to ensure efficient deployment and version control of the metadata changes.

Which tool or mechanism should be utilized for managing the source-driven deployment process?

- ☐ A. Change Sets
- ☐ B. Unmanaged Packages
- ☒ C. Salesforce CLI with Salesforce DX
- ☐ D. Data Loader

Question 56 of 62



Choose 1 option.

Consider the following code snippet:

```
public class searchFeature{  
    public static List<List<sObject>> searchRecords(string searchquery){  
        return [FIND searchquery IN ALL FIELDS RETURNING Account, Opportunity, Lead];  
    }  
}
```

A developer created the following test class to provide the proper code coverage for the snippet above:

```
@isTest  
private class searchFeature_Test{  
  
    @TestSetup  
    private static void makeData(){  
        //insert opportunities, accounts and lead  
    }  
  
    @isTest  
    private static searchRecords_Test(){  
        List<List<sObject>> records = searchFeature.searchRecords('Test');  
        System.assertNotEquals(records.size(),0);  
    }  
}
```

However, when the test runs, no data is returned and the assertion fails.

Which edit should the developer make to ensure the test class runs successfully?

- ☒ A. Implement the `setFixedSearchResults` method in the test class.
- ☐ B. Implement the `seeAllData=true` attribute in the `@IsTest` annotation.



Choose 1 option.

There is an Apex controller and a Visualforce page in an org that displays records with a custom filter consisting of a combination of picklist values selected by the user.

The page takes too long to display results for some of the input combinations, while for other input choices it throws the exception, "Maximum view state size limit exceeded".

What step should the developer take to resolve this issue?

- ☐ A. Adjust any code that filters by picklist values since they are not indexed.
- ☐ B. Remove instances of the transient keyword from the Apex controller to avoid the view state error.
- ☐ C. Split the layout to filter records in one Visualforce page and display the list of records in a second page using the same Apex controller.
- ☒ D. Use a StandardSetController or SOQL LIMIT in the Apex controller to limit the number of records displayed at a time.

Question 58 of 62

Choose 1 option.

What is the best practice to initialize a Visualforce page in a test class?

- ☐ A. Use `controller.currentPage.setPage(MyTestPage);`
- ☐ B. Use `Test.setCurrentPage(MyTestPage);`
- ☒ C. Use `Test.setCurrentPage(Page.MyTestPage);`
- ☐ D. Use `Test.currentPage.getParameters.put(MyTestPage);`

Question 59 of 62



Choose 2 options.

Which two queries are selective SOQL queries and can be used for a large data set of 200,000 Account records?

- ☒ A. `SELECT Id FROM Account WHERE Id IN (List of Account Ids)`
- ☒ B. `SELECT Id FROM Account WHERE Name IN (List of Names) AND Customer_Number__c = 'ValueA'`
- ☐ C. `SELECT Id FROM Account WHERE Name != ''`
- ☐ D. `SELECT Id FROM Account WHERE Name LIKE '%Partner'`

Question 60 of 62



Choose 1 option.

Universal Containers wants to use a Customer Community with Customer Community Plus licenses to allow their customers access to track how many containers they have rented and when they are due back. Universal Containers uses a Private sharing model for External users.

Many of their customers are multi-national corporations with complex Account hierarchies. Each account on the hierarchy represents a department within the same business.

One of the requirements is to allow certain community users within the same Account hierarchy to see several departments' containers, based on a custom junction object that relates the Contact to the various Account records that represent the departments.

Which solution solves these requirements?

- ☐ A. A Lightning web component on the Community Home Page that uses Lightning Data Services.
- ☐ B. A custom list view on the junction object with filters that will show the proper records based on owner
- ☐ C. A Visualforce page that uses a custom controller that specifies `without sharing` to expose the records
- ☒ D. An Apex trigger that creates Apex managed sharing records based on the junction object's relationships

Question 61 of 62



Choose 1 option.

An org has a requirement that addresses on Contacts and Accounts should be normalized to a company standard by Apex code any time that they are saved.

What is the optimal way to implement this?

- ☐ A. Apex triggers on Contact and Account that normalize the address
- ☐ B. Apex trigger on Account that calls the Contact trigger to normalize the address
- ☐ C. Apex trigger on Contact that calls the Account trigger to normalize the address
- ☒ D. Apex triggers on Contact and Account that call a helper class to normalize the address

Question 62 of 62



Choose 1 option.

Refer to the test method below:

```
@isTest
static void testAccountUpdate() {
    Account acct = new Account(Name = 'Test');
    acct.Integration_Updated__c = false;
    insert acct;

    CalloutUtil.sendAccountUpdate(acct.Id);

    Account acctAfter = [SELECT Id, Integration_Updated__c FROM Account WHERE Id = :acct.Id][0];

    System.assert(true, acctAfter.Integration_Updated__c);
}
```

The test method calls a web service that updates an external system with Account information and sets the Account's Integration_Updated__c checkbox to True when it completes.

The test fails to execute and exits with an error: "Methods defined as TestMethod do not support Web service callouts."

What is the optimal way to fix this?

- ☐ A. Add `if (!Test.isRunningTest())` around `CalloutUtil.sendAccountUpdate`.
- ☐ B. Add `Test.startTest()` before and `Test.stopTest()` after `CalloutUtil.sendAccountUpdate`.
- ☐ C. Add `Test.startTest()` before and `Test.setMock` and `Test.stopTest()` after `CalloutUtil.sendAccountUpdate`.
- ☒ D. Add `Test.startTest()` and `Test.setMock` before and `Test.stopTest()` after `CalloutUtil.sendAccountUpdate`.

EXAM: Salesforce Certified Platform Developer II - Multiple Choice

GRADE: Pass

The report below shows the percentage of questions in each section that you answered correctly for the Salesforce Certified Platform Developer II - Multiple Choice exam. You will receive this information in your exam results email and can also access it via My Dashboard in Trailhead Academy.

SECTION NAME:	PERCENT CORRECT:
Advanced Developer Fundamentals	100%
Process Automation, Logic, and Integration	81%
User Interface	75%
Testing, Debugging, and Deployment	100%
Performance	82%