

Salesforce Certified Platform Developer II

1. **Choose 1 option.**

```
public class searchFeature{  
    public static List<List<object>> searchRecords(string searchquery){  
        return [FIND :searchquery IN ALL FIELDS RETURNING Account, Opportunity, Lead];  
    }  
}
```

```
// Test Class
```

```
@isTest
```

```
private class searchFeature_Test{
```

```
    @TestSetup
```

```
    private static void makeData(){
```

```
        //insert opportunities, accounts and lead
```

```
    }
```

```
    private static searchRecords_Test() {
```

```
        List<List<object>> records = searchFeature.searchRecords('Test');
```

```
        System.assertNotEquals(records.size(),0);
```

```
    }
```

```
}
```

```
...
```

However, when the test runs, no data is returned and the assertion fails.

Which edit should the developer make to ensure the test class runs successfully?

- A. Enclose the method call within Test.startTest() and Test.stopTest().
- B. Implement the seeAllData=true attribute in the @IsTest annotation.
- C. Implement the without sharing keyword in the searchFeature Apex class.

- D. Implement the `setFixedSearchResults` method in the test class.

2. ****Choose 2 options.****

A Lightning web component exists in the system and displays information about the record in context as a modal. Salesforce administrators need to use this component within the Lightning App Builder.

Which two settings should the developer configure within the xml resource file?

- A. Set the `isVisible` attribute to `true`.
- B. Set the `isExposed` attribute to `true`.
- C. Specify the `target` to be `lightning_RecordPage`.
- D. Specify the `target` to be `lightning_AppPage`.

3. ****Choose 1 option.****

A developer is asked to look into an issue where a scheduled Apex is running into DML limits. Upon investigation, the developer finds that the number of records processed by the scheduled Apex has recently increased to more than 10,000.

What should the developer do to eliminate the limit exception error?

- A. Implement the `Batchable` interface.
- B. Use platform events.
- C. Use the `@future` annotation.
- D. Implement the `Queueable` interface.

4. ****Choose 2 options.****

A Salesforce org has more than 50,000 contacts. A new business process requires a calculation that aggregates data from all of these contact records. This calculation needs to run once a day after business hours.

Which two steps should a developer take to accomplish this?

- A. Use the '@future' annotation.
- B. Implement the 'Database.Batchable' interface.
- C. Implement the 'Schedulable' interface.
- D. Implement the 'Queueable' interface.

5. **Choose 1 option.**

A developer is writing a Visualforce page that queries accounts in the system and presents a data table with the results. The users want to be able to filter the results based on up to five fields. However, the users want to pick the five fields to use as filter fields when they run the page.

Which Apex code feature is required to facilitate this solution?

- A. Dynamic SOQL

- B. Metadata API
- C. Streaming API
- D. Variable binding

6. **Choose 1 option.**

Consider the Apex controller below, that is called from an Aura component.

Line 1 public class AttributeTypes

Line 2 {

Line 3 private final String[] arrayItems;

Line 4

Line 5 @AuraEnabled

Line 6 public List<String> getStringArray() {

Line 7 String[] arrayItems = new String[]{ 'red', 'green', 'blue' };

Line 8 return arrayItems;

Line 9 }

Line 10 }

...

What is wrong with this code?

- A. Lines 1 and 6: class and method must be global
- B. Line 1: class must be global
- C. Line 6: method must be static
- D. Line 8: method must first serialize the list to JSON before returning

7. **Choose 1 option.**

The use of the transient keyword in Visualforce page controllers helps with which common performance issue?

- A. Reduces view state
- B. Improves query performance
- C. Reduces load times
- D. Improves page transfers

8. **Choose 1 option.**

A developer is trying to decide between creating a Visualforce component or a Lightning component for a custom screen.

Which functionality consideration impacts the final decision?

- A. Does the screen need to be accessible from the Lightning Experience UI?
- B. Will the screen be accessed via a mobile app?
- C. Will the screen make use of a JavaScript framework?
- D. Does the screen need to be rendered as a PDF without using a third-party application?

9. **Choose 1 option.**

There are user complaints about slow render times of a custom data table within a Visualforce page that loads thousands of Account records at once.

What can a developer do to help alleviate such issues?

- A. Use the transient keyword in the Apex code when querying the Account records.
- B. Upload a third-party data table library as a static resource.
- C. Use the standard Account List controller and implement pagination.
- D. Use JavaScript remoting to query the accounts.

10. **Choose 1 option.**

A developer needs to add code to a Lightning web component's configuration file so the component only renders for a desktop size form factor when on a record page.

What should the developer add to the component's record page target configuration to meet this requirement?

- A. `<supportedFormFactors>`
 `<supportedFormFactor type="Large"/>`
 `</supportedFormFactors>`
 ...
- B. `<lightningLayout formFactor="Large">`
 `</lightningLayout>`
 ...
- C. `<design>`
 `<designAttribute name="formFactor" value="Large"/>`
 `</design>`
 ...
- D. `<property name="formFactor" value="Large">`
 `</property>`
 ...

11. **Choose 1 option.**

A developer created the following test method:

```
@isTest(SeeAllData= true)
```

```

public static void testDeleteTrigger(){
    Account testAccount = new Account(name = 'Test1');
    insert testAccount;

    List<Account> testAccounts = [SELECT Id, Name from Account WHERE Name like 'Test%'];
    System.assert(testAccounts.size() > 0);

    delete testAccounts;
    testAccounts = [SELECT Id, Name from Account WHERE Name like 'Test%'];
    System.assert(testAccounts.size() == 0);
}
...

```

The developer org has five accounts where the name starts with "Test". The developer executes this test in the Developer Console.

After the test code runs, which statement is true?

- A. There will be five accounts where the name starts with "Test".
- B. There will be no accounts where the name starts with "Test".
- C. There will be six accounts where the name starts with "Test".
- D. The test will fail.

12. ****Choose 1 option.****

A company needs to automatically delete sensitive information after seven years. This could delete almost a million records every day.

How can this be achieved?

- A. Schedule an @future process to query records older than seven years, and then recursively invoke itself in 1,000 record batches to delete them.
- B. Use aggregate functions to query for records older than seven years, and then delete the AggregateResult objects.

- C. Perform a SOSL statement to find records older than 7 years, and then delete the entire result set.

- D. Schedule a batch Apex process to run every day that queries and deletes records older than seven years.

13. **Choose 1 option.**

A company manages information about their product offerings in custom objects named Catalog and Catalog Item. Catalog Item has a master-detail field to Catalog, and each Catalog may have as many as 100,000 Catalog Items.

Both custom objects have a CurrencyIsoCode text field that contains the currency code they should use. If a Catalog's CurrencyIsoCode changes, all of its Catalog Items' CurrencyIsoCodes should be changed as well.

What should a developer use to update the CurrencyIsoCodes on the Catalog Items when the Catalog's CurrencyIsoCode changes?

- A. An after update trigger on Catalog that updates the Catalog Items if the Catalog's CurrencyIsoCode is different.

- B. An after insert trigger on Catalog Item that updates the Catalog Items if the Catalog's CurrencyIsoCode is different.

- C. A Database.Schedulable and Database.Batchable class that queries the Catalog object and updates the Catalog Items if the Catalog CurrencyIsoCode is different.

- D. A Database.Schedulable and Database.Batchable class that queries the Catalog Item object and updates the Catalog Items if the Catalog CurrencyIsoCode is different.

14. **Choose 1 option.**

When developing a Lightning web component, which setting displays lightning-layout items in one column on small devices, such as mobile phones, and in two columns on tablet-size and desktop-size screens?

- A. Set size="12" tablet-device-size="6"

- B. Set size="6" small-device-size="12"

- C. Set size="12" medium-device-size="6"

- D. Set size="6" mobile-device-size="12"

15. ****Choose 2 options.****

A developer is tasked with creating a Lightning web component that is responsive on various devices.

Which two components should help accomplish this goal?

- A. Lightning-input-location
- B. Lightning-layout
- C. Lightning-navigation
- D. Lightning-layout-item

16. ****Choose 1 option.****

A developer needs to send Account records to an external system for backup purposes. The process must take a snapshot of Accounts as they are saved and then make a callout to a RESTful web service. The web service can only receive, at most, one record per call.

What should a developer do to implement these requirements?

- A. Implement platform events.
- B. Create a future method.
- C. Implement the Queueable interface.
- D. Expose an Apex class as a web service.

17. ****Choose 1 option.****

Universal Containers uses a custom Lightning page to provide a mechanism to perform a step-by-step wizard search for Accounts. One of the steps in the wizard is to allow the user to input text into a text field, ERP_Number__c, that is then used in a query to find matching Accounts.

```
erpNumber = erpNumber + '%';
```

```
List<Account> accounts = [SELECT Id, Name FROM Account WHERE ERP_Number__c LIKE  
:erpNumber]
```

```
...
```

A developer receives the exception 'SOQL query not selective enough'.

Which step should be taken to resolve the issue?

- A. Move the SOQL query to within an asynchronous process.
- B. Mark the ERP_Number__c field as required.
- C. Mark the ERP_Number__c field as an external ID.

18. **Choose 1 option.**

Universal Containers is leading a development team that follows the source-driven development approach in Salesforce. As part of their continuous integration and delivery (CI/CD) process, they need to automatically deploy changes to multiple environments, including sandbox and production.

Which mechanism or tool would best support their CI/CD pipeline in source-driven development?

- A. Salesforce CLI with Salesforce DX
- B. Change Sets
- C. Salesforce Extensions for Visual Studio Code
- D. Ant Migration Tool

19. **Choose 1 option.**

A developer is writing code that requires making callouts to an external web service.

Which scenario necessitates that the callout be made in an asynchronous method?

- A. The callout could take longer than 60 seconds to complete.
- B. The callouts will be made in an Apex trigger.
- C. Over 10 callouts will be made in a single transaction.
- D. The callouts will be made using the REST API.

20. **Choose 1 option.**

A developer is tasked with ensuring that email addresses entered into the system for Contacts and for a custom object called `Survey\_Response\_\_c` do not belong to a list of blocked domains.

The list of blocked domains is stored in a custom object for ease of maintenance by users. The `Survey\_Response\_\_c` object is populated via a custom Visualforce page.

What is the optimal way to implement this?

- A. Implement the logic in validation rules on the Contact and the `Survey\_Response\_\_c` objects.
- B. Implement the logic in a helper class that is called by an Apex trigger on Contact and from the custom Visualforce page controller.
- C. Implement the logic in an Apex trigger on Contact and also implement the logic within the custom Visualforce page controller.

21. **Choose 1 option.**

Universal Charities (UC) uses Salesforce to collect electronic donations in the form of credit card deductions from individuals and corporations.

When a customer service agent enters the credit card information, it must be sent to a 3rd-party payment processor for the donation to be processed. UC uses one payment processor for individuals and a different one for corporations.

What should a developer use to store the payment processor settings for the different payment processors, so that their system administrator can modify the settings once they are deployed, if needed?

- A. Hierarchy custom setting
- B. Custom label
- C. Custom metadata
- D. List custom setting

22. **Choose 1 option.**

@isTest

```
static void testUpdateSuccess() {
```

```
    Account acet = new Account(Name = 'test');
```

```

insert acet;

// Add code here

extension.inputValue = 'test';

PageReference pageRef = extension.update();

System.assertNotEquals(null, pageRef);
}
...

```

What should be added to the setup, in the location indicated, for the unit test above to create the controller extension for the test?

- A. ``AccountControllerExt extension = new AccountControllerExt(acet);``
- B. ``ApexPages.StandardController sc = new ApexPages.StandardController(acet);``
`AccountControllerExt extension = new AccountControllerExt(sc);``
- C. ``ApexPages.StandardController sc = new ApexPages.StandardController(acet.Id);``
`AccountControllerExt extension = new AccountControllerExt(sc);``
- D. ``AccountControllerExt extension = new AccountControllerExt(acet.Id);``

23. ****Choose 1 option.****

How should a developer assert that a trigger with an asynchronous process has successfully run?

- A. Create all test data, use `@future` in the test class, then perform assertions.
- B. Create all test data in the test class, use `System.runAs()` to invoke the trigger, then perform assertions.
- C. Create all test data in the test class, invoke `Test.startTest()` and `Test.stopTest()` and then perform assertions.
- D. Insert records into Salesforce, use `seeAllData=true`, then perform assertions.

24. ****Choose 1 option.****

A developer wrote a class named `AccountHistoryManager` that relies on field history tracking. The class has a static method called `getAccountHistory` that takes in an `Account` as a parameter and returns a list of associated `AccountHistory` object records.

The following test fails:

@isTest

```
public static void testAccountHistory(){  
    Account a = new Account(name = 'test');  
    insert a;  
    a.name = a.name + '1';  
    update a;  
    List<AccountHistory> ahList = AccountHistoryManager.getAccountHistory(a);  
    System.assert(ahList.size() > 0);  
}  
...
```

What should be done to make this test pass?

- A. Use @isTest(SeeAllData=true) to see historical data from the org and query for AccountHistory records.
- B. Use Test.isRunningTest() in getAccountHistory() to conditionally return fake AccountHistory records.
- C. The test method should be deleted since this code cannot be tested.
- D. Create AccountHistory records manually in the test setup and write a query to get them.

25. **Choose 2 options.**

Consider the following code snippet:

```
trigger OpportunityTrigger on Opportunity (before insert, before update) {  
    for(Opportunity opp : Trigger.new){  
        OpportunityHandler.setPricingStructure(opp);  
    }  
}
```

```
public class OpportunityHandler{
```

```
    public static void setPricingStructure(Opportunity thisOpp){  
        Pricing_Structure_c ps = [Select Type_c FROM Pricing_Structure_c WHERE industry_c =  
:thisOpp.Account_Industry_c];
```

```

        thisOpp.Pricing_Structure_c = ps.Type_c;
        update thisOpp;
    }
}
...

```

Which two best practices should the developer implement to optimize this code?

- A. Remove the DML statement.
- B. Change the trigger context to after update, after insert.
- C. Query the Pricing_Structure_c records outside of the loop.
- D. Use a collection for the DML statement.

26. **Choose 1 option.**

Universal Containers needs to integrate with their own, existing, internal custom web application. The web application accepts JSON payloads, resizes product images, and sends the resized images back to Salesforce.

What should the developer use to implement this integration?

- A. An Apex trigger that calls an @future method that allows callouts
- B. A flow that calls an @future method that allows callouts
- C. A flow with an outbound message that contains a session ID
- D. A platform event that makes a callout to the web application

27. **Choose 1 option.**

Refer to the markup below:

```

<<html
<template>
<!-- ... other code ... -->
<lightning-record-form

```

```
record-id={recordId}
object-api-name="Account"
layout-type="Full">
</lightning-record-form>
</template>
```
```

A Lightning web component displays the Account name and two custom fields out of 275 that exist on the object. The custom fields are correctly declared and populated. However, the developer receives complaints that the component performs slowly.

What can the developer do to improve the performance?

- A. Replace `layout-type="Full"` with `fields={fields}`.
- B. Add `density="compact"` to the component.
- C. Replace `layout-type="Full"` with `layout-type="Partial"`.
- D. Add `cache="true"` to the component.

28. \*\*Choose 1 option.\*\*

Universal Containers uses Salesforce to track orders in an `Order__c` object.

The `Order__c` object has private organization-wide defaults. The `Order__c` object has a custom field, `Quality_Controller__c`, that is a Lookup to User and is used to indicate that the specified User is performing quality control on the `Order__c`.

What should be used to automatically give read only access to the User set in the `Quality_Controller__c` field?

- A. User managed sharing
- B. Record ownership
- C. Apex managed sharing
- D. Criteria-based sharing

29. \*\*Choose 1 option.\*\*

Given the following containment hierarchy:

```
```html
<!-- myParentComponent.html -->

<template>

  <c-my-child-components></c-my-child-components>

</template>
```
```

What is the correct way to communicate the new value of a property named "passthrough" to my-parent-component if the property is defined within my-child-component?

- A. ``let cEvent = new CustomEvent('passthrough', { detail: 'this.passthrough' }); this.dispatchEvent(cEvent);``
- B. ``let cEvent = new CustomEvent('passthrough'); this.dispatchEvent(cEvent);``
- C. ``let cEvent = new CustomEvent('passthrough', { detail: this.passthrough }); this.dispatchEvent(cEvent);``
- D. ``let cEvent = new CustomEvent($passthrough); this.dispatchEvent(cEvent);``

30. **\*\*Choose 1 option.\*\***

A developer is debugging an Apex-based order creation process that has a requirement to have three savepoints, SP1, SP2, and SP3 (created in order), before the final execution of the process.

During the final execution process, the developer has a routine to roll back to SP1 for a given condition. Once the condition is fixed, the code then calls a roll back to SP3 to continue with final execution. However, when the roll back to SP3 is called, a runtime error occurs.

Why does the developer receive a runtime error?

- A. The developer has too many DML statements between the savepoints.
- B. SP3 became invalid when SP1 was rolled back.
- C. The developer should have called SP2 before calling SP3.
- D. The developer used too many savepoints in one trigger session.

31. \*\*Choose 1 option.\*\*

A developer is writing a Lightning Web component that queries accounts in the system and presents a lightning-datatable with the results. The users want to be able to filter the results based on up to five fields, that will vary according to their selections when running the page.

Which feature of Apex code is required to facilitate this solution?

- A. `describeSObjects()`
- B. REST API
- C. SOSL queries
- D. Dynamic SOQL

32. \*\*Choose 1 option.\*\*

A business requires that every parent record must have a child record. A developer writes an Apex method with two DML statements to insert a parent record and a child record.

A validation rule blocks child records from being created. The method uses a try/catch block to handle the DML exception.

What should the developer do to ensure the parent always has a child record?

- A. Use `Database.insert()` and set the `allOrNone` parameter to true.
- B. Delete the parent record in the catch statement when an error occurs on the child record DML operation.
- C. Set a database savepoint to rollback if there are errors.
- D. Use `addError()` on the parent record if an error occurs on the child record.

33. \*\*Choose 3 options.\*\*

What are three reasons that a developer should write Jest tests for Lightning web components?



- A. To test basic user interaction
- B. To test a component's non-public properties
- C. To test how multiple components work together
- D. To verify the DOM output of a component
- E. To verify that events fire when expected

34. \*\*Choose 1 option.\*\*

Salesforce users consistently receive a "Maximum trigger depth exceeded" error when saving an Account.

How can a developer fix this error?

- A. Split the trigger logic into two separate triggers.
- B. Modify the trigger to use the `isMultiThread=true` annotation.
- C. Convert the trigger to use the `@future` annotation, and chain any subsequent trigger invocations to the Account object.
- D. Use a helper class to set a Boolean to TRUE the first time a trigger is fired, and then modify the trigger to only fire when the Boolean is FALSE.

35. \*\*Choose 1 option.\*\*

A software company uses a custom object, `Defect\_\_c`, to track defects in their software. `Defect\_\_c` has organization-wide defaults set to private. Each `Defect\_\_c` has a related list of `Reviewer\_\_c` records, each with a lookup field to User that is used to indicate that the User will review the `Defect\_\_c`.

What should be used to give the User on the `Reviewer\_\_c` record read only access to the `Defect\_\_c` record on the `Reviewer\_\_c` record?

- A. View All on `Defect\_\_c`
- B. Criteria-based sharing

- C. Lightning web component
- D. Apex managed sharing

36. \*\*Choose 2 options.\*\*

A developer is tasked with creating a Lightning web component that allows users to create a Case for a selected product, directly from a custom Lightning page. The input fields in the component are displayed in a non-linear fashion on top of an image of the product to help the user better understand the meaning of the fields.

Which two components should a developer use to implement the creation of the Case from the Lightning web component?

- A. lightning-record-form
- B. lightning-record-edit-form
- C. lightning-input-field
- D. lightning-input

37. \*\*Choose 2 options.\*\*

A large company uses Salesforce across several departments. Each department has its own Salesforce Administrator. It was agreed that each Administrator would have their own sandbox in which to test changes.

Recently, users notice that fields that were recently added for one department suddenly disappear without warning.

Which two statements are true regarding these issues and resolution?

- A. The administrators are deploying their own Change Sets, thus deleting each other's fields from the objects in production.
- B. The administrators are deploying their own Change Sets over each other, thus replacing entire Page Layouts in production.
- C. Page Layouts should never be deployed via Change Sets, as this causes Field-Level Security to be reset and fields to disappear.

- D. A sandbox should be created to use as a unified testing environment instead of deploying Change Sets directly to production.

38. \*\*Choose 1 option.\*\*

A company has a Lightning page with many Lightning Components, some that cache reference data. It is reported that the page does not always show the most current reference data.

What can a developer use to analyze and diagnose the problem in the Lightning page?

- A. Salesforce Lightning Inspector Storage tab

- B. Salesforce Lightning Inspector Event Log tab

- C. Salesforce Lightning Inspector Actions tab

- D. Salesforce Lightning Inspector Transactions tab

---

39. \*\*Choose 1 option.\*\*

Consider the following code snippet:

```
```html
<apex:page docType="html-5.0" controller="FindOpportunities">
  <apex:form >
    <apex:pageBlock >
      <apex:pageBlockSection title="find opportunity">
        <apex:input label="opportunity name"/>
        <apex:commandButton value="search" action="{!search}"/>
      </apex:pageBlockSection>
      <apex:pageBlockSection title="Opportunity List" id="opportunityList">
        <!-- DATA Table -->
      </apex:pageBlockSection>
    </apex:pageBlock>
  </apex:form>
```

</apex:page>

...

Users of this Visualforce page complain that the page does a full refresh every time the Search button is pressed.

What should the developer do to ensure that a partial refresh is made so that only the section identified with `opportunityList` is re-drawn on the screen?

- A. Enclose the DATA table within the `<apex:actionRegion>` tag.
- B. Implement the `<apex:actionFunction>` tag with `immediate = true`.
- C. Ensure the action method search returns null.
- D. Implement the `reRender` attribute on the `<apex:commandButton>` tag.

40. **Choose 1 option.**

Given a list of Opportunity records named `opportunityList`, which code snippet is best for querying all Contacts of the Opportunity's Account?

- A.

```
List <Contact> contactList = new List <Contact>();
```

```
Set <Id> accountIds = new Set <Id>();
```

```
for(Opportunity o : opportunityList){
```

```
    accountIds.add(o.AccountId);
```

```
}
```

```
for(Account a : [SELECT Id, (SELECT Id FROM Contacts) FROM Account WHERE Id IN :accountIds]){
```

```
    contactList.addAll(a.Contacts);
```

```
}
```

```
...
```

- B.

```
List <Contact> contactList = new List <Contact>();
```

```
for ( Contact c : [SELECT Id FROM Contact WHERE AccountId IN :opportunityList.AccountId ]){  
    contactList.add(c);  
}  
...
```

41. **Choose 1 option.**

The Account after-update trigger fires whenever an Account's address is updated, and it updates every associated Contact with that address. The Contact after-update trigger fires on every edit, and it updates every Campaign Member record related to the Contact with the Contact's state.

Consider the following: A mass update of 200 Account records' addresses, where each Account has 50 Contacts. Each Contact has one Campaign Member. This means there are 10,000 Contact records across the Accounts and 10,000 Campaign Member records across the contacts.

What will happen when the mass update occurs?

- A. The mass update of Account address will succeed, but the Contact address updates will fail due to exceeding number of records processed by DML statements.
- B. There will be no error, since each trigger fires within its own context and each trigger does not exceed the limit of the number of records processed by DML statements.
- C. The mass update will fail, since the two triggers fire in the same context, thus exceeding the number of records.

42. **Choose 1 option.**

Which statement is considered a best practice for writing bulk safe Apex triggers?

- A. Add LIMIT 50000 to every SOQL statement.
- B. Add records to collections and perform DML operations against these collections.
- C. Use the Database methods with allOrNone set to false instead of DML statements.
- D. Perform all DML operations from within a future method.

43. **Choose 1 option.**

Universal Containers (UC) has enabled the translation workbench and has translated picklist values. UC has a custom multi-select picklist field, Products__c, on the Account object that allows sales reps to specify which of UC's products an Account already has. A developer is tasked with writing an Apex method that retrieves Account records, including the Products__c field.

What should the developer do to ensure the value of Products__c is in the current user's language?

- A. Use `toLabel(Products__c)` in the fields list of the SOQL query.

- B. Call the `translate()` method on each record in the SOQL result list.

- C. Set the locale on each record in the SOQL result list.

- D. Use the locale clause in the SOQL query.

44. **Choose 1 option.**

Universal Containers decided to use Salesforce to manage a new hire interview process. A custom object called Candidate was created with organization-wide defaults set to Private. A lookup on the Candidate object sets an employee as an Interviewer.

What should be used to automatically give Read access to the record when the lookup field is set to the Interviewer user?

- A. The record can be shared using an Apex class.

- B. The record can be shared using a permission set.

- C. The record can be shared using a sharing rule.

- D. The record cannot be shared with the current setup.

45. **Choose 2 options.**

A developer created a Lightning web component for the Account record page that displays the five most recently contacted Contacts for an Account. The Apex method, `getRecentContacts`, returns a list of Contacts and will be wired to a property in the component.

01:

02: public class ContactFetcher {

03:

```

04: static List<Contact> getRecentContacts(Id accountId) {
05:     List<Contact> contacts = getFiveMostRecent(accountId);
06:     return contacts;
07: }
08: private static List<Contact> getFiveMostRecent(Id accountId) {
10:     //...implementation...
11: }
12: }
...

```

Which two lines must change in the above code to make the Apex method able to be wired?

- A. Add `public` to line 04.
- B. Add `@AuraEnabled(cacheable=true)` to line 08.
- C. Remove `private` from line 09.
- D. Add `@AuraEnabled(cacheable=true)` to line 03.

46. **Choose 1 option.**

A developer created a JavaScript library that simplifies the development of repetitive tasks and features and uploaded the library as a static resource called jsUtils in Salesforce. Another developer is coding a new Lightning web component (LWC) and wants to leverage the library.

Which statement properly loads the static resource within the LWC?

- A. `import jsUtilities from '@salesforce/resourceUrl/jsUtils';`
- B. `import {jsUtilities} from '@salesforce/resourceUrl/jsUtils';`
- C. `const jsUtility = \$A.get('\$Resource.jsUtils');`
- D. `

47. **Choose 1 option.**

A developer needs to implement a system audit feature that allows users, assigned to a custom profile named "Auditors", to perform searches against the historical records in the Account object.

The developer must ensure the search is able to return history records that are between 6 and 12 months old.

Given the code below, which select statement should be inserted below as a valid way to retrieve the Account History records ranging from 6 to 12 months old?

```
Date initialDate = System.Today().addMonths(-12);
```

```
Date endDate = System.Today().addMonths(-6);
```

```
// Insert SELECT statement here
```

```
...
```

- A. `[SELECT AccountId, CreatedDate, Field, NewValue, OldValue FROM Account\_History WHERE CreatedDate <= :initialDate AND CreatedDate <= :endDate];`

- B. `[SELECT AccountId, CreatedDate, Field, NewValue, OldValue FROM Account\_History WHERE CreatedDate >= :endDate AND CreatedDate <= :initialDate];`

- C. `[SELECT AccountId, CreatedDate, Field, NewValue, OldValue FROM AccountHistory WHERE CreatedDate BETWEEN :initialDate AND :endDate];`

- D. `[SELECT AccountId, CreatedDate, Field, NewValue, OldValue FROM AccountHistory WHERE CreatedDate => :initialDate AND CreatedDate <= :endDate];`

48. **Choose 1 option.**

Universal Containers wants to notify an external system, in the event that an unhandled exception occurs, by publishing a custom event using Apex.

What is the appropriate publish/subscribe logic to meet this requirement?

- A. Publish the error event using the `EventBus.publish()` method and have the external system subscribe to the event using CometD.

- B. Publish the error event using the `addError()` method and have the external system subscribe to the event using CometD.

- C. Publish the error event using the `addError()` method and write a trigger to subscribe to the event and notify the external system.

- D. Have the external system subscribe to the event channel. No publishing is necessary.

49. ****Choose 1 option.****

A developer notices the execution of all the test methods in a class takes a long time to run, due to the initial setup of all the test data that is needed to perform the tests.

What should the developer do to speed up test execution?

- A. Define a method that creates test data and annotate with `@createData``.
- B. Reduce the amount of test methods in the class.
- C. Define a method that creates test data and annotate with `@testSetup``.
- D. Ensure proper usage of test data factory in all test methods.

50. ****Choose 1 option.****

A developer is asked to find a way to store secret data with an ability to specify which profiles and users can access which secrets.

What should be used to store this data?

- A. Static resources
- B. Custom metadata
- C. Custom settings
- D. System.Cookie class

51. ****Choose 1 option.****

A developer wrote the following method to find all the test accounts in the org:

```
public static Account[] searchTestAccounts() {  
    List<List<SObject>> searchList = [FIND 'test' IN ALL FIELDS RETURNING Account(Name)];  
    return (Account[]) searchList[0];  
}  
...
```

However, the test method below fails.

@isTest

```
public static void testSearchTestAccounts() {  
    Account a = new Account(name='test');  
    insert a;  
    Account [] accounts = TestAccountFinder.searchTestAccounts();  
    System.assert(accounts.size() == 1);  
}  
...
```

What should be used to fix this failing test?

- A. '@isTest(SeeAllData=true)' to access org data for the test
- B. 'Test.loadData' to set up expected data
- C. 'Test.setFixedSearchResults()' method to set up expected data
- D. '@testSetup' method to set up expected data

52. **Choose 2 options.**

A company has reference data stored in multiple custom metadata records that represent default information and delete behavior for certain geographic regions.

When a contact is inserted, the default information should be set on the contact from the custom metadata records based on the contact's address information. Additionally, if a user attempts to delete a contact that belongs to a flagged region, the user must get an error message.

Depending on company personnel resources, what are two ways to automate this?

- A. Remote action
- B. Flow Builder
- C. Apex invocable method

- D. Apex trigger

53. **Choose 2 options.**

As part of a custom interface, a developer team creates various new Lightning web components. Each of the components handles errors using toast messages. When the development is complete, all the components are added to the same Lightning page.

During acceptance testing, users complain about the long chain of toast messages that display when errors occur loading the components.

Which two techniques should the developer implement to improve the user experience?

- A. Use a Lightning web component to aggregate and display all errors.
- B. Use the window.alert() method to display the error messages.
- C. Use a `` tag to display in-place error messages.
- D. Use public properties on each component to display the error messages.

54. **Choose 1 option.**

An Apex trigger creates a Contract record every time an Opportunity record is marked as Closed and Won. This trigger is working great, except (due to a recent acquisition) historical Opportunity records need to be loaded into the Salesforce instance.

When a test batch of records are loaded, the Apex trigger creates Contract records. A developer is tasked with preventing Contract records from being created when mass loading the Opportunities, but the daily users still need to have the Contract records created.

What is the most extendable way to update the Apex trigger to accomplish this?

- A. Add the Profile ID of the user who loads the data to the trigger, so the trigger will not fire for this user.
- B. Add a validation rule to the Contract to prevent Contract creation by the user who loads the data.
- C. Use a list custom setting to disable the trigger for the user who loads the data.

- D. Use a hierarchy custom setting to skip executing the logic inside the trigger for the user who loads the data.

55. **Choose 1 option.**

An org has a requirement that an Account must always have one and only one Contact listed as Primary. So selecting one Contact will de-select any others. The client wants a checkbox on the Contact called 'Is Primary' to control this feature. The client also wants to ensure that the last name of every Contact is stored entirely in uppercase characters.

What is the optimal way to implement these requirements?

- A. Write a Validation Rule on the Contact for the Is Primary logic and a before update trigger on Contact for the last name logic.
- B. Write an after update trigger on Contact for the Is Primary logic and a separate before update trigger on Contact for the last name logic.
- C. Write an after update trigger on Account for the Is Primary logic and a before update trigger on Contact for the last name logic.
- D. Write a single trigger on Contact for both after update and before update and callout to helper classes to handle each set of logic.

56. **Choose 1 option.**

In an organization that has multi-currency enabled, a developer is tasked with building a Lightning component that displays the top ten Opportunities most recently accessed by the logged in user. The developer must ensure the Amount and LastModifiedDate field values are displayed according to the user's locale.

What is the most effective approach to ensure values displayed respect the user's locale settings?

- A. Use the FORMAT () function in the SOQL query.
- B. Use a wrapper class to format the values retrieved via SOQL.
- C. Use REGEX expressions to format the values retrieved via SOQL.
- D. Use the FOR VIEW clause in the SOQL query.

57. ****Choose 1 option.****

An org records customer order information in a custom object, Order__c, that has fields for the shipping address. A developer is tasked with adding code to calculate shipping charges on an order, based on a flat percentage rate associated with the region of the shipping address.

What should the developer use to store the rates by region, so that when the changes are deployed to production no additional steps are needed for the calculation to work?

- A. Custom metadata type

- B. Custom list setting

- C. Custom object

- D. Custom hierarchy setting

58. ****Choose 2 options.****

As part of point-to-point integration, a developer must call an external web service which, due to high demand, takes a long time to provide a response. As part of the request, the developer must collect key inputs from the end user before making the callout.

Which two elements should the developer use to implement these business requirements?

- A. Batch Apex

- B. Lightning web component

- C. Screen Flow

- D. Apex method that returns a Continuation object

59. An Apex trigger and Apex class increment a counter, Edit_Count__c, any time the Case is changed.

```
public class CaseTriggerHandler {  
    public static void handle(List<Case> cases) {  
        for (Case c : cases) {  
            c.Edit_Count__c = c.Edit_Count__c + 1;  
        }  
    }  
}
```

```
    }  
  }  
}
```

```
trigger on Case(before update) {  
    CaseTriggerHandler.handle(Trieger.new);  
}  
...
```

A new before-save record-triggered flow on the Case object was just created in production for when a Case is created or updated. Since the process was added, there are reports that Edit_Count__c is being incremented more than once for Case edits.

Which Apex code fixes this problem?

- A.

```
public class CaseTriggerHandler {  
    public static Boolean firstRun = true;  
    public static void handle(List<Case> cases) {  
        for (Case c : cases) {  
            c.Edit_Count__c = c.Edit_Count__c + 1;  
        }  
    }  
}
```

```
trigger on Case(before update) {  
    CaseTriggerHandler.firstRun = true;  
    if (CaseTriggerHandler.firstRun) {  
        CaseTriggerHandler.handle(Trieger.newMap);  
    }  
    CaseTriggerHandler.firstRun = false;  
}  
...
```

- B.

```
public class CaseTriggerHandler {  
    public static Boolean firstRun = true;  
    public static void handle(List<Case> cases) {  
        for (Case c : cases) {  
            c.Edit_Count__c = c.Edit_Count__c + 1;  
        }  
    }  
}
```

```
trigger on Case(before update) {  
    if (CaseTriggerHandler.firstRun) {  
        CaseTriggerHandler.handle(Trigger.new);  
    }  
    CaseTriggerHandler.firstRun = false;  
}  
...
```

- C.

```
public class CaseTriggerHandler {  
    Boolean firstRun = true;  
    public static void handle(List<Case> cases) {  
        if (firstRun) {  
            for (Case c : cases) {  
                c.Edit_Count__c = c.Edit_Count__c + 1;  
            }  
        }  
        firstRun = false;  
    }  
}
```

```
trigger on Case(before update) {  
    CaseTriggerHandler.handle(Trigger.new);  
}  
...
```

- D.

```
trigger on Case(before update) {  
    Boolean firstRun = true;  
    if (firstRun) {  
        CaseTriggerHandler.handle(Trigger.newMap);  
    }  
    firstRun = false;  
} ...
```

60. **Choose 1 option.**

A developer has a test class that creates test data before making a mock callout but now receives a "You have uncommitted work pending. Please commit or rollback before calling out" error.

Which step should be taken to resolve the error?

- A. Ensure both the insertion and mock callout occur after the Test.stopTest().
- B. Ensure the records are inserted before the Test.startTest() statement and the mock callout occurs within a method annotated with @testSetup.
- C. Ensure the records are inserted before the Test.startTest() statement and the mock callout occurs after the Test.startTest().
- D. Ensure both the insertion and mock callout occur after the Test.startTest().

61. **Choose 1 option.**

A company has a native iOS order placement app that needs to connect to Salesforce to retrieve consolidated information from many different objects in a JSON format.

Which is the optimal method to implement this in Salesforce?

- A. Apex SOAP web service
- B. Apex SOAP callout
- C. Apex REST callout
- D. Apex REST web service

62. **Choose 1 option.**

****MyOpportunities.js****

```
````javascript
```

```
import { LightningElement, api, wire } from 'lwc';
```

```
import getOpportunities from '@salesforce/apex/OpportunityController.findMyOpportunities';
```

```
export default class MyOpportunities extends LightningElement {
```

```
 @api userId;
```

```
 @wire(getOpportunities, {oppOwner: '$userId'})
```

```
 opportunities;
```

```
}
```

```
````
```

****OpportunityController.cls****

```
public with sharing class OpportunityController {
```

```
    @AuraEnabled
```

```
    public static List<Opportunity> findMyOpportunities(Id oppOwner) {
```

```
        return [
```

```
            SELECT Id, Name, StageName, Amount
```

```
            FROM Opportunity
```

```
            WHERE OwnerId = :oppOwner
```

```
];  
}  
}
```

A developer is experiencing issues with a Lightning web component. The component must surface information about Opportunities owned by the currently logged-in user.

When the component is rendered, the following message is displayed: "Error retrieving data".

Which three actions must be completed in a Lightning web component for a JavaScript file in a static

- A. Use the `Continuation=true` attribute in the Apex method.
- B. Edit the code to use the `without` sharing keyword in the Apex class.
- C. Use the `Cacheable=true` attribute in the Apex method.
- D. Ensure the OWD for the Opportunity object is Public.

63. Choose 1 option.

Which statement is true regarding savepoints?

- A. You can roll back to any savepoint variable created in any order.
- B. Static variables are not reverted during a rollback.
- C. Savepoints are not limited by DML statement governor limits.
- D. Reference to savepoints can cross trigger invocations.

64. Choose 1 option.

A developer wrote an Apex class to make several callouts to an external system.

If the URLs used in these callouts will change often, which feature should the developer use to minimize changes needed to the Apex class?

- A. Named Credentials
- B. Connected Apps
- C. Remote Site Settings
- D. Session Id

65. Choose 1 option.

Given the following code:

```
for ( Contact c : [SELECT Id, LastName FROM Contact WHERE CreatedDate = TODAY] )
{
    Account a = [SELECT Id, Name FROM Account WHERE CreatedDate = TODAY LIMIT 5];
    c.AccountId = a.Id;
    update c;
}
...
```

Assuming there were 10 Contacts and five Accounts created today, what is the expected result?

- A. System.QueryException: List has more than one row for Assignment on Account
- B. System.LimitException: Too many SOQL Queries on Contact
- C. System.LimitException: Too many SOQL Queries on Account
- D. System.QueryException: Too many DML Statement errors on Contact

66. Choose 1 option.

A developer has a Visualforce page that automatically assigns ownership of an Account to a queue upon save. The page appears to correctly assign ownership, but an assertion validating the correct ownership fails.

What can cause this problem?

- A. The test class does not implement the Queueable interface.
- B. The test class does not retrieve the updated value from the database.
- C. The test class does not use the seeAllData=true annotation.
- D. The test class does not use the Bulk API for loading test data.

67. Choose 1 option.

A developer is asked to build a solution that will automatically send an email to the customer when an Opportunity stage changes. The solution must scale to allow for 10,000 emails per day. The criteria to send the email should be evaluated after certain conditions are met.

What is the optimal way to accomplish this?

- A. Use an Apex trigger with Batch Apex.

B. Use an Email Alert with Flow Builder.

C. Use MassEmailMessage() with an Apex trigger.

D. Use SingleEmailMessage() with an Apex trigger.

68. Choose 3 options.

Which three actions must be completed in a Lightning web component for a JavaScript file in a static resource to be loaded?

A. Call loadScript.

B. Import the static resource.

C. Import a method from the platformResourceLoader.

D. Reference the static resource in a <script> tag.

E. Append the static resource to the DOM.

69. Choose 1 option.

Universal Containers wants to use a Customer Community with Customer Community Plus licenses to allow their customers access to track how many containers they have rented and when they are due back. Universal Containers uses a Private sharing model for External users.

Many of their customers are multi-national corporations with complex Account hierarchies. Each account on the hierarchy represents a department within the same business.

One of the requirements is to allow certain community users within the same Account hierarchy to see several departments' containers, based on a custom junction object that relates the Contact to the various Account records that represent the departments.

Which solution solves these requirements?

A. An Apex trigger that creates Apex managed sharing records based on the junction object's relationships

B. A custom list view on the junction object with filters that will show the proper records based on owner

C. A Visualforce page that uses a custom controller that specifies without sharing to expose the records

D. A Lightning web component on the Community Home Page that uses Lightning Data Services.

70. Choose 1 option.

Part of a custom Lightning component displays the total number of Opportunities in the org, which are in the millions. The Lightning component uses an Apex method to get the data it needs.

What is the optimal way for a developer to get the total number of Opportunities for the Lightning component?

- A. COUNT () SOQL aggregate query on the Opportunity object
- B. Apex batch job that counts the number of Opportunity records
- C. SUM () SOQL aggregate query on the Opportunity object
- D. SOQL for loop that counts the number of Opportunities records

71.. Choose 1 option.

Which tag should a developer use to display different text while an <apex:commandButton> is processing an action?

- A. <apex:actionStatus>
- B. <apex:actionPoller>
- C. <apex:pageMessages>
- D. <apex:actionSupport>

72. Choose 1 option.

A developer creates a lightning web component to allow a Contact to be quickly entered. However, error messages are not displayed.

```
```html
```

```
<template>
```

```
 <lightning-record-edit-form object-api-name="Contact">
```

```
 <lightning-input-field field-name="FirstName"></lightning-input-field>
```

```
 <lightning-input-field field-name="LastName"></lightning-input-field>
```

```
 <lightning-input-field field-name="Email"></lightning-input-field>
```

```
 <lightning-button type="submit" name="submit" label="Create Contact">
```

```
 </lightning-button>
```

```
 </lightning-record-edit-form>
```

```
</template>
```

```
```
```

Which component should the developer add to the form to display error messages?

- A. lightning-messages
- B. lightning-error

C. apex:messages

D. aura:messages

73. Question 14 of 62**

Choose 1 option.

A company uses Salesforce to sell products to customers. They also have an external product information management (PIM) system that is the system of record for products.

A developer received these requirements:

- Whenever a product is created or updated in the PIM, a product must be created or updated as a Product2 record in Salesforce and a PricebookEntry record must be created or updated automatically by Salesforce.
- The PricebookEntry should be created in a Pricebook2 that is specified in a custom setting.

What should the developer use to satisfy these requirements?

A. SOject Tree REST

B. Custom Apex REST

C. Invocable Action

D. Event Monitoring

74. Choose 1 option.

A developer is writing a Jest test for a Lightning web component that conditionally displays child components based on a user's checkbox selections.

What should the developer do to properly test that the correct components display and hide for each scenario?

A. Add a teardown block to reset the DOM after each test.

B. Create a new describe block for each test.

C. Create a new j.sdom instance for each test.

D. Reset the DOM after each test with the afterEach() method.

75. Choose 1 option.

A developer sees test failures in the sandbox but not in production. No code or metadata changes have been actively made to either environment since the sandbox was created.

Which consideration should be checked to resolve the issue?

A. Ensure test classes are using SeeAllData = true.

B. Ensure the Apex classes are on the same API version.

C. Ensure the sandbox is on the same release as production.

D. Ensure that Disable Parallel Apex Testing is unchecked.

76. Choose 1 option.

A company's support process dictates that any time a case is closed with a status of 'Could not fix,' an Engineering Review custom object record should be created and populated with information from the case, the contact, and any of the products associated with the case.

What is the correct way to automate this using an Apex trigger?

A. A before update trigger on Case that creates the Engineering Review record and inserts it

B. An after upset trigger on Case that creates the Engineering Review record and inserts it

C. A before upset trigger on Case that creates the Engineering Review record and inserts it

D. An after update trigger on Case that creates the Engineering Review record and inserts it

77. Choose 1 option.

A developer built an Aura component for guests to self-register upon arrival at a front desk kiosk. Now the developer needs to create a component for the utility tray to alert users whenever a guest arrives at the front desk.

What should be used?

A. DML Operation

B. ChangeLog

C. Application Event

D. Component Event

78. Choose 2 options.

A developer created an Opportunity trigger that updates the account rating when an associated opportunity is considered high value. Current criteria for an opportunity to be considered high value is an amount greater than or equal to \$1,000,000. However, this criteria value can change over time.

There is a new requirement to also display high value opportunities in a Lightning web component.

Which two actions should the developer take to meet these business requirements, and also prevent the business logic that obtains the high value opportunities from being repeated in more than one place?

A. Leave the business logic code inside the trigger for efficiency.

B. Use custom metadata to hold the high value amount.

C. Call the trigger from the Lightning web component.

D. Create a helper class that fetches the high value opportunities.

79. Choose 2 options.

A developer created a Lightning web component that allows users to input a text value that is used to search for Accounts by calling an Apex method. The Apex method returns a list of AccountWrappers and is called imperatively from a JavaScript event handler.

```
01: public class AccountSearcher {  
02:  
03: public static List<AccountWrapper> search(String term) {  
04: List<AccountWrapper> wrappers = getMatchingAccountWrappers(term);  
05: return wrappers;  
06: }  
07:  
08:  
09: public class AccountWrapper {  
10: public Account account { get; set; }  
11: public Decimal matchProbability { get; set; }  
12: }  
13: // ...other methods, including getMatchingAccountWrappers implementation...  
14: }  
...
```

Which two changes should the developer make so the Apex method functions correctly?

A. Add @AuraEnabled to line 01.

B. Add @AuraEnabled to line 09.

C. Add @AuraEnabled to lines 10 and 11.

D. Add @AuraEnabled to line 03.

80. Choose 1 option.

A developer needs to store variables to control the style and behavior of a Lightning Web Component.

Which feature can be used to ensure that the variables are testable in both Production and all Sandboxes?

A. Custom metadata

B. Custom object

C. Custom setting

D. Custom variable

81. Choose 1 option.

A Salesforce developer is hired by a multi-national company to build a custom Lightning application that shows employees their employment benefits and earned commissions over time. The application must acknowledge and respect the user's locale context for dates, times, numbers, currency, and currency symbols.

When using Aura components, which approach should the developer implement to ensure the Lightning application complies with the user's locale?

A. Use the `$User` global variable to retrieve the user preferences.

B. Create a Hierarchical custom setting to store user preferences.

C. Use the `$Locale` value provider to retrieve the user preferences.

D. Use the `$Label` global value provider.

82. Choose 3 options.

A company recently deployed a Visualforce page with a custom controller that has a data grid of information about Opportunities in the org. Users report that they receive a "Maximum view state size limit" error message under certain conditions.

According to Visualforce best practice, which three actions should the developer take to reduce the view state?

A. Use the `transient` keyword in the Apex controller for variables that do not maintain state.

B. Use the `private` keyword in the controller for variables.

C. Use the `final` keyword in the controller for variables that will not change.

D. Use filters and pagination to reduce the amount of data.

E. Refine any SOQL queries to return only data relevant to the page.

83. Choose 1 option.

An Apex trigger creates a Contract record every time an Opportunity record is marked as Closed and Won. This trigger is working great, except (due to a recent acquisition) historical Opportunity records need to be loaded into the Salesforce instance.

When a test batch of records are loaded, the Apex trigger creates Contract records. A developer is tasked with preventing Contract records from being created when mass loading the Opportunities, but the daily users still need to have the Contract records created.

What is the most extendable way to update the Apex trigger to accomplish this?

- A. Add the Profile ID of the user who loads the data to the trigger, so the trigger will not fire for this user.
- B. Add a validation rule to the Contract to prevent Contract creation by the user who loads the data.
- C. Use a hierarchy custom setting to skip executing the logic inside the trigger for the user who loads the data.
- D. Use a list custom setting to disable the trigger for the user who loads the data.

84. Choose 1 option.

A company wants to incorporate a third-party web service to set the Address fields when an Account is inserted, if they have not already been set.

What is the optimal way to achieve this?

- A. Create a Before Save Flow, execute a Queueable job from it, and make a callout from the Queueable job.
- B. Create an Apex class, execute a Batch Apex job from it, and make a callout from the Batch Apex job.
- C. Create an Apex trigger, execute a Queueable job from it, and make a callout from the Queueable job.
- D. Create an Apex class, execute a Future method from it, and make a callout from the Future method.

85. Choose 2 options.

Refer to the code:

****Lightning Web Component HTML file****

```
```html
```

```
<template>
```

```
 <lightning-button label="Call server" onclick={handleClick}></lightning-button>
```

```
</template>
```

```
```
```

****Lightning Web Component JS file****

```
``javascript
```

```
import {LightningElement} from 'lwc';
```

```
import serverEcho from '@salesforce/apex/SimpleServerSideController.serverEcho';
```

```
export default class Helloworld extends LightningElement {
```

```
    firstName = 'world';
```

```
    handleClick() {
```

```
        serverEcho({
```

```
            firstName: this.firstName
```

```
        })
```

```
        .then((result) => {
```

```
            alert('From server: ' + result);
```

```
        })
```

```
        .catch((error) => {
```

```
            console.error(error);
```

```
        });
```

```
    }
```

```
}
```

```
...
```

```
public with sharing class SimpleServerSideController {
```

```
    @AuraEnabled
```

```
    public static String serverEcho(sObject firstName) {
```

```
        String firstNameStr = (String)firstName.get('firstName');
```

```
        return ('Hello from the server, ' + firstNameStr);
```

```
    }
```

```
}
```

```
...
```

Given the code above, which two changes need to be made in the Apex Controller for the code to work?

A. Annotate the entire class as @AuraEnabled instead of just the single method.

B. Change the argument in the Apex Controller line 05 from sObject to String.

C. Remove line 06 from the Apex Controller and instead use firstName in the return on line 07.

D. Change the method signature to be global static, not public static.

86. Choose 3 options.

A developer is building a complex commission calculation engine in Apex that is called from an Opportunity trigger. During QA it was reported that the calculations are incorrect.

The developer has representative test data and passing test methods in their developer sandbox.

Which three tools or techniques could the developer use to execute the code and pause it at key lines to visually inspect values of various Apex variables?

A. Apex Interactive Debugger

B. Apex Replay Debugger

C. Workbench

D. Developer Console

E. Breakpoints

87. Choose 1 option.

Consider the following code snippet:

```
01 public class with sharing AccountsController{
02
03     @AuraEnabled
04     public List<Account> getAllAccounts(){
05         return [Select Id, Name, Industry FROM Account];
06     }
07
08 }
...
```

As part of the deployment cycle, a developer creates the following test class:

```

01 private class with sharing AccountsController_Test{
02
03     @TestSetup
04     private static void makeData(){
05         User user1 = [Select Id FROM User WHERE Profile.Name = 'System Administrator' and isActive
= true LIMIT 1 ];
06         User user2 = [Select Id FROM User WHERE Profile.Name = 'Standard User' and userName =
'test@test.com' and isActive = true LIMIT 1 ];
07
08         TestUtils.insertAccounts(10,user1.Id);
09         TestUtils.insertAccounts(20,user2.Id);
10     }
11
12     @isTest
13     private static void testGetAllAccounts(){
14         // Query the Standard User into memory and enclose lines 15 and 16 within the
System.runAs(user) method.
15         List<Account> result = AccountsController.getAllAccounts();
16         System.assertEquals(20,result.size());
17     }
18 }
...

```

When the test class runs, the assertion fails.

Which change should the developer implement in the Apex test method to ensure the test method executes successfully?

- A. Add @IsTest(seeAllData=true) to line 12 and enclose lines 15 and 16 within Test.startTest() and Test.stopTest().
- B. Add System.runAs(User) to line 14 and enclose line 15 within Test.startTest() and Test.stopTest().
- C. Query the Standard User into memory and enclose lines 15 and 16 within the System.runAs(user) method.**
- D. Query the Administrator user into memory and enclose lines 15 and 16 within the System.runAs(user) method.

88. Choose 1 option.

Consider the Apex class below that defines a RemoteAction used on a Visualforce search page.

```
global with sharing class MyRemoter {  
    public String accountName { get; set; }  
    public static Account account { get; set; }  
    public MyRemoter() {}  
    @RemoteAction  
    global static Account getAccount(String accountName) {  
        account = [SELECT Id, Name, NumberOfEmployees FROM Account WHERE Name = :accountName];  
        return account;  
    }  
}  
...  
...
```

Which code snippet will assert that the remote action returned the correct Account?

A.

```
MyRemoter remote = new MyRemoter();  
Account a = remote.getAccount('TestAccount');  
System.assertEquals( 'TestAccount', a.Name );  
...  
...
```

B.

```
MyRemoter remote = new MyRemoter('TestAccount');  
Account a = remote.getAccount();  
System.assertEquals( 'TestAccount' , a.Name );  
...  
...
```

C.

```
Account a = controller.getAccount('TestAccount');  
System.assertEquals( 'TestAccount', a.Name );
```

...

D.

```
Account a = MyRemoter.getAccount('TestAccount');
```

```
System.assertEquals( 'TestAccount', a.Name );
```

...

89. Choose 2 options.

Consider the queries in the options below and the following information:

- For these queries, assume that there are more than 200,000 Account records.
- These records include soft-deleted records; that is, deleted records that are still in the Recycle Bin.
- There are two fields that are marked as External Id on the Account. These fields are Customer_Number__c and ERP_Key__c.

Which two queries are optimized for large data volumes?

A. SELECT Id FROM Account WHERE Name != '' AND Customer_Number__c = 'ValueA'

B. SELECT Id FROM Account WHERE Name != '' AND IsDeleted = false

C. SELECT Id FROM Account WHERE Name != NULL

D. SELECT Id FROM Account WHERE Id IN :aListVariable

90. Choose 1 option.

An Aura component has a section that displays some information about an Account and it works well on the desktop, but we have to scroll horizontally to see the description field output on their mobile devices and tablets.

```
``html
```

```
<lightning:layout multipleRows="false">
```

```
  <lightning:layoutItem size="6">{!v.rec.Name}
```

```
</lightning:layoutItem>
```

```
  <lightning:layoutItem size="6">{!v.rec.Description__c}
```

```
</lightning:layoutItem>
```

```
</lightning:layout>
```

...

How should a developer change the component to be responsive for mobile and tablet devices?

- A.

```
```html
```

```
<lightning:layout multipleRows="false">

 <lightning:layoutItem multipleRows="12"
largeDeviceSize="6">{!v.rec.Name}</lightning:layoutItem>

 <lightning:layoutItem multipleRows="12"
largeDeviceSize="6">{!v.rec.Description__c}</lightning:layoutItem>

</lightning:layout>
```

...

- B.

```
```html
```

```
<lightning:layout>

  <lightning:layoutItem smallDeviceSize="12" mediumDeviceSize="6"
largeDeviceSize="6">{!v.rec.Name}</lightning:layoutItem>

  <lightning:layoutItem smallDeviceSize="12" mediumDeviceSize="6"
largeDeviceSize="6">{!v.rec.Description__c}</lightning:layoutItem>

</lightning:layout>
```

...

- C.

```
```html
```

```
<lightning:layout multipleRows="true">

 <lightning:layoutItem padding="around-small" size="6">{!v.rec.Name}</lightning:layoutItem>

 <lightning:layoutItem padding="around-small"
size="6">{!v.rec.Description__c}</lightning:layoutItem>

</lightning:layout>
```

...

- D.

```
```html
```

```
<lightning:layout verticalAlign="start" multipleRows="true">

  <lightning:layoutItem flexibility="auto" size="6">{!v.rec.Name}</lightning:layoutItem>

  <lightning:layoutItem flexibility="auto" size="6">{!v.rec.Description__c}</lightning:layoutItem>

</lightning:layout>
```


...

91. Choose 2 options.

A developer created a class that implements the Queueable Interface, as follows:

```
public class without sharing OrderQueueableJob implements Queueable {  
    public void execute(QueueableContext context) {  
        // implementation logic  
        System.enqueueJob(new FollowUpJob());  
    }  
}
```

...

As part of the deployment process, the developer is asked to create a corresponding test class.

Which two actions should the developer take to successfully execute the test class?

- A. Implement `seeAllData=true` to ensure the Queueable job is able to run in bulk mode.
- B. Implement `Test.isRunningTest()` to prevent chaining jobs during test execution.
- C. Ensure the running user of the test class has, at least, the View All permission on the Order object.
- D. Enclose `System.enqueueJob(new OrderQueueableJob())` within `Test.startTest` and `Test.stopTest()`.

92. Choose 1 option.

A developer is writing code that requires making callouts to an external web service.

Which scenario necessitates that the callout be made in an asynchronous method?

- A. The callout could take longer than 60 seconds to complete.
- B. The callouts will be made using the REST API.
- C. The callouts will be made in an Apex trigger.
- D. Over 10 callouts will be made in a single transaction.

93. Choose 1 option.

A developer wants to write a generic Apex method that will compare the Salesforce Name field between any two object records. For example, to compare the Name field of an Account and an Opportunity; or the Name of an Account and a Contact.

Assuming the Name field exists, how should the developer do this?

- A. Use a `String.replace()` method to parse the contents of each Name field and then compare the results.
- B. Use the Salesforce Metadata API to extract the value of each object and compare the Name fields.
- C. Cast each object into an `sObject` and use `sObject.get('Name')` to compare the Name fields.
- D. Invoke a `Schema.describe()` function to compare the values of each Name field.

94. Choose 1 option.

After a platform event is defined in a Salesforce org, events can be published via which mechanism?

- A. External Apps require the standard Streaming API.
- B. Internal Apps can use outbound messages.
- C. External Apps use an API to publish event messages.
- D. Internal Apps can use entitlement processes.

95. Choose 1 option.

An Apex trigger creates an Order__c record every time an Opportunity is won by a Sales Rep. Recently the trigger is creating two orders.

What is the optimal technique for a developer to troubleshoot this?

- A. Disable all flows, and then re-enable them one at a time to see which one causes the error.
- B. Set up debug logging for every Sales Rep, then monitor the logs for errors and exceptions.
- C. Run the Apex Test Classes for the Apex trigger to ensure the code still has sufficient code coverage.
- D. Add `system.debug()` statements to the code and use the Developer Console logs to trace the code.

96. Choose 3 options.

Refer to the following code snippet:

```
public class LeadController {  
    public static List<Lead> getFetchLeadList(String searchTerm, Decimal aRevenue) {  
        String safeTerm = '%' + searchTerm.escapeSingleQuotes() + '%';  
        return [  

```

```

SELECT Name, Company, AnnualRevenue
FROM Lead

WHERE AnnualRevenue >= :aRevenue

AND Company LIKE :safeTerm

LIMIT 20

];

}

}

...

```

A developer created a JavaScript function as part of a Lightning web component (LWC) that surfaces information about Leads by wire calling `getFetchLeadList` when certain criteria are met.

Which three changes should the developer implement in the Apex class above to ensure the LWC can display data efficiently while preserving security?

- A. Use the `WITH SECURITY_ENFORCED` clause within the SOQL query.
- B. Implement the `with sharing` keyword in the class declaration.
- C. Annotate the Apex method with `@AuraEnabled(Cacheable=true)`.
- D. Implement the `without sharing` keyword in the class declaration.
- E. Annotate the Apex method with `@AuraEnabled`.

97. Choose 1 option.

A company notices that their unit tests in a test class with many methods to create many records for prerequisite reference data are slow.

What can a developer do to address the issue?

- A. Turn off triggers, flows, and validations when running tests.
- B. Move the prerequisite reference data setup to the constructor for the test class.
- C. Move the prerequisite reference data setup to a `@testSetup` method in the test class.
- D. Move the prerequisite reference data setup to a `TestDataFactory` and call that from each test method.

98. Choose 2 options.

A company has reference data stored in multiple custom metadata records that represent default information and delete behavior for certain geographic regions.

When a contact is inserted, the default information should be set on the contact from the custom metadata records based on the contact's address information. Additionally, if a user attempts to delete a contact that belongs to a flagged region, the user must get an error message.

Depending on company personnel resources, what are two ways to automate this?

A. Apex trigger

B. Remote action

C. Flow Builder

D. Apex invocable method

99. Choose 1 option.

A developer used custom settings to store some configuration data that changes occasionally. However, tests are now failing in some of the sandboxes that were recently refreshed.

What should be done to eliminate this issue going forward?

A. Set the setting type on the custom setting to List.

B. Replace custom settings with static resources.

C. Replace custom settings with custom metadata.

D. Set the setting type on the custom setting to Hierarchy.

100. Choose 1 option.

A developer is responsible for formulating the deployment process for a Salesforce project. The project follows a source-driven development approach, and the developer wants to ensure efficient deployment and version control of the metadata changes.

Which tool or mechanism should be utilized for managing the source-driven deployment process?

A. Data Loader

B. Change Sets

C. Salesforce CLI with Salesforce DX

D. Unmanaged Packages

101. Choose 1 option.

Universal Containers is using a custom Salesforce application to manage customer support cases. The support team needs to collaborate with external partners to resolve certain cases. However, they want to control the visibility and access to the cases shared with the external partners.

Which Salesforce feature can help achieve this requirement?

A. Apex managed sharing

B. Sharing sets

C. Role hierarchy

D. Criteria-based sharing rules

102. Choose 2 options.

```
trigger AssignOwnerByRegion on Account ( before insert, before update ) {  
    List<Account> accountList = new List<Account>();  
    for( Account anAccount : trigger.new ) {  
        Region__c theRegion = [  
            SELECT Id, Name, Region_Manager__c  
            FROM Region__c  
            WHERE Name = :anAccount.Region_Name__c  
        ];  
        anAccount.OwnerId = theRegion.Region_Manager__c;  
        accountList.add( anAccount );  
    }  
    update accountList;  
}  
...
```

Consider the above trigger intended to assign the Account to the manager of the Account's region.

Which two changes should a developer make in this trigger to adhere to best practices?

A. Remove the last line updating accountList as it is not needed.

B. Use a Map accountMap instead of List accountList.

C. Use a Map to cache the results of the Region__c query by Id.

D. Move the Region__c query to outside the loop.

103. Choose 1 option.

A developer is building a Lightning web component that retrieves data from Salesforce and assigns it to the record property:

```
```\njavascript\n\nimport { LightningElement, api, wire } from 'lwc';\n\nimport { getRecord } from 'lightning/uiRecordApi';\n\nexport default class Record extends LightningElement {\n\n  @api fields;\n\n  @api recordId;\n\n  record;\n\n}\n```\n
```

What must be done in the component to get the data from Salesforce?

A. Add the following code above record:

```
`@api(getRecord, { recordId: '$recordId' })`
```

Get the fields in renderedCallback() and assign them to record.

B. Add the following code above record:

```
`@wire(getRecord, { recordId: '$recordId' })`
```

Get the fields in renderedCallback() and assign them to record.

C. Add the following code above record:

```
`@api(getRecord, { recordId: '$recordId', fields: '$fields' })`
```

D. Add the following code above record:

```
`@wire(getRecord, { recordId: '$recordId', fields: '$fields' })`
```

104. Choose 2 options.

Consider the following code snippet:

```
HttpRequest req = new HttpRequest();\n\nreq.setEndpoint('https://TestEndpoint.example.com/some_path');\n\nreq.setMethod('GET');
```

```

Blob headerValue = Blob.valueOf('myUserName' + ':' + 'strongPassword');
String authorizationHeader = 'BASIC ' + EncodingUtil.base64Encode(headerValue);
req.setHeader('Authorization', authorizationHeader);
Http http = new Http();
HTTPResponse res = http.send(req);
...

```

Which two steps should the developer take to add flexibility to change the endpoint and credentials without needing to modify code?

- A. Use req.setEndpoint(Label endPointURL);
- B. Use req.setEndpoint('callout:endPoint\_NC'); within the callout request.
- C. Store the URL of the endpoint in a custom Label named endPointURL.
- D. Create a Named Credential, endPoint\_NC, to store the endpoint and credentials.

105. Choose 1 option.

Which code snippet processes records in the most memory efficient manner, avoiding governor limits such as "Apex heap size too large"?

A.

```

Map<Id, Opportunity> opportunities = new Map<Id, Opportunity>([SELECT Id, Amount from Opportunity]);
for(Id oppld: opportunities.keySet()){
 // perform operation here
}
...

```

B.

```

for(Opportunity opp: [SELECT Id, Amount from Opportunity]){
 // perform operation here
}
...

```

C.

```
List<Opportunity> opportunities = Database.query('SELECT Id, Amount from Opportunity');
for(Opportunity opp: opportunities){
 // perform operation here
}
...
```

D.

```
List<Opportunity> opportunities = [SELECT Id, Amount from Opportunity];
for(Opportunity opp: opportunities){
 // perform operation here
}
...
```

Of course. Here are questions 47 to 62 in English, including all provided code snippets and options.

106. Choose 1 option.

A developer is working with existing functionality that tracks how many times a stage has changed for an Opportunity. When the Opportunity's stage is changed, a workflow rule is fired to increase the value of a field by one. The developer wrote an after trigger to create a child record when the field changes from 4 to 5.

A user changes the stage of an Opportunity and manually sets the count field to 4. The count field updates to 5, but the child record is not created.

What is the reason this is happening?

A. After triggers fire before workflow rules.

B. Trigger.new does not change after a field update.

C. Trigger.old does not contain the updated value of the count field.

D. After triggers are not fired after field updates.

107. Choose 1 option.

A Visualforce page loads slowly due to the large amount of data it displays.

Which strategy can a developer use to improve the performance?

A. Use the transient keyword for the List variables used in the custom controller.



B. Use lazy loading to load the data on demand, instead of in the controller's constructor.

C. Use JavaScript to move data processing to the browser instead of the controller.

D. Use an <apex:actionPoller> in the page to load all of the data asynchronously.

108. Choose 1 option.

A developer is developing a reusable Aura component that will reside on an sObject Lightning page with the following HTML snippet:

```
``html
<aura:component implements="force:hasRecordId,flexipage:availableForAllPageTypes">
 <div>Hello!</div>
</aura:component>
``
```

How can the component's controller get the context of the Lightning page that the sObject is on without requiring additional test coverage?

A. Create a design attribute and configure via App Builder.

B. Set the sObject type as a component attribute.

C. Use the getObjectType() method in an Apex class.

D. Add force:hasSubjectName to the implements attribute.

109. Choose 1 option.

A developer is creating a Lightning web component to display a calendar. The component will be used in multiple countries. In some locales, the first day of the week is a Monday, or a Saturday, or a Sunday.

What should the developer do to ensure the calendar displays accurately for users in every locale?

A. Query the FirstDayOfWeek field from the Locale for the current user.

B. Use a custom metadata type to store key/value pairs.

C. Use UserInfo.getLocale() in the component.

D. Import the @salesforce/i18n module and use the firstDayOfWeek internationalization property.

---

110. Choose 1 option.

The Salesforce admin at Cloud Kicks created a custom object called `Region\_\_c` to store all postal zip codes in the United States and the Cloud Kicks sales region the zip code belongs to.

**\*\*Object Name\*\*:** `Region\_\_c`

**\*\*Fields\*\*:** `Zip\_Code\_\_c` (Text), `Region\_Name\_\_c` (Text)

Cloud Kicks wants a trigger on the Lead to populate the Region based on the Lead's zip code.

Which code segment is the most efficient way to fulfill this request?

A.

```
Set<String> zips = new Set<String>();
for(Lead l : Trigger.new) {
 if(l.PostalCode != Null) {
 zips.add(l.PostalCode);
 }
}
for(Lead l : Trigger.new) {
 List<Region__c> regions = [SELECT Zip_Code__c, Region_Name__c FROM Region__c WHERE
Zip_Code__c IN :zips];
 for(Region__c r : regions) {
 if(l.PostalCode == r.Zip_Code__c) {
 l.Region__c = r.Region_Name__c;
 }
 }
}
...
```

B.

```
Set<String> zips = new Set<String>();
for(Lead l : Trigger.new) {
```

```

 if(l.PostalCode != Null) {
 zips.add(l.PostalCode);
 }
 }

 List<Region__c> regions = [SELECT Zip_Code__c, Region_Name__c FROM Region__c WHERE
Zip_Code__c IN :zips];

 for(Lead l : Trigger.new) {
 for(Region__c r : regions) {
 if(l.PostalCode == r.Zip_Code__c) {
 l.Region__c = r.Region_Name__c;
 }
 }
 }
 ...

```

C.

```

 for(Lead l : Trigger.new) {
 Region__c reg = [SELECT Region_Name__c FROM Region__c WHERE Zip_Code__c =
:l.PostalCode];
 l.Region__c = reg.Region_Name__c;
 }
 ...

```

D.

```

Set<String> zips = new Set<String>();

 for(Lead l : Trigger.new) {
 if(l.PostalCode != Null) {
 zips.add(l.PostalCode);
 }
 }

 List<Region__c> regions = [SELECT Zip_Code__c, Region_Name__c FROM Region__c WHERE
Zip_Code__c IN :zips];

```

```

Map<String, String> zipMap = new Map<String, String>();

for(Region__c r : regions) {

 zipMap.put(r.Zip_Code__c, r.Region_Name__c);

}

for(Lead l : Trigger.new) {

 if(l.PostalCode != Null) {

 l.Region__c = zipMap.get(l.PostalCode);

 }

}

...

```

111. Choose 1 option.

Refer to the code snippet below:

```

public static void updateCreditMemo(String customerId, Decimal newAmount){

 List<Credit_Memo__c> toUpdate = new List<Credit_Memo__c>();

 for(Credit_Memo__c creditMemo : [Select Id, Name, Amount__c FROM Credit_Memo__c WHERE
Customer_Id__c = :customerId LIMIT 50]) {

 creditMemo.Amount__c = newAmount;

 toUpdate.add(creditMemo);

 }

 Database.update(toUpdate,false);

}

...

```

A custom object called Credit\_Memo\_\_c exists in a Salesforce environment. As part of a new feature development that retrieves and manipulates this type of record, the developer needs to ensure race conditions are prevented when a set of records are modified within an Apex transaction.

In the preceding Apex code, how can the developer alter the query statement to use SOQL features to prevent race conditions within a transaction?

A. `[Select Id, Name, Amount\_\_c FROM Credit\_Memo\_\_c WHERE Customer\_Id\_\_c = :customerId LIMIT 50 FOR UPDATE]`

B. `[Select Id, Name, Amount\_\_c FROM Credit\_Memo\_\_c WHERE Customer\_Id\_\_c = :customerId USING SCOPE LIMIT 50]`

C. `[Select Id, Name, Amount\_\_c FROM Credit\_Memo\_\_c WHERE Customer\_Id\_\_c = :customerId LIMIT 50 FOR REFERENCE]`

D. `[Select Id, Name, Amount\_\_c FROM Credit\_Memo\_\_c WHERE Customer\_Id\_\_c = :customerId LIMIT 50 FOR VIEW]`

113. Choose 1 option.

Business rules require a Contact to always be created when a new Account is created.

What can be used when developing a custom screen to ensure an Account is not created if the creation of the Contact fails?

A. Use `setSavePoint()` and `rollback()` with a try-catch block.

B. Use a Database Savepoint method with a try-catch block.

C. Use the `Database.Insert` method with `allOrNone` set to false.

D. Use the `Database.Delete` method if the Contact insertion fails.

114. Choose 1 option.

A developer creates an application event that has triggered an infinite loop.

What may have caused this problem?

A. The event has multiple handlers registered in the project.

B. The event is fired from a custom renderer.

C. An event is fired 'ontouched' and is unhandled.

D. The event handler calls a trigger.

---

115. Choose 1 option.

A company uses Opportunities to track sales to their customers and their org has millions of Opportunities. They want to begin to track revenue over time through a related Revenue object.

As part of their initial implementation, they want to perform a one-time seeding of their data by automatically creating and populating Revenue records for Opportunities, based on complex logic.

They estimate that roughly 100,000 Opportunities will have Revenue records created and populated.

What is the optimal way to automate this?

A. Use `Database.executeBatch()` to invoke a `Database.Batchable` class.

- B. Use `System.enqueueJob()` to invoke a Queueable class.
- C. Use `Database.executeBatch()` to invoke a Queueable class.
- D. Use `System.scheduleJob()` to schedule a Database.Schedulable class.

116. Choose 1 option.

A company has an Apex process that makes multiple extensive database operations and web service callouts. The database processes and web services can take a long time to run and must be run sequentially.

How should the developer write this Apex code without running into governor limits and system limitations?

- A. Use Apex Scheduler to schedule each process.
- B. Use Limits class to stop entire process once governor limits are reached.
- C. Use multiple `@future` methods for each process and callout.
- D. Use Queueable Apex to chain the jobs to run sequentially.

117. Choose 1 option.

Universal Containers has an Apex trigger on Account that creates an Account Plan record when an Account is marked as a Customer.

Recently a record-triggered flow was added so that whenever an Account is marked as a Customer, a 'Customer Since' date field is updated with today's date. Since the addition of the flow, two Account Plan records are created whenever the Account is marked as a Customer.

What might cause this to happen?

- A. The Apex trigger is not bulk safe and calls insert inside of a for loop.
- B. The flow is configured to use an 'Update Records' element.
- C. The flow is configured to evaluate when a record is created and every time it is edited.
- D. The Apex trigger does not use a static variable to ensure it only fires once.

118. Choose 1 option.

Refer to the test method below:

@isTest

```

static void testIncrement() {

 Account acct = new Account(Name = 'Test');

 acct.Number_Of_Times_Viewed__c = 0;

 insert acct;

 AuditUtil.incrementViewed(acct.Id);

 Account acctAfter = [SELECT Number_Of_Times_Viewed__c FROM Account WHERE Id =
:acct.Id][0];

 System.assertEquals(1, acctAfter.Number_Of_Times_Viewed__c);
}
...

```

The test method calls an @future method that increments the Number\_of\_Times\_Viewed\_\_c value. The assertion is failing because the Number\_of\_Times\_Viewed\_\_c equals 0.

What is the optimal way to fix this?

- A. Change the assertion to `System.assertEquals(0, acctAfter.Number\_Of\_Times\_Viewed\_\_c)`.
- B. Add `Test.startTest()` before and `Test.stopTest()` after insert `acct`.
- C. Change the initialization to `acct.Number\_Of\_Times\_Viewed\_\_c = 1`.
- D. Add `Test.startTest()` before and `Test.stopTest()` after `AuditUtil.incrementViewed`.

119. Choose 1 option.

A developer implemented a custom data table in a Lightning web component with filter functionality. However, users are submitting support tickets about long load times when the filters are changed. The component uses an Apex method that is called to query for records based on the selected filters.

What should the developer do to improve performance of the component?

- A. Use SOSL to query the records on filter change.
- B. Use `setStorable()` in the Apex method to store the response in the client-side cache.
- C. Return all records into a list when the component is created and filter the array in JavaScript.
- D. Use a selective SOQL query with a custom index.

120. A Salesforce Platform Developer is leading a team that is tasked with deploying a new application to production. The team has used source-driven development, and they want to ensure that the application is deployed successfully.

What tool or mechanism should be used to verify that the deployment is successful?

- A. Force.com Migration Tool
- B. Apex Test Execution
- C. Salesforce DX CLI
- D. Salesforce Inspector

121. What is a benefit of JavaScript remoting over Visualforce Remote Objects?

- A. Supports complex server-side application logic
- B. Does not require any Apex code
- C. Does not require any JavaScript code
- D. Allows for specified re-render targets

122. A developer needs to implement a historical Task reporting feature that allows users, assigned to a custom profile named "Auditors", to perform searches against the Tasks related to the Account object.

The developer must ensure the search is able to return Tasks that are between 12 and 24 months old. It should exclude any tasks which have been deleted, and include Tasks whether archived or not.

Given the following code, which select statement should be inserted at the placeholder as a valid way to retrieve the Tasks ranging from 12 to 24 month old?

```
...
Date initialDate = System.Today().addMonths(-24);
Date endDate = System.Today().addMonths(-12);
// Insert SELECT statement here
...
```

- A. `[SELECT AccountId, CreatedDate, Subject FROM Task WHERE What.Type = 'Account' AND isArchived=true AND CreatedDate => :initialDate AND CreatedDate <= :endDate];`
- B. `[SELECT AccountId, CreatedDate, Subject FROM Task WHERE What.Type = 'Account' AND CreatedDate => :initialDate AND CreatedDate <= :endDate ALL ROWS];`



C. `[SELECT AccountId, CreatedDate, Subject FROM Task WHERE What.Type = 'Account' AND isDeleted=false AND CreatedDate => :initialDate AND CreatedDate <= :endDate ALL ROWS];`

D. `[SELECT AccountId, CreatedDate, Subject FROM Task WHERE What.Type = 'Account' AND isArchived=true AND CreatedDate => :initialDate AND CreatedDate <= :endDate ALL ROWS];`

123. A company has code to update a Request and Request Lines and make a callout to their external ERP system's REST endpoint with the updated records.

...

```
public void updateAndMakeCallout(Map<Id, Request__c> regs, Map<Id, Request_Line__c> regLines)
{
 Savepoint sp = Database.setSavepoint();
 try {
 insert regs.values();
 insert regLines.values();
 HttpResponse response = CalloutUtil.makeRestCallout(regs.keySet(), regLines.keySet());
 } catch (Exception e) {
 Database.rollback(sp);
 System.debug(e);
 }
}
```

...

The CalloutUtil.makeRestCallout fails with a 'You have uncommitted work pending. Please commit or rollback before calling out' error.

What should be done to address the problem?

A. Move the CalloutUtil.makeRestCallout method call below the catch block.

B. Change the CalloutUtil.makeRestCallout to an @future method.

C. Remove the Database.setSavepoint and Database.rollback.

D. Change the CalloutUtil.makeRestCallout to an @InvocableMethod method.

124. A developer writes a Lightning web component that displays a dropdown list of all custom objects in the org from which a user was selected. An Apex method prepares and returns data to the component.

What should the developer do to determine which objects to include in the response?

- A. Import the list of all custom objects from @salesforce/schema.
- B. Check the getObjectType() value for 'Custom' or 'Standard' on the sObject describe result.
- C. Check the isCustom() value on the sObject describe result.
- D. Use the getCustomObjects() method from the Schema class.

125. A developer is trying to access org data from within a test class.

Which sObject type requires the test class to have the `(seeAllData=true)` annotation?

- A. RecordType
- B. Report
- C. User
- D. Profile

126. Which three Visualforce components can be used to initiate Ajax behavior to perform partial page updates?

- A. ``
- B. ``
- C. ``
- D. ``
- E. ``

127. Universal Containers develops a Salesforce application that requires frequent interaction with an external REST API.

To avoid duplicating code and improve maintainability, how should they implement the API integration for code reuse?

A. Create a reusable Apex class for the API integration and invoke it from the relevant Apex classes.

B. Use a separate Apex class for each API endpoint to encapsulate the integration logic.

C. Store the API integration code as a static resource and reference it in each Apex class.

D. Include the API integration code directly in each Apex class that requires it.

128. A developer is asked to modify a lightning web component so that it displays in one column on phones and in two columns on tablets, desktops, and larger devices.

Given to the code below:

...

```
<lightning-layout multiple-rows="true">
```

```
 <lightning-layout-item>
```

```
 <div>Example 1</div>
```

```
 </lightning-layout-item>
```

```
 <lightning-layout-item>
```

```
 <div>Example 2</div>
```

```
 </lightning-layout-item>
```

```
</lightning-layout>
```

...

Which should the developer add to the code to meet the requirements?

A. Add `size="12" medium-device-size="6"` to the `<lightning-layout-item>` elements

B. Add `size="6" small-device-size="12"` to the `<lightning-layout-item>` elements

C. Add `small-device-size="12"` to the `<lightning-layout-item>` elements

D. Add `medium-device-size="6"` to the `<lightning-layout-item>` elements

129. A company uses an external system to manage its custom account territory assignments. Every quarter, millions of Accounts may be updated in Salesforce with new Owners when the territory assignments are completed in the external system.

What is the optimal way to update the Accounts from the external system?

A. Composite REST API

B. SOAP API

C. Bulk API

D. Apex REST Web Service

130. Consider the following code snippet:

```
...
```

```
public static List<Account> getAccounts(Date thisDate, Id goldenRT){
 List<Account> accountList = [Select Id, Name, Industry FROM Account WHERE CreatedDate =
:thisDate OR RecordTypeId = :goldenRT];
 return accountList;
}
```

```
...
```

The Apex method is executed in an environment with a large data volume count for Accounts, and the query is performing poorly.

Which technique should the developer implement to ensure the query performs optimally, while preserving the entire result set?

A. Break down the query into two individual queries and join the two result sets.

B. Annotate the method with the `@Future` annotation.

C. Use the `Database.querySelector` method to retrieve the accounts.

D. Create a formula field to combine the CreatedDate and RecordType value, then filter based on the formula.

131. Which use case can be performed only by using asynchronous Apex?

A. Querying tens of thousands of records

B. Making a call to schedule a batch process to complete in the future

C. Calling a web service from an Apex trigger

D. Updating a record after the completion of an insert

132. Which interface needs to be implemented by an Aura component so that it may be displayed in modal dialog by clicking a button on a Lightning record page?

A. `lightning:editAction`

B. `lightning:quickAction`

C. `force:lightningEditAction`

D. `force:lightningQuickAction`

133. Refer to the component code and requirements below:

```
<lightning: layout multipleRows="true">
<lightning: layoutItem size="12">{!v.account.Name}
</lighting: layoutItem>
<lightning: layoutItem size="12">{!v.account.Account Number} </lighting: layoutItem>
<lightning:layoutItem size="12">{!v.account.Industry} </lighting:layoutItem>
</lightning:layout>
```

Requirements:

1. For mobile devices, the information should display in three rows.
2. For desktops and tablets, the information should display in a single row.

Requirement 2 is not displaying as desired.

Which option has the correct component code to meet the requirements for desktops and tablets?

A. <lightning: layout multipleRows="true">

<lightning:layoutItem size="12" mediumDeviceSize="6">{!v.account.Name} </lighting:layoutItem>

<lightning: layoutItem size="12" mediumDeviceSize="6">{!v.account.AccountNumber}

</lighting:layoutItem>

<lightning:layoutItem size="12" mediumDeviceSize="6">{!v.account. Industry}

</lighting: layoutItem>

</lightning:layout>

B. <lightning: layout multipleRows="true"></lightning:layout>

C.<lightning: layout multipleRows="true">

<lightning:layoutItem size="12" largeDeviceSize="4">{!v.account.Name} </lightning:layoutItem>

<lightning: layoutItem size="12" large DeviceSize="4">{!v.account.Account Number}

</lightning:layoutItem>

<lightning:layoutItem size="12" large DeviceSize="4">{!v.account.Industry} </lightning:layoutItem>

</lightning: layout>

D. <lightning: layout multipleRows="true">

<lightning: layoutItem size="12" mediumDeviceSize="6" large DeviceSize="4"> {!v.account.Name}

</lightning: layoutItem>

<lightning: layoutItem size="12" mediumDeviceSize="6" large DeviceSize="4">

{!v.account.AccountNumber}

</lightning:layoutItem>

<lightning:layoutItem size="12" mediumDeviceSize="6" large DeviceSize="4"> {!v.account. Industry}

</lightning: layoutItem>

</lightning: layout>

134. Consider the following code snippet:

...

<c-selected-order>

<template for:each={orders.data} for:item="order">

<c-order orderId={order.Id}></c-order>

</template>

</c-selected-order>

...

How should the `<c-order>` component communicate to the `<c-selected-order>` component that an order has been selected by the user?

A. Create and dispatch a custom event.

B. Create and fire a component event.

C. Create and fire an application event.

D. Create and fire a standard DOM event.

135. A developer created a Lightning web component that uses a `lightning-record-edit-form` to collect information about Leads. Users complain that they only see one error message at a time about their input when trying to save a Lead record.

Which best practice should the developer use to perform the validations on more than one field, thus allowing more than one error message to be displayed simultaneously?

A. Apex REST

B. Client-side validation

C. Next Best Action

D. Custom validation rules

136. Refer to the Aura component below:

Component markup:

...

<aura:component>

<aura:attribute name="contactInfo" type="Object"/>

<aura:attribute name="showContactInfo" type="boolean" default="true"/>

<aura:handler name="init" value="{!this}" action="{!c.init}"/>

<!-- ... other code ... -->

<aura:if isTrue="{!v.showContactInfo}">

<c:contactInfo value="{!v.contactInfo}"/>

</aura:if>

</aura:component>

...

Controller JS:

...

```
{
 init: function(cmp, helper) {
 // ...other code ...
 var show = helper.getShowContactInfo();
 cmp.set("v.showContactInfo", show);
 },
 // other code...
}
...
```

A developer receives complaints that the component loads slowly.

Which change can the developer implement to make the component perform faster?

- A. Move the contents of `` into the component.
- B. Change the type of contactInfo to "Map".
- C. Change the default for showContactInfo to "false".

137. Which technique can run custom logic when a Lightning web component is loaded?

- A. Use an `` init event to call a function.
- B. Use the `` method.
- C. Use the `` method.
- D. Call `<\$A.enqueueAction>` and pass in the method to call.

138. Which Salesforce feature allows a developer to see when a user last logged in to Salesforce if real-time notification is not required?

- A. Asynchronous Data Capture Events
- B. Calendar Events
- C. Event Monitoring Log
- D. Developer Log



139. Refer to the Lightning component below:

```
...

<lightning:button label="Save" onclick="{!c.handleSave}" />
...

...

{
 handleSave : function (component, event, helper) {
 helper.saveAndRedirect(component);
 }
}
...
...
```

The Lightning Component allows users to click a button to save their changes and then redirects them to a different page. Currently when the user hits the Save button, the records are getting saved, but they are not redirected.

Which three techniques can a developer use to debug the JavaScript?

- A. Use the browser's dev tools to debug the JavaScript.
- B. Use Developer Console to view the debug log.
- C. Use `console.log()` messages in the JavaScript.
- D. Use Developer Console to view checkpoints.
- E. Enable Debug Mode for Lightning components for the user.

140. A company wants to run different logic based on an Opportunity's record type.

Which code segment handles this request and follows best practices?

- [ ] A.

```
List<RecordType> recTypes = [SELECT Id, Name FROM RecordType WHERE SubjectType = 'Opportunity' AND IsActive = True];
```

```
Map<String, Id> recTypeMap = new Map<String, Id>();
```

```
for (RecordType rt : recTypes) {
```

```
 recTypeMap.put(rt.Name, rt.Id);
```

```
}
```

```
for (Opportunity o : Trigger.new) {
```

```
 if(o.RecordTypeId == recTypeMap.get('New')) {
```

```
 // do some logic Record Type 1
```

```
 }
```

```
 else if (o.RecordTypeId == recTypeMap.get('Renewal')) {
```

```
 // do some logic for Record Type 2
```

```
 }
```

```
}
```

```
...
```

- [ ] B.

```
for (Opportunity o : Trigger.new) {
```

```
 if (o.RecordType.Name == 'New') {
```

```
 // do some logic Record Type 1
```

```
 }
```

```
 else if (o.RecordType.Name == 'Renewal') {
```

```
 // do some logic for Record Type 2
```

```
 }
```

```
}
```

```
...
```

- [ ] C.

```
List<RecordType> recTypes = [SELECT Id, Name FROM RecordType WHERE SubjectType = 'Opportunity' AND IsActive = True];
```

```
Map<String, Id> recTypeMap = new Map<String, Id>();
```

```
for (RecordType rt : recTypes) {
```

```
 recTypeMap.put(rt.Name, rt.Id);
```

```
}
```

```

for (Opportunity o : Trigger.new) {
 if (recTypeMap.get('New') != null && o.RecordTypeId == recTypeMap.get('New')) {
 // do some logic Record Type 1
 }
 else if (recTypeMap.get('Renewal') != null && o.RecordTypeId == recTypeMap.get('Renewal')) {
 // do some logic for Record Type 2
 }
}
...
- [] D.

```

```

Id newRecordTypeId =
Schema.SObjectType.Opportunity.getRecordTypeInfoByName().get('New').getRecordTypeId();

Id renewalRecordTypeId =
Schema.SObjectType.Opportunity.getRecordTypeInfoByName().get('Renewal').getRecordTypeId();

for (Opportunity o : Trigger.new) {
 if (o.RecordTypeId == newRecordTypeId) {
 // do some logic Record Type 1
 }
 else if (o.RecordTypeId == renewalRecordTypeId) {
 // do some logic for Record Type 2
 }
}

```

141. The Account object has a field, `Audit\_Code\_\_c`, that is used to specify what type of auditing the Account needs and a Lookup to User, `Auditor\_\_c`, that is the assigned auditor.

When an Account is initially created, the user specifies the `Audit\_Code\_\_c`. Each User in the org has a unique text field, `Audit\_Code\_\_c`, that is used to automatically assign the correct user to the Account's `Auditor\_\_c` field.

```

Trigger:
...

trigger AccountTrigger on Account (before insert) {
 AuditAssigner.setAuditor(Trigger.new);
}

```

```

}
...

...

public class AuditAssigner {
 public static void setAuditor(List<Account> accounts) {
 for (User u : [SELECT Id, Audit_Code__c FROM User]) {
 for (Account a : accounts) {
 if (u.Audit_Code__c == a.Audit_Code__c) {
 a.Auditor__c = u.Id;
 }
 }
 }
 }
}
...

```

What should be changed to most optimize the code's efficiency?

- A. Add a WHERE clause to the SOQL query to filter on audit codes.
- B. Build a `Map<String, List<Account>>` of audit code to accounts.
- C. Build a `Map<Id, List<String>>` of Account Id to audit codes.
- D. Add an initial SOQL query to get all distinct audit codes.

142. A developer created and tested a Visualforce page in their developer sandbox, but now receives reports that user encounter view state errors when using it in production.

What should the developer ensure to correct these errors?

- A. Ensure profiles have access to the Visualforce page.
- B. Ensure properties are marked as private.
- C. Ensure variables are marked as transient.

D. Ensure queries do not exceed governor limits.

143. Universal Containers develops a Visualforce page that requires the inclusion of external JavaScript and CSS files. They want to ensure efficient loading and caching of the page.

Which feature should be utilized to achieve this goal?

A. Static resources

B. `@RemoteAction`

C. ``

D. ``

144. Refer to the test method below:

...

Line 1: @isTest

Line 2: static void testMyTrigger()

Line 3: {

Line 4: //Do a bunch of data setup

Line 5: DataFactory.setupDataForMyTriggerTest();

Line 6:

Line 7: List<Account> acctsBefore = [SELECT Is\_Customer\_\_c FROM Account WHERE Id IN :DataFactory.accounts];

Line 8:

Line 9: //Utility to assert all accounts are not customers before the update

Line 10: AssertUtil.assertNotCustomers(acctsBefore);

Line 11:

Line 12: //Set accounts to be customers

Line 13: for(Account a : DataFactory.accounts)

Line 14: {

Line 15: a.Is\_Customer\_\_c = true;

Line 16: }

Line 17:

Line 18: update DataFactory.accounts;

Line 19:

Line 20: `List<Account> acctsAfter = [SELECT Number_Of_Transfers__c FROM Account WHERE Id IN :DataFactory.accounts];`

Line 21:

Line 22: `//Utility to assert Number_Of_Transfers__c is correct based on test data`

Line 23: `AssertUtil.assertNumberOfTransfers(acctsAfter);`

Line 24: `}`

...

The test method tests an Apex trigger that the developer knows will make a lot of queries when a lot of Accounts are simultaneously updated to be customers.

The test method fails at the Line 20 because of too many SOQL queries.

What is the correct way to fix this?

- A. Use ``Limits.getLimitQueries()`` to find the total number of queries that can be issued.
- B. Change the DataFactory class to create fewer Accounts so that the number of queries in the trigger is reduced.
- C. Add ``Test.startTest()`` before and add ``Test.stopTest()`` after both Line 7 and Line 20 of the code.
- D. Add ``Test.startTest()`` before and add ``Test.stopTest()`` after Line 18 of the code.

145. A company accepts orders for customers in their enterprise resource planning (ERP) system that must be integrated into Salesforce as Order\_\_c records with a lookup field to Account. The Account object has an external ID field, ERP\_Customer\_ID\_\_c.

What should the integration use to create new Order\_\_c records that will automatically be related to the correct Account?

- A. Upsert on the Order\_\_c object and specify the ERP\_Customer\_ID\_\_c for the Account relationship.
- B. Upsert on the Account and specify the ERP\_Customer\_ID\_\_c for the relationship.
- C. Merge on the Order\_\_c object and specify the ERP\_Customer\_ID\_\_c for the Account relationship.
- D. Insert on the Order\_\_c object followed by an update on the Order\_\_c object.

146. Universal Containers analyzes a Lightning web component and its Apex controller class that retrieves a list of contacts associated with an account. The code snippets are as follows:

**\*\*Lightning web component (accountContacts.html):\*\***

...

<template>

    <lightning-card title="Account Contacts">

        <lightning-datatable data={contacts} columns={columns} key-field="Id"></lightning-datatable>

    </lightning-card>

</template>

...

**\*\*Apex controller class (AccountContactsController.cls):\*\***

...

public with sharing class AccountContactsController {

    @AuraEnabled

    public static List<Contact> getAccountContacts(String accountId) {

        return [SELECT Id, Name, Email, Phone FROM Contact WHERE AccountId = :accountId];

    }

}

...

Based on the code snippets, what change should be made to display the contacts' mailing addresses in the Lightning web component?

A. Add a new method in the Apex controller class to retrieve the mailing addresses separately and modify the Lightning web component to invoke this method.

B. Modify the SOQL query in the getAccountContacts method to include the MailingAddress field.

C. Extend the lightning-datatable component in the Lightning web component to include a column for the MailingAddress field.

- [ ] D. Modify the SOQL query in the getAccountContacts method to include the MailingAddress field and update the columns attribute in javascript file to add Mailing address fields.

147. A developer created an Apex class that updates an Account based on input from a Lightning web component that is used to register an Account. The update to the Account should only be made if it has not already been registered.

```
...
```

```
account = [SELECT Id, Is_Registered__c FROM Account WHERE Id = :accountId];
```

```
if (!account.Is_Registered__c) {
 account.Is_Registered__c = true;
 // ...set other account fields...
 update account;
}
...
```

What should the developer do to ensure that users do not overwrite each other's updates to the same Account if they make updates at the same time?

- A. Add a try/catch block around the update.
- B. Use upset instead of update.
- C. Use `FOR UPDATE` in the SOQL query.
- D. Include LastModifiedDate in the query to make sure it wasn't recently updated.

148A developer is asked to develop a new AppExchange application. A feature of the program creates Survey records when a Case reaches a certain stage and is of a certain Record Type. This feature needs to be configurable, as different Salesforce instances require Surveys at different times. Additionally, the out-of-the-box AppExchange app needs to come with a set of best practice settings that apply to most customers.

What should the developer use to store and package the custom configuration settings for the app?

- A. Custom settings
- B. Custom objects
- C. Custom metadata
- D. Custom labels



149. Universal Containers implements a private sharing model for the `Convention\_Attendee\_\_c` custom object. As part of a new quality assurance effort, the company created an `Event\_Reviewer\_\_c` user lookup field on the object. Management wants the event reviewer to automatically gain Read/Write access to every record they are assigned to.

What is the best approach to ensure the assigned reviewer obtains Read/Write access to the record?

**A. Create an after insert trigger on the Convention Attendee custom object, and use Apex Sharing Reasons and Apex Managed Sharing.**

B. Create a before insert trigger on the Convention Attendee custom object, and use Apex Sharing Reasons and Apex Managed Sharing.

C. Create criteria-based sharing rules on the Convention Attendee custom object to share the records with the Event Reviewers.

D. Create a criteria-based sharing rule on the Convention Attendee custom object to share the records with a group of Event Reviewers.

150. The head of recruiting at Universal Containers (UC) wants to provide all internal users the ability to search for open positions by role, department, and location via a new recruiting app. In addition to search, users of the app should be able to refer a friend, apply for a position, and review the status of their current submissions.

The app will be surfaced to UC's existing iOS and Android users via the standard mobile app that Salesforce provides. It has a custom user interface design and offline access is not required.

Given these requirements, what is the recommended approach to develop the app?

A. Salesforce SDK

**B. Lightning Web Components**

C. Lightning Experience Builder

D. Visualforce

151. A developer is inserting, updating, and deleting multiple lists of records in a single transaction and wants to ensure that any error prevents all execution.

How should the developer implement error exception handling in their code to handle this?

A. Use Database methods to obtain lists of Database.SaveResults.

B. Use `Database.setSavepoint()` and `Database.rollback()` with a try-catch statement.

C. Use a try-catch statement and handle DML cleanup in the catch statement.

D. Use a try-catch and use `Object.addError()` on any failures.

152. How should a developer verify that a specific Account record is being tested in a test class for a Visualforce controller?

A. Insert the Account into Salesforce, instantiate the page reference in the test class, then use `System.setParentRecordId().get()` to set the Account ID.

B. Insert the Account in the test class, instantiate the page reference in the test class, then use `System.currentPageReference().getParameters().put()` to set the Account ID.

C. Instantiate the page reference in the test class, insert the Account in the test class, then use `seeAllData=true` to view the Account.

D. Instantiate the page reference in the test class, insert the Account in the test class, then use `System.setParentRecordId().get()` to set the Account ID.

153. Which method should be used to convert a Date to a String in the current user's locale?

A. `Date.parse`

B. `String.format`

C. `String.valueOf`

D. `Date.format`

154. A business currently has a process to manually upload orders from its external Order Management System (OMS) into Salesforce.

This is a labor intensive process since accounts must be exported out of Salesforce to get the IDs. The upload file must be updated with the correct account IDs to relate the orders to the corresponding accounts.

Which two recommendations should make this process more efficient?

A. Use the insert wizard in the Data Loader to import the data.

B. Ensure the data in the file is sorted by the order ID.

C. Use the upsert wizard in the Data Loader to import the data.

D. Identify unique fields on Order and Account and set them as External IDs.

155. There is an Apex controller and a Visualforce page in an org that displays records with a custom filter consisting of a combination of picklist values selected by the user.

The page takes too long to display results for some of the input combinations, while for other input choices it throws the exception, "Maximum view state size limit exceeded".

What step should the developer take to resolve this issue?

- A. Adjust any code that filters by picklist values since they are not indexed.
- B. Remove instances of the transient keyword from the Apex controller to avoid the view state error.
- C. Split the layout to filter records in one Visualforce page and display the list of records in a second page using the same Apex controller.

D. Use a StandardSetController or SOQL LIMIT in the Apex controller to limit the number of records displayed at a time.

156. What is the best practice to initialize a Visualforce page in a test class?

- A. Use ``controller.currentPage.setPage (MyTestPage);``
- B. Use ``Test.setCurrentPage.MyTestPage;``
- C. Use ``Test.setCurrentPage (Page.MyTestPage);``
- D. Use ``Test.currentPage.getParameters.put (MyTestPage);``

157. Which two queries are selective SOQL queries and can be used for a large data set of 200,000 Account records?

- A. ``SELECT Id FROM Account WHERE Id IN (List of Account Ids)``
- B. ``SELECT Id FROM Account WHERE Name IN (List of Names) AND Customer_Number__c = 'ValueA'``
- C. ``SELECT Id FROM Account WHERE Name != ''``
- D. ``SELECT Id FROM Account WHERE Name LIKE '%Partner'``

158. An org has a requirement that addresses on Contacts and Accounts should be normalized to a company standard by Apex code any time that they are saved.

What is the optimal way to implement this?

- A. Apex triggers on Contact and Account that normalize the address
- B. Apex trigger on Account that calls the Contact trigger to normalize the address
- C. Apex trigger on Contact that calls the Account trigger to normalize the address
- D. Apex triggers on Contact and Account that call a helper class to normalize the address

159. Refer to the test method below:

...

@isTest

static void testAccountUpdate() {

    Account acct = new Account(Name = 'Test');

    acct.Integration\_Updated\_\_c = false;

    insert acct;

    CalloutUtil.sendAccountUpdate(acct.Id);

    Account acctAfter = [SELECT Id, Integration\_Updated\_\_c FROM Account WHERE Id = :acct.Id][0];

    System.assert(true, acctAfter.Integration\_Updated\_\_c);

}

...

The test method calls a web service that updates an external system with Account information and sets the Account's Integration\_Updated\_\_c checkbox to True when it completes.

The test fails to execute and exits with an error: "Methods defined as TestMethod do not support Web service callouts."

What is the optimal way to fix this?

- A. Add ``if (!Test.isRunningTest())`` around ``CalloutUtil.sendAccountUpdate``.
- B. Add ``Test.startTest()`` before and ``Test.stopTest()`` after ``CalloutUtil.sendAccountUpdate``.
- C. Add ``Test.startTest()`` before and ``Test.setMock`` and ``Test.stopTest()`` after ``CalloutUtil.sendAccountUpdate``.
- D. Add ``Test.startTest()`` and ``Test.setMock`` before and ``Test.stopTest()`` after ``CalloutUtil.sendAccountUpdate``.-86

160. Choose 1 option.

Which code snippet represents the optimal Apex trigger logic for assigning a Lead's Region based on its PostalCode, using a custom ``Region__c`` object?

**\*\*Option A:\*\***

```
Set<String> zips = new Set<String>();
for(Lead l : Trigger.new) {
 if(l.PostalCode != Null) {
 zips.add(l.PostalCode);
 }
}
```

```
List<Region__c> regions = [SELECT Zip_Code__c, Region_Name__c FROM Region__c WHERE
Zip_Code__c IN :zips];
```

```
Map<String, String> zipMap = new Map<String, String>();
for(Region__c r : regions) {
 zipMap.put(r.Zip_Code__c, r.Region_Name__c);
}
```

```
for(Lead l : Trigger.new) {
 if(l.PostalCode != Null) {
 l.Region__c = zipMap.get(l.PostalCode);
 }
}
```

...

**\*\*Option B:\*\***

```
Set<String> zips = new Set<String>();
```

```
for(Lead l : Trigger.new) {
```

```
 if(l.PostalCode != Null) {
```

```
 zips.add(l.PostalCode);
```

```
 }
```

```
}
```

```
for (Lead l : Trigger.new) {
```

```
 List<Region__c> regions = [SELECT Zip_Code__c, Region_Name__c FROM Region__c WHERE
Zip_Code__c IN :zips];
```

```
 for (Region__c r : regions) {
```

```
 if(l.PostalCode == r.Zip_Code__c) {
```

```
 l.Region__c = r.Region_Name__c;
```

```
 }
```

```
 }
```

```
}
```

...

**\*\*Option C:\*\***

```
for (Lead l : Trigger.new) {
```

```
 Region__c reg = [SELECT Region_Name__c FROM Region__c WHERE Zip_Code__c = :l.PostalCode];
```

```
 l.Region__c = reg.Region_Name__c;
```

```
}
```

...

**\*\*Option D:\*\***

```
Set<String> zips = new Set<String>();
```

```

for(Lead l : Trigger.new) {
 if(l.PostalCode != Null) {
 zips.add(l.PostalCode);
 }
}

```

```

for(Lead l : Trigger.new) {
 List<Region__c> regions = [SELECT Zip_Code__c, Region_Name__c FROM Region__c WHERE
Zip_Code__c IN :zips];
 for(Region__c r : regions) {
 if(l.PostalCode == r.Zip_Code__c) {
 l.Region__c = r.Region_Name__c;
 }
 }
}

```

161. Choose 2 options.

A developer has business logic in a trigger that flags high-value opportunities. There is a new requirement to also display high value opportunities in a Lightning web component.

Which two steps should the developer take to meet these business requirements, and also prevent the business logic that identifies high-value opportunities from being repeated in more than one place?

- A. Call the trigger from the Lightning web component.
- B. Leave the business logic code inside the trigger for efficiency.
- C. Create a helper class that fetches the high value opportunities.
- D. Use custom metadata to hold the high value amount.

162. A company wants to allow support managers to see all cases in the org, regardless of who owns them. However, they want to support agents to only see cases they own or cases owned by someone in their role or a subordinate role.

Which sharing solution should a developer use to achieve this requirement?

- A. Sharing sets

- B. Apex managed sharing

- C. Role hierarchy

- D. Criteria-based sharing rules

Ravi-Hayatullah Team