The role of Projects of Common Interest in reaching Europe's energy policy targets

Bobby Xiong[a,*], Iegor Riepin[1], Tom Brown[1]

[a] *TU Berlin, Department of Digital Transformation in Energy Systems, Berlin, Germany*

Abstract

The European Union (EU) aims to achieve climate-neutrality by 2050, with ambitious 2030 target, such as 55 % greenhouse gas emissions reduction compared to 1990 levels, 10 Mt p.a. of a domestic green H_2 production, and 50 Mt p.a. of CO_2 injection capacity, which should be sequestered within the EU. The European Commission selects so-called Projects of Common Interest (PCI) and Projects of Mutual Interest (PMI)—a large infrastructure projects for electricity, hydrogen and CO_2 transport, and storage—that are of transnational importance as they link the energy systems of European countries. In this work, we evaluate the impact of PCI-PMI projects for the European energy system and EU energy policies. To achieve this, we investigate how delays in these projects could affect the EU's policy targets and examine potential conflicts between various policy objectives and the overarching greenhouse gas reduction goal. **Our preliminary results for 2030 indicate that policy targets can be met even without PCI-PMI projects; however, these projects offer additional benefits: (i) $\mathbf{H_2}$ pipelines enhance the affordability and distribution of green $\mathbf{H_2}$, thereby jumpstarting the hydrogen economy, and (ii) $\mathbf{CO_2}$ transport projects connect major industrial emissions to offshore sequestration sites in the North Sea. In our future work, we will analyse long-term pathway effects up to 2050, and incorporate hybrid interconnectors and $\mathbf{CO_2}$ shipping routes from the PCI-PMI list. Overall, our findings highlight the critical interplay between cross-border cooperation, infrastructure investments, and policy targets in the European energy transition across all sectors.**

Keywords: energy system modelling, energy policy, infrastructure, resilience, Europe, hydrogen, carbon

---

*Corresponding author: xiong@tu-berlin.de

List of abbreviations

API Application Programming Interface
EU European Union
GHG Greenhouse gas
PCI Projects of Common Interest
PMI Projects of Mutual Interest
REST Representational State Transfer

1. Introduction

On the pathway to a climate-neutral Europe by 2050, the European Union (EU) has set ambitious targets for 2030. These targets include a reduction of 55 % in greenhouse gas emissions compared to 1990 levels [1], 10 Mt p.a. domestic green H_2 production [2], and 50 Mt p.a. of CO_2 injection capacity with sequestration in within the EU [3].

To support reaching these targets, the European Commission bi-annually identifies a list of Projects of Common Interest (PCI), which are key cross-border infrastructure projects that link the energy systems of the EU members, including transmission and storage projects for electricity, hydrogen and CO_2 [4]. The pool of project sutable for PCI status is based on projects submitted by transmission system operators, consortia, or third parties. Projects of Mutual Interest (PMI) further include cooperations with countries outside the EU, such as Norway or the United Kingdom. With a PCI-PMI status, project awardees receive strong political support and are, amongst others, eligible for financial support (e.g. through funding of the Connecting Europe Facility) and see accelerated permitting processes. On the other hand, project promoters are obliged to undergo comprehensive reporting and monitoring processes. In order for projects to be eligible for PCI-PMI status, their *potential benefits need to outweigh their costs* [4]. Given the political and lighthouse character, these projects are highly likely to be implemented. However, any large infrastructure project, including PCI-PMI projects, commonly face delays due to permitting, financing, procurement bottlenecks, etc. [5].

1.1. Fuels, carriers, targets

test

1.2. Projects of Common/Mutual Interest

This paper aims to evaluate the impact of PCI-PMI projects on the European energy system and EU energy policies. We focus on the following key research questions:

1. What is the impact of delay in PCI-PMI projects' realisation on the EU's policy targets for 2030?
2. What are the costs associated with adhering to the EU policy targets, even if PCI-PMI projects are delayed?
3. Do the green hydrogen production and carbon sequestration targets conflict with the cost-effective achievement of the greenhouse gas emission reduction goals?

2. Literature review

3. Methodology

We use the open-source, sector-coupled energy system model PyPSA-Eur [6, 7, 8, 9] to optimise investment and dispatch decisions for generation, storage, transmission energy infrastructure, as well as conversion technologies in the European energy system.

A space of model endogenous decisions includes expansion of renewable energy sources and dispatchable power plants, electricity storage technologies, power-to-X conversion capacities, transmission infrastructure for power, hydrogen, and CO_2, heating technologies, as well as technology stacks for gray, blue or green hydrogen production, among others. The model also considers various energy carriers like electricity, heat, hydrogen, CO_2, methane, methanol, liquid hydrocarbons, and biomass, as well as a broad range of conversion technologies. The model is spatially and temporally highly resolved and covers the entire European continent, including stocks of existing power plants [10], renewable potentials, and availability time series [11]. It covers today's high-voltage transmission grid (AC 220 kV to 750 kV and DC 150 kV upwards) [12].

3.1. Feature implementation

By accessing the REST API of the PCI-PMI Transparency Platform [13] and associated public project sheets provided by the European Commission, we implement the PCI-PMI projects into the PyPSA-Eur model to assess their impact in the power, heat, transport, industry, feedstock, and agriculture sector. Note that we use standardised costs for all PCI-PMI projects [14] for two reasons: (i) Cost data provided by project promoters can be incomplete and may not include the same cost components, and (ii) to ensure comparability as well as level-playing field between all potential projects, including both PCI-PMI and model-endogenous investments. Our implementation can adapt to the needs and configuration of the model, including selected technologies, geographical and temporal resolution, as well as the level of sector-coupling. An overview of the implemented PCI-PMI projects is shown in Figure 1.

3.2. Scenario setup

As of the date of submission, we model three key scenarios for the target year 2030 which will set the base year for pathways towards 2050: a *Base* scenario in which policy targets are achieved and all projects are commissioned



Figure 1: Map of the regional scope including clustered onshore (grey) and offshore regions (blue), as well as PCI-PMI CO_2 and H_2 pipelines, storage and sequestration sites. Depleted offshore oil and gas fields (red) provide additional CO_2 sequestration potential. Own illustration based on [15] and data from the European Commission [13].

on time as well as two PCI-PMI delay scenarios *A* and *B*. Table 1 gives an overview of the scenarios' key assumptions and their differences. Depending on the scenario, we formulate and activate additional constraints to ensure the fulfilment of the EU policy targets.

Table 1: Scenario matrix setup. Own illustration.

Short-term	**Reduced targets**	**Delayed pipelines**	**No pipelines**
Long-term scenarios			
i. No pipelines	■	–	–
ii. PCI-PMI projects	■	■	■
iii. (ii.) + national expansion	■	■	■
iv. (iii.) + internat. expansion	■	■	■
v. Greenfield	■	■	■
Targets			
GHG emission reduction	■	■	■
CO_2 sequestration	–	■	■
Green H_2 production	–	■	■
H_2 electrolysers	–	■	■
CO_2 + H_2 infrastructure			
CO_2 sequestration sites	■	■	■
CO_2 pipelines to offs. seq. site	■	■	■
CO_2 onshore pipelines	■	□	–
H_2 pipelines	■	□	–
Model configuration			
Planning horizons	Myopic: [2030, 2040, 2050]		
Electricity grid	OSM, TYNDP, NEP, PCI-PMI		

■ active □ delayed by one period – inactive

Table 2: Pathway for implemented targets. Own illustration.

Planning horizon	**2030**	**2040**	**2050**
Targets			
GHG emission reduction	−55 %	−90 %	−100 %
CO_2 sequestration	50 Mtpa	150 Mtpa	250 Mtpa
Green H_2 production	10 Mtpa	27.5 Mtpa	45 Mtpa
H_2 electrolysers	40 GW	110 GW	180 GW

4. Results and discussion

Base scenario. Figure 2 shows the regional distribution of the H_2 and CO_2 value chain in the Base scenario. Note that for the specific year of 2030, a disconnect in H_2 infrastructure between central and southeastern Europe can be observed, due to the delay in commissioning of the project connecting the two networks. Within the two interconnected regions, almost homogenous average marginal prices for H_2 can be observed. Note that Figure 2a shows the cost of all H_2 produced, weighted by the respective regional demand at a certain point in time. CO_2 prices are higher in demand regions for industry processes and methanolisation located in northwestern Europe — primarily Norway and the United Kingdom (Figure 2b). Negative CO_2 prices in souhtheastern Europe indicate a lack of demand and missing economic value. Utilisation of H_2 pipelines vary strongly across the PCI-PMI projects. In most of the times, pipelines serve the purpose of transporting H_2 in a single direction only, i.e. from high renewable potential regions to H_2 consumption sites, where it serves as a precursor for methanolisation or direct use in industry and shipping (see Figure 2a). Prominent PCI-PMI projects with particularly high full-load hours include P9.9.2 *Hydrogen Interconnector Denmark-Germany* (6937 h) and P11.2 *Nordic-Baltic Hydrogen Corridor* (2295 h), followed by projects connecting major steel-industrial and chemical sites of Germany (southwest) with Belgium (P9.4 *H2ercules West*, 1634 h), the Netherlands (P9.6 *Netherlands National Hydrogen Backbone*, 1967 h and P9.7.3 *Delta Rhine Corridor H2*, 1510 h), and France (P9.2.2 *MosaHYc*, 4662 h). PCI project P13.8 *EU2NSEA* connects CO_2 from process emissions in Germany, Belgium and the Netherlands to major geological sequestration sinks close to the Norwegian shore *Smeaheia* and *Luna* with an annual injection potential of 20 Mt p.a. and 5Mt p.a., respectively.

Scenario A compared to Base. PCI-PMI infrastructure account for a total of around 30 bn. € p.a. in additional total system costs, indicating that for the target year 2030, the projects are not cost-optimal. With a delay of PCI-PMI projects in scenario *A*, Europe's policy targets can still be achieved at significantly lower cost. However, this comes at the expense of a less interconnected energy system, which may lead to higher costs in the long run. Further, H_2 prices vary more strongly across regions, seeing higher costs in southeastern Europe due to industrial demand and lower renewable potentials (Figure A.6a). We make similar observations for CO_2 — a lack of pipeline infrastruc-



(a) H_2 regional balances and flows (all H_2 produced).

(b) CO_2 regional balances and flows.

Figure 2: Results *Base* scenario — Regional distribution of H_2 and CO_2 production, utilisation, storage, and transport in the Base scenario. Own illustration.

ture increases spread of CO_2 prices, seeing higher values for CO_2 in regions with high demand (e.g. for industrial processes or methanolisation).

Scenario B compared to Base. By omitting a green H_2 target, almost no electrolysers are installed. Around 8 Mt are still produced to cover industrial H_2 and methanol (primarily shipping) demand (Figures A.4 and A.5). However, this demand is met by decentral steam methane reforming instead of electrolysers (Figure A.4). Without specifying a CO_2 sequestration target, the system still collects around 21 Mt of CO_2 p.a. primarily from process emissions in the industry sector and sequesters it in carbon sinks near industrial sites where a sequestration potential is identified (see Figure 1) [16]. This carbon sequestration is incentivised by the emission constraint for 2030. As no pipeline infrastructure is built in these scenarios, the chosen locations differ in the delay scenarios — this can be observed for regions near the coast, such as the United Kingdom and Norway (see Figure 1). Given the lack of infrastructure, both the average cost for H_2 and CO_2 are higher in scenario *B* compared to the Base scenario (Figures A.6c and A.6d.

Overall, the results for the modelling year 2030 show that reaching the

EU's 2030 H_2 production and CO_2 sequestration targets translates into around 20 bn. € p.a. in total system costs for all included sectors (Figure 3). This is true for both comparing scenario *A* and *Base* scenario with scenario *B*, respectively, deducting the cost of the PCI-PMI projects.

4.1. Limitations of our study

- Haversine distance for level playing field
- No discetisation of pipelines
- Regional resolution for computational reasons
- ...



Figure 3: Results — Total system costs by technology and infrastructure. Own illustration.

5. Conclusion

We conclude that although all three EU policy targets for 2030 can be achieved without PCI-PMI infrastructure, they bring additional benefits: i) H_2 pipelines projects help distribute more affordable green H_2 from northern and south-western Europe to high-demand regions in central Europe; ii) CO_2 transport and storage projects help decarbonising the industry by connecting major industrial sites and their process emissions to offshore sequestration sites in the North Sea (Denmark, Norway, and the Netherlands). Preliminary results have further shown that most PCI-PMI projects seem to be over-dimensioned and are not cost-optimal, as very few projects show utilisation above 1000 full-load hours. However, to adequately assess the value of PCI-PMI projects, we need to assess their benefits in future target years. Further, policy targets for 2030 are not cost-effective, although needed in the long run to reach net-zero emissions by 2050.

Research outlook. Next steps include the implementation of remaining PCI-PMI projects, such as hybrid offshore interconnectors (energy islands), electricity storages, and CO_2 shipping routes. To evaluate the long-term value of PCI-PMI projects in a sector-coupled European energy system, we will model pathway dependencies towards 2050. We will also assess the sensitivity of the infrastructure to technology-specific build-out rates.

CRediT authorship contribution statement

Bobby Xiong: Conceptualisation, Methodology, Software, Validation, Investigation, Data curation, Writing, Visualisation. **Iegor Riepin**: Conceptualisation, Methodology, Investigation, Writing, Supervision, Funding acquisition. **Tom Brown**: Investigation, Resources, Writing, Supervision, Funding acquisition.

Declaration of competing interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Data and code availability

The entire workflow, including the custom model based on PyPSA-Eur, PCI-PMI project implementation, scenario setup, postprocessing and visualisation routines can be accessed via the GitHub repository: https://github.com/bobbyxng/pcipmi-policy-targets

Acknowledgements

This work was supported by the German Federal Ministry for Economic Affairs and Climate Action (BMWK) under Grant No. 03EI4083A (RESILIENT). This project has been funded by partners of the CETPartnership (https://cetpartnership.eu) through the Joint Call 2022. As such, this project has received funding from the European Union's Horizon Europe research and innovation programme under grant agreement no. 101069750.

195 ## Appendix A. Additional material



Figure A.4: Results — H_2 balance. Own illustration.



Figure A.5: Results — CO_2 balance. Own illustration.



(a) H_2 regional balances and flows (Scenario A, all H_2 produced).



(b) CO_2 regional balances and flows (Scenario A).



(c) H_2 regional balances and flows (Scenario B, all H_2 produced).



(d) CO_2 regional balances and flows (Scenario B).

Figure A.6: Results scenarios *A* and *B* — Regional distribution of H_2 and CO_2 production, utilisation, storage, and transport. Own illustration.

References

[1] European Commission, 'Fit for 55': Delivering the EU's 2030 Climate Target on the way to climate neutrality. Communication from the Commission to the European Parliament, the Council, the European Economic and Social Committee and the Committee of the Regions, COM(2021) 550 final, Brussels. (2021).

[2] European Commission, REPowerEU Plan. Communication from the Commission to the European Parliament, the Council, the European Economic and Social Committee and the Committee of the Regions, COM(2022) 230 final, Brussels. (2022).

[3] E. Parliament, Council of the European Union, Regulation (EU) 2024/1735 of the European Parliament and of the Council of 13 June 2024 on establishing a framework of measures for strengthening Europe's net-zero technology manufacturing ecosystem and amending Regulation (EU) 2018/1724 (Text with EEA relevance) (Jun. 2024).

[4] European Commission, Commission Delegated Regulation (EU) 2024/1041 of 28 November 2023 amending Regulation (EU) 2022/869 of the European Parliament and of the Council as regards the Union list of projects of common interest and projects of mutual interest (Nov. 2023).

[5] ACER, Consolidated report on the progress of electricity and gas Projects of Common Interest in 2023, Tech. rep., European Union Agency for the Cooperation of Energy Regulators, Ljubljana (Jun. 2023).

[6] F. Neumann, E. Zeyen, M. Victoria, T. Brown, The potential role of a hydrogen network in Europe, Joule 7 (8) (2023) 1793–1817. `doi:10.1016/j.joule.2023.06.016`.

[7] M. M. Frysztacki, G. Recht, T. Brown, A comparison of clustering methods for the spatial reduction of renewable electricity optimisation models of Europe, Energy Informatics 5 (1) (2022) 4. `doi:10.1186/s42162-022-00187-7`.

[8] P. Glaum, F. Neumann, T. Brown, Offshore power and hydrogen networks for Europe's North Sea, Applied Energy 369 (2024) 123530. doi:10.1016/j.apenergy.2024.123530.

[9] J. Hörsch, F. Hofmann, D. Schlachtberger, T. Brown, PyPSA-Eur: An open optimisation model of the European transmission system, Energy Strategy Reviews 22 (2018) 207–215. doi:10.1016/j.esr.2018.08.012.

[10] F. Gotzens, H. Heinrichs, J. Hörsch, F. Hofmann, Performing energy modelling exercises in a transparent way - The issue of data quality in power plant databases, Energy Strategy Reviews 23 (2019) 1–12. doi:10.1016/j.esr.2018.11.004.

[11] F. Hofmann, J. Hampp, F. Neumann, T. Brown, J. Hörsch, Atlite: A Lightweight Python Package for Calculating Renewable Power Potentials and Time Series, Journal of Open Source Software 6 (62) (2021) 3294. doi:10.21105/joss.03294.

[12] B. Xiong, D. Fioriti, F. Neumann, I. Riepin, T. Brown, Modelling the High-Voltage Grid Using Open Data for Europe and Beyond, Preprint (Aug. 2024). arXiv:2408.17178, doi:10.48550/arXiv.2408.17178.

[13] European Commission, PCI-PMI transparency platform. Projects of Common Interest & Projects of Mutual Intereset - Interactive map, https://ec.europa.eu/energy/infrastructure/transparency_platform/map-viewer (2024).

[14] E. Zeyen, J. Hampp, F. Neumann, M. Millinger, M. Parzen, L. Franken, T. Brown, J. Geis, P. Glaum, M. Victoria, C. Schauss, K. van Greevenbroek, L. Trippe, T. Seibold, PyPSA/technology-data: V0.9.2 (Aug. 2024). doi:10.5281/zenodo.13617294.

[15] F. Hofmann, C. Tries, F. Neumann, E. Zeyen, T. Brown, H2 and CO2 network strategies for the European energy system, Nature Energy (2025) 1–10doi:10.1038/s41560-025-01752-6.

[16] F. Hofmann, C. Tries, F. Neumann, E. Zeyen, T. Brown, H2 and CO2 Network Strategies for the European Energy System (Feb. 2024). arXiv:2402.19042, doi:10.48550/arXiv.2402.19042.