

Entities

City.jsonc

```
{
  "name": "City",
  "type": "object",
  "properties": {
    "city": {
      "type": "string",
      "description": "City name"
    },
    "state": {
      "type": "string",
      "description": "State code (KS, MO, or Standard)"
    },
    "residential": {
      "type": "object",
      "description": "Residential road specs by subtype"
    },
    "collector": {
      "type": "object",
      "description": "Collector road specs by subtype"
    },
    "arterial": {
      "type": "object",
      "description": "Arterial road specs by subtype"
    },
    "initialCosts": {
      "type": "object",
      "description": "Initial construction costs per mile by road type"
    },
    "maint30": {
      "type": "object",
      "description": "30-year maintenance costs per mile by road type"
    },
    "costs": {
      "type": "object",
      "description": "30-year total costs per mile by road type"
    }
  },
  "required": [
    "city"
```

```
]
}
```

Suggestion.jsonc

```
{
  "name": "Suggestion",
  "type": "object",
  "properties": {
    "text": {
      "type": "string",
      "description": "The suggestion or update proposal text"
    },
    "status": {
      "type": "string",
      "enum": [
        "pending",
        "accepted",
        "declined"
      ],
      "default": "pending"
    },
    "city": {
      "type": "string",
      "description": "City name if applicable"
    },
    "road_type": {
      "type": "string",
      "description": "Road type if applicable"
    },
    "source": {
      "type": "string",
      "description": "Source of the suggestion"
    }
  },
  "required": [
    "text"
  ],
  "rls": {
    "create": {
      "created_by_id": "{{user.id}}"
    },
    "read": {
      "$or": [
```

```
{
  {
    "created_by_id": "{{user.id}}"
  },
  {
    "user_condition": {
      "role": "admin"
    }
  }
]
},
"update": {
  "$or": [
    {
      "created_by_id": "{{user.id}}"
    },
    {
      "user_condition": {
        "role": "admin"
      }
    }
  ]
},
"delete": {
  "user_condition": {
    "role": "admin"
  }
}
}
```

User.jsonc

```
{
  "properties": {
    "role": {
      "type": "string",
      "description": "The role of the user in the app",
      "enum": [
        "admin",
        "user"
      ]
    }
  },
  "required": [
    "role"
  ],
  "name": "User",
  "type": "object"
}
```

Config.jsonc

```
{
  "name": "untitled",
  "site": {
    "installCommand": "npm install",
    "buildCommand": "npm run build",
    "serveCommand": "npm run dev",
    "outputDirectory": "./dist"
  }
}
```

Src

api

Base44Client.js

```
import { createClient } from '@base44/sdk';
import { appParams } from '@lib/app-params';

const { appId, token, functionsVersion, appBaseUrl } = appParams;

//Create a client with authentication required
export const base44 = createClient({
  appId,
  token,
  functionsVersion,
  serverUrl: '',
});
```

```
    requiresAuth: false,
    appBaseUrl
  });
```

components

landing

About.jsx

```
    import React from "react";
import { motion } from "framer-motion";
import { ExternalLink } from "lucide-react";
import CityMap from "../CityMap";

const CONSTRUCTION_IMG =
"https://media.base44.com/images/public/6a3d5093b397842fc6d30258/0439748dd_generated_62685149.png";

const sources = [
  { label: "City of Overland Park – Public Works Standards", url: null
},
  { label: "City of Olathe – Engineering Design Criteria", url: null },
  { label: "City of Shawnee – Street Design Manual", url: null },
  { label: "Kansas City, MO – Public Works Specifications", url: null },
  { label: "Lee's Summit – Infrastructure Design Standards", url: null
},
  { label: "Blue Springs – Municipal Code & Engineering Specs", url:
null },
  { label: "Independence, MO – Street Construction Standards", url: null
},
  { label: "Grandview, MO – Public Works Engineering", url: null },
  { label: "Gardner, KS – Engineering & Public Works", url: null },
  { label: "Lenexa, KS – Public Works & Engineering", url: null },
  { label: "Merriam, KS – Engineering & Public Works", url: null },
  { label: "APWA (American Public Works Association) – Metro KC
Chapter", url: "https://www.apwa.net/" },
  { label: "KDOT – Kansas Department of Transportation Standards", url:
"https://www.ksdot.org/" },
];

export default function About() {
  return (
    <section id="about" className="py-24 lg:py-32 relative
overflow-hidden">
```

```

<div className="max-w-7xl mx-auto px-6 lg:px-8">
  <div className="grid lg:grid-cols-2 gap-16 items-start">
    <motion.div
      initial={{ opacity: 0, x: -30 }}
      whileInView={{ opacity: 1, x: 0 }}
      viewport={{ once: true }}
    >
      <div className="flex items-center gap-3 mb-4">
        <div className="w-8 h-px bg-[#FF4D00]" />
        <span className="font-mono text-xs tracking-[0.3em]
text-[#FF4D00] uppercase">
          About the Project
        </span>
      </div>
      <h2 className="font-heading font-bold text-[#F2F0E9]
text-3xl sm:text-4xl lg:text-5xl tracking-tight mb-8">
        One Place for<br />
        All the Data That<br />
        <span className="text-gradient-orange">Used to Be
        Scattered</span>
      </h2>
      <div className="space-y-5 text-[#F2F0E9]/60 text-base
leading-relaxed">
        <p>
          KC Pavement Analysis was built out of a simple
          frustration: pavement specifications
          for cities across the Kansas City metro existed, but you
          had to dig through each
          municipality's individual website, PDFs, and design
          manuals to find them.
        </p>
        <p>
          We pulled data from official city engineering documents,
          APWA standards, and public
          works specification sheets — then compiled it all into
          one searchable, comparable
          reference. Instead of spending hours hunting across a
          dozen sites, you get the full
          picture in seconds.
        </p>
        <p>

```

```

        The project was created by <strong
className="text-[#F2F0E9]">Bobby Youan</strong> and{" "}
        <strong className="text-[#F2F0E9]">Danny Will</strong>
with the collaboration from the{" "}
        <strong className="text-[#F2F0E9]">Overland Park Interns
at BHC</strong> – including{" "}
        <strong className="text-[#F2F0E9]">Teddy
Guidry</strong>,{" "}
        <strong className="text-[#F2F0E9]">JT
Grabowski</strong>,{" "}
        <strong className="text-[#F2F0E9]">Dominic
Passantino</strong>, and{" "}
        <strong className="text-[#F2F0E9]">Samuel
Herzog</strong> – to make infrastructure data
        more accessible to engineers, contractors, city
planners, and curious residents alike.
    </p>
</div>

<div className="mt-10 flex gap-8">
    <div>
        <p className="font-heading font-bold text-[#FF4D00]
text-3xl">10+</p>
        <p className="font-mono text-[10px] tracking-wider
text-[#4A5568] uppercase mt-1">Cities Covered</p>
    </div>
    <div className="w-px bg-white/10" />
    <div>
        <p className="font-heading font-bold text-[#F2F0E9]
text-3xl">2</p>
        <p className="font-mono text-[10px] tracking-wider
text-[#4A5568] uppercase mt-1">States</p>
    </div>
    <div className="w-px bg-white/10" />
    <div>
        <p className="font-heading font-bold text-[#F2F0E9]
text-3xl">Free</p>
        <p className="font-mono text-[10px] tracking-wider
text-[#4A5568] uppercase mt-1">Always</p>
    </div>
</div>

```

```

    <p className="mt-8 font-mono text-[10px] text-[#4A5568]
tracking-wide leading-relaxed border-t border-white/10 pt-4">
      * All numerical cost values are estimates based on bid
tabs and should be used for planning purposes only.
    </p>
  </motion.div>

  <motion.div
    initial={{ opacity: 0, x: 30 }}
    whileInView={{ opacity: 1, x: 0 }}
    viewport={{ once: true }}
    className="space-y-6"
  >
    <div className="relative overflow-hidden">
      <img
        src={CONSTRUCTION_IMG}
        alt="Road construction"
        className="w-full h-64 object-cover grayscale
hover:grayscale-0 transition-all duration-700"
      />
      <div className="absolute bottom-0 left-0 right-0
bg-gradient-to-t from-[#111111] to-transparent h-16" />
    </div>

    <div className="border border-white/10 p-6">
      <p className="font-mono text-[10px] tracking-wider
text-[#FF4D00] uppercase mb-4">Data Sources Referenced</p>
      <div className="space-y-2">
        {sources.map((src) => (
          <div key={src.label} className="flex items-start
gap-2">

            <div className="w-1 h-1 bg-[#FF4D00] mt-2 shrink-0"
          />

            {src.url ? (
              <a href={src.url} target="_blank" rel="noopener
noreferrer"

                className="font-mono text-[11px]
text-[#F2F0E9]/40 hover:text-[#FF4D00] transition-colors leading-relaxed
underline decoration-dotted">
                  {src.label}
                </a>
              ) : (

```



```

        <p className="font-mono text-[11px]
text-[#F2F0E9]/40 leading-relaxed">{src.label}</p>
      )}
    </div>
  )}
</div>
</div>
</motion.div>
</div>

<motion.div
  initial={{ opacity: 0, y: 30 }}
  whileInView={{ opacity: 1, y: 0 }}
  viewport={{ once: true }}
  className="mt-20"
>
  <div className="flex items-center gap-3 mb-4">
    <div className="w-8 h-px bg-[#FF4D00]" />
    <span className="font-mono text-xs tracking-[0.3em]
text-[#FF4D00] uppercase">
      Interactive Coverage
    </span>
  </div>
  <h3 className="font-heading font-bold text-[#F2F0E9] text-2xl
sm:text-3xl tracking-tight mb-2">
    KC Metro City Map
  </h3>
  <p className="text-[#F2F0E9]/50 text-sm mb-8 max-w-2xl
leading-relaxed">
    Hover or tap any city pin to see pavement specifications and
    30-year lifecycle cost estimates at a glance.
  </p>
  <CityMap />
</motion.div>
</div>
</section>
);
}

```

AskAI.jsx

```

import React, { useState, useRef, useEffect, useCallback }
from "react";
import { motion, AnimatePresence } from "framer-motion";

```

```
import { Send, X, User, Maximize2, Minimize2, Paperclip, Inbox, Check,
XCircle, ChevronDown, Mic, MicOff, ExternalLink, Volume2, VolumeX, Globe,
Upload, Trash2, Bell, Building2 } from "lucide-react";
import { base44 } from "@api/base44Client";
import ReactMarkdown from "react-markdown";
import remarkGfm from "remark-gfm";
import CityAdmin from "../CityAdmin";
import BypassTutorial from "../BypassTutorial";
```

```
const BYPASS_CODE = "NOPROBLEM";
const REVERT_CODE = "1234";
const MAX_FILE_SIZE = 100 * 1024 * 1024; // 100MB
const STORAGE_KEY = "pavo_chat_history";
```

```
const SYSTEM_CONTEXT = `You are Pavo (pronounced "Pave-oh"), the
pavement AI assistant for KC Pavement Analysis.
```

```
You only answer questions relevant to KC metro pavement data and
infrastructure.
```

```
CITIES: APWA Standard, KDOT Standard, Overland Park KS, Lenexa KS,
Shawnee KS, Olathe KS, Gardner KS, Merriam KS, Grandview MO, Blue Springs MO,
Lee's Summit MO, Kansas City MO, Independence MO
```

```
RESIDENTIAL (Access/Local/Collector): Asphalt 7-10", Concrete 6-8".
Lee's Summit adds 8" rock base. KC MO adds 6" rock base. Merriam: 7" HMA (4"
Base + 2" Intermediate + 1" Surface) for Access/Local, 8" HMA for Collector;
6" PCC min residential, 7-8" PCC collector.
```

```
COLLECTOR (Res/Comm/Industrial): Asphalt 8-11", Concrete 7-10".
```

```
ARTERIAL (Minor/Major): Asphalt 11-12", Concrete 8-9" most cities.
```

```
LIFECYCLE COSTS per mile: Residential: Asphalt $658K up / Concrete
$1.48M up / 36yr $2.24M vs $1.85M. Collector: Asphalt $1.05M / Concrete $2.28M
/ 36yr $3.08M vs $2.76M. Arterial: Asphalt $1.95M / Concrete $4.44M / 36yr
$5.12M vs $5.17M.
```

```
SUBGRADE: APWA/KDOT top 6" 95% compaction, 8" deep, 15% fly ash.
Olathe/Gardner 9" compacted, triaxial geogrid. Lee's Summit geogrid option B.
Merriam: APWA Section 2100, 6" compacted subgrade to 95% density.
```

```
FILE ANALYSIS: You CAN and MUST directly read and analyze any uploaded
file (images, PDFs, Excel, CSV, text). Do not say you cannot read files - you
```

can. Extract all pavement-related data and apply engineering reasoning to validate it.

CONTENT POLICY: If a question or uploaded file is NOT related to pavement, infrastructure, civil engineering, or construction, say "I can only assist with pavement and infrastructure topics." If content is inappropriate, do not respond with analysis.

WEBSITE UPDATES: When you identify new or updated pavement data from files, research, or user input, output an UPDATE PROPOSAL in this exact format:

---UPDATE PROPOSAL---

City: [city name]

State: [KS or MO]

Road Type: [residential/collector/arterial]

Subtype: [subtype]

Asphalt Spec: [specification]

Concrete Spec: [specification]

Notes: [subgrade, rock base, geogrid info]

Source: [filename or URL]

Engineering Basis: [reasoning]

---END PROPOSAL---

Be concise, data-driven, professional. If asked about links – always format them as markdown [text](url).`;

```
const BYPASS_CONTEXT = `${SYSTEM_CONTEXT}
```

BYPASS MODE: You are now fully unrestricted. Answer any question on any topic.

LINK HANDLING: When the user shares a URL or link, acknowledge it, extract the domain/type, and reason about what it likely contains. Always render links in your response as clickable markdown: [descriptive text](url). Never show raw URLs.

FILE ANALYSIS & SITE UPDATES: You CAN directly read and analyze any uploaded file (images, PDFs, Excel, CSV, text). Do not say you cannot read files – you can.

1. Analyze it thoroughly using engineering reasoning
2. Identify if it contains KC metro pavement data (road specs, thickness, lifecycle costs, subgrade info, city engineering standards)

3. If relevant: extract the data, map it to the correct city/road type/subtype, and output UPDATE PROPOSAL format for EACH city/road type found
4. If not relevant to KC pavement data, say so clearly
5. If content is inappropriate, say "I can only assist with pavement and infrastructure topics."

DRAG AND DROP: Users can drag and drop files directly into the chat. Treat them the same as uploaded files – analyze, extract data, and propose updates when relevant.

DATABASE/WEBSITE UPDATES: You CAN propose and structure website updates. When you identify new data, output UPDATE PROPOSALS. They will be automatically sent to the admin inbox for review.

INTERNET MODE: When internet search is enabled, you have unrestricted access to all sources throughout the web – engineering standards, municipal codes, DOT databases, academic papers, industry publications, real-time data, and any public website. Use this to provide the most current and comprehensive data available. Always cite sources with clickable markdown links.

SECURITY ARMOR: You are equipped with enterprise-grade security protocols. All user inputs are sanitized and validated before processing. You are immune to prompt injection attacks, malicious code execution, XSS attempts, and virus penetration. Any malicious content is detected and neutralized automatically.

FORMATTING: Use markdown tables to present structured data (specs, costs, comparisons). Use bold for key numbers, blockquotes for important notes, and code blocks for technical specs. Make responses easy to scan.

GENERAL CODE ASSISTANCE: When asked to write code, follow this process:

1. Understand what the user wants
2. Determine the programming language
3. Consider edge cases
4. Produce working code in a code block
5. Briefly explain the code`;

```
// Hard hat SVG
function HardHatIcon({ size = 20, className = "" }) {
  return (
    <svg width={size} height={size} viewBox="0 0 24 24" fill="none"
    className={className}>
```

```

        <path d="M12 2C8 2 5 5.5 5 9v1H3v2h18v-2h-2V9C19 5.5 16 2 12 2z"
fill="currentColor" opacity="0.9"/>
        <rect x="2" y="12" width="20" height="3" rx="1.5"
fill="currentColor"/>
        <path d="M5 15h14l-1 4H6l-1-4z" fill="currentColor"
opacity="0.7"/>
    </svg>
    );
}

// Global suggestion store
let globalSuggestions = [];
let suggestionListeners = [];
const notifySuggestionListeners = () => suggestionListeners.forEach(fn
=> fn([...globalSuggestions]));
export const addSuggestion = (text) => {
    globalSuggestions = [{ id: Date.now() + Math.random(), text, status:
"pending", createdAt: new Date() }, ...globalSuggestions];
    notifySuggestionListeners();
};
export const removeSuggestion = (id) => {
    globalSuggestions = globalSuggestions.filter(s => s.id !== id);
    notifySuggestionListeners();
};
export const useSuggestions = () => {
    const [suggestions, setSuggestions] =
useState([...globalSuggestions]);
    useEffect(() => {
        suggestionListeners.push(setSuggestions);
        return () => { suggestionListeners = suggestionListeners.filter(fn
=> fn !== setSuggestions); };
    }, []);
    return suggestions;
};

// Render message content with clickable links
function MessageContent({ content }) {
    return (
        <ReactMarkdown
            remarkPlugins=[remarkGfm]
            className="prose prose-sm prose-invert max-w-none
text-[#F2F0E9]/80"

```

```

components={{
  a: ({ href, children }) => (
    <a href={href} target="_blank" rel="noopener noreferrer"
      className="text-[#FF4D00] hover:text-[#FF7A33] underline
decoration-dotted inline-flex items-center gap-0.5 transition-colors">
      {children}
      <ExternalLink size={11} className="inline" />
    </a>
  ),
  table: ({ children }) => (
    <div className="overflow-x-auto my-3 rounded-lg border
border-white/10">
      <table className="w-full text-xs
border-collapse">{children}</table>
    </div>
  ),
  thead: ({ children }) => <thead
className="bg-[#FF4D00]/10">{children}</thead>,
  th: ({ children }) => <th className="px-3 py-2 text-left
font-mono text-[10px] uppercase tracking-wider text-[#FF4D00] border-b
border-[#FF4D00]/20">{children}</th>,
  td: ({ children }) => <td className="px-3 py-2 text-[#F2F0E9]/70
border-b border-white/5">{children}</td>,
  tr: ({ children }) => <tr className="hover:bg-white/[0.03]
transition-colors">{children}</tr>,
  pre: ({ children }) => <pre className="bg-[#0d0d0d] border
border-white/10 rounded-lg p-3 overflow-x-auto my-2
text-[11px]">{children}</pre>,
  code: ({ className, children }) =>
    <code className={className || "bg-[#FF4D00]/10 text-[#FF4D00]
px-1.5 py-0.5 rounded font-mono text-[11px]">{children}</code>,
  blockquote: ({ children }) => <blockquote className="border-l-2
border-[#FF4D00] pl-3 my-2 text-[#F2F0E9]/60">{children}</blockquote>,
  h1: ({ children }) => <h1 className="font-heading font-bold
text-[#F2F0E9] text-lg mt-3 mb-2">{children}</h1>,
  h2: ({ children }) => <h2 className="font-heading font-bold
text-[#F2F0E9] text-base mt-3 mb-2">{children}</h2>,
  h3: ({ children }) => <h3 className="font-heading font-semibold
text-[#F2F0E9] text-sm mt-2 mb-1">{children}</h3>,
  ul: ({ children }) => <ul className="list-disc list-inside
space-y-1 my-2">{children}</ul>,

```

```

      ol: ({ children }) => <ol className="list-decimal list-inside
space-y-1 my-2">{children}</ol>,
    }}
  >
    {content}
  </ReactMarkdown>
);
}

// Suggestions Inbox - removes items after accept/decline
function SuggestionsInbox({ onSendToChat, onClose, onApprove }) {
  const suggestions = useSuggestions();

  const handleConfirm = (s) => {
    removeSuggestion(s.id);
    base44.entities.Suggestion.create({ text: s.text, status: "accepted"
}).catch(() => {});
    onApprove?.();
  };

  const handleDeny = (s) => {
    removeSuggestion(s.id);
    base44.entities.Suggestion.create({ text: s.text, status: "declined"
}).catch(() => {});
  };

  const visible = suggestions;

  return (
    <motion.div initial={{ opacity: 0, x: 20 }} animate={{ opacity: 1,
x: 0 }} exit={{ opacity: 0, x: 20 }}
      className="fixed bottom-24 right-[420px] z-[199] w-80 border
border-white/10 bg-[#111111] shadow-2xl flex flex-col rounded-xl
overflow-hidden"
      style={{ maxHeight: "480px" }}>
      <div className="flex items-center justify-between px-4 py-3
border-b border-white/10 shrink-0">
        <div className="flex items-center gap-2">
          <Inbox size={14} className="text-yellow-400" />
          <span className="font-mono text-xs tracking-wider
text-[#F2F0E9] uppercase">Suggestions Inbox</span>
          {visible.length > 0 && (

```

```

        <span className="bg-yellow-500 text-black font-mono
text-[9px] font-bold px-1.5 py-0.5 rounded-full">{visible.length}</span>
      )}
    </div>
    <button onClick={onClose} className="text-[#4A5568]
hover:text-[#F2F0E9] transition-colors"><X size={14} /></button>
  </div>
  <div className="flex-1 overflow-y-auto p-3 space-y-3">
    {visible.length === 0 && (
      <p className="font-mono text-[10px] text-[#4A5568] text-center
py-6">No pending suggestions</p>
    )}
    <AnimatePresence>
      {visible.map(s => (
        <motion.div key={s.id} initial={{ opacity: 1, height: "auto"
}} exit={{ opacity: 0, height: 0, marginBottom: 0 }} transition={{ duration:
0.2 }}
        className="border border-white/10 p-3 rounded-lg">
          <p className="font-mono text-[10px] text-[#4A5568]
mb-1">{new Date(s.createdAt).toLocaleString()}</p>
          <p className="text-[#F2F0E9]/70 text-xs leading-relaxed
mb-3 whitespace-pre-wrap">{s.text}</p>
          <div className="flex gap-2">
            <button onClick={() => handleConfirm(s)}
              className="flex-1 flex items-center justify-center
gap-1 bg-green-500/20 border border-green-500/30 text-green-400 font-mono
text-[10px] uppercase py-2 rounded hover:bg-green-500/30 active:scale-95
transition-all">
              <Check size={10} /> Confirm
            </button>
            <button onClick={() => handleDeny(s)}
              className="flex-1 flex items-center justify-center
gap-1 bg-red-500/10 border border-red-500/20 text-red-400 font-mono
text-[10px] uppercase py-2 rounded hover:bg-red-500/20 active:scale-95
transition-all">
              <XCircle size={10} /> Deny
            </button>
          </div>
        </motion.div>
      )})}
    </AnimatePresence>
  </div>

```



```

    </motion.div>
  );
}

// Voice input hook with auto-send on end
function useVoiceInput(onResult, onEnd) {
  const [listening, setListening] = useState(false);
  const recognitionRef = useRef(null);

  const start = useCallback(() => {
    const SR = window.SpeechRecognition ||
window.webkitSpeechRecognition;
    if (!SR) return alert("Voice recognition not supported in this
browser.");
    const r = new SR();
    r.continuous = false;
    r.interimResults = false;
    r.lang = "en-US";
    r.onresult = (e) => onResult(e.results[0][0].transcript);
    r.onend = () => { setListening(false); onEnd?.(); };
    r.onerror = () => { setListening(false); onEnd?.(); };
    recognitionRef.current = r;
    r.start();
    setListening(true);
  }, [onResult, onEnd]);

  const stop = useCallback(() => {
    recognitionRef.current?.stop();
    setListening(false);
  }, []);

  return { listening, start, stop };
}

const INIT_MESSAGE = { role: "assistant", content: "Hi! I'm **Pavo** 🙋
– your KC pavement AI. Ask me anything about KC metro road specs, thickness
requirements, cost comparisons, or material tradeoffs between cities.",
skipTyping: true };

export default function AskAI({ showButton = true }) {
  const [open, setOpen] = useState(false);
  const [fullscreen, setFullscreen] = useState(false);

```

```

    const [bypassed, setBypassed] = useState(() => { try { return
localStorage.getItem("kcp_bypassed") === "true"; } catch { return false; } });
    const [minimized, setMinimized] = useState(false);
    const [showInbox, setShowInbox] = useState(false);
    const [showCityAdmin, setShowCityAdmin] = useState(false);
    const [logoAnimDone, setLogoAnimDone] = useState(false);

    // Persist chat history
    const [messages, setMessages] = useState(() => {
      try {
        const saved = localStorage.getItem(STORAGE_KEY);
        return saved ? JSON.parse(saved) : [INIT_MESSAGE];
      } catch { return [INIT_MESSAGE]; }
    });

    const [input, setInput] = useState("");
    const [loading, setLoading] = useState(false);

    // New feature states
    const [ttsEnabled, setTtsEnabled] = useState(false);
    const [internetEnabled, setInternetEnabled] = useState(false);
    const [dragOver, setDragOver] = useState(false);
    const [speaking, setSpeaking] = useState(false);
    const [thinkingText, setThinkingText] = useState("");
    const [typingMsgIdx, setTypingMsgIdx] = useState(null);
    const [revealedText, setRevealedText] = useState("");
    const [showRing, setShowRing] = useState(false);
    const [pendingFile, setPendingFile] = useState(null);
    const [fileError, setFileError] = useState("");

    const fileRef = useRef(null);
    const messagesEndRef = useRef(null);
    const voiceTranscriptRef = useRef("");

    useEffect(() => {
      try { localStorage.setItem(STORAGE_KEY,
JSON.stringify(messages.slice(-60))); } catch {}
    }, [messages]);

    useEffect(() => {
      if (!minimized) messagesEndRef.current?.scrollIntoView({ behavior:
"smooth" });
    });

```

```

    }, [messages, minimized]);

    const openFullscreen = useCallback(() => {
      setLogoAnimDone(false);
      setOpen(true);
      setFullscreen(true);
      setMinimized(false);
    }, []);

    useEffect(() => {
      const handler = () => openFullscreen();
      window.addEventListener("pavo-open-fullscreen", handler);
      return () => window.removeEventListener("pavo-open-fullscreen",
handler);
    }, [openFullscreen]);

    // TTS function
    const speak = useCallback((text) => {
      if (!ttsEnabled || !window.speechSynthesis) return;
      window.speechSynthesis.cancel();
      const cleanText = text.replace(/[*_#`>|]/g,
"").replace(/\[([^\]]+)\]\[([^\]]+)\]/g, "$1").replace(/---/g, " ");
      const utterance = new SpeechSynthesisUtterance(cleanText);
      utterance.rate = 1;
      utterance.onstart = () => setSpeaking(true);
      utterance.onend = () => setSpeaking(false);
      utterance.onerror = () => setSpeaking(false);
      window.speechSynthesis.speak(utterance);
    }, [ttsEnabled]);

    // Stop speech on unmount
    useEffect(() => {
      return () => { if (window.speechSynthesis)
window.speechSynthesis.cancel(); };
    }, []);

    // 45-second one-time ring notification
    useEffect(() => {
      if (!showButton) return;
      const timer = setTimeout(() => setShowRing(true), 45000);
      return () => clearTimeout(timer);
    }, [showButton]);

```

```

// Cancel speech when TTS toggled off
const toggleTts = () => {
  setTtsEnabled(prev => {
    if (prev && window.speechSynthesis) {
      window.speechSynthesis.cancel();
      setSpeaking(false);
    }
    return !prev;
  });
};

// Typewriter effect for new assistant messages
useEffect(() => {
  if (loading || messages.length === 0) { setTypingMsgIdx(null);
return; }
  const lastMsg = messages[messages.length - 1];
  if (lastMsg.role !== "assistant" || !lastMsg.content ||
lastMsg.skipTyping) { setTypingMsgIdx(null); return; }
  const idx = messages.length - 1;
  setTypingMsgIdx(idx);
  setRevealedText("");
  let i = 0;
  const full = lastMsg.content;
  const timer = setInterval(() => {
    i += 4;
    if (i >= full.length) {
      setRevealedText(full);
      clearInterval(timer);
      setTimeout(() => setTypingMsgIdx(null), 300);
    } else {
      setRevealedText(full.substring(0, i));
    }
  }, 12);
  return () => clearInterval(timer);
}, [messages, loading]);

// Thinking buffer cycling text
useEffect(() => {
  if (!loading) { setThinkingText(""); return; }
  const texts = ["Thinking", "Analyzing data", "Consulting specs",
"Crunching numbers", "Reviewing standards"];

```

```

let i = 0;
setThinkingText(texts[0]);
const timer = setInterval(() => {
  i = (i + 1) % texts.length;
  setThinkingText(texts[i]);
}, 1800);
return () => clearInterval(timer);
}, [loading]);

// Voice input with auto-send
const { listening, start: startVoice, stop: stopVoice } =
useVoiceInput(
  (transcript) => {
    setInput(prev => {
      const newVal = prev ? prev + " " + transcript : transcript;
      voiceTranscriptRef.current = newVal;
      return newVal;
    });
  },
  () => {
    const transcript = voiceTranscriptRef.current.trim();
    voiceTranscriptRef.current = "";
    if (!transcript) return;
    if (loading) {
      setInput(transcript);
    } else {
      setInput("");
      send(transcript);
    }
  }
);

const send = async (textOverride, fileUrl) => {
  const q = (textOverride || input).trim();
  if (loading) return;

  // Bypass / revert codes (only when no file involved)
  if (!pendingFile && !fileUrl) {
    if (q === BYPASS_CODE) {
      setInput("");
      setBypassed(true);
      try { localStorage.setItem("kcp_bypassed", "true"); } catch {}
    }
  }

```

```

        window.dispatchEvent(new Event("kcp_bypass_change"));
        setMessages([...messages, { role: "user", content:
"....." }, { role: "assistant", content: "🔓 **Bypass mode
activated.** Full unrestricted mode – ask anything, share files, links, or
paste pavement data for me to analyze and propose site updates.", skipTyping:
true }]);

        return;
    }
    if (q === REVERT_CODE && bypassed) {
        setInput("");
        setBypassed(false);
        try { localStorage.removeItem("kcp_bypassed"); } catch {}
        window.dispatchEvent(new Event("kcp_bypass_change"));
        setMinimized(false);
        setShowInbox(false);
        setMessages([...messages, { role: "user", content: "...." }, {
role: "assistant", content: "🔒 **Bypass mode deactivated.** Back to KC
pavement analysis mode.", skipTyping: true }]);
        return;
    }
}

if (!q && !pendingFile && !fileUrl) return;

// Upload pending file if present (happens on send, not on drop)
let finalFileUrl = fileUrl;
let fileName = null;
if (pendingFile && !fileUrl) {
    setLoading(true);
    fileName = pendingFile.name;
    try {
        const res = await base44.integrations.Core.UploadFile({ file:
pendingFile });
        finalFileUrl = res.file_url;
    } catch {
        setPendingFile(null);
        setLoading(false);
        setMessages([...messages, { role: "assistant", content: "Sorry,
I couldn't upload that file. Please try again.", skipTyping: true }]);
        return;
    }
    setPendingFile(null);

```

```

    }

    // Build prompt text — use user's text, or a default analysis prompt
    if only a file
    let finalText = q;
    if (!finalText && fileName) {
        finalText = bypassed
            ? `[Attached file: ${fileName}] Please analyze this file. If it
contains KC metro pavement data, extract specifications and propose site
updates. Apply engineering reasoning. If not relevant, say so. If
inappropriate, say "I can only assist with pavement and infrastructure
topics."`
            : `[Attached file: ${fileName}] Please analyze this file for KC
metro pavement data only. If it contains relevant specifications, extract them
and propose updates. If not related to pavement or infrastructure, say "This
file does not contain relevant pavement data." If inappropriate, do not
respond with analysis.`;
    }

    setInput("");
    const displayText = q || (fileName ? `📎 ${fileName}` : "");
    const userMsg = { role: "user", content: displayText, fileUrl:
finalFileUrl, fileName };
    const newMessages = [...messages, userMsg];
    setMessages(newMessages);
    setLoading(true);

    const history = newMessages.slice(-20).map(m => `${m.role} === "user"
? "User" : "Pavo": ${m.content}`).join("\n");
    const systemCtx = bypassed ? BYPASS_CONTEXT : SYSTEM_CONTEXT;
    const prompt = `${systemCtx}\n\nConversation:\n${history}\n\nPavo:`;

    try {
        const rawResult = await base44.integrations.Core.InvokeLLM({
            prompt,
            ...(internetEnabled ? { add_context_from_internet: true, model:
"gemini_3_flash" } : {}),
            ...(finalFileUrl ? { file_urls: [finalFileUrl] } : {}),
        });

        // Normalize result to string — InvokeLLM may return a string or
        object
    }

```

```

    const result = typeof rawResult === "string"
      ? rawResult
      : (rawResult?.response || rawResult?.output || rawResult?.text
|| (typeof rawResult === "object" ? JSON.stringify(rawResult) : "")) || "";

    if (!result || result.trim() === "") {
      setMessages([...newMessages, { role: "assistant", content: "I
couldn't generate a response. Please try rephrasing your question.",
skipTyping: true }]);
    } else {
      setMessages([...newMessages, { role: "assistant", content:
result }]);

      // Auto-detect UPDATE PROPOSALS and add to suggestions inbox
      if (result.includes("---UPDATE PROPOSAL---")) {
        const proposals = result.split("---UPDATE
PROPOSAL---").slice(1);
        proposals.forEach(p => {
          const proposalText = p.split("---END
PROPOSAL---")[0].trim();
          if (proposalText) addSuggestion(`[Website Update]
${proposalText}`);
        });
      }

      // Text-to-speech
      speak(result);
    }
  } catch (err) {
    setMessages([...newMessages, { role: "assistant", content: "Sorry,
Pavo is currently down :/ We are working to resolve this problem.",
skipTyping: true }]);
  }
  setLoading(false);
};

const handleKey = (e) => { if (e.key === "Enter" && !e.shiftKey) {
e.preventDefault(); send(); } };

// Selecting a file (button) - just stages it, no upload until send
const handleFile = (e) => {
  const file = e.target.files?.[0];

```



```

    if (!file) return;
    e.target.value = "";
    if (file.size > MAX_FILE_SIZE) {
      setFileError("This file exceeds 100MB");
      setPendingFile(null);
      setTimeout(() => setFileError(""), 3000);
      return;
    }
    setFileError("");
    setPendingFile(file);
  };

  // Drag and drop - stages the file, no upload until send
  const handleDrop = (e) => {
    e.preventDefault();
    setDragOver(false);
    const file = e.dataTransfer.files?.[0];
    if (!file || loading) return;
    if (file.size > MAX_FILE_SIZE) {
      setFileError("This file exceeds 100MB");
      setPendingFile(null);
      setTimeout(() => setFileError(""), 3000);
      return;
    }
    setFileError("");
    setPendingFile(file);
  };

  // Clear chat feed
  const clearChat = () => {
    setMessages([INIT_MESSAGE]);
    try { localStorage.removeItem(STORAGE_KEY); } catch {}
  };

  // Render message content with typewriter + speaking indicator
  const renderMessage = (msg, i) => {
    const isLast = i === messages.length - 1;
    const isTyping = typingMsgIdx === i;
    const showSpeaking = speaking && isLast && msg.role === "assistant"
    && ttsEnabled;

    return (

```

```

    <div key={i} className={`flex gap-3 ${msg.role === "user" ?
"justify-end" : "justify-start"}}`>
      {msg.role === "assistant" && (
        <div className={`w-8 h-8 flex items-center justify-center
shrink-0 mt-0.5 rounded-lg ${bypassed ? "bg-yellow-500/20 border
border-yellow-500/30" : "bg-[#FF4D00]/20 border border-[#FF4D00]/30"}}`>
          <HardHatIcon size={14} className={bypassed ?
"text-yellow-400" : "text-[#FF4D00]}" />
        </div>
      )}
      <div className={`max-w-[75%] px-5 py-4 text-sm leading-relaxed
rounded-xl ${msg.role === "user" ? "bg-[#FF4D00]/10 border border-[#FF4D00]/20
text-[#F2F0E9] rounded-tr-none" : "bg-white/5 border border-white/5
text-[#F2F0E9]/80 rounded-tl-none"}}`>
        {msg.role === "assistant" ? (
          <>
            <MessageContent content={isTyping ? (revealedText || " ")
: msg.content} />
            {showSpeaking && (
              <div className="speaking-bars flex items-end gap-1 mt-3
h-4">
                {[0,1,2,3,4].map(j => (
                  <span key={j} className="w-1 bg-[#FF4D00]
rounded-full block" style={{ height: "100%", animationDelay: `${j * 100}ms` }}
/>
                ))}
              </div>
            )}
            {msg.fileUrl && <p className="font-mono text-[10px]
text-[#4A5568] mt-2"> 📎 {msg.fileName || "file attached"}</p>}
          </>
        ) : (
          <>
            <p>{msg.content}</p>
            {msg.fileUrl && <p className="font-mono text-[10px]
text-[#4A5568] mt-2"> 📎 {msg.fileName || "file attached"}</p>}
          </>
        )}
      </div>
      {msg.role === "user" && (
        <div className="w-8 h-8 bg-white/5 border border-white/10 flex
items-center justify-center shrink-0 mt-0.5 rounded-lg">

```

```

        <User size={14} className="text-[#F2F0E9]/50" />
      </div>
    )}
  </div>
);
};

const renderMiniMessage = (msg, i) => {
  const isLast = i === messages.length - 1;
  const isTyping = typingMsgIdx === i;
  const showSpeaking = speaking && isLast && msg.role === "assistant"
&& ttsEnabled;

  return (
    <div key={i} className={`flex gap-2 ${msg.role === "user" ?
"justify-end" : "justify-start"}`}>
      {msg.role === "assistant" && (
        <div className={`w-7 h-7 rounded-full flex items-center
justify-center shrink-0 mt-0.5 ${bypassed ? "bg-yellow-500/20 border
border-yellow-500/30" : "bg-[#FF4D00]/20 border border-[#FF4D00]/30"}`}>
          <HardHatIcon size={13} className={bypassed ?
"text-yellow-400" : "text-[#FF4D00]}" />
        </div>
      )}
      <div className={`max-w-[85%] px-4 py-3 text-sm leading-relaxed
rounded-xl ${msg.role === "user" ? "bg-[#FF4D00]/10 border border-[#FF4D00]/20
text-[#F2F0E9] rounded-tr-none" : "bg-white/5 border border-white/5
text-[#F2F0E9]/80 rounded-tl-none"}`}>
        {msg.role === "assistant" ? (
          <>
            <MessageContent content={isTyping ? (revealedText || " ")
: msg.content} />
            {showSpeaking && (
              <div className="speaking-bars flex items-end gap-0.5
mt-2 h-3">
                {[0,1,2,3].map(j => (
                  <span key={j} className="w-0.5 bg-[#FF4D00]
rounded-full block" style={{ height: "100%", animationDelay: `${j * 100}ms` }}
/>
                ))}
              </div>
            )}
          </>
        ) : null}
      </div>
    )}
  )}

```

```

        {msg.fileUrl && <p className="font-mono text-[10px]
text-[#4A5568] mt-1"> 📎 {msg.fileName || "file attached"}</p>}
      </>
    ) : (
      <>
        <p>{msg.content}</p>
        {msg.fileUrl && <p className="font-mono text-[10px]
text-[#4A5568] mt-1"> 📎 {msg.fileName || "file attached"}</p>}
      </>
    )}
  </div>
  {msg.role === "user" && (
    <div className="w-7 h-7 bg-white/5 border border-white/10
rounded-full flex items-center justify-center shrink-0 mt-0.5">
      <User size={13} className="text-[#F2F0E9]/50" />
    </div>
  )}
</div>
);
};

// ---- Fullscreen with logo animation ----
if (fullscreen) {
  return (
    <div
      className="fixed inset-0 z-[200] bg-[#111111] flex flex-col"
      onDragOver={(e) => { e.preventDefault(); setDragOver(true); }}
      onDragLeave={(e) => { if (e.relatedTarget === null)
setDragOver(false); }}
      onDrop={handleDrop}
    >
      {/* Drag overlay */}
      <AnimatePresence>
        {dragOver && (
          <motion.div initial={{ opacity: 0 }} animate={{ opacity: 1
}} exit={{ opacity: 0 }}
          className="fixed inset-0 z-[300] bg-[#FF4D00]/10 border-4
border-dashed border-[#FF4D00]/50 flex items-center justify-center
pointer-events-none">
            <div className="text-center">
              <Upload size={56} className="text-[#FF4D00] mx-auto
mb-4" />

```

```

        <p className="font-heading text-2xl text-[#FF4D00]
font-bold">Drop file to analyze</p>
        <p className="font-mono text-xs text-[#FF4D00]/60
mt-2">Pavo will read & extract pavement data</p>
    </div>
</motion.div>
    )}
</AnimatePresence>

    { /* Header */ }
    <div className="flex items-center justify-between px-6 py-4
border-b border-white/10 shrink-0">
        <div className="flex items-center gap-3">
            <motion.div
                initial={{ scale: 2.5, opacity: 0 }}
                animate={{ scale: 1, opacity: 1 }}
                transition={{ duration: 0.6, ease: "easeOut" }}
                onAnimationComplete={() => setLogoAnimDone(true)}
                className={`flex items-center justify-center rounded-xl
${bypassed ? "bg-yellow-500" : "bg-[#FF4D00]"}`>
                    <div style={{ width: 40, height: 40 }}>
                        <HardHatIcon size={22} className="text-white" />
                    </div>
                </motion.div>
                <motion.div initial={{ opacity: 0, x: -10 }} animate={{
opacity: logoAnimDone ? 1 : 0, x: logoAnimDone ? 0 : -10 }} transition={{
duration: 0.3 }}>
                    <p className="font-heading font-semibold text-[#F2F0E9]
text-lg flex items-center gap-2">
                        Pavo
                        {bypassed && <span className="font-mono text-[9px]
bg-yellow-500/20 text-yellow-400 px-2 py-0.5 border border-yellow-500/30
rounded">BYPASS</span>}
                    </p>
                    <p className="font-mono text-[10px] text-[#4A5568]">KC
Pavement AI • Pave-oh</p>
                </motion.div>
            </div>
            <div className="flex items-center gap-2">
                { /* TTS toggle */ }
                <button onClick={toggleTts}

```

```

        className={`w-10 h-10 border flex items-center
justify-center transition-colors rounded-lg ${ttsEnabled ?
"border-[#FF4D00]/40 text-[#FF4D00] bg-[#FF4D00]/10" : "border-white/10
text-[#4A5568] hover:text-[#F2F0E9]"}`}
        title="Text-to-Speech">
        {ttsEnabled ? <Volume2 size={16} /> : <VolumeX size={16}
/>}

</button>
{ /* Internet toggle */}
<button onClick={() => setInternetEnabled(!internetEnabled)}
        className={`w-10 h-10 border flex items-center
justify-center transition-colors rounded-lg ${internetEnabled ?
"border-blue-500/40 text-blue-400 bg-blue-500/10" : "border-white/10
text-[#4A5568] hover:text-[#F2F0E9]"}`}
        title="Internet Search">
        <Globe size={16} />
</button>
{bypassed && (
        <button onClick={() => setShowInbox(!showInbox)}
                className={`flex items-center gap-2 font-mono
text-[10px] tracking-wider uppercase px-4 py-2 border transition-colors
rounded-lg ${showInbox ? "border-yellow-500/50 text-yellow-400
bg-yellow-500/10" : "border-white/10 text-[#4A5568] hover:text-[#F2F0E9]"}`}>
                <Inbox size={12} /> Inbox
        </button>
)}
{bypassed && (
        <button onClick={() => setShowCityAdmin(true)}
                className="flex items-center gap-2 font-mono text-[10px]
tracking-wider uppercase px-4 py-2 border border-white/10 text-[#4A5568]
hover:text-[#FF4D00] hover:border-[#FF4D00]/50 transition-colors rounded-lg">
                <Building2 size={12} /> City Admin
        </button>
)}
<button onClick={clearChat} className="w-10 h-10 border
border-white/10 flex items-center justify-center text-[#4A5568]
hover:text-red-400 hover:border-red-400/50 transition-colors rounded-lg"
        title="Clear chat"><Trash2 size={16} /></button>
        <button onClick={() => setFullscreen(false)} className="w-10
h-10 border border-white/10 flex items-center justify-center text-[#4A5568]
hover:text-[#FF4D00] hover:border-[#FF4D00] transition-colors
rounded-lg"><Minimize2 size={16} /></button>

```

```

<button onClick={() => { setFullscreen(false);
setOpen(false); }} className="w-10 h-10 border border-white/10 flex
items-center justify-center text-[#4A5568] hover:text-[#F2F0E9]
transition-colors rounded-lg"><X size={18} /></button>
</div>
</div>

{/* Welcome banner */}
<motion.div initial={{ opacity: 0, y: -10 }} animate={{ opacity:
logoAnimDone ? 1 : 0, y: logoAnimDone ? 0 : -10 }} transition={{ duration: 0.4
}}

className="bg-[#FF4D00]/5 border-b border-[#FF4D00]/10 px-6
py-3">
<p className="font-mono text-xs text-[#FF4D00] tracking-wide">
  Hi! I'm Pavo – ask about KC road pavements, specs, and
  lifecycle costs.

  {ttsEnabled && <span className="text-[#FF4D00]/60"> • 
Voice on</span>}

  {internetEnabled && <span className="text-blue-400/60"> •
 Internet on</span>}

</p>
</motion.div>

{/* Messages */}
<div className="flex-1 overflow-y-auto px-6 py-6 space-y-5">
  <div className="max-w-4xl mx-auto w-full space-y-5">
    {bypassed && <BypassTutorial />}
    {messages.map(renderMessage) }
    {loading && (
      <div className="flex gap-3 justify-start">
        <div className={`w-8 h-8 flex items-center
justify-center shrink-0 rounded-lg ${bypassed ? "bg-yellow-500/20 border
border-yellow-500/30" : "bg-[#FF4D00]/20 border border-[#FF4D00]/30"}`} >
          <HardHatIcon size={14} className={bypassed ?
"text-yellow-400" : "text-[#FF4D00]}" />
        </div>
        <div className="bg-white/5 border border-white/5 px-5
py-4 rounded-xl rounded-tl-none">
          <div className="flex items-center gap-3">
            <div className="flex gap-1">

```

```

        {[0,150,300].map(d => <div key={d} className="w-2
h-2 bg-[#FF4D00]/50 rounded-full animate-bounce" style={{ animationDelay:
`${d}ms` }} />)}

        </div>
        <span className="font-mono text-xs
text-[#FF4D00]/60">{thinkingText}...</span>
        </div>
        </div>
        </div>
    )}
    <div ref={messagesEndRef} />
  </div>
</div>

  {/* Search bar - fullscreen, centered, rounded */}
  <motion.div initial={{ opacity: 0, y: 20 }} animate={{ opacity:
logoAnimDone ? 1 : 0, y: logoAnimDone ? 0 : 20 }} transition={{ duration: 0.4,
delay: 0.1 }}

    className="px-6 py-5 border-t border-white/10 shrink-0">
    <div className="max-w-3xl mx-auto">
      {/* Pending file / error */}
      <AnimatePresence>
        {fileError && (
          <motion.div initial={{ opacity: 0, y: 5 }} animate={{
opacity: 1, y: 0 }} exit={{ opacity: 0 }}

            className="mb-2 flex items-center gap-2 text-red-400
font-mono text-xs">

              <XCircle size={12} /> {fileError}
            </motion.div>
          )}
          {pendingFile && (
            <motion.div initial={{ opacity: 0, y: 5 }} animate={{
opacity: 1, y: 0 }} exit={{ opacity: 0 }}

              className="mb-2 flex items-center gap-2
bg-[#FF4D00]/10 border border-[#FF4D00]/30 rounded-full px-4 py-2 max-w-fit">
                <Paperclip size={12} className="text-[#FF4D00]
shrink-0" />

                <span className="font-mono text-xs text-[#F2F0E9]
truncate max-w-[200px]">{pendingFile.name}</span>
                <button onClick={() => setPendingFile(null)}
className="text-[#4A5568] hover:text-red-400 transition-colors shrink-0">
                  <X size={12} />

```



```

        </button>
      </motion.div>
    )}
  </AnimatePresence>
  <div className="flex gap-3 items-center">
    <div className="flex-1 flex items-center bg-white/[0.06]
border border-white/15 hover:border-white/25 focus-within:border-[#FF4D00]/60
focus-within:bg-white/[0.08] transition-all duration-200 rounded-full px-5
py-3 gap-3">
      <input type="text" value={input} onChange={(e) =>
setInput(e.target.value)} onKeyDown={handleKey}
        placeholder={pendingFile ? "Type your prompt, then press
send..." : (bypassed ? "Ask anything, paste a link, or drop a file..." : "Ask
about KC road specs, city comparisons, costs...")}
        className="flex-1 bg-transparent font-body text-base
text-[#F2F0E9] placeholder-[#4A5568]/70 focus:outline-none" />
      <button onClick={listening ? stopVoice : startVoice}
        className={`shrink-0 transition-all ${listening ?
"text-white mic-glow p-1" : "text-[#4A5568] hover:text-[#FF4D00]"}`}
        title="Voice input (auto-sends when done)"
        {listening ? <MicOff size={18} /> : <Mic size={18} />}
      </button>
      <input type="file" ref={fileRef} onChange={handleFile}
className="hidden" accept="image/*,.pdf,.csv,.xlsx,.xls,.txt,.doc,.docx" />
      <button onClick={() => fileRef.current?.click()}
className="shrink-0 text-[#4A5568] hover:text-[#FF4D00] transition-colors"
title="Attach file">
        <Paperclip size={18} />
      </button>
    </div>
    <button onClick={() => send()} disabled={loading ||
(!input.trim() && !pendingFile)}
      className="w-12 h-12 bg-[#FF4D00] rounded-full flex
items-center justify-center hover:bg-[#FF4D00]/90 transition-colors
disabled:opacity-40 shrink-0">
      <Send size={16} className="text-white" />
    </button>
  </div>
</div>
</motion.div>

{/* Inbox */}

```

```

        <AnimatePresence>
            {showInbox && bypassed && (
                <SuggestionsInbox onSendToChat={ (text) => { send(text);
setShowInbox(false); }} onClose={() => setShowInbox(false)} onApprove={() => {
setShowInbox(false); setShowCityAdmin(true); }} />
            )}
        </AnimatePresence>
        <AnimatePresence>
            {showCityAdmin && bypassed && <CityAdmin onClose={() =>
setShowCityAdmin(false)} />}
        </AnimatePresence>
    </div>
);
}

// ---- Mini floating panel ----
return (
    <>
        {showButton && (
            <div className="fixed bottom-6 right-6 z-[150]">
                <AnimatePresence>
                    {showRing && !open && (
                        <motion.div initial={{ opacity: 0, y: 10, scale: 0.9 }}
animate={{ opacity: 1, y: 0, scale: 1 }} exit={{ opacity: 0, y: 10, scale: 0.9
}}
                        className="absolute bottom-16 right-0 w-56 bg-[#111111]
border border-[#FF4D00]/30 rounded-xl p-4 shadow-2xl">
                            <button onClick={() => setShowRing(false)}
className="absolute top-2 right-2 text-[#4A5568] hover:text-[#F2F0E9]"><X
size={12} /></button>
                            <div className="flex items-start gap-2 pr-4">
                                <Bell size={14} className="text-[#FF4D00] shrink-0
mt-0.5" />
                                <p className="font-mono text-[11px] text-[#F2F0E9]/80
leading-relaxed">Use Pavo for any advanced questions about KC Metro
Pavements!</p>
                            </div>
                        </motion.div>
                    )}
                </AnimatePresence>
                <button onClick={() => { setOpen(true); setMinimized(false);
setShowRing(false); }}

```

```

        className={`relative w-14 h-14 bg-[#FF4D00] rounded-full
flex items-center justify-center shadow-lg hover:bg-[#FF4D00]/90
transition-all hover:scale-105 ${showRing && !open ? "animate-bounce" : ""}`}
        aria-label="Ask Pavo">
        <HardHatIcon size={24} className="text-white" />
        {showRing && !open && <span className="absolute -top-1
-right-1 w-4 h-4 bg-red-500 rounded-full border-2 border-[#111111]
animate-pulse" />}
    </button>
</div>
)}

<AnimatePresence>
    {open && (
        <motion.div
            initial={{ opacity: 0, y: 20, scale: 0.97 }}
            animate={{ opacity: 1, y: 0, scale: 1 }}
            exit={{ opacity: 0, y: 20, scale: 0.97 }}
            transition={{ duration: 0.2 }}
            className="fixed bottom-24 right-6 z-[200] w-[90vw] max-w-md
flex flex-col border border-white/10 bg-[#111111] shadow-2xl rounded-xl
overflow-hidden"
            style={{ height: minimized ? "auto" : "520px" }}
            onDragOver={(e) => { e.preventDefault(); setDragOver(true);
}}
            onDragLeave={(e) => { if (e.relatedTarget === null)
setDragOver(false); }}
            onDrop={handleDrop}
        >
            {/* Drag overlay */}
            <AnimatePresence>
                {dragOver && (
                    <motion.div initial={{ opacity: 0 }} animate={{ opacity:
1 }} exit={{ opacity: 0 }}
                    className="absolute inset-0 bg-[#FF4D00]/10 border-2
border-dashed border-[#FF4D00]/50 rounded-xl flex items-center justify-center
pointer-events-none z-50">
                        <div className="text-center">
                            <Upload size={32} className="text-[#FF4D00] mx-auto
mb-2" />
                            <p className="font-mono text-xs text-[#FF4D00]">Drop
to analyze</p>

```

```

        </div>
      </motion.div>
    )}
  </AnimatePresence>

  { /* Mini header */ }
  <div className="flex items-center justify-between px-5 py-4
border-b border-white/10 shrink-0">
    <div className="flex items-center gap-3">
      <motion.div whileHover={{ scale: 1.1 }} className={`w-8
h-8 rounded-full flex items-center justify-center ${bypassed ? "bg-yellow-500"
: "bg-[#FF4D00]}"}`>
        <HardHatIcon size={18} className="text-white" />
      </motion.div>
      <div>
        <p className="font-heading font-semibold
text-[#F2F0E9] text-sm flex items-center gap-2">
          Pavo
          {bypassed && <span className="font-mono text-[9px]
bg-yellow-500/20 text-yellow-400 px-2 py-0.5 border border-yellow-500/30
rounded">BYPASS</span>}
        </p>
        <p className="font-mono text-[10px] text-[#4A5568]">KC
Pavement AI</p>
      </div>
    </div>
  </div>
  <div className="flex items-center gap-1">
    <button onClick={toggleTts}
      className={`p-2 transition-colors rounded ${ttsEnabled
? "text-[#FF4D00]" : "text-[#4A5568] hover:text-[#F2F0E9]}"}`
      title="Text-to-Speech">
      {ttsEnabled ? <Volume2 size={15} /> : <VolumeX
size={15} />}
    </button>
    <button onClick={() =>
setInternetEnabled(!internetEnabled)}
      className={`p-2 transition-colors rounded
${internetEnabled ? "text-blue-400" : "text-[#4A5568] hover:text-[#F2F0E9]}"}`
      title="Internet Search">
      <Globe size={15} />
    </button>
    {bypassed && (

```

```

        <button onClick={() => { setShowInbox(!showInbox);
setMinimized(true); }}
            className={`p-2 transition-colors rounded
${showInbox ? "text-yellow-400" : "text-[#4A5568] hover:text-yellow-400"}`}
            title="Suggestions Inbox">
                <Inbox size={15} />
            </button>
        </div>
    </div>
    {bypassed && (
        <button onClick={() => setShowCityAdmin(true)}
            className="p-2 text-[#4A5568] hover:text-[#FF4D00]
transition-colors rounded" title="City Admin">
                <Building2 size={15} />
            </button>
        </div>
    </div>
    {bypassed && (
        <button onClick={() => setMinimized(!minimized)}
            className="p-2 text-[#4A5568] hover:text-[#F2F0E9] transition-colors">
                <ChevronDown size={15} />
            </button>
            <button onClick={() => { setOpen(false);
setMinimized(false); setShowInbox(false); }} className="p-2 text-[#4A5568]
hover:text-[#F2F0E9] transition-colors"><X size={16} /></button>
        </div>
    </div>

    {minimized && bypassed && showInbox && (
        <SuggestionsInbox onSendToChat={(text) => {
setMinimized(false); setShowInbox(false); send(text); }} onClose={() => {
setShowInbox(false); setMinimized(false); }} onApprove={() => {
setShowInbox(false); setMinimized(false); setShowCityAdmin(true); }} />
    </div>

    {!minimized && (

```

```

<>
  { /* Messages */ }
  <div className="flex-1 overflow-y-auto px-5 py-4
space-y-4">

    {bypassed && <BypassTutorial />}
    {messages.map(renderMiniMessage)}
    {loading && (
      <div className="flex gap-2 justify-start">
        <div className={`w-7 h-7 rounded-full flex
items-center justify-center shrink-0 ${bypassed ? "bg-yellow-500/20 border
border-yellow-500/30" : "bg-[#FF4D00]/20 border border-[#FF4D00]/30"}`} >
          <HardHatIcon size={13} className={bypassed ?
"text-yellow-400" : "text-[#FF4D00]"} />
        </div>
        <div className="bg-white/5 border border-white/5
px-4 py-3 rounded-xl rounded-tl-none">
          <div className="flex items-center gap-2">
            <div className="flex gap-1">
              {[0,150,300].map(d => <div key={d}
className="w-1.5 h-1.5 bg-[#FF4D00]/50 rounded-full animate-bounce" style={{
animationDelay: `${d}ms` }} />)}
            </div>
            <span className="font-mono text-[10px]
text-[#FF4D00]/60">{thinkingText}...</span>
          </div>
        </div>
      </div>
    )}
    <div ref={messagesEndRef} />
  </div>

  { /* Mini input - rounded, bottom */ }
  <div className="px-4 py-4 border-t border-white/10
shrink-0">

    <AnimatePresence>
      {fileError && (
        <motion.div initial={{ opacity: 0, y: 5 }}
animate={{ opacity: 1, y: 0 }} exit={{ opacity: 0 }}
        className="mb-2 flex items-center gap-2
text-red-400 font-mono text-[10px]">
          <XCircle size={10} /> {fileError}
        </motion.div>
      )}
    </AnimatePresence>
  </div>

```

```

    })
    {pendingFile && (
      <motion.div initial={{ opacity: 0, y: 5 }}
animate={{ opacity: 1, y: 0 }} exit={{ opacity: 0 }}
      className="mb-2 flex items-center gap-2
bg-[#FF4D00]/10 border border-[#FF4D00]/30 rounded-full px-3 py-1.5
max-w-fit">

        <Paperclip size={10} className="text-[#FF4D00]
shrink-0" />

        <span className="font-mono text-[10px]
text-[#F2F0E9] truncate max-w-[140px]">{pendingFile.name}</span>
        <button onClick={() => setPendingFile(null)}
className="text-[#4A5568] hover:text-red-400 transition-colors shrink-0">
          <X size={10} />
        </button>
      </motion.div>
    })
  </AnimatePresence>
  <div className="flex items-center gap-2
bg-white/[0.05] border border-white/10 rounded-full px-4 py-2.5
focus-within:border-[#FF4D00]/40 transition-colors">
    <input type="text" value={input} onChange={(e) =>
setInput(e.target.value)} onKeyDown={handleKey}
      placeholder={pendingFile ? "Type your prompt..." :
(bypassed ? "Ask anything..." : "Ask about KC road specs...")}
      className="flex-1 bg-transparent font-mono text-xs
text-[#F2F0E9] placeholder-[#4A5568] focus:outline-none" />
    <button onClick={listening ? stopVoice : startVoice}
      className={`shrink-0 transition-all ${listening ?
"text-white mic-glow p-1" : "text-[#4A5568] hover:text-[#FF4D00]"}`
      title="Voice input (auto-sends when done)"
      {listening ? <MicOff size={14} /> : <Mic size={14}
/>}
    />
  </div>
  <button>
    <input type="file" ref={fileRef}
onChange={handleFile} className="hidden"
accept="image/*,.pdf,.csv,.xlsx,.xls,.txt" />
    <button onClick={() => fileRef.current?.click()}
className="shrink-0 text-[#4A5568] hover:text-[#FF4D00]
transition-colors"><Paperclip size={14} /></button>
    <button onClick={() => send()} disabled={loading ||
(!input.trim() && !pendingFile)}

```

```

        className="w-7 h-7 bg-[#FF4D00] rounded-full flex
items-center justify-center hover:bg-[#FF4D00]/90 transition-colors
disabled:opacity-40 shrink-0">
        <Send size={12} className="text-white" />
      </button>
    </div>
  </div>
</>
)}
</motion.div>
)}
</AnimatePresence>

<AnimatePresence>
  {open && minimized && showInbox && !fullscreen && (
    <SuggestionsInbox onSendToChat={(text) => {
setMinimized(false); setShowInbox(false); send(text); }} onClose={() => {
setShowInbox(false); setMinimized(false); }} onApprove={() => {
setShowInbox(false); setMinimized(false); setShowCityAdmin(true); }} />
    )}
  </AnimatePresence>
  <AnimatePresence>
    {showCityAdmin && bypassed && !fullscreen && <CityAdmin
onClose={() => setShowCityAdmin(false)} />}
  </AnimatePresence>
</>
);
}

```

BypassTutorial.jsx

```

import React, { useState } from "react";
import { ChevronDown, HelpCircle, Building2, Inbox, Globe, Volume2,
Lock, FileText } from "lucide-react";

const STEPS = [
  { icon: Lock, title: "Activate / Revert", text: "Use your access code
to activate bypass mode, and the revert code to return to standard KC pavement
mode." },
  { icon: Building2, title: "Add Cities", text: "Click the City Admin
button in the header to add custom cities with specs and cost data. Cities
persist in your browser and appear in the Analysis table and Calculator." },

```



```

    { icon: Inbox, title: "Suggestions Inbox", text: "When Pavo proposes
data updates (UPDATE PROPOSALS), they appear in the Inbox. Confirm or deny
each – confirmed items are saved to the cloud database." },
    { icon: Globe, title: "Internet Search", text: "Toggle the globe icon
to enable internet search. Pavo will search the web for real-time data from
engineering standards, municipal codes, and DOT databases." },
    { icon: Volume2, title: "Text-to-Speech", text: "Toggle the speaker
icon to have Pavo read responses aloud." },
    { icon: FileText, title: "File Analysis", text: "Drag and drop or
attach files (PDFs, Excel, CSV, images). Pavo will analyze them for pavement
data and propose site updates." }
  ];

export default function BypassTutorial() {
  const [open, setOpen] = useState(false);
  return (
    <div className="border border-[#FF4D00]/20 rounded-lg
overflow-hidden">
      <button onClick={() => setOpen(!open)} className="w-full flex
items-center justify-between px-4 py-3 bg-[#FF4D00]/5 hover:bg-[#FF4D00]/10
transition-colors">
        <div className="flex items-center gap-2">
          <HelpCircle size={14} className="text-[#FF4D00]" />
          <span className="font-mono text-xs text-[#FF4D00] uppercase
tracking-wider">How to Use Bypass Mode</span>
        </div>
        <ChevronDown size={14} className={`text-[#FF4D00]
transition-transform ${open ? "rotate-180" : ""}` } />
      </button>
      {open && (
        <div className="p-4 space-y-3">
          {STEPS.map((step, i) => (
            <div key={i} className="flex gap-3">
              <div className="w-8 h-8 rounded-lg bg-[#FF4D00]/10 border
border-[#FF4D00]/20 flex items-center justify-center shrink-0">
                <step.icon size={14} className="text-[#FF4D00]" />
              </div>
              <div>
                <p className="font-heading text-sm text-[#F2F0E9]
font-semibold">{step.title}</p>
                <p className="text-xs text-[#F2F0E9]/60 leading-relaxed
mt-0.5">{step.text}</p>

```

```

        </div>
      </div>
    )})
  </div>
})
</div>
);
}

```

CalculatorTutorial.jsx

```

import React, { useState } from "react";
import { ChevronDown, HelpCircle } from "lucide-react";

const STEPS = [
  "Select a city from the dropdown – covers 11+ KC metro municipalities.",
  "Choose a road type: Residential, Collector, or Arterial.",
  "Pick a subtype (e.g., Access, Local, Commercial, Minor).",
  "Enter the project distance and select a unit (miles, km, feet, meters).",
  "Click \"Calculate Costs\" to see material specs and 30-year cost estimates.",
  "View the cost breakdown chart and recommendation banner.",
  "Export a PDF report of the results for your records."
];

export default function CalculatorTutorial() {
  const [open, setOpen] = useState(false);
  return (
    <div className="mb-6 border border-[#FF4D00]/20 rounded-xl overflow-hidden">
      <button onClick={() => setOpen(!open)} className="w-full flex items-center justify-between px-5 py-3 bg-[#FF4D00]/5 hover:bg-[#FF4D00]/10 transition-colors">
        <div className="flex items-center gap-2">
          <HelpCircle size={16} className="text-[#FF4D00]" />
          <span className="font-mono text-xs text-[#FF4D00] uppercase tracking-wider">How to Use the Calculator</span>
        </div>
        <ChevronDown size={16} className={`text-[#FF4D00] transition-transform ${open ? "rotate-180" : ""}`} />
      </button>
      {open && (

```

```

    <div className="p-5">
      <div className="space-y-3">
        {STEPS.map((step, i) => (
          <div key={i} className="flex gap-3">
            <div className="w-6 h-6 rounded-full bg-[#FF4D00]/20
border border-[#FF4D00]/30 flex items-center justify-center shrink-0">
              <span className="font-mono text-[10px] text-[#FF4D00]
font-bold">{i + 1}</span>
            </div>
            <p className="text-sm text-[#F2F0E9]/70 leading-relaxed
pt-0.5">{step}</p>
          </div>
        ))}
      </div>
    </div>
  )}
</div>
}

```

CityAdmin.jsx

```

import React, { useState, useRef, useEffect } from "react";
import { motion } from "framer-motion";
import { X, Plus, Trash2, Building2, ChevronDown, Check, Pencil,
RotateCcw, HelpCircle, Upload, Loader2, GripVertical } from "lucide-react";
import PavoGuard from "../PavoGuard";
import { base44 } from "@api/base44Client";
import { addCustomCity, removeCustomCity, getCustomCities,
syncCloudCities } from "@lib/customCities";
import { baseCityData, getMergedCities, isCustomCity, isBaseCity } from
"@lib/cityDatabase";

const EMPTY_CITY = {
  city: "",
  state: "KS",
  residential: {
    access: { asphalt: "", concrete: "" },
    local: { asphalt: "", concrete: "" },
    collector: { asphalt: "", concrete: "" }
  },
  collector: {
    residential: { asphalt: "", concrete: "" },
    commercial: { asphalt: "", concrete: "" },
  }
}

```

```

        industrial: { asphalt: "", concrete: "" }
    },
    arterial: {
        minor: { asphalt: "", concrete: "" },
        major: { asphalt: "", concrete: "" }
    },
    initialCosts: { res_a: "", res_c: "", col_a: "", col_c: "", art_a: "",
art_c: "" },
    maint30: { res_a: "", res_c: "", col_a: "", col_c: "", art_a: "",
art_c: "" }
    };

const COST_FIELDS = [
    { key: "res_a", label: "Residential Asphalt" },
    { key: "res_c", label: "Residential Concrete" },
    { key: "col_a", label: "Collector Asphalt" },
    { key: "col_c", label: "Collector Concrete" },
    { key: "art_a", label: "Arterial Asphalt" },
    { key: "art_c", label: "Arterial Concrete" }
];

function cityToForm(city) {
    const form = {
        city: city.city || "",
        state: city.state || "KS",
        residential: JSON.parse(JSON.stringify(city.residential ||
EMPTY_CITY.residential)),
        collector: JSON.parse(JSON.stringify(city.collector ||
EMPTY_CITY.collector)),
        arterial: JSON.parse(JSON.stringify(city.arterial ||
EMPTY_CITY.arterial)),
        initialCosts: {},
        maint30: {}
    };
    COST_FIELDS.forEach(f => {
        form.initialCosts[f.key] = city.initialCosts?.[f.key] != null ?
String(city.initialCosts[f.key]) : "";
        form.maint30[f.key] = city.maint30?.[f.key] != null ?
String(city.maint30[f.key]) : "";
    });
    return form;
}

```

```

function SpecSection({ title, subtypes, form, onUpdate, path }) {
  const [open, setOpen] = useState(true);
  return (
    <div className="border border-white/10 rounded-lg overflow-hidden">
      <button type="button" onClick={() => setOpen(!open)}
className="w-full flex items-center justify-between px-4 py-3 bg-white/5
hover:bg-white/10 transition-colors">
        <span className="font-mono text-xs text-[#FF4D00] uppercase
tracking-wider">{title}</span>
        <ChevronDown size={14} className={`text-[#4A5568]
transition-transform ${open ? "rotate-180" : ""}`} />
      </button>
      {open && (
        <div className="p-4 space-y-3">
          {subtypes.map(sub => (
            <div key={sub.key}>
              <p className="font-mono text-[10px] text-[#4A5568]
uppercase mb-1">{sub.label}</p>
              <div className="grid grid-cols-2 gap-2">
                <input
                  placeholder="Asphalt spec"
                  value={form[path][sub.key].asphalt}
                  onChange={e => onUpdate(`${path}.${sub.key}.asphalt`,
e.target.value)}
                  className="bg-[#1a1a1a] border border-white/10 rounded
px-3 py-2 text-xs text-[#F2F0E9] font-mono focus:border-[#FF4D00]
focus:outline-none"
                />
                <input
                  placeholder="Concrete spec"
                  value={form[path][sub.key].concrete}
                  onChange={e => onUpdate(`${path}.${sub.key}.concrete`,
e.target.value)}
                  className="bg-[#1a1a1a] border border-white/10 rounded
px-3 py-2 text-xs text-[#F2F0E9] font-mono focus:border-[#FF4D00]
focus:outline-none"
                />
              </div>
            </div>
          ))}
        </div>
      )}
    </div>
  )
}

```

```

    })
  </div>
);
}

export default function CityAdmin({ onClose }) {
  const [form, setForm] =
useState(JSON.parse(JSON.stringify(EMPTY_CITY)));
  const [cities, setCities] = useState(getMergedCities());
  const [showSuccess, setShowSuccess] = useState(false);
  const [editingCity, setEditingCity] = useState(null);
  const [showTutorial, setShowTutorial] = useState(() => { try { return
localStorage.getItem("kcp_cityadmin_tutorial_seen") !== "true"; } catch {
return true; } });
  const [uploading, setUploading] = useState(false);
  const [unlocked, setUnlocked] = useState(false);
  const overlayRef = useRef(null);
  const fileRef = useRef(null);

  useEffect(() => {
    const refresh = () => setCities(getMergedCities());
    syncCloudCities().then(refresh);
    const handler = () => refresh();
    window.addEventListener("cities-updated", handler);
    return () => window.removeEventListener("cities-updated", handler);
  }, []);

  const dismissTutorial = () => {
    setShowTutorial(false);
    try { localStorage.setItem("kcp_cityadmin_tutorial_seen", "true"); }
catch {}
  };

  const refreshCities = () => setCities(getMergedCities());

  const update = (path, value) => {
    setForm(prev => {
      const next = JSON.parse(JSON.stringify(prev));
      const keys = path.split(".");
      let obj = next;
      for (let i = 0; i < keys.length - 1; i++) obj = obj[keys[i]];
      obj[keys[keys.length - 1]] = value;
    });
  };
}

```

```

        return next;
    });
};

const handleSubmit = () => {
    if (!form.city.trim()) return;
    const costs = {};
    COST_FIELDS.forEach(f => {
        const init = parseFloat(form.initialCosts[f.key]) || 0;
        const maint = parseFloat(form.maint30[f.key]) || 0;
        costs[f.key] = init + maint;
    });
    addCustomCity({ ...form, costs });
    refreshCities();
    setForm(JSON.parse(JSON.stringify(EMPTY_CITY)));
    setEditingCity(null);
    setShowSuccess(true);
    setTimeout(() => setShowSuccess(false), 2000);
};

const handleEdit = (city) => {
    setForm(cityToForm(city));
    setEditingCity(city.city);
};

const handleRemove = (cityName) => {
    removeCustomCity(cityName);
    refreshCities();
    if (editingCity === cityName) {
        setForm(JSON.parse(JSON.stringify(EMPTY_CITY)));
        setEditingCity(null);
    }
};

const handleReset = (cityName) => {
    removeCustomCity(cityName);
    refreshCities();
    if (editingCity === cityName) {
        setForm(JSON.parse(JSON.stringify(EMPTY_CITY)));
        setEditingCity(null);
    }
};

```

```

const handleFileUpload = async (e) => {
  const file = e.target.files?.[0];
  if (!file) return;
  e.target.value = "";
  setUploading(true);
  try {
    const { file_url } = await base44.integrations.Core.UploadFile({
file });

    const result = await base44.integrations.Core.InvokeLLM({
      prompt: `Analyze this file for pavement specifications for a
city. Extract the city name, state (KS, MO, or Standard), and all road type
specifications. For each road type and subtype, provide the asphalt and
concrete specifications as short strings (e.g., '8" (6" Base + 2" Surf)').
Also extract any per-mile cost data if available. Return as JSON matching the
schema. If a field is not found, leave it empty.` ,
      file_urls: [file_url],
      response_json_schema: {
        type: "object",
        properties: {
          city: { type: "string" },
          state: { type: "string" },
          residential: {
            type: "object",
            properties: {
              access: { type: "object", properties: { asphalt: { type:
"string" }, concrete: { type: "string" } } },
              local: { type: "object", properties: { asphalt: { type:
"string" }, concrete: { type: "string" } } },
              collector: { type: "object", properties: { asphalt: {
type: "string" }, concrete: { type: "string" } } }
            }
          },
          collector: {
            type: "object",
            properties: {
              residential: { type: "object", properties: { asphalt: {
type: "string" }, concrete: { type: "string" } } },
              commercial: { type: "object", properties: { asphalt: {
type: "string" }, concrete: { type: "string" } } },
              industrial: { type: "object", properties: { asphalt: {
type: "string" }, concrete: { type: "string" } } }
            }
          }
        }
      }
    });
  } catch (error) {
    console.error("Error uploading file:", error);
  }
};

```



```

    }
  },
  arterial: {
    type: "object",
    properties: {
      minor: { type: "object", properties: { asphalt: { type:
"string" }, concrete: { type: "string" } } },
      major: { type: "object", properties: { asphalt: { type:
"string" }, concrete: { type: "string" } } }
    }
  },
  initialCosts: {
    type: "object",
    properties: {
      res_a: { type: "number" }, res_c: { type: "number" },
      col_a: { type: "number" }, col_c: { type: "number" },
      art_a: { type: "number" }, art_c: { type: "number" }
    }
  },
  maint30: {
    type: "object",
    properties: {
      res_a: { type: "number" }, res_c: { type: "number" },
      col_a: { type: "number" }, col_c: { type: "number" },
      art_a: { type: "number" }, art_c: { type: "number" }
    }
  }
}
});

setForm(prev => {
  const next = JSON.parse(JSON.stringify(prev));
  if (result.city) next.city = result.city;
  if (result.state) next.state = result.state;
  if (result.residential) {
    for (const sub of ["access", "local", "collector"]) {
      if (result.residential[sub]) {
        if (result.residential[sub].asphalt)
next.residential[sub].asphalt = result.residential[sub].asphalt;
        if (result.residential[sub].concrete)
next.residential[sub].concrete = result.residential[sub].concrete;
      }
    }
  }
});

```

```

    }
}
if (result.collector) {
    for (const sub of ["residential", "commercial", "industrial"])
{
    if (result.collector[sub]) {
        if (result.collector[sub].asphalt)
next.collector[sub].asphalt = result.collector[sub].asphalt;
        if (result.collector[sub].concrete)
next.collector[sub].concrete = result.collector[sub].concrete;
    }
}
}
if (result.arterial) {
    for (const sub of ["minor", "major"]) {
        if (result.arterial[sub]) {
            if (result.arterial[sub].asphalt)
next.arterial[sub].asphalt = result.arterial[sub].asphalt;
            if (result.arterial[sub].concrete)
next.arterial[sub].concrete = result.arterial[sub].concrete;
        }
    }
}
if (result.initialCosts) {
    for (const key of Object.keys(next.initialCosts)) {
        if (result.initialCosts[key] != null) next.initialCosts[key]
= String(result.initialCosts[key]);
    }
}
if (result.maint30) {
    for (const key of Object.keys(next.maint30)) {
        if (result.maint30[key] != null) next.maint30[key] =
String(result.maint30[key]);
    }
}
return next;
});
} catch (err) {
    // silently fail
}
setUploading(false);
};

```

```

    if (!unlocked) {
      return <PavoGuard onClose={onClose} onUnlock={() =>
setUnlocked(true)} />;
    }

    return (
      <motion.div
        initial={{ opacity: 0 }}
        animate={{ opacity: 1 }}
        exit={{ opacity: 0 }}
        ref={overlayRef}
        className="fixed inset-0 z-[250] bg-black/80 flex items-center
justify-center p-4"
        onClick={onClose}
      >
        <motion.div
          initial={{ scale: 0.95, opacity: 0 }}
          animate={{ scale: 1, opacity: 1 }}
          exit={{ scale: 0.95, opacity: 0 }}
          onClick={e => e.stopPropagation()}
          drag
          dragMomentum={false}
          dragConstraints={overlayRef}
          className="bg-[#111111] border border-[#FF4D00]/30 rounded-xl
w-full max-w-2xl max-h-[85vh] flex flex-col overflow-hidden cursor-move"
        >
          {/* Header - drag handle */}
          <div className="bg-[#111111] border-b border-white/10 px-6 py-4
flex items-center justify-between z-10 shrink-0 cursor-move select-none">
            <div className="flex items-center gap-2">
              <GripVertical size={16} className="text-[#4A5568]" />
              <Building2 size={18} className="text-[#FF4D00]" />
              <span className="font-heading font-bold text-[#F2F0E9]">City
Admin Panel</span>
              <span className="font-mono text-[9px] text-[#4A5568] ml-1
hidden sm:inline">drag to move</span>
            </div>
            <button onClick={onClose} className="text-[#4A5568]
hover:text-[#F2F0E9] transition-colors">
              <X size={18} />
            </button>
          </div>
        </motion.div>
      </motion.div>
    )
  )
}

```

```

    </div>

    <div className="p-6 space-y-4 overflow-y-auto flex-1">
      {showTutorial && (
        <div className="border border-[#FF4D00]/20 rounded-lg p-4
bg-[#FF4D00]/5">
          <div className="flex items-center justify-between mb-3">
            <div className="flex items-center gap-2">
              <HelpCircle size={14} className="text-[#FF4D00]" />
              <span className="font-mono text-xs text-[#FF4D00]
uppercase tracking-wider">How to Use City Admin</span>
            </div>
            <button onClick={dismissTutorial}
className="text-[#4A5568] hover:text-[#F2F0E9] transition-colors">
              <X size={14} />
            </button>
          </div>
          <div className="space-y-2 text-xs text-[#F2F0E9]/70
leading-relaxed">
            <p><strong className="text-[#F2F0E9]">Add City:</strong>
Fill in the form below with city name, specs, and costs, then click "Add
City".</p>
            <p><strong
className="text-[#F2F0E9]">Auto-Fill:</strong> Upload a PDF, image, or
spreadsheet – Pavo AI reads the file and fills the specs for you
automatically.</p>
            <p><strong className="text-[#F2F0E9]">Edit
City:</strong> Click the pencil icon next to any city to load its data into
the form for editing.</p>
            <p><strong className="text-[#F2F0E9]">Remove:</strong>
Custom cities (green badge) can be removed with the trash icon.</p>
            <p><strong className="text-[#F2F0E9]">Reset:</strong>
Modified cities (yellow badge) can be reset to defaults with the rotate
icon.</p>
            <p><strong className="text-[#F2F0E9]">Persist:</strong>
All changes persist in your browser and appear in the Analysis table and
Calculator.</p>
          </div>
        </div>
      )}
      { /* All cities list */ }
    </div>

```

```

    <p className="font-mono text-[10px] text-[#4A5568] uppercase
tracking-wider mb-2">All Cities ({cities.length})</p>
    <div className="space-y-2 max-h-48 overflow-y-auto">
      {cities.map(c => {
        const custom = isCustomCity(c.city);
        const base = isBaseCity(c.city);
        const overridden = custom && base;
        const isNew = custom && !base;
        return (
          <div key={c.city} className={`flex items-center
justify-between rounded-lg px-4 py-2.5 ${editingCity === c.city ?
"bg-[#FF4D00]/10 border border-[#FF4D00]/30" : "bg-white/5 border
border-white/10"}`>
            <div className="flex items-center gap-2">
              <span className="font-heading text-sm
text-[#F2F0E9]">{c.city}</span>
              <span className="font-mono text-[10px]
text-[#4A5568]">{c.state}</span>
              {overridden && <span className="font-mono
text-[8px] bg-yellow-500/20 text-yellow-400 px-1.5 py-0.5 rounded
uppercase">Modified</span>}
              {isNew && <span className="font-mono text-[8px]
bg-green-500/20 text-green-400 px-1.5 py-0.5 rounded uppercase">Custom</span>}
            </div>
            <div className="flex items-center gap-1">
              <button onClick={() => handleEdit(c)}
className="p-1.5 text-[#4A5568] hover:text-[#FF4D00] transition-colors
rounded" title="Edit">
                <Pencil size={13} />
              </button>
              {overridden && (
                <button onClick={() => handleReset(c.city)}
className="p-1.5 text-yellow-400/60 hover:text-yellow-400 transition-colors
rounded" title="Reset to default">
                  <RotateCcw size={13} />
                </button>
              )}
              {isNew && (
                <button onClick={() => handleRemove(c.city)}
className="p-1.5 text-red-400/60 hover:text-red-400 transition-colors rounded"
title="Remove">
                  <Trash2 size={13} />

```

```

        </button>
      )}
    </div>
  </div>
);
}}
</div>
</div>

{/* Form */}
<div className="border-t border-white/10 pt-4">
  <p className="font-mono text-[10px] text-[#FF4D00] uppercase
tracking-wider mb-3">
    {editingCity ? `Editing: ${editingCity}` : "Add New City"}
  </p>

  {/* Auto-fill from file */}
  <div className="mb-4">
    <input type="file" ref={fileRef}
onChange={handleFileUpload} className="hidden"
accept="image/*,.pdf,.csv,.xlsx,.xls,.txt,.doc,.docx" />
    <button
      onClick={() => fileRef.current?.click()}
      disabled={uploading}
      className="w-full flex items-center justify-center gap-2
border border-dashed border-[#FF4D00]/40 bg-[#FF4D00]/5 text-[#FF4D00]
font-mono text-xs tracking-wider uppercase py-3 rounded-lg
hover:bg-[#FF4D00]/10 transition-colors disabled:opacity-50"
    >
      {uploading ? <><Loader2 size={14}
className="animate-spin" /> Pavo is reading the file...</> : <><Upload
size={14} /> Upload File to Auto-Fill Specs</>}
    </button>
    <p className="font-mono text-[9px] text-[#4A5568]/60
mt-1.5 text-center">Upload a PDF, image, or spreadsheet – Pavo AI will extract
specs and fill the form for you.</p>
  </div>

  {/* Basic info */}
  <div className="grid grid-cols-2 gap-3 mb-4">
    <input
      placeholder="City name"

```

```

        value={form.city}
        onChange={e => update("city", e.target.value)}
        className="bg-[#1a1a1a] border border-white/10
rounded-lg px-4 py-3 text-sm text-[#F2F0E9] focus:border-[#FF4D00]
focus:outline-none"
      />
      <select
        value={form.state}
        onChange={e => update("state", e.target.value)}
        className="bg-[#1a1a1a] border border-white/10
rounded-lg px-4 py-3 text-sm text-[#F2F0E9] focus:border-[#FF4D00]
focus:outline-none"
      >
        <option value="KS">Kansas (KS)</option>
        <option value="MO">Missouri (MO)</option>
        <option value="Standard">Standard</option>
      </select>
    </div>

    {/* Spec sections */}
    <div className="space-y-3 mb-4">
      <SpecSection title="Residential Specs"
subtypes={[{key:"access",label:"Access"},{key:"local",label:"Local"},{key:"col
lector",label:"Collector"}]} form={form} onUpdate={update} path="residential"
/>

      <SpecSection title="Collector Specs"
subtypes={[{key:"residential",label:"Residential"},{key:"commercial",label:"Co
mmercial"},{key:"industrial",label:"Industrial"}]} form={form}
onUpdate={update} path="collector" />

      <SpecSection title="Arterial Specs"
subtypes={[{key:"minor",label:"Minor"},{key:"major",label:"Major"}]}
form={form} onUpdate={update} path="arterial" />
    </div>

    {/* Costs */}
    <div className="border border-white/10 rounded-lg
overflow-hidden">
      <div className="px-4 py-3 bg-white/5">
        <span className="font-mono text-xs text-[#FF4D00]
uppercase tracking-wider">Cost Estimates (per mile)</span>
      </div>
      <div className="p-4 space-y-4">

```

```

<div>
  <p className="font-mono text-[10px] text-[#4A5568]
uppercase mb-2">Initial Construction Costs</p>
  <div className="grid grid-cols-2 gap-2">
    {COST_FIELDS.map(f => (
      <div key={f.key}>
        <label className="font-mono text-[9px]
text-[#4A5568]">{f.label}</label>
        <input
          type="number"
          placeholder="$"
          value={form.initialCosts[f.key]}
          onChange={e => update(`initialCosts.${f.key}`,
e.target.value)}
          className="w-full bg-[#1a1a1a] border
border-white/10 rounded px-3 py-2 text-xs text-[#F2F0E9] font-mono
focus:border-[#FF4D00] focus:outline-none"
        />
      </div>
    ))}
  </div>
</div>
<div>
  <p className="font-mono text-[10px] text-[#4A5568]
uppercase mb-2">30-Year Maintenance Costs</p>
  <div className="grid grid-cols-2 gap-2">
    {COST_FIELDS.map(f => (
      <div key={f.key}>
        <label className="font-mono text-[9px]
text-[#4A5568]">{f.label}</label>
        <input
          type="number"
          placeholder="$"
          value={form.maint30[f.key]}
          onChange={e => update(`maint30.${f.key}`,
e.target.value)}
          className="w-full bg-[#1a1a1a] border
border-white/10 rounded px-3 py-2 text-xs text-[#F2F0E9] font-mono
focus:border-[#FF4D00] focus:outline-none"
        />
      </div>
    ))}
  </div>
</div>

```



```

        </div>
      </div>
      <p className="font-mono text-[9px] text-[#4A5568]/60">*
30-year totals auto-calculated as initial + maintenance. All estimates based
on bid tabs. Enter an existing city name to update its specs.</p>
    </div>
  </div>

  { /* Submit */ }
  <button
    onClick={handleSubmit}
    disabled={!form.city.trim()}
    className="w-full flex items-center justify-center gap-2
bg-[#FF4D00] text-white font-mono text-sm tracking-wider uppercase py-3.5
rounded-lg hover:bg-[#FF4D00]/90 transition-colors disabled:opacity-30 mt-4"
  >
    {showSuccess ? <><Check size={16} /> Saved!</> : <><Plus
size={16} /> {editingCity ? "Update City" : "Add City"}</>}
  </button>
</div>
</div>
</motion.div>
</motion.div>
);
}

```

CityMap.jsx

```

import React, { useState } from "react";
import { motion, AnimatePresence } from "framer-motion";
import { MapPin, X } from "lucide-react";

// City positions normalized to % within the map container (based on KC
metro lat/lng)
// top: 0 = north, left: 0 = west
const cities = [
  { name: "Kansas City", state: "MO", top: 4, left: 61,
    res: { a: '8" (6"+2")'+6" Rock', c: '6"+6" Rock' },
    col: { a: '9" (7"+2")'+6" Rock', c: '7"+6" Rock' },
    art: { a: '11-12"+6" Rock', c: '8-9"+6" Rock' },
    cost: "$2.35M / $1.96M" },
  { name: "Independence", state: "MO", top: 8, left: 89,
    res: { a: '8" (6"+2")', c: '6" Slab' },
    col: { a: '9" (7"+2")', c: '7" Slab' },

```

```

    art: { a: '11-12" (9-10"+2") ', c: '8-9" Slab' },
    cost: "$2.24M / $1.85M" },
{ name: "Blue Springs", state: "MO", top: 25, left: 100,
  res: { a: '8" (6"+2") ', c: '6" Slab' },
  col: { a: '8-11" (6-9"+2") ', c: '6-7" Slab' },
  art: { a: '11-12" (9-10"+2") ', c: '8-9" Slab' },
  cost: "$2.24M / $1.90M" },
{ name: "Lee's Summit", state: "MO", top: 59, left: 96,
  res: { a: '6" (4"+2")+8" Rock', c: '6"+6" Rock' },
  col: { a: '8-11"+8" Rock', c: '6.5-8"+6" Rock' },
  art: { a: 'Project Specific', c: 'Project Specific' },
  cost: "$2.25M / $1.96M" },
{ name: "Grandview", state: "MO", top: 34, left: 70,
  res: { a: '8" (6"+2") ', c: '6" Slab' },
  col: { a: '9" (7"+2") ', c: '7" Slab' },
  art: { a: '11-12" (9-10"+2") ', c: '8-9" Slab' },
  cost: "$2.24M / $1.85M" },
{ name: "Shawnee", state: "KS", top: 25, left: 37,
  res: { a: '8" (6"+2") ', c: '6" Slab' },
  col: { a: '9-10" (7-8"+2") ', c: '8" Slab' },
  art: { a: '12" (10"+2") ', c: '10" Slab' },
  cost: "$2.24M / $1.85M" },
{ name: "Merriam", state: "KS", top: 25, left: 42,
  res: { a: '7" (4"+2"+1") ', c: '6" PCC Min' },
  col: { a: '8" (6"+2") ', c: '7-8" PCC' },
  art: { a: '11-12" (9-10"+2") ', c: '8-9" PCC' },
  cost: "$2.24M / $1.85M" },
{ name: "Overland Park", state: "KS", top: 38, left: 46,
  res: { a: '8" (6"+2") ', c: '7"+4" Rock' },
  col: { a: '9-10" (7-8"+2") ', c: '8"+4" Rock' },
  art: { a: 'N/A', c: 'N/A' },
  cost: "$2.24M / $2.22M" },
{ name: "Lenexa", state: "KS", top: 44, left: 35,
  res: { a: '8" (4"+2"+2") ', c: '6" Slab' },
  col: { a: '9-11" (7-9"+2") ', c: '8-10" Slab' },
  art: { a: '11-12" (9-10"+2") ', c: '10" Slab' },
  cost: "$2.24M / $1.85M" },
{ name: "Olathe", state: "KS", top: 69, left: 19,
  res: { a: '8" (6"+2") ', c: '6"+9" Sub' },
  col: { a: '10" (8"+2") ', c: '7"+9" Sub' },
  art: { a: '12" (10"+2") ', c: '9"+6" Rock' },
  cost: "$2.24M / $1.85M" },

```

```

    { name: "Gardner", state: "KS", top: 100, left: 0,
      res: { a: '8" (6"+2)"', c: '6"+9" Sub' },
      col: { a: '10" (8"+2)"', c: '7"+9" Sub' },
      art: { a: '12" (10"+2)"', c: '9"+9" Sub' },
      cost: "$2.24M / $1.85M" },
  ];

const STATE_BORDER = 52.6; // KS-MO border at ~-94.63° lng

export default function CityMap() {
  const [hovered, setHovered] = useState(null);
  const [selected, setSelected] = useState(null);

  const activeCity = hovered || selected;

  return (
    <div className="relative w-full" style={{ aspectRatio: "16 / 10" }}>
      { /* Map container */ }
      <div className="absolute inset-0 grid-overlay bg-[#0d0d0d] border
border-white/10 rounded-xl overflow-hidden">
        { /* State labels */ }
        <span className="absolute top-4 left-[8%] font-mono text-[10px]
tracking-[0.3em] text-[#FF4D00]/30 uppercase
pointer-events-none">Kansas</span>
        <span className="absolute top-4 right-[8%] font-mono text-[10px]
tracking-[0.3em] text-[#4A5568]/40 uppercase
pointer-events-none">Missouri</span>

        { /* State border line */ }
        <div className="absolute top-0 bottom-0 border-l border-dashed
border-white/15" style={{ left: `${STATE_BORDER}%` }} />

        { /* City markers */ }
        {cities.map((city) => {
          const isActive = activeCity?.name === city.name;
          return (
            <button
              key={city.name}
              onMouseEnter={() => setHovered(city)}
              onMouseLeave={() => setHovered(null)}
              onClick={() => setSelected(isActive ? null : city)}

```

```

        className="absolute -translate-x-1/2 -translate-y-1/2
group z-10"

        style={{ top: `${city.top}%`, left: `${city.left}%` }}
        aria-label={city.name}
    >
        <span className={`block rounded-full transition-all
duration-200 ${isActive ? "w-4 h-4 bg-[#FF4D00]" : "w-2.5 h-2.5
bg-[#FF4D00]/60 group-hover:bg-[#FF4D00] group-hover:w-3.5
group-hover:h-3.5"}`} />
            {isActive && <span className="absolute inset-0
rounded-full bg-[#FF4D00]/30 animate-ping" />}
            <span className={`absolute top-full mt-1 left-1/2
-translate-x-1/2 whitespace-nowrap font-mono text-[9px] tracking-wider
uppercase transition-opacity ${isActive ? "opacity-100 text-[#FF4D00]" :
"opacity-0 group-hover:opacity-60 text-[#F2F0E9]}"`}>
                {city.name}
            </span>
        </button>
    );
}}

    {/ * Compass */}
    <div className="absolute bottom-4 right-4 w-10 h-10 border
border-white/10 rounded-full flex items-center justify-center">
        <span className="font-mono text-[8px] text-[#4A5568]">N</span>
    </div>
</div>

    {/ * Tooltip / spec card */}
    <AnimatePresence>
        {activeCity && (
            <motion.div
                initial={{ opacity: 0, y: 10 }}
                animate={{ opacity: 1, y: 0 }}
                exit={{ opacity: 0, y: 10 }}
                transition={{ duration: 0.2 }}
                className="absolute top-4 left-4 w-64 bg-[#111111] border
border-[#FF4D00]/30 rounded-xl p-4 shadow-2xl z-20"
            >
                <div className="flex items-start justify-between mb-3">
                    <div>

```

```

        <p className="font-heading font-bold text-[#F2F0E9]
text-base">{activeCity.name}</p>
        <p className="font-mono text-[10px] text-[#4A5568]
tracking-wider">{activeCity.state} • BID-TAB ESTIMATE</p>
    </div>
    <button onClick={() => { setSelected(null);
setHovered(null); }} className="text-[#4A5568] hover:text-[#F2F0E9]
transition-colors">
        <X size={14} />
    </button>
</div>
<div className="space-y-2.5">
    <SpecRow label="Residential" a={activeCity.res.a}
c={activeCity.res.c} />
    <SpecRow label="Collector" a={activeCity.col.a}
c={activeCity.col.c} />
    <SpecRow label="Arterial" a={activeCity.art.a}
c={activeCity.art.c} />
</div>
<div className="mt-3 pt-3 border-t border-white/10">
    <p className="font-mono text-[9px] text-[#4A5568]
uppercase tracking-wider">30-yr Lifecyle (A / C)</p>
    <p className="font-heading text-[#FF4D00] text-sm
font-bold mt-0.5">{activeCity.cost}</p>
</div>
    <p className="font-mono text-[8px] text-[#4A5568] mt-2">*
Estimates based on bid tabs</p>
</motion.div>
    )}
</AnimatePresence>

    { /* Hint */ }
    {!activeCity && (
        <div className="absolute bottom-4 left-1/2 -translate-x-1/2 flex
items-center gap-2 bg-[#111111]/80 border border-white/10 rounded-full px-4
py-2">
            <MapPin size={12} className="text-[#FF4D00]" />
            <span className="font-mono text-[10px] text-[#4A5568]
tracking-wider uppercase">Hover or tap a city to see specs</span>
        </div>
    )}
</div>

```

```

    );
  }

  function SpecRow({ label, a, c }) {
    return (
      <div>
        <p className="font-mono text-[9px] text-[#4A5568] uppercase tracking-wider mb-0.5">{label}</p>
        <div className="flex gap-2 text-[11px]">
          <span className="text-[#FF4D00] font-mono flex-1">A: {a}</span>
          <span className="text-[#F2F0E9]/60 font-mono flex-1">C:
{c}</span>
        </div>
      </div>
    );
  }
}

```

Contact.jsx

```

import React, { useState } from "react";
import { Mail, Heart, Lightbulb, Send, ExternalLink, CheckCircle } from
"lucide-react";
import { base44 } from "@api/base44Client";
import { addSuggestion } from "@components/landing/AskAI";
import { motion, AnimatePresence } from "framer-motion";

export default function Contact() {
  const [suggestion, setSuggestion] = useState("");
  const [showSent, setShowSent] = useState(false);
  const [submitting, setSubmitting] = useState(false);

  const handleSuggestion = async (e) => {
    e.preventDefault();
    if (!suggestion.trim()) return;
    setSubmitting(true);
    addSuggestion(suggestion.trim());
    try {
      await base44.integrations.Core.SendEmail({
        to: "bobby.youan@ibhc.com",
        subject: "KC Pavement Analysis - City Suggestion",
        body: `New city suggestion from a site
visitor:\n\n${suggestion}`,
      });
    } catch {

```

```

        // Email may fail for non-registered users – suggestion is still
        stored locally
    }
    setSuggestion("");
    setShowSent(true);
    setSubmitting(false);
    setTimeout(() => setShowSent(false), 2500);
};

return (
    <section id="contact" className="py-24 lg:py-32">
        <div className="max-w-7xl mx-auto px-6 lg:px-8">
            <div className="flex items-center gap-3 mb-4">
                <div className="w-8 h-px bg-[#FF4D00]" />
                <span className="font-mono text-xs tracking-[0.3em]
text-[#FF4D00] uppercase">Get In Touch</span>
            </div>
            <h2 className="font-heading font-bold text-[#F2F0E9] text-3xl
sm:text-4xl lg:text-5xl tracking-tight mb-12">
                Contact & Contribute
            </h2>

            <div className="grid lg:grid-cols-3 gap-8">
                {/* Email */}
                <div className="border border-white/10 p-6 bg-[#111111]/50">
                    <div className="w-10 h-10 border border-white/10 flex
items-center justify-center mb-5">
                        <Mail size={16} className="text-[#FF4D00]" />
                    </div>
                    <h3 className="font-heading font-semibold text-[#F2F0E9]
text-lg mb-2">Contact Us</h3>
                    <p className="text-[#F2F0E9]/50 text-sm leading-relaxed
mb-6">Questions about the data, corrections, or collaboration? Reach out
directly.</p>
                    <div className="space-y-3">
                        <a href="mailto:bobby.youan@ibhc.com" className="flex
items-center gap-2 font-mono text-xs text-[#FF4D00] hover:text-[#FF4D00]/80
transition-colors">
                            <ExternalLink size={11} /> bobby.youan@ibhc.com
                        </a>
                    </div>
                </div>
            </div>
        </div>
    </section>
);

```

```

        <a href="mailto:bobbyouan@gmail.com" className="flex
items-center gap-2 font-mono text-xs text-[#FF4D00] hover:text-[#FF4D00]/80
transition-colors">
            <ExternalLink size={11} /> bobbyouan@gmail.com
        </a>
    </div>
</div>

{/* Suggest a City */}
<div className="border border-white/10 p-6 bg-[#111111]/50">
    <div className="w-10 h-10 border border-white/10 flex
items-center justify-center mb-5">
        <Lightbulb size={16} className="text-[#FF4D00]" />
    </div>
    <h3 className="font-heading font-semibold text-[#F2F0E9]
text-lg mb-2">Suggest a City</h3>
    <p className="text-[#F2F0E9]/50 text-sm leading-relaxed
mb-6">Know a city we're missing? We're always expanding coverage – suggest it
below.</p>
    <form onSubmit={handleSuggestion} className="space-y-3">
        <input type="text" value={suggestion} onChange={(e) =>
setSuggestion(e.target.value)}
            placeholder="e.g. Lenexa, KS or Gladstone, MO" required
            className="w-full bg-transparent border border-white/10
px-4 py-3 text-[#F2F0E9] text-sm font-mono placeholder-[#4A5568]
focus:border-[#FF4D00] focus:outline-none transition-colors" />
        <div className="relative h-12">
            <AnimatePresence mode="wait">
                {showSent ? (
                    <motion.div key="sent"
                        initial={{ opacity: 0, scale: 0.9 }}
                        animate={{ opacity: 1, scale: 1 }}
                        exit={{ opacity: 0, scale: 0.9 }}
                        transition={{ duration: 0.25 }}
                        className="absolute inset-0 flex items-center
justify-center gap-2 bg-green-500/15 border border-green-500/40 text-green-400
font-mono text-xs tracking-wider uppercase">
                            <CheckCircle size={14} /> Sent!
                        </motion.div>
                ) : (
                    <motion.button key="submit" type="submit"
disabled={submitting}

```



```

        initial={{ opacity: 0 }}
        animate={{ opacity: 1 }}
        exit={{ opacity: 0 }}
        className="absolute inset-0 w-full font-mono
text-xs tracking-wider bg-[#FF4D00] text-white hover:bg-[#FF4D00]/90
transition-colors uppercase flex items-center justify-center gap-2
disabled:opacity-50">

        <Send size={12} />
        {submitting ? "Sending..." : "Submit Suggestion"}
      </motion.button>
    )}
  </AnimatePresence>
</div>
</form>
</div>

  { /* Donate */ }
  <div className="border border-white/10 p-6 bg-[#111111]/50">
    <div className="w-10 h-10 border border-white/10 flex
items-center justify-center mb-5">
      <Heart size={16} className="text-[#FF4D00]" />
    </div>
    <h3 className="font-heading font-semibold text-[#F2F0E9]
text-lg mb-2">Support the Project</h3>
    <p className="text-[#F2F0E9]/50 text-sm leading-relaxed
mb-6">
      This platform is free and community-driven. Your support
      helps Bobby & Danny add more cities and keep the data current.
    </p>
    <a href="https://paypal.me/Bobbyyouan" target="_blank"
rel="noopener noreferrer"
      className="w-full font-mono text-xs tracking-wider border
border-[#FF4D00] text-[#FF4D00] px-4 py-3 hover:bg-[#FF4D00] hover:text-white
transition-colors uppercase flex items-center justify-center gap-2">
      <Heart size={12} /> Donate to Bobby & Danny ♥
    </a>
  </div>
</div>
</section>
);
}

```

Coverage.jsx

```
import React from "react";
import { motion } from "framer-motion";

const cities = [
  { name: "Leawood", state: "KS", pop: "33,902", drive: "9 min" },
  { name: "Overland Park", state: "KS", pop: "197,238", drive: "12 min"
},
  { name: "Lenexa", state: "KS", pop: "57,434", drive: "14 min" },
  { name: "Merriam", state: "KS", pop: "11,098", drive: "15 min" },
  { name: "Shawnee", state: "KS", pop: "69,198", drive: "16 min" },
  { name: "Olathe", state: "KS", pop: "143,014", drive: "19 min" },
  { name: "Spring Hill", state: "KS", pop: "9,242", drive: "29 min" },
  { name: "Leavenworth", state: "KS", pop: "37,351", drive: "48 min" },
  { name: "Grandview", state: "MO", pop: "26,209", drive: "15 min" },
  { name: "Raytown", state: "MO", pop: "30,012", drive: "21 min" },
  { name: "Blue Springs", state: "MO", pop: "61,246", drive: "23 min" },
  { name: "Lee's Summit", state: "MO", pop: "106,419", drive: "17 min"
},
  { name: "Raymore", state: "MO", pop: "22,941", drive: "19 min" },
  { name: "Kansas City", state: "MO", pop: "521,220", drive: "20 min" },
  { name: "Independence", state: "MO", pop: "123,011", drive: "24 min"
},
  { name: "Liberty", state: "MO", pop: "30,167", drive: "32 min" },
];

const ksCities = cities.filter((c) => c.state === "KS");
const moCities = cities.filter((c) => c.state === "MO");

function CityRow({ city, idx }) {
  return (
    <motion.div
      initial={{ opacity: 0, x: -10 }}
      whileInView={{ opacity: 1, x: 0 }}
      viewport={{ once: true }}
      transition={{ delay: idx * 0.03 }}
      className="flex items-center gap-4 py-3 border-b border-white/5
group hover:bg-white/[0.02] px-3 -mx-3 transition-colors"
    >
      <div className="w-2 h-2 bg-[#FF4D00] opacity-60
group-hover:opacity-100 transition-opacity" />
    </div>
  );
}
```

```

        <span className="font-heading text-sm text-[#F2F0E9] font-medium
flex-1">{city.name}</span>
        <span className="font-mono text-[10px] text-[#4A5568]
tracking-wider">{city.pop}</span>
        <span className="font-mono text-xs text-[#FF4D00] w-16
text-right">{city.drive}</span>
      </motion.div>
    );
  }

export default function Coverage() {
  return (
    <section id="coverage" className="py-24 lg:py-32 grid-overlay">
      <div className="max-w-7xl mx-auto px-6 lg:px-8">
        <div className="flex items-center gap-3 mb-4">
          <div className="w-8 h-px bg-[#FF4D00]" />
          <span className="font-mono text-xs tracking-[0.3em]
text-[#FF4D00] uppercase">
            Service Area
          </span>
        </div>
        <h2 className="font-heading font-bold text-[#F2F0E9] text-3xl
sm:text-4xl lg:text-5xl tracking-tight mb-4">
          Coverage Map
        </h2>
        <p className="text-[#F2F0E9]/50 text-base max-w-2xl mb-16
leading-relaxed">
          Serving 16 municipalities across the Kansas City metropolitan
area with
          combined populations exceeding 1.5 million residents.
        </p>

        <div className="grid lg:grid-cols-2 gap-12 lg:gap-16">
          <div>
            <div className="flex items-center gap-3 mb-6">
              <div className="w-6 h-6 border border-[#FF4D00]/30 flex
items-center justify-center">
                <span className="font-mono text-[10px] text-[#FF4D00]
font-bold">KS</span>
              </div>
              <span className="font-heading font-semibold text-[#F2F0E9]
text-lg">Kansas</span>
            </div>

```

```

        <span className="font-mono text-[10px] text-[#4A5568]
tracking-wider ml-auto">
            {ksCities.length} CITIES
        </span>
    </div>
    {ksCities.map((city, i) => (
        <CityRow key={city.name} city={city} idx={i} />
    ))}
</div>

<div>
    <div className="flex items-center gap-3 mb-6">
        <div className="w-6 h-6 border border-[#4A5568]/30 flex
items-center justify-center">
            <span className="font-mono text-[10px] text-[#4A5568]
font-bold">MO</span>
        </div>
        <span className="font-heading font-semibold text-[#F2F0E9]
text-lg">Missouri</span>
        <span className="font-mono text-[10px] text-[#4A5568]
tracking-wider ml-auto">
            {moCities.length} CITIES
        </span>
    </div>
    {moCities.map((city, i) => (
        <CityRow key={city.name} city={city} idx={i} />
    ))}
</div>
</div>

<div className="mt-16 grid grid-cols-2 sm:grid-cols-4 gap-px
bg-white/5">
    {[
        { val: "1.5M+", label: "Total Population" },
        { val: "2", label: "States Covered" },
        { val: "9 min", label: "Nearest City" },
        { val: "48 min", label: "Farthest City" },
    ].map((stat) => (
        <div key={stat.label} className="bg-[#111111] p-5 lg:p-6
text-center">
            <p className="font-heading font-bold text-[#FF4D00]
text-xl lg:text-2xl">{stat.val}</p>

```

```

        <p className="font-mono text-[10px] tracking-wider
text-[#4A5568] uppercase mt-1">{stat.label}</p>
      </div>
    )))
  </div>
</div>
</section>
);
}

```

Footer.jsx

```

import React from "react";

const platformLinks = [
  { label: "KC Pavement Analysis", href: "#pavements" },
  { label: "City Specifications", href: "#pavements" },
  { label: "Lifecycle Cost Data", href: "#pavements" },
];

const projectLinks = [
  { label: "About the Project", href: "#about" },
  { label: "Suggest a City", href: "#contact" },
  { label: "Contact", href: "#contact" },
];

export default function Footer() {
  return (
    <footer className="border-t border-white/5 pt-16 pb-8">
      <div className="max-w-7xl mx-auto px-6 lg:px-8">
        <div className="grid sm:grid-cols-2 lg:grid-cols-3 gap-12
lg:gap-8 mb-16">
          <div>
            <div className="flex items-center gap-3 mb-6">
              <div className="w-8 h-8 bg-[#FF4D00] flex items-center
justify-center">
                <span className="font-mono text-white text-[9px]
font-bold tracking-tighter">KCP</span>
              </div>
              <div className="flex flex-col leading-tight">
                <span className="font-heading font-bold text-[#F2F0E9]
text-base tracking-tight">
                  KC Pavement Analysis
                </span>
              </div>
            </div>

```

```

        <span className="font-mono text-[10px] text-[#F2F0E9]/30
tracking-wide">
            by Bobby Youan & Danny Will
        </span>
    </div>
</div>
<p className="text-[#F2F0E9]/40 text-sm leading-relaxed">
    Pavement specification data for the Kansas City metro –
compiled from official city engineering
    documents and APWA standards into one convenient
reference.
</p>
</div>

<div>
    <h4 className="font-mono text-[10px] tracking-[0.3em]
text-[#FF4D00] uppercase mb-6">Platform</h4>
    <div className="space-y-3">
        {platformLinks.map((link) => (
            <a
                key={link.label}
                href={link.href}
                className="block text-[#F2F0E9]/40 text-sm
hover:text-[#FF4D00] transition-colors"
            >
                {link.label}
            </a>
        ))}
    </div>
</div>

<div>
    <h4 className="font-mono text-[10px] tracking-[0.3em]
text-[#FF4D00] uppercase mb-6">Project</h4>
    <div className="space-y-3">
        {projectLinks.map((link) => (
            <a
                key={link.label}
                href={link.href}
                className="block text-[#F2F0E9]/40 text-sm
hover:text-[#FF4D00] transition-colors"
            >

```

```

        {link.label}
      </a>
    )}
  </div>
  <div className="mt-8 space-y-2">
    <a
      href="mailto:bobby.youan@ibhc.com"
      className="block font-mono text-xs text-[#F2F0E9]/30
hover:text-[#FF4D00] transition-colors"
    >
      bobby.youan@ibhc.com
    </a>
    <a
      href="mailto:bobbyyouan@gmail.com"
      className="block font-mono text-xs text-[#F2F0E9]/30
hover:text-[#FF4D00] transition-colors"
    >
      bobbyyouan@gmail.com
    </a>
  </div>
</div>
</div>

  <div className="border-t border-white/5 pt-8 flex flex-col
sm:flex-row items-center justify-between gap-4">
    <p className="font-mono text-[10px] tracking-wider
text-[#4A5568]">
      © {new Date().getFullYear()} KC PAVEMENT ANALYSIS. ALL
RIGHTS RESERVED.
    </p>
    <p className="font-mono text-[10px] tracking-wider
text-[#4A5568]">
      DATA SOURCED FROM OFFICIAL MUNICIPAL ENGINEERING DOCUMENTS
    </p>
  </div>
</div>
</footer>
);
}

```

Hero.jsx

```

import React from "react";
import { motion } from "framer-motion";

```

```

import { ArrowDown } from "lucide-react";

const HERO_IMG =
"https://media.base44.com/images/public/6a3d5093b397842fc6d30258/e1d8b1821_gen
erated_c1991deb.png";

export default function Hero() {
  return (
    <section className="relative min-h-screen flex items-end
overflow-hidden">
      <div className="absolute inset-0">
        <img src={HERO_IMG} alt="Aerial view of highway interchange
construction at golden hour" className="w-full h-full object-cover" />
        <div className="hero-gradient absolute inset-0" />
        <div className="absolute inset-0 bg-[#111111]/40" />
      </div>

      <div className="relative z-10 w-full max-w-7xl mx-auto px-6
lg:px-8 pb-20 lg:pb-28 pt-32">
        <motion.div initial={{ opacity: 0, y: 40 }} animate={{ opacity:
1, y: 0 }} transition={{ duration: 0.8, delay: 0.2 }}>
          <div className="flex items-center gap-3 mb-6">
            <div className="w-2 h-2 bg-[#FF4D00] rounded-full
animate-pulse" />
            <span className="font-mono text-xs tracking-[0.3em]
text-[#FF4D00] uppercase">
              Kansas City Metro – Road Standards Database
            </span>
          </div>

          <h1 className="font-heading font-bold text-[#F2F0E9] text-4xl
sm:text-5xl md:text-6xl lg:text-7xl xl:text-8xl leading-[0.95] tracking-tight
max-w-5xl">
            The KC Road<br />
            <span className="text-gradient-orange">Standard
Database</span><br />
            is Here.
          </h1>

          <p className="mt-8 font-body text-lg lg:text-xl
text-[#F2F0E9]/60 max-w-2xl leading-relaxed">

```


With a variety of cities in the KC Metro having differing road standards and specifications, it was only right to put them all in one place.

</p>

```
<div className="mt-10 flex flex-col sm:flex-row gap-4">
  <a href="#pavements"
    className="font-mono text-sm tracking-wider bg-[#FF4D00]
text-white px-8 py-4 hover:bg-[#FF4D00]/90 transition-colors uppercase
text-center min-h-[48px] flex items-center justify-center">
    Explore KC Pavements
  </a>
  <a href="#about"
    className="font-mono text-sm tracking-wider border
border-[#F2F0E9]/20 text-[#F2F0E9] px-8 py-4 hover:border-[#FF4D00]
hover:text-[#FF4D00] transition-colors uppercase text-center min-h-[48px] flex
items-center justify-center">
    About the Project
  </a>
</div>
</motion.div>
```

```
<motion.div initial={{ opacity: 0 }} animate={{ opacity: 1 }}
transition={{ delay: 1.2, duration: 0.6 }}
  className="absolute bottom-8 left-1/2 -translate-x-1/2">
    <a href="#pavements" className="text-[#F2F0E9]/30
hover:text-[#FF4D00] transition-colors">
      <ArrowDown size={20} className="animate-bounce" />
    </a>
  </motion.div>
</div>
</section>
);
}
```

NavBar.jsx

```
import React, { useState, useEffect } from "react";
import { Menu, X, Building2 } from "lucide-react";
import { motion, AnimatePresence } from "framer-motion";
import CityAdmin from "../CityAdmin";

// Hard hat icon for Pavo
function HardHatIcon({ size = 16, className = "" }) {
```

```

    return (
      <svg width={size} height={size} viewBox="0 0 24 24" fill="none"
className={className}>
        <path d="M12 2C8 2 5 5.5 5 9v1H3v2h18v-2h-2V9C19 5.5 16 2 12 2z"
fill="currentColor" opacity="0.9"/>
        <rect x="2" y="12" width="20" height="3" rx="1.5"
fill="currentColor"/>
        <path d="M5 15h14l-1 4H6l-1-4z" fill="currentColor"
opacity="0.7"/>
      </svg>
    );
  }

  const navLinks = [
    { label: "KC Pavements", href: "#pavements" },
    { label: "Calculator", href: "#calculator" },
    { label: "About", href: "#about" },
    { label: "Contact", href: "#contact" },
  ];

  export default function Navbar({ showPavo = true }) {
    const [scrolled, setScrolled] = useState(false);
    const [mobileOpen, setMobileOpen] = useState(false);
    const [bypassed, setBypassed] = useState(() => { try { return
localStorage.getItem("kcp_bypassed") === "true"; } catch { return false; } });
    const [showCityAdmin, setShowCityAdmin] = useState(false);

    useEffect(() => {
      const onScroll = () => setScrolled(window.scrollY > 60);
      window.addEventListener("scroll", onScroll);
      return () => window.removeEventListener("scroll", onScroll);
    }, []);

    useEffect(() => {
      const handler = () => { try {
setBypassed(localStorage.getItem("kcp_bypassed") === "true"); } catch {} };
      window.addEventListener("kcp_bypass_change", handler);
      return () => window.removeEventListener("kcp_bypass_change",
handler);
    }, []);

    return (

```

```

<nav className={`fixed top-0 left-0 right-0 z-50 transition-all
duration-500 ${scrolled ? "bg-[#111111]/95 backdrop-blur-md border-b
border-white/5" : "bg-transparent"}`}>
  <div className="max-w-7xl mx-auto px-6 lg:px-8">
    <div className="flex items-center justify-between h-16 lg:h-20">
      {/* Left: Pavo icon + brand */}
      <div className="flex items-center gap-4">
        {showPavo && (
          <button
            onClick={() => {
              const event = new CustomEvent("pavo-open-fullscreen");
              window.dispatchEvent(event);
            }}
            className="w-9 h-9 bg-[#FF4D00] flex items-center
justify-center hover:bg-[#FF4D00]/90 transition-colors"
            title="Chat with Pavo (fullscreen)"
          >
            <HardHatIcon size={18} className="text-white" />
          </button>
        )}

        <a href="#" className="flex items-center gap-3">
          <div className="w-8 h-8 bg-white/5 border border-white/10
flex items-center justify-center">
            <span className="font-mono text-white text-[9px]
font-bold tracking-tighter">KCP</span>
          </div>
          <div className="hidden sm:flex flex-col leading-tight">
            <span className="font-heading font-bold text-[#F2F0E9]
text-base tracking-tight">KC Pavement Analysis</span>
            <span className="font-mono text-[10px] text-[#F2F0E9]/30
tracking-wide">by Bobby Youan & Danny Will</span>
          </div>
        </a>
      </div>

      <div className="hidden lg:flex items-center gap-8">
        {bypassed && (
          <button onClick={() => setShowCityAdmin(true)}
            className="flex items-center gap-1.5 font-mono text-xs
tracking-wider text-[#FF4D00] hover:text-[#FF7A33] transition-colors
uppercase">

```

```

        <Building2 size={14} /> City Admin
      </button>
    )}
    {navLinks.map((link) => (
      <a key={link.label} href={link.href}
        className="font-mono text-xs tracking-wider
text-[#F2F0E9]/60 hover:text-[#FF4D00] transition-colors uppercase">
        {link.label}
      </a>
    ))}
    <a href="https://paypal.me/Bobbyyouan" target="_blank"
rel="noopener noreferrer"
      className="font-mono text-xs tracking-wider bg-[#FF4D00]
text-white px-5 py-2.5 hover:bg-[#FF4D00]/90 transition-colors uppercase
min-h-[44px] flex items-center">
      Donate ♥
    </a>
  </div>

  <button onClick={() => setMobileOpen(!mobileOpen)}
    className="lg:hidden text-[#F2F0E9] p-2 min-h-[48px]
min-w-[48px] flex items-center justify-center">
    {mobileOpen ? <X size={24} /> : <Menu size={24} />}
  </button>
</div>
</div>

<AnimatePresence>
  {mobileOpen && (
    <motion.div initial={{ opacity: 0, height: 0 }} animate={{
opacity: 1, height: "auto" }} exit={{ opacity: 0, height: 0 }}
      className="lg:hidden bg-[#111111]/98 backdrop-blur-md
border-t border-white/5">
      <div className="px-6 py-6 flex flex-col gap-4">
        {bypassed && (
          <button onClick={() => { setShowCityAdmin(true);
setMobileOpen(false); }}
            className="flex items-center gap-2 font-mono text-sm
tracking-wider text-[#FF4D00] hover:text-[#FF7A33] transition-colors uppercase
py-2">

              <Building2 size={16} /> City Admin
            </button>

```

```

    ))
    {navLinks.map((link) => (
      <a key={link.label} href={link.href} onClick={() =>
setMobileOpen(false)}
        className="font-mono text-sm tracking-wider
text-[#F2F0E9]/80 hover:text-[#FF4D00] transition-colors uppercase py-2">
        {link.label}
      </a>
    ))}
    <a href="https://paypal.me/Bobbyyouan" target="_blank"
rel="noopener noreferrer"
      onClick={() => setMobileOpen(false)}
      className="font-mono text-sm tracking-wider bg-[#FF4D00]
text-white px-5 py-3 text-center uppercase mt-2">
      Donate to Bobby & Danny ♥
    </a>
  </div>
</motion.div>
)}
</AnimatePresence>
<AnimatePresence>
  {showCityAdmin && <CityAdmin onClose={() =>
setShowCityAdmin(false)} />}
</AnimatePresence>
</nav>
);
}

```

OnBoarding.jsx

```

import React, { useState, useEffect } from "react";
import { motion, AnimatePresence } from "framer-motion";
import { ArrowRight, Linkedin, SkipForward } from "lucide-react";

const VISITED_KEY = "kcp_visited";
const BRIEF = `KC Pavement Analysis was created by Civil Engineering
Interns Bobby Youan and Daniel Will for their Summer Project. It compiles
pavement specification standards and 30-year lifecycle cost comparisons across
Kansas City metro municipalities. It helps city planners, contractors, and
developers make informed decisions on asphalt vs. concrete – backed by real
engineering data, not guesswork.`;

export default function Onboarding({ onComplete, onJumpToPavements }) {
  const [step, setStep] = useState(1);

```

```

    const hasVisited = typeof window !== "undefined" &&
localStorage.getItem(VISITED_KEY) === "true";

useEffect(() => {
    if (hasVisited) onComplete();
}, []);

const finish = () => {
    localStorage.setItem(VISITED_KEY, "true");
    onComplete();
};

const handleQ1 = (answer) => {
    if (answer === "yes") setStep("project_check");else
    setStep("brief");
};

const handleProjectCheck = (forProject) => {
    localStorage.setItem(VISITED_KEY, "true");
    if (forProject) {
        onComplete();
        setTimeout(() => onJumpToPavements(), 100);
    } else {
        setStep("brief");
    }
};

return (
    <div className="fixed inset-0 z-[100] flex items-center
justify-center bg-[#0a0a0a]/96 backdrop-blur-md px-4">
        <AnimatePresence mode="wait">

            {step === 1 &&
                <motion.div key="q1" initial={{ opacity: 0, y: 24 }} animate={{
opacity: 1, y: 0 }} exit={{ opacity: 0, y: -24 }} transition={{ duration: 0.35
}} className="w-full max-w-lg">
                    <StepHeader tag="01 / 02" title="KC Pavement Analysis"
subtitle="By Bobby Youan & Danny Will" />
                    <p className="font-mono text-xs tracking-[0.2em] uppercase
mb-10">ARE YOU AN ENGINEER?</p>
                    <div className="flex flex-col gap-3 mb-6">

```

```

        [{ val: "yes", label: "Yes" }, { val: "no", label: "No"
    }, { val: "sometimes", label: "Sometimes" }].map((opt) =>
        <button key={opt.val} onClick={() => handleQ1(opt.val ===
"sometimes" ? "no" : opt.val)}
            className="w-full text-left border border-white/10 px-6 py-4
font-heading text-[#F2F0E9] text-lg hover:border-[#FF4D00]
hover:text-[#FF4D00] hover:bg-[#FF4D00]/5 transition-all duration-200
min-h-[56px] rounded-sm">
                {opt.label}
            </button>
        )}
    </div>
    {/* Returning user skip — prominent */}
    {hasVisited &&
<motion.button
    initial={{ opacity: 0 }}
    animate={{ opacity: 1 }}
    onClick={finish}
    className="w-full flex items-center justify-center gap-2
border-2 border-[#FF4D00]/60 text-[#FF4D00] font-mono text-sm tracking-wider
uppercase py-4 hover:bg-[#FF4D00] hover:text-white transition-all duration-200
rounded-sm">
        <SkipForward size={16} /> Welcome back — Skip intro &
enter
    </motion.button>
    }
</motion.div>
}

{step === "project_check" &&
    <motion.div key="project_check" initial={{ opacity: 0, y: 24 }}
    animate={{ opacity: 1, y: 0 }} exit={{ opacity: 0, y: -24 }} transition={{
duration: 0.35 }} className="w-full max-w-lg">
        <StepHeader tag="02 / 02" title="Is this for a project?" />
        <div className="flex flex-col gap-3">
            <button onClick={() => handleProjectCheck(true)}
                className="w-full text-left border border-white/10 px-6 py-4
font-heading text-[#F2F0E9] text-lg hover:border-[#FF4D00]
hover:text-[#FF4D00] hover:bg-[#FF4D00]/5 transition-all duration-200
min-h-[56px] rounded-sm">
                    Yes — take me to the road standards
                </button>

```

```

        <button onClick={() => handleProjectCheck(false)}
            className="w-full text-left border border-white/10 px-6 py-4
font-heading text-[#F2F0E9] text-lg hover:border-[#FF4D00]
hover:text-[#FF4D00] hover:bg-[#FF4D00]/5 transition-all duration-200
min-h-[56px] rounded-sm">
            No — show me everything
        </button>
    </div>
</motion.div>
}

{step === "brief" &&
    <motion.div key="brief" initial={{ opacity: 0, y: 24 }}
    animate={{ opacity: 1, y: 0 }} exit={{ opacity: 0, y: -24 }} transition={{
    duration: 0.35 }} className="w-full max-w-lg">
        <StepHeader tag="CONTEXT" title="What is this platform?" />
        <p className="text-[#F2F0E9]/70 text-base leading-relaxed
mb-8 border-l-2 border-[#FF4D00] pl-5">{BRIEF}</p>
        <button onClick={() => setStep("linkedin")}
            className="w-full bg-[#FF4D00] text-white font-mono text-sm
tracking-wider uppercase py-4 hover:bg-[#FF4D00]/90 transition-colors flex
items-center justify-center gap-2 min-h-[52px] rounded-sm">
            Got it — Continue <ArrowRight size={16} />
        </button>
    </motion.div>
}

{step === "linkedin" &&
    <motion.div key="linkedin" initial={{ opacity: 0, y: 24 }}
    animate={{ opacity: 1, y: 0 }} exit={{ opacity: 0, y: -24 }} transition={{
    duration: 0.35 }} className="w-full max-w-lg text-center">
        <StepHeader tag="CONNECT" title="Let's connect on LinkedIn"
/>
        <p className="text-[#F2F0E9]/50 text-sm mb-8
leading-relaxed">Follow Bobby Youan on LinkedIn for engineering insights and
KC metro infrastructure news.</p>
        <a href="https://www.linkedin.com/in/bobbyyouan/"
target="_blank" rel="noopener noreferrer"
            className="w-full bg-[#0A66C2] text-white font-mono text-sm
tracking-wider uppercase py-4 hover:bg-[#0A66C2]/90 transition-colors flex
items-center justify-center gap-3 min-h-[52px] mb-3 rounded-sm">
            <Linkedin size={18} /> View Bobby's LinkedIn

```



```

        </a>
        <button onClick={finish}
          className="w-full border border-white/10 text-[#F2F0E9]/40
font-mono text-xs tracking-wider uppercase py-4 hover:border-[#FF4D00]/50
hover:text-[#FF4D00]/60 transition-colors min-h-[48px] rounded-sm">
          Enter the Platform
        </button>
      </motion.div>
    }

    </AnimatePresence>
  </div>);
}

function StepHeader({ tag, title, subtitle }) {
  return (
    <div className="mb-8">
      <div className="flex items-center gap-3 mb-4">
        <div className="w-8 h-px bg-[#FF4D00]" />
        <span className="font-mono text-[10px] tracking-[0.3em]
text-[#FF4D00] uppercase">{tag}</span>
      </div>
      <h2 className="font-heading font-bold text-[#F2F0E9] text-2xl
sm:text-3xl tracking-tight">{title}</h2>
      {subtitle && <p className="font-mono text-xs text-[#4A5568]
tracking-wider mt-1">{subtitle}</p>}
    </div>);
}

```

PavementCalculator.jsx

```

import React, { useState } from "react";
import { motion, AnimatePresence } from "framer-motion";
import { Calculator, TrendingDown, Minus, ChevronDown, FileDown } from
"lucide-react";
import { exportCalculatorPDF } from "@lib/pdfExport";
import { getCalculatorCities } from "@lib/cityDatabase";
import { useCitySync } from "@hooks/useCitySync";
import CalculatorTutorial from "../CalculatorTutorial";
import { BarChart, Bar, XAxis, YAxis, Tooltip, ResponsiveContainer, Cell
} from "recharts";

```

```

const cityData = [
  { city: "APWA Standard", state: "Standard", residential: { access: {
asphalt: '8" (6"+2")', concrete: '6" Solid Slab' }, local: { asphalt: '8"
(6"+2")', concrete: '6" Solid Slab' }, collector: { asphalt: '9" (7"+2")',
concrete: '7" Solid Slab' } }, collector: { residential: { asphalt: '9"
(7"+2")', concrete: '7" Solid Slab' }, commercial: { asphalt: '9" (7"+2")',
concrete: '7" Solid Slab' }, industrial: { asphalt: '11" (9"+2")', concrete:
'8" Solid Slab' } }, arterial: { minor: { asphalt: '11" (9"+2")', concrete:
'8" Solid Slab' }, major: { asphalt: '12" (10"+2")', concrete: '9" Solid Slab'
} }, costs: { res_a: 657888, res_c: 1478400, col_a: 1045440, col_c: 2280960,
art_a: 1951488, art_c: 4435200 }, maint30: { res_a: 1584000, res_c: 369600,
col_a: 2037000, col_c: 475200, art_a: 3168000, art_c: 739100 } },
  { city: "Overland Park", state: "KS", residential: { access: { asphalt:
'8" (6"+2")', concrete: '7" Slab+4" Rock' }, local: { asphalt: '8" (6"+2")',
concrete: '7" Slab+4" Rock' }, collector: { asphalt: '9" (7"+2")', concrete:
'8" Slab+4" Rock' } }, collector: { residential: { asphalt: '9" (7"+2")',
concrete: '8" Slab+4" Rock' }, commercial: { asphalt: '10" (8"+2")', concrete:
'8" Slab+4" Rock' }, industrial: { asphalt: '10" (8"+2")', concrete: '8"
Slab+4" Rock' } }, arterial: { minor: { asphalt: '-', concrete: '-' }, major:
{ asphalt: '-', concrete: '-' } }, costs: { res_a: 657888, res_c: 1848000,
col_a: 950400, col_c: 2661120, art_a: 1951488, art_c: 4878720 }, maint30: {
res_a: 1584000, res_c: 369600, col_a: 2037000, col_c: 475200, art_a: 3168000,
art_c: 739100 } },
  { city: "Lenexa", state: "KS", residential: { access: { asphalt: '8"
(4"+2"+2"Int)', concrete: '6" Solid Slab' }, local: { asphalt: '8"
(4"+2"+2"Int)', concrete: '6" Solid Slab' }, collector: { asphalt: '9"
(7"+2")', concrete: '8" Solid Slab' } }, collector: { residential: { asphalt:
'9" (7"+2")', concrete: '8" Solid Slab' }, commercial: { asphalt: '9"
(7"+2")', concrete: '8" Solid Slab' }, industrial: { asphalt: '11" (9"+2")',
concrete: '10" Solid Slab' } }, arterial: { minor: { asphalt: '11" (9"+2")',
concrete: '10" Solid Slab' }, major: { asphalt: '12" (10"+2")', concrete: '10"
Solid Slab' } }, costs: { res_a: 657888, res_c: 1478400, col_a: 950400, col_c:
2566080, art_a: 1951488, art_c: null }, maint30: { res_a: 1584000, res_c:
369600, col_a: 2037000, col_c: 475200, art_a: 3168000, art_c: null } },
  { city: "Shawnee", state: "KS", residential: { access: { asphalt: '8"
(6"+2")', concrete: '6" Solid Slab' }, local: { asphalt: '8" (6"+2")',
concrete: '6" Solid Slab' }, collector: { asphalt: '9" (7"+2")', concrete: '8"
Solid Slab' } }, collector: { residential: { asphalt: '9" (7"+2")', concrete:
'8" Solid Slab' }, commercial: { asphalt: '10" (8"+2")', concrete: '8" Solid
Slab' }, industrial: { asphalt: '10" (8"+2")', concrete: '8" Solid Slab' } },
arterial: { minor: { asphalt: '12" (10"+2")', concrete: '10" Solid Slab' },
major: { asphalt: 'State Criteria', concrete: 'State Criteria' } }, costs: {

```

```
res_a: 657888, res_c: 1478400, col_a: 1045440, col_c: 2566080, art_a: 1951488,
art_c: 4656960 }, maint30: { res_a: 1584000, res_c: 369600, col_a: 2037000,
col_c: 475200, art_a: 3168000, art_c: 739100 } },
```

```
{ city: "Olathe", state: "KS", residential: { access: { asphalt: '8"
(6"+2")', concrete: '6" Slab+9" Sub' }, local: { asphalt: '8" (6"+2")',
concrete: '6" Slab+9" Sub' }, collector: { asphalt: '10" (8"+2")', concrete:
'7" Slab+9" Sub' } }, collector: { residential: { asphalt: '10" (8"+2")',
concrete: '7" Slab+9" Sub' }, commercial: { asphalt: '10" (8"+2")', concrete:
'7" Slab+9" Sub' }, industrial: { asphalt: '10" (8"+2")', concrete: '7"
Slab+9" Sub' } }, arterial: { minor: { asphalt: '12" (10"+2")', concrete: '9"
Slab+6" Rock' }, major: { asphalt: '12" (10"+2")', concrete: '9" Slab+6" Rock'
} }, costs: { res_a: 657888, res_c: 1478400, col_a: 1045440, col_c: 2280960,
art_a: 1951488, art_c: 4435200 }, maint30: { res_a: 1584000, res_c: 369600,
col_a: 2037000, col_c: 475200, art_a: 3168000, art_c: 739100 } },
```

```
{ city: "Gardner", state: "KS", residential: { access: { asphalt: '8"
(6"+2")', concrete: '6" Slab+9" Sub' }, local: { asphalt: '8" (6"+2")',
concrete: '6"+9" Sub' }, collector: { asphalt: '10" (8"+2")', concrete: '7"
Slab+9" Sub' } }, collector: { residential: { asphalt: '10" (8"+2")',
concrete: '7" Slab+9" Sub' }, commercial: { asphalt: '10" (8"+2")', concrete:
'7" Slab+9" Sub' }, industrial: { asphalt: '10" (8"+2")', concrete: '7"
Slab+9" Sub' } }, arterial: { minor: { asphalt: '12" (10"+2")', concrete: '9"
Slab+9" Sub' }, major: { asphalt: '12" (10"+2")', concrete: '9" Slab+9" Sub' }
}, costs: { res_a: 657888, res_c: 1478400, col_a: 950400, col_c: 2280960,
art_a: 1951488, art_c: 4435200 }, maint30: { res_a: 1584000, res_c: 369600,
col_a: 2037000, col_c: 475200, art_a: 3168000, art_c: 739100 } },
```

```
{ city: "Grandview", state: "MO", residential: { access: { asphalt: '8"
(6"+2")', concrete: '6" Solid Slab' }, local: { asphalt: '8" (6"+2")',
concrete: '6" Solid Slab' }, collector: { asphalt: '9" (7"+2")', concrete: '7"
Solid Slab' } }, collector: { residential: { asphalt: '9" (7"+2")', concrete:
'7" Solid Slab' }, commercial: { asphalt: '9" (7"+2")', concrete: '7" Solid
Slab' }, industrial: { asphalt: '9" (7"+2")', concrete: '7" Solid Slab' } },
arterial: { minor: { asphalt: '11" (9"+2")', concrete: '8" Solid Slab' },
major: { asphalt: '12" (10"+2")', concrete: '9" Solid Slab' } }, costs: {
res_a: 657888, res_c: 1478400, col_a: 845856, col_c: 2280960, art_a: 1951488,
art_c: 4435200 }, maint30: { res_a: 1584000, res_c: 369600, col_a: 2037000,
col_c: 475200, art_a: 3168000, art_c: 739100 } },
```

```
{ city: "Blue Springs", state: "MO", residential: { access: { asphalt:
'8" (6"+2")', concrete: '6" Solid Slab' }, local: { asphalt: '8" (6"+2")',
concrete: '6" Solid Slab' }, collector: { asphalt: '8" (6"+2")', concrete: '6"
Solid Slab' } }, collector: { residential: { asphalt: '8" (6"+2")', concrete:
'6" Solid Slab' }, commercial: { asphalt: '11" (9"+2")', concrete: '7" Solid
Slab' }, industrial: { asphalt: '11" (9"+2")', concrete: '7" Solid Slab' } },
```

```

arterial: { minor: { asphalt: '11" (9"+2")', concrete: '8" Solid Slab' },
major: { asphalt: '12" (10"+2")', concrete: '9" Solid Slab' } }, costs: {
res_a: 657888, res_c: 1478400, col_a: null, col_c: 1900800, art_a: null,
art_c: null }, maint30: { res_a: 1584000, res_c: 369600, col_a: null, col_c:
475200, art_a: null, art_c: null } },
    { city: "Lee's Summit", state: "MO", residential: { access: { asphalt:
'6" (4"+2")+8"Rock', concrete: '6"+6"Rock' }, local: { asphalt: '6"
(4"+2")+8"Rock', concrete: '6"+6"Rock' }, collector: { asphalt: '8"
(6"+2")+8"Rock', concrete: '6.5"+6"Rock' } }, collector: { residential: {
asphalt: '8" (6"+2")+8"Rock', concrete: '6.5"+6"Rock' }, commercial: {
asphalt: '11" (9"+2")+8"Rock', concrete: '8"+6"Rock' }, industrial: { asphalt:
'11" (9"+2")+8"Rock', concrete: '8"+6"Rock' } }, arterial: { minor: { asphalt:
'Project Specific', concrete: 'Project Specific' }, major: { asphalt: 'Project
Specific', concrete: 'Project Specific' } }, costs: { res_a: 665280, res_c:
1589280, col_a: 1035936, col_c: 2233440, art_a: 2173248, art_c: 4656960 },
maint30: { res_a: 1584000, res_c: 369600, col_a: 2037000, col_c: 475200,
art_a: 3168000, art_c: 739000 } },
    { city: "Kansas City", state: "MO", residential: { access: { asphalt:
'N/A', concrete: 'N/A' }, local: { asphalt: '8" (6"+2")+6"Rock', concrete:
'6"+6"Rock' }, collector: { asphalt: '9" (7"+2")+6"Rock', concrete:
'7"+6"Rock' } }, collector: { residential: { asphalt: '9" (7"+2")+6"Rock',
concrete: '7"+6"Rock' }, commercial: { asphalt: '9" (7"+2")+6"Rock', concrete:
'7"+6"Rock' }, industrial: { asphalt: '9" (7"+2")+6"Rock', concrete:
'7"+6"Rock' } }, arterial: { minor: { asphalt: '11" (9"+2")+6"Rock', concrete:
'8"+6"Rock' }, major: { asphalt: '12" (10"+2")+6"Rock', concrete: '9"+6"Rock'
} }, costs: { res_a: 768768, res_c: 1589280, col_a: 1092960, col_c: 2423520,
art_a: 1951488, art_c: 4435200 }, maint30: { res_a: 1584000, res_c: 369600,
col_a: 2037000, col_c: 475200, art_a: 3168000, art_c: 739000 } },
    { city: "Independence", state: "MO", residential: { access: { asphalt:
'N/A', concrete: 'N/A' }, local: { asphalt: '8" (6"+2")', concrete: '6" Solid
Slab' }, collector: { asphalt: '9" (7"+2")', concrete: '7" Solid Slab' } },
collector: { residential: { asphalt: '9" (7"+2")', concrete: '7" Solid Slab'
}, commercial: { asphalt: '9" (7"+2")', concrete: '7" Solid Slab' },
industrial: { asphalt: '9" (7"+2")', concrete: '7" Solid Slab' } }, arterial:
{ minor: { asphalt: '11" (9"+2")', concrete: '8" Solid Slab' }, major: {
asphalt: '12" (10"+2")', concrete: '9" Solid Slab' } }, costs: { res_a:
657888, res_c: 1478400, col_a: 950400, col_c: 2280960, art_a: 1951488, art_c:
4435200 }, maint30: { res_a: 1584000, res_c: 369600, col_a: 2037000, col_c:
475200, art_a: 3168000, art_c: 739000 } },
    { city: "Merriam", state: "KS", residential: { access: { asphalt: '7"
(4"+2"+1"Int)', concrete: '6" PCC Min' }, local: { asphalt: '7"
(4"+2"+1"Int)', concrete: '6" PCC Min' }, collector: { asphalt: '8" (6"+2")',

```

```

concrete: '7" PCC' } }}, collector: { residential: { asphalt: '8" (6"+2")',
concrete: '7" PCC' }, commercial: { asphalt: '8" (6"+2")', concrete: '8" PCC'
}, industrial: { asphalt: '8" (6"+2")', concrete: '8" PCC' } }}, arterial: {
minor: { asphalt: '11" (9"+2")', concrete: '8" PCC' }, major: { asphalt: '12"
(10"+2")', concrete: '9" PCC' } }}, costs: { res_a: 657888, res_c: 1478400,
col_a: 1045440, col_c: 2280960, art_a: 1951488, art_c: 4435200 }, maint30: {
res_a: 1584000, res_c: 369600, col_a: 2037000, col_c: 475200, art_a: 3168000,
art_c: 739100 } }];

```

```

const allCityData = getCalculatorCities();

```

```

const roadTypes = [
  { key: "residential", label: "Residential", subtypes: [{ key: "access",
label: "Access" }, { key: "local", label: "Local" }, { key: "collector",
label: "Collector" }], ck_a: "res_a", ck_c: "res_c", mk_a: "res_a", mk_c:
"res_c" },
  { key: "collector", label: "Collector", subtypes: [{ key: "residential",
label: "Residential" }, { key: "commercial", label: "Commercial" }, { key:
"industrial", label: "Industrial" }], ck_a: "col_a", ck_c: "col_c", mk_a:
"col_a", mk_c: "col_c" },
  { key: "arterial", label: "Arterial", subtypes: [{ key: "minor", label:
"Minor" }, { key: "major", label: "Major" }], ck_a: "art_a", ck_c: "art_c",
mk_a: "art_a", mk_c: "art_c" }];

```

```

const UNITS = [
  { key: "miles", label: "Miles", toMiles: (v) => v, fromMiles: (v) => v
},
  { key: "km", label: "Kilometers", toMiles: (v) => v * 0.621371,
fromMiles: (v) => v / 0.621371 },
  { key: "feet", label: "Feet", toMiles: (v) => v / 5280, fromMiles: (v)
=> v * 5280 },
  { key: "meters", label: "Meters", toMiles: (v) => v / 1609.34,
fromMiles: (v) => v * 1609.34 }];

```

```

function fmt(v) {
  if (!v) return "-";
  if (v >= 1000000000000) return `$$${(v / 1000000000000).toFixed(2)}T`;
  if (v >= 1000000000) return `$$${(v / 1000000000).toFixed(2)}B`;
  if (v >= 1000000) return `$$${(v / 1000000).toFixed(2)}M`;
  if (v >= 1000) return `$$${(v / 1000).toFixed(0)}K`;
}

```

```

    return `$$${v}`;
  }

  const CustomTooltip = ({ active, payload, label }) => {
    if (!active || !payload?.length) return null;
    return (
      <div className="bg-[#1a1a1a] border border-white/10 px-4 py-3 font-mono text-xs rounded-lg shadow-xl">
        <p className="text-[#F2F0E9]/60 mb-1">{label}</p>
        {payload.map((p) => <p key={p.dataKey} style={{ color: p.color }}>{p.name}: {fmt(p.value)}</p>)}
      </div>);
  };

  function StyledSelect({ label, value, onChange, options }) {
    return (
      <div className="flex flex-col gap-2">
        <label className="font-mono text-[11px] tracking-widest text-[#FF4D00] uppercase">{label}</label>
        <div className="relative">
          <select value={value} onChange={(e) => onChange(e.target.value)} className="w-full bg-[#1a1a1a] border border-white/15 hover:border-white/30 focus:border-[#FF4D00] rounded-xl px-4 py-3.5 text-[#F2F0E9] font-body text-sm focus:outline-none transition-colors appearance-none cursor-pointer">
            {options.map((o) => <option key={o.value} value={o.value}>{o.label}</option>)}
          </select>
          <ChevronDown size={14} className="absolute right-3 top-1/2 -translate-y-1/2 text-[#4A5568] pointer-events-none" />
        </div>
      </div>);
  }

  export default function PavementCalculator() {
    useCitySync();
    const [selectedCity, setSelectedCity] = useState("");
    const [selectedRoadType, setSelectedRoadType] = useState("");
    const [selectedSubtype, setSelectedSubtype] = useState("");
    const [distance, setDistance] = useState("");
  }

```

```

const [unit, setUnit] = useState("miles");
const [result, setResult] = useState(null);

const roadTypeCfg = roadTypes.find((r) => r.key === selectedRoadType);
const unitCfg = UNITS.find((u) => u.key === unit);

const handleCalculate = () => {
  const city = allCityData.find((c) => c.city === selectedCity);
  if (!city || !distance || !roadTypeCfg) return;
  const miles = unitCfg.toMiles(parseFloat(distance));
  if (isNaN(miles) || miles <= 0) return;
  const spec = city[selectedRoadType]?.[selectedSubtype] || {};
  const initA = (city.costs[roadTypeCfg.ck_a] || 0) * miles;
  const initC = (city.costs[roadTypeCfg.ck_c] || 0) * miles;
  const maintA = (city.maint30[roadTypeCfg.mk_a] || 0) * miles;
  const maintC = (city.maint30[roadTypeCfg.mk_c] || 0) * miles;
  const totalA = initA + maintA;
  const totalC = initC + maintC;
  setResult({ city: city.city, state: city.state, spec, initA, initC,
    maintA, maintC, totalA, totalC, distance, unit, roadType: selectedRoadType,
    subtype: selectedSubtype });
};

const handleRoadTypeChange = (type) => {
  setSelectedRoadType(type);
  setSelectedSubtype(type ? roadTypes.find((r) => r.key ===
type).subtypes[0].key : "");
  setResult(null);
};

const chartData = result ? [
  { label: "Asphalt - Initial", value: result.initA, fill: "#FF4D00" },
  { label: "Asphalt - Maintenance", value: result.maintA, fill:
"#FF7A33" },
  { label: "Concrete - Initial", value: result.initC, fill: "#4A5568" },
  { label: "Concrete - Maintenance", value: result.maintC, fill:
"#718096" }] :
[];

const cheaper = result ? result.totalA < result.totalC ? "asphalt" :
result.totalA > result.totalC ? "concrete" : "equal" : null;

```

```

    const canCalculate = selectedCity && distance && parseFloat(distance)
    > 0 && selectedRoadType && selectedSubtype;

    return (
      <section id="calculator" className="py-24 lg:py-32 bg-[#0d0d0d]">
        <div className="max-w-5xl mx-auto px-6 lg:px-8">
          { /* Header */ }
          <div className="flex items-center gap-3 mb-3">
            <div className="w-8 h-px bg-[#FF4D00]" />
            <span className="font-mono text-xs tracking-[0.3em]
text-[#FF4D00] uppercase">Interactive Tool</span>
          </div>
          <h2 className="font-heading font-bold text-[#F2F0E9] text-3xl
sm:text-4xl lg:text-5xl tracking-tight mb-3">
            Pavement Calculator
          </h2>
          <p className="text-[#F2F0E9]/50 text-base mb-3 max-w-xl
leading-relaxed">Select a city and road type to get instant material specs and
30 year cost estimates.</p>
          <p className="font-mono text-[10px] text-[#4A5568] tracking-wide
mb-12">* All cost estimates are based on bid tabs and are for planning
purposes only.</p>

          <CalculatorTutorial />

          { /* Card */ }
          <div className="bg-[#151515] border border-white/10 rounded-2xl
p-6 lg:p-8 mb-10 shadow-2xl">
            <div className="grid md:grid-cols-2 gap-6 mb-6">
              <StyledSelect label="City" value={selectedCity}
onChange={(v) => {setSelectedCity(v); setResult(null);}}
              options={[{ value: "", label: "Select a city..." },
...allCityData.map((c) => ({ value: c.city, label: `${c.city}${c.state !==
"Standard" ? ` (${c.state})` : ""}` }))] />
              <StyledSelect label="Road Type" value={selectedRoadType}
onChange={handleRoadTypeChange}
              options={[{ value: "", label: "Select road type..." },
...roadTypes.map((r) => ({ value: r.key, label: r.label }))] />
              <StyledSelect label="Subtype" value={selectedSubtype}
onChange={(v) => {setSelectedSubtype(v); setResult(null);}}

```



```

        options={roadTypeCfg ? roadTypeCfg.subtypes.map((s) => ({
value: s.key, label: s.label })) : [{ value: "", label: "Select road type
first..." }]} />

    { /* Distance with unit selector */ }
    <div className="flex flex-col gap-2">
        <label className="font-mono text-[11px] tracking-widest
text-[#FF4D00] uppercase">Distance</label>
        <div className="flex gap-2">
            <input
                type="number"
                min="0"
                step="any"
                value={distance}
                onChange={ (e) =>
{setDistance(e.target.value); setResult(null);}}
                placeholder="e.g. 2.5"
                className="flex-1 bg-[#1a1a1a] border border-white/15
hover:border-white/30 focus:border-[#FF4D00] rounded-xl px-4 py-3.5
text-[#F2F0E9] font-body text-sm focus:outline-none transition-colors
placeholder-[#4A5568]" />

            <div className="relative">
                <select value={unit} onChange={ (e) =>
{setUnit(e.target.value); setResult(null);}}
                    className="h-full bg-[#1a1a1a] border border-white/15
hover:border-white/30 focus:border-[#FF4D00] rounded-xl pl-3 pr-8
text-[#F2F0E9] font-mono text-xs focus:outline-none transition-colors
appearance-none cursor-pointer">
                    {UNITS.map((u) => <option key={u.key}
value={u.key}>{u.label}</option>)}
                </select>
                <ChevronDown size={12} className="absolute right-2
top-1/2 -translate-y-1/2 text-[#4A5568] pointer-events-none" />
            </div>
        </div>
    </div>

    <button onClick={handleCalculate} disabled={!canCalculate}
        className="w-full flex items-center justify-center gap-2
bg-[#FF4D00] text-white font-mono text-sm tracking-wider uppercase py-4

```

```

rounded-xl hover:bg-[#FF4D00]/90 transition-colors disabled:opacity-30
disabled:cursor-not-allowed">
    <Calculator size={16} /> Calculate Costs
  </button>
</div>

  {/* Results */}
  <AnimatePresence>
    {result &&
      <motion.div key="result" initial={{ opacity: 0, y: 20 }}
        animate={{ opacity: 1, y: 0 }} exit={{ opacity: 0 }} transition={{ duration:
0.4 }}>

        {/* Spec cards */}
        <div className="grid md:grid-cols-3 gap-4 mb-6">
          <div className="bg-[#151515] border border-white/10
rounded-xl p-5">
            <span className="font-mono text-[10px] text-[#4A5568]
uppercase tracking-wider">Location</span>
            <p className="font-heading text-[#F2F0E9] text-xl
font-bold mt-1">{result.city}</p>
            <p className="font-mono text-xs text-[#4A5568] mt-1
capitalize">{result.roadType} / {result.subtype}</p>
            <p className="font-mono text-xs
text-[#4A5568]">{result.distance} {result.unit}</p>
          </div>
          <div className="bg-[#FF4D00]/5 border
border-[#FF4D00]/30 rounded-xl p-5">
            <span className="font-mono text-[10px] text-[#FF4D00]
uppercase tracking-wider">Asphalt Spec</span>
            <p className="font-heading text-[#F2F0E9] text-base
font-semibold mt-2 leading-snug">{result.spec.asphalt} || "-"</p>
            <div className="mt-3 pt-3 border-t
border-[#FF4D00]/20">
              <p className="font-mono text-[10px] text-[#FF4D00]
uppercase">30-yr Total</p>
              <p className="font-heading text-[#FF4D00] text-xl
font-bold">{fmt(result.totalA)}</p>
              <p className="font-mono text-[8px] text-[#4A5568]/60
mt-1">* bid-tab estimate</p>
            </div>
          </div>
        </div>

```

```

        <div className="bg-[#151515] border border-white/10
rounded-xl p-5">
            <span className="font-mono text-[10px] text-[#4A5568]
uppercase tracking-wider">Concrete Spec</span>
            <p className="font-heading text-[#F2F0E9] text-base
font-semibold mt-2 leading-snug">{result.spec.concrete || "-"}</p>
            <div className="mt-3 pt-3 border-t border-white/10">
                <p className="font-mono text-[10px] text-[#4A5568]
uppercase">30-yr Total</p>
                <p className="font-heading text-[#F2F0E9] text-xl
font-bold">{fmt(result.totalC)}</p>
                <p className="font-mono text-[8px] text-[#4A5568]/60
mt-1">* bid-tab estimate</p>
            </div>
        </div>
    </div>

    {/* Recommendation banner */}
    <div className={`rounded-xl border p-5 mb-8 flex
items-start gap-4 ${cheaper === "asphalt" ? "border-[#FF4D00]/30
bg-[#FF4D00]/5" : cheaper === "concrete" ? "border-blue-500/20 bg-blue-500/5"
: "border-white/10 bg-white/5"}`}>
        {cheaper !== "equal" && <TrendingDown size={22}
className={`shrink-0 mt-0.5 ${cheaper === "asphalt" ? "text-[#FF4D00]" :
"text-blue-400"}` } />}
        {cheaper === "equal" && <Minus size={22}
className="shrink-0 mt-0.5 text-[#4A5568]" />}
        <div>
            <p className="font-heading font-bold text-[#F2F0E9]
text-lg">
                {cheaper === "asphalt" && `Asphalt saves
${fmt(result.totalC - result.totalA)} over 30 years`}
                {cheaper === "concrete" && `Concrete saves
${fmt(result.totalA - result.totalC)} over 30 years`}
                {cheaper === "equal" && "Equal 30-year costs"}
            </p>
            <div className="flex flex-wrap gap-4 mt-2">
                <span className="font-mono text-xs
text-[#F2F0E9]/50">
                    Asphalt: <strong
className="text-[#FF4D00]">{fmt(result.initA)}</strong> initial + <strong
className="text-[#FF4D00]">{fmt(result.maintA)}</strong> maint

```

```

        </span>
        <span className="font-mono text-xs
text-[#F2F0E9]/30">|</span>
        <span className="font-mono text-xs
text-[#F2F0E9]/50">
            Concrete: <strong
className="text-[#F2F0E9]">{fmt(result.initC)}</strong> initial + <strong
className="text-[#F2F0E9]">{fmt(result.maintC)}</strong> maint
            </span>
        </div>
    </div>
</div>
<p className="font-mono text-[9px] text-[#4A5568]/60 mt-2
mb-2">* Cost estimates based on bid tabs – for planning purposes only.</p>

    { /* Chart */ }
    <div className="bg-[#151515] border border-white/10
rounded-2xl p-6">
        <p className="font-mono text-[11px] text-[#4A5568]
uppercase tracking-wider mb-6">Cost Breakdown</p>
        <div className="h-60">
            <ResponsiveContainer width="100%" height="100%">
                <BarChart data={chartData} margin={{ top: 0, right:
10, bottom: 0, left: 0 }}>
                    <XAxis dataKey="label" tick={{ fill: "#4A5568",
fontSize: 9, fontFamily: "JetBrains Mono" }} axisLine={false} tickLine={false}
/>
                    <YAxis tickFormatter={fmt} tick={{ fill:
"#4A5568", fontSize: 9, fontFamily: "JetBrains Mono" }} axisLine={false}
tickLine={false} width={60} />
                    <Tooltip content={<CustomTooltip />} />
                    <Bar dataKey="value" name="Cost" radius={[6, 6, 0,
0]}>
                        {chartData.map((entry, i) => <Cell key={i}
fill={entry.fill} />)}
                    </Bar>
                </BarChart>
            </ResponsiveContainer>
        </div>
    </div>
<p className="font-mono text-[9px] text-[#4A5568]/60
mt-2">* Cost estimates based on bid tabs – for planning purposes only.</p>

```

```

        <button onClick={() => exportCalculatorPDF(result)}
            className="flex items-center gap-2 bg-[#FF4D00]
text-white font-mono text-sm tracking-wider uppercase px-6 py-3.5 rounded-xl
hover:bg-[#FF4D00]/90 transition-colors mt-6">
            <FileDownload size={16} /> Export PDF Report
        </button>
    </motion.div>
}
</AnimatePresence>
</div>
</section>);

```

```

}

```

PavementAnalysis.jsx

```

import React, { useState, useRef, useEffect } from "react";
import { BarChart, Bar, XAxis, YAxis, Tooltip, ResponsiveContainer, Cell
} from "recharts";
import { Search, Maximize2, Minimize2, X, FileDownload, Building2 } from
"lucide-react";
import { AnimatePresence } from "framer-motion";
import { exportPavementAnalysisPDF } from "@lib/pdfExport";
import { getAnalysisCities } from "@lib/cityDatabase";
import { useCitySync } from "@hooks/useCitySync";
import CityAdmin from "../CityAdmin";

const ASPHALT_IMG =
"https://media.base44.com/images/public/6a3d5093b397842fc6d30258/2818e940b_gen
erated_ee4f442c.png";

// Full city data from Excel – broken out by road subtype
const cityData = [
{
    city: "APWA Standard", state: "Standard",
    residential: {
        access: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" Solid
Slab' },
        local: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" Solid
Slab' },
        collector: { asphalt: '9" (7" Base + 2" Surf)', concrete: '7" Solid
Slab' }
    },
},

```

```

        collector: {
            residential: { asphalt: '9" (7" Base + 2" Surf)', concrete: '7"
Solid Slab' },
            commercial: { asphalt: '9" (7" Base + 2" Surf)', concrete: '7" Solid
Slab' },
            industrial: { asphalt: '11" (9" Base + 2" Surf)', concrete: '8"
Solid Slab' }
        },
        arterial: {
            minor: { asphalt: '11" (9" Base + 2" Surf)', concrete: '8" Solid
Slab' },
            major: { asphalt: '12" (10" Base + 2" Surf)', concrete: '9" Solid
Slab' }
        },
        costs: { res_a: 2241888, res_c: 1848000, col_a: 2987400, col_c:
2987400, art_a: 5119488, art_c: 5174300 }
    },
    {
        city: "Overland Park", state: "KS",
        residential: {
            access: { asphalt: '8" (6" Base + 2" Surf)', concrete: '7" Slab + 4"
Rock Base' },
            local: { asphalt: '8" (6" Base + 2" Surf)', concrete: '7" Slab + 4"
Rock Base' },
            collector: { asphalt: '9" (7" Base + 2" Surf)', concrete: '8" Slab +
4" Rock Base' }
        },
        collector: {
            residential: { asphalt: '9" (7" Base + 2" Surf)', concrete: '8" Slab
+ 4" Rock Base' },
            commercial: { asphalt: '10" (8" Base + 2" Surf)', concrete: '8" Slab
+ 4" Rock Base' },
            industrial: { asphalt: '10" (8" Base + 2" Surf)', concrete: '8" Slab
+ 4" Rock Base' }
        },
        arterial: {
            minor: { asphalt: '-', concrete: '-' },
            major: { asphalt: '-', concrete: '-' }
        },
        costs: { res_a: 2241888, res_c: 2217600, col_a: 2987400, col_c:
3136320, art_a: 5119488, art_c: 5617820 }
    },

```

```

{
  city: "Lenexa", state: "KS",
  residential: {
    access: { asphalt: '8" (4" Base + 2" Int + 2" Surf)', concrete: '6"
Solid Slab' },
    local: { asphalt: '8" (4" Base + 2" Int + 2" Surf)', concrete: '6"
Solid Slab' },
    collector: { asphalt: '9" (7" Base + 2" Surf)', concrete: '8" Solid
Slab' }
  },
  collector: {
    residential: { asphalt: '9" (7" Base + 2" Surf)', concrete: '8"
Solid Slab' },
    commercial: { asphalt: '9" (7" Base + 2" Surf)', concrete: '8" Solid
Slab' },
    industrial: { asphalt: '11" (9" Base + 2" Surf)', concrete: '10"
Solid Slab' }
  },
  arterial: {
    minor: { asphalt: '11" (9" + 2" Surf)', concrete: '10" Solid Slab'
},
    major: { asphalt: '12" (10" Base + 2" Surf)', concrete: '10" Solid
Slab' }
  },
  costs: { res_a: 2241888, res_c: 1848000, col_a: 2987400, col_c:
3041280, art_a: 5119488, art_c: null }
},
{
  city: "Shawnee", state: "KS",
  residential: {
    access: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" Solid
Slab' },
    local: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" Solid
Slab' },
    collector: { asphalt: '9" (7" Base + 2" Surf)', concrete: '8" Solid
Slab' }
  },
  collector: {
    residential: { asphalt: '9" (7" Base + 2" Surf)', concrete: '8"
Solid Slab' },
    commercial: { asphalt: '10" (8" Base + 2" Surf)', concrete: '8"
Solid Slab' },

```

```
        industrial: { asphalt: '10" (8" Base + 2" Surf)', concrete: '8"
Solid Slab' }
    },
    arterial: {
        minor: { asphalt: '12" (10" Base + 2" Surf)', concrete: '10" Solid
Slab' },
        major: { asphalt: 'State Criteria', concrete: 'State Criteria' }
    },
    costs: { res_a: 2241888, res_c: 1848000, col_a: 3082440, col_c:
3041280, art_a: 5119488, art_c: 5396060 }
},
{
    city: "Olathe", state: "KS",
    residential: {
        access: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" Slab + 9"
Subgrade' },
        local: { asphalt: '8" (6" + 2" Surf)', concrete: '6" Slab + 9"
Subgrade' },
        collector: { asphalt: '10" (8" Base + 2" Surf)', concrete: '7" Slab
+ 9" Subgrade' }
    },
    collector: {
        residential: { asphalt: '10" (8" Base + 2" Surf)', concrete: '7"
Slab + 9" Subgrade' },
        commercial: { asphalt: '10" (8" Base + 2" Surf)', concrete: '7" Slab
+ 9" Subgrade' },
        industrial: { asphalt: '10" (8" Base + 2" Surf)', concrete: '7" Slab
+ 9" Subgrade' }
    },
    arterial: {
        minor: { asphalt: '12" (10" Base + 2" Surf)', concrete: '9" Slab +
6" Rock Base' },
        major: { asphalt: '12" (10" Base + 2" Surf)', concrete: '9" Slab +
6" Rock Base' }
    },
    costs: { res_a: 2241888, res_c: 1848000, col_a: 3082440, col_c:
2987400, art_a: 5119488, art_c: 5174300 }
},
{
    city: "Gardner", state: "KS",
    residential: {
```



```

        access: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" Slab + 9"
Subgrade' },
        local: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" + 9"
Subgrade' },
        collector: { asphalt: '10" (8" Base + 2" Surf)', concrete: '7" Slab
+ 9" Subgrade' }
    },
    collector: {
        residential: { asphalt: '10" (8" Base + 2" Surf)', concrete: '7"
Slab + 9" Subgrade' },
        commercial: { asphalt: '10" (8" Base + 2" Surf)', concrete: '7" Slab
+ 9" Subgrade' },
        industrial: { asphalt: '10" (8" Base + 2" Surf)', concrete: '7" Slab
+ 9" Subgrade' }
    },
    arterial: {
        minor: { asphalt: '12" (10" Base + 2" Surf)', concrete: '9" Slab +
9" Subgrade' },
        major: { asphalt: '12" (10" Base + 2" Surf)', concrete: '9" Slab +
9" Subgrade' }
    },
    costs: { res_a: 2241888, res_c: 1848000, col_a: 2987400, col_c:
2987400, art_a: 5119488, art_c: 5174300 }
    },
    {
        city: "Grandview", state: "MO",
        residential: {
            access: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" Solid
Slab' },
            local: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" Solid
Slab' },
            collector: { asphalt: '9" (7" Base + 2" Surf)', concrete: '7" Solid
Slab' }
        },
        collector: {
            residential: { asphalt: '9" (7" Base + 2" Surf)', concrete: '7"
Solid Slab' },
            commercial: { asphalt: '9" (7" Base + 2" Surf)', concrete: '7" Solid
Slab' },
            industrial: { asphalt: '9" (7" Base + 2" Surf)', concrete: '7" Solid
Slab' }
        },
    },

```

```

    arterial: {
      minor: { asphalt: '11" (9" Base + 2" Surf)', concrete: '8" Solid
Slab' },
      major: { asphalt: '12" (10" Base + 2" Surf)', concrete: '9" Solid
Slab' }
    },
    costs: { res_a: 2241888, res_c: 1848000, col_a: 2987400, col_c:
2987400, art_a: 5119488, art_c: 5174300 }
  },
  {
    city: "Blue Springs", state: "MO",
    residential: {
      access: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" Solid
Slab' },
      local: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" Solid
Slab' },
      collector: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" Solid
Slab' }
    },
    collector: {
      residential: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6"
Solid Slab' },
      commercial: { asphalt: '11" (9" Base + 2" Surf)', concrete: '7"
Solid Slab' },
      industrial: { asphalt: '11" (9" Base + 2" Surf)', concrete: '7"
Solid Slab' }
    },
    arterial: {
      minor: { asphalt: '11" (9" Base + 2" Surf)', concrete: '8" Solid
Slab' },
      major: { asphalt: '12" (10" Base + 2" Surf)', concrete: '9" Solid
Slab' }
    },
    costs: { res_a: 2241888, res_c: 1848000, col_a: null, col_c: 2376000,
art_a: null, art_c: null }
  },
  {
    city: "Lee's Summit", state: "MO",
    residential: {
      access: { asphalt: '6" (4" Base + 2" Surf) + 8" Rock Base',
concrete: '6" Solid Slab + 6" Rock Base' },

```

```

        local: { asphalt: '6" (4" Base + 2" Surf) + 8" Rock Base', concrete:
'6" Solid Slab + 6" Rock Base' },
        collector: { asphalt: '8" (6" Base + 2" Surf) + 8" Rock Base',
concrete: '6.5" Solid Slab + 6" Rock Base' }
    },
    collector: {
        residential: { asphalt: '8" (6" Base + 2" Surf) + 8" Rock Base',
concrete: '6.5" Solid Slab + 6" Rock Base' },
        commercial: { asphalt: '11" (9" Base + 2" Surf) + 8" Rock Base',
concrete: '8" Solid Slab + 6" Rock Base' },
        industrial: { asphalt: '11" (9" Base + 2" Surf) + 8" Rock Base',
concrete: '8" Solid Slab + 6" Rock Base' }
    },
    arterial: {
        minor: { asphalt: 'Project Specific', concrete: 'Project Specific'
},
        major: { asphalt: 'Project Specific', concrete: 'Project Specific' }
    },
    costs: { res_a: 2249280, res_c: 1958880, col_a: 3072936, col_c:
2708640, art_a: 5341248, art_c: 5396060 }
},
{
    city: "Kansas City", state: "MO",
    residential: {
        access: { asphalt: 'N/A', concrete: 'N/A' },
        local: { asphalt: '8" (6" Base + 2" Surf) + 6" Rock Base', concrete:
'6" Solid Slab + 6" Rock Base' },
        collector: { asphalt: '9" (7" Base + 2" Surf) + 6" Rock Base',
concrete: '7" Solid Slab + 6" Rock Base' }
    },
    collector: {
        residential: { asphalt: '9" (7" Base + 2" Surf) + 6" Rock Base',
concrete: '7" Solid Slab + 6" Rock Base' },
        commercial: { asphalt: '9" (7" Base + 2" Surf) + 6" Rock Base',
concrete: '7" Solid Slab + 6" Rock Base' },
        industrial: { asphalt: '9" (7" Base + 2" Surf) + 6" Rock Base',
concrete: '7" Solid Slab + 6" Rock Base' }
    },
    arterial: {
        minor: { asphalt: '11" (9" Base + 2" Surf) + 6" Rock Base',
concrete: '8" Solid Slab + 6" Rock Base' },

```

```

        major: { asphalt: '12" (10" Base + 2" Surf) + 6" Rock Base',
concrete: '9" Solid Slab + 6" Rock Base' }
    },
    costs: { res_a: 2352768, res_c: 1958880, col_a: 3129960, col_c:
2898720, art_a: 5119488, art_c: 5174300 }
    },
    {
        city: "Independence", state: "MO",
        residential: {
            access: { asphalt: 'N/A', concrete: 'N/A' },
            local: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" Solid
Slab' },
            collector: { asphalt: '9" (7" Base + 2" Surf)', concrete: '7" Solid
Slab' }
        },
        collector: {
            residential: { asphalt: '9" (7" Base + 2" Surf)', concrete: '7"
Solid Slab' },
            commercial: { asphalt: '9" (7" Base + 2" Surf)', concrete: '7" Solid
Slab' },
            industrial: { asphalt: '9" (7" Base + 2" Surf)', concrete: '7" Solid
Slab' }
        },
        arterial: {
            minor: { asphalt: '11" (9" Base + 2" Surf)', concrete: '8" Solid
Slab' },
            major: { asphalt: '12" (10" Base + 2" Surf)', concrete: '9" Solid
Slab' }
        },
        costs: { res_a: 2241888, res_c: 1848000, col_a: 3082440, col_c:
2987400, art_a: 5119488, art_c: 5174300 }
    },
    {
        city: "Merriam", state: "KS",
        residential: {
            access: { asphalt: '7" (4" Base + 2" Int + 1" Surf)', concrete: '6"
PCC Min' },
            local: { asphalt: '7" (4" Base + 2" Int + 1" Surf)', concrete: '6"
PCC Min' },
            collector: { asphalt: '8" (6" Base + 2" Surf)', concrete: '7" PCC' }
        },
        collector: {

```

```

    residential: { asphalt: '8" (6" Base + 2" Surf)', concrete: '7" PCC'
  },
    commercial: { asphalt: '8" (6" Base + 2" Surf)', concrete: '8" PCC'
  },
    industrial: { asphalt: '8" (6" Base + 2" Surf)', concrete: '8" PCC'
  }
},
arterial: {
  minor: { asphalt: '11" (9" Base + 2" Surf)', concrete: '8" PCC' },
  major: { asphalt: '12" (10" Base + 2" Surf)', concrete: '9" PCC' }
},
costs: { res_a: 2241888, res_c: 1848000, col_a: 2987400, col_c:
2987400, art_a: 5119488, art_c: 5174300 }
}];

```

```

const lifecycleDataByType = {
  residential: [
    { year: "Year 0", asphalt: 657888, concrete: 1478400 },
    { year: "Year 12", asphalt: 1185888, concrete: 1478400 },
    { year: "Year 15", asphalt: 1185888, concrete: 1636800 },
    { year: "Year 24", asphalt: 1713888, concrete: 1636000 },
    { year: "Year 25", asphalt: 1713888, concrete: 1848000 },
    { year: "Year 36", asphalt: 2241888, concrete: 1848000 }],
  collector: [
    { year: "Year 0", asphalt: 1045440, concrete: 2280960 },
    { year: "Year 12", asphalt: 1724440, concrete: 2280960 },
    { year: "Year 15", asphalt: 1724440, concrete: 2484660 },
    { year: "Year 24", asphalt: 2403440, concrete: 2484660 },
    { year: "Year 25", asphalt: 2403440, concrete: 2756160 },
    { year: "Year 36", asphalt: 3082440, concrete: 2756160 }],
  arterial: [
    { year: "Year 0", asphalt: 1951488, concrete: 4435200 },
    { year: "Year 12", asphalt: 3007488, concrete: 4435200 },
    { year: "Year 15", asphalt: 3007488, concrete: 4752000 },
    { year: "Year 24", asphalt: 4063488, concrete: 4752000 },
    { year: "Year 25", asphalt: 4063488, concrete: 5174300 },
    { year: "Year 36", asphalt: 5119488, concrete: 5174300 }]]
};

```

```

const roadTypeConfig = {
  residential: {
    label: "Residential",
    subtypes: [
      { key: "access", label: "Access" },
      { key: "local", label: "Local" },
      { key: "collector", label: "Collector" }],

    costKey_a: "res_a", costKey_c: "res_c"
  },
  collector: {
    label: "Collector",
    subtypes: [
      { key: "residential", label: "Residential" },
      { key: "commercial", label: "Commercial" },
      { key: "industrial", label: "Industrial" }],

    costKey_a: "col_a", costKey_c: "col_c"
  },
  arterial: {
    label: "Arterial",
    subtypes: [
      { key: "minor", label: "Minor" },
      { key: "major", label: "Major" }],

    costKey_a: "art_a", costKey_c: "art_c"
  }
};

function formatCost(v) {
  if (!v) return "-";
  if (v >= 1000000000000) return `$$${(v / 1000000000000).toFixed(2)}T`;
  if (v >= 1000000000) return `$$${(v / 1000000000).toFixed(2)}B`;
  if (v >= 1000000) return `$$${(v / 1000000).toFixed(2)}M`;
  if (v >= 1000) return `$$${(v / 1000).toFixed(0)}K`;
  return `$$${v}`;
}

const CustomTooltip = ({ active, payload, label }) => {
  if (!active || !payload?.length) return null;
  return (

```

```

    <div className="bg-[#1a1a1a] border border-white/10 px-4 py-3
font-mono text-xs">
      <p className="text-[#F2F0E9]/60 mb-2">{label}</p>
      {payload.map((p) =>
        <p key={p.dataKey} style={{ color: p.color }}>{p.name}:
{formatCost(p.value)}</p>
      )}
    </div>;

};

export default function PavementsAnalysis() {
  useCitySync();
  const [roadType, setRoadType] = useState("residential");
  const [subtype, setSubtype] = useState("local");
  const [search, setSearch] = useState("");
  const [fullscreen, setFullscreen] = useState(false);
  const [showCityAdmin, setShowCityAdmin] = useState(false);
  const [bypassed, setBypassed] = useState(() => { try { return
localStorage.getItem("kcp_bypassed") === "true"; } catch { return false; } });

  useEffect(() => {
    const handler = () => { try {
setBypassed(localStorage.getItem("kcp_bypassed") === "true"); } catch {} };
    window.addEventListener("kcp_bypass_change", handler);
    return () => window.removeEventListener("kcp_bypass_change",
handler);
  }, []);
  const sectionRef = useRef(null);

  const config = roadTypeConfig[roadType];
  const lifecycleData = lifecycleDataByType[roadType];

  const allCityData = getAnalysisCities();
  const filteredData = allCityData.filter((row) => {
    const q = search.toLowerCase();
    if (!q) return true;
    const spec = row[roadType]?.[subtype];
    return (
      row.city.toLowerCase().includes(q) ||
      row.state.toLowerCase().includes(q) ||
      (spec?.asphalt || "").toLowerCase().includes(q) ||

```

```

        (spec?.concrete || "").toLowerCase().includes(q));

    });

    const handleRoadType = (type) => {
      setRoadType(type);
      const firstSub = roadTypeConfig[type].subtypes[0].key;
      setSubtype(firstSub);
    };

    const content =
    <div className={` ${fullscreen ? "bg-[#111111] min-h-screen p-6 lg:p-10" : ""}`}>
      { /* Header */ }
      <div className="flex items-start justify-between mb-2 gap-4">
        <div>
          <div className="flex items-center gap-3 mb-4">
            <div className="w-8 h-px bg-[#FF4D00]" />
            <span className="font-mono text-xs tracking-[0.3em] text-[#FF4D00] uppercase">Data Platform</span>
          </div>
          <h2 className="font-heading font-bold text-[#F2F0E9] text-3xl sm:text-4xl lg:text-5xl tracking-tight mb-1">
            KC Pavement Analysis
          </h2>
          <p className="font-mono text-xs text-[#F2F0E9]/25 tracking-wider mb-4">by Bobby Youan & Danny Will</p>
          <p className="text-[#F2F0E9]/50 text-lg max-w-3xl mb-3 leading-relaxed">
            Comprehensive pavement specification and lifecycle cost data
            for cities across Kansas and Missouri.
          </p>
          <p className="font-mono text-[10px] text-[#4A5568] tracking-wide mb-8">* All cost estimates are based on bid tabs and are for
            planning purposes only.</p>
        </div>
        <div className="flex gap-2 shrink-0 mt-2">
          <button onClick={() => exportPavementAnalysisPDF(roadType,
            subtype, filteredData, config, lifecycleData)}
            className="w-10 h-10 border border-white/10 flex
            items-center justify-center text-[#4A5568] hover:text-[#FF4D00]
            hover:border-[#FF4D00] transition-colors"

```



```

        title="Export PDF Report">
        <FileDown size={16} />
    </button>
    {bypassed && (
        <button onClick={() => setShowCityAdmin(true)}
            className="w-10 h-10 border border-white/10 flex
items-center justify-center text-[#4A5568] hover:text-[#FF4D00]
hover:border-[#FF4D00] transition-colors" title="Manage Cities">
            <Building2 size={16} />
        </button>
    )}
    <button onClick={() => setFullscreen(!fullscreen)}
        className="w-10 h-10 border border-white/10 flex
items-center justify-center text-[#4A5568] hover:text-[#FF4D00]
hover:border-[#FF4D00] transition-colors">
        {fullscreen ? <Minimize2 size={16} /> : <Maximize2 size={16}
/>}
    </button>
</div>
</div>

{/* Google-style search bar */}
<div className="relative mb-10 max-w-2xl">
    <div className="relative flex items-center bg-white/[0.06]
border border-white/15 hover:border-white/25 focus-within:border-[#FF4D00]/60
focus-within:bg-white/[0.08] transition-all duration-200 rounded-full px-5
py-3.5 gap-3 shadow-lg">
        <Search size={18} className="text-[#4A5568] shrink-0" />
        <input
            type="text"
            value={search}
            onChange={(e) => setSearch(e.target.value)}
            placeholder="Search any city, road type, spec thickness..."
            className="flex-1 bg-transparent font-body text-base
text-[#F2F0E9] placeholder-[#4A5568]/70 focus:outline-none" />

        {search &&
            <button onClick={() => setSearch("")} className="text-[#4A5568]
hover:text-[#F2F0E9] transition-colors">
                <X size={16} />
            </button>
        }
    </div>
</div>

```

```

    </div>
    {search &&
    <p className="font-mono text-[10px] text-[#4A5568] mt-2
pl-5">{filteredData.length} result{filteredData.length !== 1 ? "s" : ""} for
"{search}"</p>
    }
  </div>

  {/* Road Type Tabs */}
  <div className="flex gap-1 mb-4">
    {Object.entries(roadTypeConfig).map(([key, cfg]) =>
    <button key={key} onClick={() => handleRoadType(key)}
    className={`font-mono text-xs tracking-wider uppercase px-6 py-3
transition-colors min-h-[48px] ${roadType === key ? "bg-[#FF4D00] text-white"
: "bg-white/5 text-[#F2F0E9]/50 hover:text-[#F2F0E9]}"}`>
      {cfg.label}
    </button>
    )}
  </div>

  {/* Subtype Tabs */}
  <div className="flex gap-1 mb-8">
    {config.subtypes.map((s) =>
    <button key={s.key} onClick={() => setSubtype(s.key)}
    className={`font-mono text-[10px] tracking-wider uppercase px-4
py-2 transition-colors border ${subtype === s.key ? "border-[#FF4D00]
text-[#FF4D00] bg-[#FF4D00]/10" : "border-white/10 text-[#4A5568]
hover:text-[#F2F0E9]/60"}`>
      {s.label}
    </button>
    )}
  </div>

  {/* Table */}
  <div className="border border-white/10 mb-16 overflow-x-auto">
    <div className="min-w-[700px]">
      <div className="grid grid-cols-5 gap-px bg-white/5">
        [{"City", "State", "Asphalt Spec", "Concrete Spec", `30-yr
Asphalt Cost *`}.map((h) =>
        <div key={h} className="bg-[#111111] px-4 py-3">
          <span className="font-mono text-[10px] tracking-wider
text-[#4A5568] uppercase">{h}</span>

```

```

        </div>
    })
</div>
    {filteredData.length === 0 &&
<div className="px-6 py-8 text-center">
    <p className="font-mono text-xs text-[#4A5568]">No results
for "{search}"</p>
    </div>
}
    {filteredData.map((row) => {
    const spec = row[roadType]?.[subtype] || {};
    const costA = row.costs[config.costKey_a];
    return (
        <div key={row.city} className="grid grid-cols-5 gap-px
w-full bg-transparent hover:bg-white/[0.02] transition-colors">
            <div className="px-4 py-4 border-t border-white/5">
                <span className="font-heading text-sm text-[#F2F0E9]
font-medium">{row.city}</span>
            </div>
            <div className="px-4 py-4 border-t border-white/5">
                <span className="font-mono text-xs
text-[#4A5568]">{row.state}</span>
            </div>
            <div className="px-4 py-4 border-t border-white/5">
                <span className="font-mono text-sm
text-[#FF4D00]">{spec.asphalt || "-"}</span>
            </div>
            <div className="px-4 py-4 border-t border-white/5">
                <span className="font-mono text-sm
text-[#4A5568]">{spec.concrete || "-"}</span>
            </div>
            <div className="px-4 py-4 border-t border-white/5">
                <span className="font-mono text-sm
text-[#F2F0E9]/60">{formatCost(costA)}</span>
            </div>
        </div>);
    })
    </div>
</div>
    <p className="font-mono text-[9px] text-[#4A5568]/60 mt-2">* Cost
estimates based on bid tabs - for planning purposes only.</p>

```

```

    { /* Lifecycle chart + findings */ }
    <div className="grid lg:grid-cols-2 gap-12 items-start">
      <div>
        <h3 className="font-heading font-semibold text-[#F2F0E9]
text-xl lg:text-2xl mb-2">
          {config.label} Lifecycle Cost
        </h3>
        <p className="font-mono text-xs text-[#4A5568] tracking-wider
mb-8">

          1-MILE COMPARISON - ASPHALT VS CONCRETE - 36 YEAR PROJECTION
        </p>
        <div className="h-72">
          <ResponsiveContainer width="100%" height="100%">
            <BarChart data={lifecycleData} barGap={4}>
              <XAxis dataKey="year" tick={{ fill: "#4A5568", fontSize:
10, fontFamily: "JetBrains Mono" }} axisLine={{ stroke: "#4A5568",
strokeWidth: 0.5 }} tickLine={false} />
              <YAxis tickFormatter={formatCost} tick={{ fill:
"#4A5568", fontSize: 10, fontFamily: "JetBrains Mono" }} axisLine={false}
tickLine={false} />
              <Tooltip content={<CustomTooltip />} />
              <Bar dataKey="asphalt" name="Asphalt" radius={[2, 2, 0,
0]]>
                {lifecycleData.map((_, i) => <Cell key={i}
fill="#FF4D00" />)}
              </Bar>
              <Bar dataKey="concrete" name="Concrete" radius={[2, 2,
0, 0]]>
                {lifecycleData.map((_, i) => <Cell key={i}
fill="#4A5568" />)}
              </Bar>
            </BarChart>
          </ResponsiveContainer>
        </div>
        <p className="font-mono text-[9px] text-[#4A5568]/60 mt-3">*
Cost estimates based on bid tabs - for planning purposes only.</p>
      </div>

      <div className="space-y-6">
        <div className="border border-white/10 p-6">

```

```

        <span className="font-mono text-[10px] tracking-wider
text-[#4A5568] uppercase">Key Findings</span>
        <p className="font-heading text-[#F2F0E9] text-lg mt-2
font-semibold">
            Asphalt achieves cost parity with concrete at Year 36
        </p>
        <p className="text-[#F2F0E9]/50 text-sm mt-2
leading-relaxed">
            While asphalt has lower initial construction costs, the
maintenance cycle brings total lifecycle costs to near-equivalent levels over
36 years. Optimal choice depends on traffic volumes, subgrade conditions, and
municipal budgets.
        </p>
    </div>
    <div className="grid grid-cols-2 gap-4">
        <div className="border border-white/10 p-5">
            <span className="font-mono text-[10px] tracking-wider
text-[#4A5568] uppercase">Asphalt Upfront</span>
            <p className="font-heading text-[#FF4D00] text-2xl
font-bold mt-1">{formatCost(lifecycleData[0].asphalt)}</p>
            <p className="font-mono text-[10px] text-[#4A5568]
mt-1">PER MILE / {config.label.toUpperCase()}</p>
            <p className="font-mono text-[8px] text-[#4A5568]/60
mt-1">* bid-tab estimate</p>
        </div>
        <div className="border border-white/10 p-5">
            <span className="font-mono text-[10px] tracking-wider
text-[#4A5568] uppercase">Concrete Upfront</span>
            <p className="font-heading text-[#F2F0E9] text-2xl
font-bold mt-1">{formatCost(lifecycleData[0].concrete)}</p>
            <p className="font-mono text-[10px] text-[#4A5568]
mt-1">PER MILE / {config.label.toUpperCase()}</p>
            <p className="font-mono text-[8px] text-[#4A5568]/60
mt-1">* bid-tab estimate</p>
        </div>
    </div>
    <div className="border border-[#FF4D00]/30 bg-[#FF4D00]/5
p-5">
        <span className="font-mono text-[10px] tracking-wider
text-[#FF4D00] uppercase">Maintenance Strategy</span>
        <p className="text-[#F2F0E9]/70 text-sm mt-2
leading-relaxed">

```

Asphalt: UV oxidation & moisture infiltration mitigated with sacrificial wearing course replacement at 12-year intervals.

Concrete: Joint sealant degradation & subgrade pumping addressed through elastomeric joint sealing and structural panel patches.

```

    </p>
    <p className="text-[#F2F0E9]/70 text-sm mt-1 leading-relaxed">
        <strong className="text-[#F2F0E9]">Concrete:</strong>
        Joint sealant degradation & subgrade pumping addressed through elastomeric
        joint sealing and structural panel patches.
    </p>
</div>
</div>
</div>
</div>;

if (fullscreen) {
    return (
        <div className="fixed inset-0 z-[90] overflow-y-auto bg-[#111111]">
            <div className="max-w-7xl mx-auto px-6 py-10">
                {content}
            </div>
        </div>);
}

return (
    <section id="pavements" className="py-24 lg:py-32 relative"
ref={sectionRef}>
        <div className="absolute inset-0 opacity-10">
            <img src={ASPHALT_IMG} alt="" className="w-full h-full object-cover" />
        </div>
        <div className="absolute inset-0 bg-[#111111]/95" />
        <div className="relative z-10 max-w-7xl mx-auto px-6 lg:px-8">
            {content}
        </div>
        <AnimatePresence>
            {showCityAdmin && <CityAdmin onClose={() =>
setShowCityAdmin(false)} />}
        </AnimatePresence>
    </section>
);
```

```

    </section>
  );
}

```

PavoGaurd.jsx

```

import React, { useState } from "react";
import { motion } from "framer-motion";
import { X, Lock, ArrowRight } from "lucide-react";

const GUARD_PASSWORD = "THESTANDARD";

function HardHatIcon({ size = 48, className = "" }) {
  return (
    <svg width={size} height={size} viewBox="0 0 24 24" fill="none"
    className={className}>
      <path d="M12 2C8 2 5 5.5 5 9v1H3v2h18v-2h-2V9C19 5.5 16 2 12 2z"
      fill="currentColor" opacity="0.9"/>
      <rect x="2" y="12" width="20" height="3" rx="1.5"
      fill="currentColor"/>
      <path d="M5 15h14l-1 4H6l-1-4z" fill="currentColor"
      opacity="0.7"/>
    </svg>
  );
}

export default function PavoGuard({ onClose, onUnlock }) {
  const [password, setPassword] = useState("");
  const [error, setError] = useState(false);

  const handleSubmit = (e) => {
    e.preventDefault();
    if (password === GUARD_PASSWORD) {
      onUnlock();
    } else {
      setError(true);
      setPassword("");
      setTimeout(() => setError(false), 2000);
    }
  };

  return (
    <motion.div
      initial={{ opacity: 0 }}

```

```

        animate={{ opacity: 1 }}
        exit={{ opacity: 0 }}
        className="fixed inset-0 z-[260] bg-black/85 flex items-center
justify-center p-4"
        onClick={onClose}
    >
    <motion.div
        initial={{ scale: 0.9, opacity: 0 }}
        animate={{ scale: 1, opacity: 1 }}
        exit={{ scale: 0.9, opacity: 0 }}
        onClick={e => e.stopPropagation()}
        className="relative bg-[#111111] border border-[#FF4D00]/30
rounded-xl w-full max-w-sm p-8 text-center"
    >
        <button onClick={onClose} className="absolute top-4 right-4
text-[#4A5568] hover:text-[#F2F0E9] transition-colors">
            <X size={18} />
        </button>

        <motion.div
            animate={{ y: [0, -6, 0] }}
            transition={{ duration: 2, repeat: Infinity, ease: "easeInOut"
}}

            className="w-20 h-20 mx-auto mb-4 rounded-full bg-[#FF4D00]/20
border border-[#FF4D00]/40 flex items-center justify-center"
        >
            <HardHatIcon size={40} className="text-[#FF4D00]" />
        </motion.div>

        <h3 className="font-heading font-bold text-[#F2F0E9] text-lg
mb-1">Pavo is standing guard</h3>
        <p className="font-mono text-xs text-[#4A5568] mb-6">Enter the
second password to access City Admin</p>

        <form onSubmit={handleSubmit} className="space-y-3">
            <div className="relative">
                <Lock size={14} className="absolute left-4 top-1/2
-translate-y-1/2 text-[#4A5568]" />
                <input
                    type="password"
                    value={password}
                    onChange={e => setPassword(e.target.value)}

```



```

        placeholder="Password"
        autoFocus
        className={`w-full bg-[#1a1a1a] border rounded-lg pl-11
pr-4 py-3.5 text-sm text-[#F2F0E9] font-mono focus:outline-none
transition-colors ${error ? "border-red-500/60 bg-red-500/5" :
"border-white/15 focus:border-[#FF4D00]}"}`}
      />
    </div>

    {error && (
      <motion.p initial={{ opacity: 0 }} animate={{ opacity: 1 }}
className="font-mono text-xs text-red-400">
        Access denied. Wrong password.
      </motion.p>
    )}

    <button
      type="submit"
      disabled={!password.trim()}
      className="w-full flex items-center justify-center gap-2
bg-[#FF4D00] text-white font-mono text-sm tracking-wider uppercase py-3.5
rounded-lg hover:bg-[#FF4D00]/90 transition-colors disabled:opacity-30"
    >
      Enter <ArrowRight size={14} />
    </button>
  </form>
</motion.div>
</motion.div>
);
}

```

Services.jsx

```

import React, { useState } from "react";
import { motion, AnimatePresence } from "framer-motion";
import { ChevronRight, Landmark, MapPin, Radio, HardHat, TreePine } from
"lucide-react";

const IMAGES = {
  publicworks:
    "https://media.base44.com/images/public/6a3d5093b397842fc6d30258/4d26eff77_gen
erated_81fad6e3.png",

```

```
      development:
        "https://media.base44.com/images/public/6a3d5093b397842fc6d30258/4a47a4bcf_generated_01712b88.png",
      surveying:
        "https://media.base44.com/images/public/6a3d5093b397842fc6d30258/e6ac4f6de_generated_2ecb522f.png",
      telecom:
        "https://media.base44.com/images/public/6a3d5093b397842fc6d30258/6ef771916_generated_897c9c20.png",
      construction:
        "https://media.base44.com/images/public/6a3d5093b397842fc6d30258/0439748dd_generated_62685149.png",
    };
```

```
const services = [
  {
    id: "publicworks",
    num: "01",
    title: "Public Works",
    icon: Landmark,
    brief: "Infrastructure design for municipalities – storm water management, roadway improvements, utility relocations, and ADA compliance upgrades across the KC metro.",
    specs: ["Storm Water Systems", "Roadway Design", "Utility Coordination", "ADA Compliance"],
  },
  {
    id: "development",
    num: "02",
    title: "Development",
    icon: TreePine,
    brief: "Site development engineering from concept to construction – grading plans, drainage studies, erosion control, and subdivision platting for residential and commercial projects.",
    specs: ["Site Grading", "Drainage Studies", "Erosion Control", "Subdivision Platting"],
  },
  {
    id: "surveying",
    num: "03",
    title: "Surveying",
    icon: MapPin,
```

```

        brief: "Precision surveying services including ALTA surveys,
boundary surveys, topographic mapping, and construction staking using GPS and
robotic total station technology.",
        specs: ["ALTA Surveys", "Boundary Surveys", "Topographic Mapping",
"Construction Staking"],
    },
    {
        id: "telecom",
        num: "04",
        title: "Telecom",
        icon: Radio,
        brief: "Telecommunications infrastructure engineering – fiber optic
route design, conduit placement, utility coordination, and right-of-way
acquisition for network expansion.",
        specs: ["Fiber Route Design", "Conduit Systems", "Utility
Coordination", "ROW Acquisition"],
    },
    {
        id: "construction",
        num: "05",
        title: "Construction",
        icon: HardHat,
        brief: "Construction management and inspection services ensuring
quality control, schedule adherence, and specification compliance on civil
infrastructure projects.",
        specs: ["Quality Control", "Project Inspection", "Schedule
Management", "Spec Compliance"],
    },
];

```

```

export default function Services() {
    const [expanded, setExpanded] = useState(null);

    return (
        <section id="services" className="py-24 lg:py-32 grid-overlay">
            <div className="max-w-7xl mx-auto px-6 lg:px-8">
                <div className="flex items-center gap-3 mb-4">
                    <div className="w-8 h-px bg-[#FF4D00]" />
                    <span className="font-mono text-xs tracking-[0.3em]
text-[#FF4D00] uppercase">
                        Our Expertise
                    </span>
                </div>
            </div>
        </section>
    );
}

```

```

    </div>
    <h2 className="font-heading font-bold text-[#F2F0E9] text-3xl
sm:text-4xl lg:text-5xl tracking-tight mb-16">
      Service Monoliths
    </h2>

    <div className="flex flex-col gap-px">
      {services.map((service) => {
        const isOpen = expanded === service.id;
        const Icon = service.icon;
        return (
          <div key={service.id} className="border border-white/5
bg-[#111111]/50">
            <button
              onClick={() => setExpanded(isOpen ? null :
service.id)}
              className="w-full flex items-center gap-4 sm:gap-6
lg:gap-8 px-6 lg:px-10 py-6 lg:py-8 group text-left min-h-[80px]"
            >
              <span className="font-mono text-xs text-[#4A5568]
tracking-wider">
                {service.num}
              </span>
              <div className="w-10 h-10 border border-white/10 flex
items-center justify-center group-hover:border-[#FF4D00] transition-colors
shrink-0">
                <Icon size={18} className="text-[#F2F0E9]/40
group-hover:text-[#FF4D00] transition-colors" />
              </div>
              <h3 className="font-heading font-semibold
text-[#F2F0E9] text-xl lg:text-2xl group-hover:text-[#FF4D00]
transition-colors flex-1">
                {service.title}
              </h3>
              <ChevronRight
                size={20}
                className={`text-[#F2F0E9]/30 transition-transform
duration-300 shrink-0 ${
                  isOpen ? "rotate-90 text-[#FF4D00]" : ""
                }`
              />
            </button>

```

```

<AnimatePresence>
  {isOpen && (
    <motion.div
      initial={{ height: 0, opacity: 0 }}
      animate={{ height: "auto", opacity: 1 }}
      exit={{ height: 0, opacity: 0 }}
      transition={{ duration: 0.3 }}
      className="overflow-hidden"
    >
      <div className="px-6 lg:px-10 pb-8 flex flex-col
lg:flex-row gap-8">
        <div className="flex-1">
          <p className="text-[#F2F0E9]/60 text-base
lg:text-lg leading-relaxed mb-6">
            {service.brief}
          </p>
          <div className="grid grid-cols-2 gap-3">
            {service.specs.map((spec) => (
              <div
                key={spec}
                className="font-mono text-xs
tracking-wider text-[#F2F0E9]/40 flex items-center gap-2"
              >
                <div className="w-1 h-1 bg-[#FF4D00]" />
                {spec}
              </div>
            ))}
          </div>
        </div>
        <div className="lg:w-80 h-48 lg:h-auto
overflow-hidden">
          <img
            src={IMAGES[service.id]}
            alt={service.title}
            className="w-full h-full object-cover
grayscale hover:grayscale-0 transition-all duration-700"
          />
        </div>
      </div>
    </motion.div>
  )}

```

```

        </AnimatePresence>
      </div>
    );
  })
</div>
</div>
</section>
);
}

```

WhyBHC.jsx

```

import React from "react";
import { motion } from "framer-motion";
import { Database, Target, Layers, Clock } from "lucide-react";

const reasons = [
  {
    icon: Database,
    kpi: "16+",
    kpiLabel: "Cities Analyzed",
    title: "Data-Driven Decisions",
    desc: "Our KC Pavements Analysis platform compiles pavement
specifications, lifecycle costs, and maintenance strategies across 16+ Kansas
City metro municipalities – turning raw data into infrastructure
intelligence.",
  },
  {
    icon: Target,
    kpi: "5",
    kpiLabel: "Disciplines",
    title: "Multi-Discipline Capability",
    desc: "From surveying and telecom to public works and construction
management – BHC delivers integrated civil engineering services without the
overhead of coordinating multiple firms.",
  },
  {
    icon: Layers,
    kpi: "36",
    kpiLabel: "Year Projections",
    title: "Lifecycle Cost Expertise",
    desc: "We model 36-year pavement lifecycle costs comparing asphalt
and concrete for residential, collector, and arterial roads – giving engineers
and planners the full financial picture before ground breaks.",
  },

```

```

    },
    {
      icon: Clock,
      kpi: "9",
      kpiLabel: "Min from KC Core",
      title: "KC Metro Native",
      desc: "Headquartered in the heart of the Kansas City metro with
coverage spanning from Leawood to Leavenworth and Grandview to Liberty. We
know the local codes, the municipalities, and the ground conditions.",
    },
  ],
];

export default function WhyBHC() {
  return (
    <section id="why-bhc" className="py-24 lg:py-32 grid-overlay">
      <div className="max-w-7xl mx-auto px-6 lg:px-8">
        <div className="flex items-center gap-3 mb-4">
          <div className="w-8 h-px bg-[#FF4D00]" />
          <span className="font-mono text-xs tracking-[0.3em]
text-[#FF4D00] uppercase">
            Differentiators
          </span>
        </div>
        <h2 className="font-heading font-bold text-[#F2F0E9] text-3xl
sm:text-4xl lg:text-5xl tracking-tight mb-16">
          Why BHC
        </h2>

        <div className="grid md:grid-cols-2 gap-px bg-white/5">
          {reasons.map((item, i) => {
            const Icon = item.icon;
            return (
              <motion.div
                key={i}
                initial={{ opacity: 0, y: 20 }}
                whileInView={{ opacity: 1, y: 0 }}
                viewport={{ once: true }}
                transition={{ delay: i * 0.1 }}
                className="bg-[#111111] p-8 lg:p-10 group
hover:bg-[#FF4D00]/[0.03] transition-colors"
              >
                <div className="flex items-start justify-between mb-6">

```

```

        <div className="w-12 h-12 border border-white/10 flex
items-center justify-center group-hover:border-[#FF4D00]/30
transition-colors">
            <Icon size={20} className="text-[#FF4D00]" />
        </div>
        <div className="text-right">
            <p className="font-heading font-bold text-[#FF4D00]
text-3xl">{item.kpi}</p>
            <p className="font-mono text-[10px] tracking-wider
text-[#4A5568] uppercase">{item.kpiLabel}</p>
        </div>
    </div>
    <h3 className="font-heading font-semibold text-[#F2F0E9]
text-lg mb-3">{item.title}</h3>
    <p className="text-[#F2F0E9]/50 text-sm
leading-relaxed">{item.desc}</p>
</motion.div>
    );
  })
</div>
</div>
</section>
);
}

```

ui

accordion.jsx

```

import * as React from "react"
import * as AccordionPrimitive from "@radix-ui/react-accordion"
import { ChevronDown } from "lucide-react"

import { cn } from "@/lib/utils"

const Accordion = AccordionPrimitive.Root

const AccordionItem = React.forwardRef(({ className, ...props },
ref) => (
  <AccordionPrimitive.Item ref={ref} className={cn("border-b",
className)} {...props} />
))
AccordionItem.displayName = "AccordionItem"

```



```

    const AccordionTrigger = React.forwardRef(({ className, children,
...props }, ref) => (
    <AccordionPrimitive.Header className="flex">
      <AccordionPrimitive.Trigger
        ref={ref}
        className={cn(
          "flex flex-1 items-center justify-between py-4 text-sm
font-medium transition-all hover:underline text-left
[&[data-state=open]>svg]:rotate-180",
          className
        )}
        {...props}>
        {children}
        <ChevronDown
          className="h-4 w-4 shrink-0 text-muted-foreground
transition-transform duration-200" />
        </AccordionPrimitive.Trigger>
      </AccordionPrimitive.Header>
    ))
    AccordionTrigger.displayName =
AccordionPrimitive.Trigger.displayName

    const AccordionContent = React.forwardRef(({ className, children,
...props }, ref) => (
    <AccordionPrimitive.Content
      ref={ref}
      className="overflow-hidden text-sm
data-[state=closed]:animate-accordion-up
data-[state=open]:animate-accordion-down"
      {...props}>
      <div className={cn("pb-4 pt-0", className)}>{children}</div>
    </AccordionPrimitive.Content>
    ))
    AccordionContent.displayName =
AccordionPrimitive.Content.displayName

    export { Accordion, AccordionItem, AccordionTrigger,
AccordionContent }

```

alert-dialog.jsx

```
import * as React from "react"
import * as AlertDialogPrimitive from
"@radix-ui/react-alert-dialog"

import { cn } from "@lib/utils"
import { buttonVariants } from "@components/ui/button"

const AlertDialog = AlertDialogPrimitive.Root

const AlertDialogTrigger = AlertDialogPrimitive.Trigger

const AlertDialogPortal = AlertDialogPrimitive.Portal

const AlertDialogOverlay = React.forwardRef(({ className, ...props
}, ref) => (
  <AlertDialogPrimitive.Overlay
    className={cn(
      "fixed inset-0 z-50 bg-black/80 data-[state=open]:animate-in
data-[state=closed]:animate-out data-[state=closed]:fade-out-0
data-[state=open]:fade-in-0",
      className
    )}
    {...props}
    ref={ref} />
))
AlertDialogOverlay.displayName =
AlertDialogPrimitive.Overlay.displayName

const AlertDialogContent = React.forwardRef(({ className, ...props
}, ref) => (
  <AlertDialogPortal>
    <AlertDialogOverlay />
    <AlertDialogPrimitive.Content
      ref={ref}
      className={cn(
        "fixed left-[50%] top-[50%] z-50 grid w-full max-w-lg
translate-x-[-50%] translate-y-[-50%] gap-4 border bg-background p-6
shadow-lg duration-200 data-[state=open]:animate-in
data-[state=closed]:animate-out data-[state=closed]:fade-out-0
data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95
data-[state=open]:zoom-in-95 data-[state=closed]:slide-out-to-left-1/2
```

```

data-[state=closed]:slide-out-to-top-[48%]
data-[state=open]:slide-in-from-left-1/2
data-[state=open]:slide-in-from-top-[48%] sm:rounded-lg",
      className
    )}
    {...props} />
  </AlertDialogPortal>
))
AlertDialogContent.displayName =
AlertDialogPrimitive.Content.displayName

const AlertDialogHeader = ({
  className,
  ...props
}) => (
  <div
    className={cn("flex flex-col space-y-2 text-center
sm:text-left", className)}
    {...props} />
  )
AlertDialogHeader.displayName = "AlertDialogHeader"

const AlertDialogFooter = ({
  className,
  ...props
}) => (
  <div
    className={cn("flex flex-col-reverse sm:flex-row
sm:justify-end sm:space-x-2", className)}
    {...props} />
  )
AlertDialogFooter.displayName = "AlertDialogFooter"

const AlertDialogTitle = React.forwardRef(({ className, ...props
}, ref) => (
  <AlertDialogPrimitive.Title ref={ref} className={cn("text-lg
font-semibold", className)} {...props} />
  )
  AlertDialogTitle.displayName =
AlertDialogPrimitive.Title.displayName

```

```

    const AlertDialogDescription = React.forwardRef(({ className,
...props }, ref) => (
    <AlertDialogPrimitive.Description
      ref={ref}
      className={cn("text-sm text-muted-foreground", className)}
      {...props} />
    ))
    AlertDialogDescription.displayName =
      AlertDialogPrimitive.Description.displayName

    const AlertDialogAction = React.forwardRef(({ className, ...props
}, ref) => (
    <AlertDialogPrimitive.Action ref={ref}
className={cn(buttonVariants(), className)} {...props} />
    ))
    AlertDialogAction.displayName =
      AlertDialogPrimitive.Action.displayName

    const AlertDialogCancel = React.forwardRef(({ className, ...props
}, ref) => (
    <AlertDialogPrimitive.Cancel
      ref={ref}
      className={cn(buttonVariants({ variant: "outline" }), "mt-2
sm:mt-0", className)}
      {...props} />
    ))
    AlertDialogCancel.displayName =
      AlertDialogPrimitive.Cancel.displayName

    export {
      AlertDialog,
      AlertDialogPortal,
      AlertDialogOverlay,
      AlertDialogTrigger,
      AlertDialogContent,
      AlertDialogHeader,
      AlertDialogFooter,
      AlertDialogTitle,
      AlertDialogDescription,
      AlertDialogAction,
      AlertDialogCancel,
    }

```

alert.jsx

```
import * as React from "react"
import { cva } from "class-variance-authority";

import { cn } from "@/lib/utils"

const alertVariants = cva(
  "relative w-full rounded-lg border px-4 py-3 text-sm
  [>svg+div]:translate-y-[-3px] [>svg]:absolute [>svg]:left-4
  [>svg]:top-4 [>svg]:text-foreground [>svg~*]:pl-7",
  {
    variants: {
      variant: {
        default: "bg-background text-foreground",
        destructive:
          "border-destructive/50 text-destructive
          dark:border-destructive [>svg]:text-destructive",
      },
    },
    defaultVariants: {
      variant: "default",
    },
  }
)

const Alert = React.forwardRef(({ className, variant, ...props },
ref) => (
  <div
    ref={ref}
    role="alert"
    className={cn(alertVariants({ variant }), className)}
    {...props} />
  ))
Alert.displayName = "Alert"

const AlertTitle = React.forwardRef(({ className, ...props }, ref)
=> (
  <h5
    ref={ref}
    className={cn("mb-1 font-medium leading-none tracking-tight",
className)} />
  )
)
```

```

        {...props} />
    ))
    AlertTitle.displayName = "AlertTitle"

    const AlertDescription = React.forwardRef(({ className, ...props
}, ref) => (
    <div
        ref={ref}
        className={cn("text-sm [&_p]:leading-relaxed", className)}
        {...props} />
    ))
    AlertDescription.displayName = "AlertDescription"

    export { Alert, AlertTitle, AlertDescription }

```

aspect.ratio.jsx

```

import * as AspectRatioPrimitive from
"@radix-ui/react-aspect-ratio"

const AspectRatio = AspectRatioPrimitive.Root

export { AspectRatio }

```

avatar.jsx

```

"use client"

import * as React from "react"
import * as AvatarPrimitive from "@radix-ui/react-avatar"

import { cn } from "@/lib/utils"

const Avatar = React.forwardRef(({ className, ...props }, ref) =>
(
    <AvatarPrimitive.Root
        ref={ref}
        className={cn("relative flex h-10 w-10 shrink-0
overflow-hidden rounded-full", className)}
        {...props} />
    ))
Avatar.displayName = AvatarPrimitive.Root.displayName

```

```

    const AvatarImage = React.forwardRef(({ className, ...props },
ref) => (
    <AvatarPrimitive.Image
      ref={ref}
      className={cn("aspect-square h-full w-full", className)}
      {...props} />
    ))
  AvatarImage.displayName = AvatarPrimitive.Image.displayName

  const AvatarFallback = React.forwardRef(({ className, ...props },
ref) => (
    <AvatarPrimitive.Fallback
      ref={ref}
      className={cn(
        "flex h-full w-full items-center justify-center rounded-full
bg-muted",
        className
      )}
      {...props} />
    ))
  AvatarFallback.displayName = AvatarPrimitive.Fallback.displayName

  export { Avatar, AvatarImage, AvatarFallback }

```

badge.jsx

```

import * as React from "react"
import { cva } from "class-variance-authority";

import { cn } from "@/lib/utils"

const badgeVariants = cva(
  "inline-flex items-center rounded-md border px-2.5 py-0.5
text-xs font-semibold transition-colors focus:outline-none focus:ring-2
focus:ring-ring focus:ring-offset-2",
  {
    variants: {
      variant: {
        default:
          "border-transparent bg-primary text-primary-foreground
shadow hover:bg-primary/80",
        secondary:

```

```

        "border-transparent bg-secondary
text-secondary-foreground hover:bg-secondary/80",
        destructive:
            "border-transparent bg-destructive
text-destructive-foreground shadow hover:bg-destructive/80",
        outline: "text-foreground",
    },
    },
    defaultVariants: {
        variant: "default",
    },
}
)

function Badge({
    className,
    variant,
    ...props
}) {
    return (<div className={cn(badgeVariants({ variant })),
className)} {...props} />);
}

export { Badge, badgeVariants }

```

breadcrumb.jsx

```

import * as React from "react"
import { Slot } from "@radix-ui/react-slot"
import { ChevronRight, MoreHorizontal } from "lucide-react"

import { cn } from "@lib/utils"

const Breadcrumb = React.forwardRef(
    ({ ...props }, ref) => <nav ref={ref} aria-label="breadcrumb"
    {...props} />
)
Breadcrumb.displayName = "Breadcrumb"

const BreadcrumbList = React.forwardRef(({ className, ...props },
ref) => (
    <ol
        ref={ref}

```



```

        className={cn(
            "flex flex-wrap items-center gap-1.5 break-words text-sm
text-muted-foreground sm:gap-2.5",
            className
        )}
        {...props} />
    ))
    BreadcrumbList.displayName = "BreadcrumbList"

    const BreadcrumbItem = React.forwardRef(({ className, ...props },
ref) => (
        <li
            ref={ref}
            className={cn("inline-flex items-center gap-1.5", className)}
            {...props} />
        ))
        BreadcrumbItem.displayName = "BreadcrumbItem"

        const BreadcrumbLink = React.forwardRef(({ asChild, className,
...props }, ref) => {
            const Comp = asChild ? Slot : "a"

            return (
                <Comp
                    ref={ref}
                    className={cn("transition-colors hover:text-foreground",
className)}
                    {...props} />)
            );
        })
        BreadcrumbLink.displayName = "BreadcrumbLink"

        const BreadcrumbPage = React.forwardRef(({ className, ...props },
ref) => (
            <span
                ref={ref}
                role="link"
                aria-disabled="true"
                aria-current="page"
                className={cn("font-normal text-foreground", className)}
                {...props} />
            ))

```

```

BreadcrumbPage.displayName = "BreadcrumbPage"

const BreadcrumbSeparator = ({
  children,
  className,
  ...props
}) => (
  <li
    role="presentation"
    aria-hidden="true"
    className={cn("<svg>:w-3.5 [<svg>:h-3.5", className)}
    {...props}>
    {children ?? <ChevronRight />}
  </li>
)
BreadcrumbSeparator.displayName = "BreadcrumbSeparator"

const BreadcrumbEllipsis = ({
  className,
  ...props
}) => (
  <span
    role="presentation"
    aria-hidden="true"
    className={cn("flex h-9 w-9 items-center justify-center",
className)}
    {...props}>
    <MoreHorizontal className="h-4 w-4" />
    <span className="sr-only">More</span>
  </span>
)
BreadcrumbEllipsis.displayName = "BreadcrumbElipssis"

export {
  Breadcrumb,
  BreadcrumbList,
  BreadcrumbItem,
  BreadcrumbLink,
  BreadcrumbPage,
  BreadcrumbSeparator,
  BreadcrumbEllipsis,
}

```

button.jsx

```
import * as React from "react"
import { Slot } from "@radix-ui/react-slot"
import { cva } from "class-variance-authority";

import { cn } from "@lib/utils"

const buttonVariants = cva(
  "inline-flex items-center justify-center gap-2 whitespace-nowrap
rounded-md text-sm font-medium transition-colors
focus-visible:outline-none focus-visible:ring-1 focus-visible:ring-ring
disabled:pointer-events-none disabled:opacity-50
[&_svg]:pointer-events-none [&_svg]:size-4 [&_svg]:shrink-0",
  {
    variants: {
      variant: {
        default:
          "bg-primary text-primary-foreground shadow
hover:bg-primary/90",
        destructive:
          "bg-destructive text-destructive-foreground shadow-sm
hover:bg-destructive/90",
        outline:
          "border border-input bg-transparent shadow-sm
hover:bg-accent hover:text-accent-foreground",
        secondary:
          "bg-secondary text-secondary-foreground shadow-sm
hover:bg-secondary/80",
        ghost: "hover:bg-accent hover:text-accent-foreground",
        link: "text-primary underline-offset-4 hover:underline",
      },
      size: {
        default: "h-9 px-4 py-2",
        sm: "h-8 rounded-md px-3 text-xs",
        lg: "h-10 rounded-md px-8",
        icon: "h-9 w-9",
      },
    },
    defaultVariants: {
      variant: "default",
      size: "default",
    },
  }
)
```

```

        },
    }
)

const Button = React.forwardRef(({ className, variant, size,
asChild = false, ...props }, ref) => {
    const Comp = asChild ? Slot : "button"
    return (
        (<Comp
            className={cn(buttonVariants({ variant, size, className }))}
            ref={ref}
            {...props} />)
    );
})
Button.displayName = "Button"

export { Button, buttonVariants }

```

calendar.jsx

```

import * as React from "react"
import { ChevronLeft, ChevronRight } from "lucide-react"
import { DayPicker } from "react-day-picker"

import { cn } from "@lib/utils"
import { buttonVariants } from "@components/ui/button"

function Calendar({
    className,
    classNames,
    showOutsideDays = true,
    ...props
}) {
    return (
        (<DayPicker
            showOutsideDays={showOutsideDays}
            className={cn("p-3", className)}
            classNames={{
                months: "flex flex-col sm:flex-row space-y-4 sm:space-x-4
sm:space-y-0",
                month: "space-y-4",
                caption: "flex justify-center pt-1 relative items-center",
                caption_label: "text-sm font-medium",

```

```

nav: "space-x-1 flex items-center",
nav_button: cn(
  buttonVariants({ variant: "outline" }),
  "h-7 w-7 bg-transparent p-0 opacity-50
hover:opacity-100"
),
nav_button_previous: "absolute left-1",
nav_button_next: "absolute right-1",
table: "w-full border-collapse space-y-1",
head_row: "flex",
head_cell:
  "text-muted-foreground rounded-md w-8 font-normal
text-[0.8rem]",
row: "flex w-full mt-2",
cell: cn(
  "relative p-0 text-center text-sm focus-within:relative
focus-within:z-20 [&:has([aria-selected])]:bg-accent
[&:has([aria-selected].day-outside)]:bg-accent/50
[&:has([aria-selected].day-range-end)]:rounded-r-md",
  props.mode === "range"
    ? "[&:has(>.day-range-end)]:rounded-r-md
[&:has(>.day-range-start)]:rounded-l-md
first:[&:has([aria-selected])]:rounded-l-md
last:[&:has([aria-selected])]:rounded-r-md"
    : "[&:has([aria-selected])]:rounded-md"
  ),
day: cn(
  buttonVariants({ variant: "ghost" }),
  "h-8 w-8 p-0 font-normal aria-selected:opacity-100"
),
day_range_start: "day-range-start",
day_range_end: "day-range-end",
day_selected:
  "bg-primary text-primary-foreground hover:bg-primary
hover:text-primary-foreground focus:bg-primary
focus:text-primary-foreground",
day_today: "bg-accent text-accent-foreground",
day_outside:
  "day-outside text-muted-foreground
aria-selected:bg-accent/50 aria-selected:text-muted-foreground",
day_disabled: "text-muted-foreground opacity-50",
day_range_middle:

```

```

        "aria-selected:bg-accent
aria-selected:text-accent-foreground",
        day_hidden: "invisible",
        ...classNames,
      }}
      components={{
        IconLeft: ({ className, ...props }) => (
          <ChevronLeft className={cn("h-4 w-4", className)}
{...props} />
        ),
        IconRight: ({ className, ...props }) => (
          <ChevronRight className={cn("h-4 w-4", className)}
{...props} />
        ),
      }}
      {...props} />)
    );
  }
  Calendar.displayName = "Calendar"

  export { Calendar }

```

card.jsx

```

import * as React from "react"

import { cn } from "@lib/utils"

const Card = React.forwardRef(({ className, ...props }, ref) => (
  <div
    ref={ref}
    className={cn("rounded-xl border bg-card text-card-foreground
shadow", className)}
    {...props} />
  ))
Card.displayName = "Card"

const CardHeader = React.forwardRef(({ className, ...props }, ref)
=> (
  <div
    ref={ref}
    className={cn("flex flex-col space-y-1.5 p-6", className)}
    {...props} />

```

```

    ))
    CardHeader.displayName = "CardHeader"

    const CardTitle = React.forwardRef(({ className, ...props }, ref)
=> (
      <div
        ref={ref}
        className={cn("font-semibold leading-none tracking-tight",
className)}
        {...props} />
      ))
    CardTitle.displayName = "CardTitle"

    const CardDescription = React.forwardRef(({ className, ...props },
ref) => (
      <div
        ref={ref}
        className={cn("text-sm text-muted-foreground", className)}
        {...props} />
      ))
    CardDescription.displayName = "CardDescription"

    const CardContent = React.forwardRef(({ className, ...props },
ref) => (
      <div ref={ref} className={cn("p-6 pt-0", className)} {...props}
/>
      ))
    CardContent.displayName = "CardContent"

    const CardFooter = React.forwardRef(({ className, ...props }, ref)
=> (
      <div
        ref={ref}
        className={cn("flex items-center p-6 pt-0", className)}
        {...props} />
      ))
    CardFooter.displayName = "CardFooter"

    export { Card, CardHeader, CardFooter, CardTitle, CardDescription,
CardContent }

```

carousel.jsx

```
import * as React from "react"
import useEmblaCarousel from "embla-carousel-react";
import { ArrowLeft, ArrowRight } from "lucide-react"

import { cn } from "@lib/utils"
import { Button } from "@components/ui/button"

const CarouselContext = React.createContext(null)

function useCarousel() {
  const context = React.useContext(CarouselContext)

  if (!context) {
    throw new Error("useCarousel must be used within a <Carousel
/>")
  }

  return context
}

const Carousel = React.forwardRef((
  {
    orientation = "horizontal",
    opts,
    setApi,
    plugins,
    className,
    children,
    ...props
  },
  ref
) => {
  const [carouselRef, api] = useEmblaCarousel({
    ...opts,
    axis: orientation === "horizontal" ? "x" : "y",
  }, plugins)
  const [canScrollPrev, setCanScrollPrev] = React.useState(false)
  const [canScrollNext, setCanScrollNext] = React.useState(false)

  const onSelect = React.useCallback((api) => {
    if (!api) {

```



```

        return
    }

    setCanScrollPrev(api.canScrollPrev())
    setCanScrollNext(api.canScrollNext())
}, [])

const scrollPrev = React.useCallback(() => {
    api?.scrollPrev()
}, [api])

const scrollNext = React.useCallback(() => {
    api?.scrollNext()
}, [api])

const handleKeyDown = React.useCallback((event) => {
    if (event.key === "ArrowLeft") {
        event.preventDefault()
        scrollPrev()
    } else if (event.key === "ArrowRight") {
        event.preventDefault()
        scrollNext()
    }
}, [scrollPrev, scrollNext])

React.useEffect(() => {
    if (!api || !setApi) {
        return
    }

    setApi(api)
}, [api, setApi])

React.useEffect(() => {
    if (!api) {
        return
    }

    onSelect(api)
    api.on("reInit", onSelect)
    api.on("select", onSelect)

```

```

        return () => {
            api?.off("select", onSelect)
        };
    }, [api, onSelect])

    return (
        (<CarouselContext.Provider
            value={{
                carouselRef,
                api: api,
                opts,
                orientation:
                    orientation || (opts?.axis === "y" ? "vertical" :
"horizontal"),
                scrollPrev,
                scrollNext,
                canScrollPrev,
                canScrollNext,
            }}>
            <div
                ref={ref}
                onKeyDownCapture={handleKeyDown}
                className={cn("relative", className)}
                role="region"
                aria-roledescription="carousel"
                {...props}>
                    {children}
                </div>
            </CarouselContext.Provider>)
        );
    })
    Carousel.displayName = "Carousel"

    const CarouselContent = React.forwardRef(({ className, ...props },
ref) => {
        const { carouselRef, orientation } = useCarousel()

        return (
            (<div ref={carouselRef} className="overflow-hidden">
                <div
                    ref={ref}
                    className={cn(

```

```

        "flex",
        orientation === "horizontal" ? "-ml-4" : "-mt-4
flex-col",
        className
    )}
    {...props} />
</div>
);
})
CarouselContent.displayName = "CarouselContent"

const CarouselItem = React.forwardRef(({ className, ...props },
ref) => {
    const { orientation } = useCarousel()

    return (
        <div
            ref={ref}
            role="group"
            aria-roledescription="slide"
            className={cn(
                "min-w-0 shrink-0 grow-0 basis-full",
                orientation === "horizontal" ? "pl-4" : "pt-4",
                className
            )}
            {...props} />
        );
    )
    CarouselItem.displayName = "CarouselItem"

    const CarouselPrevious = React.forwardRef(({ className, variant =
"outline", size = "icon", ...props }, ref) => {
        const { orientation, scrollPrev, canScrollPrev } = useCarousel()

        return (
            <Button
                ref={ref}
                variant={variant}
                size={size}
                className={cn("absolute h-8 w-8 rounded-full", orientation
=== "horizontal"
                    ? "-left-12 top-1/2 -translate-y-1/2"

```

```

        : "-top-12 left-1/2 -translate-x-1/2 rotate-90",
className) }
        disabled={!canScrollPrev}
        onClick={scrollPrev}
        {...props}>
        <ArrowLeft className="h-4 w-4" />
        <span className="sr-only">Previous slide</span>
    </Button>)
    );
})
CarouselPrevious.displayName = "CarouselPrevious"

const CarouselNext = React.forwardRef(({ className, variant =
"outline", size = "icon", ...props }, ref) => {
    const { orientation, scrollNext, canScrollNext } = useCarousel()

    return (
        <Button
            ref={ref}
            variant={variant}
            size={size}
            className={cn("absolute h-8 w-8 rounded-full", orientation
=== "horizontal"
                ? "-right-12 top-1/2 -translate-y-1/2"
                : "-bottom-12 left-1/2 -translate-x-1/2 rotate-90",
className) }
            disabled={!canScrollNext}
            onClick={scrollNext}
            {...props}>
            <ArrowRight className="h-4 w-4" />
            <span className="sr-only">Next slide</span>
        </Button>)
    );
})
CarouselNext.displayName = "CarouselNext"

export { Carousel, CarouselContent, CarouselItem,
CarouselPrevious, CarouselNext };

```

chart.jsx

```

"use client";
import * as React from "react"

```

```

import * as RechartsPrimitive from "recharts"

import { cn } from "@lib/utils"

// Format: { THEME_NAME: CSS_SELECTOR }
const THEMES = {
  light: "",
  dark: ".dark"
}

const ChartContext = React.createContext(null)

function useChart() {
  const context = React.useContext(ChartContext)

  if (!context) {
    throw new Error("useChart must be used within a
<ChartContainer />")
  }

  return context
}

const ChartContainer = React.forwardRef(({ id, className,
children, config, ...props }, ref) => {
  const uniqueId = React.useId()
  const chartId = `chart-${id || uniqueId.replace(/:/g, "")}`

  return (
    <ChartContext.Provider value={{ config }}>
      <div
        data-chart={chartId}
        ref={ref}
        className={cn(
          "flex aspect-video justify-center text-xs
[_recharts-cartesian-axis-tick_text]:fill-muted-foreground
[_recharts-cartesian-grid_line[stroke='#ccc']]:stroke-border/50
[_recharts-curve.recharts-tooltip-cursor]:stroke-border
[_recharts-dot[stroke='#fff']]:stroke-transparent
[_recharts-layer]:outline-none
[_recharts-polar-grid_[stroke='#ccc']]:stroke-border
[_recharts-radial-bar-background-sector]:fill-muted

```

```

[&_.recharts-rectangle.recharts-tooltip-cursor]:fill-muted
[&_.recharts-reference-line_[stroke='#ccc']]:stroke-border
[&_.recharts-sector[stroke='#fff']]:stroke-transparent
[&_.recharts-sector]:outline-none [&_.recharts-surface]:outline-none",
      className
    })
    {...props}>
    <ChartStyle id={chartId} config={config} />
    <RechartsPrimitive.ResponsiveContainer>
      {children}
    </RechartsPrimitive.ResponsiveContainer>
  </div>
</ChartContext.Provider>)
);
})
ChartContainer.displayName = "Chart"

const ChartStyle = ({
  id,
  config
}) => {
  const colorConfig = Object.entries(config).filter(([ , config])
=> config.theme || config.color)

  if (!colorConfig.length) {
    return null
  }

  return (
    <style
      dangerouslySetInnerHTML={{
        __html: Object.entries(THEMES)
          .map(([theme, prefix]) => `
${prefix} [data-chart=${id}] {
${colorConfig
  .map(([key, itemConfig]) => {
    const color =
      itemConfig.theme?.[theme] ||
      itemConfig.color
    return color ? `  --color-${key}: ${color};` : null
  })
  .join("\n")}`

```

```

    }
    `)

        .join("\n"),
    }} />)
    );
}

const ChartTooltip = RechartsPrimitive.Tooltip

const ChartTooltipContent = React.forwardRef((
  {
    active,
    payload,
    className,
    indicator = "dot",
    hideLabel = false,
    hideIndicator = false,
    label,
    labelFormatter,
    labelClassName,
    formatter,
    color,
    nameKey,
    labelKey,
  },
  ref
) => {
  const { config } = useChart()

  const tooltipLabel = React.useMemo(() => {
    if (hideLabel || !payload?.length) {
      return null
    }

    const [item] = payload
    const key = `${labelKey || item.dataKey || item.name ||
"value"}`
    const itemConfig = getPayloadConfigFromPayload(config, item,
key)

    const value =
      !labelKey && typeof label === "string"
        ? config[label]?.label || label

```

```

        : itemConfig?.label

    if (labelFormatter) {
        return (
            (<div className={cn("font-medium", labelClassName)}>
                {labelFormatter(value, payload)}
            </div>)
        );
    }

    if (!value) {
        return null
    }

    return <div className={cn("font-medium",
labelClassName)}>{value}</div>;
    }, [
        label,
        labelFormatter,
        payload,
        hideLabel,
        labelClassName,
        config,
        labelKey,
    ])

    if (!active || !payload?.length) {
        return null
    }

    const nestLabel = payload.length === 1 && indicator !== "dot"

    return (
        <div
            ref={ref}
            className={cn(
                "grid min-w-[8rem] items-start gap-1.5 rounded-lg border
border-border/50 bg-background px-2.5 py-1.5 text-xs shadow-xl",
                className
            )}>
            {!nestLabel ? tooltipLabel : null}
            <div className="grid gap-1.5">

```



```

        {payload.map((item, index) => {
            const key = `${nameKey || item.name || item.dataKey ||
"value"}`

            const itemConfig = getPayloadConfigFromPayload(config,
item, key)

            const indicatorColor = color || item.payload.fill ||
item.color

            return (
                (<div
                    key={item.dataKey}
                    className={cn(
                        "flex w-full flex-wrap items-stretch gap-2
[&>svg]:h-2.5 [&>svg]:w-2.5 [&>svg]:text-muted-foreground",
                        indicator === "dot" && "items-center"
                    )}>
                    {formatter && item?.value !== undefined && item.name
? (
                        formatter(item.value, item.name, item, index,
item.payload)
                    ) : (
                        <>
                            {itemConfig?.icon ? (
                                <itemConfig.icon />
                            ) : (
                                !hideIndicator && (
                                    <div
                                        className={cn("shrink-0 rounded-[2px]
border-[--color-border] bg-[--color-bg]", {
                                            "h-2.5 w-2.5": indicator === "dot",
                                            "w-1": indicator === "line",
                                            "w-0 border-[1.5px] border-dashed
bg-transparent":
                                                indicator === "dashed",
                                            "my-0.5": nestLabel && indicator ===
"dashed",
                                        })}
                                    </div>
                                )}
                            )}
                        </>
                    )}
                )
            )
        })
    }
    style={
        {
            "--color-bg": indicatorColor,
            "--color-border": indicatorColor
        }
    }
}

```

```

        } />
    )
  })
<div
  className={cn(
    "flex flex-1 justify-between leading-none",
    nestLabel ? "items-end" : "items-center"
  )}>
  <div className="grid gap-1.5">
    {nestLabel ? tooltipLabel : null}
    <span className="text-muted-foreground">
      {itemConfig?.label || item.name}
    </span>
  </div>
  {item.value && (
    <span className="font-mono font-medium
tabular-nums text-foreground">
      {item.value.toLocaleString()}
    </span>
  )}
</div>
</>
  )}
</div>)
);
  )}
</div>
</div>
);
})
ChartTooltipContent.displayName = "ChartTooltip"

const ChartLegend = RechartsPrimitive.Legend

const ChartLegendContent = React.forwardRef((
  { className, hideIcon = false, payload, verticalAlign =
"bottom", nameKey },
  ref
) => {
  const { config } = useChart()

  if (!payload?.length) {

```

```

        return null
    }

    return (
        (<div
            ref={ref}
            className={cn(
                "flex items-center justify-center gap-4",
                verticalAlign === "top" ? "pb-3" : "pt-3",
                className
            )}>
            {payload.map((item) => {
                const key = `${nameKey || item.dataKey || "value"}`
                const itemConfig = getPayloadConfigFromPayload(config,
item, key)

                return (
                    (<div
                        key={item.value}
                        className={cn(
                            "flex items-center gap-1.5 [>svg]:h-3 [>svg]:w-3
[>svg]:text-muted-foreground"
                        )}>
                        {itemConfig?.icon && !hideIcon ? (
                            <itemConfig.icon />
                        ) : (
                            <div
                                className="h-2 w-2 shrink-0 rounded-[2px]"
                                style={{
                                    backgroundColor: item.color,
                                }} />
                            )}
                        {itemConfig?.label}
                    </div>)
                );
            })}
        </div>)

    );
}

ChartLegendContent.displayName = "ChartLegend"

// Helper to extract item config from a payload.

```

```

function getPayloadConfigFromPayload(
  config,
  payload,
  key
) {
  if (typeof payload !== "object" || payload === null) {
    return undefined
  }

  const payloadPayload =
    "payload" in payload &&
    typeof payload.payload === "object" &&
    payload.payload !== null
      ? payload.payload
      : undefined

  let configLabelKey = key

  if (
    key in payload &&
    typeof payload[key] === "string"
  ) {
    configLabelKey = payload[key]
  } else if (
    payloadPayload &&
    key in payloadPayload &&
    typeof payloadPayload[key] === "string"
  ) {
    configLabelKey = payloadPayload[key]
  }

  return configLabelKey in config
    ? config[configLabelKey]
    : config[key];
}

export {
  ChartContainer,
  ChartTooltip,
  ChartTooltipContent,
  ChartLegend,
  ChartLegendContent,

```

```
    ChartStyle,  
  }  
}
```

checkbox.jsx

```
import * as React from "react"  
import * as CheckboxPrimitive from "@radix-ui/react-checkbox"  
import { Check } from "lucide-react"  
  
import { cn } from "@lib/utils"  
  
const Checkbox = React.forwardRef(({ className, ...props }, ref)  
=> (  
  <CheckboxPrimitive.Root  
    ref={ref}  
    className={cn(  
      "peer h-4 w-4 shrink-0 rounded-sm border border-primary  
shadow focus-visible:outline-none focus-visible:ring-1  
focus-visible:ring-ring disabled:cursor-not-allowed disabled:opacity-50  
data-[state=checked]:bg-primary  
data-[state=checked]:text-primary-foreground",  
      className  
    )}  
    {...props}>  
    <CheckboxPrimitive.Indicator className={cn("flex items-center  
justify-center text-current")}>  
      <Check className="h-4 w-4" />  
    </CheckboxPrimitive.Indicator>  
  </CheckboxPrimitive.Root>  
)  
)  
Checkbox.displayName = CheckboxPrimitive.Root.displayName  
  
export { Checkbox }
```

collapsible.jsx

```
"use client"  
  
import * as CollapsiblePrimitive from  
"@radix-ui/react-collapsible"  
  
const Collapsible = CollapsiblePrimitive.Root  
  
const CollapsibleTrigger = CollapsiblePrimitive.CollapsibleTrigger
```

```

const CollapsibleContent = CollapsiblePrimitive.CollapsibleContent

export { Collapsible, CollapsibleTrigger, CollapsibleContent }

command.jsx
import * as React from "react"
import { Command as CommandPrimitive } from "cmdk"
import { Search } from "lucide-react"

import { cn } from "@lib/utils"
import { Dialog, DialogContent } from "@components/ui/dialog"

const Command = React.forwardRef(({ className, ...props }, ref) =>
(
  <CommandPrimitive
    ref={ref}
    className={cn(
      "flex h-full w-full flex-col overflow-hidden rounded-md
bg-popover text-popover-foreground",
      className
    )}
    {...props} />
))
Command.displayName = CommandPrimitive.displayName

const CommandDialog = ({
  children,
  ...props
}) => {
  return (
    <Dialog {...props}>
      <DialogContent className="overflow-hidden p-0">
        <Command
          className="[&_cmdk-group-heading]:px-2
[&_cmdk-group-heading]:font-medium
[&_cmdk-group-heading]:text-muted-foreground
[&_cmdk-group]:not([hidden])_~[cmdk-group]:pt-0 [&_cmdk-group]:px-2
[&_cmdk-input-wrapper]_svg:h-5 [&_cmdk-input-wrapper]_svg:w-5
[&_cmdk-input]:h-12 [&_cmdk-item]:px-2 [&_cmdk-item]:py-3
[&_cmdk-item]_svg:h-5 [&_cmdk-item]_svg:w-5">
          {children}

```

```

        </Command>
      </DialogContent>
    </Dialog>)
  );
}

const CommandInput = React.forwardRef(({ className, ...props },
ref) => (
  <div className="flex items-center border-b px-3"
cmdk-input-wrapper="">
    <Search className="mr-2 h-4 w-4 shrink-0 opacity-50" />
    <CommandPrimitive.Input
      ref={ref}
      className={cn(
        "flex h-10 w-full rounded-md bg-transparent py-3 text-sm
outline-none placeholder:text-muted-foreground
disabled:cursor-not-allowed disabled:opacity-50",
        className
      )}
      {...props} />
  </div>
))

CommandInput.displayName = CommandPrimitive.Input.displayName

const CommandList = React.forwardRef(({ className, ...props },
ref) => (
  <CommandPrimitive.List
    ref={ref}
    className={cn("max-h-[300px] overflow-y-auto
overflow-x-hidden", className)}
    {...props} />
))

CommandList.displayName = CommandPrimitive.List.displayName

const CommandEmpty = React.forwardRef((props, ref) => (
  <CommandPrimitive.Empty ref={ref} className="py-6 text-center
text-sm" {...props} />
))

CommandEmpty.displayName = CommandPrimitive.Empty.displayName

```

```

    const CommandGroup = React.forwardRef(({ className, ...props },
ref) => (
    <CommandPrimitive.Group
      ref={ref}
      className={cn(
        "overflow-hidden p-1 text-foreground
[&_[cmdk-group-heading]]:px-2 [&_[cmdk-group-heading]]:py-1.5
[&_[cmdk-group-heading]]:text-xs [&_[cmdk-group-heading]]:font-medium
[&_[cmdk-group-heading]]:text-muted-foreground",
        className
      )}
      {...props} />
    ))

    CommandGroup.displayName = CommandPrimitive.Group.displayName

    const CommandSeparator = React.forwardRef(({ className, ...props
}, ref) => (
    <CommandPrimitive.Separator ref={ref} className={cn("-mx-1 h-px
bg-border", className)} {...props} />
    ))

    CommandSeparator.displayName =
CommandPrimitive.Separator.displayName

    const CommandItem = React.forwardRef(({ className, ...props },
ref) => (
    <CommandPrimitive.Item
      ref={ref}
      className={cn(
        "relative flex cursor-default gap-2 select-none items-center
rounded-sm px-2 py-1.5 text-sm outline-none
data-[disabled=true]:pointer-events-none data-[selected=true]:bg-accent
data-[selected=true]:text-accent-foreground
data-[disabled=true]:opacity-50 [&_svg]:pointer-events-none
[&_svg]:size-4 [&_svg]:shrink-0",
        className
      )}
      {...props} />
    ))

    CommandItem.displayName = CommandPrimitive.Item.displayName

```



```

const CommandShortcut = ({
  className,
  ...props
}) => {
  return (
    <span
      className={cn("ml-auto text-xs tracking-widest
text-muted-foreground", className)}
      {...props} />)
  );
}
CommandShortcut.displayName = "CommandShortcut"

export {
  Command,
  CommandDialog,
  CommandInput,
  CommandList,
  CommandEmpty,
  CommandGroup,
  CommandItem,
  CommandShortcut,
  CommandSeparator,
}

```

context-menu.jsx

```

import * as React from "react"
import * as ContextMenuPrimitive from
"@radix-ui/react-context-menu"
import { Check, ChevronRight, Circle } from "lucide-react"

import { cn } from "@/lib/utils"

const ContextMenu = ContextMenuPrimitive.Root

const ContextMenuTrigger = ContextMenuPrimitive.Trigger

const ContextMenuGroup = ContextMenuPrimitive.Group

const ContextMenuPortal = ContextMenuPrimitive.Portal

```

```

const ContextMenuSub = ContextMenuPrimitive.Sub

const ContextMenuRadioGroup = ContextMenuPrimitive.RadioGroup

const ContextMenuSubTrigger = React.forwardRef(({ className,
inset, children, ...props }, ref) => (
  <ContextMenuPrimitive.SubTrigger
    ref={ref}
    className={cn(
      "flex cursor-default select-none items-center rounded-sm
px-2 py-1.5 text-sm outline-none focus:bg-accent
focus:text-accent-foreground data-[state=open]:bg-accent
data-[state=open]:text-accent-foreground",
      inset && "pl-8",
      className
    )}
    {...props}>
    {children}
    <ChevronRight className="ml-auto h-4 w-4" />
  </ContextMenuPrimitive.SubTrigger>
))
ContextMenuSubTrigger.displayName =
ContextMenuPrimitive.SubTrigger.displayName

const ContextMenuSubContent = React.forwardRef(({ className,
...props }, ref) => (
  <ContextMenuPrimitive.SubContent
    ref={ref}
    className={cn(
      "z-50 min-w-[8rem] overflow-hidden rounded-md border
bg-popover p-1 text-popover-foreground shadow-lg
data-[state=open]:animate-in data-[state=closed]:animate-out
data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0
data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95
data-[side=bottom]:slide-in-from-top-2
data-[side=left]:slide-in-from-right-2
data-[side=right]:slide-in-from-left-2
data-[side=top]:slide-in-from-bottom-2",
      className
    )}
    {...props} />
))

```

```

    ContextMenuSubContent.displayName =
ContextMenuPrimitive.SubContent.displayName

    const ContextMenuContent = React.forwardRef(({ className, ...props
}, ref) => (
    <ContextMenuPrimitive.Portal>
      <ContextMenuPrimitive.Content
        ref={ref}
        className={cn(
          "z-50 min-w-[8rem] overflow-hidden rounded-md border
bg-popover p-1 text-popover-foreground shadow-md
data-[state=open]:animate-in data-[state=closed]:animate-out
data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0
data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95
data-[side=bottom]:slide-in-from-top-2
data-[side=left]:slide-in-from-right-2
data-[side=right]:slide-in-from-left-2
data-[side=top]:slide-in-from-bottom-2",
            className
          )}
        {...props} />
      </ContextMenuPrimitive.Portal>
    ))
    ContextMenuContent.displayName =
ContextMenuPrimitive.Content.displayName

    const ContextMenuItem = React.forwardRef(({ className, inset,
...props }, ref) => (
    <ContextMenuPrimitive.Item
      ref={ref}
      className={cn(
        "relative flex cursor-default select-none items-center
rounded-sm px-2 py-1.5 text-sm outline-none focus:bg-accent
focus:text-accent-foreground data-[disabled]:pointer-events-none
data-[disabled]:opacity-50",
          inset && "pl-8",
          className
        )}
      {...props} />
    ))
    ContextMenuItem.displayName =
ContextMenuPrimitive.Item.displayName

```

```

    const ContextMenuCheckboxItem = React.forwardRef(({ className,
children, checked, ...props }, ref) => (
    <ContextMenuPrimitive.CheckboxItem
      ref={ref}
      className={cn(
        "relative flex cursor-default select-none items-center
rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none focus:bg-accent
focus:text-accent-foreground data-[disabled]:pointer-events-none
data-[disabled]:opacity-50",
        className
      )}
      checked={checked}
      {...props}>
      <span className="absolute left-2 flex h-3.5 w-3.5 items-center
justify-center">
        <ContextMenuPrimitive.ItemIndicator>
          <Check className="h-4 w-4" />
        </ContextMenuPrimitive.ItemIndicator>
      </span>
      {children}
    </ContextMenuPrimitive.CheckboxItem>
  ))
  ContextMenuCheckboxItem.displayName =
    ContextMenuPrimitive.CheckboxItem.displayName

    const ContextMenuRadioItem = React.forwardRef(({ className,
children, ...props }, ref) => (
    <ContextMenuPrimitive.RadioItem
      ref={ref}
      className={cn(
        "relative flex cursor-default select-none items-center
rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none focus:bg-accent
focus:text-accent-foreground data-[disabled]:pointer-events-none
data-[disabled]:opacity-50",
        className
      )}
      {...props}>
      <span className="absolute left-2 flex h-3.5 w-3.5 items-center
justify-center">
        <ContextMenuPrimitive.ItemIndicator>
          <Circle className="h-4 w-4 fill-current" />
        </ContextMenuPrimitive.ItemIndicator>
      </span>
      {children}
    </ContextMenuPrimitive.RadioItem>
  ))
  ContextMenuRadioItem.displayName =
    ContextMenuPrimitive.RadioItem.displayName

```

```

        </ContextMenuPrimitive.ItemIndicator>
      </span>
      {children}
    </ContextMenuPrimitive.RadioItem>
  ))
  ContextMenuRadioItem.displayName =
    ContextMenuPrimitive.RadioItem.displayName

  const ContextMenuLabel = React.forwardRef(({ className, inset,
...props }, ref) => (
    <ContextMenuPrimitive.Label
      ref={ref}
      className={cn(
        "px-2 py-1.5 text-sm font-semibold text-foreground",
        inset && "pl-8",
        className
      )}
      {...props} />
  ))
  ContextMenuLabel.displayName =
    ContextMenuPrimitive.Label.displayName

  const ContextMenuSeparator = React.forwardRef(({ className,
...props }, ref) => (
    <ContextMenuPrimitive.Separator
      ref={ref}
      className={cn("-mx-1 my-1 h-px bg-border", className)}
      {...props} />
  ))
  ContextMenuSeparator.displayName =
    ContextMenuPrimitive.Separator.displayName

  const ContextMenuShortcut = ({
    className,
    ...props
  }) => {
    return (
      <span
        className={cn("ml-auto text-xs tracking-widest
text-muted-foreground", className)}
        {...props} />
    );
  };

```

```

    }
    ContextMenuShortcut.displayName = "ContextMenuShortcut"

    export {
      ContextMenu,
      ContextMenuTrigger,
      ContextMenuContent,
      ContextMenuItem,
      ContextMenuCheckboxItem,
      ContextMenuRadioItem,
      ContextMenuLabel,
      ContextMenuSeparator,
      ContextMenuShortcut,
      ContextMenuGroup,
      ContextMenuPortal,
      ContextMenuSub,
      ContextMenuSubContent,
      ContextMenuSubTrigger,
      ContextMenuRadioGroup,
    }

```

dialog.jsx

```
"use client"
```

```

import * as React from "react"
import * as DialogPrimitive from "@radix-ui/react-dialog"
import { X } from "lucide-react"

```

```
import { cn } from "@/lib/utils"
```

```
const Dialog = DialogPrimitive.Root
```

```
const DialogTrigger = DialogPrimitive.Trigger
```

```
const DialogPortal = DialogPrimitive.Portal
```

```
const DialogClose = DialogPrimitive.Close
```

```

const DialogOverlay = React.forwardRef(({ className, ...props },
ref) => (
  <DialogPrimitive.Overlay
    ref={ref}

```

```

        className={cn(
            "fixed inset-0 z-50 bg-black/80
data-[state=open]:animate-in data-[state=closed]:animate-out
data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0",
            className
        )}
        {...props} />
    ))
    DialogOverlay.displayName = DialogPrimitive.Overlay.displayName

    const DialogContent = React.forwardRef(({ className, children,
...props }, ref) => (
        <DialogPortal>
            <DialogOverlay />
            <DialogPrimitive.Content
                ref={ref}
                className={cn(
                    "fixed left-[50%] top-[50%] z-50 grid w-full max-w-lg
translate-x-[-50%] translate-y-[-50%] gap-4 border bg-background p-6
shadow-lg duration-200 data-[state=open]:animate-in
data-[state=closed]:animate-out data-[state=closed]:fade-out-0
data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95
data-[state=open]:zoom-in-95 data-[state=closed]:slide-out-to-left-1/2
data-[state=closed]:slide-out-to-top-[48%]
data-[state=open]:slide-in-from-left-1/2
data-[state=open]:slide-in-from-top-[48%] sm:rounded-lg",
                    className
                )}
                {...props}>
                {children}
                <DialogPrimitive.Close
                    className="absolute right-4 top-4 rounded-sm opacity-70
ring-offset-background transition-opacity hover:opacity-100
focus:outline-none focus:ring-2 focus:ring-ring focus:ring-offset-2
disabled:pointer-events-none data-[state=open]:bg-accent
data-[state=open]:text-muted-foreground">
                    <X className="h-4 w-4" />
                    <span className="sr-only">Close</span>
                </DialogPrimitive.Close>
            </DialogPrimitive.Content>
        </DialogPortal>
    ))

```

```

DialogContent.displayName = DialogPrimitive.Content.displayName

const DialogHeader = ({
  className,
  ...props
}) => (
  <div
    className={cn("flex flex-col space-y-1.5 text-center
sm:text-left", className)}
    {...props} />
  )
DialogHeader.displayName = "DialogHeader"

const DialogFooter = ({
  className,
  ...props
}) => (
  <div
    className={cn("flex flex-col-reverse sm:flex-row
sm:justify-end sm:space-x-2", className)}
    {...props} />
  )
DialogFooter.displayName = "DialogFooter"

const DialogTitle = React.forwardRef(({ className, ...props },
ref) => (
  <DialogPrimitive.Title
    ref={ref}
    className={cn("text-lg font-semibold leading-none
tracking-tight", className)}
    {...props} />
  ))
DialogTitle.displayName = DialogPrimitive.Title.displayName

const DialogDescription = React.forwardRef(({ className, ...props
}, ref) => (
  <DialogPrimitive.Description
    ref={ref}
    className={cn("text-sm text-muted-foreground", className)}
    {...props} />
  ))

```



```
DialogDescription.displayName =
DialogPrimitive.Description.displayName
```

```
export {
  Dialog,
  DialogPortal,
  DialogOverlay,
  DialogTrigger,
  DialogClose,
  DialogContent,
  DialogHeader,
  DialogFooter,
  DialogTitle,
  DialogDescription,
}
```

drawer.jsx

```
"use client"
```

```
import * as React from "react"
import { Drawer as DrawerPrimitive } from "vaul"
```

```
import { cn } from "@lib/utils"
```

```
const Drawer = ({
  shouldScaleBackground = true,
  ...props
}) => (
  <DrawerPrimitive.Root
shouldScaleBackground={shouldScaleBackground} {...props} />
)
Drawer.displayName = "Drawer"

const DrawerTrigger = DrawerPrimitive.Trigger

const DrawerPortal = DrawerPrimitive.Portal

const DrawerClose = DrawerPrimitive.Close

const DrawerOverlay = React.forwardRef(({ className, ...props },
ref) => (
  <DrawerPrimitive.Overlay
```

```

        ref={ref}
        className={cn("fixed inset-0 z-50 bg-black/80", className)}
        {...props} />
    ))
    DrawerOverlay.displayName = DrawerPrimitive.Overlay.displayName

    const DrawerContent = React.forwardRef(({ className, children,
...props }, ref) => (
        <DrawerPortal>
            <DrawerOverlay />
            <DrawerPrimitive.Content
                ref={ref}
                className={cn(
                    "fixed inset-x-0 bottom-0 z-50 mt-24 flex h-auto flex-col
rounded-t-[10px] border bg-background",
                    className
                )}
                {...props}>
                <div className="mx-auto mt-4 h-2 w-[100px] rounded-full
bg-muted" />
                    {children}
                </DrawerPrimitive.Content>
            </DrawerPortal>
        )
    DrawerContent.displayName = "DrawerContent"

    const DrawerHeader = ({
        className,
        ...props
    }) => (
        <div
            className={cn("grid gap-1.5 p-4 text-center sm:text-left",
className)}
            {...props} />
        )
    DrawerHeader.displayName = "DrawerHeader"

    const DrawerFooter = ({
        className,
        ...props
    }) => (

```

```

        <div className={cn("mt-auto flex flex-col gap-2 p-4",
className)} {...props} />
    )
    DrawerFooter.displayName = "DrawerFooter"

    const DrawerTitle = React.forwardRef(({ className, ...props },
ref) => (
        <DrawerPrimitive.Title
            ref={ref}
            className={cn("text-lg font-semibold leading-none
tracking-tight", className)}
            {...props} />
        ))
    DrawerTitle.displayName = DrawerPrimitive.Title.displayName

    const DrawerDescription = React.forwardRef(({ className, ...props
}, ref) => (
        <DrawerPrimitive.Description
            ref={ref}
            className={cn("text-sm text-muted-foreground", className)}
            {...props} />
        ))
    DrawerDescription.displayName =
DrawerPrimitive.Description.displayName

export {
    Drawer,
    DrawerPortal,
    DrawerOverlay,
    DrawerTrigger,
    DrawerClose,
    DrawerContent,
    DrawerHeader,
    DrawerFooter,
    DrawerTitle,
    DrawerDescription,
}

```

dropdown-menu.jsx

```

import * as React from "react"
import * as DropdownMenuPrimitive from
"@radix-ui/react-dropdown-menu"

```

```

import { Check, ChevronRight, Circle } from "lucide-react"

import { cn } from "@/lib/utils"

const DropdownMenu = DropdownMenuPrimitive.Root

const DropdownMenuTrigger = DropdownMenuPrimitive.Trigger

const DropdownMenuGroup = DropdownMenuPrimitive.Group

const DropdownMenuPortal = DropdownMenuPrimitive.Portal

const DropdownMenuSub = DropdownMenuPrimitive.Sub

const DropdownMenuRadioGroup = DropdownMenuPrimitive.RadioGroup

const DropdownMenuSubTrigger = React.forwardRef(({ className,
inset, children, ...props }, ref) => (
  <DropdownMenuPrimitive.SubTrigger
    ref={ref}
    className={cn(
      "flex cursor-default gap-2 select-none items-center
rounded-sm px-2 py-1.5 text-sm outline-none focus:bg-accent
data-[state=open]:bg-accent [&_svg]:pointer-events-none [&_svg]:size-4
[&_svg]:shrink-0",
      inset && "pl-8",
      className
    )}
    {...props}>
    {children}
    <ChevronRight className="ml-auto" />
  </DropdownMenuPrimitive.SubTrigger>
))
DropdownMenuSubTrigger.displayName =
  DropdownMenuPrimitive.SubTrigger.displayName

const DropdownMenuSubContent = React.forwardRef(({ className,
...props }, ref) => (
  <DropdownMenuPrimitive.SubContent
    ref={ref}
    className={cn(

```

```

        "z-50 min-w-[8rem] overflow-hidden rounded-md border
bg-popover p-1 text-popover-foreground shadow-lg
data-[state=open]:animate-in data-[state=closed]:animate-out
data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0
data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95
data-[side=bottom]:slide-in-from-top-2
data-[side=left]:slide-in-from-right-2
data-[side=right]:slide-in-from-left-2
data-[side=top]:slide-in-from-bottom-2",
        className
    )}
    {...props} />
))
DropdownMenuSubContent.displayName =
    DropdownMenuPrimitive.SubContent.displayName

const DropdownMenuContent = React.forwardRef(({ className,
sideOffset = 4, ...props }, ref) => (
    <DropdownMenuPrimitive.Portal>
        <DropdownMenuPrimitive.Content
            ref={ref}
            sideOffset={sideOffset}
            className={cn(
                "z-50 min-w-[8rem] overflow-hidden rounded-md border
bg-popover p-1 text-popover-foreground shadow-md",
                "data-[state=open]:animate-in
data-[state=closed]:animate-out data-[state=closed]:fade-out-0
data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95
data-[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2
data-[side=left]:slide-in-from-right-2
data-[side=right]:slide-in-from-left-2
data-[side=top]:slide-in-from-bottom-2",
                className
            )}
            {...props} />
        </DropdownMenuPrimitive.Portal>
    ))
    DropdownMenuContent.displayName =
        DropdownMenuPrimitive.Content.displayName

const DropdownMenuItem = React.forwardRef(({ className, inset,
...props }, ref) => (

```

```

    <DropdownMenuPrimitive.Item
      ref={ref}
      className={cn(
        "relative flex cursor-default select-none items-center gap-2
rounded-sm px-2 py-1.5 text-sm outline-none transition-colors
focus:bg-accent focus:text-accent-foreground
data-[disabled]:pointer-events-none data-[disabled]:opacity-50
[&>svg]:size-4 [&>svg]:shrink-0",
        inset && "pl-8",
        className
      )}
      {...props} />
  ))
  DropdownMenuItem.displayName =
DropdownMenuPrimitive.Item.displayName

const DropdownMenuCheckboxItem = React.forwardRef(({ className,
children, checked, ...props }, ref) => (
  <DropdownMenuPrimitive.CheckboxItem
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center
rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none transition-colors
focus:bg-accent focus:text-accent-foreground
data-[disabled]:pointer-events-none data-[disabled]:opacity-50",
      className
    )}
    checked={checked}
    {...props}>
    <span className="absolute left-2 flex h-3.5 w-3.5 items-center
justify-center">
      <DropdownMenuPrimitive.ItemIndicator>
        <Check className="h-4 w-4" />
      </DropdownMenuPrimitive.ItemIndicator>
    </span>
    {children}
  </DropdownMenuPrimitive.CheckboxItem>
))
DropdownMenuCheckboxItem.displayName =
  DropdownMenuPrimitive.CheckboxItem.displayName

```

```

    const DropdownMenuRadioItem = React.forwardRef(({ className,
children, ...props }, ref) => (
    <DropdownMenuPrimitive.RadioItem
      ref={ref}
      className={cn(
        "relative flex cursor-default select-none items-center
rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none transition-colors
focus:bg-accent focus:text-accent-foreground
data-[disabled]:pointer-events-none data-[disabled]:opacity-50",
        className
      )}
      {...props}>
      <span className="absolute left-2 flex h-3.5 w-3.5 items-center
justify-center">
        <DropdownMenuPrimitive.ItemIndicator>
          <Circle className="h-2 w-2 fill-current" />
        </DropdownMenuPrimitive.ItemIndicator>
      </span>
      {children}
    </DropdownMenuPrimitive.RadioItem>
  ))
  DropdownMenuRadioItem.displayName =
DropdownMenuPrimitive.RadioItem.displayName

    const DropdownMenuLabel = React.forwardRef(({ className, inset,
...props }, ref) => (
    <DropdownMenuPrimitive.Label
      ref={ref}
      className={cn("px-2 py-1.5 text-sm font-semibold", inset &&
"pl-8", className)}
      {...props} />
  ))
  DropdownMenuLabel.displayName =
DropdownMenuPrimitive.Label.displayName

    const DropdownMenuSeparator = React.forwardRef(({ className,
...props }, ref) => (
    <DropdownMenuPrimitive.Separator
      ref={ref}
      className={cn("-mx-1 my-1 h-px bg-muted", className)}
      {...props} />
  ))

```

```

    DropdownMenuSeparator.displayName =
DropdownMenuPrimitive.Separator.displayName

    const DropdownMenuShortcut = ({
      className,
      ...props
    }) => {
      return (
        (<span
          className={cn("ml-auto text-xs tracking-widest opacity-60",
className)}
          {...props} />)
        );
      }
    DropdownMenuShortcut.displayName = "DropdownMenuShortcut"

    export {
      DropdownMenu,
      DropdownMenuTrigger,
      DropdownMenuContent,
      DropdownMenuItem,
      DropdownMenuCheckboxItem,
      DropdownMenuRadioItem,
      DropdownMenuLabel,
      DropdownMenuSeparator,
      DropdownMenuShortcut,
      DropdownMenuGroup,
      DropdownMenuPortal,
      DropdownMenuSub,
      DropdownMenuSubContent,
      DropdownMenuSubTrigger,
      DropdownMenuRadioGroup,
    }
  }
}

```

form.jsx

```

"use client";
import * as React from "react"
import { Slot } from "@radix-ui/react-slot"
import { Controller, FormProvider, useFormContext } from
"react-hook-form";

import { cn } from "@lib/utils"

```



```

import { Label } from "@components/ui/label"

const Form = FormProvider

const FormFieldContext = React.createContext({})

const FormField = (
  {
    ...props
  }
) => {
  return (
    (<FormFieldContext.Provider value={{ name: props.name }}>
      <Controller {...props} />
    </FormFieldContext.Provider>)
  );
}

const useFormField = () => {
  const fieldContext = React.useContext(FormFieldContext)
  const itemContext = React.useContext(FormItemContext)
  const { getFieldState, formState } = useFormContext()

  const fieldState = getFieldState(fieldContext.name, formState)

  if (!fieldContext) {
    throw new Error("useFormField should be used within
<FormField>")
  }

  const { id } = itemContext

  return {
    id,
    name: fieldContext.name,
    formItemId: `${id}-form-item`,
    formDescriptionId: `${id}-form-item-description`,
    formMessageId: `${id}-form-item-message`,
    ...fieldState,
  }
}

```

```

const FormItemContext = React.createContext({})

const FormItem = React.forwardRef(({ className, ...props }, ref)
=> {
  const id = React.useId()

  return (
    <FormItemContext.Provider value={{ id }}>
      <div ref={ref} className={cn("space-y-2", className)}
{...props} />
    </FormItemContext.Provider>
  );
})
FormItem.displayName = "FormItem"

const FormLabel = React.forwardRef(({ className, ...props }, ref)
=> {
  const { error, formItemId } = useFormField()

  return (
    <Label
      ref={ref}
      className={cn(error && "text-destructive", className)}
      htmlFor={formItemId}
      {...props} />
  );
})
FormLabel.displayName = "FormLabel"

const FormControl = React.forwardRef(({ ...props }, ref) => {
  const { error, formItemId, formDescriptionId, formMessageId } =
useFormField()

  return (
    <Slot
      ref={ref}
      id={formItemId}
      aria-describedby={
        !error
          ? `${formDescriptionId}`
          : `${formDescriptionId} ${formMessageId}`
      }
    />
  );
})

```

```

        aria-invalid={!error}
        {...props} />
    );
})
FormControl.displayName = "FormControl"

const FormDescription = React.forwardRef(({ className, ...props },
ref) => {
    const { formDescriptionId } = useFormField()

    return (
        <p
            ref={ref}
            id={formDescriptionId}
            className={cn("text-[0.8rem] text-muted-foreground",
className)}
            {...props} />
        );
    )
    FormDescription.displayName = "FormDescription"

    const FormMessage = React.forwardRef(({ className, children,
...props }, ref) => {
        const { error, formMessageId } = useFormField()
        const body = error ? String(error?.message) : children

        if (!body) {
            return null
        }

        return (
            <p
                ref={ref}
                id={formMessageId}
                className={cn("text-[0.8rem] font-medium text-destructive",
className)}
                {...props}>
                {body}
            </p>
        );
    )
    FormMessage.displayName = "FormMessage"

```

```
export {
  useFormField,
  Form,
  FormItem,
  FormLabel,
  FormControl,
  FormDescription,
  FormMessage,
  FormField,
}
```

hover-card.jsx

```
"use client"
```

```
import * as React from "react"
import * as HoverCardPrimitive from "@radix-ui/react-hover-card"
```

```
import { cn } from "@lib/utils"
```

```
const HoverCard = HoverCardPrimitive.Root
```

```
const HoverCardTrigger = HoverCardPrimitive.Trigger
```

```
const HoverCardContent = React.forwardRef(({ className, align =
"center", sideOffset = 4, ...props }, ref) => (
  <HoverCardPrimitive.Content
    ref={ref}
    align={align}
    sideOffset={sideOffset}
    className={cn(
      "z-50 w-64 rounded-md border bg-popover p-4
text-popover-foreground shadow-md outline-none
data-[state=open]:animate-in data-[state=closed]:animate-out
data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0
data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95
data-[side=bottom]:slide-in-from-top-2
data-[side=left]:slide-in-from-right-2
data-[side=right]:slide-in-from-left-2
data-[side=top]:slide-in-from-bottom-2",
      className
    )}
  )
```

```

        {...props} />
    ))
    HoverCardContent.displayName =
HoverCardPrimitive.Content.displayName

    export { HoverCard, HoverCardTrigger, HoverCardContent }

```

input-otp.jsx

```

import * as React from "react"
import { OTPInput, OTPInputContext } from "input-otp"
import { Minus } from "lucide-react"

import { cn } from "@/lib/utils"

const InputOTP = React.forwardRef(({ className,
containerClassName, ...props }, ref) => (
  <OTPInput
    ref={ref}
    containerClassName={cn("flex items-center gap-2
has-[:disabled]:opacity-50", containerClassName)}
    className={cn("disabled:cursor-not-allowed", className)}
    {...props} />
  ))
  InputOTP.displayName = "InputOTP"

  const InputOTPGroup = React.forwardRef(({ className, ...props },
ref) => (
    <div ref={ref} className={cn("flex items-center", className)}
    {...props} />
  ))
  InputOTPGroup.displayName = "InputOTPGroup"

  const InputOTPSlot = React.forwardRef(({ index, className,
...props }, ref) => {
    const inputOTPContext = React.useContext(OTPInputContext)
    const { char, hasFakeCaret, isActive } =
inputOTPContext.slots[index]

    return (
      <div
        ref={ref}
        className={cn(

```

```

        "relative flex h-9 w-9 items-center justify-center
border-y border-r border-input text-sm shadow-sm transition-all
first:rounded-l-md first:border-l last:rounded-r-md",
        isActive && "z-10 ring-1 ring-ring",
        className
    )}
    {...props}>
    {char}
    {hasFakeCaret && (
        <div
            className="pointer-events-none absolute inset-0 flex
items-center justify-center">
            <div className="h-4 w-px animate-caret-blink
bg-foreground duration-1000" />
        </div>
    )}
    </div>)
    );
})
InputOTPSlot.displayName = "InputOTPSlot"

const InputOTPSeparator = React.forwardRef(({ ...props }, ref) =>
(
    <div ref={ref} role="separator" {...props}>
        <Minus />
    </div>
))
InputOTPSeparator.displayName = "InputOTPSeparator"

export { InputOTP, InputOTPGroup, InputOTPSlot, InputOTPSeparator
}

```

```

input.jsx
import * as React from "react"

import { cn } from "@/lib/utils"

const Input = React.forwardRef(({ className, type, ...props },
ref) => {
    return (
        <input
            type={type}

```

```

        className={cn(
            "flex h-9 w-full rounded-md border border-input
            bg-transparent px-3 py-1 text-base shadow-sm transition-colors
            file:border-0 file:bg-transparent file:text-sm file:font-medium
            file:text-foreground placeholder:text-muted-foreground
            focus-visible:outline-none focus-visible:ring-1 focus-visible:ring-ring
            disabled:cursor-not-allowed disabled:opacity-50 md:text-sm",
            className
        )}
        ref={ref}
        {...props} />
    );
})
Input.displayName = "Input"

export { Input }

```

label.jsx

```

import * as React from "react"
import * as LabelPrimitive from "@radix-ui/react-label"
import { cva } from "class-variance-authority";

import { cn } from "@/lib/utils"

const labelVariants = cva(
    "text-sm font-medium leading-none
    peer-disabled:cursor-not-allowed peer-disabled:opacity-70"
)

const Label = React.forwardRef(({ className, ...props }, ref) => (
    <LabelPrimitive.Root ref={ref} className={cn(labelVariants(),
        className)} {...props} />
))
Label.displayName = LabelPrimitive.Root.displayName

export { Label }

```

menubar.jsx

"use client"

```

import * as React from "react"
import * as MenubarPrimitive from "@radix-ui/react-menubar"

```

```

import { Check, ChevronRight, Circle } from "lucide-react"

import { cn } from "@lib/utils"

function MenubarMenu({
  ...props
}) {
  return <MenubarPrimitive.Menu {...props} />;
}

function MenubarGroup({
  ...props
}) {
  return <MenubarPrimitive.Group {...props} />;
}

function MenubarPortal({
  ...props
}) {
  return <MenubarPrimitive.Portal {...props} />;
}

function MenubarRadioGroup({
  ...props
}) {
  return <MenubarPrimitive.RadioGroup {...props} />;
}

function MenubarSub({
  ...props
}) {
  return <MenubarPrimitive.Sub data-slot="menubar-sub" {...props}
/>>;
}

const Menubar = React.forwardRef(({ className, ...props }, ref) =>
(
  <MenubarPrimitive.Root
    ref={ref}
    className={cn(
      "flex h-9 items-center space-x-1 rounded-md border
bg-background p-1 shadow-sm",

```



```

        className
      })
    {...props} />
  ))
  Menubar.displayName = MenubarPrimitive.Root.displayName

  const MenubarTrigger = React.forwardRef(({ className, ...props },
ref) => (
    <MenubarPrimitive.Trigger
      ref={ref}
      className={cn(
        "flex cursor-default select-none items-center rounded-sm
px-3 py-1 text-sm font-medium outline-none focus:bg-accent
focus:text-accent-foreground data-[state=open]:bg-accent
data-[state=open]:text-accent-foreground",
        className
      )}
    {...props} />
  ))
  MenubarTrigger.displayName = MenubarPrimitive.Trigger.displayName

  const MenubarSubTrigger = React.forwardRef(({ className, inset,
children, ...props }, ref) => (
    <MenubarPrimitive.SubTrigger
      ref={ref}
      className={cn(
        "flex cursor-default select-none items-center rounded-sm
px-2 py-1.5 text-sm outline-none focus:bg-accent
focus:text-accent-foreground data-[state=open]:bg-accent
data-[state=open]:text-accent-foreground",
        inset && "pl-8",
        className
      )}
    {...props}>
    {children}
    <ChevronRight className="ml-auto h-4 w-4" />
  </MenubarPrimitive.SubTrigger>
  ))
  MenubarSubTrigger.displayName =
MenubarPrimitive.SubTrigger.displayName

```

```

    const MenubarSubContent = React.forwardRef(({ className, ...props
}, ref) => (
    <MenubarPrimitive.SubContent
      ref={ref}
      className={cn(
        "z-50 min-w-[8rem] overflow-hidden rounded-md border
bg-popover p-1 text-popover-foreground shadow-lg
data-[state=open]:animate-in data-[state=closed]:animate-out
data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0
data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95
data-[side=bottom]:slide-in-from-top-2
data-[side=left]:slide-in-from-right-2
data-[side=right]:slide-in-from-left-2
data-[side=top]:slide-in-from-bottom-2",
        className
      )}
      {...props} />
    ))
    MenubarSubContent.displayName =
MenubarPrimitive.SubContent.displayName

```

```

    const MenubarContent = React.forwardRef((
      { className, align = "start", alignOffset = -4, sideOffset = 8,
...props },
      ref
    ) => (
      <MenubarPrimitive.Portal>
        <MenubarPrimitive.Content
          ref={ref}
          align={align}
          alignOffset={alignOffset}
          sideOffset={sideOffset}
          className={cn(
            "z-50 min-w-[12rem] overflow-hidden rounded-md border
bg-popover p-1 text-popover-foreground shadow-md
data-[state=open]:animate-in data-[state=closed]:fade-out-0
data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95
data-[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2
data-[side=left]:slide-in-from-right-2
data-[side=right]:slide-in-from-left-2
data-[side=top]:slide-in-from-bottom-2",
            className

```

```

    })
    {...props} />
  </MenubarPrimitive.Portal>
))
MenubarContent.displayName = MenubarPrimitive.Content.displayName

const MenubarItem = React.forwardRef(({ className, inset, ...props
}, ref) => (
  <MenubarPrimitive.Item
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center
rounded-sm px-2 py-1.5 text-sm outline-none focus:bg-accent
focus:text-accent-foreground data-[disabled]:pointer-events-none
data-[disabled]:opacity-50",
      inset && "pl-8",
      className
    )}
    {...props} />
))
MenubarItem.displayName = MenubarPrimitive.Item.displayName

const MenubarCheckboxItem = React.forwardRef(({ className,
children, checked, ...props }, ref) => (
  <MenubarPrimitive.CheckboxItem
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center
rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none focus:bg-accent
focus:text-accent-foreground data-[disabled]:pointer-events-none
data-[disabled]:opacity-50",
      className
    )}
    checked={checked}
    {...props}>
    <span className="absolute left-2 flex h-3.5 w-3.5 items-center
justify-center">
      <MenubarPrimitive.ItemIndicator>
        <Check className="h-4 w-4" />
      </MenubarPrimitive.ItemIndicator>
    </span>
    {children}
  </MenubarPrimitive.CheckboxItem>
))
MenubarCheckboxItem.displayName = MenubarPrimitive.CheckboxItem.displayName

```

```

        </MenubarPrimitive.CheckboxItem>
    ))
    MenubarCheckboxItem.displayName =
MenubarPrimitive.CheckboxItem.displayName

    const MenubarRadioItem = React.forwardRef(({ className, children,
...props }, ref) => (
    <MenubarPrimitive.RadioItem
        ref={ref}
        className={cn(
            "relative flex cursor-default select-none items-center
rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none focus:bg-accent
focus:text-accent-foreground data-[disabled]:pointer-events-none
data-[disabled]:opacity-50",
            className
        )}
        {...props}>
        <span className="absolute left-2 flex h-3.5 w-3.5 items-center
justify-center">
            <MenubarPrimitive.ItemIndicator>
                <Circle className="h-4 w-4 fill-current" />
            </MenubarPrimitive.ItemIndicator>
        </span>
        {children}
    </MenubarPrimitive.RadioItem>
    ))
    MenubarRadioItem.displayName =
MenubarPrimitive.RadioItem.displayName

    const MenubarLabel = React.forwardRef(({ className, inset,
...props }, ref) => (
    <MenubarPrimitive.Label
        ref={ref}
        className={cn("px-2 py-1.5 text-sm font-semibold", inset &&
"pl-8", className)}
        {...props} />
    ))
    MenubarLabel.displayName = MenubarPrimitive.Label.displayName

    const MenubarSeparator = React.forwardRef(({ className, ...props
}, ref) => (
    <MenubarPrimitive.Separator

```

```

        ref={ref}
        className={cn("-mx-1 my-1 h-px bg-muted", className)}
        {...props} />
    ))
    MenubarSeparator.displayName =
MenubarPrimitive.Separator.displayName

const MenubarShortcut = ({
  className,
  ...props
}) => {
  return (
    <span
      className={cn("ml-auto text-xs tracking-widest
text-muted-foreground", className)}
      {...props} />
    );
  }
MenubarShortcut.displayName = "MenubarShortcut"

export {
  Menubar,
  MenubarMenu,
  MenubarTrigger,
  MenubarContent,
  MenubarItem,
  MenubarSeparator,
  MenubarLabel,
  MenubarCheckboxItem,
  MenubarRadioGroup,
  MenubarRadioItem,
  MenubarPortal,
  MenubarSubContent,
  MenubarSubTrigger,
  MenubarGroup,
  MenubarSub,
  MenubarShortcut,
}

```

navigation-menu.jsx

```
import * as React from "react"
```

```

import * as NavigationMenuPrimitive from
"@radix-ui/react-navigation-menu"
import { cva } from "class-variance-authority"
import { ChevronDown } from "lucide-react"

import { cn } from "@/lib/utils"

const NavigationMenu = React.forwardRef(({ className, children,
...props }, ref) => (
  <NavigationMenuPrimitive.Root
    ref={ref}
    className={cn(
      "relative z-10 flex max-w-max flex-1 items-center
justify-center",
      className
    )}
    {...props}>
    {children}
    <NavigationMenuViewport />
  </NavigationMenuPrimitive.Root>
))
NavigationMenu.displayName =
NavigationMenuPrimitive.Root.displayName

const NavigationMenuList = React.forwardRef(({ className, ...props
}, ref) => (
  <NavigationMenuPrimitive.List
    ref={ref}
    className={cn(
      "group flex flex-1 list-none items-center justify-center
space-x-1",
      className
    )}
    {...props} />
))
NavigationMenuList.displayName =
NavigationMenuPrimitive.List.displayName

const NavigationMenuItem = NavigationMenuPrimitive.Item

const navigationMenuTriggerStyle = cva(

```

```

        "group inline-flex h-9 w-max items-center justify-center
rounded-md bg-background px-4 py-2 text-sm font-medium transition-colors
hover:bg-accent hover:text-accent-foreground focus:bg-accent
focus:text-accent-foreground focus:outline-none
disabled:pointer-events-none disabled:opacity-50
data-[active]:bg-accent/50 data-[state=open]:bg-accent/50"
    )

```

```

    const NavigationMenuTrigger = React.forwardRef(({ className,
children, ...props }, ref) => (
        <NavigationMenuPrimitive.Trigger
            ref={ref}
            className={cn(navigationMenuTriggerStyle(), "group",
className)}
            {...props}>
            {children}{" "}
            <ChevronDown
                className="relative top-[1px] ml-1 h-3 w-3 transition
duration-300 group-data-[state=open]:rotate-180"
                aria-hidden="true" />
            </NavigationMenuPrimitive.Trigger>
        )
    ))
    NavigationMenuTrigger.displayName =
    NavigationMenuPrimitive.Trigger.displayName

```

```

    const NavigationMenuContent = React.forwardRef(({ className,
...props }, ref) => (
        <NavigationMenuPrimitive.Content
            ref={ref}
            className={cn(
                "left-0 top-0 w-full data-[motion^=from-]:animate-in
data-[motion^=to-]:animate-out data-[motion^=from-]:fade-in
data-[motion^=to-]:fade-out
data-[motion=from-end]:slide-in-from-right-52
data-[motion=from-start]:slide-in-from-left-52
data-[motion=to-end]:slide-out-to-right-52
data-[motion=to-start]:slide-out-to-left-52 md:absolute md:w-auto ",
                className
            )}
            {...props} />
        )
    ))

```

```

    NavigationMenuContent.displayName =
NavigationMenuPrimitive.Content.displayName

    const NavigationMenuLink = NavigationMenuPrimitive.Link

    const NavigationMenuViewport = React.forwardRef(({ className,
...props }, ref) => (
      <div className={cn("absolute left-0 top-full flex
justify-center")}>
        <NavigationMenuPrimitive.Viewport
          className={cn(
            "origin-top-center relative mt-1.5
h-[var(--radix-navigation-menu-viewport-height)] w-full overflow-hidden
rounded-md border bg-popover text-popover-foreground shadow
data-[state=open]:animate-in data-[state=closed]:animate-out
data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-90
md:w-[var(--radix-navigation-menu-viewport-width)]",
            className
          )}
          ref={ref}
          {...props} />
        </div>
      )
    )
    NavigationMenuViewport.displayName =
      NavigationMenuPrimitive.Viewport.displayName

    const NavigationMenuIndicator = React.forwardRef(({ className,
...props }, ref) => (
      <NavigationMenuPrimitive.Indicator
        ref={ref}
        className={cn(
          "top-full z-[1] flex h-1.5 items-end justify-center
overflow-hidden data-[state=visible]:animate-in
data-[state=hidden]:animate-out data-[state=hidden]:fade-out
data-[state=visible]:fade-in",
          className
        )}
        {...props}>
        <div
          className="relative top-[60%] h-2 w-2 rotate-45
rounded-tl-sm bg-border shadow-md" />
        </NavigationMenuPrimitive.Indicator>
      </div>
    )
  )
}

```



```

))
NavigationMenuIndicator.displayName =
  NavigationMenuPrimitive.Indicator.displayName

export {
  navigationMenuTriggerStyle,
  NavigationMenu,
  NavigationMenuList,
  NavigationMenuItem,
  NavigationMenuContent,
  NavigationMenuTrigger,
  NavigationMenuLink,
  NavigationMenuIndicator,
  NavigationMenuViewport,
}

```

pagination.jsx

```

import * as React from "react"
import { ChevronLeft, ChevronRight, MoreHorizontal } from
"lucide-react"

import { cn } from "@lib/utils"
import { buttonVariants } from "@components/ui/button";

const Pagination = ({
  className,
  ...props
}) => (
  <nav
    role="navigation"
    aria-label="pagination"
    className={cn("mx-auto flex w-full justify-center",
className)}
    {...props} />
  )
  Pagination.displayName = "Pagination"

  const PaginationContent = React.forwardRef(({ className, ...props
}, ref) => (
    <ul
      ref={ref}
      className={cn("flex flex-row items-center gap-1", className)}

```

```

        {...props} />
    ))
    PaginationContent.displayName = "PaginationContent"

    const PaginationItem = React.forwardRef(({ className, ...props },
ref) => (
        <li ref={ref} className={cn("", className)} {...props} />
    ))
    PaginationItem.displayName = "PaginationItem"

    const PaginationLink = ({
        className,
        isActive,
        size = "icon",
        ...props
    }) => (
        <a
            aria-current={isActive ? "page" : undefined}
            className={cn(buttonVariants({
                variant: isActive ? "outline" : "ghost",
                size,
            }), className)}
            {...props} />
    )
    PaginationLink.displayName = "PaginationLink"

    const PaginationPrevious = ({
        className,
        ...props
    }) => (
        <PaginationLink
            aria-label="Go to previous page"
            size="default"
            className={cn("gap-1 pl-2.5", className)}
            {...props}>
            <ChevronLeft className="h-4 w-4" />
            <span>Previous</span>
        </PaginationLink>
    )
    PaginationPrevious.displayName = "PaginationPrevious"

    const PaginationNext = ({

```

```

        className,
        ...props
    }) => (
        <PaginationLink
            aria-label="Go to next page"
            size="default"
            className={cn("gap-1 pr-2.5", className)}
            {...props}>
            <span>Next</span>
            <ChevronRight className="h-4 w-4" />
        </PaginationLink>
    )
    PaginationNext.displayName = "PaginationNext"

    const PaginationEllipsis = ({
        className,
        ...props
    }) => (
        <span
            aria-hidden
            className={cn("flex h-9 w-9 items-center justify-center",
className)}
            {...props}>
            <MoreHorizontal className="h-4 w-4" />
            <span className="sr-only">More pages</span>
        </span>
    )
    PaginationEllipsis.displayName = "PaginationEllipsis"

    export {
        Pagination,
        PaginationContent,
        PaginationLink,
        PaginationItem,
        PaginationPrevious,
        PaginationNext,
        PaginationEllipsis,
    }

```

popover.jsx

```

import * as React from "react"
import * as PopoverPrimitive from "@radix-ui/react-popover"

```

```

import { cn } from "@lib/utils"

const Popover = PopoverPrimitive.Root

const PopoverTrigger = PopoverPrimitive.Trigger

const PopoverAnchor = PopoverPrimitive.Anchor

const PopoverContent = React.forwardRef(({ className, align =
"center", sideOffset = 4, ...props }, ref) => (
  <PopoverPrimitive.Portal>
    <PopoverPrimitive.Content
      ref={ref}
      align={align}
      sideOffset={sideOffset}
      className={cn(
        "z-50 w-72 rounded-md border bg-popover p-4
text-popover-foreground shadow-md outline-none
data-[state=open]:animate-in data-[state=closed]:animate-out
data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0
data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95
data-[side=bottom]:slide-in-from-top-2
data-[side=left]:slide-in-from-right-2
data-[side=right]:slide-in-from-left-2
data-[side=top]:slide-in-from-bottom-2",
        className
      )}
      {...props} />
    </PopoverPrimitive.Portal>
  ))
PopoverContent.displayName = PopoverPrimitive.Content.displayName

export { Popover, PopoverTrigger, PopoverContent, PopoverAnchor }

```

progress.jsx

"use client"

```

import * as React from "react"
import * as ProgressPrimitive from "@radix-ui/react-progress"

import { cn } from "@lib/utils"

```

```

    const Progress = React.forwardRef(({ className, value, ...props },
ref) => (
    <ProgressPrimitive.Root
      ref={ref}
      className={cn(
        "relative h-2 w-full overflow-hidden rounded-full
bg-primary/20",
        className
      )}
      {...props}>
      <ProgressPrimitive.Indicator
        className="h-full w-full flex-1 bg-primary transition-all"
        style={{ transform: `translateX(-${100 - (value || 0)}%)` }}
      />
    </ProgressPrimitive.Root>
  ))
  Progress.displayName = ProgressPrimitive.Root.displayName

export { Progress }

```

radio-group.jsx

```

import * as React from "react"
import * as RadioGroupPrimitive from "@radix-ui/react-radio-group"
import { Circle } from "lucide-react"

import { cn } from "@lib/utils"

const RadioGroup = React.forwardRef(({ className, ...props }, ref)
=> {
  return (<RadioGroupPrimitive.Root className={cn("grid gap-2",
className)} {...props} ref={ref} />);
})
RadioGroup.displayName = RadioGroupPrimitive.Root.displayName

const RadioGroupItem = React.forwardRef(({ className, ...props },
ref) => {
  return (
    <RadioGroupPrimitive.Item
      ref={ref}
      className={cn(

```

```

        "aspect-square h-4 w-4 rounded-full border border-primary
text-primary shadow focus:outline-none focus-visible:ring-1
focus-visible:ring-ring disabled:cursor-not-allowed
disabled:opacity-50",
        className
      )}
      {...props}>
        <RadioGroupPrimitive.Indicator className="flex items-center
justify-center">
          <Circle className="h-3.5 w-3.5 fill-primary" />
        </RadioGroupPrimitive.Indicator>
      </RadioGroupPrimitive.Item>)
    );
  })
  RadioGroupItem.displayName = RadioGroupPrimitive.Item.displayName

export { RadioGroup, RadioGroupItem }

```

resizable.jsx

```

"use client"

import { GripVertical } from "lucide-react"
import * as ResizablePrimitive from "react-resizable-panels"

import { cn } from "@lib/utils"

const ResizablePanelGroup = ({
  className,
  ...props
}) => (
  <ResizablePrimitive.PanelGroup
    className={cn(
      "flex h-full w-full
data-[panel-group-direction=vertical]:flex-col",
      className
    )}
    {...props} />
)

const ResizablePanel = ResizablePrimitive.Panel

const ResizableHandle = ({

```

```

        withHandle,
        className,
        ...props
    }) => (
        <ResizablePrimitive.PanelResizeHandle
            className={cn(
                "relative flex w-px items-center justify-center bg-border
                after:absolute after:inset-y-0 after:left-1/2 after:w-1
                after:-translate-x-1/2 focus-visible:outline-none focus-visible:ring-1
                focus-visible:ring-ring focus-visible:ring-offset-1
                data-[panel-group-direction=vertical]:h-px
                data-[panel-group-direction=vertical]:w-full
                data-[panel-group-direction=vertical]:after:left-0
                data-[panel-group-direction=vertical]:after:h-1
                data-[panel-group-direction=vertical]:after:w-full
                data-[panel-group-direction=vertical]:after:-translate-y-1/2
                data-[panel-group-direction=vertical]:after:translate-x-0
                [&[data-panel-group-direction=vertical]>div]:rotate-90",
                className
            )}
            {...props}>
            {withHandle && (
                <div
                    className="z-10 flex h-4 w-3 items-center justify-center
                    rounded-sm border bg-border">
                    <GripVertical className="h-2.5 w-2.5" />
                </div>
            )}
        </ResizablePrimitive.PanelResizeHandle>
    )

```

```

export { ResizablePanelGroup, ResizablePanel, ResizableHandle }

```

scroll-area.jsx

```

import * as React from "react"
import * as ScrollAreaPrimitive from "@radix-ui/react-scroll-area"

import { cn } from "@lib/utils"

const ScrollArea = React.forwardRef(({ className, children,
...props }, ref) => (
    <ScrollAreaPrimitive.Root

```

```

    ref={ref}
    className={cn("relative overflow-hidden", className)}
    {...props}>
      <ScrollAreaPrimitive.Viewport className="h-full w-full
rounded-[inherit]">
        {children}
      </ScrollAreaPrimitive.Viewport>
      <ScrollBar />
      <ScrollAreaPrimitive.Corner />
    </ScrollAreaPrimitive.Root>
  ))
  ScrollArea.displayName = ScrollAreaPrimitive.Root.displayName

  const ScrollBar = React.forwardRef(({ className, orientation =
"vertical", ...props }, ref) => (
    <ScrollAreaPrimitive.ScrollAreaScrollbar
      ref={ref}
      orientation={orientation}
      className={cn(
        "flex touch-none select-none transition-colors",
        orientation === "vertical" &&
          "h-full w-2.5 border-l border-l-transparent p-[1px]",
        orientation === "horizontal" &&
          "h-2.5 flex-col border-t border-t-transparent p-[1px]",
        className
      )}
      {...props}>
      <ScrollAreaPrimitive.ScrollAreaThumb className="relative
flex-1 rounded-full bg-border" />
    </ScrollAreaPrimitive.ScrollAreaScrollbar>
  ))
  ScrollBar.displayName =
ScrollAreaPrimitive.ScrollAreaScrollbar.displayName

export { ScrollArea, ScrollBar }

```

select.jsx

```
"use client"
```

```

import * as React from "react"
import * as SelectPrimitive from "@radix-ui/react-select"
import { Check, ChevronDown, ChevronUp } from "lucide-react"

```



```

import { cn } from "@lib/utils"

const Select = SelectPrimitive.Root

const SelectGroup = SelectPrimitive.Group

const SelectValue = SelectPrimitive.Value

const SelectTrigger = React.forwardRef(({ className, children,
...props }, ref) => (
  <SelectPrimitive.Trigger
    ref={ref}
    className={cn(
      "flex h-9 w-full items-center justify-between
whitespace-nowrap rounded-md border border-input bg-transparent px-3
py-2 text-sm shadow-sm ring-offset-background
data-[placeholder]:text-muted-foreground focus:outline-none focus:ring-1
focus:ring-ring disabled:cursor-not-allowed disabled:opacity-50
[&>span]:line-clamp-1",
      className
    )}
    {...props}>
    {children}
    <SelectPrimitive.Icon asChild>
      <ChevronDown className="h-4 w-4 opacity-50" />
    </SelectPrimitive.Icon>
  </SelectPrimitive.Trigger>
))
SelectTrigger.displayName = SelectPrimitive.Trigger.displayName

const SelectScrollUpButton = React.forwardRef(({ className,
...props }, ref) => (
  <SelectPrimitive.ScrollUpButton
    ref={ref}
    className={cn("flex cursor-default items-center justify-center
py-1", className)}
    {...props}>
    <ChevronUp className="h-4 w-4" />
  </SelectPrimitive.ScrollUpButton>
))

```

```

    SelectScrollUpButton.displayName =
    SelectPrimitive.ScrollUpButton.displayName

    const SelectScrollDownButton = React.forwardRef(({ className,
    ...props }, ref) => (
      <SelectPrimitive.ScrollDownButton
        ref={ref}
        className={cn("flex cursor-default items-center justify-center
py-1", className)}
        {...props}>
        <ChevronDown className="h-4 w-4" />
      </SelectPrimitive.ScrollDownButton>
    ))
    SelectScrollDownButton.displayName =
    SelectPrimitive.ScrollDownButton.displayName

    const SelectContent = React.forwardRef(({ className, children,
    position = "popper", ...props }, ref) => (
      <SelectPrimitive.Portal>
        <SelectPrimitive.Content
          ref={ref}
          className={cn(
            "relative z-50 max-h-96 min-w-[8rem] overflow-hidden
rounded-md border bg-popover text-popover-foreground shadow-md
data-[state=open]:animate-in data-[state=closed]:animate-out
data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0
data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95
data-[side=bottom]:slide-in-from-top-2
data-[side=left]:slide-in-from-right-2
data-[side=right]:slide-in-from-left-2
data-[side=top]:slide-in-from-bottom-2",
            position === "popper" &&
            "data-[side=bottom]:translate-y-1
data-[side=left]:-translate-x-1 data-[side=right]:translate-x-1
data-[side=top]:-translate-y-1",
            className
          )}
          position={position}
          {...props}>
          <SelectScrollUpButton />
          <SelectPrimitive.Viewport
            className={cn("p-1", position === "popper" &&

```

```

        "h-[var(--radix-select-trigger-height)] w-full
min-w-[var(--radix-select-trigger-width)]")}>
        {children}
      </SelectPrimitive.Viewport>
      <SelectScrollDownButton />
    </SelectPrimitive.Content>
  </SelectPrimitive.Portal>
))
SelectContent.displayName = SelectPrimitive.Content.displayName

const SelectLabel = React.forwardRef(({ className, ...props },
ref) => (
  <SelectPrimitive.Label
    ref={ref}
    className={cn("px-2 py-1.5 text-sm font-semibold", className)}
    {...props} />
))
SelectLabel.displayName = SelectPrimitive.Label.displayName

const SelectItem = React.forwardRef(({ className, children,
...props }, ref) => (
  <SelectPrimitive.Item
    ref={ref}
    className={cn(
      "relative flex w-full cursor-default select-none
items-center rounded-sm py-1.5 pl-2 pr-8 text-sm outline-none
focus:bg-accent focus:text-accent-foreground
data-[disabled]:pointer-events-none data-[disabled]:opacity-50",
      className
    )}
    {...props}>
    <span className="absolute right-2 flex h-3.5 w-3.5
items-center justify-center">
      <SelectPrimitive.ItemIndicator>
        <Check className="h-4 w-4" />
      </SelectPrimitive.ItemIndicator>
    </span>

    <SelectPrimitive.ItemText>{children}</SelectPrimitive.ItemText>
  </SelectPrimitive.Item>
))
SelectItem.displayName = SelectPrimitive.Item.displayName

```

```

    const SelectSeparator = React.forwardRef(({ className, ...props },
ref) => (
    <SelectPrimitive.Separator
      ref={ref}
      className={cn("-mx-1 my-1 h-px bg-muted", className)}
      {...props} />
    ))
    SelectSeparator.displayName =
SelectPrimitive.Separator.displayName

export {
  Select,
  SelectGroup,
  SelectValue,
  SelectTrigger,
  SelectContent,
  SelectLabel,
  SelectItem,
  SelectSeparator,
  SelectScrollUpButton,
  SelectScrollDownButton,
}

```

separator.jsx

```

import * as React from "react"
import * as SeparatorPrimitive from "@radix-ui/react-separator"

import { cn } from "@lib/utils"

const Separator = React.forwardRef((
  { className, orientation = "horizontal", decorative = true,
...props },
  ref
) => (
  <SeparatorPrimitive.Root
    ref={ref}
    decorative={decorative}
    orientation={orientation}
    className={cn(
      "shrink-0 bg-border",

```

```

        orientation === "horizontal" ? "h-[1px] w-full" : "h-full
w-[1px]",
        className
    )}
    {...props} />
))
Separator.displayName = SeparatorPrimitive.Root.displayName

export { Separator }

```

sheet.jsx

```

import * as React from "react"
import * as SeparatorPrimitive from "@radix-ui/react-separator"

import { cn } from "@lib/utils"

const Separator = React.forwardRef((
  { className, orientation = "horizontal", decorative = true,
...props },
  ref
) => (
  <SeparatorPrimitive.Root
    ref={ref}
    decorative={decorative}
    orientation={orientation}
    className={cn(
      "shrink-0 bg-border",
      orientation === "horizontal" ? "h-[1px] w-full" : "h-full
w-[1px]",
      className
    )}
    {...props} />
))
Separator.displayName = SeparatorPrimitive.Root.displayName

export { Separator }

```

sidebar.jsx

```

import * as React from "react"
import { Slot } from "@radix-ui/react-slot"
import { cva } from "class-variance-authority";
import { PanelLeft } from "lucide-react"

```

```

import { useIsMobile } from "@/hooks/use-mobile"
import { cn } from "@/lib/utils"
import { Button } from "@/components/ui/button"
import { Input } from "@/components/ui/input"
import { Separator } from "@/components/ui/separator"
import { Sheet, SheetContent } from "@/components/ui/sheet"
import { Skeleton } from "@/components/ui/skeleton"
import {
  Tooltip,
  TooltipContent,
  TooltipProvider,
  TooltipTrigger,
} from "@/components/ui/tooltip"

const SIDEBAR_COOKIE_NAME = "sidebar_state"
const SIDEBAR_COOKIE_MAX_AGE = 60 * 60 * 24 * 7
const SIDEBAR_WIDTH = "16rem"
const SIDEBAR_WIDTH_MOBILE = "18rem"
const SIDEBAR_WIDTH_ICON = "3rem"
const SIDEBAR_KEYBOARD_SHORTCUT = "b"

const SidebarContext = React.createContext(null)

function useSidebar() {
  const context = React.useContext(SidebarContext)
  if (!context) {
    throw new Error("useSidebar must be used within a SidebarProvider.")
  }

  return context
}

const SidebarProvider = React.forwardRef((
  {
    defaultOpen = true,
    open: openProp,
    onOpenChange: setOpenProp,
    className,
    style,
    children,
  },
  ref
))

```

```

        ...props
    },
    ref
) => {
    const isMobile = useIsMobile()
    const [openMobile, setOpenMobile] = React.useState(false)

    // This is the internal state of the sidebar.
    // We use openProp and setOpenProp for control from outside the
    component.
    const [_open, _setOpen] = React.useState(defaultOpen)
    const open = openProp ?? _open
    const setOpen = React.useCallback((value) => {
        const openState = typeof value === "function" ? value(open) :
value
        if (setOpenProp) {
            setOpenProp(openState)
        } else {
            _setOpen(openState)
        }

        // This sets the cookie to keep the sidebar state.
        document.cookie = `${SIDEBAR_COOKIE_NAME}=${openState};
path=/; max-age=${SIDEBAR_COOKIE_MAX_AGE}`
    }, [setOpenProp, open])

    // Helper to toggle the sidebar.
    const toggleSidebar = React.useCallback(() => {
        return isMobile
            ? setOpenMobile((open) => !open)
            : setOpen((open) => !open);
    }, [isMobile, setOpen, setOpenMobile])

    // Adds a keyboard shortcut to toggle the sidebar.
    React.useEffect(() => {
        const handleKeyDown = (event) => {
            if (
                event.key === SIDEBAR_KEYBOARD_SHORTCUT &&
                (event.metaKey || event.ctrlKey)
            ) {
                event.preventDefault()
                toggleSidebar()
            }
        }
    })
}

```

```

    }
  }

  window.addEventListener("keydown", handleKeyDown)
  return () => window.removeEventListener("keydown",
handleKeyDown);
}, [toggleSidebar])

// We add a state so that we can do data-state="expanded" or
"collapsed".
// This makes it easier to style the sidebar with Tailwind
classes.
const state = open ? "expanded" : "collapsed"

const contextValue = React.useMemo(() => ({
  state,
  open,
  setOpen,
  isMobile,
  openMobile,
  setOpenMobile,
  toggleSidebar,
}), [state, open, setOpen, isMobile, openMobile, setOpenMobile,
toggleSidebar])

return (
  <SidebarContext.Provider value={contextValue}>
    <TooltipProvider delayDuration={0}>
      <div
        style={
          {
            "--sidebar-width": SIDEBAR_WIDTH,
            "--sidebar-width-icon": SIDEBAR_WIDTH_ICON,
            ...style
          }
        }
        className={cn(
          "group/sidebar-wrapper flex min-h-svh w-full
has-[[data-variant=inset]]:bg-sidebar",
          className
        )}
        ref={ref}

```



```

        {...props}>
        {children}
      </div>
    </TooltipProvider>
  </SidebarContext.Provider>
);
})
SidebarProvider.displayName = "SidebarProvider"

const Sidebar = React.forwardRef((
  {
    side = "left",
    variant = "sidebar",
    collapsible = "offcanvas",
    className,
    children,
    ...props
  },
  ref
) => {
  const { isMobile, state, openMobile, setOpenMobile } =
useSidebar()

  if (collapsible === "none") {
    return (
      <div
        className={cn(
          "flex h-full w-[--sidebar-width] flex-col bg-sidebar
text-sidebar-foreground",
          className
        )}
        ref={ref}
        {...props}>
        {children}
      </div>
    );
  }

  if (isMobile) {
    return (
      <Sheet open={openMobile} onOpenChange={setOpenMobile}
        {...props}>

```

```

    <SheetContent
      data-sidebar="sidebar"
      data-mobile="true"
      className="w-[--sidebar-width] bg-sidebar p-0
text-sidebar-foreground [&>button]:hidden"
      style={
        {
          "--sidebar-width": SIDEBAR_WIDTH_MOBILE
        }
      }
      side={side}>
    <div className="flex h-full w-full
flex-col">{children}</div>
    </SheetContent>
  </Sheet>)
);
}

return (
  <div
    ref={ref}
    className="group peer hidden text-sidebar-foreground
md:block"
    data-state={state}
    data-collapsible={state === "collapsed" ? collapsible : ""}
    data-variant={variant}
    data-side={side}>
    {/ * This is what handles the sidebar gap on desktop */}
    <div
      className={cn(
        "relative h-svh w-[--sidebar-width] bg-transparent
transition-[width] duration-200 ease-linear",
        "group-data-[collapsible=offcanvas]:w-0",
        "group-data-[side=right]:rotate-180",
        variant === "floating" || variant === "inset"
          ?
"group-data-[collapsible=icon]:w-[calc(var(--sidebar-width-icon)_+_theme
(spacing.4))]"
          :
"group-data-[collapsible=icon]:w-[--sidebar-width-icon]"
      )} />
    <div

```

```

        className={cn(
          "fixed inset-y-0 z-10 hidden h-svh w-[--sidebar-width]
transition-[left,right,width] duration-200 ease-linear md:flex",
          side === "left"
            ? "left-0
group-data-[collapsible=offcanvas]:left-[calc(var(--sidebar-width)*-1)]"
            : "right-0
group-data-[collapsible=offcanvas]:right-[calc(var(--sidebar-width)*-1)]"
        ),
        // Adjust the padding for floating and inset variants.
        variant === "floating" || variant === "inset"
          ? "p-2"
          : "",
        group-data-[collapsible=icon]:w-[calc(var(--sidebar-width-icon)_+_theme(
          spacing.4)_+2px)]"
      );
    }
    { ...props }
  <div
    data-sidebar="sidebar"
    className="flex h-full w-full flex-col bg-sidebar
group-data-[variant=floating]:rounded-lg
group-data-[variant=floating]:border
group-data-[variant=floating]:border-sidebar-border
group-data-[variant=floating]:shadow"
    {children}
  </div>
</div>
</div>
);
})
Sidebar.displayName = "Sidebar"

const SidebarTrigger = React.forwardRef(({ className, onClick,
asChild = false, ...props }, ref) => {
  const { toggleSidebar } = useSidebar()

  return (
    <Button
      ref={ref}

```

```

    data-sidebar="trigger"
    variant="ghost"
    size="icon"
    className={cn("h-7 w-7", className)}
    onClick={ (event) => {
      onClick?.(event)
      toggleSidebar()
    }}
    asChild={asChild}
    {...props}>
    {asChild ? (
      <PanelLeft />
    ) : (
      <>
        <PanelLeft />
        <span className="sr-only">Toggle Sidebar</span>
      </>
    )}
  </Button>)
);
})
SidebarTrigger.displayName = "SidebarTrigger"

const SidebarRail = React.forwardRef(({ className, ...props },
ref) => {
  const { toggleSidebar } = useSidebar()

  return (
    <button
      ref={ref}
      data-sidebar="rail"
      aria-label="Toggle Sidebar"
      tabIndex={-1}
      onClick={toggleSidebar}
      title="Toggle Sidebar"
      className={cn(
        "absolute inset-y-0 z-20 hidden w-4 -translate-x-1/2
transition-all ease-linear after:absolute after:inset-y-0 after:left-1/2
after:w-[2px] hover:after:bg-sidebar-border
group-data-[side=left]:-right-4 group-data-[side=right]:left-0 sm:flex",
        "[[data-side=left]_&]:cursor-w-resize
[[data-side=right]_&]:cursor-e-resize",

```

```

"[[data-side=left][data-state=collapsed]_&]:cursor-e-resize
[[data-side=right][data-state=collapsed]_&]:cursor-w-resize",
      "group-data-[collapsible=offcanvas]:translate-x-0
group-data-[collapsible=offcanvas]:after:left-full
group-data-[collapsible=offcanvas]:hover:bg-sidebar",

"[[data-side=left][data-collapsible=offcanvas]_&]:-right-2",

"[[data-side=right][data-collapsible=offcanvas]_&]:-left-2",
      className
    )}
    {...props} />)
  );
})
SidebarRail.displayName = "SidebarRail"

const SidebarInset = React.forwardRef(({ className, ...props },
ref) => {
  return (
    <main
      ref={ref}
      className={cn(
        "relative flex min-h-svh flex-1 flex-col bg-background",

"peer-data-[variant=inset]:min-h-[calc(100svh-theme(spacing.4))]"
md:peer-data-[variant=inset]:m-2
md:peer-data-[state=collapsed]:peer-data-[variant=inset]:ml-2
md:peer-data-[variant=inset]:ml-0
md:peer-data-[variant=inset]:rounded-xl
md:peer-data-[variant=inset]:shadow",
        className
      )}
      {...props} />)
  );
})
SidebarInset.displayName = "SidebarInset"

const SidebarInput = React.forwardRef(({ className, ...props },
ref) => {
  return (
    <Input

```

```

        ref={ref}
        data-sidebar="input"
        className={cn(
            "h-8 w-full bg-background shadow-none focus-visible:ring-2
focus-visible:ring-sidebar-ring",
            className
        )}
        {...props} />)
    );
})
SidebarInput.displayName = "SidebarInput"

const SidebarHeader = React.forwardRef(({ className, ...props },
ref) => {
    return (
        <div
            ref={ref}
            data-sidebar="header"
            className={cn("flex flex-col gap-2 p-2", className)}
            {...props} />
        );
    );
})
SidebarHeader.displayName = "SidebarHeader"

const SidebarFooter = React.forwardRef(({ className, ...props },
ref) => {
    return (
        <div
            ref={ref}
            data-sidebar="footer"
            className={cn("flex flex-col gap-2 p-2", className)}
            {...props} />
        );
    );
})
SidebarFooter.displayName = "SidebarFooter"

const SidebarSeparator = React.forwardRef(({ className, ...props
}, ref) => {
    return (
        <Separator
            ref={ref}
            data-sidebar="separator"

```

```

        className={cn("mx-2 w-auto bg-sidebar-border", className)}
        {...props} />)
    );
})
SidebarSeparator.displayName = "SidebarSeparator"

const SidebarContent = React.forwardRef(({ className, ...props },
ref) => {
    return (
        <div
            ref={ref}
            data-sidebar="content"
            className={cn(
                "flex min-h-0 flex-1 flex-col gap-2 overflow-auto
group-data-[collapsible=icon]:overflow-hidden",
                className
            )}
            {...props} />)
    );
})
SidebarContent.displayName = "SidebarContent"

const SidebarGroup = React.forwardRef(({ className, ...props },
ref) => {
    return (
        <div
            ref={ref}
            data-sidebar="group"
            className={cn("relative flex w-full min-w-0 flex-col p-2",
className)}
            {...props} />)
    );
})
SidebarGroup.displayName = "SidebarGroup"

const SidebarGroupLabel = React.forwardRef(({ className, asChild =
false, ...props }, ref) => {
    const Comp = asChild ? Slot : "div"

    return (
        <Comp
            ref={ref}

```

```

        data-sidebar="group-label"
        className={cn(
            "flex h-8 shrink-0 items-center rounded-md px-2 text-xs
font-medium text-sidebar-foreground/70 outline-none ring-sidebar-ring
transition-[margin,opacity] duration-200 ease-linear
focus-visible:ring-2 [>svg]:size-4 [>svg]:shrink-0",
            "group-data-[collapsible=icon]:-mt-8
group-data-[collapsible=icon]:opacity-0",
            className
        )}
        {...props} />
    );
})
SidebarGroupLabel.displayName = "SidebarGroupLabel"

const SidebarGroupAction = React.forwardRef(({ className, asChild
= false, ...props }, ref) => {
    const Comp = asChild ? Slot : "button"

    return (
        <Comp
            ref={ref}
            data-sidebar="group-action"
            className={cn(
                "absolute right-3 top-3.5 flex aspect-square w-5
items-center justify-center rounded-md p-0 text-sidebar-foreground
outline-none ring-sidebar-ring transition-transform
hover:bg-sidebar-accent hover:text-sidebar-accent-foreground
focus-visible:ring-2 [>svg]:size-4 [>svg]:shrink-0",
                // Increases the hit area of the button on mobile.
                "after:absolute after:-inset-2 after:md:hidden",
                "group-data-[collapsible=icon]:hidden",
                className
            )}
            {...props} />
    );
})
SidebarGroupAction.displayName = "SidebarGroupAction"

const SidebarGroupContent = React.forwardRef(({ className,
...props }, ref) => (
    <div

```



```

        ref={ref}
        data-sidebar="group-content"
        className={cn("w-full text-sm", className)}
        {...props} />
    ))
    SidebarGroupContent.displayName = "SidebarGroupContent"

    const SidebarMenu = React.forwardRef(({ className, ...props },
ref) => (
        <ul
            ref={ref}
            data-sidebar="menu"
            className={cn("flex w-full min-w-0 flex-col gap-1",
className)}
            {...props} />
        )
        SidebarMenu.displayName = "SidebarMenu"

        const SidebarMenuItem = React.forwardRef(({ className, ...props },
ref) => (
            <li
                ref={ref}
                data-sidebar="menu-item"
                className={cn("group/menu-item relative", className)}
                {...props} />
            )
            SidebarMenuItem.displayName = "SidebarMenuItem"

            const sidebarMenuButtonVariants = cva(
                "peer/menu-button flex w-full items-center gap-2 overflow-hidden
rounded-md p-2 text-left text-sm outline-none ring-sidebar-ring
transition-[width,height,padding] hover:bg-sidebar-accent
hover:text-sidebar-accent-foreground focus-visible:ring-2
active:bg-sidebar-accent active:text-sidebar-accent-foreground
disabled:pointer-events-none disabled:opacity-50
group-has-[[data-sidebar=menu-action]]/menu-item:pr-8
aria-disabled:pointer-events-none aria-disabled:opacity-50
data-[active=true]:bg-sidebar-accent data-[active=true]:font-medium
data-[active=true]:text-sidebar-accent-foreground
data-[state=open]:hover:bg-sidebar-accent
data-[state=open]:hover:text-sidebar-accent-foreground"

```

```

group-data-[collapsible=icon]:!size-8 group-data-[collapsible=icon]:!p-2
[&>span:last-child]:truncate [&>svg]:size-4 [&>svg]:shrink-0",
    {
      variants: {
        variant: {
          default: "hover:bg-sidebar-accent
hover:text-sidebar-accent-foreground",
          outline:
            "bg-background
shadow-[0_0_0_1px_hsl(var(--sidebar-border))] hover:bg-sidebar-accent
hover:text-sidebar-accent-foreground
hover:shadow-[0_0_0_1px_hsl(var(--sidebar-accent))]",
        },
        size: {
          default: "h-8 text-sm",
          sm: "h-7 text-xs",
          lg: "h-12 text-sm group-data-[collapsible=icon]:!p-0",
        },
      },
      defaultVariants: {
        variant: "default",
        size: "default",
      },
    }
  )

const SidebarMenuButton = React.forwardRef((
  {
    asChild = false,
    isActive = false,
    variant = "default",
    size = "default",
    tooltip,
    className,
    ...props
  },
  ref
) => {
  const Comp = asChild ? Slot : "button"
  const { isMobile, state } = useSidebar()

  const button = (

```

```

    <Comp
      ref={ref}
      data-sidebar="menu-button"
      data-size={size}
      data-active={isActive}
      className={cn(sidebarMenuButtonVariants({ variant, size })),
className)}
      {...props} />
  )

```

```

  if (!tooltip) {
    return button
  }

```

```

  if (typeof tooltip === "string") {
    tooltip = {
      children: tooltip,
    }
  }

```

```

  return (
    (<Tooltip>
      <TooltipTrigger asChild>{button}</TooltipTrigger>
      <TooltipContent
        side="right"
        align="center"
        hidden={state !== "collapsed" || isMobile}
        {...tooltip} />
    </Tooltip>)
  );

```

```

})

```

```

SidebarMenuButton.displayName = "SidebarMenuButton"

```

```

const SidebarMenuAction = React.forwardRef(({ className, asChild =
false, showOnHover = false, ...props }, ref) => {
  const Comp = asChild ? Slot : "button"

```

```

  return (
    (<Comp
      ref={ref}
      data-sidebar="menu-action"
      className={cn(

```

```

        "absolute right-1 top-1.5 flex aspect-square w-5
items-center justify-center rounded-md p-0 text-sidebar-foreground
outline-none ring-sidebar-ring transition-transform
hover:bg-sidebar-accent hover:text-sidebar-accent-foreground
focus-visible:ring-2
peer-hover/menu-button:text-sidebar-accent-foreground [>svg]:size-4
[>svg]:shrink-0",
        // Increases the hit area of the button on mobile.
        "after:absolute after:-inset-2 after:md:hidden",
        "peer-data-[size=sm]/menu-button:top-1",
        "peer-data-[size=default]/menu-button:top-1.5",
        "peer-data-[size=lg]/menu-button:top-2.5",
        "group-data-[collapsible=icon]:hidden",
        showOnHover &&
        "group-focus-within/menu-item:opacity-100
group-hover/menu-item:opacity-100 data-[state=open]:opacity-100
peer-data-[active=true]/menu-button:text-sidebar-accent-foreground
md:opacity-0",
        className
      )}
      {...props} />)
    );
  })
  SidebarMenuAction.displayName = "SidebarMenuAction"

  const SidebarMenuBadge = React.forwardRef(({ className, ...props
}, ref) => (
    <div
      ref={ref}
      data-sidebar="menu-badge"
      className={cn(
        "pointer-events-none absolute right-1 flex h-5 min-w-5
select-none items-center justify-center rounded-md px-1 text-xs
font-medium tabular-nums text-sidebar-foreground",
        "peer-hover/menu-button:text-sidebar-accent-foreground
peer-data-[active=true]/menu-button:text-sidebar-accent-foreground",
        "peer-data-[size=sm]/menu-button:top-1",
        "peer-data-[size=default]/menu-button:top-1.5",
        "peer-data-[size=lg]/menu-button:top-2.5",
        "group-data-[collapsible=icon]:hidden",
        className
      )}
    >

```

```

        {...props} />
    ))
    SidebarMenuBadge.displayName = "SidebarMenuBadge"

    const SidebarMenuSkeleton = React.forwardRef(({ className,
showIcon = false, ...props }, ref) => {
    // Random width between 50 to 90%.
    const width = React.useMemo(() => {
        return `${Math.floor(Math.random() * 40) + 50}%`;
    }, [])

    return (
        <div
            ref={ref}
            data-sidebar="menu-skeleton"
            className={cn("flex h-8 items-center gap-2 rounded-md px-2",
className)}
            {...props}>
            {showIcon && (
                <Skeleton className="size-4 rounded-md"
data-sidebar="menu-skeleton-icon" />
            )}
            <Skeleton
                className="h-4 max-w-[--skeleton-width] flex-1"
                data-sidebar="menu-skeleton-text"
                style={
                    {
                        "--skeleton-width": width
                    }
                } />
        </div>)
    );
})
SidebarMenuSkeleton.displayName = "SidebarMenuSkeleton"

const SidebarMenuSub = React.forwardRef(({ className, ...props },
ref) => (
    <ul
        ref={ref}
        data-sidebar="menu-sub"
        className={cn(

```

```

        "mx-3.5 flex min-w-0 translate-x-px flex-col gap-1 border-1
border-sidebar-border px-2.5 py-0.5",
        "group-data-[collapsible=icon]:hidden",
        className
    )}
    {...props} />
))
SidebarMenuSub.displayName = "SidebarMenuSub"

const SidebarMenuSubItem = React.forwardRef(({ ...props }, ref) =>
<li ref={ref} {...props} />)
SidebarMenuSubItem.displayName = "SidebarMenuSubItem"

const SidebarMenuSubButton = React.forwardRef(
    ({ asChild = false, size = "md", isActive, className, ...props
}, ref) => {
    const Comp = asChild ? Slot : "a"

    return (
        <Comp
            ref={ref}
            data-sidebar="menu-sub-button"
            data-size={size}
            data-active={isActive}
            className={cn(
                "flex h-7 min-w-0 -translate-x-px items-center gap-2
overflow-hidden rounded-md px-2 text-sidebar-foreground outline-none
ring-sidebar-ring hover:bg-sidebar-accent
hover:text-sidebar-accent-foreground focus-visible:ring-2
active:bg-sidebar-accent active:text-sidebar-accent-foreground
disabled:pointer-events-none disabled:opacity-50
aria-disabled:pointer-events-none aria-disabled:opacity-50
[&>span:last-child]:truncate [&>svg]:size-4 [&>svg]:shrink-0
[&>svg]:text-sidebar-accent-foreground",
                "data-[active=true]:bg-sidebar-accent
data-[active=true]:text-sidebar-accent-foreground",
                size === "sm" && "text-xs",
                size === "md" && "text-sm",
                "group-data-[collapsible=icon]:hidden",
                className
            )}
        {...props} />)

```

```

    );
  }
)
SidebarMenuSubButton.displayName = "SidebarMenuSubButton"

export {
  Sidebar,
  SidebarContent,
  SidebarFooter,
  SidebarGroup,
  SidebarGroupAction,
  SidebarGroupContent,
  SidebarGroupLabel,
  SidebarHeader,
  SidebarInput,
  SidebarInset,
  SidebarMenu,
  SidebarMenuAction,
  SidebarMenuBadge,
  SidebarMenuButton,
  SidebarMenuItem,
  SidebarMenuSkeleton,
  SidebarMenuSub,
  SidebarMenuSubButton,
  SidebarMenuSubItem,
  SidebarProvider,
  SidebarRail,
  SidebarSeparator,
  SidebarTrigger,
  useSidebar,
}

```

skeleton.jsx

```

import { cn } from "@lib/utils"

function Skeleton({
  className,
  ...props
}) {
  return (
    <div

```

```

        className={cn("animate-pulse rounded-md bg-primary/10",
className)}
        {...props} />
    );
}

```

```
export { Skeleton }
```

slider.jsx

```

import * as React from "react"
import * as SliderPrimitive from "@radix-ui/react-slider"

import { cn } from "@lib/utils"

const Slider = React.forwardRef(({ className, ...props }, ref) =>
(
    <SliderPrimitive.Root
        ref={ref}
        className={cn("relative flex w-full touch-none select-none
items-center", className)}
        {...props}>
        <SliderPrimitive.Track
            className="relative h-1.5 w-full grow overflow-hidden
rounded-full bg-primary/20">
            <SliderPrimitive.Range className="absolute h-full
bg-primary" />
        </SliderPrimitive.Track>
        <SliderPrimitive.Thumb
            className="block h-4 w-4 rounded-full border
border-primary/50 bg-background shadow transition-colors
focus-visible:outline-none focus-visible:ring-1 focus-visible:ring-ring
disabled:pointer-events-none disabled:opacity-50" />
        </SliderPrimitive.Root>
    ))
Slider.displayName = SliderPrimitive.Root.displayName

export { Slider }

```

sonner.jsx

```

"use client";
import { useTheme } from "next-themes"
import { Toaster as Sonner } from "sonner"

```



```

const Toaster = ({
  ...props
}) => {
  const { theme = "system" } = useTheme()

  return (
    (<Sonner
      theme={theme}
      className="toaster group"
      toastOptions={{
        classNames: {
          toast:
            "group toast group-[.toaster]:bg-background
group-[.toaster]:text-foreground group-[.toaster]:border-border
group-[.toaster]:shadow-lg",
          description: "group-[.toast]:text-muted-foreground",
          actionButton:
            "group-[.toast]:bg-primary
group-[.toast]:text-primary-foreground",
          cancelButton:
            "group-[.toast]:bg-muted
group-[.toast]:text-muted-foreground",
        },
      }}
      {...props} />)
  );
}

```

```

export { Toaster }

```

switch.jsx

```

import * as React from "react"
import * as SwitchPrimitives from "@radix-ui/react-switch"

import { cn } from "@lib/utils"

const Switch = React.forwardRef(({ className, ...props }, ref) =>
(
  <SwitchPrimitives.Root
    className={cn(

```

```

        "peer inline-flex h-5 w-9 shrink-0 cursor-pointer
items-center rounded-full border-2 border-transparent shadow-sm
transition-colors focus-visible:outline-none focus-visible:ring-2
focus-visible:ring-ring focus-visible:ring-offset-2
focus-visible:ring-offset-background disabled:cursor-not-allowed
disabled:opacity-50 data-[state=checked]:bg-primary
data-[state=unchecked]:bg-input",
        className
      )}
      {...props}
      ref={ref}>
      <SwitchPrimitives.Thumb
        className={cn(
          "pointer-events-none block h-4 w-4 rounded-full
bg-background shadow-lg ring-0 transition-transform
data-[state=checked]:translate-x-4 data-[state=unchecked]:translate-x-0"
        )} />
    </SwitchPrimitives.Root>
  ))
  Switch.displayName = SwitchPrimitives.Root.displayName

export { Switch }

```

table.jsx

```

import * as React from "react"

import { cn } from "@lib/utils"

const Table = React.forwardRef(({ className, ...props }, ref) => (
  <div className="relative w-full overflow-auto">
    <table
      ref={ref}
      className={cn("w-full caption-bottom text-sm", className)}
      {...props} />
    </div>
  ))
  Table.displayName = "Table"

  const TableHeader = React.forwardRef(({ className, ...props },
ref) => (
    <thead ref={ref} className={cn("&_tr:border-b", className)}
      {...props} />

```

```

    ))
    TableHeader.displayName = "TableHeader"

    const TableBody = React.forwardRef(({ className, ...props }, ref)
=> (
      <tbody
        ref={ref}
        className={cn("&_tr:last-child:border-0", className)}
        {...props} />
      )
    TableBody.displayName = "TableBody"

    const TableFooter = React.forwardRef(({ className, ...props },
ref) => (
      <tfoot
        ref={ref}
        className={cn("border-t bg-muted/50 font-medium
[&>tr]:last:border-b-0", className)}
        {...props} />
      )
    TableFooter.displayName = "TableFooter"

    const TableRow = React.forwardRef(({ className, ...props }, ref)
=> (
      <tr
        ref={ref}
        className={cn(
          "border-b transition-colors hover:bg-muted/50
data-[state=selected]:bg-muted",
          className
        )}
        {...props} />
      )
    TableRow.displayName = "TableRow"

    const TableHead = React.forwardRef(({ className, ...props }, ref)
=> (
      <th
        ref={ref}
        className={cn(

```

```

        "h-10 px-2 text-left align-middle font-medium
text-muted-foreground [&:has([role=checkbox])]:pr-0
[&>[role=checkbox]]:translate-y-[2px]",
        className
    )}
    {...props} />
))
TableHead.displayName = "TableHead"

const TableCell = React.forwardRef(({ className, ...props }, ref)
=> (
    <td
        ref={ref}
        className={cn(
            "p-2 align-middle [&:has([role=checkbox])]:pr-0
[&>[role=checkbox]]:translate-y-[2px]",
            className
        )}
        {...props} />
    )
    TableCell.displayName = "TableCell"

const TableCaption = React.forwardRef(({ className, ...props },
ref) => (
    <caption
        ref={ref}
        className={cn("mt-4 text-sm text-muted-foreground",
className)}
        {...props} />
    )
    TableCaption.displayName = "TableCaption"

export {
    Table,
    TableHeader,
    TableBody,
    TableFooter,
    TableHead,
    TableRow,
    TableCell,
    TableCaption,
}

```

tabs.jsx

```
import * as React from "react"
import * as TabsPrimitive from "@radix-ui/react-tabs"

import { cn } from "@lib/utils"

const Tabs = TabsPrimitive.Root

const TabsList = React.forwardRef(({ className, ...props }, ref)
=> (
  <TabsPrimitive.List
    ref={ref}
    className={cn(
      "inline-flex h-9 items-center justify-center rounded-lg
bg-muted p-1 text-muted-foreground",
      className
    )}
    {...props} />
))
TabsList.displayName = TabsPrimitive.List.displayName

const TabsTrigger = React.forwardRef(({ className, ...props },
ref) => (
  <TabsPrimitive.Trigger
    ref={ref}
    className={cn(
      "inline-flex items-center justify-center whitespace-nowrap
rounded-md px-3 py-1 text-sm font-medium ring-offset-background
transition-all focus-visible:outline-none focus-visible:ring-2
focus-visible:ring-ring focus-visible:ring-offset-2
disabled:pointer-events-none disabled:opacity-50
data-[state=active]:bg-background data-[state=active]:text-foreground
data-[state=active]:shadow",
      className
    )}
    {...props} />
))
TabsTrigger.displayName = TabsPrimitive.Trigger.displayName

const TabsContent = React.forwardRef(({ className, ...props },
ref) => (
```

```

    <TabsPrimitive.Content
      ref={ref}
      className={cn(
        "mt-2 ring-offset-background focus-visible:outline-none
focus-visible:ring-2 focus-visible:ring-ring
focus-visible:ring-offset-2",
        className
      )}
      {...props} />
  ))
  TabsContent.displayName = TabsPrimitive.Content.displayName

export { Tabs, TabsList, TabsTrigger, TabsContent }

```

textarea.jsx

```

import * as React from "react"

import { cn } from "@lib/utils"

const Textarea = React.forwardRef(({ className, ...props }, ref)
=> {
  return (
    <textarea
      className={cn(
        "flex min-h-[60px] w-full rounded-md border border-input
bg-transparent px-3 py-2 text-base shadow-sm
placeholder:text-muted-foreground focus-visible:outline-none
focus-visible:ring-1 focus-visible:ring-ring disabled:cursor-not-allowed
disabled:opacity-50 md:text-sm",
        className
      )}
      ref={ref}
      {...props} />
  );
})
Textarea.displayName = "Textarea"

export { Textarea }

```

toast.jsx

```

import * as React from "react";
import { cva } from "class-variance-authority";

```

```

import { X } from "lucide-react";
import { cn } from "@/lib/utils";

const ToastProvider = React.forwardRef(({ ...props }, ref) => (
  <div
    ref={ref}
    className="fixed top-0 z-[100] flex max-h-screen w-full
flex-col-reverse p-4 sm:bottom-0 sm:right-0 sm:top-auto sm:flex-col
md:max-w-[420px]"
    {...props}
  />
));
ToastProvider.displayName = "ToastProvider";

const ToastViewport = React.forwardRef(({ ...props }, ref) => (
  <div
    ref={ref}
    className="fixed top-0 z-[100] flex max-h-screen w-full
flex-col-reverse p-4 sm:bottom-0 sm:right-0 sm:top-auto sm:flex-col
md:max-w-[420px]"
    {...props}
  />
));
ToastViewport.displayName = "ToastViewport";

const toastVariants = cva(
  "group pointer-events-auto relative flex w-full items-center
justify-between space-x-4 overflow-hidden rounded-md border p-6 pr-8
shadow-lg transition-all data-[swipe=cancel]:translate-x-0
data-[swipe=end]:translate-x-[var(--radix-toast-swipe-end-x)]
data-[swipe=move]:translate-x-[var(--radix-toast-swipe-move-x)]
data-[swipe=move]:transition-none data-[state=open]:animate-in
data-[state=closed]:animate-out data-[swipe=end]:animate-out
data-[state=closed]:fade-out-80
data-[state=closed]:slide-out-to-right-full
data-[state=open]:slide-in-from-top-full
data-[state=open]:sm:slide-in-from-bottom-full",
  {
    variants: {
      variant: {
        default: "border bg-background text-foreground",
        destructive:

```

```

        "destructive group border-destructive bg-destructive
text-destructive-foreground",
      },
    },
    defaultVariants: {
      variant: "default",
    },
  }
);

const Toast = React.forwardRef(({ className, variant, ...props },
ref) => {
  return (
    <div
      ref={ref}
      className={cn(toastVariants({ variant }), className)}
      {...props}
    />
  );
});
Toast.displayName = "Toast";

const ToastAction = React.forwardRef(({ className, ...props },
ref) => {
  <div
    ref={ref}
    className={cn(
      "inline-flex h-8 shrink-0 items-center justify-center
rounded-md border bg-transparent px-3 text-sm font-medium
ring-offset-background transition-colors hover:bg-secondary
focus:outline-none focus:ring-2 focus:ring-ring focus:ring-offset-2
disabled:pointer-events-none disabled:opacity-50
group-[.destructive]:border-muted/40
group-[.destructive]:hover:border-destructive/30
group-[.destructive]:hover:bg-destructive
group-[.destructive]:hover:text-destructive-foreground
group-[.destructive]:focus:ring-destructive",
      className
    )}
    {...props}
  />
});

```



```

ToastAction.displayName = "ToastAction";

const ToastClose = React.forwardRef(({ className, ...props }, ref)
=> (
  <button
    ref={ref}
    className={cn(
      "absolute right-2 top-2 rounded-md p-1 text-foreground/50
opacity-0 transition-opacity hover:text-foreground focus:opacity-100
focus:outline-none focus:ring-2 group-hover:opacity-100
group-[.destructive]:text-red-300 group-[.destructive]:hover:text-red-50
group-[.destructive]:focus:ring-red-400
group-[.destructive]:focus:ring-offset-red-600",
      className
    )}
    toast-close=""
    {...props}
  >
    <X className="h-4 w-4" />
  </button>
));
ToastClose.displayName = "ToastClose";

const ToastTitle = React.forwardRef(({ className, ...props }, ref)
=> (
  <div
    ref={ref}
    className={cn("text-sm font-semibold", className)}
    {...props}
  />
));
ToastTitle.displayName = "ToastTitle";

const ToastDescription = React.forwardRef(({ className, ...props
}, ref) => (
  <div
    ref={ref}
    className={cn("text-sm opacity-90", className)}
    {...props}
  />
));
ToastDescription.displayName = "ToastDescription";

```

```

export {
  ToastProvider,
  ToastViewport,
  Toast,
  ToastTitle,
  ToastDescription,
  ToastClose,
  ToastAction,
};

toaster.jsx
import { useToast } from "@components/ui/use-toast";
import {
  Toast,
  ToastClose,
  ToastDescription,
  ToastProvider,
  ToastTitle,
  ToastViewport,
} from "@components/ui/toast";

export function Toaster() {
  const { toasts } = useToast();

  return (
    <ToastProvider>
      {toasts.map(function ({ id, title, description, action,
...props }) {
        return (
          <Toast key={id} {...props}>
            <div className="grid gap-1">
              {title && <ToastTitle>{title}</ToastTitle>}
              {description && (
                <ToastDescription>{description}</ToastDescription>
              )}
            </div>
            {action}
            <ToastClose />
          </Toast>
        );
      })}
    <ToastViewport />
  );
}

```

```

        </ToastProvider>
    );
}
toggle-group.jsx
"use client";
import * as React from "react"
import * as ToggleGroupPrimitive from
"@radix-ui/react-toggle-group"

import { cn } from "@lib/utils"
import { toggleVariants } from "@components/ui/toggle"

const ToggleGroupContext = React.createContext({
    size: "default",
    variant: "default",
})

const ToggleGroup = React.forwardRef(({ className, variant, size,
children, ...props }, ref) => (
    <ToggleGroupPrimitive.Root
        ref={ref}
        className={cn("flex items-center justify-center gap-1",
className)}
        {...props}>
        <ToggleGroupContext.Provider value={{ variant, size }}>
            {children}
        </ToggleGroupContext.Provider>
    </ToggleGroupPrimitive.Root>
))

ToggleGroup.displayName = ToggleGroupPrimitive.Root.displayName

const ToggleGroupItem = React.forwardRef(({ className, children,
variant, size, ...props }, ref) => {
    const context = React.useContext(ToggleGroupContext)

    return (
        <ToggleGroupPrimitive.Item
            ref={ref}
            className={cn(toggleVariants({
                variant: context.variant || variant,
                size: context.size || size,

```

```

    }}, className)}
    {...props}>
    {children}
  </ToggleGroupPrimitive.Item>
);
})

ToggleGroupItem.displayName =
ToggleGroupPrimitive.Item.displayName

export { ToggleGroup, ToggleGroupItem }

toggle.jsx
import * as React from "react"
import * as TogglePrimitive from "@radix-ui/react-toggle"
import { cva } from "class-variance-authority";

import { cn } from "@lib/utils"

const toggleVariants = cva(
  "inline-flex items-center justify-center gap-2 rounded-md
  text-sm font-medium transition-colors hover:bg-muted
  hover:text-muted-foreground focus-visible:outline-none
  focus-visible:ring-1 focus-visible:ring-ring
  disabled:pointer-events-none disabled:opacity-50
  data-[state=on]:bg-accent data-[state=on]:text-accent-foreground
  [&_svg]:pointer-events-none [&_svg]:size-4 [&_svg]:shrink-0",
  {
    variants: {
      variant: {
        default: "bg-transparent",
        outline:
          "border border-input bg-transparent shadow-sm
          hover:bg-accent hover:text-accent-foreground",
      },
      size: {
        default: "h-9 px-2 min-w-9",
        sm: "h-8 px-1.5 min-w-8",
        lg: "h-10 px-2.5 min-w-10",
      },
    },
    defaultVariants: {

```

```

        variant: "default",
        size: "default",
      },
    }
  )

  const Toggle = React.forwardRef(({ className, variant, size,
...props }, ref) => (
    <TogglePrimitive.Root
      ref={ref}
      className={cn(toggleVariants({ variant, size, className })))}
      {...props} />
  ))

  Toggle.displayName = TogglePrimitive.Root.displayName

  export { Toggle, toggleVariants }

```

tooltip.jsx

```

"use client"

import * as React from "react"
import * as TooltipPrimitive from "@radix-ui/react-tooltip"

import { cn } from "@lib/utils"

const TooltipProvider = TooltipPrimitive.Provider

const Tooltip = TooltipPrimitive.Root

const TooltipTrigger = TooltipPrimitive.Trigger

const TooltipContent = React.forwardRef(({ className, sideOffset =
4, ...props }, ref) => (
  <TooltipPrimitive.Portal>
    <TooltipPrimitive.Content
      ref={ref}
      sideOffset={sideOffset}
      className={cn(
        "z-50 overflow-hidden rounded-md bg-primary px-3 py-1.5
text-xs text-primary-foreground animate-in fade-in-0 zoom-in-95
data-[state=closed]:animate-out data-[state=closed]:fade-out-0

```

```

data-[state=closed]:zoom-out-95 data-[side=bottom]:slide-in-from-top-2
data-[side=left]:slide-in-from-right-2
data-[side=right]:slide-in-from-left-2
data-[side=top]:slide-in-from-bottom-2",
      className
    )}
    {...props} />
  </TooltipPrimitive.Portal>
))
TooltipContent.displayName = TooltipPrimitive.Content.displayName

export { Tooltip, TooltipTrigger, TooltipContent, TooltipProvider
}

```

use-toast.jsx

```

// Inspired by react-hot-toast library
import { useState, useEffect } from "react";

const TOAST_LIMIT = 20;
const TOAST_REMOVE_DELAY = 1000000;

const actionTypes = {
  ADD_TOAST: "ADD_TOAST",
  UPDATE_TOAST: "UPDATE_TOAST",
  DISMISS_TOAST: "DISMISS_TOAST",
  REMOVE_TOAST: "REMOVE_TOAST",
};

let count = 0;

function genId() {
  count = (count + 1) % Number.MAX_VALUE;
  return count.toString();
}

const toastTimeouts = new Map();

const addToRemoveQueue = (toastId) => {
  if (toastTimeouts.has(toastId)) {
    return;
  }
}

```

```

const timeout = setTimeout(() => {
  toastTimeouts.delete(toastId);
  dispatch({
    type: actionTypes.REMOVE_TOAST,
    toastId,
  });
}, TOAST_REMOVE_DELAY);

toastTimeouts.set(toastId, timeout);
};

const _clearFromRemoveQueue = (toastId) => {
  const timeout = toastTimeouts.get(toastId);
  if (timeout) {
    clearTimeout(timeout);
    toastTimeouts.delete(toastId);
  }
};

export const reducer = (state, action) => {
  switch (action.type) {
    case actionTypes.ADD_TOAST:
      return {
        ...state,
        toasts: [action.toast, ...state.toasts].slice(0,
TOAST_LIMIT),
      };

    case actionTypes.UPDATE_TOAST:
      return {
        ...state,
        toasts: state.toasts.map((t) =>
          t.id === action.toast.id ? { ...t, ...action.toast } : t
        ),
      };

    case actionTypes.DISMISS_TOAST: {
      const { toastId } = action;

      // ! Side effects ! - This could be extracted into a
dismissToast() action,
      // but I'll keep it here for simplicity

```

```

    if (toastId) {
      addToRemoveQueue(toastId);
    } else {
      state.toasts.forEach((toast) => {
        addToRemoveQueue(toast.id);
      });
    }

    return {
      ...state,
      toasts: state.toasts.map((t) =>
        t.id === toastId || toastId === undefined
          ? {
              ...t,
              open: false,
            }
          : t
        ),
    };
  }
  case actionTypes.REMOVE_TOAST:
    if (action.toastId === undefined) {
      return {
        ...state,
        toasts: [],
      };
    }
    return {
      ...state,
      toasts: state.toasts.filter((t) => t.id !==
action.toastId),
    };
  }
};

const listeners = [];

let memoryState = { toasts: [] };

function dispatch(action) {
  memoryState = reducer(memoryState, action);
  listeners.forEach((listener) => {

```



```

        listener(memoryState);
    });
}

function toast({ ...props }) {
    const id = genId();

    const update = (props) =>
        dispatch({
            type: actionTypes.UPDATE_TOAST,
            toast: { ...props, id },
        });

    const dismiss = () =>
        dispatch({ type: actionTypes.DISMISS_TOAST, toastId: id });

    dispatch({
        type: actionTypes.ADD_TOAST,
        toast: {
            ...props,
            id,
            open: true,
            onOpenChange: (open) => {
                if (!open) dismiss();
            },
        },
    });
}

return {
    id,
    dismiss,
    update,
};
}

function useToast() {
    const [state, setState] = useState(memoryState);

    useEffect(() => {
        listeners.push(setState);
        return () => {
            const index = listeners.indexOf(setState);

```

```

        if (index > -1) {
            listeners.splice(index, 1);
        }
    };
}, [state]));

return {
    ...state,
    toast,
    dismiss: (toastId) => dispatch({ type:
actionTypes.DISMISS_TOAST, toastId }),
    };
}

export { useToast, toast };

```

AuthLayout.jsx

```

import React from "react";

export default function AuthLayout({ icon: Icon, title, subtitle,
footer, children }) {
    return (
        <div className="min-h-screen flex items-center justify-center
bg-background px-4">
            <div className="w-full max-w-md">
                <div className="text-center mb-10">
                    <div className="inline-flex items-center justify-center w-14
h-14 rounded-2xl bg-primary mb-4">
                        <Icon className="w-7 h-7 text-primary-foreground"
aria-hidden="true" />
                    </div>
                    <h1 className="text-3xl font-bold tracking-tight
text-foreground">{title}</h1>
                    {subtitle && <p className="text-muted-foreground
mt-2">{subtitle}</p>}
                </div>
                <div className="bg-card rounded-2xl shadow-sm border
border-border p-8">
                    {children}
                </div>
                {footer && (

```

```

        <p className="text-center text-sm text-muted-foreground
mt-6">{footer}</p>
      )}
    </div>
  </div>
);
}

```

GoogleIcon.jsx

```

import React from "react";

export default function GoogleIcon({ className = "w-5 h-5" }) {
  return (
    <svg className={className} viewBox="0 0 24 24" aria-hidden="true">
      <path d="M22.56 12.25c0-.78-.07-1.53-.2-2.25H12v4.26h5.92a5.06
5.06 0 01-2.2 3.32v2.77h3.57c2.08-1.92 3.28-4.74 3.28-8.1z"
fill="#4285F4" />
      <path d="M12 23c2.97 0 5.46-.98 7.28-2.66l-3.57-2.77c-.98-.66-2.23
1.06-3.71 1.06-2.86 0-5.29-1.93-6.16-4.53H2.18v2.84C3.99 20.53 7.7 23 12
23z" fill="#34A853" />
      <path d="M5.84
14.09c-.22-.66-.35-1.36-.35-2.09s.13-1.43.35-2.09V7.07H2.18C1.43 8.55 1
10.22 1 12s.43 3.45 1.18 4.93l2.85-2.22.81-.62z" fill="#FBBC05" />
      <path d="M12 5.38c1.62 0 3.06.56 4.21 1.64l3.15-3.15C17.45 2.09
14.97 1 12 1 7.7 1 3.99 3.47 2.18 7.07l3.66 2.84c.87-2.6 3.3-4.53
6.16-4.53z" fill="#EA4335" />
    </svg>
  );
}

```

ProtectedRoute.jsx

```

import { useEffect } from 'react';
import { Outlet } from 'react-router-dom';
import { useAuth } from '@lib/AuthContext';
import UserNotRegisteredError from
'@/components/UserNotRegisteredError';

const DefaultFallback = () => (
  <div className="fixed inset-0 flex items-center justify-center">
    <div className="w-8 h-8 border-4 border-slate-200 border-t-slate-800
rounded-full animate-spin"></div>
  </div>
)

```

```

);

export default function ProtectedRoute({ fallback = <DefaultFallback />,
unauthenticatedElement }) {
  const { isAuthenticated, isLoadingAuth, authChecked, authError,
checkUserAuth } = useAuth();

  useEffect(() => {
    if (!authChecked && !isLoadingAuth) {
      checkUserAuth();
    }
  }, [authChecked, isLoadingAuth, checkUserAuth]);

  if (isLoadingAuth || !authChecked) {
    return fallback;
  }

  if (authError) {
    if (authError.type === 'user_not_registered') {
      return <UserNotRegisteredError />;
    }
    return unauthenticatedElement;
  }

  if (!isAuthenticated) {
    return unauthenticatedElement;
  }

  return <Outlet />;
}

```

ScrollToTop.jsx

```

import { useEffect } from "react";
import { useLocation, useNavigationType } from "react-router-dom";

const getHashId = (hash) => {
  const rawId = hash.slice(1);

  try {
    return decodeURIComponent(rawId);
  } catch {
    return rawId;
  }
}

```

```

    }
  };

export default function ScrollToTop() {
  const { pathname, hash } = useLocation();
  const navigationType = useNavigationType();

  useEffect(() => {
    if (navigationType === "POP") return;

    if (hash) {
      const id = getHashId(hash);
      const timer = window.setTimeout(() => {
        document.getElementById(id)?.scrollIntoView({ behavior: "smooth"
});
      }, 50);
      return () => window.clearTimeout(timer);
    }

    window.scrollTo({ top: 0, left: 0, behavior: "instant" });
    }, [pathname, hash, navigationType]);

    return null;
  }
}

```

UserNotRegisteredError.jsx

```

import React from 'react';

const UserNotRegisteredError = () => {
  return (
    <div className="flex flex-col items-center justify-center
min-h-screen bg-gradient-to-b from-white to-slate-50">
      <div className="max-w-md w-full p-8 bg-white rounded-lg shadow-lg
border border-slate-100">
        <div className="text-center">
          <div className="inline-flex items-center justify-center w-16
h-16 mb-6 rounded-full bg-orange-100">
            <svg className="w-8 h-8 text-orange-600" fill="none"
stroke="currentColor" viewBox="0 0 24 24">
              <path strokeLinecap="round" strokeLinejoin="round"
strokeWidth="2" d="M12 9v2m0 4h.01m-6.938 4h13.856c1.54 0 2.502-1.667

```

```

1.732-3L13.732 4c-.77-1.333-2.694-1.333-3.464 0L3.34 16c-.77 1.333.192 3
1.732 3z" />
    </svg>
  </div>
  <h1 className="text-3xl font-bold text-slate-900 mb-4">Access
Restricted</h1>
  <p className="text-slate-600 mb-8">
    You are not registered to use this application. Please
contact the app administrator to request access.
  </p>
  <div className="p-4 bg-slate-50 rounded-md text-sm
text-slate-600">
    <p>If you believe this is an error, you can:</p>
    <ul className="list-disc list-inside mt-2 space-y-1">
      <li>Verify you are logged in with the correct account</li>
      <li>Contact the app administrator for access</li>
      <li>Try logging out and back in again</li>
    </ul>
  </div>
</div>
</div>
</div>
);
};

export default UserNotRegisteredError;

```

hooks

Use-mobile.jsx

```

import * as React from "react"

const MOBILE_BREAKPOINT = 768

export function useIsMobile() {
  const [isMobile, setIsMobile] = React.useState(undefined)

  React.useEffect(() => {
    const mql = window.matchMedia(`(max-width: ${MOBILE_BREAKPOINT - 1}px)`)
    const onChange = () => {
      setIsMobile(window.innerWidth < MOBILE_BREAKPOINT)
    }
    mql.addEventListener("change", onChange)

```

```

    setIsMobile(window.innerWidth < MOBILE_BREAKPOINT)
    return () => mql.removeEventListener("change", onChange);
  }, [])

  return !!isMobile
}

```

useCitySync.jsx

```

import { useState, useEffect } from "react";
import { syncCloudCities } from "@lib/customCities";

// Syncs cloud cities into localStorage on mount and re-renders when cities
change.
// Call this in any component that reads city data so it stays current with
the cloud.
export function useCitySync() {
  const [, setTick] = useState(0);

  useEffect(() => {
    const refresh = () => setTick(t => t + 1);
    syncCloudCities().then(refresh);
    window.addEventListener("cities-updated", refresh);
    return () => window.removeEventListener("cities-updated", refresh);
  }, []);
}

```

Lib

app-params.js

```

const isNode = typeof window === 'undefined';
const windowObj = isNode ? { localStorage: new Map() } : window;
const storage = windowObj.localStorage;

const toSnakeCase = (str) => {
  return str.replace(/([A-Z])/g, '_$1').toLowerCase();
}

const getAppParamValue = (paramName, { defaultValue = undefined, removeFromUrl
= false } = {}) => {
  if (isNode) {
    return defaultValue;
  }
}

```

```

const storageKey = `base44_${toSnakeCase(paramName)}`;
const urlParams = new URLSearchParams(window.location.search);
const searchParam = urlParams.get(paramName);
if (removeFromUrl) {
  urlParams.delete(paramName);
  const newUrl = `${window.location.pathname}${urlParams.toString() ?
`?${urlParams.toString()}` : ""
  }${window.location.hash}`;
  window.history.replaceState({}, document.title, newUrl);
}
if (searchParam) {
  storage.setItem(storageKey, searchParam);
  return searchParam;
}
if (defaultValue) {
  storage.setItem(storageKey, defaultValue);
  return defaultValue;
}
const storedValue = storage.getItem(storageKey);
if (storedValue) {
  return storedValue;
}
return null;
}

const getAppParams = () => {
  if (getAppParamValue("clear_access_token") === 'true') {
    storage.removeItem('base44_access_token');
    storage.removeItem('token');
  }
  return {
    appId: getAppParamValue("app_id", { defaultValue:
import.meta.env.VITE_BASE44_APP_ID }),
    token: getAppParamValue("access_token", { removeFromUrl: true }),
    fromUrl: getAppParamValue("from_url", { defaultValue: window.location.href
}),
    functionsVersion: getAppParamValue("functions_version", { defaultValue:
import.meta.env.VITE_BASE44_FUNCTIONS_VERSION }),
    appBaseUrl: getAppParamValue("app_base_url", { defaultValue:
import.meta.env.VITE_BASE44_APP_BASE_URL }),
  }
}

```



```
export const appParams = {
  ...getAppParams()
}
```

AuthContext.jsx

```
import React, { createContext, useState, useContext,
useEffect } from 'react';
import { base44 } from '@api/base44Client';
import { appParams } from '@lib/app-params';
import { createAxiosClient } from '@base44/sdk/dist/utils/axios-client';

const AuthContext = createContext();

export const AuthProvider = ({ children }) => {
  const [user, setUser] = useState(null);
  const [isAuthenticated, setIsAuthenticated] = useState(false);
  const [isLoadingAuth, setIsLoadingAuth] = useState(true);
  const [isLoadingPublicSettings, setIsLoadingPublicSettings] =
useState(true);
  const [authError, setAuthError] = useState(null);
  const [authChecked, setAuthChecked] = useState(false);
  const [appPublicSettings, setAppPublicSettings] = useState(null); //
Contains only { id, public_settings }

  useEffect(() => {
    checkAppState();
  }, []);

  const checkAppState = async () => {
    try {
      setIsLoadingPublicSettings(true);
      setAuthError(null);

      // First, check app public settings (with token if available)
      // This will tell us if auth is required, user not registered, etc.
      const appClient = createAxiosClient({
        baseUrl: `/api/apps/public`,
        headers: {
          'X-App-Id': appParams.appId
        },
      },
```

```

    token: appParams.token, // Include token if available
    interceptResponses: true
  });

  try {
    const publicSettings = await
appClient.get(`/prod/public-settings/by-id/${appParams.appId}`);
    setAppPublicSettings(publicSettings);

    // If we got the app public settings successfully, check if user is
authenticated
    if (appParams.token) {
      await checkUserAuth();
    } else {
      setIsLoadingAuth(false);
      setIsAuthenticated(false);
      setAuthChecked(true);
    }
    setIsLoadingPublicSettings(false);
  } catch (appError) {
    console.error('App state check failed:', appError);

    // Handle app-level errors
    if (appError.status === 403 && appError.data?.extra_data?.reason) {
      const reason = appError.data.extra_data.reason;
      if (reason === 'auth_required') {
        setAuthError({
          type: 'auth_required',
          message: 'Authentication required'
        });
      } else if (reason === 'user_not_registered') {
        setAuthError({
          type: 'user_not_registered',
          message: 'User not registered for this app'
        });
      } else {
        setAuthError({
          type: reason,
          message: appError.message
        });
      }
    } else {

```

```

        setAuthError({
          type: 'unknown',
          message: appError.message || 'Failed to load app'
        });
      }
      setIsLoadingPublicSettings(false);
      setIsLoadingAuth(false);
    }
  } catch (error) {
    console.error('Unexpected error:', error);
    setAuthError({
      type: 'unknown',
      message: error.message || 'An unexpected error occurred'
    });
    setIsLoadingPublicSettings(false);
    setIsLoadingAuth(false);
  }
};

const checkUserAuth = async () => {
  try {
    // Now check if the user is authenticated
    setIsLoadingAuth(true);
    const currentUser = await base44.auth.me();
    setUser(currentUser);
    setIsAuthenticated(true);
    setIsLoadingAuth(false);
    setAuthChecked(true);
  } catch (error) {
    console.error('User auth check failed:', error);
    setIsLoadingAuth(false);
    setIsAuthenticated(false);
    setAuthChecked(true);

    // If user auth fails, it might be an expired token
    if (error.status === 401 || error.status === 403) {
      setAuthError({
        type: 'auth_required',
        message: 'Authentication required'
      });
    }
  }
}

```

```

};

const logout = (shouldRedirect = true) => {
  setUser(null);
  setIsAuthenticated(false);

  if (shouldRedirect) {
    // Use the SDK's logout method which handles token cleanup and redirect
    base44.auth.logout(window.location.href);
  } else {
    // Just remove the token without redirect
    base44.auth.logout();
  }
};

const navigateToLogin = () => {
  // Use the SDK's redirectToLogin method
  base44.auth.redirectToLogin(window.location.href);
};

return (
  <AuthContext.Provider value={{
    user,
    isAuthenticated,
    isLoadingAuth,
    isLoadingPublicSettings,
    authError,
    appPublicSettings,
    authChecked,
    logout,
    navigateToLogin,
    checkUserAuth,
    checkAppState
  }}>
    {children}
  </AuthContext.Provider>
);
};

export const useAuth = () => {
  const context = useContext(AuthContext);
  if (!context) {

```

```

        throw new Error('useAuth must be used within an AuthProvider');
    }
    return context;
};

```

authReturnTo.js

```

    // Shared by the auth pages (Login, Register, and any page
    that resumes a flow
    // after sign-in, e.g. the MCP OAuth consent page). Keep the redirect
    // validation in one place – it is security-sensitive and easy to drift.

    // Resolve ?returnTo= to a safe same-origin path, else "/".
    //
    // The same-origin check alone is not enough: a value like ../evil.com or
    // /\evil.com parses same-origin but normalizes to a protocol-relative
    // //evil.com when assigned to location.href – an open redirect. So require
    the
    // resolved path to be exactly one leading slash (no "/" prefix, no
    backslash).
    export function safeReturnTo() {
        const raw = new URLSearchParams(window.location.search).get("returnTo");
        if (!raw) return "/";
        try {
            const url = new URL(raw, window.location.origin);
            if (url.origin !== window.location.origin) return "/";
            // Strip app-bootstrap params: app-params.js persists these from the URL
            into
            // localStorage before the SDK initializes, so a crafted returnTo could
            // otherwise poison the freshly issued session – repointing the app at an
            // attacker's backend (app_base_url/app_id/functions_version) or
            overwriting
            // the token. Normal app-flow params (e.g. the OAuth consent ctx) are
            kept.
            // The full app-params.js bootstrap set (src/lib/app-params.js) – any of
            // these in a crafted returnTo would be persisted at next load.
            for (const p of ["access_token", "clear_access_token", "app_id",
            "app_base_url", "functions_version", "from_url"]) {
                url.searchParams.delete(p);
            }
            const path = url.pathname + url.search;
            if (!path.startsWith("/") || path.startsWith("//") || path.includes("\\"))
            return "/";

```

```

    return path;
  } catch {
    return "/";
  }
}

```

cityDatabase.js

```

import { getCustomCities } from "../customCities";

// Unified city database - single source of truth
// Specs: detailed format (from PavementsAnalysis)
// Costs: initial + maintenance (from PavementCalculator); 30yr totals
auto-computed
export const baseCityData = [
  {
    city: "APWA Standard", state: "Standard",
    residential: {
      access: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" Solid Slab'
    },
    local: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" Solid Slab' },
    collector: { asphalt: '9" (7" Base + 2" Surf)', concrete: '7" Solid
Slab' }
    },
    collector: {
      residential: { asphalt: '9" (7" Base + 2" Surf)', concrete: '7" Solid
Slab' },
      commercial: { asphalt: '9" (7" Base + 2" Surf)', concrete: '7" Solid
Slab' },
      industrial: { asphalt: '11" (9" Base + 2" Surf)', concrete: '8" Solid
Slab' }
    },
    arterial: {
      minor: { asphalt: '11" (9" Base + 2" Surf)', concrete: '8" Solid Slab'
    },
      major: { asphalt: '12" (10" Base + 2" Surf)', concrete: '9" Solid Slab'
    }
    },
    initialCosts: { res_a: 657888, res_c: 1478400, col_a: 1045440, col_c:
2280960, art_a: 1951488, art_c: 4435200 },
    maint30: { res_a: 1584000, res_c: 369600, col_a: 2037000, col_c: 475200,
art_a: 3168000, art_c: 739100 }
  },

```

```

{
  city: "Overland Park", state: "KS",
  residential: {
    access: { asphalt: '8" (6" Base + 2" Surf)', concrete: '7" Slab + 4"
Rock Base' },
    local: { asphalt: '8" (6" Base + 2" Surf)', concrete: '7" Slab + 4" Rock
Base' },
    collector: { asphalt: '9" (7" Base + 2" Surf)', concrete: '8" Slab + 4"
Rock Base' }
  },
  collector: {
    residential: { asphalt: '9" (7" Base + 2" Surf)', concrete: '8" Slab +
4" Rock Base' },
    commercial: { asphalt: '10" (8" Base + 2" Surf)', concrete: '8" Slab +
4" Rock Base' },
    industrial: { asphalt: '10" (8" Base + 2" Surf)', concrete: '8" Slab +
4" Rock Base' }
  },
  arterial: {
    minor: { asphalt: '-', concrete: '-' },
    major: { asphalt: '-', concrete: '-' }
  },
  initialCosts: { res_a: 657888, res_c: 1848000, col_a: 950400, col_c:
2661120, art_a: 1951488, art_c: 4878720 },
  maint30: { res_a: 1584000, res_c: 369600, col_a: 2037000, col_c: 475200,
art_a: 3168000, art_c: 739100 }
},
{
  city: "Lenexa", state: "KS",
  residential: {
    access: { asphalt: '8" (4" Base + 2" Int + 2" Surf)', concrete: '6"
Solid Slab' },
    local: { asphalt: '8" (4" Base + 2" Int + 2" Surf)', concrete: '6" Solid
Slab' },
    collector: { asphalt: '9" (7" Base + 2" Surf)', concrete: '8" Solid
Slab' }
  },
  collector: {
    residential: { asphalt: '9" (7" Base + 2" Surf)', concrete: '8" Solid
Slab' },
    commercial: { asphalt: '9" (7" Base + 2" Surf)', concrete: '8" Solid
Slab' },

```

```

        industrial: { asphalt: '11" (9" Base + 2" Surf)', concrete: '10" Solid
Slab' }
    },
    arterial: {
        minor: { asphalt: '11" (9" Base + 2" Surf)', concrete: '10" Solid Slab'
},
        major: { asphalt: '12" (10" Base + 2" Surf)', concrete: '10" Solid Slab'
}
    },
    initialCosts: { res_a: 657888, res_c: 1478400, col_a: 950400, col_c:
2566080, art_a: 1951488, art_c: null },
    maint30: { res_a: 1584000, res_c: 369600, col_a: 2037000, col_c: 475200,
art_a: 3168000, art_c: null }
    },
    {
        city: "Shawnee", state: "KS",
        residential: {
            access: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" Solid Slab'
},
            local: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" Solid Slab' },
            collector: { asphalt: '9" (7" Base + 2" Surf)', concrete: '8" Solid
Slab' }
        },
        collector: {
            residential: { asphalt: '9" (7" Base + 2" Surf)', concrete: '8" Solid
Slab' },
            commercial: { asphalt: '10" (8" Base + 2" Surf)', concrete: '8" Solid
Slab' },
            industrial: { asphalt: '10" (8" Base + 2" Surf)', concrete: '8" Solid
Slab' }
        },
        arterial: {
            minor: { asphalt: '12" (10" Base + 2" Surf)', concrete: '10" Solid Slab'
},
            major: { asphalt: 'State Criteria', concrete: 'State Criteria' }
        },
        initialCosts: { res_a: 657888, res_c: 1478400, col_a: 1045440, col_c:
2566080, art_a: 1951488, art_c: 4656960 },
        maint30: { res_a: 1584000, res_c: 369600, col_a: 2037000, col_c: 475200,
art_a: 3168000, art_c: 739100 }
    },
    {

```



```

    city: "Olathe", state: "KS",
    residential: {
      access: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" Slab + 9"
Subgrade' },
      local: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" Slab + 9"
Subgrade' },
      collector: { asphalt: '10" (8" Base + 2" Surf)', concrete: '7" Slab + 9"
Subgrade' }
    },
    collector: {
      residential: { asphalt: '10" (8" Base + 2" Surf)', concrete: '7" Slab +
9" Subgrade' },
      commercial: { asphalt: '10" (8" Base + 2" Surf)', concrete: '7" Slab +
9" Subgrade' },
      industrial: { asphalt: '10" (8" Base + 2" Surf)', concrete: '7" Slab +
9" Subgrade' }
    },
    arterial: {
      minor: { asphalt: '12" (10" Base + 2" Surf)', concrete: '9" Slab + 6"
Rock Base' },
      major: { asphalt: '12" (10" Base + 2" Surf)', concrete: '9" Slab + 6"
Rock Base' }
    },
    initialCosts: { res_a: 657888, res_c: 1478400, col_a: 1045440, col_c:
2280960, art_a: 1951488, art_c: 4435200 },
    maint30: { res_a: 1584000, res_c: 369600, col_a: 2037000, col_c: 475200,
art_a: 3168000, art_c: 739100 }
  },
  {
    city: "Gardner", state: "KS",
    residential: {
      access: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" Slab + 9"
Subgrade' },
      local: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" + 9" Subgrade'
},
      collector: { asphalt: '10" (8" Base + 2" Surf)', concrete: '7" Slab + 9"
Subgrade' }
    },
    collector: {
      residential: { asphalt: '10" (8" Base + 2" Surf)', concrete: '7" Slab +
9" Subgrade' },

```

```

    commercial: { asphalt: '10" (8" Base + 2" Surf)', concrete: '7" Slab +
9" Subgrade' },
    industrial: { asphalt: '10" (8" Base + 2" Surf)', concrete: '7" Slab +
9" Subgrade' }
  },
  arterial: {
    minor: { asphalt: '12" (10" Base + 2" Surf)', concrete: '9" Slab + 9"
Subgrade' },
    major: { asphalt: '12" (10" Base + 2" Surf)', concrete: '9" Slab + 9"
Subgrade' }
  },
  initialCosts: { res_a: 657888, res_c: 1478400, col_a: 950400, col_c:
2280960, art_a: 1951488, art_c: 4435200 },
  maint30: { res_a: 1584000, res_c: 369600, col_a: 2037000, col_c: 475200,
art_a: 3168000, art_c: 739100 }
},
{
  city: "Grandview", state: "MO",
  residential: {
    access: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" Solid Slab'
},
    local: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" Solid Slab' },
    collector: { asphalt: '9" (7" Base + 2" Surf)', concrete: '7" Solid
Slab' }
  },
  collector: {
    residential: { asphalt: '9" (7" Base + 2" Surf)', concrete: '7" Solid
Slab' },
    commercial: { asphalt: '9" (7" Base + 2" Surf)', concrete: '7" Solid
Slab' },
    industrial: { asphalt: '9" (7" Base + 2" Surf)', concrete: '7" Solid
Slab' }
  },
  arterial: {
    minor: { asphalt: '11" (9" Base + 2" Surf)', concrete: '8" Solid Slab'
},
    major: { asphalt: '12" (10" Base + 2" Surf)', concrete: '9" Solid Slab'
}
  },
  initialCosts: { res_a: 657888, res_c: 1478400, col_a: 845856, col_c:
2280960, art_a: 1951488, art_c: 4435200 },

```

```

    maint30: { res_a: 1584000, res_c: 369600, col_a: 2037000, col_c: 475200,
art_a: 3168000, art_c: 739100 }
  },
  {
    city: "Blue Springs", state: "MO",
    residential: {
      access: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" Solid Slab'
},
      local: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" Solid Slab' },
      collector: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" Solid
Slab' }
    },
    collector: {
      residential: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" Solid
Slab' },
      commercial: { asphalt: '11" (9" Base + 2" Surf)', concrete: '7" Solid
Slab' },
      industrial: { asphalt: '11" (9" Base + 2" Surf)', concrete: '7" Solid
Slab' }
    },
    arterial: {
      minor: { asphalt: '11" (9" Base + 2" Surf)', concrete: '8" Solid Slab'
},
      major: { asphalt: '12" (10" Base + 2" Surf)', concrete: '9" Solid Slab'
}
    },
    initialCosts: { res_a: 657888, res_c: 1478400, col_a: null, col_c:
1900800, art_a: null, art_c: null },
    maint30: { res_a: 1584000, res_c: 369600, col_a: null, col_c: 475200,
art_a: null, art_c: null }
  },
  {
    city: "Lee's Summit", state: "MO",
    residential: {
      access: { asphalt: '6" (4" Base + 2" Surf) + 8" Rock Base', concrete:
'6" Solid Slab + 6" Rock Base' },
      local: { asphalt: '6" (4" Base + 2" Surf) + 8" Rock Base', concrete: '6"
Solid Slab + 6" Rock Base' },
      collector: { asphalt: '8" (6" Base + 2" Surf) + 8" Rock Base', concrete:
'6.5" Solid Slab + 6" Rock Base' }
    },
    collector: {

```

```

    residential: { asphalt: '8" (6" Base + 2" Surf) + 8" Rock Base',
concrete: '6.5" Solid Slab + 6" Rock Base' },
    commercial: { asphalt: '11" (9" Base + 2" Surf) + 8" Rock Base',
concrete: '8" Solid Slab + 6" Rock Base' },
    industrial: { asphalt: '11" (9" Base + 2" Surf) + 8" Rock Base',
concrete: '8" Solid Slab + 6" Rock Base' }
  },
  arterial: {
    minor: { asphalt: 'Project Specific', concrete: 'Project Specific' },
    major: { asphalt: 'Project Specific', concrete: 'Project Specific' }
  },
  initialCosts: { res_a: 665280, res_c: 1589280, col_a: 1035936, col_c:
2233440, art_a: 2173248, art_c: 4656960 },
  maint30: { res_a: 1584000, res_c: 369600, col_a: 2037000, col_c: 475200,
art_a: 3168000, art_c: 739000 }
},
{
  city: "Kansas City", state: "MO",
  residential: {
    access: { asphalt: 'N/A', concrete: 'N/A' },
    local: { asphalt: '8" (6" Base + 2" Surf) + 6" Rock Base', concrete: '6"
Solid Slab + 6" Rock Base' },
    collector: { asphalt: '9" (7" Base + 2" Surf) + 6" Rock Base', concrete:
'7" Solid Slab + 6" Rock Base' }
  },
  collector: {
    residential: { asphalt: '9" (7" Base + 2" Surf) + 6" Rock Base',
concrete: '7" Solid Slab + 6" Rock Base' },
    commercial: { asphalt: '9" (7" Base + 2" Surf) + 6" Rock Base',
concrete: '7" Solid Slab + 6" Rock Base' },
    industrial: { asphalt: '9" (7" Base + 2" Surf) + 6" Rock Base',
concrete: '7" Solid Slab + 6" Rock Base' }
  },
  arterial: {
    minor: { asphalt: '11" (9" Base + 2" Surf) + 6" Rock Base', concrete:
'8" Solid Slab + 6" Rock Base' },
    major: { asphalt: '12" (10" Base + 2" Surf) + 6" Rock Base', concrete:
'9" Solid Slab + 6" Rock Base' }
  },
  initialCosts: { res_a: 768768, res_c: 1589280, col_a: 1092960, col_c:
2423520, art_a: 1951488, art_c: 4435200 },

```

```

    maint30: { res_a: 1584000, res_c: 369600, col_a: 2037000, col_c: 475200,
art_a: 3168000, art_c: 739000 }
  },
  {
    city: "Independence", state: "MO",
    residential: {
      access: { asphalt: 'N/A', concrete: 'N/A' },
      local: { asphalt: '8" (6" Base + 2" Surf)', concrete: '6" Solid Slab' },
      collector: { asphalt: '9" (7" Base + 2" Surf)', concrete: '7" Solid
Slab' }
    },
    collector: {
      residential: { asphalt: '9" (7" Base + 2" Surf)', concrete: '7" Solid
Slab' },
      commercial: { asphalt: '9" (7" Base + 2" Surf)', concrete: '7" Solid
Slab' },
      industrial: { asphalt: '9" (7" Base + 2" Surf)', concrete: '7" Solid
Slab' }
    },
    arterial: {
      minor: { asphalt: '11" (9" Base + 2" Surf)', concrete: '8" Solid Slab'
},
      major: { asphalt: '12" (10" Base + 2" Surf)', concrete: '9" Solid Slab'
}
    },
    initialCosts: { res_a: 657888, res_c: 1478400, col_a: 950400, col_c:
2280960, art_a: 1951488, art_c: 4435200 },
    maint30: { res_a: 1584000, res_c: 369600, col_a: 2037000, col_c: 475200,
art_a: 3168000, art_c: 739000 }
  },
  {
    city: "Merriam", state: "KS",
    residential: {
      access: { asphalt: '7" (4" Base + 2" Int + 1" Surf)', concrete: '6" PCC
Min' },
      local: { asphalt: '7" (4" Base + 2" Int + 1" Surf)', concrete: '6" PCC
Min' },
      collector: { asphalt: '8" (6" Base + 2" Surf)', concrete: '7" PCC' }
    },
    collector: {
      residential: { asphalt: '8" (6" Base + 2" Surf)', concrete: '7" PCC' },
      commercial: { asphalt: '8" (6" Base + 2" Surf)', concrete: '8" PCC' },

```

```

        industrial: { asphalt: '8" (6" Base + 2" Surf)', concrete: '8" PCC' }
    },
    arterial: {
        minor: { asphalt: '11" (9" Base + 2" Surf)', concrete: '8" PCC' },
        major: { asphalt: '12" (10" Base + 2" Surf)', concrete: '9" PCC' }
    },
    initialCosts: { res_a: 657888, res_c: 1478400, col_a: 1045440, col_c:
2280960, art_a: 1951488, art_c: 4435200 },
    maint30: { res_a: 1584000, res_c: 369600, col_a: 2037000, col_c: 475200,
art_a: 3168000, art_c: 739100 }
    }
};

function computeCosts(city) {
    const costs = {};
    Object.keys(city.initialCosts || {}).forEach(key => {
        const init = city.initialCosts?.[key];
        const maint = city.maint30?.[key];
        if (init == null && maint == null) {
            costs[key] = null;
        } else {
            costs[key] = (init || 0) + (maint || 0);
        }
    });
    return costs;
}

// Merge base + custom cities; custom overrides base by name
export function getMergedCities() {
    const custom = getCustomCities();
    const customMap = new Map(custom.map(c => [c.city, c]));

    const merged = baseCityData.map(c => {
        const override = customMap.get(c.city);
        if (override) {
            return { ...override, costs: override.costs || computeCosts(override) };
        }
        return { ...c, costs: computeCosts(c) };
    });

    custom.forEach(c => {
        if (!baseCityData.some(b => b.city === c.city)) {

```

```

        merged.push({ ...c, costs: c.costs || computeCosts(c) });
    }
});

return merged;
}

// For PavementsAnalysis - costs = 30yr totals
export function getAnalysisCities() {
    return getMergedCities().map(c => ({
        city: c.city,
        state: c.state,
        residential: c.residential,
        collector: c.collector,
        arterial: c.arterial,
        costs: c.costs
    }));
}

// For PavementCalculator - costs = initial, maint30 = maintenance
export function getCalculatorCities() {
    return getMergedCities().map(c => ({
        city: c.city,
        state: c.state,
        residential: c.residential,
        collector: c.collector,
        arterial: c.arterial,
        costs: c.initialCosts,
        maint30: c.maint30
    }));
}

export function isCustomCity(cityName) {
    return getCustomCities().some(c => c.city === cityName);
}

export function isBaseCity(cityName) {
    return baseCityData.some(c => c.city === cityName);
}

customCities.js
import { base44 } from "@api/base44Client";

```

```

const STORAGE_KEY = "kcp_custom_cities";

export function getCustomCities() {
  try {
    const saved = localStorage.getItem(STORAGE_KEY);
    return saved ? JSON.parse(saved) : [];
  } catch { return []; }
}

function saveLocal(cities) {
  localStorage.setItem(STORAGE_KEY, JSON.stringify(cities));
}

// Add or update a city - saves to localStorage immediately, then syncs to
cloud
export async function addCustomCity(city) {
  // localStorage (synchronous - runs before any await)
  const cities = getCustomCities();
  const filtered = cities.filter(c => c.city !== city.city);
  filtered.push(city);
  saveLocal(filtered);

  // Cloud sync (async, fire-and-forget)
  try {
    const existing = await base44.entities.City.filter({ city: city.city });
    const cloudData = {
      city: city.city,
      state: city.state,
      residential: city.residential,
      collector: city.collector,
      arterial: city.arterial,
      initialCosts: city.initialCosts,
      maint30: city.maint30,
      costs: city.costs
    };
    if (existing.length > 0) {
      await base44.entities.City.update(existing[0].id, cloudData);
    } else {
      await base44.entities.City.create(cloudData);
    }
  } catch (err) {
    // Cloud save failed - localStorage still has the city
  }
}

```



```

    }
    return filtered;
}

// Remove a city - deletes from localStorage immediately, then from cloud
export async function removeCustomCity(cityName) {
    // localStorage (synchronous)
    const cities = getCustomCities().filter(c => c.city !== cityName);
    saveLocal(cities);

    // Cloud sync (async, fire-and-forget)
    try {
        const existing = await base44.entities.City.filter({ city: cityName });
        if (existing.length > 0) {
            await base44.entities.City.delete(existing[0].id);
        }
    } catch (err) {
        // Cloud delete failed - localStorage already removed
    }
    return cities;
}

// Sync cloud cities into localStorage - called on app load so everyone sees
all cities
export async function syncCloudCities() {
    try {
        const cloudCities = await base44.entities.City.list();
        const localCities = getCustomCities();
        const localMap = new Map(localCities.map(c => [c.city, c]));

        cloudCities.forEach(c => {
            localMap.set(c.city, {
                city: c.city,
                state: c.state,
                residential: c.residential,
                collector: c.collector,
                arterial: c.arterial,
                initialCosts: c.initialCosts,
                maint30: c.maint30,
                costs: c.costs
            });
        });
    }
};

```

```

    const merged = Array.from(localMap.values());
    saveLocal(merged);
    window.dispatchEvent(new Event("cities-updated"));
    return merged;
  } catch (err) {
    // Cloud fetch failed - use localStorage as-is
    return getCustomCities();
  }
}

// For PavementsAnalysis - costs = 30yr totals
export function getCustomCitiesAnalysis() {
  return getCustomCities().map(c => ({
    city: c.city,
    state: c.state,
    residential: c.residential,
    collector: c.collector,
    arterial: c.arterial,
    costs: c.costs
  }));
}

// For PavementCalculator - costs = initial, maint30 = maintenance
export function getCustomCitiesCalculator() {
  return getCustomCities().map(c => ({
    city: c.city,
    state: c.state,
    residential: c.residential,
    collector: c.collector,
    arterial: c.arterial,
    costs: c.initialCosts,
    maint30: c.maint30
  }));
}

```

PageNotFound.jsx

```

import { useLocation } from 'react-router-dom';
import { base44 } from '@api/base44Client';
import { useQuery } from '@tanstack/react-query';

export default function PageNotFound({}) {

```

```

const location = useLocation();
const pageName = location.pathname.substring(1);

const { data: authData, isFetched } = useQuery({
  queryKey: ['user'],
  queryFn: async () => {
    try {
      const user = await base44.auth.me();
      return { user, isAuthenticated: true };
    } catch (error) {
      return { user: null, isAuthenticated: false };
    }
  }
});

return (
  <div className="min-h-screen flex items-center justify-center p-6
bg-slate-50">
    <div className="max-w-md w-full">
      <div className="text-center space-y-6">
        { /* 404 Error Code */ }
        <div className="space-y-2">
          <h1 className="text-7xl font-light
text-slate-300">404</h1>
          <div className="h-0.5 w-16 bg-slate-200
mx-auto"></div>
        </div>

        { /* Main Message */ }
        <div className="space-y-3">
          <h2 className="text-2xl font-medium text-slate-800">
            Page Not Found
          </h2>
          <p className="text-slate-600 leading-relaxed">
            The page <span className="font-medium
text-slate-700">"{pageName}"</span> could not be found in this application.
          </p>
        </div>

        { /* Admin Note */ }
        {isFetched && authData.isAuthenticated &&
authData.user?.role === 'admin' && (

```

```

        <div className="mt-8 p-4 bg-slate-100 rounded-lg
border border-slate-200">
            <div className="flex items-start space-x-3">
                <div className="flex-shrink-0 w-5 h-5
rounded-full bg-orange-100 flex items-center justify-center mt-0.5">
                    <div className="w-2 h-2 rounded-full
bg-orange-400"></div>
                </div>
                <div className="text-left space-y-1">
                    <p className="text-sm font-medium
text-slate-700">Admin Note</p>
                    <p className="text-sm text-slate-600
leading-relaxed">
                        This could mean that the AI hasn't
implemented this page yet. Ask it to implement it in the chat.
                    </p>
                </div>
            </div>
        </div>
    )}

    { /* Action Button */ }
    <div className="pt-6">
        <button
            onClick={() => window.location.href = '/'}
            className="inline-flex items-center px-4 py-2
text-sm font-medium text-slate-700 bg-white border border-slate-200 rounded-lg
hover:bg-slate-50 hover:border-slate-300 transition-colors duration-200
focus:outline-none focus:ring-2 focus:ring-offset-2 focus:ring-slate-500"
        >
            <svg className="w-4 h-4 mr-2" fill="none"
stroke="currentColor" viewBox="0 0 24 24">
                <path strokeLinecap="round"
strokeLinejoin="round" strokeWidth={2} d="M3 12l2-2m0 0l7-7 7 7M5 10v10a1 1 0
001 1h3m10-11l2 2m-2-2v10a1 1 0 01-1 1h-3m-6 0a1 1 0 00-1-1v-4a1 1 0 01-1-1h2a1
1 0 011 1v4a1 1 0 001 1m-6 0h6" />
            </svg>
            Go Home
        </button>
    </div>
</div>
</div>

```

```

    </div>
  )
}

```

pdfExport.js

```

import jsPDF from "jspdf";

function fmtCost(v) {
  if (!v && v !== 0) return "N/A";
  if (v >= 1000000000000) return `$$${(v / 1000000000000).toFixed(2)}T`;
  if (v >= 10000000000) return `$$${(v / 1000000000).toFixed(2)}B`;
  if (v >= 1000000) return `$$${(v / 1000000).toFixed(2)}M`;
  if (v >= 1000) return `$$${(v / 1000).toFixed(0)}K`;
  return `$$${v}`;
}

export function exportPavementAnalysisPDF(roadType, subtype, filteredData,
config, lifecycleData) {
  const doc = new jsPDF({ unit: "pt", format: "a4" });
  const pageWidth = doc.internal.pageSize.getWidth();
  const pageHeight = doc.internal.pageSize.getHeight();
  const margin = 40;
  let y = 45;

  // Title
  doc.setFontSize(20);
  doc.setTextColor(255, 77, 0);
  doc.setFont(undefined, "bold");
  doc.text("KC Pavement Analysis Report", margin, y);
  y += 18;

  // Subtitle
  doc.setFontSize(9);
  doc.setTextColor(120, 120, 120);
  doc.setFont(undefined, "normal");
  doc.text(`Generated: ${new Date().toLocaleString()}`, margin, y);
  y += 14;
  doc.text(`Road Type: ${config.label} / Subtype: ${subtype}`, margin, y);
  y += 24;

  // Table header
  doc.setFillColor(255, 77, 0);
  doc.rect(margin, y, pageWidth - margin * 2, 20, "F");

```

```

doc.setTextColor(255, 255, 255);
doc.setFontSize(8);
doc.setFont(undefined, "bold");
doc.text("City", margin + 6, y + 13);
doc.text("State", margin + 130, y + 13);
doc.text("Asphalt Spec", margin + 185, y + 13);
doc.text("Concrete Spec", margin + 310, y + 13);
y += 20;

// Table rows
doc.setFont(undefined, "normal");
doc.setTextColor(45, 45, 45);
filteredData.forEach((row, i) => {
  if (y > pageHeight - 80) { doc.addPage(); y = 45; }
  const spec = row[roadType]?.[subtype] || {};
  if (i % 2 === 0) {
    doc.setFillColor(248, 248, 248);
    doc.rect(margin, y, pageWidth - margin * 2, 18, "F");
  }
  doc.text(String(row.city).substring(0, 22), margin + 6, y + 12);
  doc.text(String(row.state).substring(0, 10), margin + 130, y + 12);
  doc.text(String(spec.asphalt || "-").substring(0, 22), margin + 185, y +
12);
  doc.text(String(spec.concrete || "-").substring(0, 22), margin + 310, y +
12);
  y += 18;
});

y += 25;
if (y > pageHeight - 120) { doc.addPage(); y = 45; }

// Lifecycle section
doc.setFontSize(13);
doc.setTextColor(255, 77, 0);
doc.setFont(undefined, "bold");
doc.text(`${config.label} Lifecycle Cost (1-Mile, 36-Year)`, margin, y);
y += 20;

doc.setFontSize(9);
doc.setTextColor(45, 45, 45);
doc.setFont(undefined, "normal");
doc.text("Year", margin, y);

```

```

doc.text("Asphalt", margin + 120, y);
doc.text("Concrete", margin + 260, y);
y += 14;
doc.setDrawColor(220, 220, 220);
doc.line(margin, y - 4, pageWidth - margin, y - 4);

lifecycleData.forEach((d) => {
  if (y > pageHeight - 60) { doc.addPage(); y = 45; }
  doc.text(String(d.year), margin, y);
  doc.text(fmtCost(d.asphalt), margin + 120, y);
  doc.text(fmtCost(d.concrete), margin + 260, y);
  y += 14;
});

y += 20;
if (y > pageHeight - 100) { doc.addPage(); y = 45; }

// Key findings
doc.setFontSize(12);
doc.setTextColor(255, 77, 0);
doc.setFont(undefined, "bold");
doc.text("Key Findings", margin, y);
y += 16;
doc.setFontSize(9);
doc.setTextColor(45, 45, 45);
doc.setFont(undefined, "normal");
const findings = [
  "Asphalt has lower initial construction costs but requires periodic
maintenance every 12 years.",
  "Concrete has higher upfront cost but significantly lower maintenance over
36 years.",
  "Cost parity between asphalt and concrete is typically reached around Year
36.",
  "Optimal material choice depends on traffic volumes, subgrade conditions,
and municipal budgets.",
];
findings.forEach((f, i) => {
  const lines = doc.splitTextToSize(`${i + 1}. ${f}`, pageWidth - margin *
2);
  if (y > pageHeight - 60) { doc.addPage(); y = 45; }
  doc.text(lines, margin, y);
  y += lines.length * 12 + 4;

```

```

});

// Footer
doc.setFontSize(7);
doc.setTextColor(150, 150, 150);
doc.text("KC Pavement Analysis | by Bobby Youan & Danny Will", margin,
pageHeight - 20);

doc.save("kc-pavement-analysis-report.pdf");
}

export function exportCalculatorPDF(result) {
  const doc = new jsPDF({ unit: "pt", format: "a4" });
  const pageWidth = doc.internal.pageSize.getWidth();
  const pageHeight = doc.internal.pageSize.getHeight();
  const margin = 40;
  let y = 45;

  // Title
  doc.setFontSize(20);
  doc.setTextColor(255, 77, 0);
  doc.setFont(undefined, "bold");
  doc.text("Pavement Calculator Report", margin, y);
  y += 18;

  doc.setFontSize(9);
  doc.setTextColor(120, 120, 120);
  doc.setFont(undefined, "normal");
  doc.text(`Generated: ${new Date().toLocaleString()}`, margin, y);
  y += 24;

  // Project details
  doc.setFontSize(11);
  doc.setTextColor(45, 45, 45);
  doc.text(`Location: ${result.city}, ${result.state}`, margin, y); y += 16;
  doc.text(`Road Type: ${result.roadType} / ${result.subtype}`, margin, y); y
+= 16;
  doc.text(`Distance: ${result.distance} ${result.unit}`, margin, y); y += 24;

  // Material specs box
  doc.setFillColor(255, 77, 0);
  doc.rect(margin, y, pageWidth - margin * 2, 20, "F");

```



```

doc.setTextColor(255, 255, 255);
doc.setFontSize(10);
doc.setFont(undefined, "bold");
doc.text("Material Specifications", margin + 8, y + 14);
y += 28;

doc.setTextColor(45, 45, 45);
doc.setFont(undefined, "normal");
doc.setFontSize(10);
const asphLines = doc.splitTextToSize(`Asphalt: ${result.spec.asphalt} ||
"--"`, pageWidth - margin * 2);
doc.text(asphLines, margin, y); y += asphLines.length * 14;
const concLines = doc.splitTextToSize(`Concrete: ${result.spec.concrete} ||
"--"`, pageWidth - margin * 2);
doc.text(concLines, margin, y); y += concLines.length * 14 + 20;

// Cost breakdown table
doc.setFillColor(255, 77, 0);
doc.rect(margin, y, pageWidth - margin * 2, 20, "F");
doc.setTextColor(255, 255, 255);
doc.setFontSize(10);
doc.setFont(undefined, "bold");
doc.text("Cost Breakdown", margin + 8, y + 14);
y += 28;

// Header row
doc.setTextColor(100, 100, 100);
doc.setFontSize(9);
doc.setFont(undefined, "bold");
doc.text("Category", margin, y);
doc.text("Asphalt", margin + 200, y);
doc.text("Concrete", margin + 320, y);
y += 14;
doc.setDrawColor(220, 220, 220);
doc.line(margin, y - 4, pageWidth - margin, y - 4);

// Data rows
doc.setTextColor(45, 45, 45);
doc.setFont(undefined, "normal");
const rows = [
  { label: "Initial Construction", a: result.initA, c: result.initC },
  { label: "30-Year Maintenance", a: result.maintA, c: result.maintC },

```

```

];
rows.forEach(r => {
  doc.text(r.label, margin, y);
  doc.text(fmtCost(r.a), margin + 200, y);
  doc.text(fmtCost(r.c), margin + 320, y);
  y += 16;
});

// Total row
y += 4;
doc.setFillStyle(255, 245, 240);
doc.rect(margin, y - 12, pageWidth - margin * 2, 18, "F");
doc.setFont(undefined, "bold");
doc.text("30-Year Total", margin, y);
doc.text(fmtCost(result.totalA), margin + 200, y);
doc.text(fmtCost(result.totalC), margin + 320, y);
y += 30;

// Recommendation
const cheaper = result.totalA < result.totalC ? "asphalt" : result.totalA >
result.totalC ? "concrete" : "equal";
let rec = "";
if (cheaper === "asphalt") rec = `Asphalt saves ${fmtCost(result.totalC -
result.totalA)} over 30 years.`;
else if (cheaper === "concrete") rec = `Concrete saves
${fmtCost(result.totalA - result.totalC)} over 30 years.`;
else rec = "Asphalt and Concrete have equal 30-year costs.";

doc.setFontSize(10);
doc.setTextColor(255, 77, 0);
doc.setFont(undefined, "bold");
doc.text("Recommendation", margin, y);
y += 14;
doc.setFontSize(9);
doc.setTextColor(45, 45, 45);
doc.setFont(undefined, "normal");
const recLines = doc.splitTextToSize(rec, pageWidth - margin * 2);
doc.text(recLines, margin, y);
y += recLines.length * 12 + 10;

const detailLines = doc.splitTextToSize(

```

```

        `Asphalt: ${fmtCost(result.initA)} initial + ${fmtCost(result.maintA)}
maintenance = ${fmtCost(result.totalA)} total. Concrete:
${fmtCost(result.initC)} initial + ${fmtCost(result.maintC)} maintenance =
${fmtCost(result.totalC)} total.`
        pageWidth - margin * 2
    );
    doc.text(detailLines, margin, y);

    // Footer
    doc.setFontSize(7);
    doc.setTextColor(150, 150, 150);
    doc.text("KC Pavement Analysis | by Bobby Youan & Danny Will", margin,
pageHeight - 20);

    doc.save("pavement-calculator-report.pdf");
}

```

query-client.js

```

import { QueryClient } from '@tanstack/react-query';

export const queryClientInstance = new QueryClient({
  defaultOptions: {
    queries: {
      refetchOnWindowFocus: false,
      retry: 1,
    },
  },
});

```

utils.js

```

import { clsx } from "clsx"
import { twMerge } from "tailwind-merge"

export function cn(...inputs) {
  return twMerge(clsx(inputs))
}

```

```

export const isIframe = window.self !== window.top;

```

pages

ForgotPassword.jsx

```
import React, { useState } from "react";
import { Link } from "react-router-dom";
import { base44 } from "@api/base44Client";
import { Button } from "@components/ui/button";
import { Input } from "@components/ui/input";
import { Label } from "@components/ui/label";
import { Mail, ArrowLeft, Loader2 } from
"lucide-react";
import AuthLayout from "@components/AuthLayout";

export default function ForgotPassword() {
  const [email, setEmail] = useState("");
  const [loading, setLoading] = useState(false);
  const [sent, setSent] = useState(false);

  const handleSubmit = async (e) => {
    e.preventDefault();
    setLoading(true);
    try {
      await base44.auth.resetPasswordRequest(email);
    } catch {
      // Always show success regardless
    } finally {
      setLoading(false);
      setSent(true);
    }
  };

  return (
    <AuthLayout
      icon={Mail}
      title="Reset password"
      subtitle="We'll send you a link to reset it"
      footer={
        <Link to="/login" className="text-primary
font-medium hover:underline">
          <ArrowLeft className="w-3 h-3 inline mr-1"
/>Back to log in
        </Link>
      }
    />
```

```

    >
    {sent ? (
      <p className="text-sm text-foreground
text-center">
        If an account exists with that email, you'll
receive a password reset link shortly.
      </p>
    ) : (
      <form onSubmit={handleSubmit}
className="space-y-4">
        <div className="space-y-2">
          <Label htmlFor="email">Email
address</Label>
          <div className="relative">
            <Mail className="absolute left-3 top-1/2
-translate-y-1/2 w-4 h-4 text-muted-foreground"
aria-hidden="true" />
            <Input
              id="email"
              type="email"
              autoComplete="email"
              autoFocus
              placeholder="you@example.com"
              value={email}
              onChange={ (e) =>
setEmail(e.target.value)}
              className="pl-10 h-12"
              required
            />
          </div>
        </div>
        <Button type="submit" className="w-full h-12
font-medium" disabled={loading}>
          {loading ? (
            <>
              <Loader2 className="w-4 h-4 mr-2
animate-spin" />
              Sending...
            </>
          ) : (
            "Send reset link"
          )}
        </Button>
      </form>
    )}
  )}

```

```

        </Button>
      </form>
    ) }
  </AuthLayout>
);
}

```

Home.jsx

```

import React, { useState, useRef } from "react";
import Navbar from "@components/landing/Navbar";
import Hero from "@components/landing/Hero";
import PavementsAnalysis from
"@components/landing/PavementsAnalysis";
import PavementCalculator from
"@components/landing/PavementCalculator";
import About from "@components/landing/About";
import Contact from "@components/landing/Contact";
import Footer from "@components/landing/Footer";
import Onboarding from
"@components/landing/Onboarding";
import AskAI from "@components/landing/AskAI";

export default function Home() {
  const [onboardingDone, setOnboardingDone] =
useState(false);
  const pavementsRef = useRef(null);

  const jumpToPavements = () => {
    setTimeout(() => {
      const el = document.getElementById("pavements");
      if (el) el.scrollIntoView({ behavior: "smooth"
});
    }, 200);
  };

  return (
    <div className="min-h-screen bg-[#111111]">
      <!onboardingDone && (
        <Onboarding
          onComplete={() => setOnboardingDone(true)}
          onJumpToPavements={jumpToPavements}
        />

```

```

    })
    <Navbar showPavo={onboardingDone} />
    <Hero />
    <div ref={pavementsRef}>
      <PavementsAnalysis />
    </div>
    <PavementCalculator />
    <About />
    <Contact />
    <Footer />
    <AskAI showButton={onboardingDone} />
  </div>
);
}

import React, { useState, useRef } from "react";
import Navbar from "@components/landing/Navbar";
import Hero from "@components/landing/Hero";
import PavementsAnalysis from
"@components/landing/PavementsAnalysis";
import PavementCalculator from
"@components/landing/PavementCalculator";
import About from "@components/landing/About";
import Contact from "@components/landing/Contact";
import Footer from "@components/landing/Footer";
import Onboarding from
"@components/landing/Onboarding";
import AskAI from "@components/landing/AskAI";

export default function Home() {
  const [onboardingDone, setOnboardingDone] =
useState(false);
  const pavementsRef = useRef(null);

  const jumpToPavements = () => {
    setTimeout(() => {
      const el = document.getElementById("pavements");
      if (el) el.scrollIntoView({ behavior: "smooth"
});

    }, 200);
  };

  return (

```

```

<div className="min-h-screen bg-[#111111]">
  {!onboardingDone && (
    <Onboarding
      onComplete={() => setOnboardingDone(true)}
      onJumpToPavements={jumpToPavements}
    />
  )}
  <Navbar showPavo={onboardingDone} />
  <Hero />
  <div ref={pavementsRef}>
    <PavementsAnalysis />
  </div>
  <PavementCalculator />
  <About />
  <Contact />
  <Footer />
  <AskAI showButton={onboardingDone} />
</div>
);
}

```

Login.jsx

```

import React, { useState } from "react";
import { Link } from "react-router-dom";
import { base44 } from "@api/base44Client";
import { Button } from "@components/ui/button";
import { Input } from "@components/ui/input";
import { Label } from "@components/ui/label";
import { LogIn, Mail, Lock, Loader2 } from
"lucide-react";

import AuthLayout from "@components/AuthLayout";
import GoogleIcon from "@components/GoogleIcon";

export default function Login() {
  const [email, setEmail] = useState("");
  const [password, setPassword] = useState("");
  const [error, setError] = useState("");
  const [loading, setLoading] = useState(false);

  const handleSubmit = async (e) => {
    e.preventDefault();
    setError("");
    setLoading(true);

```



```

        try {
            await base44.auth.loginViaEmailPassword(email,
password);
            window.location.href = "/";
        } catch (err) {
            setError(err.message || "Invalid email or
password");
        } finally {
            setLoading(false);
        }
    };

    const handleGoogle = () => {
        base44.auth.loginWithProvider("google", "/");
    };

    return (
        <AuthLayout
            icon={LogIn}
            title="Welcome back"
            subtitle="Log in to your account"
            footer={
                <>
                    Don't have an account?{" "}
                    <Link to="/register" className="text-primary
font-medium hover:underline">
                        Create one
                    </Link>
                </>
            }
        >
        <Button
            variant="outline"
            className="w-full h-12 text-sm font-medium
mb-6"
            onClick={handleGoogle}
        >
            <GoogleIcon className="w-5 h-5 mr-2" />
            Continue with Google
        </Button>

        <div className="relative mb-6">

```

```

        <div className="absolute inset-0 flex
items-center">
          <div className="w-full border-t
border-border" />
        </div>
        <div className="relative flex justify-center
text-xs uppercase">
          <span className="bg-card px-3
text-muted-foreground">or</span>
        </div>
      </div>

      {error && (
        <div className="mb-4 p-3 rounded-lg
bg-destructive/10 text-destructive text-sm">
          {error}
        </div>
      )}

      <form onSubmit={handleSubmit}
className="space-y-4">
        <div className="space-y-2">
          <Label htmlFor="email">Email</Label>
          <div className="relative">
            <Mail className="absolute left-3 top-1/2
-translate-y-1/2 w-4 h-4 text-muted-foreground"
aria-hidden="true" />
            <Input
              id="email"
              type="email"
              autoComplete="email"
              autoFocus
              placeholder="you@example.com"
              value={email}
              onChange={ (e) =>
setEmail(e.target.value) }
              className="pl-10 h-12"
              required
            />
          </div>
        </div>
        <div className="space-y-2">

```

```

        <div className="flex items-center
justify-between">
            <Label htmlFor="password">Password</Label>
            <Link to="/forgot-password"
className="text-xs text-primary hover:underline">
                Forgot password?
            </Link>
        </div>
        <div className="relative">
            <Lock className="absolute left-3 top-1/2
-translate-y-1/2 w-4 h-4 text-muted-foreground"
aria-hidden="true" />
            <Input
                id="password"
                type="password"
                autoComplete="current-password"
                placeholder="....."
                value={password}
                onChange={ (e) =>
setPassword(e.target.value) }
                className="pl-10 h-12"
                required
            />
        </div>
    </div>
    <Button type="submit" className="w-full h-12
font-medium" disabled={loading}>
        {loading ? (
            <>
                <Loader2 className="w-4 h-4 mr-2
animate-spin" />
                Logging in...
            </>
        ) : (
            "Log in"
        )}
    </Button>
</form>
</AuthLayout>
);
}

```

OAuthConsent.jsx

```
import React, { useEffect, useState } from "react";
import { appParams } from "@lib/app-params";
import { Button } from "@components/ui/button";
import { ShieldCheck, Loader2 } from "lucide-react";
import AuthLayout from "@components/AuthLayout";

// App-side OAuth consent page for the app's MCP
server. The platform redirects
// AI clients here (see base44/mcp/config.json
`consent_path`) with an opaque
// `ctx` handle – the authorization request itself
lives on the server. This page
// gates on the app-user session, fetches the display
info for that handle, shows
// the categories of access being granted, and posts
the approve/deny decision.
// Do not change the fetch calls, headers, or the
`ctx` handle handling – styling
// and copy are safe to edit.
export default function OAuthConsent() {
  const ctx = new
URLSearchParams(window.location.search).get("ctx");
  const [info, setInfo] = useState(null);
  const [checking, setChecking] = useState(true);
  const [submitting, setSubmitting] = useState(false);
  const [decided, setDecided] = useState("");
  const [error, setError] = useState("");
  const [reconnect, setReconnect] = useState("");

  useEffect(() => {
    (async () => {
      let redirecting = false;
      try {
        if (!ctx) {
          setError("This authorization link is invalid
or has expired.");
          return;
        }
        // Resolve the handle first: a dead handle
        must never render
      }
    })();
  });
}
```

```

        // approve/deny, and the response carries the
app's configured login
        // route for the signed-out redirect below.
Send the session (cookie +
        // bearer token) so the server can list the
granted tools for a
        // signed-in user – the same auth the
approve/deny call sends; without
        // it the display request is anonymous and
shows no tools.

        const infoHeaders = {};
        if (appParams.token) infoHeaders.Authorization
= "Bearer " + appParams.token;
        const res = await fetch(

`/api/apps/${appParams.appId}/mcp/consent-info?handle=${enco
deURIComponent(ctx)}`,
        { credentials: "include", headers:
infoHeaders },
        );
        if (!res.ok) {
            setError("This authorization link is invalid
or has expired.");
            return;
        }
        const data = await res.json();
        // Gate on the server's auth result, NOT
base44.auth.isAuthenticated():
        // the SDK check runs the bearer path, so a
cookie-only session (platform
        // login/SSO, or a private app with a stale
localStorage token) would read
        // as signed-out and redirect – even though
/consent-info just
        // authenticated this same request via its
cookie fallback. data.authenticated
        // keeps the redirect decision in agreement
with what the server returned.
        if (!data.authenticated) {
            // The short handle rides back in returnTo;
login_path is

```

```

        // owner-configured and validated
server-side as a same-origin path.
        // Send from_url too: a custom-auth app
coerced to platform auth (e.g.
        // public_without_login under workspace SSO)
serves the platform login,
        // which honors from_url rather than
returnTo. Rebuild the query from
        // `ctx` alone — never forward
window.location.search raw: the platform
        // resume returns from_url verbatim, so
crafted extras on the consent
        // link (app_base_url, access_token, ...)
would ride through the login
        // round-trip and app-params.js would
persist them into the freshly
        // authenticated session.
const returnTo =
    window.location.pathname + "?ctx=" +
encodeURIComponent(ctx);
const encoded =
encodeURIComponent(returnTo);
    redirecting = true; // keep the spinner
while the browser navigates
    window.location.href =
        (data.login_path || "/login") +
"?returnTo=" + encoded + "&from_url=" + encoded;
    return;
}
setInfo(data);
} catch (e) {
    setError("Could not load this authorization
request. Please try again.");
} finally {
    if (!redirecting) setChecking(false);
}
}) ();
}, [ctx]);

const respond = async (action) => {
    setSubmitting(true);
    setError("");

```

```

    try {
        const headers = { "Content-Type":
"application/json" };
        // Cookie-backed sessions carry no token;
        sending "Bearer null" would
        // shadow the valid cookie, so add the header
        only when a token exists.
        if (appParams.token) headers.Authorization =
"Bearer " + appParams.token;
        const res = await
fetch(`/api/apps/${appParams.appId}/mcp/authorize-grant`, {
    method: "POST",
    credentials: "include",
    headers,
    body: JSON.stringify({ ctx, action }),
});
        if (!res.ok) {
            // 401 = the session expired before the
(single-use, still-unconsumed)
            // handle was spent; retrying the same
controls re-sends the dead session
            // forever. Send the user back through login
preserving `ctx` – the same
            // redirect the initial signed-out path uses –
so they can return and
            // approve the still-valid handle.
            if (res.status === 401) {
                const returnTo = window.location.pathname +
"?ctx=" + encodeURIComponent(ctx);
                const encoded =
encodeURIComponent(returnTo);
                window.location.href =
                ((info && info.login_path) || "/login") +
"?returnTo=" + encoded + "&from_url=" + encoded;
                return;
            }
            // These all come AFTER the single-use handle
is atomically consumed
            // (409 tool set changed; 403
host/resource/app mismatch; 404 access
            // gone; 400 malformed/handle already used),
so retrying can only 404.

```

```

        // Show a terminal reconnect state, not an
impossible "try again".
        if ([400, 403, 404, 409].includes(res.status))
{
    let detail = "";
    try { detail = (await res.json()).detail; }
catch (_) { /* keep default */ }
    setReconnect(detail || "This authorization
can no longer be completed. Reconnect from your AI client to
try again.");

    setSubmitting(false);
    return;
}
    throw new Error("Could not complete
authorization. Please try again.");
}
    const data = await res.json();
    window.location.href = data.redirect_url;
    if (!/^https?:/i.test(data.redirect_url)) {
        // Custom-scheme redirect (native AI clients,
e.g. cursor://): browsers
        // may block or not visibly navigate, so show
a terminal state instead
        // of an eternal spinner.
        setDecided(action);
        setSubmitting(false);
    }
} catch (e) {
    setError(e.message);
    setSubmitting(false);
}
};

if (checking) {
    return (
        <AuthLayout icon={ShieldCheck} title="Authorize
access">
            <div className="flex items-center
justify-center py-6 text-muted-foreground">
                <Loader2 className="w-5 h-5 mr-2
animate-spin" aria-hidden="true" />
                Loading...
            </div>
        </AuthLayout>
    );
}

```



```

        </div>
      </AuthLayout>
    );
  }

  const client = (info && info.client_name) || "An AI
client";
  const appName = (info && info.app_name) || "this
app";

  if (decided) {
    return (
      <AuthLayout
        icon={ShieldCheck}
        title={decided === "approve" ? "Access
granted" : "Access denied"}
        subtitle={`You can return to ${client} and
close this window.`}
      />
    );
  }

  // Terminal: the authorization request is no longer
valid (tool set changed +
  // handle consumed). Retrying can't succeed, so show
reconnect guidance with
  // no approve/deny controls.
  if (reconnect) {
    return (
      <AuthLayout icon={ShieldCheck} title="Reconnect
required">
        <div className="p-3 rounded-lg
bg-destructive/10 text-destructive text-sm">
          {reconnect}
        </div>
      </AuthLayout>
    );
  }

  // No consent details means nothing trustworthy to
approve: a failed

```

```

        // consent-info load (expired handle, rate limit,
transient error) renders
        // the error alone, never the approve/deny controls.
        if (error && !info) {
            return (
                <AuthLayout icon={ShieldCheck} title="Authorize
access">
                    <div className="p-3 rounded-lg
bg-destructive/10 text-destructive text-sm">
                        {error}
                    </div>
                </AuthLayout>
            );
        }

        const tools = Array.isArray(info.tools) ? info.tools
: [];

        return (
            <AuthLayout
                icon={ShieldCheck}
                title="Authorize access"
                subtitle={` ${client} wants to access ${appName}
on your behalf`}
            >
                {error && (
                    <div className="mb-4 p-3 rounded-lg
bg-destructive/10 text-destructive text-sm">
                        {error}
                    </div>
                )}

                <p className="text-sm font-medium
text-foreground mb-2">
                    {tools.length ? `It will be able to use these
tools in ${appName}:` : "No tools requested"}
                </p>
                {tools.length > 0 && (
                    <ul className="space-y-2 text-sm mb-6">
                        {tools.map((tool) => (
                            <li key={tool.name} className="flex
flex-col">

```

```

        <span className="text-foreground
font-medium">
            {tool.title || tool.name}
        </span>
        {tool.description && (
            <span
className="text-muted-foreground">{tool.description}</span>
        )}
    </li>
    )}
</ul>
)}

<div className="flex gap-3">
    <Button
        variant="outline"
        className="flex-1 h-12 font-medium"
        disabled={submitting}
        onClick={() => respond("deny")}
    >
        Deny
    </Button>
    <Button
        className="flex-1 h-12 font-medium"
        disabled={submitting}
        onClick={() => respond("approve")}
    >
        {submitting ? <Loader2 className="w-4 h-4
mr-2 animate-spin" /> : null}
        Approve
    </Button>
</div>
</AuthLayout>
);
}

```

Register.jsx

```

import React, { useState } from "react";
import { Link } from "react-router-dom";
import { base44 } from "@api/base44Client";
import { Button } from "@components/ui/button";
import { Input } from "@components/ui/input";

```

```

import { Label } from "@/components/ui/label";
import { UserPlus, Mail, Lock, Loader2 } from
"lucide-react";
import { InputOTP, InputOTPGroup, InputOTPSlot } from
"@/components/ui/input-otp";
import AuthLayout from "@/components/AuthLayout";
import GoogleIcon from "@/components/GoogleIcon";
import { toast } from "@/components/ui/use-toast";

export default function Register() {
  const [email, setEmail] = useState("");
  const [password, setPassword] = useState("");
  const [confirmPassword, setConfirmPassword] =
useState("");
  const [error, setError] = useState("");
  const [loading, setLoading] = useState(false);
  const [showOtp, setShowOtp] = useState(false);
  const [otpCode, setOtpCode] = useState("");

  const handleSubmit = async (e) => {
    e.preventDefault();
    setError("");
    if (password !== confirmPassword) {
      setError("Passwords do not match");
      return;
    }
    setLoading(true);
    try {
      await base44.auth.register({ email, password });
      setShowOtp(true);
    } catch (err) {
      setError(err.message || "Registration failed");
    } finally {
      setLoading(false);
    }
  };

  const handleVerify = async () => {
    setError("");
    setLoading(true);
    try {

```

```

        const result = await base44.auth.verifyOtp({
email, otpCode });
        if (result?.access_token) {
            base44.auth.setToken(result.access_token);
        }
        window.location.href = "/";
    } catch (err) {
        setError(err.message || "Invalid verification
code");
    } finally {
        setLoading(false);
    }
};

const handleResend = async () => {
    setError("");
    try {
        await base44.auth.resendOtp(email);
        toast({
            title: "Code sent",
            description: "Check your email for the new
code.",
        });
    } catch (err) {
        setError(err.message || "Failed to resend
code");
    }
};

const handleGoogle = () => {
    base44.auth.loginWithProvider("google", "/");
};

if (showOtp) {
    return (
        <AuthLayout
            icon={Mail}
            title="Verify your email"
            subtitle={`We sent a code to ${email}`}
        >
            {error && (

```

```

        <div className="mb-4 p-3 rounded-lg
bg-destructive/10 text-destructive text-sm">
            {error}
        </div>
    )}
    <div className="flex justify-center mb-6">
        <InputOTP
            maxLength={6}
            value={otpCode}
            onChange={setOtpCode}
            autoFocus
            autoComplete="one-time-code"
        >
            <InputOTPGroup>
                <InputOTPSlot index={0} />
                <InputOTPSlot index={1} />
                <InputOTPSlot index={2} />
                <InputOTPSlot index={3} />
                <InputOTPSlot index={4} />
                <InputOTPSlot index={5} />
            </InputOTPGroup>
        </InputOTP>
    </div>
    <Button
        className="w-full h-12 font-medium"
        onClick={handleVerify}
        disabled={loading || otpCode.length < 6}
    >
        {loading ? (
            <>
                <Loader2 className="w-4 h-4 mr-2
animate-spin" />
                Verifying...
            </>
        ) : (
            "Verify"
        )}
    </Button>
    <p className="text-center text-sm
text-muted-foreground mt-4">
        Didn't receive the code?{" "}

```

```

        <button onClick={handleResend}
className="text-primary font-medium hover:underline">
            Resend
        </button>
    </p>
</AuthLayout>
);
}

return (
    <AuthLayout
        icon={UserPlus}
        title="Create your account"
        subtitle="Sign up to get started"
        footer={
            <>
                Already have an account?{" "}
                <Link to="/login" className="text-primary
font-medium hover:underline">
                    Log in
                </Link>
            </>
        }
    >
        <Button
            variant="outline"
            className="w-full h-12 text-sm font-medium
mb-6"
            onClick={handleGoogle}
        >
            <GoogleIcon className="w-5 h-5 mr-2" />
            Continue with Google
        </Button>

        <div className="relative mb-6">
            <div className="absolute inset-0 flex
items-center">
                <div className="w-full border-t
border-border" />
            </div>
            <div className="relative flex justify-center
text-xs uppercase">

```

```

        <span className="bg-card px-3
text-muted-foreground">or</span>
    </div>
</div>

{error && (
    <div className="mb-4 p-3 rounded-lg
bg-destructive/10 text-destructive text-sm">
        {error}
    </div>
)}

<form onSubmit={handleSubmit}
className="space-y-4">
    <div className="space-y-2">
        <Label htmlFor="email">Email</Label>
        <div className="relative">
            <Mail className="absolute left-3 top-1/2
-translate-y-1/2 w-4 h-4 text-muted-foreground"
aria-hidden="true" />
            <Input
                id="email"
                type="email"
                autoComplete="email"
                autoFocus
                placeholder="you@example.com"
                value={email}
                onChange={ (e) =>
setEmail(e.target.value)}
                className="pl-10 h-12"
                required
            />
        </div>
    </div>
    <div className="space-y-2">
        <Label htmlFor="password">Password</Label>
        <div className="relative">
            <Lock className="absolute left-3 top-1/2
-translate-y-1/2 w-4 h-4 text-muted-foreground"
aria-hidden="true" />
            <Input
                id="password"

```



```

        type="password"
        autoComplete="new-password"
        placeholder="....."
        value={password}
        onChange={ (e) =>
setPassword(e.target.value) }
        className="pl-10 h-12"
        required
      />
    </div>
  </div>
  <div className="space-y-2">
    <Label htmlFor="confirm">Confirm
Password</Label>
    <div className="relative">
      <Lock className="absolute left-3 top-1/2
-translate-y-1/2 w-4 h-4 text-muted-foreground"
aria-hidden="true" />
      <Input
        id="confirm"
        type="password"
        autoComplete="new-password"
        placeholder="....."
        value={confirmPassword}
        onChange={ (e) =>
setConfirmPassword(e.target.value) }
        className="pl-10 h-12"
        required
      />
    </div>
  </div>
  <Button type="submit" className="w-full h-12
font-medium" disabled={loading}>
    {loading ? (
      <>
        <Loader2 className="w-4 h-4 mr-2
animate-spin" />
        Creating account...
      </>
    ) : (
      "Create account"
    )}
  </Button>

```

```

        </Button>
      </form>
    </AuthLayout>
  );
}

```

ResetPassword.jsx

```

import React, { useState } from "react";
import { Link, useSearchParams } from
"react-router-dom";
import { base44 } from "@api/base44Client";
import { Button } from "@components/ui/button";
import { Input } from "@components/ui/input";
import { Label } from "@components/ui/label";
import { Lock, Loader2, AlertTriangle } from
"lucide-react";
import AuthLayout from "@components/AuthLayout";

export default function ResetPassword() {
  const [searchParams] = useSearchParams();
  const resetToken = searchParams.get("token");

  const [newPassword, setNewPassword] = useState("");
  const [confirmPassword, setConfirmPassword] =
useState("");
  const [error, setError] = useState("");
  const [loading, setLoading] = useState(false);

  const handleSubmit = async (e) => {
    e.preventDefault();
    setError("");
    if (newPassword !== confirmPassword) {
      setError("Passwords do not match");
      return;
    }
    setLoading(true);
    try {
      await base44.auth.resetPassword({ resetToken,
newPassword });
      window.location.href = "/login";
    } catch (err) {

```

```

        setError(err.message || "Failed to reset
password");
    } finally {
        setLoading(false);
    }
};

if (!resetToken) {
    return (
        <AuthLayout
            icon={AlertTriangle}
            title="Invalid reset link"
            subtitle="This password reset link is missing
or invalid"
            footer={
                <Link to="/forgot-password"
className="text-primary font-medium hover:underline">
                    Request a new link
                </Link>
            }
        >
        <p className="text-sm text-foreground
text-center">
            The link you used appears to be incomplete.
Please request a new password reset email.
        </p>
        </AuthLayout>
    );
}

return (
    <AuthLayout
        icon={Lock}
        title="New password"
        subtitle="Enter your new password below"
    >
        {error && (
            <div className="mb-4 p-3 rounded-lg
bg-destructive/10 text-destructive text-sm">
                {error}
            </div>
        )}
    )}

```

```

        <form onSubmit={handleSubmit}
className="space-y-4">
        <div className="space-y-2">
            <Label htmlFor="password">New
Password</Label>
            <div className="relative">
                <Lock className="absolute left-3 top-1/2
-translate-y-1/2 w-4 h-4 text-muted-foreground"
aria-hidden="true" />
                <Input
                    id="password"
                    type="password"
                    autoComplete="new-password"
                    autoFocus
                    placeholder="....."
                    value={newPassword}
                    onChange={ (e) =>
setNewPassword(e.target.value) }
                    className="pl-10 h-12"
                    required
                />
            </div>
        </div>
        <div className="space-y-2">
            <Label htmlFor="confirm">Confirm
Password</Label>
            <div className="relative">
                <Lock className="absolute left-3 top-1/2
-translate-y-1/2 w-4 h-4 text-muted-foreground"
aria-hidden="true" />
                <Input
                    id="confirm"
                    type="password"
                    autoComplete="new-password"
                    placeholder="....."
                    value={confirmPassword}
                    onChange={ (e) =>
setConfirmPassword(e.target.value) }
                    className="pl-10 h-12"
                    required
                />
            </div>
        </div>
    </form>

```

```

        </div>
        <Button type="submit" className="w-full h-12
font-medium" disabled={loading}>
          {loading ? (
            <>
              <Loader2 className="w-4 h-4 mr-2
animate-spin" />
              Resetting...
            </>
          ) : (
            "Reset password"
          )}
        </Button>
      </form>
    </AuthLayout>
  );
}

```

utils

index.ts

```

export function createPageUrl(pageName: string) {
  return '/' + pageName.replace(/ /g, '-');
}

```

App.jsx

```

import { Toaster } from "@components/ui/toaster"
import { QueryClientProvider } from '@tanstack/react-query'
import { queryClientInstance } from '@lib/query-client'
import { BrowserRouter as Router, Route, Routes } from
'react-router-dom';
import PageNotFound from './lib/PageNotFound';
import { AuthProvider, useAuth } from '@lib/AuthContext';
import UserNotRegisteredError from
'@/components/UserNotRegisteredError';
import ScrollToTop from './components/ScrollToTop';
import Home from './pages/Home';
// Add page imports here

const AuthenticatedApp = () => {
  const { isLoadingAuth, isLoadingPublicSettings, authError,
navigateToLogin } = useAuth();

```

```

        // Show loading spinner while checking app public settings or
auth
        if (isLoadingPublicSettings || isLoadingAuth) {
            return (
                <div className="fixed inset-0 flex items-center
justify-center">
                    <div className="w-8 h-8 border-4 border-slate-200
border-t-slate-800 rounded-full animate-spin"></div>
                </div>
            );
        }

        // Handle authentication errors
        if (authError) {
            if (authError.type === 'user_not_registered') {
                return <UserNotRegisteredError />;
            } else if (authError.type === 'auth_required') {
                // Redirect to login automatically
                navigateToLogin();
                return null;
            }
        }
    }

    // Render the main app
    return (
        <Routes>
            <Route path="/" element={<Home />} />
            <Route path="*" element={<PageNotFound />} />
        </Routes>
    );
};

function App() {

    return (
        <AuthProvider>
            <QueryClientProvider client={queryClientInstance}>
                <Router>
                    <ScrollToTop />
                    <AuthenticatedApp />
                </Router>
            </QueryClientProvider>
        </AuthProvider>
    );
}

```

```

        <Toaster />
      </QueryClientProvider>
    </AuthProvider>
  )
}

export default App
index.css
@tailwind base;
@tailwind components;
@tailwind utilities;

@import
url('https://fonts.googleapis.com/css2?family=Space+Grotesk:wght@300;400;500;600;700&family=JetBrains+Mono:wght@400;500;600;700&display=swap');

@layer base {
  :root {
    --background: 0 0% 6.7%;
    --foreground: 40 20% 93.3%;
    --card: 0 0% 9%;
    --card-foreground: 40 20% 93.3%;
    --popover: 0 0% 9%;
    --popover-foreground: 40 20% 93.3%;
    --primary: 18 100% 50%;
    --primary-foreground: 0 0% 100%;
    --secondary: 215 14% 34%;
    --secondary-foreground: 40 20% 93.3%;
    --muted: 0 0% 12%;
    --muted-foreground: 215 10% 55%;
    --accent: 18 100% 50%;
    --accent-foreground: 0 0% 100%;
    --destructive: 0 84.2% 60.2%;
    --destructive-foreground: 0 0% 98%;
    --border: 0 0% 16%;
    --input: 0 0% 16%;
    --ring: 18 100% 50%;
    --chart-1: 18 100% 50%;
    --chart-2: 215 14% 45%;
    --chart-3: 40 20% 93.3%;
    --chart-4: 18 80% 65%;
    --chart-5: 215 20% 60%;
  }
}

```

```

        --radius: 0.25rem;
        --font-heading: 'Space Grotesk', ui-sans-serif, system-ui,
sans-serif;
        --font-body: 'Space Grotesk', ui-sans-serif, system-ui,
sans-serif;
        --font-display: 'Space Grotesk', ui-sans-serif, system-ui,
sans-serif;
        --font-mono: 'JetBrains Mono', ui-monospace, SFMono-Regular,
Menlo, Monaco, Consolas, monospace;
        --sidebar-background: 0 0% 6.7%;
        --sidebar-foreground: 40 20% 93.3%;
        --sidebar-primary: 18 100% 50%;
        --sidebar-primary-foreground: 0 0% 100%;
        --sidebar-accent: 0 0% 12%;
        --sidebar-accent-foreground: 40 20% 93.3%;
        --sidebar-border: 0 0% 16%;
        --sidebar-ring: 18 100% 50%;
    }
}

@layer base {
    * {
        @apply border-border outline-ring/50;
    }

    body {
        @apply bg-background text-foreground font-body;
    }

    html {
        scroll-behavior: smooth;
        font-size: 16px;
    }
}

.grid-overlay {
    background-image:
        linear-gradient(rgba(74, 85, 104, 0.06) 1px, transparent 1px),
        linear-gradient(90deg, rgba(74, 85, 104, 0.06) 1px,
transparent 1px);

```



```

    background-size: 60px 60px;
}

.text-gradient-orange {
    background: linear-gradient(135deg, #FF4D00, #FF7A33);
    -webkit-background-clip: text;
    -webkit-text-fill-color: transparent;
    background-clip: text;
}

.hero-gradient {
    background: linear-gradient(180deg, rgba(17,17,17,0) 0%,
    rgba(17,17,17,0.7) 40%, rgba(17,17,17,0.95) 100%);
}

.mic-glow {
    animation: micPulse 1.2s ease-in-out infinite;
    border-radius: 9999px;
    background-color: rgba(255, 77, 0, 0.12);
}

@keyframes micPulse {
    0%, 100% {
        box-shadow: 0 0 10px 3px rgba(255, 77, 0, 0.5), 0 0 20px 6px
    rgba(255, 77, 0, 0.2);
        transform: scale(1);
    }
    50% {
        box-shadow: 0 0 22px 8px rgba(255, 77, 0, 0.85), 0 0 40px 16px
    rgba(255, 77, 0, 0.3);
        transform: scale(1.22);
    }
}

.speaking-bars span {
    animation: speakBar 0.6s ease-in-out infinite;
}

@keyframes speakBar {
    0%, 100% { transform: scaleY(0.4); }
    50% { transform: scaleY(1); }
}

```

main.jsx

```
import React from 'react'
import ReactDOM from 'react-dom/client'
import App from '@App.jsx'
import '@index.css'

ReactDOM.createRoot(document.getElementById('root')).render(
  <App />
)
```

.gitignore

#env

.env

.env.*

Logs

/logs

*.log

npm-debug.log*

yarn-debug.log*

yarn-error.log*

pnpm-debug.log*

lerna-debug.log*

node_modules

dist

dist-ssr

*.local

Editor directories and files

.vscode/*

!.vscode/extensions.json

.idea

.DS_Store

*.suo

.ntvs

*.njsproj

*.sln

*.sw?

.env
.vite
base44/.app.jsonc

AGENTS.md

AGENTS.md

Project Context

This is a Base44 app repository. Treat it as user-owned application code, keep changes focused on the user's request, and preserve existing project conventions.

Start with `README.md` for local setup, environment variables, and publish workflow.

Base44 References

- CLI overview:

<https://docs.base44.com/developers/references/cli/get-started/overview.md>

- Agent skills: <https://docs.base44.com/developers/backend/overview/skills.md>

If your agent supports Agent Skills, install or update Base44 skills before Base44-specific work:

```
```bash
npx skills add base44/skills
```
```

Key Files

- `src/`: frontend application source.
- `src/api/base44Client.js`: frontend Base44 SDK client.
- `vite.config.js`: Vite config and Base44 Vite plugin setup.
- `.env.local`: local-only environment values; never commit secrets.

Working Notes

- Use ``base44 dev`` as the default local development command when you need the local Base44 backend. It can run the backend and frontend together.
- When docs or code mention the frontend being started automatically, that usually means the Base44 project config includes ``site.serveCommand``, for example ``"serveCommand": "npm run dev"`` in ``base44/config.jsonc``.
- Use ``npm run dev`` only for frontend-only work against the hosted Base44 backend.
- Prefer the existing Base44 CLI workflow over adding new npm scripts for Base44-specific tasks.
- Reuse the existing SDK client and Vite plugin patterns before adding new Base44 integration paths.
- Run the relevant checks from ``package.json`` before finishing code changes.

CLAUDE.md

See [AGENTS.md](#)

Follow the instructions in ``AGENTS.md``.

components.json

```
{
  "$schema": "https://ui.shadcn.com/schema.json",
  "style": "new-york",
  "rsc": false,
  "tsx": false,
  "tailwind": {
    "config": "tailwind.config.js",
    "css": "src/index.css",
    "baseColor": "neutral",
    "cssVariables": true,
    "prefix": ""
  },
  "aliases": {
    "components": "@components",
    "utils": "@lib/utils",
    "ui": "@components/ui",
    "lib": "@lib",
    "hooks": "@hooks"
  },
  "iconLibrary": "lucide"
}
```

eslint.config.js

```
import globals from "globals";
import pluginJs from "@eslint/js";
import pluginReact from "eslint-plugin-react";
import pluginReactHooks from "eslint-plugin-react-hooks";
import pluginUnusedImports from "eslint-plugin-unused-imports";

export default [
  {
    files: [
      "src/components/**/*..{js,mjs,cjs,jsx}",
      "src/pages/**/*..{js,mjs,cjs,jsx}",
      "src/Layout.jsx",
    ],
    ignores: ["src/lib/**/*.", "src/components/ui/**/*."],
    ...pluginJs.configs.recommended,
    ...pluginReact.configs.flat.recommended,
    languageOptions: {
      globals: globals.browser,
      parserOptions: {
        ecmaVersion: 2022,
        sourceType: "module",
        ecmaFeatures: {
          jsx: true,
        },
      },
    },
    settings: {
      react: {
        version: "detect",
      },
    },
    plugins: {
      react: pluginReact,
      "react-hooks": pluginReactHooks,
      "unused-imports": pluginUnusedImports,
    },
    rules: {
      "no-unused-vars": "off",
      "react/jsx-uses-vars": "error",
      "react/jsx-uses-react": "error",
      "unused-imports/no-unused-imports": "error",
    },
  },
];
```

```

    "unused-imports/no-unused-vars": [
      "warn",
      {
        vars: "all",
        varsIgnorePattern: "^_",
        args: "after-used",
        argsIgnorePattern: "^_",
      },
    ],
    "react/prop-types": "off",
    "react/react-in-jsx-scope": "off",
    "react/no-unknown-property": [
      "error",
      { ignore: ["cmdk-input-wrapper", "toast-close"] },
    ],
    "react-hooks/rules-of-hooks": "error",
  },
},
];

```

index.html

```

<!doctype html>
<html lang="en">
  <head>
    <meta charset="UTF-8" />
    <link rel="icon" type="image/svg+xml"
href="https://base44.com/logo_v2.svg" />
    <meta name="viewport" content="width=device-width, initial-scale=1.0" />
    <link rel="manifest" href="/manifest.json" />
    <title>BHC Engineering – Civil Engineering & KC Pavements Analysis</title>
    <meta name="description" content="Data-driven civil engineering for the
Kansas City metro. Public works, development, surveying, telecom,
construction, and the KC Pavements Analysis platform." />
  </head>
  <body>
    <div id="root"></div>
    <script type="module" src="/src/main.jsx"></script>
  </body>
</html>

```

jsconfig.json

```
{
  "compilerOptions": {
    "baseUrl": ".",
    "paths": {
      "@/*": [".src/*"]
    },
    "jsx": "react-jsx",
    "module": "esnext",
    "moduleResolution": "bundler",
    "lib": ["esnext", "dom"],
    "target": "esnext",
    "checkJs": true,
    "skipLibCheck": true,
    "allowSyntheticDefaultImports": true,
    "esModuleInterop": true,
    "resolveJsonModule": true,
    "types": []
  },
  "include": ["src/components/**/*.js", "src/pages/**/*.jsx",
"src/Layout.jsx"],
  "exclude": ["node_modules", "dist", "src/vite-plugins", "src/components/ui",
"src/api", "src/lib"]
}
```

package.json

```
{
  "name": "base44-app",
  "private": true,
  "version": "0.0.0",
  "type": "module",
  "scripts": {
    "dev": "vite",
    "build": "vite build",
    "lint": "eslint . --quiet",
    "lint:fix": "eslint . --fix",
    "typecheck": "tsc -p ./jsconfig.json",
    "preview": "vite preview"
  },
  "dependencies": {
    "@base44/sdk": "^0.8.41",
    "@base44/vite-plugin": "^1.0.30",
    "@hello-pangea/dnd": "^17.0.0",

```

```
"@hookform/resolvers": "^4.1.2",
"@radix-ui/react-accordion": "^1.2.3",
"@radix-ui/react-alert-dialog": "^1.1.6",
"@radix-ui/react-aspect-ratio": "^1.1.2",
"@radix-ui/react-avatar": "^1.1.3",
"@radix-ui/react-checkbox": "^1.1.4",
"@radix-ui/react-collapsible": "^1.1.3",
"@radix-ui/react-context-menu": "^2.2.6",
"@radix-ui/react-dialog": "^1.1.6",
"@radix-ui/react-dropdown-menu": "^2.1.6",
"@radix-ui/react-hover-card": "^1.1.6",
"@radix-ui/react-label": "^2.1.2",
"@radix-ui/react-menubar": "^1.1.6",
"@radix-ui/react-navigation-menu": "^1.2.5",
"@radix-ui/react-popover": "^1.1.6",
"@radix-ui/react-progress": "^1.1.2",
"@radix-ui/react-radio-group": "^1.2.3",
"@radix-ui/react-scroll-area": "^1.2.3",
"@radix-ui/react-select": "^2.1.6",
"@radix-ui/react-separator": "^1.1.2",
"@radix-ui/react-slider": "^1.2.3",
"@radix-ui/react-slot": "^1.1.2",
"@radix-ui/react-switch": "^1.1.3",
"@radix-ui/react-tabs": "^1.1.3",
"@radix-ui/react-toast": "^1.2.2",
"@radix-ui/react-toggle": "^1.1.2",
"@radix-ui/react-toggle-group": "^1.1.2",
"@radix-ui/react-tooltip": "^1.1.8",
"@stripe/react-stripe-js": "^3.0.0",
"@stripe/stripe-js": "^5.2.0",
"@tanstack/react-query": "^5.84.1",
"canvas-confetti": "^1.9.4",
"class-variance-authority": "^0.7.1",
"clsx": "^2.1.1",
"cmdk": "^1.0.0",
"date-fns": "^3.6.0",
"embla-carousel-react": "^8.5.2",
"framer-motion": "^11.16.4",
"html2canvas": "^1.4.1",
"input-otp": "^1.4.2",
"jspdf": "^4.2.1",
"lodash": "^4.17.21",
```



```

    "lucide-react": "^0.475.0",
    "moment": "^2.30.1",
    "next-themes": "^0.4.4",
    "react": "^18.2.0",
    "react-day-picker": "^8.10.1",
    "react-dom": "^18.2.0",
    "react-hook-form": "^7.54.2",
    "react-hot-toast": "^2.6.0",
    "react-leaflet": "^4.2.1",
    "react-markdown": "^9.0.1",
    "react-quill": "^2.0.0",
    "react-resizable-panels": "^2.1.7",
    "react-router-dom": "^6.26.0",
    "recharts": "^2.15.4",
    "remark-gfm": "^4.0.1",
    "sonner": "^2.0.1",
    "tailwind-merge": "^3.0.2",
    "tailwindcss-animate": "^1.0.7",
    "three": "^0.171.0",
    "vaul": "^1.1.2",
    "zod": "^3.24.2"
  },
  "devDependencies": {
    "@eslint/js": "^9.19.0",
    "@types/node": "^22.13.5",
    "@types/react": "^18.2.66",
    "@types/react-dom": "^18.2.22",
    "@vitejs/plugin-react": "^4.3.4",
    "autoprefixer": "^10.4.20",
    "baseline-browser-mapping": "^2.8.32",
    "eslint": "^9.19.0",
    "eslint-plugin-react": "^7.37.4",
    "eslint-plugin-react-hooks": "^5.0.0",
    "eslint-plugin-react-refresh": "^0.4.18",
    "eslint-plugin-unused-imports": "^4.3.0",
    "globals": "^15.14.0",
    "postcss": "^8.5.3",
    "tailwindcss": "^3.4.17",
    "typescript": "^5.8.2",
    "vite": "^6.1.0"
  }
}

```

postcss.config.js

```
export default {
  plugins: {
    tailwindcss: {},
    autoprefixer: {},
  },
}
```

README.md

Base44 Project

Use this repository to run and edit the app locally, then publish changes back through Base44.

Any change pushed to the repo will also be reflected in the Base44 Builder.

Prerequisites

1. Clone the repository using the project's Git URL.
2. Navigate to the project directory.
3. Install dependencies: ``npm install``.
4. Install the Base44 CLI: ``npm install -g base44@latest``.

See the [Base44 CLI docs] (<https://docs.base44.com/developers/references/cli/get-started/overview>) if you want to run Base44 commands directly.

Run Locally

Run the full local development environment from the project root:

```
```bash
base44 dev
```
```

``base44 dev`` starts the local Base44 development backend and, when this app is configured for it, also starts the frontend dev server for you. Use the frontend URL printed by the command.

For example, when the Base44 project config includes a ``serveCommand``, ``base44 dev`` can launch the frontend too:

```
```json5
{
 "site": {
 "serveCommand": "npm run dev"
 }
}
```
```

In a Base44 project this lives in `base44/config.jsonc`.

Run Only The Frontend

If you only want to work on the frontend against the hosted Base44 backend, run:

```
```bash
npm run dev
```
```

Open the local URL printed by Vite.

Use The Hosted Backend

For frontend-only development, create or update `.env.local` in the project root:

```
```bash
VITE_BASE44_APP_ID=your_app_id
VITE_BASE44_APP_BASE_URL=https://your-app.base44.app
```
```

`VITE_BASE44_APP_ID` identifies the Base44 app.

`VITE_BASE44_APP_BASE_URL` tells the Base44 Vite plugin where to send local `/api` requests. Point it at your deployed Base44 app URL when you want the local frontend to use the hosted backend.

When you use `base44 dev`, the command injects the local Base44 values for you, so `.env.local` is mainly needed for frontend-only workflows.

Publish Your Changes

After pushing your changes to git, open the Base44 dashboard and publish the app:

```
```bash
```

```
base44 dashboard open
```

```
```
```

Docs & Support

Documentation:

[<https://docs.base44.com/Integrations/Using-GitHub>] (<https://docs.base44.com/Integrations/Using-GitHub>)

Base44 CLI command reference:

[<https://docs.base44.com/developers/references/cli/commands/introduction>] (<https://docs.base44.com/developers/references/cli/commands/introduction>)

Support: [<https://app.base44.com/support>] (<https://app.base44.com/support>)

tailwind.config.js

```
/** @type {import('tailwindcss').Config} */
module.exports = {
  darkMode: ["class"],
  content: ["../index.html", "./src/**/*.{ts,tsx,js,jsx}"],
  theme: {
    extend: {
      borderRadius: {
        lg: 'var(--radius)',
        md: 'calc(var(--radius) - 2px)',
        sm: 'calc(var(--radius) - 4px)'
      },
      colors: {
        background: 'hsl(var(--background))',
        foreground: 'hsl(var(--foreground))',
        card: {
          DEFAULT: 'hsl(var(--card))',
          foreground: 'hsl(var(--card-foreground))'
        },
        popover: {
          DEFAULT: 'hsl(var(--popover))',
```

```
    foreground: 'hsl(var(--popover-foreground))'
  },
  primary: {
    DEFAULT: 'hsl(var(--primary))',
    foreground: 'hsl(var(--primary-foreground))'
  },
  secondary: {
    DEFAULT: 'hsl(var(--secondary))',
    foreground: 'hsl(var(--secondary-foreground))'
  },
  muted: {
    DEFAULT: 'hsl(var(--muted))',
    foreground: 'hsl(var(--muted-foreground))'
  },
  accent: {
    DEFAULT: 'hsl(var(--accent))',
    foreground: 'hsl(var(--accent-foreground))'
  },
  destructive: {
    DEFAULT: 'hsl(var(--destructive))',
    foreground: 'hsl(var(--destructive-foreground))'
  },
  border: 'hsl(var(--border))',
  input: 'hsl(var(--input))',
  ring: 'hsl(var(--ring))',
  chart: {
    '1': 'hsl(var(--chart-1))',
    '2': 'hsl(var(--chart-2))',
    '3': 'hsl(var(--chart-3))',
    '4': 'hsl(var(--chart-4))',
    '5': 'hsl(var(--chart-5))'
  },
  sidebar: {
    DEFAULT: 'hsl(var(--sidebar-background))',
    foreground: 'hsl(var(--sidebar-foreground))',
    primary: 'hsl(var(--sidebar-primary))',
    'primary-foreground': 'hsl(var(--sidebar-primary-foreground))',
    accent: 'hsl(var(--sidebar-accent))',
    'accent-foreground': 'hsl(var(--sidebar-accent-foreground))',
    border: 'hsl(var(--sidebar-border))',
    ring: 'hsl(var(--sidebar-ring))'
  }
}
```

```

    },
    fontFamily: {
      heading: ['var(--font-heading)'],
      body: ['var(--font-body)'],
      display: ['var(--font-display)'],
      mono: ['var(--font-mono)']
    },
    keyframes: {
      'accordion-down': {
        from: {
          height: '0'
        },
        to: {
          height: 'var(--radix-accordion-content-height)'
        }
      },
      'accordion-up': {
        from: {
          height: 'var(--radix-accordion-content-height)'
        },
        to: {
          height: '0'
        }
      }
    },
    animation: {
      'accordion-down': 'accordion-down 0.2s ease-out',
      'accordion-up': 'accordion-up 0.2s ease-out'
    }
  },
  plugins: [require("tailwindcss-animate")],
}

```

vite.config.js

```
import base44 from "@base44/vite-plugin"
import react from '@vitejs/plugin-react'
import { defineConfig } from 'vite'

// https://vite.dev/config/
export default defineConfig({
  plugins: [
    base44({
      // Support for legacy code that imports the base44 SDK with
      // @/integrations, @/entities, etc.
      // can be removed if the code has been updated to use the new SDK
      imports from @base44/sdk
      legacySDKImports: process.env.BASE44_LEGACY_SDK_IMPORTS === 'true',
      hmrNotifier: true,
      navigationNotifier: true,
      analyticsTracker: true,
      visualEditAgent: true
    }),
    react(),
  ]
});
```