

arcade

0.1.0

Generated by Doxygen 1.9.1

1 Namespace Index	1
1.1 Namespace List	1
2 Hierarchical Index	3
2.1 Class Hierarchy	3
3 Class Index	5
3.1 Class List	5
4 File Index	7
4.1 File List	7
5 Namespace Documentation	9
5.1 Arcade Namespace Reference	9
5.1.1 Detailed Description	10
5.1.2 Enumeration Type Documentation	10
5.1.2.1 KeyboardEvents	10
6 Class Documentation	11
6.1 Arcade::Core Class Reference	11
6.1.1 Detailed Description	12
6.1.2 Member Function Documentation	12
6.1.2.1 getNextLibIndex()	12
6.1.2.2 getPreviousLibIndex()	13
6.1.2.3 getRenderer()	13
6.1.2.4 handleEvents()	13
6.1.2.5 mainLoop()	13
6.1.2.6 runArcade()	14
6.1.2.7 setMode()	14
6.1.2.8 switchLib()	14
6.2 Arcade::Core::CoreException Class Reference	15
6.2.1 Detailed Description	15
6.3 Arcade::IGame Class Reference	15
6.3.1 Detailed Description	16
6.4 Arcade::IRenderer Class Reference	16
6.4.1 Detailed Description	17
6.4.2 Member Function Documentation	17
6.4.2.1 createSprite()	17
6.4.2.2 createText()	17
6.4.2.3 displaySprite()	18
6.4.2.4 displayText()	18
6.4.2.5 getEvent()	18
6.4.2.6 getWindow()	19
6.4.2.7 isASCII()	19

6.4.2.8 loadFont()	19
6.4.2.9 loadTexture()	20
6.5 Arcade::ISprite Class Reference	20
6.5.1 Detailed Description	20
6.5.2 Member Function Documentation	20
6.5.2.1 createSprite()	20
6.5.2.2 setPosition()	21
6.6 Arcade::IWindow Class Reference	21
6.6.1 Detailed Description	22
6.6.2 Member Function Documentation	22
6.6.2.1 openWindow()	22
6.6.2.2 setTitle()	22
6.7 Arcade::NCursesRenderer Class Reference	22
6.7.1 Detailed Description	23
6.7.2 Member Function Documentation	23
6.7.2.1 createSprite()	24
6.7.2.2 createText()	25
6.7.2.3 displaySprite()	25
6.7.2.4 displayText()	26
6.7.2.5 getEvent()	26
6.7.2.6 getWindow()	26
6.7.2.7 isASCII()	26
6.7.2.8 loadFont()	27
6.7.2.9 loadTexture()	28
6.8 Arcade::NCursesWindow Class Reference	28
6.8.1 Detailed Description	29
6.8.2 Member Function Documentation	29
6.8.2.1 getWindow()	29
6.8.2.2 openWindow()	29
6.8.2.3 setTitle()	30
6.9 Arcade::RuntimeException Class Reference	30
6.9.1 Detailed Description	30
6.10 Arcade::Sdl2Renderer Class Reference	31
6.10.1 Detailed Description	31
6.10.2 Member Function Documentation	31
6.10.2.1 createSprite()	32
6.10.2.2 createText()	32
6.10.2.3 displaySprite()	32
6.10.2.4 displayText()	33
6.10.2.5 getEvent()	33
6.10.2.6 getWindow()	33
6.10.2.7 isASCII()	34

6.10.2.8 loadFont()	34
6.10.2.9 loadTexture()	34
6.11 Arcade::Sdl2Window Class Reference	35
6.11.1 Detailed Description	35
6.11.2 Member Function Documentation	36
6.11.2.1 getHeight()	36
6.11.2.2 getRenderer()	36
6.11.2.3 getWidth()	36
6.11.2.4 getWindow()	36
6.11.2.5 openWindow()	36
6.11.2.6 setTitle()	37
6.12 Arcade::SfmlRenderer Class Reference	37
6.12.1 Detailed Description	38
6.12.2 Member Function Documentation	38
6.12.2.1 createSprite()	38
6.12.2.2 createText()	39
6.12.2.3 displaySprite()	39
6.12.2.4 displayText()	39
6.12.2.5 getEvent()	40
6.12.2.6 getWindow()	40
6.12.2.7 isASCII()	40
6.12.2.8 loadFont()	40
6.12.2.9 loadTexture()	41
6.13 Arcade::SfmlWindow Class Reference	41
6.13.1 Detailed Description	42
6.13.2 Member Function Documentation	42
6.13.2.1 getWindow()	42
6.13.2.2 openWindow()	42
6.13.2.3 setTitle()	43
7 File Documentation	45
7.1 Core/include/Arcade/abstractions/IGame.hpp File Reference	45
7.1.1 Detailed Description	45
7.2 Core/include/Arcade/abstractions/IRenderer.hpp File Reference	45
7.2.1 Detailed Description	46
7.3 Core/include/Arcade/abstractions/ISprite.hpp File Reference	46
7.3.1 Detailed Description	46
7.4 Core/include/Arcade/abstractions/IWindow.hpp File Reference	46
7.4.1 Detailed Description	47
7.5 Core/include/Arcade/Constants.hpp File Reference	47
7.5.1 Detailed Description	47
7.6 Core/include/Arcade/Core.hpp File Reference	47

7.6.1 Detailed Description	48
7.7 Core/include/Arcade/Enum.hpp File Reference	48
7.7.1 Detailed Description	48
7.8 Core/include/Arcade/RuntimeException.hpp File Reference	49
7.8.1 Detailed Description	49
7.9 Graphics/NCurses/include/Arcade/NCursesRenderer.hpp File Reference	49
7.9.1 Detailed Description	49
7.10 Graphics/NCurses/include/Arcade/NCursesWindow.hpp File Reference	50
7.10.1 Detailed Description	50
7.11 Graphics/SDL2/include/Arcade/Sdl2Renderer.hpp File Reference	50
7.11.1 Detailed Description	51
7.12 Graphics/SDL2/include/Arcade/Sdl2Window.hpp File Reference	51
7.12.1 Detailed Description	51
7.13 Graphics/SFML/include/Arcade/SfmlRenderer.hpp File Reference	51
7.13.1 Detailed Description	52
7.14 Graphics/SFML/include/Arcade/SfmlWindow.hpp File Reference	52
7.14.1 Detailed Description	52
Index	53

Chapter 1

Namespace Index

1.1 Namespace List

Here is a list of all documented namespaces with brief descriptions:

Arcade	Main namespace for the Arcade project	9
------------------------	---	---

Chapter 2

Hierarchical Index

2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

Arcade::Core	11
std::exception	
Arcade::Core::CoreException	15
Arcade::RuntimeException	30
Arcade::IGame	15
Arcade::IRenderer	16
Arcade::NCursesRenderer	22
Arcade::Sdl2Renderer	31
Arcade::SfmlRenderer	37
Arcade::ISprite	20
Arcade::IWindow	21
Arcade::NCursesWindow	28
Arcade::Sdl2Window	35
Arcade::SfmlWindow	41

Chapter 3

Class Index

3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

Arcade::Core	
Core class	11
Arcade::Core::CoreException	
CoreException class	15
Arcade::IGame	
Game Interface	15
Arcade::IRenderer	
Graphic Interface	16
Arcade::ISprite	
Sprite Interface	20
Arcade::IWindow	
Window Interface	21
Arcade::NCursesRenderer	
NCursesRenderer class	22
Arcade::NCursesWindow	
NCursesWindow class	28
Arcade::RuntimeException	
RuntimeException class	30
Arcade::Sdl2Renderer	
Sdl2Renderer class	31
Arcade::Sdl2Window	
Sdl2Window class	35
Arcade::SfmlRenderer	
SfmlRenderer class	37
Arcade::SfmlWindow	
SfmlWindow class	41

Chapter 4

File Index

4.1 File List

Here is a list of all documented files with brief descriptions:

Core/include/Arcade/ Constants.hpp	47
File containing constant values used in the Arcade project	
Core/include/Arcade/ Core.hpp	47
File declaring Core	
Core/include/Arcade/ Enum.hpp	48
File declaring Enum	
Core/include/Arcade/ RuntimeException.hpp	49
File declaring RuntimeException	
Core/include/Arcade/abstractions/ IGame.hpp	45
File declaring Game Interface	
Core/include/Arcade/abstractions/ IRenderer.hpp	45
File declaring Graphic Interface	
Core/include/Arcade/abstractions/ ISprite.hpp	46
File declaring Sprite Interface	
Core/include/Arcade/abstractions/ IWindow.hpp	46
File declaring Window Interface	
Graphics/NCurses/include/Arcade/ NCursesRenderer.hpp	49
File declaring NCursesRenderer	
Graphics/NCurses/include/Arcade/ NCursesWindow.hpp	50
File declaring NCursesWindow	
Graphics/SDL2/include/Arcade/ Sdl2Renderer.hpp	50
File declaring Sdl2Renderer class	
Graphics/SDL2/include/Arcade/ Sdl2Window.hpp	51
File declaring Sdl2Window class	
Graphics/SFML/include/Arcade/ SfmlRenderer.hpp	51
File declaring SfmlRenderer class	
Graphics/SFML/include/Arcade/ SfmlWindow.hpp	52
File declaring SfmlWindow class	

Chapter 5

Namespace Documentation

5.1 Arcade Namespace Reference

Main namespace for the [Arcade](#) project.

Classes

- class [IGame](#)
Game Interface.
- class [IRenderer](#)
Graphic Interface.
- class [ISprite](#)
Sprite Interface.
- class [IWindow](#)
Window Interface.
- class [Core](#)
Core class.
- class [RuntimeException](#)
RuntimeException class.
- class [Sdl2Renderer](#)
Sdl2Renderer class.
- class [Sdl2Window](#)
Sdl2Window class.
- class [NCursesRenderer](#)
NCursesRenderer class.
- class [NCursesWindow](#)
NCursesWindow class.
- class [SfmlRenderer](#)
SfmlRenderer class.
- class [SfmlWindow](#)
SfmlWindow class.

Enumerations

- enum class **CoreMode** { **GAME** , **MENU** , **PAUSE** , **QUIT** }
- enum class **GameMode** {
 GAME , **GAME_OVER** , **MENU** , **PAUSE** ,
 QUIT }
- enum class **KeyboardEvents** {
 UP , **DOWN** , **LEFT** , **RIGHT** ,
 CLICK , **ESC** , **F1** , **ENTER** ,
 NONE }

Enum for the KeyboardEvents.

5.1.1 Detailed Description

Main namespace for the [Arcade](#) project.

5.1.2 Enumeration Type Documentation

5.1.2.1 KeyboardEvents

```
enum Arcade::KeyboardEvents [strong]
```

Enum for the KeyboardEvents.

Set of enum used for the game event

Chapter 6

Class Documentation

6.1 Arcade::Core Class Reference

[Core](#) class.

```
#include <Arcade/Core.hpp>
```

Classes

- class [CoreException](#)
CoreException class.

Public Member Functions

- **Core** (const [Core](#) &)=delete
- **Core** & **operator=** (const [Core](#) &)=delete
- **Core** (const [Core](#) &&)=delete
- **Core** & **operator=** (const [Core](#) &&)=delete
- int [runArcade](#) (const std::string &path)
Run Arcade.
- void [getLibraries](#) (const std::string &libPath)
Get actives libraries.
- void [switchGraphicLibrary](#) ()
Switch Graphic library.
- template<typename T >
void [switchLib](#) (const std::string &libPath)
Switch library.
- void [mainLoop](#) ()
Game loop.
- void [handleEvents](#) (const [KeyboardEvents](#) &event)
Handle events.
- void [setMode](#) (const CoreMode &gameMode)
Set the game mode.
- void [loadMenu](#) ()
load Menu

- void `displayMenu` ()
display menu
- `IRenderer` * `getRenderer` ()
Get the renderer.
- void `moveCursorDown` ()
- void `moveCursorUp` ()
- void `launchGame` ()
- void `setGameIndex` (size_t index)

Static Public Member Functions

- static size_t `getNextLibIndex` (std::vector< std::string > &libs, size_t currentIndex)
Get next library index.
- static size_t `getPreviousLibIndex` (std::vector< std::string > &libs, size_t currentIndex)
Get previous library index.

6.1.1 Detailed Description

`Core` class.

`Core` class for the `Arcade` project

6.1.2 Member Function Documentation

6.1.2.1 getNextLibIndex()

```
static size_t Arcade::Core::getNextLibIndex (
    std::vector< std::string > & libs,
    size_t currentIndex ) [static]
```

Get next library index.

Parameters

<i>libs</i>	
<i>currentIndex</i>	

Returns

size_t

6.1.2.2 getPreviousLibIndex()

```
static size_t Arcade::Core::getPreviousLibIndex (
    std::vector< std::string > & libs,
    size_t currentIndex ) [static]
```

Get previous library index.

Parameters

<i>libs</i>	
<i>currentIndex</i>	

Returns

size_t

6.1.2.3 getRenderer()

```
IRenderer* Arcade::Core::getRenderer ( ) [inline]
```

Get the renderer.

Returns

The renderer

6.1.2.4 handleEvents()

```
void Arcade::Core::handleEvents (
    const KeyboardEvents & event )
```

Handle events.

Parameters

<i>event</i>	
--------------	--

6.1.2.5 mainLoop()

```
void Arcade::Core::mainLoop ( )
```

Game loop.

Main game loop

6.1.2.6 runArcade()

```
int Arcade::Core::runArcade (
    const std::string & path )
```

Run [Arcade](#).

Parameters

<i>path</i>	
-------------	--

Returns

int

6.1.2.7 setMode()

```
void Arcade::Core::setMode (
    const CoreMode & gameMode ) [inline]
```

Set the game mode.

Parameters

<i>gameMode</i>	
-----------------	--

6.1.2.8 switchLib()

```
template<typename T >
void Arcade::Core::switchLib (
    const std::string & libPath )
```

Switch library.

Template Parameters

<i>T</i>	
----------	--

Parameters

<i>libPath</i>	
----------------	--

The documentation for this class was generated from the following file:


- Core/include/Arcade/[Core.hpp](#)

6.2 Arcade::Core::CoreException Class Reference

[CoreException](#) class.

```
#include <Arcade/Core.hpp>
```

Inheritance diagram for Arcade::Core::CoreException:



Public Member Functions

- **CoreException** (std::string msg)
- **CoreException** (const [CoreException](#) &)=delete
- [CoreException](#) & **operator=** (const [CoreException](#) &)=delete
- **CoreException** (const [CoreException](#) &&)=delete
- [CoreException](#) & **operator=** (const [CoreException](#) &&)=delete
- const char * **what** () const noexcept override

6.2.1 Detailed Description

[CoreException](#) class.

Exception class for the [Core](#) class

The documentation for this class was generated from the following file:

- Core/include/Arcade/[Core.hpp](#)

6.3 Arcade::IGame Class Reference

Game Interface.

```
#include <Arcade/abstractions/IGame.hpp>
```

Public Member Functions

- virtual void [start](#) ()=0
start the game
- virtual void [stop](#) ()=0
stop the game

6.3.1 Detailed Description

Game Interface.

Set of method to implement for the business logic of the [Arcade](#) project

The documentation for this class was generated from the following file:


- Core/include/Arcade/abstractions/[IGame.hpp](#)

6.4 Arcade::IRenderer Class Reference

Graphic Interface.

```
#include <Arcade/abstractions/IRenderer.hpp>
```

Inheritance diagram for Arcade::IRenderer:



Public Member Functions

- virtual [IWindow](#) * [getWindow](#) ()=0
Retrieve the window associated with the renderer.
- virtual [KeyboardEvents](#) [getEvent](#) ()=0
Retrieve the current event from the window.
- virtual bool [isASCII](#) ()=0
Check if the renderer supports only ASCII characters.
- virtual bool [loadTexture](#) (const std::string &filepath, const std::string &name)=0
Load a texture from a file.
- virtual bool [loadFont](#) (const std::string &filepath, const std::string &name)=0
Load a font from a file.
- virtual void [createSprite](#) (const std::string &textureName, float pos_x, float pos_y, float scale_x, float scale_y)=0
Create a sprite with the specified parameters.
- virtual void [displaySprite](#) (const std::string &spriteName)=0
Display a sprite with the specified name.
- virtual void [createText](#) (const std::string &fontName, const std::string &text, int size, float pos_x, float pos_y)=0
Create a text object with the specified parameters.
- virtual void [displayText](#) (const std::string &textName)=0
Display a text object with the specified name.
- virtual void [moveText](#) (const std::string &textName, int pos_x, int pos_y)=0
- virtual void [loadSound](#) ()=0
- virtual void [playSound](#) ()=0
- virtual void [stopSound](#) ()=0

6.4.1 Detailed Description

Graphic Interface.

Set of method for the [Arcade](#) project

6.4.2 Member Function Documentation

6.4.2.1 createSprite()

```
virtual void Arcade::IRenderer::createSprite (
    const std::string & textureName,
    float pos_x,
    float pos_y,
    float scale_x,
    float scale_y ) [pure virtual]
```

Create a sprite with the specified parameters.

Parameters

<i>textureName</i>	The name of the texture to use for the sprite
<i>pos_x</i>	The x-coordinate of the sprite's position
<i>pos_y</i>	The y-coordinate of the sprite's position
<i>scale_x</i>	The scale factor for the sprite's width
<i>scale_y</i>	The scale factor for the sprite's height

Implemented in [Arcade::SfmlRenderer](#), [Arcade::Sdl2Renderer](#), and [Arcade::NCursesRenderer](#).

6.4.2.2 createText()

```
virtual void Arcade::IRenderer::createText (
    const std::string & fontName,
    const std::string & text,
    int size,
    float pos_x,
    float pos_y ) [pure virtual]
```

Create a text object with the specified parameters.

Parameters

<i>fontName</i>	The name of the font to use for the text
<i>text</i>	The text to display
<i>size</i>	The size of the text
<i>pos_x</i>	The x-coordinate of the text's position
<i>pos_y</i>	The y-coordinate of the text's position

Implemented in [Arcade::SfmlRenderer](#), [Arcade::Sdl2Renderer](#), and [Arcade::NCursesRenderer](#).

6.4.2.3 displaySprite()

```
virtual void Arcade::IRenderer::displaySprite (
    const std::string & spriteName ) [pure virtual]
```

Display a sprite with the specified name.

Parameters

<i>spriteName</i>	The name of the sprite to display
-------------------	-----------------------------------

Implemented in [Arcade::SfmlRenderer](#), [Arcade::Sdl2Renderer](#), and [Arcade::NCursesRenderer](#).

6.4.2.4 displayText()

```
virtual void Arcade::IRenderer::displayText (
    const std::string & textName ) [pure virtual]
```

Display a text object with the specified name.

Parameters

<i>textName</i>	The name of the text to display
-----------------	---------------------------------

Implemented in [Arcade::SfmlRenderer](#), [Arcade::Sdl2Renderer](#), and [Arcade::NCursesRenderer](#).

6.4.2.5 getEvent()

```
virtual KeyboardEvents Arcade::IRenderer::getEvent ( ) [pure virtual]
```

Retrieve the current event from the window.

Returns

The current event

Implemented in [Arcade::SfmlRenderer](#), [Arcade::Sdl2Renderer](#), and [Arcade::NCursesRenderer](#).

6.4.2.6 getWindow()

```
virtual IWindow* Arcade::IRenderer::getWindow ( ) [pure virtual]
```

Retrieve the window associated with the renderer.

Returns

The window associated with the renderer

Implemented in [Arcade::SfmlRenderer](#), [Arcade::Sdl2Renderer](#), and [Arcade::NCursesRenderer](#).

6.4.2.7 isASCII()

```
virtual bool Arcade::IRenderer::isASCII ( ) [pure virtual]
```

Check if the renderer supports only ASCII characters.

Returns

True if the renderer supports ASCII, false otherwise

Implemented in [Arcade::SfmlRenderer](#), [Arcade::Sdl2Renderer](#), and [Arcade::NCursesRenderer](#).

6.4.2.8 loadFont()

```
virtual bool Arcade::IRenderer::loadFont (
    const std::string & filepath,
    const std::string & name ) [pure virtual]
```

Load a font from a file.

Parameters

<i>filepath</i>	The path to the font file
<i>name</i>	The name to associate with the font

Returns

True if the font was loaded successfully, false otherwise

Implemented in [Arcade::SfmlRenderer](#), [Arcade::Sdl2Renderer](#), and [Arcade::NCursesRenderer](#).

6.4.2.9 loadTexture()

```
virtual bool Arcade::IRenderer::loadTexture (
    const std::string & filepath,
    const std::string & name ) [pure virtual]
```

Load a texture from a file.

Parameters

<i>filepath</i>	The path to the texture file
<i>name</i>	The name to associate with the texture

Returns

True if the texture was loaded successfully, false otherwise

Implemented in [Arcade::SfmlRenderer](#), [Arcade::NCursesRenderer](#), and [Arcade::Sdl2Renderer](#).

The documentation for this class was generated from the following file:

- Core/include/Arcade/abstractions/[IRenderer.hpp](#)

6.5 Arcade::ISprite Class Reference

Sprite Interface.

```
#include <Arcade/abstractions/ISprite.hpp>
```

Public Member Functions

- **ISprite** (const [ISprite](#) &)=delete
- [ISprite](#) & **operator=** (const [ISprite](#) &)=delete
- virtual void [createSprite](#) (const std::vector< std::string > &sprite)=0
create the sprite
- virtual void [draw](#) ()=0
draw the sprite
- virtual void [setPosition](#) (int x, int y)=0
set the position of the sprite

6.5.1 Detailed Description

Sprite Interface.

Set of method to implement for the business logic of the [Arcade](#) project

6.5.2 Member Function Documentation

6.5.2.1 createSprite()

```
virtual void Arcade::ISprite::createSprite (
    const std::vector< std::string > & sprite ) [pure virtual]
```

create the sprite

Parameters

<i>sprite</i>	
---------------	--

create the sprite with the given sprite, can be a filePath, or a ASCII art

6.5.2.2 setPosition()

```
virtual void Arcade::ISprite::setPosition (
    int x,
    int y ) [pure virtual]
```

set the position of the sprite

Parameters

<i>x</i>	
<i>y</i>	

The documentation for this class was generated from the following file:


- Core/include/Arcade/abstractions/[ISprite.hpp](#)

6.6 Arcade::IWindow Class Reference

Window Interface.

```
#include <Arcade/abstractions/IWindow.hpp>
```

Inheritance diagram for Arcade::IWindow:



Public Member Functions

- virtual void [openWindow](#) (unsigned int width, unsigned int height)=0
Create a window with the specified dimensions.
- virtual void [displayWindow](#) ()=0
Display the current window.
- virtual void [clearWindow](#) ()=0
Clear the contents of the current window.
- virtual void [closeWindow](#) ()=0
Close the current window.
- virtual void [setTitle](#) (const std::string &title)=0
Set the title of the window.

6.6.1 Detailed Description

Window Interface.

Set of method to implement for the business logic of the [Arcade](#) project

6.6.2 Member Function Documentation

6.6.2.1 openWindow()

```
virtual void Arcade::IWindow::openWindow (
    unsigned int width,
    unsigned int height ) [pure virtual]
```

Create a window with the specified dimensions.

Parameters

<i>width</i>	The width of the window
<i>height</i>	The height of the window

Implemented in [Arcade::SfmlWindow](#), [Arcade::Sdl2Window](#), and [Arcade::NCursesWindow](#).

6.6.2.2 setTitle()

```
virtual void Arcade::IWindow::setTitle (
    const std::string & title ) [pure virtual]
```

Set the title of the window.

Parameters

<i>title</i>	The new title of the window
--------------	-----------------------------

Implemented in [Arcade::SfmlWindow](#), [Arcade::Sdl2Window](#), and [Arcade::NCursesWindow](#).

The documentation for this class was generated from the following file:


- [Core/include/Arcade/abstractions/IWindow.hpp](#)

6.7 Arcade::NCursesRenderer Class Reference

[NCursesRenderer](#) class.

```
#include <Arcade/NCursesRenderer.hpp>
```

Inheritance diagram for Arcade::NCursesRenderer:



Public Member Functions

- [KeyboardEvents](#) [getEvent](#) () override
Retrieve the current event from the window.
- bool [loadTexture](#) (const std::string &texture, const std::string &name) override
Load a texture from a file.
- void [createSprite](#) (const std::string &textureName, float pos_x, float pos_y, float scale_x, float scale_y) override
Create a sprite with the specified parameters.
- void [displaySprite](#) (const std::string &spriteName) override
Display a sprite with the specified name.
- bool [loadFont](#) (const std::string &filepath, const std::string &name) override
Load a font from a file.
- void [createText](#) (const std::string &fontName, const std::string &text, int size, float pos_x, float pos_y) override
Create a text object with the specified parameters.
- void [displayText](#) (const std::string &textName) override
Display a text object with the specified name.
- void [moveText](#) (const std::string &textName, int pos_x, int pos_y) override
- bool [isASCII](#) () override
Check if the renderer supports only ASCII characters.
- [IWindow](#) * [getWindow](#) () override
Retrieve the window associated with the renderer.
- void [loadSound](#) () override
- void [playSound](#) () override
- void [stopSound](#) () override

6.7.1 Detailed Description

[NCursesRenderer](#) class.

[NCursesRenderer](#) class for the [Arcade](#) project

6.7.2 Member Function Documentation

6.7.2.1 createSprite()

```
void Arcade::NCursesRenderer::createSprite (
    const std::string & textureName,
    float pos_x,
    float pos_y,
    float scale_x,
    float scale_y ) [inline], [override], [virtual]
```

Create a sprite with the specified parameters.

Parameters

<i>textureName</i>	The name of the texture to use for the sprite
<i>pos_x</i>	The x-coordinate of the sprite's position
<i>pos_y</i>	The y-coordinate of the sprite's position
<i>scale_x</i>	The scale factor for the sprite's width
<i>scale_y</i>	The scale factor for the sprite's height

Implements [Arcade::IRenderer](#).

6.7.2.2 createText()

```
void Arcade::NCursesRenderer::createText (
    const std::string & fontName,
    const std::string & text,
    int size,
    float pos_x,
    float pos_y ) [inline], [override], [virtual]
```

Create a text object with the specified parameters.

Parameters

<i>fontName</i>	The name of the font to use for the text
<i>text</i>	The text to display
<i>size</i>	The size of the text
<i>pos_x</i>	The x-coordinate of the text's position
<i>pos_y</i>	The y-coordinate of the text's position

Implements [Arcade::IRenderer](#).

6.7.2.3 displaySprite()

```
void Arcade::NCursesRenderer::displaySprite (
    const std::string & spriteName ) [inline], [override], [virtual]
```

Display a sprite with the specified name.

Parameters

<i>spriteName</i>	The name of the sprite to display
-------------------	-----------------------------------

Implements [Arcade::IRenderer](#).

6.7.2.4 displayText()

```
void Arcade::NCursesRenderer::displayText (
    const std::string & textName ) [inline], [override], [virtual]
```

Display a text object with the specified name.

Parameters

<i>textName</i>	The name of the text to display
-----------------	---------------------------------

Implements [Arcade::IRenderer](#).

6.7.2.5 getEvent()

```
KeyboardEvents Arcade::NCursesRenderer::getEvent ( ) [override], [virtual]
```

Retrieve the current event from the window.

Returns

The current event

Implements [Arcade::IRenderer](#).

6.7.2.6 getWindow()

```
IWindow\* Arcade::NCursesRenderer::getWindow ( ) [inline], [override], [virtual]
```

Retrieve the window associated with the renderer.

Returns

The window associated with the renderer

Implements [Arcade::IRenderer](#).

6.7.2.7 isASCII()

```
bool Arcade::NCursesRenderer::isASCII ( ) [inline], [override], [virtual]
```

Check if the renderer supports only ASCII characters.

Returns

True if the renderer supports ASCII, false otherwise

Implements [Arcade::IRenderer](#).

6.7.2.8 loadFont()

```
bool Arcade::NCursesRenderer::loadFont (
    const std::string & filepath,
    const std::string & name ) [inline], [override], [virtual]
```

Load a font from a file.

Parameters

<i>filepath</i>	The path to the font file
<i>name</i>	The name to associate with the font

Returns

True if the font was loaded successfully, false otherwise

Implements [Arcade::IRenderer](#).

6.7.2.9 loadTexture()

```
bool Arcade::NCursesRenderer::loadTexture (
    const std::string & filepath,
    const std::string & name ) [inline], [override], [virtual]
```

Load a texture from a file.

Parameters

<i>filepath</i>	The path to the texture file
<i>name</i>	The name to associate with the texture

Returns

True if the texture was loaded successfully, false otherwise

Implements [Arcade::IRenderer](#).

The documentation for this class was generated from the following file:


- Graphics/NCurses/include/Arcade/[NCursesRenderer.hpp](#)

6.8 Arcade::NCursesWindow Class Reference

[NCursesWindow](#) class.

```
#include <Arcade/NCursesWindow.hpp>
```

Inheritance diagram for Arcade::NCursesWindow:



Public Member Functions

- void [openWindow](#) (unsigned int width, unsigned int height) override
Create a window with the specified dimensions.
- void [displayWindow](#) () override
Display the current window.
- void [clearWindow](#) () override
Clear the contents of the current window.
- void [closeWindow](#) () override
Close the current window.
- void [setTitle](#) (const std::string &title) override
Set the title of the window.
- WINDOW * [getWindow](#) ()
Get the current window.

6.8.1 Detailed Description

[NCursesWindow](#) class.

[NCursesWindow](#) class for the [Arcade](#) project

6.8.2 Member Function Documentation

6.8.2.1 getWindow()

```
WINDOW* Arcade::NCursesWindow::getWindow ( ) [inline]
```

Get the current window.

Returns

The current window

6.8.2.2 openWindow()

```
void Arcade::NCursesWindow::openWindow (
    unsigned int width,
    unsigned int height ) [override], [virtual]
```

Create a window with the specified dimensions.

Parameters

<i>width</i>	The width of the window
<i>height</i>	The height of the window

Implements [Arcade::IWindow](#).

6.8.2.3 setTitle()

```
void Arcade::NCursesWindow::setTitle (
    const std::string & title ) [inline], [override], [virtual]
```

Set the title of the window.

Parameters

<i>title</i>	The new title of the window
--------------	-----------------------------

Implements [Arcade::IWindow](#).

The documentation for this class was generated from the following file:


- Graphics/NCurses/include/Arcade/[NCursesWindow.hpp](#)

6.9 Arcade::RuntimeException Class Reference

[RuntimeException](#) class.

```
#include <Arcade/RuntimeException.hpp>
```

Inheritance diagram for Arcade::RuntimeException:



Public Member Functions

- **RuntimeException** (std::string msg)
- **RuntimeException** ([RuntimeException](#) const &)=delete
- const char * **what** () const noexcept override

6.9.1 Detailed Description

[RuntimeException](#) class.

[RuntimeException](#) class for the [Arcade](#) project

The documentation for this class was generated from the following file:


- Core/include/Arcade/[RuntimeException.hpp](#)

6.10 Arcade::Sdl2Renderer Class Reference

[Sdl2Renderer](#) class.

```
#include <Arcade/Sdl2Renderer.hpp>
```

Inheritance diagram for Arcade::Sdl2Renderer:



Public Member Functions

- [KeyboardEvents](#) [getEvent](#) () override
Retrieve the current event from the window.
- bool [loadTexture](#) (const std::string &filePath, const std::string &name) override
Load a texture from a file.
- bool [loadFont](#) (const std::string &filepath, const std::string &name) override
Load a font from a file.
- void [createSprite](#) (const std::string &textureName, float pos_x, float pos_y, float scale_x, float scale_y) override
Create a sprite with the specified parameters.
- void [createText](#) (const std::string &fontName, const std::string &text, int size, float pos_x, float pos_y) override
Create a text object with the specified parameters.
- void [displaySprite](#) (const std::string &spriteName) override
Display a sprite with the specified name.
- void [displayText](#) (const std::string &textName) override
Display a text object with the specified name.
- void [moveText](#) (const std::string &textName, int pos_x, int pos_y) override
- bool [isASCII](#) () override
Check if the renderer supports only ASCII characters.
- [IWindow](#) * [getWindow](#) () override
Retrieve the window associated with the renderer.
- void [loadSound](#) () override
- void [playSound](#) () override
- void [stopSound](#) () override

6.10.1 Detailed Description

[Sdl2Renderer](#) class.

[Sdl2Renderer](#) class for the [Arcade](#) project

6.10.2 Member Function Documentation

6.10.2.1 createSprite()

```
void Arcade::Sdl2Renderer::createSprite (
    const std::string & textureName,
    float pos_x,
    float pos_y,
    float scale_x,
    float scale_y ) [override], [virtual]
```

Create a sprite with the specified parameters.

Parameters

<i>textureName</i>	The name of the texture to use for the sprite
<i>pos_x</i>	The x-coordinate of the sprite's position
<i>pos_y</i>	The y-coordinate of the sprite's position
<i>scale_x</i>	The scale factor for the sprite's width
<i>scale_y</i>	The scale factor for the sprite's height

Implements [Arcade::IRenderer](#).

6.10.2.2 createText()

```
void Arcade::Sdl2Renderer::createText (
    const std::string & fontName,
    const std::string & text,
    int size,
    float pos_x,
    float pos_y ) [override], [virtual]
```

Create a text object with the specified parameters.

Parameters

<i>fontName</i>	The name of the font to use for the text
<i>text</i>	The text to display
<i>size</i>	The size of the text
<i>pos_x</i>	The x-coordinate of the text's position
<i>pos_y</i>	The y-coordinate of the text's position

Implements [Arcade::IRenderer](#).

6.10.2.3 displaySprite()

```
void Arcade::Sdl2Renderer::displaySprite (
    const std::string & spriteName ) [override], [virtual]
```

Display a sprite with the specified name.

Parameters

<i>spriteName</i>	The name of the sprite to display
-------------------	-----------------------------------

Implements [Arcade::IRenderer](#).

6.10.2.4 displayText()

```
void Arcade::Sdl2Renderer::displayText (
    const std::string & textName ) [override], [virtual]
```

Display a text object with the specified name.

Parameters

<i>textName</i>	The name of the text to display
-----------------	---------------------------------

Implements [Arcade::IRenderer](#).

6.10.2.5 getEvent()

```
KeyboardEvents Arcade::Sdl2Renderer::getEvent ( ) [override], [virtual]
```

Retrieve the current event from the window.

Returns

The current event

Implements [Arcade::IRenderer](#).

6.10.2.6 getWindow()

```
IWindow\* Arcade::Sdl2Renderer::getWindow ( ) [inline], [override], [virtual]
```

Retrieve the window associated with the renderer.

Returns

The window associated with the renderer

Implements [Arcade::IRenderer](#).

6.10.2.7 isASCII()

```
bool Arcade::Sdl2Renderer::isASCII ( ) [inline], [override], [virtual]
```

Check if the renderer supports only ASCII characters.

Returns

True if the renderer supports ASCII, false otherwise

Implements [Arcade::IRenderer](#).

6.10.2.8 loadFont()

```
bool Arcade::Sdl2Renderer::loadFont (
    const std::string & filepath,
    const std::string & name ) [override], [virtual]
```

Load a font from a file.

Parameters

<i>filepath</i>	The path to the font file
<i>name</i>	The name to associate with the font

Returns

True if the font was loaded successfully, false otherwise

Implements [Arcade::IRenderer](#).

6.10.2.9 loadTexture()

```
bool Arcade::Sdl2Renderer::loadTexture (
    const std::string & filepath,
    const std::string & name ) [override], [virtual]
```

Load a texture from a file.

Parameters

<i>filepath</i>	The path to the texture file
<i>name</i>	The name to associate with the texture

Returns

True if the texture was loaded successfully, false otherwise

Implements [Arcade::IRenderer](#).

The documentation for this class was generated from the following file:


- Graphics/SDL2/include/Arcade/[Sdl2Renderer.hpp](#)

6.11 Arcade::Sdl2Window Class Reference

[Sdl2Window](#) class.

```
#include <Arcade/Sdl2Window.hpp>
```

Inheritance diagram for Arcade::Sdl2Window:



Public Member Functions

- void [openWindow](#) (unsigned int width, unsigned int height) override
Create a window with the specified dimensions.
- void [displayWindow](#) () override
Display the current window.
- void [clearWindow](#) () override
Clear the contents of the current window.
- void [closeWindow](#) () override
Close the current window.
- void [setTitle](#) (const std::string &title) override
Set the title of the window.
- SDL_Window * [getWindow](#) ()
Get the current window.
- SDL_Renderer * [getRenderer](#) ()
Get the current renderer.
- int [getWidth](#) () const
Get the width of the window.
- int [getHeight](#) () const
Get the height of the window.

6.11.1 Detailed Description

[Sdl2Window](#) class.

[Sdl2Window](#) class for the [Arcade](#) project

6.11.2 Member Function Documentation

6.11.2.1 getHeight()

```
int Arcade::Sdl2Window::getHeight ( ) const [inline]
```

Get the height of the window.

Returns

The height of the window

6.11.2.2 getRenderer()

```
SDL_Renderer* Arcade::Sdl2Window::getRenderer ( ) [inline]
```

Get the current renderer.

Returns

The current renderer

6.11.2.3 getWidth()

```
int Arcade::Sdl2Window::getWidth ( ) const [inline]
```

Get the width of the window.

Returns

The width of the window

6.11.2.4 getWindow()

```
SDL_Window* Arcade::Sdl2Window::getWindow ( ) [inline]
```

Get the current window.

Returns

The current window

6.11.2.5 openWindow()

```
void Arcade::Sdl2Window::openWindow (
    unsigned int width,
    unsigned int height ) [override], [virtual]
```

Create a window with the specified dimensions.

Parameters

<i>width</i>	The width of the window
<i>height</i>	The height of the window

Implements [Arcade::IWindow](#).

6.11.2.6 setTitle()

```
void Arcade::Sdl2Window::setTitle (
    const std::string & title ) [inline], [override], [virtual]
```

Set the title of the window.

Parameters

<i>title</i>	The new title of the window
--------------	-----------------------------

Implements [Arcade::IWindow](#).

The documentation for this class was generated from the following file:


- Graphics/SDL2/include/Arcade/[Sdl2Window.hpp](#)

6.12 Arcade::SfmlRenderer Class Reference

[SfmlRenderer](#) class.

```
#include <Arcade/SfmlRenderer.hpp>
```

Inheritance diagram for Arcade::SfmlRenderer:



Public Member Functions

- [KeyboardEvents](#) [getEvent](#) () override
Retrieve the current event from the window.
- bool [loadTexture](#) (const std::string &texture, const std::string &name) override
Load a texture from a file.
- bool [loadFont](#) (const std::string &filepath, const std::string &name) override

Load a font from a file.

- void [createSprite](#) (const std::string &textureName, float pos_x, float pos_y, float scale_x, float scale_y) override

Create a sprite with the specified parameters.

- void [createText](#) (const std::string &fontName, const std::string &text, int size, float pos_x, float pos_y) override

Create a text object with the specified parameters.

- void [displaySprite](#) (const std::string &spriteName) override

Display a sprite with the specified name.

- void [displayText](#) (const std::string &textName) override

Display a text object with the specified name.

- void **moveText** (const std::string &textName, int pos_x, int pos_y) override
- bool **isASCII** () override

Check if the renderer supports only ASCII characters.

- [IWindow](#) * [getWindow](#) () override

Retrieve the window associated with the renderer.

- void **loadSound** () override
- void **playSound** () override
- void **stopSound** () override

6.12.1 Detailed Description

[SfmlRenderer](#) class.

[SfmlRenderer](#) class for the [Arcade](#) project

6.12.2 Member Function Documentation

6.12.2.1 createSprite()

```
void Arcade::SfmlRenderer::createSprite (
    const std::string & textureName,
    float pos_x,
    float pos_y,
    float scale_x,
    float scale_y ) [override], [virtual]
```

Create a sprite with the specified parameters.

Parameters

<i>textureName</i>	The name of the texture to use for the sprite
<i>pos_x</i>	The x-coordinate of the sprite's position
<i>pos_y</i>	The y-coordinate of the sprite's position
<i>scale_x</i>	The scale factor for the sprite's width
<i>scale_y</i>	The scale factor for the sprite's height

Implements [Arcade::IRenderer](#).

6.12.2.2 createText()

```
void Arcade::SfmlRenderer::createText (
    const std::string & fontName,
    const std::string & text,
    int size,
    float pos_x,
    float pos_y ) [override], [virtual]
```

Create a text object with the specified parameters.

Parameters

<i>fontName</i>	The name of the font to use for the text
<i>text</i>	The text to display
<i>size</i>	The size of the text
<i>pos_x</i>	The x-coordinate of the text's position
<i>pos_y</i>	The y-coordinate of the text's position

Implements [Arcade::IRenderer](#).

6.12.2.3 displaySprite()

```
void Arcade::SfmlRenderer::displaySprite (
    const std::string & spriteName ) [override], [virtual]
```

Display a sprite with the specified name.

Parameters

<i>spriteName</i>	The name of the sprite to display
-------------------	-----------------------------------

Implements [Arcade::IRenderer](#).

6.12.2.4 displayText()

```
void Arcade::SfmlRenderer::displayText (
    const std::string & textName ) [override], [virtual]
```

Display a text object with the specified name.

Parameters

<i>textName</i>	The name of the text to display
-----------------	---------------------------------

Implements [Arcade::IRenderer](#).

6.12.2.5 `getEvent()`

```
KeyboardEvents Arcade::SfmlRenderer::getEvent ( ) [override], [virtual]
```

Retrieve the current event from the window.

Returns

The current event

Implements [Arcade::IRenderer](#).

6.12.2.6 `getWindow()`

```
IWindow* Arcade::SfmlRenderer::getWindow ( ) [inline], [override], [virtual]
```

Retrieve the window associated with the renderer.

Returns

The window associated with the renderer

Implements [Arcade::IRenderer](#).

6.12.2.7 `isASCII()`

```
bool Arcade::SfmlRenderer::isASCII ( ) [inline], [override], [virtual]
```

Check if the renderer supports only ASCII characters.

Returns

True if the renderer supports ASCII, false otherwise

Implements [Arcade::IRenderer](#).

6.12.2.8 `loadFont()`

```
bool Arcade::SfmlRenderer::loadFont (
    const std::string & filepath,
    const std::string & name ) [override], [virtual]
```

Load a font from a file.

Parameters

<i>filepath</i>	The path to the font file
<i>name</i>	The name to associate with the font

Returns

True if the font was loaded successfully, false otherwise

Implements [Arcade::IRenderer](#).

6.12.2.9 loadTexture()

```
bool Arcade::SfmlRenderer::loadTexture (
    const std::string & filepath,
    const std::string & name ) [override], [virtual]
```

Load a texture from a file.

Parameters

<i>filepath</i>	The path to the texture file
<i>name</i>	The name to associate with the texture

Returns

True if the texture was loaded successfully, false otherwise

Implements [Arcade::IRenderer](#).

The documentation for this class was generated from the following file:


- Graphics/SFML/include/Arcade/[SfmlRenderer.hpp](#)

6.13 Arcade::SfmlWindow Class Reference

[SfmlWindow](#) class.

```
#include <Arcade/SfmlWindow.hpp>
```

Inheritance diagram for Arcade::SfmlWindow:



Public Member Functions

- void [openWindow](#) (unsigned int width, unsigned int height) override
Create a window with the specified dimensions.
- void [displayWindow](#) () override
Display the current window.
- void [clearWindow](#) () override
Clear the contents of the current window.
- void [closeWindow](#) () override
Close the current window.
- void [setTitle](#) (const std::string &title) override
Set the title of the window.
- sf::RenderWindow * [getWindow](#) ()
Get the current window.

6.13.1 Detailed Description

[SfmlWindow](#) class.

[SfmlWindow](#) class for the [Arcade](#) project

6.13.2 Member Function Documentation

6.13.2.1 getWindow()

```
sf::RenderWindow* Arcade::SfmlWindow::getWindow ( ) [inline]
```

Get the current window.

Returns

The current window

6.13.2.2 openWindow()

```
void Arcade::SfmlWindow::openWindow (
    unsigned int width,
    unsigned int height ) [override], [virtual]
```

Create a window with the specified dimensions.

Parameters

<i>width</i>	The width of the window
<i>height</i>	The height of the window

Implements [Arcade::IWindow](#).

6.13.2.3 setTitle()

```
void Arcade::SfmlWindow::setTitle (
    const std::string & title ) [inline], [override], [virtual]
```

Set the title of the window.

Parameters

<i>title</i>	The new title of the window
--------------	-----------------------------

Implements [Arcade::IWindow](#).

The documentation for this class was generated from the following file:

- Graphics/SFML/include/Arcade/[SfmlWindow.hpp](#)

Chapter 7

File Documentation

7.1 Core/include/Arcade/abstractions/IGame.hpp File Reference

File declaring Game Interface.

Classes

- class [Arcade::IGame](#)
Game Interface.

Namespaces

- [Arcade](#)
Main namespace for the [Arcade](#) project.

7.1.1 Detailed Description

File declaring Game Interface.

7.2 Core/include/Arcade/abstractions/IRenderer.hpp File Reference

File declaring Graphic Interface.

```
#include "Arcade/Enum.hpp"  
#include "Arcade/abstractions/IWindow.hpp"
```

Classes

- class [Arcade::IRenderer](#)
Graphic Interface.

Namespaces

- [Arcade](#)

Main namespace for the [Arcade](#) project.

7.2.1 Detailed Description

File declaring Graphic Interface.

7.3 Core/include/Arcade/abstractions/ISprite.hpp File Reference

File declaring Sprite Interface.

```
#include <iostream>
#include <vector>
```

Classes

- class [Arcade::ISprite](#)

Sprite Interface.

Namespaces

- [Arcade](#)

Main namespace for the [Arcade](#) project.

7.3.1 Detailed Description

File declaring Sprite Interface.

7.4 Core/include/Arcade/abstractions/IWindow.hpp File Reference

File declaring Window Interface.

```
#include <iostream>
```

Classes

- class [Arcade::IWindow](#)

Window Interface.

Namespaces

- [Arcade](#)

Main namespace for the [Arcade](#) project.

7.4.1 Detailed Description

File declaring Window Interface.

7.5 Core/include/Arcade/Constants.hpp File Reference

File containing constant values used in the [Arcade](#) project.

Variables

- constexpr int [EPITECH_ERROR](#) = 84
Exit code for Epitech errors.
- constexpr int [SUCCESS](#) = 0
Exit code indicating that the program has executed successfully.
- constexpr int [ERROR](#) = -1
Exit code indicating that an error has occurred.
- constexpr int [WIDTH](#) = 1920
Width of the window.
- constexpr int [HEIGHT](#) = 1080
Height of the window.
- constexpr char const * [LIB_PATH](#) = "./lib/"

7.5.1 Detailed Description

File containing constant values used in the [Arcade](#) project.

This file provides a set of constant values that are used throughout the [Arcade](#) project.

7.6 Core/include/Arcade/Core.hpp File Reference

File declaring Core.

```
#include <memory>
#include <vector>
#include "Arcade/Enum.hpp"
#include "Arcade/abstractions/IRenderer.hpp"
#include "Arcade/abstractions/IWindow.hpp"
#include "Arcade/abstractions/IGame.hpp"
```

Classes

- class [Arcade::Core](#)
Core class.
- class [Arcade::Core::CoreException](#)
CoreException class.

Namespaces

- [Arcade](#)
Main namespace for the [Arcade](#) project.

7.6.1 Detailed Description

File declaring Core.

7.7 Core/include/Arcade/Enum.hpp File Reference

File declaring Enum.

Namespaces

- [Arcade](#)
Main namespace for the [Arcade](#) project.

Enumerations

- enum class **CoreMode** { **GAME** , **MENU** , **PAUSE** , **QUIT** }
- enum class **GameMode** {
GAME , **GAME_OVER** , **MENU** , **PAUSE** ,
QUIT }
- enum class [Arcade::KeyboardEvents](#) {
UP , **DOWN** , **LEFT** , **RIGHT** ,
CLICK , **ESC** , **F1** , **ENTER** ,
NONE }
Enum for the KeyboardEvents.

7.7.1 Detailed Description

File declaring Enum.

Set of enum used in the [Arcade](#) project

7.8 Core/include/Arcade/RuntimeException.hpp File Reference

File declaring RuntimeException.

```
#include <iostream>
#include <exception>
```

Classes

- class [Arcade::RuntimeException](#)
RuntimeException class.

Namespaces

- [Arcade](#)
Main namespace for the [Arcade](#) project.

7.8.1 Detailed Description

File declaring RuntimeException.

7.9 Graphics/NCurses/include/Arcade/NCursesRenderer.hpp File Reference

File declaring NCursesRenderer.

```
#include <ncurses.h>
#include "Arcade/abstractions/IRenderer.hpp"
#include "Arcade/NCursesWindow.hpp"
```

Classes

- class [Arcade::NCursesRenderer](#)
NCursesRenderer class.

Namespaces

- [Arcade](#)
Main namespace for the [Arcade](#) project.

7.9.1 Detailed Description

File declaring NCursesRenderer.

7.10 Graphics/NCurses/include/Arcade/NCursesWindow.hpp File Reference

File declaring NCursesWindow.

```
#include <ncurses.h>
#include "Arcade/abstractions/IWindow.hpp"
```

Classes

- class [Arcade::NCursesWindow](#)
NCursesWindow class.

Namespaces

- [Arcade](#)
Main namespace for the [Arcade](#) project.

7.10.1 Detailed Description

File declaring NCursesWindow.

7.11 Graphics/SDL2/include/Arcade/Sdl2Renderer.hpp File Reference

File declaring Sdl2Renderer class.

```
#include <map>
#include <SDL2/SDL.h>
#include <SDL2/SDL_ttf.h>
#include <SDL2/SDL_image.h>
#include "Arcade/abstractions/IRenderer.hpp"
#include "Arcade/Sdl2Window.hpp"
```

Classes

- class [Arcade::Sdl2Renderer](#)
Sdl2Renderer class.

Namespaces

- [Arcade](#)
Main namespace for the [Arcade](#) project.

7.11.1 Detailed Description

File declaring Sdl2Renderer class.

7.12 Graphics/SDL2/include/Arcade/Sdl2Window.hpp File Reference

File declaring Sdl2Window class.

```
#include <SDL2/SDL.h>
#include <SDL2/SDL_ttf.h>
#include <SDL2/SDL_image.h>
#include "Arcade/abstractions/IWindow.hpp"
```

Classes

- class [Arcade::Sdl2Window](#)
Sdl2Window class.

Namespaces

- [Arcade](#)
Main namespace for the [Arcade](#) project.

7.12.1 Detailed Description

File declaring Sdl2Window class.

7.13 Graphics/SFML/include/Arcade/SfmlRenderer.hpp File Reference

File declaring SfmlRenderer class.

```
#include <SFML/Graphics.hpp>
#include <SFML/Audio.hpp>
#include "Arcade/abstractions/IRenderer.hpp"
#include "Arcade/abstractions/IWindow.hpp"
#include "Arcade/SfmlWindow.hpp"
```

Classes

- class [Arcade::SfmlRenderer](#)
SfmlRenderer class.

Namespaces

- [Arcade](#)

Main namespace for the [Arcade](#) project.

7.13.1 Detailed Description

File declaring SfmlRenderer class.

7.14 Graphics/SFML/include/Arcade/SfmlWindow.hpp File Reference

File declaring SfmlWindow class.

```
#include <SFML/Graphics.hpp>
#include "Arcade/abstractions/IRenderer.hpp"
#include "Arcade/abstractions/IWindow.hpp"
```

Classes

- class [Arcade::SfmlWindow](#)

[SfmlWindow](#) class.

Namespaces

- [Arcade](#)

Main namespace for the [Arcade](#) project.

7.14.1 Detailed Description

File declaring SfmlWindow class.

Index

- Arcade, [9](#)
 - KeyboardEvents, [10](#)
- Arcade::Core, [11](#)
 - getNextLibIndex, [12](#)
 - getPreviousLibIndex, [12](#)
 - getRenderer, [13](#)
 - handleEvents, [13](#)
 - mainLoop, [13](#)
 - runArcade, [13](#)
 - setMode, [14](#)
 - switchLib, [14](#)
- Arcade::Core::CoreException, [15](#)
- Arcade::IGame, [15](#)
- Arcade::IRenderer, [16](#)
 - createSprite, [17](#)
 - createText, [17](#)
 - displaySprite, [18](#)
 - displayText, [18](#)
 - getEvent, [18](#)
 - getWindow, [18](#)
 - isASCII, [19](#)
 - loadFont, [19](#)
 - loadTexture, [19](#)
- Arcade::ISprite, [20](#)
 - createSprite, [20](#)
 - setPosition, [21](#)
- Arcade::IWindow, [21](#)
 - openWindow, [22](#)
 - setTitle, [22](#)
- Arcade::NCursesRenderer, [22](#)
 - createSprite, [23](#)
 - createText, [25](#)
 - displaySprite, [25](#)
 - displayText, [25](#)
 - getEvent, [26](#)
 - getWindow, [26](#)
 - isASCII, [26](#)
 - loadFont, [26](#)
 - loadTexture, [28](#)
- Arcade::NCursesWindow, [28](#)
 - getWindow, [29](#)
 - openWindow, [29](#)
 - setTitle, [30](#)
- Arcade::RuntimeException, [30](#)
- Arcade::Sdl2Renderer, [31](#)
 - createSprite, [31](#)
 - createText, [32](#)
 - displaySprite, [32](#)
 - displayText, [33](#)
- getEvent, [33](#)
- getWindow, [33](#)
- isASCII, [33](#)
- loadFont, [34](#)
- loadTexture, [34](#)
- Arcade::Sdl2Window, [35](#)
 - getHeight, [36](#)
 - getRenderer, [36](#)
 - getWidth, [36](#)
 - getWindow, [36](#)
 - openWindow, [36](#)
 - setTitle, [37](#)
- Arcade::SfmlRenderer, [37](#)
 - createSprite, [38](#)
 - createText, [39](#)
 - displaySprite, [39](#)
 - displayText, [39](#)
 - getEvent, [40](#)
 - getWindow, [40](#)
 - isASCII, [40](#)
 - loadFont, [40](#)
 - loadTexture, [41](#)
- Arcade::SfmlWindow, [41](#)
 - getWindow, [42](#)
 - openWindow, [42](#)
 - setTitle, [43](#)
- Core/include/Arcade/abstractions/IGame.hpp, [45](#)
- Core/include/Arcade/abstractions/IRenderer.hpp, [45](#)
- Core/include/Arcade/abstractions/ISprite.hpp, [46](#)
- Core/include/Arcade/abstractions/IWindow.hpp, [46](#)
- Core/include/Arcade/Constants.hpp, [47](#)
- Core/include/Arcade/Core.hpp, [47](#)
- Core/include/Arcade/Enum.hpp, [48](#)
- Core/include/Arcade/RuntimeException.hpp, [49](#)
- createSprite
 - Arcade::IRenderer, [17](#)
 - Arcade::ISprite, [20](#)
 - Arcade::NCursesRenderer, [23](#)
 - Arcade::Sdl2Renderer, [31](#)
 - Arcade::SfmlRenderer, [38](#)
- createText
 - Arcade::IRenderer, [17](#)
 - Arcade::NCursesRenderer, [25](#)
 - Arcade::Sdl2Renderer, [32](#)
 - Arcade::SfmlRenderer, [39](#)
- displaySprite
 - Arcade::IRenderer, [18](#)
 - Arcade::NCursesRenderer, [25](#)

- Arcade::Sdl2Renderer, [32](#)
 - Arcade::SfmlRenderer, [39](#)
- displayText
 - Arcade::IRenderer, [18](#)
 - Arcade::NCursesRenderer, [25](#)
 - Arcade::Sdl2Renderer, [33](#)
 - Arcade::SfmlRenderer, [39](#)
- getEvent
 - Arcade::IRenderer, [18](#)
 - Arcade::NCursesRenderer, [26](#)
 - Arcade::Sdl2Renderer, [33](#)
 - Arcade::SfmlRenderer, [40](#)
- getHeight
 - Arcade::Sdl2Window, [36](#)
- getNextLibIndex
 - Arcade::Core, [12](#)
- getPreviousLibIndex
 - Arcade::Core, [12](#)
- getRenderer
 - Arcade::Core, [13](#)
 - Arcade::Sdl2Window, [36](#)
- getWidth
 - Arcade::Sdl2Window, [36](#)
- getWindow
 - Arcade::IRenderer, [18](#)
 - Arcade::NCursesRenderer, [26](#)
 - Arcade::NCursesWindow, [29](#)
 - Arcade::Sdl2Renderer, [33](#)
 - Arcade::Sdl2Window, [36](#)
 - Arcade::SfmlRenderer, [40](#)
 - Arcade::SfmlWindow, [42](#)
- Graphics/NCurses/include/Arcade/NCursesRenderer.hpp, [49](#)
- Graphics/NCurses/include/Arcade/NCursesWindow.hpp, [50](#)
- Graphics/SDL2/include/Arcade/Sdl2Renderer.hpp, [50](#)
- Graphics/SDL2/include/Arcade/Sdl2Window.hpp, [51](#)
- Graphics/SFML/include/Arcade/SfmlRenderer.hpp, [51](#)
- Graphics/SFML/include/Arcade/SfmlWindow.hpp, [52](#)
- handleEvents
 - Arcade::Core, [13](#)
- isASCII
 - Arcade::IRenderer, [19](#)
 - Arcade::NCursesRenderer, [26](#)
 - Arcade::Sdl2Renderer, [33](#)
 - Arcade::SfmlRenderer, [40](#)
- KeyboardEvents
 - Arcade, [10](#)
- loadFont
 - Arcade::IRenderer, [19](#)
 - Arcade::NCursesRenderer, [26](#)
 - Arcade::Sdl2Renderer, [34](#)
 - Arcade::SfmlRenderer, [40](#)
- loadTexture
 - Arcade::IRenderer, [19](#)
 - Arcade::NCursesRenderer, [28](#)
 - Arcade::Sdl2Renderer, [34](#)
 - Arcade::SfmlRenderer, [41](#)
- mainLoop
 - Arcade::Core, [13](#)
- openWindow
 - Arcade::IWindow, [22](#)
 - Arcade::NCursesWindow, [29](#)
 - Arcade::Sdl2Window, [36](#)
 - Arcade::SfmlWindow, [42](#)
- runArcade
 - Arcade::Core, [13](#)
- setMode
 - Arcade::Core, [14](#)
- setPosition
 - Arcade::ISprite, [21](#)
- setTitle
 - Arcade::IWindow, [22](#)
 - Arcade::NCursesWindow, [30](#)
 - Arcade::Sdl2Window, [37](#)
 - Arcade::SfmlWindow, [43](#)
- switchLib
 - Arcade::Core, [14](#)