

arcade

0.1.0

Generated by Doxygen 1.9.1

1 Namespace Index	1
1.1 Namespace List	1
2 Hierarchical Index	3
2.1 Class Hierarchy	3
3 Class Index	5
3.1 Class List	5
4 File Index	7
4.1 File List	7
5 Namespace Documentation	9
5.1 Arcade Namespace Reference	9
5.1.1 Detailed Description	10
5.1.2 Enumeration Type Documentation	10
5.1.2.1 GameEvent	10
6 Class Documentation	11
6.1 Arcade::Core Class Reference	11
6.1.1 Detailed Description	11
6.1.2 Member Function Documentation	12
6.1.2.1 gameLoop()	12
6.1.2.2 handleEvents()	12
6.1.2.3 parser()	12
6.1.2.4 runArcade()	12
6.1.2.5 setMode()	13
6.2 Arcade::Core::CoreException Class Reference	13
6.2.1 Detailed Description	13
6.3 Arcade::IGame Class Reference	14
6.3.1 Detailed Description	14
6.4 Arcade::IRenderer Class Reference	14
6.4.1 Detailed Description	15
6.4.2 Member Function Documentation	15
6.4.2.1 getEvent()	15
6.4.2.2 openWindow()	15
6.4.2.3 setTitle()	16
6.5 Arcade::ISprite Class Reference	16
6.5.1 Detailed Description	16
6.5.2 Member Function Documentation	17
6.5.2.1 setPosition()	17
6.6 Arcade::Ncurses Class Reference	17
6.6.1 Detailed Description	18
6.6.2 Member Function Documentation	18

6.6.2.1 getEvent()	18
6.6.2.2 openWindow()	18
6.6.2.3 setTitle()	18
6.7 Arcade::RuntimeException Class Reference	19
6.7.1 Detailed Description	19
6.8 Arcade::Sdl2 Class Reference	19
6.8.1 Detailed Description	20
6.8.2 Member Function Documentation	20
6.8.2.1 getEvent()	20
6.8.2.2 openWindow()	20
6.8.2.3 setTitle()	21
6.9 Arcade::Sfml Class Reference	21
6.9.1 Detailed Description	22
6.9.2 Member Function Documentation	22
6.9.2.1 getEvent()	22
6.9.2.2 openWindow()	22
6.9.2.3 setTitle()	23
7 File Documentation	25
7.1 Core/include/Arcade/abstractions/IGame.hpp File Reference	25
7.1.1 Detailed Description	25
7.2 Core/include/Arcade/abstractions/IRenderer.hpp File Reference	25
7.2.1 Detailed Description	26
7.3 Core/include/Arcade/abstractions/ISprite.hpp File Reference	26
7.3.1 Detailed Description	26
7.4 Core/include/Arcade/Core.hpp File Reference	26
7.4.1 Detailed Description	27
7.5 Core/include/Arcade/Enum.hpp File Reference	27
7.5.1 Detailed Description	27
7.6 Core/include/Arcade/RuntimeException.hpp File Reference	27
7.6.1 Detailed Description	28
7.7 Graphics/NCurses/include/Arcade/Ncurses.hpp File Reference	28
7.7.1 Detailed Description	28
7.8 Graphics/SDL2/include/Arcade/Sdl2.hpp File Reference	28
7.8.1 Detailed Description	29
7.9 Graphics/SFML/include/Arcade/Sfml.hpp File Reference	29
7.9.1 Detailed Description	29
Index	31

Chapter 1

Namespace Index

1.1 Namespace List

Here is a list of all documented namespaces with brief descriptions:

Arcade	Main namespace for the Arcade project	9
------------------------	---	---

Chapter 2

Hierarchical Index

2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

Arcade::Core	11
std::exception	
Arcade::Core::CoreException	13
Arcade::RuntimeException	19
Arcade::IGame	14
Arcade::IRenderer	14
Arcade::Ncurses	17
Arcade::Sdl2	19
Arcade::Sfml	21
Arcade::ISprite	16

Chapter 3

Class Index

3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

Arcade::Core	
Core class	11
Arcade::Core::CoreException	
CoreException class	13
Arcade::IGame	
Game Interface	14
Arcade::IRenderer	
Graphic Interface	14
Arcade::ISprite	
Sprite Interface	16
Arcade::Ncurses	
Ncurses class	17
Arcade::RuntimeException	
RuntimeException class	19
Arcade::Sdl2	
Sdl2 class	19
Arcade::Sfml	
Sfml class	21

Chapter 4

File Index

4.1 File List

Here is a list of all documented files with brief descriptions:

Core/include/Arcade/ Constants.hpp	??
Core/include/Arcade/ Core.hpp	
File declaring Core	26
Core/include/Arcade/ Enum.hpp	
File declaring Enum	27
Core/include/Arcade/ RuntimeException.hpp	
File declaring RuntimeException	27
Core/include/Arcade/abstractions/ IGame.hpp	
File declaring Game Interface	25
Core/include/Arcade/abstractions/ IRenderer.hpp	
File declaring Graphic Interface	25
Core/include/Arcade/abstractions/ ISprite.hpp	
File declaring Sprite Interface	26
Graphics/NCurses/include/Arcade/ Ncurses.hpp	
File declaring Ncurses	28
Graphics/SDL2/include/Arcade/ Sdl2.hpp	
File declaring Sdl2 class	28
Graphics/SFML/include/Arcade/ Sfml.hpp	
File declaring Sfml class	29

Chapter 5

Namespace Documentation

5.1 Arcade Namespace Reference

Main namespace for the [Arcade](#) project.

Classes

- class [IGame](#)
Game Interface.
- class [IRenderer](#)
Graphic Interface.
- class [ISprite](#)
Sprite Interface.
- class [Core](#)
Core class.
- class [RuntimeException](#)
RuntimeException class.
- class [Sdl2](#)
Sdl2 class.
- class [Ncurses](#)
Ncurses class.
- class [Sfml](#)
Sfml class.

Enumerations

- enum class **CoreMode** { **GAME** , **MENU** , **PAUSE** , **QUIT** }
- enum class **GameMode** { **GAME** , **GAME_OVER** , **MENU** , **PAUSE** , **QUIT** }
- enum class [GameEvent](#) { **UP** , **DOWN** , **LEFT** , **RIGHT** , **SHOOT** , **PAUSE** , **QUIT** , **NONE** }
Enum for the GameEvent.

5.1.1 Detailed Description

Main namespace for the [Arcade](#) project.

5.1.2 Enumeration Type Documentation

5.1.2.1 GameEvent

enum [Arcade::GameEvent](#) [strong]

Enum for the GameEvent.

Set of enum used for the game event

Chapter 6

Class Documentation

6.1 Arcade::Core Class Reference

[Core](#) class.

```
#include <Arcade/Core.hpp>
```

Classes

- class [CoreException](#)
CoreException class.

Public Member Functions

- **Core** (const [Core](#) &)=delete
- **Core & operator=** (const [Core](#) &)=delete
- void [parser](#) (const std::string &path)
parse arguments
- int [runArcade](#) (const std::string &path)
Run Arcade.
- void [gameLoop](#) ()
Game loop.
- void [handleEvents](#) (const [GameEvent](#) &event)
Handle events.
- void [setMode](#) (const CoreMode &gameMode)
Set the game mode.
- void [closeWindow](#) ()
close the window

6.1.1 Detailed Description

[Core](#) class.

[Core](#) class for the [Arcade](#) project

6.1.2 Member Function Documentation

6.1.2.1 gameLoop()

```
void Arcade::Core::gameLoop ( )
```

Game loop.

Main game loop

6.1.2.2 handleEvents()

```
void Arcade::Core::handleEvents (
    const GameEvent & event )
```

Handle events.

Parameters

<i>event</i>	
--------------	--

6.1.2.3 parser()

```
void Arcade::Core::parser (
    const std::string & path )
```

parse arguments

Parameters

<i>path</i>	
-------------	--

6.1.2.4 runArcade()

```
int Arcade::Core::runArcade (
    const std::string & path )
```

Run [Arcade](#).

Parameters

<i>path</i>	
-------------	--

Returns

int

6.1.2.5 setMode()

```
void Arcade::Core::setMode (
    const CoreMode & gameMode ) [inline]
```

Set the game mode.

Parameters

<i>gameMode</i>	
-----------------	--


The documentation for this class was generated from the following file:

- Core/include/Arcade/[Core.hpp](#)

6.2 Arcade::Core::CoreException Class Reference[CoreException](#) class.

#include <Arcade/Core.hpp>

Inheritance diagram for Arcade::Core::CoreException:

**Public Member Functions**

- **CoreException** (std::string msg)
- **CoreException** ([CoreException](#) const &)=delete
- const char * **what** () const noexcept override

6.2.1 Detailed Description[CoreException](#) class.Exception class for the [Core](#) class

The documentation for this class was generated from the following file:

- Core/include/Arcade/[Core.hpp](#)

6.3 Arcade::IGame Class Reference

Game Interface.

```
#include <Arcade/abstractions/IGame.hpp>
```

Public Member Functions

- **IGame** (const [IGame](#) &)=delete
- **IGame** & **operator=** (const [IGame](#) &)=delete
- virtual void **start** ()=0
start the game
- virtual void **stop** ()=0
stop the game

6.3.1 Detailed Description

Game Interface.

Set of method to implement for the business logic of the [Arcade](#) project

The documentation for this class was generated from the following file:


- Core/include/Arcade/abstractions/[IGame.hpp](#)

6.4 Arcade::IRenderer Class Reference

Graphic Interface.

```
#include <Arcade/abstractions/IRenderer.hpp>
```

Inheritance diagram for Arcade::IRenderer:



Public Member Functions

- **IRenderer** (const [IRenderer](#) &)=delete
- **IRenderer & operator=** (const [IRenderer](#) &)=delete
- virtual void [openWindow](#) (const unsigned int width, const unsigned int height)=0
Create a window.
- virtual [GameEvent](#) [getEvent](#) ()=0
Get the event object.
- virtual void [displayWindow](#) ()=0
display actual window
- virtual void [clearWindow](#) ()=0
clear actual window
- virtual void [closeWindow](#) ()=0
close actual window
- virtual void [setTitle](#) (const std::string &title)=0
set window title
- virtual void [displayMenu](#) ()=0
display menu

6.4.1 Detailed Description

Graphic Interface.

Set of method to implement for the business logic of the [Arcade](#) project

6.4.2 Member Function Documentation

6.4.2.1 [getEvent\(\)](#)

```
virtual GameEvent Arcade::IRenderer::getEvent ( ) [pure virtual]
```

Get the event object.

Returns

[GameEvent](#)

Implemented in [Arcade::Sfml](#), [Arcade::Sdl2](#), and [Arcade::Ncurses](#).

6.4.2.2 [openWindow\(\)](#)

```
virtual void Arcade::IRenderer::openWindow (
    const unsigned int width,
    const unsigned int height ) [pure virtual]
```

Create a window.

Parameters

<i>width</i>	
<i>height</i>	

Implemented in [Arcade::Sfml](#), [Arcade::Sdl2](#), and [Arcade::Ncurses](#).

6.4.2.3 setTitle()

```
virtual void Arcade::IRenderer::setTitle (
    const std::string & title ) [pure virtual]
```

set window title

Parameters

<i>title</i>	
--------------	--

Implemented in [Arcade::Sfml](#), [Arcade::Sdl2](#), and [Arcade::Ncurses](#).

The documentation for this class was generated from the following file:

- Core/include/Arcade/abstractions/[IRenderer.hpp](#)

6.5 Arcade::ISprite Class Reference

Sprite Interface.

```
#include <Arcade/abstractions/ISprite.hpp>
```

Public Member Functions

- **ISprite** (const [ISprite](#) &)=delete
- **ISprite** & **operator=** (const [ISprite](#) &)=delete
- virtual void [draw](#) ()=0
draw the sprite
- virtual void [setPosition](#) (int x, int y)=0
set the position of the sprite

6.5.1 Detailed Description

Sprite Interface.

Set of method to implement for the business logic of the [Arcade](#) project

6.5.2 Member Function Documentation

6.5.2.1 setPosition()

```
virtual void Arcade::ISprite::setPosition (
    int x,
    int y ) [pure virtual]
```

set the position of the sprite

Parameters

<i>x</i>	
<i>y</i>	

The documentation for this class was generated from the following file:


- [Core/include/Arcade/abstractions/ISprite.hpp](#)

6.6 Arcade::Ncurses Class Reference

[Ncurses](#) class.

```
#include <Arcade/Ncurses.hpp>
```

Inheritance diagram for Arcade::Ncurses:



Public Member Functions

- **Ncurses** (const [Ncurses](#) &)=delete
- [Ncurses](#) & **operator=** (const [Ncurses](#) &)=delete
- [GameEvent](#) **getEvent** () override
Get the event object.
- void [openWindow](#) (unsigned int width, unsigned int height) override
Create a window.
- void [displayWindow](#) () override
display actual window
- void [clearWindow](#) () override
clear actual window
- void [closeWindow](#) () override
close actual window
- void [setTitle](#) (const std::string &title) override
set window title
- void [displayMenu](#) () override
display menu

6.6.1 Detailed Description

[Ncurses](#) class.

[Ncurses](#) class for the [Arcade](#) project

6.6.2 Member Function Documentation

6.6.2.1 `getEvent()`

[GameEvent](#) `Arcade::Ncurses::getEvent ()` `[override]`, `[virtual]`

Get the event object.

Returns

`GameEvent`

Implements [Arcade::IRenderer](#).

6.6.2.2 `openWindow()`

```
void Arcade::Ncurses::openWindow (
    unsigned int width,
    unsigned int height ) [override], [virtual]
```

Create a window.

Parameters

<i>width</i>	
<i>height</i>	

Implements [Arcade::IRenderer](#).

6.6.2.3 `setTitle()`

```
void Arcade::Ncurses::setTitle (
    const std::string & title ) [inline], [override], [virtual]
```

set window title

Parameters

<i>title</i>	
--------------	--

Implements [Arcade::IRenderer](#).

The documentation for this class was generated from the following file:


- Graphics/NCurses/include/Arcade/[Ncurses.hpp](#)

6.7 Arcade::RuntimeException Class Reference

[RuntimeException](#) class.

```
#include <Arcade/RuntimeException.hpp>
```

Inheritance diagram for Arcade::RuntimeException:



Public Member Functions

- **RuntimeException** (std::string msg)
- **RuntimeException** ([RuntimeException](#) const &)=delete
- const char * **what** () const noexcept override

6.7.1 Detailed Description

[RuntimeException](#) class.

[RuntimeException](#) class for the [Arcade](#) project

The documentation for this class was generated from the following file:


- Core/include/Arcade/[RuntimeException.hpp](#)

6.8 Arcade::Sdl2 Class Reference

[Sdl2](#) class.

```
#include <Arcade/Sdl2.hpp>
```

Inheritance diagram for Arcade::Sdl2:



Public Member Functions

- **Sdl2** (const [Sdl2](#) &)=delete
- **Sdl2 & operator=** (const [Sdl2](#) &)=delete
- [GameEvent](#) **getEvent** () override
Get the event object.
- void [openWindow](#) (unsigned int width, unsigned int height) override
Create a window.
- void [displayWindow](#) () override
display actual window
- void [clearWindow](#) () override
clear actual window
- void [closeWindow](#) () override
close actual window
- void [setTitle](#) (const std::string &title) override
set window title
- void [displayMenu](#) () override
display menu

6.8.1 Detailed Description

[Sdl2](#) class.

[Sdl2](#) class for the [Arcade](#) project

6.8.2 Member Function Documentation

6.8.2.1 [getEvent\(\)](#)

```
GameEvent Arcade::Sdl2::getEvent ( ) [override], [virtual]
```

Get the event object.

Returns

[GameEvent](#)

Implements [Arcade::IRenderer](#).

6.8.2.2 [openWindow\(\)](#)

```
void Arcade::Sdl2::openWindow (  
    unsigned int width,  
    unsigned int height ) [override], [virtual]
```

Create a window.

Parameters

<i>width</i>	
<i>height</i>	

Implements [Arcade::IRenderer](#).

6.8.2.3 setTitle()

```
void Arcade::Sdl2::setTitle (
    const std::string & title ) [inline], [override], [virtual]
```

set window title

Parameters

<i>title</i>	
--------------	--

Implements [Arcade::IRenderer](#).

The documentation for this class was generated from the following file:


- Graphics/SDL2/include/Arcade/[Sdl2.hpp](#)

6.9 Arcade::Sfml Class Reference

[Sfml](#) class.

```
#include <Arcade/Sfml.hpp>
```

Inheritance diagram for Arcade::Sfml:



Public Member Functions

- **Sfml** (const [Sfml](#) &)=delete
- **Sfml & operator=** (const [Sfml](#) &)=delete
- **GameEvent** **getEvent** () override
Get the event object.
- void **openWindow** (unsigned int width, unsigned int height) override
Create a window.

- void [displayWindow](#) () override
display actual window
- void [clearWindow](#) () override
clear actual window
- void [closeWindow](#) () override
close actual window
- void [setTitle](#) (const std::string &title) override
set window title
- void [displayMenu](#) () override
display menu
- bool **loadTexture** (const std::string &filepath, const std::string &name)
- bool **loadFont** (const std::string &filepath, const std::string &name)

6.9.1 Detailed Description

[Sfml](#) class.

[Sfml](#) class for the [Arcade](#) project

6.9.2 Member Function Documentation

6.9.2.1 [getEvent\(\)](#)

[GameEvent](#) `Arcade::Sfml::getEvent () [override], [virtual]`

Get the event object.

Returns

`GameEvent`

Implements [Arcade::IRenderer](#).

6.9.2.2 [openWindow\(\)](#)

```
void Arcade::Sfml::openWindow (
    unsigned int width,
    unsigned int height ) [override], [virtual]
```

Create a window.

Parameters

<i>width</i>	
<i>height</i>	

Implements [Arcade::IRenderer](#).

6.9.2.3 setTitle()

```
void Arcade::Sfml::setTitle (
    const std::string & title ) [inline], [override], [virtual]
```

set window title

Parameters

<i>title</i>	
--------------	--

Implements [Arcade::IRenderer](#).

The documentation for this class was generated from the following file:

- Graphics/SFML/include/Arcade/[Sfml.hpp](#)

Chapter 7

File Documentation

7.1 Core/include/Arcade/abstractions/IGame.hpp File Reference

File declaring Game Interface.

Classes

- class [Arcade::IGame](#)
Game Interface.

Namespaces

- [Arcade](#)
Main namespace for the [Arcade](#) project.

7.1.1 Detailed Description

File declaring Game Interface.

7.2 Core/include/Arcade/abstractions/IRenderer.hpp File Reference

File declaring Graphic Interface.

```
#include <string>
#include "Arcade/Enum.hpp"
```

Classes

- class [Arcade::IRenderer](#)
Graphic Interface.

Namespaces

- [Arcade](#)

Main namespace for the [Arcade](#) project.

7.2.1 Detailed Description

File declaring Graphic Interface.

7.3 Core/include/Arcade/abstractions/ISprite.hpp File Reference

File declaring Sprite Interface.

Classes

- class [Arcade::ISprite](#)

Sprite Interface.

Namespaces

- [Arcade](#)

Main namespace for the [Arcade](#) project.

7.3.1 Detailed Description

File declaring Sprite Interface.

7.4 Core/include/Arcade/Core.hpp File Reference

File declaring Core.

```
#include <iostream>
#include <exception>
#include <memory>
#include "Arcade/Enum.hpp"
#include "Arcade/abstractions/IRenderer.hpp"
```

Classes

- class [Arcade::Core](#)
Core class.
- class [Arcade::Core::CoreException](#)
CoreException class.

Namespaces

- [Arcade](#)

Main namespace for the [Arcade](#) project.

7.4.1 Detailed Description

File declaring Core.

7.5 Core/include/Arcade/Enum.hpp File Reference

File declaring Enum.

Namespaces

- [Arcade](#)

Main namespace for the [Arcade](#) project.

Enumerations

- enum class **CoreMode** { **GAME** , **MENU** , **PAUSE** , **QUIT** }
- enum class **GameMode** { **GAME** , **GAME_OVER** , **MENU** , **PAUSE** , **QUIT** }
- enum class [Arcade::GameEvent](#) { **UP** , **DOWN** , **LEFT** , **RIGHT** , **SHOOT** , **PAUSE** , **QUIT** , **NONE** }

Enum for the GameEvent.

7.5.1 Detailed Description

File declaring Enum.

Set of enum used in the [Arcade](#) project

7.6 Core/include/Arcade/RuntimeException.hpp File Reference

File declaring RuntimeException.

```
#include <iostream>
#include <exception>
```

Classes

- class [Arcade::RuntimeException](#)
RuntimeException class.

Namespaces

- [Arcade](#)
Main namespace for the [Arcade](#) project.

7.6.1 Detailed Description

File declaring RuntimeException.

7.7 Graphics/NCurses/include/Arcade/Ncurses.hpp File Reference

File declaring Ncurses.

```
#include <ncurses.h>
#include <string_view>
#include "Arcade/abstractions/IRenderer.hpp"
```

Classes

- class [Arcade::Ncurses](#)
Ncurses class.

Namespaces

- [Arcade](#)
Main namespace for the [Arcade](#) project.

7.7.1 Detailed Description

File declaring Ncurses.

7.8 Graphics/SDL2/include/Arcade/Sdl2.hpp File Reference

File declaring Sdl2 class.

```
#include <iostream>
#include <SDL2/SDL.h>
#include "Arcade/abstractions/IRenderer.hpp"
```


Classes

- class [Arcade::Sdl2](#)
[Sdl2](#) class.

Namespaces

- [Arcade](#)
Main namespace for the [Arcade](#) project.

Variables

- constexpr std::string_view **WINDOW_TITLE** = "Arcade - SDL2"

7.8.1 Detailed Description

File declaring Sdl2 class.

7.9 Graphics/SFML/include/Arcade/Sfml.hpp File Reference

File declaring Sfml class.

```
#include <SFML/Graphics.hpp>
#include "Arcade/abstractions/IRenderer.hpp"
```

Classes

- class [Arcade::Sfml](#)
[Sfml](#) class.

Namespaces

- [Arcade](#)
Main namespace for the [Arcade](#) project.

Variables

- constexpr std::string_view **WINDOW_TITLE** = "Arcade - SFML"

7.9.1 Detailed Description

File declaring Sfml class.

Index

- Arcade, [9](#)
 - GameEvent, [10](#)
- Arcade::Core, [11](#)
 - gameLoop, [12](#)
 - handleEvents, [12](#)
 - parser, [12](#)
 - runArcade, [12](#)
 - setMode, [13](#)
- Arcade::Core::CoreException, [13](#)
- Arcade::IGame, [14](#)
- Arcade::IRenderer, [14](#)
 - getEvent, [15](#)
 - openWindow, [15](#)
 - setTitle, [16](#)
- Arcade::ISprite, [16](#)
 - setPosition, [17](#)
- Arcade::Ncurses, [17](#)
 - getEvent, [18](#)
 - openWindow, [18](#)
 - setTitle, [18](#)
- Arcade::RuntimeException, [19](#)
- Arcade::Sdl2, [19](#)
 - getEvent, [20](#)
 - openWindow, [20](#)
 - setTitle, [21](#)
- Arcade::Sfml, [21](#)
 - getEvent, [22](#)
 - openWindow, [22](#)
 - setTitle, [23](#)
- Core/include/Arcade/abstractions/IGame.hpp, [25](#)
- Core/include/Arcade/abstractions/IRenderer.hpp, [25](#)
- Core/include/Arcade/abstractions/ISprite.hpp, [26](#)
- Core/include/Arcade/Core.hpp, [26](#)
- Core/include/Arcade/Enum.hpp, [27](#)
- Core/include/Arcade/RuntimeException.hpp, [27](#)
- GameEvent
 - Arcade, [10](#)
- gameLoop
 - Arcade::Core, [12](#)
- getEvent
 - Arcade::IRenderer, [15](#)
 - Arcade::Ncurses, [18](#)
 - Arcade::Sdl2, [20](#)
 - Arcade::Sfml, [22](#)
- Graphics/NCurses/include/Arcade/Ncurses.hpp, [28](#)
- Graphics/SDL2/include/Arcade/Sdl2.hpp, [28](#)
- Graphics/SFML/include/Arcade/Sfml.hpp, [29](#)
- handleEvents
 - Arcade::Core, [12](#)
- openWindow
 - Arcade::IRenderer, [15](#)
 - Arcade::Ncurses, [18](#)
 - Arcade::Sdl2, [20](#)
 - Arcade::Sfml, [22](#)
- parser
 - Arcade::Core, [12](#)
- runArcade
 - Arcade::Core, [12](#)
- setMode
 - Arcade::Core, [13](#)
- setPosition
 - Arcade::ISprite, [17](#)
- setTitle
 - Arcade::IRenderer, [16](#)
 - Arcade::Ncurses, [18](#)
 - Arcade::Sdl2, [21](#)
 - Arcade::Sfml, [23](#)