

vengine

0.1.0

Generated by Doxygen 1.9.1

1 Hierarchical Index	1
1.1 Class Hierarchy	1
2 Class Index	3
2.1 Class List	3
3 Class Documentation	5
3.1 ven::Buffer Class Reference	5
3.1.1 Member Function Documentation	5
3.1.1.1 descriptorInfo()	5
3.1.1.2 descriptorInfoForIndex()	6
3.1.1.3 flush()	6
3.1.1.4 flushIndex()	7
3.1.1.5 invalidate()	7
3.1.1.6 invalidateIndex()	7
3.1.1.7 map()	8
3.1.1.8 unmap()	8
3.1.1.9 writeToBuffer()	8
3.1.1.10 writeToIndex()	9
3.2 ven::DescriptorPool::Builder Class Reference	9
3.3 ven::DescriptorSetLayout::Builder Class Reference	9
3.4 ven::Model::Builder Struct Reference	10
3.5 ven::Camera Class Reference	10
3.6 myLib::Clock Class Reference	10
3.7 ven::DescriptorPool Class Reference	11
3.8 ven::DescriptorSetLayout Class Reference	11
3.9 ven::DescriptorWriter Class Reference	12
3.10 ven::Device Class Reference	12
3.11 ven::Engine Class Reference	13
3.12 ven::FrameInfo Struct Reference	13
3.13 ven::GlobalUbo Struct Reference	13
3.14 ven::KeyboardController Class Reference	14
3.15 ven::KeyboardController::KeyMappings Struct Reference	14
3.16 ven::Model Class Reference	14
3.17 ven::Object Class Reference	15
3.18 ven::PipelineConfigInfo Struct Reference	16
3.19 gui::PluginLoader Class Reference	16
3.20 gui::PluginLoader::PluginLoaderException Class Reference	17
3.21 ven::PointLight Struct Reference	17
3.22 ven::PointLightComponent Struct Reference	17
3.23 ven::PointLightSystem Class Reference	18
3.24 ven::QueueFamilyIndices Struct Reference	18
3.25 myLib::Random Class Reference	18

3.26 ven::Renderer Class Reference	19
3.27 ven::RenderSystem Class Reference	19
3.28 ven::Shaders Class Reference	19
3.29 ven::SimplePushConstantData Struct Reference	20
3.30 ven::SwapChain Class Reference	20
3.31 ven::SwapChainSupportDetails Struct Reference	21
3.32 myLib::Time Class Reference	21
3.33 ven::Transform3DComponent Struct Reference	21
3.34 ven::Model::Vertex Struct Reference	22
3.35 ven::Window Class Reference	22
Index	23

Chapter 1

Hierarchical Index

1.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

ven::Buffer	5
ven::DescriptorPool::Builder	9
ven::DescriptorSetLayout::Builder	9
ven::Model::Builder	10
ven::Camera	10
myLib::Clock	10
ven::DescriptorPool	11
ven::DescriptorSetLayout	11
ven::DescriptorWriter	12
ven::Device	12
ven::Engine	13
std::exception	
gui::PluginLoader::PluginLoaderException	17
ven::FrameInfo	13
ven::GlobalUbo	13
ven::KeyboardController	14
ven::KeyboardController::KeyMappings	14
ven::Model	14
ven::Object	15
ven::PipelineConfigInfo	16
gui::PluginLoader	16
ven::PointLight	17
ven::PointLightComponent	17
ven::PointLightSystem	18
ven::QueueFamilyIndices	18
myLib::Random	18
ven::Renderer	19
ven::RenderSystem	19
ven::Shaders	19
ven::SimplePushConstantData	20
ven::SwapChain	20
ven::SwapChainSupportDetails	21
myLib::Time	21
ven::Transform3DComponent	21
ven::Model::Vertex	22
ven::Window	22

Chapter 2

Class Index

2.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

ven::Buffer	5
ven::DescriptorPool::Builder	9
ven::DescriptorSetLayout::Builder	9
ven::Model::Builder	10
ven::Camera	10
myLib::Clock	10
ven::DescriptorPool	11
ven::DescriptorSetLayout	11
ven::DescriptorWriter	12
ven::Device	12
ven::Engine	13
ven::FrameInfo	13
ven::GlobalUbo	13
ven::KeyboardController	14
ven::KeyboardController::KeyMappings	14
ven::Model	14
ven::Object	15
ven::PipelineConfigInfo	16
gui::PluginLoader	16
gui::PluginLoader::PluginLoaderException	17
ven::PointLight	17
ven::PointLightComponent	17
ven::PointLightSystem	18
ven::QueueFamilyIndices	18
myLib::Random	18
ven::Renderer	19
ven::RenderSystem	19
ven::Shaders	19
ven::SimplePushConstantData	20
ven::SwapChain	20
ven::SwapChainSupportDetails	21
myLib::Time	21
ven::Transform3DComponent	21
ven::Model::Vertex	22
ven::Window	22

Chapter 3

Class Documentation

3.1 ven::Buffer Class Reference

Public Member Functions

- **Buffer** ([Device](#) &device, VkDeviceSize instanceSize, uint32_t instanceCount, VkBufferUsageFlags usageFlags, VkMemoryPropertyFlags memoryPropertyFlags, VkDeviceSize minOffsetAlignment=1)
- **Buffer** (const [Buffer](#) &)=delete
- [Buffer](#) & **operator=** (const [Buffer](#) &)=delete
- VkResult [map](#) (VkDeviceSize size=VK_WHOLE_SIZE, VkDeviceSize offset=0)
- void [unmap](#) ()
- void [writeToBuffer](#) (void *data, VkDeviceSize size=VK_WHOLE_SIZE, VkDeviceSize offset=0)
- VkResult [flush](#) (VkDeviceSize size=VK_WHOLE_SIZE, VkDeviceSize offset=0)
- VkDescriptorBufferInfo [descriptorInfo](#) (VkDeviceSize size=VK_WHOLE_SIZE, VkDeviceSize offset=0)
- VkResult [invalidate](#) (VkDeviceSize size=VK_WHOLE_SIZE, VkDeviceSize offset=0)
- void [writeToIndex](#) (void *data, int index)
- VkResult [flushIndex](#) (int index)
- VkDescriptorBufferInfo [descriptorInfoForIndex](#) (int index)
- VkResult [invalidateIndex](#) (int index)
- VkBuffer **getBuffer** () const
- void * **getMappedMemory** () const
- uint32_t **getInstanceCount** () const
- VkDeviceSize **getInstanceSize** () const
- VkDeviceSize **getAlignmentSize** () const
- VkBufferUsageFlags **getUsageFlags** () const
- VkMemoryPropertyFlags **getMemoryPropertyFlags** () const
- VkDeviceSize **getBufferSize** () const

3.1.1 Member Function Documentation

3.1.1.1 descriptorInfo()

```
VkDescriptorBufferInfo ven::Buffer::descriptorInfo (  
    VkDeviceSize size = VK_WHOLE_SIZE,  
    VkDeviceSize offset = 0 ) [inline]
```

Create a buffer info descriptor

Parameters

<i>size</i>	(Optional) Size of the memory range of the descriptor
<i>offset</i>	(Optional) Byte offset from beginning

Returns

VkDescriptorBufferInfo of specified offset and range

3.1.1.2 descriptorInfoForIndex()

```
VkDescriptorBufferInfo ven::Buffer::descriptorInfoForIndex (  
    int index ) [inline]
```

Create a buffer info descriptor

Parameters

<i>index</i>	Specifies the region given by index * alignmentSize
--------------	---

Returns

VkDescriptorBufferInfo for instance at index

3.1.1.3 flush()

```
VkResult ven::Buffer::flush (  
    VkDeviceSize size = VK_WHOLE_SIZE,  
    VkDeviceSize offset = 0 )
```

Flush a memory range of the buffer to make it visible to the device

Note

Only required for non-coherent memory

Parameters

<i>size</i>	(Optional) Size of the memory range to flush. Pass VK_WHOLE_SIZE to flush the complete buffer range.
<i>offset</i>	(Optional) Byte offset from beginning

Returns

VkResult of the flush call

3.1.1.4 flushIndex()

```
VkResult ven::Buffer::flushIndex (
    int index ) [inline]
```

Flush the memory range at index * alignmentSize of the buffer to make it visible to the device

Parameters

<i>index</i>	Used in offset calculation
--------------	----------------------------

3.1.1.5 invalidate()

```
VkResult ven::Buffer::invalidate (
    VkDeviceSize size = VK_WHOLE_SIZE,
    VkDeviceSize offset = 0 )
```

Invalidate a memory range of the buffer to make it visible to the host

Note

Only required for non-coherent memory

Parameters

<i>size</i>	(Optional) Size of the memory range to invalidate. Pass VK_WHOLE_SIZE to invalidate the complete buffer range.
<i>offset</i>	(Optional) Byte offset from beginning

Returns

VkResult of the invalidate call

3.1.1.6 invalidateIndex()

```
VkResult ven::Buffer::invalidateIndex (
    int index ) [inline]
```

Invalidate a memory range of the buffer to make it visible to the host

Note

Only required for non-coherent memory

Parameters

<i>index</i>	Specifies the region to invalidate: $\text{index} * \text{alignmentSize}$
--------------	---

Returns

VkResult of the invalidate call

3.1.1.7 map()

```
VkResult ven::Buffer::map (
    VkDeviceSize size = VK_WHOLE_SIZE,
    VkDeviceSize offset = 0 )
```

Map a memory range of this buffer. If successful, mapped points to the specified buffer range.

Parameters

<i>size</i>	(Optional) Size of the memory range to map. Pass VK_WHOLE_SIZE to map the complete buffer range.
<i>offset</i>	(Optional) Byte offset from beginning

Returns

VkResult of the buffer mapping call

3.1.1.8 unmap()

```
void ven::Buffer::unmap ( )
```

Unmap a mapped memory range

Note

Does not return a result as vkUnmapMemory can't fail

3.1.1.9 writeToBuffer()

```
void ven::Buffer::writeToBuffer (
    void * data,
    VkDeviceSize size = VK_WHOLE_SIZE,
    VkDeviceSize offset = 0 )
```

Copies the specified data to the mapped buffer. Default value writes whole buffer range

Parameters

<i>data</i>	Pointer to the data to copy
<i>size</i>	(Optional) Size of the data to copy. Pass VK_WHOLE_SIZE to flush the complete buffer range.
<i>offset</i>	(Optional) Byte offset from beginning of mapped region

3.1.1.10 writeToIndex()

```
void ven::Buffer::writeToIndex (
    void * data,
    int index ) [inline]
```

Copies "instanceSize" bytes of data to the mapped buffer at an offset of index * alignmentSize

Parameters

<i>data</i>	Pointer to the data to copy
<i>index</i>	Used in offset calculation

The documentation for this class was generated from the following file:

- include/VEngine/Buffer.hpp

3.2 ven::DescriptorPool::Builder Class Reference

Public Member Functions

- **Builder** ([Device](#) &device)
- **Builder** & **addPoolSize** (VkDescriptorType descriptorType, uint32_t count)
- **Builder** & **setPoolFlags** (VkDescriptorPoolCreateFlags flags)
- **Builder** & **setMaxSets** (uint32_t count)
- std::unique_ptr< [DescriptorPool](#) > **build** () const

The documentation for this class was generated from the following file:

- include/VEngine/Descriptors.hpp

3.3 ven::DescriptorSetLayout::Builder Class Reference

Public Member Functions

- **Builder** ([Device](#) &device)
- **Builder** & **addBinding** (uint32_t binding, VkDescriptorType descriptorType, VkShaderStageFlags stageFlags, uint32_t count=1)
- std::unique_ptr< [DescriptorSetLayout](#) > **build** () const

The documentation for this class was generated from the following file:

- include/VEngine/Descriptors.hpp

3.4 ven::Model::Builder Struct Reference

Public Member Functions

- void **loadModel** (const std::string &filename)

Public Attributes

- std::vector< [Vertex](#) > **vertices** {}
- std::vector< uint32_t > **indices** {}

The documentation for this struct was generated from the following file:

- include/VEngine/Model.hpp

3.5 ven::Camera Class Reference

Public Member Functions

- void **setOrthographicProjection** (float left, float right, float top, float bottom, float near, float far)
- void **setPerspectiveProjection** (float fovy, float aspect, float near, float far)
- void **setViewDirection** (glm::vec3 position, glm::vec3 direction, glm::vec3 up=glm::vec3{0.F, -1.F, 0.F})
- void **setViewTarget** (glm::vec3 position, glm::vec3 target, glm::vec3 up=glm::vec3{0.F, -1.F, 0.F})
- void **setViewYXZ** (glm::vec3 position, glm::vec3 rotation)
- const glm::mat4 & **getProjection** () const
- const glm::mat4 & **getView** () const

The documentation for this class was generated from the following file:

- include/VEngine/Camera.hpp

3.6 myLib::Clock Class Reference

Public Member Functions

- void **restart** ()
- void **pause** ()
- void **resume** ()
- [Time](#) **getElapsedTime** () const

The documentation for this class was generated from the following file:

- lib/static/myLib/include/myLib/Clock/Clock.hpp

3.7 ven::DescriptorPool Class Reference

Classes

- class [Builder](#)

Public Member Functions

- **DescriptorPool** ([Device](#) &device, uint32_t maxSets, VkDescriptorPoolCreateFlags poolFlags, const std::vector< VkDescriptorPoolSize > &poolSizes)
- **DescriptorPool** (const [DescriptorPool](#) &)=delete
- [DescriptorPool](#) & **operator=** (const [DescriptorPool](#) &)=delete
- bool **allocateDescriptor** (const VkDescriptorSetLayout descriptorSetLayout, VkDescriptorSet &descriptor) const
- void **freeDescriptors** (std::vector< VkDescriptorSet > &descriptors) const
- void **resetPool** ()

Friends

- class **DescriptorWriter**

The documentation for this class was generated from the following file:

- include/VEngine/Descriptors.hpp

3.8 ven::DescriptorSetLayout Class Reference

Classes

- class [Builder](#)

Public Member Functions

- **DescriptorSetLayout** ([Device](#) &device, std::unordered_map< uint32_t, VkDescriptorSetLayoutBinding > bindings)
- **DescriptorSetLayout** (const [DescriptorSetLayout](#) &)=delete
- [DescriptorSetLayout](#) & **operator=** (const [DescriptorSetLayout](#) &)=delete
- VkDescriptorSetLayout **getDescriptorSetLayout** () const

Friends

- class **DescriptorWriter**

The documentation for this class was generated from the following file:

- include/VEngine/Descriptors.hpp

3.9 ven::DescriptorWriter Class Reference

Public Member Functions

- **DescriptorWriter** ([DescriptorSetLayout](#) &setLayout, [DescriptorPool](#) &pool)
- [DescriptorWriter](#) & **writeBuffer** (uint32_t binding, VkDescriptorBufferInfo *bufferInfo)
- [DescriptorWriter](#) & **writelnImage** (uint32_t binding, VkDescriptorImageInfo *imageInfo)
- bool **build** (VkDescriptorSet &set)
- void **overwrite** (VkDescriptorSet &set)

The documentation for this class was generated from the following file:

- include/VEngine/Descriptors.hpp

3.10 ven::Device Class Reference

Public Member Functions

- **Device** ([ven::Window](#) &window)
- **Device** (const [Device](#) &)=delete
- [Device](#) & **operator=** (const [Device](#) &)=delete
- **Device** ([Device](#) &&)=delete
- [Device](#) & **operator=** ([Device](#) &&)=delete
- VkCommandPool **getCommandPool** ()
- VkDevice **device** ()
- VkSurfaceKHR **surface** ()
- VkQueue **graphicsQueue** ()
- VkQueue **presentQueue** ()
- [SwapChainSupportDetails](#) **getSwapChainSupport** ()
- uint32_t **findMemoryType** (uint32_t typeFilter, VkMemoryPropertyFlags properties)
- [QueueFamilyIndices](#) **findPhysicalQueueFamilies** ()
- VkFormat **findSupportedFormat** (const std::vector< VkFormat > &candidates, VkImageTiling tiling, VkFormatFeatureFlags features)
- void **createBuffer** (VkDeviceSize size, VkBufferUsageFlags usage, VkMemoryPropertyFlags properties, VkBuffer &buffer, VkDeviceMemory &bufferMemory)
- VkCommandBuffer **beginSingleTimeCommands** ()
- void **endSingleTimeCommands** (VkCommandBuffer commandBuffer)
- void **copyBuffer** (VkBuffer srcBuffer, VkBuffer dstBuffer, VkDeviceSize size)
- void **copyBufferToImage** (VkBuffer buffer, VkImage image, uint32_t width, uint32_t height, uint32_t layerCount)
- void **createImageWithInfo** (const VkImageCreateInfo &imageInfo, VkMemoryPropertyFlags properties, VkImage &image, VkDeviceMemory &imageMemory)

Public Attributes

- const bool **enableValidationLayers** = true
- VkPhysicalDeviceProperties **m_properties**

The documentation for this class was generated from the following file:

- include/VEngine/Device.hpp

3.11 ven::Engine Class Reference

Public Member Functions

- **Engine** (uint32_t=DEFAULT_WIDTH, uint32_t=DEFAULT_HEIGHT, const std::string &title=DEFAULT_TITLE.data())
- **Engine** (const [Engine](#) &)=delete
- [Engine](#) **operator=** (const [Engine](#) &)=delete
- [Window](#) & **getWindow** ()
- void **mainLoop** ()

The documentation for this class was generated from the following file:

- include/VEngine/Engine.hpp

3.12 ven::FrameInfo Struct Reference

Public Attributes

- int **frameIndex**
- float **frameTime**
- VkCommandBuffer **commandBuffer**
- [Camera](#) & **camera**
- VkDescriptorSet **globalDescriptorSet**
- Object::Map & **objects**

The documentation for this struct was generated from the following file:

- include/VEngine/FrameInfo.hpp

3.13 ven::GlobalUbo Struct Reference

Public Attributes

- glm::mat4 **projection** {1.F}
- glm::mat4 **view** {1.F}
- glm::vec4 **ambientLightColor** {1.F, 1.F, 1.F, .02F}
- [PointLight](#) **pointLights** [MAX_LIGHTS]
- int **numLights**

The documentation for this struct was generated from the following file:

- include/VEngine/FrameInfo.hpp

3.14 ven::KeyboardController Class Reference

Classes

- struct [KeyMappings](#)

Public Member Functions

- void **moveInPlaneXZ** (GLFWwindow *window, float dt, [Object](#) &object) const

Public Attributes

- [KeyMappings](#) **m_keys** {}
- float **m_moveSpeed** {3.F}
- float **m_lookSpeed** {1.5F}

The documentation for this class was generated from the following file:

- include/VEngine/KeyboardController.hpp

3.15 ven::KeyboardController::KeyMappings Struct Reference

Public Attributes

- int **moveLeft** = GLFW_KEY_A
- int **moveRight** = GLFW_KEY_D
- int **moveForward** = GLFW_KEY_W
- int **moveBackward** = GLFW_KEY_S
- int **moveUp** = GLFW_KEY_SPACE
- int **moveDown** = GLFW_KEY_LEFT_SHIFT
- int **lookLeft** = GLFW_KEY_LEFT
- int **lookRight** = GLFW_KEY_RIGHT
- int **lookUp** = GLFW_KEY_UP
- int **lookDown** = GLFW_KEY_DOWN

The documentation for this struct was generated from the following file:

- include/VEngine/KeyboardController.hpp

3.16 ven::Model Class Reference

Classes

- struct [Builder](#)
- struct [Vertex](#)

Public Member Functions

- **Model** ([Device](#) &device, const [Model::Builder](#) &builder)
- **Model** (const [Model](#) &)=delete
- void **operator=** (const [Model](#) &)=delete
- void **bind** (VkCommandBuffer commandBuffer)
- void **draw** (VkCommandBuffer commandBuffer) const

Static Public Member Functions

- static std::unique_ptr< [Model](#) > **createModelFromFile** ([Device](#) &device, const std::string &filename)

The documentation for this class was generated from the following file:

- include/VEngine/Model.hpp

3.17 ven::Object Class Reference

Public Types

- using **Map** = std::unordered_map< id_t, [Object](#) >

Public Member Functions

- **Object** (const [Object](#) &)=delete
- [Object](#) & **operator=** (const [Object](#) &)=delete
- **Object** ([Object](#) &&)=default
- [Object](#) & **operator=** ([Object](#) &&)=default
- id_t **getId** () const

Static Public Member Functions

- static [Object](#) **createObject** ()
- static [Object](#) **makePointLight** (float intensity=10.F, float radius=0.1F, glm::vec3 color=glm::vec3(1.F))

Public Attributes

- std::shared_ptr< [ven::Model](#) > **model** {}
- glm::vec3 **color** {}
- [Transform3DComponent](#) **transform3D** {}
- std::unique_ptr< [PointLightComponent](#) > **pointLight** = nullptr

The documentation for this class was generated from the following file:

- include/VEngine/Object.hpp

3.18 ven::PipelineConfigInfo Struct Reference

Public Member Functions

- **PipelineConfigInfo** (const [PipelineConfigInfo](#) &)=delete
- [PipelineConfigInfo](#) & **operator=** (const [PipelineConfigInfo](#) &)=delete

Public Attributes

- std::vector< [VkVertexInputBindingDescription](#) > **bindingDescriptions** {}
- std::vector< [VkVertexInputAttributeDescription](#) > **attributeDescriptions** {}
- [VkPipelineInputAssemblyStateCreateInfo](#) **inputAssemblyInfo** {}
- [VkPipelineRasterizationStateCreateInfo](#) **rasterizationInfo** {}
- [VkPipelineMultisampleStateCreateInfo](#) **multisampleInfo** {}
- [VkPipelineColorBlendAttachmentState](#) **colorBlendAttachment** {}
- [VkPipelineColorBlendStateCreateInfo](#) **colorBlendInfo** {}
- [VkPipelineDepthStencilStateCreateInfo](#) **depthStencilInfo** {}
- std::vector< [VkDynamicState](#) > **dynamicStateEnables**
- [VkPipelineDynamicStateCreateInfo](#) **dynamicStateInfo** {}
- [VkPipelineLayout](#) **pipelineLayout** = nullptr
- [VkRenderPass](#) **renderPass** = nullptr
- uint32_t **subpass** = 0

The documentation for this struct was generated from the following file:

- include/VEngine/Shaders.hpp

3.19 gui::PluginLoader Class Reference

Classes

- class [PluginLoaderException](#)

Public Types

- using **PluginCreator** = std::unique_ptr< [IPlugin](#) >(*)()

Public Member Functions

- template<typename T >
std::unique_ptr< T > **getPlugin** (const std::string &pluginName)
- void **closePlugins** ()

Static Public Member Functions


- static [PluginLoader](#) & `getInstance ()`

The documentation for this class was generated from the following file:

- `include/VEngine/PluginLoader.hpp`

3.20 gui::PluginLoader::PluginLoaderException Class Reference

Inheritance diagram for gui::PluginLoader::PluginLoaderException:



Public Member Functions

- **PluginLoaderException** (std::string msg)
- const char * **what** () const noexcept override

The documentation for this class was generated from the following file:

- `include/VEngine/PluginLoader.hpp`

3.21 ven::PointLight Struct Reference

Public Attributes

- glm::vec4 **position** {}
- glm::vec4 **color** {}

The documentation for this struct was generated from the following file:

- `include/VEngine/FramelInfo.hpp`

3.22 ven::PointLightComponent Struct Reference

Public Attributes

- float **lightIntensity** = 1.0F

The documentation for this struct was generated from the following file:

- `include/VEngine/Object.hpp`

3.23 ven::PointLightSystem Class Reference

Public Member Functions

- **PointLightSystem** ([Device](#) &device, VkRenderPass renderPass, VkDescriptorSetLayout globalSetLayout)
- **PointLightSystem** (const [PointLightSystem](#) &)=delete
- [PointLightSystem](#) & **operator=** (const [PointLightSystem](#) &)=delete
- void **update** ([FrameInfo](#) &frameInfo, [GlobalUbo](#) &ubo)
- void **render** ([FrameInfo](#) &frameInfo)

The documentation for this class was generated from the following file:

- include/VEngine/System/PointLightSystem.hpp

3.24 ven::QueueFamilyIndices Struct Reference

Public Member Functions

- bool **isComplete** () const

Public Attributes

- uint32_t **graphicsFamily** {}
- uint32_t **presentFamily** {}
- bool **graphicsFamilyHasValue** = false
- bool **presentFamilyHasValue** = false

The documentation for this struct was generated from the following file:

- include/VEngine/Device.hpp

3.25 myLib::Random Class Reference

Static Public Member Functions

- static int **randomInt** (int min, int max)
- static int **randomInt** ()
- static float **randomFloat** (float min, float max)
- static float **randomFloat** ()

The documentation for this class was generated from the following file:

- lib/static/myLib/include/myLib/Random.hpp

3.26 ven::Renderer Class Reference

Public Member Functions

- **Renderer** ([Window](#) &>window, [Device](#) &device)
- **Renderer** (const [Renderer](#) &)=delete
- [Renderer](#) & **operator=** (const [Renderer](#) &)=delete
- VkRenderPass **getSwapChainRenderPass** () const
- float **getAspectRatio** () const
- bool **isFrameInProgress** () const
- VkCommandBuffer **getCurrentCommandBuffer** () const
- int **getFrameIndex** () const
- VkCommandBuffer **beginFrame** ()
- void **endFrame** ()
- void **beginSwapChainRenderPass** (VkCommandBuffer commandBuffer)

Static Public Member Functions

- static void **endSwapChainRenderPass** (VkCommandBuffer commandBuffer)

The documentation for this class was generated from the following file:

- include/VEngine/Renderer.hpp

3.27 ven::RenderSystem Class Reference

Public Member Functions

- **RenderSystem** ([Device](#) &device, VkRenderPass renderPass, VkDescriptorSetLayout globalSetLayout)
- **RenderSystem** (const [RenderSystem](#) &)=delete
- [RenderSystem](#) & **operator=** (const [RenderSystem](#) &)=delete
- void **renderObjects** ([FrameInfo](#) &frameInfo)

The documentation for this class was generated from the following file:

- include/VEngine/System/RenderSystem.hpp

3.28 ven::Shaders Class Reference

Public Member Functions

- **Shaders** ([Device](#) &device, const std::string &vertFilepath, const std::string &fragFilepath, const [PipelineConfigInfo](#) &configInfo)
- **Shaders** (const [Shaders](#) &)=delete
- [Shaders](#) & **operator=** (const [Shaders](#) &)=delete
- void **bind** (VkCommandBuffer commandBuffer)

Static Public Member Functions

- static void **defaultPipelineConfigInfo** ([PipelineConfigInfo](#) &configInfo)

The documentation for this class was generated from the following file:

- include/VEngine/Shaders.hpp

3.29 ven::SimplePushConstantData Struct Reference

Public Attributes

- glm::mat4 **modelMatrix** {1.F}
- glm::mat4 **normalMatrix** {1.F}

The documentation for this struct was generated from the following file:

- include/VEngine/System/RenderSystem.hpp

3.30 ven::SwapChain Class Reference

Public Member Functions

- **SwapChain** ([Device](#) &deviceRef, VkExtent2D windowExtent)
- **SwapChain** ([Device](#) &deviceRef, VkExtent2D windowExtent, std::shared_ptr< [SwapChain](#) > previous)
- **SwapChain** (const [SwapChain](#) &)=delete
- [SwapChain](#) & **operator=** (const [SwapChain](#) &)=delete
- VkFramebuffer **getFrameBuffer** (unsigned long index)
- VkRenderPass **getRenderPass** ()
- VkImageView **getImageView** (int index)
- size_t **imageCount** ()
- VkFormat **getSwapChainImageFormat** ()
- VkExtent2D **getSwapChainExtent** ()
- uint32_t **width** () const
- uint32_t **height** () const
- float **extentAspectRatio** () const
- VkFormat **findDepthFormat** ()
- VkResult **acquireNextImage** (uint32_t *imageIndex)
- VkResult **submitCommandBuffers** (const VkCommandBuffer *buffers, const uint32_t *imageIndex)
- bool **compareSwapFormats** (const [SwapChain](#) &swapChainp) const

Static Public Attributes

- static constexpr int **MAX_FRAMES_IN_FLIGHT** = 2

The documentation for this class was generated from the following file:

- include/VEngine/SwapChain.hpp

3.31 ven::SwapChainSupportDetails Struct Reference

Public Attributes

- VkSurfaceCapabilitiesKHR **capabilities**
- std::vector< VkSurfaceFormatKHR > **formats**
- std::vector< VkPresentModeKHR > **presentModes**

The documentation for this struct was generated from the following file:

- include/VEngine/Device.hpp

3.32 myLib::Time Class Reference

Public Member Functions

- **Time** (const double seconds)
- int **asSeconds** () const
- int **asMilliseconds** () const
- int **asMicroseconds** () const

The documentation for this class was generated from the following file:

- lib/static/myLib/include/myLib/Clock/Time.hpp

3.33 ven::Transform3DComponent Struct Reference

Public Member Functions

- glm::mat4 **mat4** () const
- glm::mat3 **normalMatrix** ()

Public Attributes

- glm::vec3 **translation** {}
- glm::vec3 **scale** {1.F, 1.F, 1.F}
- glm::vec3 **rotation** {}

The documentation for this struct was generated from the following file:

- include/VEngine/Object.hpp

3.34 ven::Model::Vertex Struct Reference

Public Member Functions

- bool **operator==** (const [Vertex](#) &other) const

Static Public Member Functions

- static std::vector< VkVertexInputBindingDescription > **getBindingDescriptions** ()
- static std::vector< VkVertexInputAttributeDescription > **getAttributeDescriptions** ()

Public Attributes

- glm::vec3 **position** {}
- glm::vec3 **color** {}
- glm::vec3 **normal** {}
- glm::vec2 **uv** {}

The documentation for this struct was generated from the following file:

- include/VEngine/Model.hpp

3.35 ven::Window Class Reference

Public Member Functions

- **Window** (const uint32_t width, const uint32_t height, const std::string &title)
- GLFWwindow * **createWindow** (uint32_t width, uint32_t height, const std::string &title)
- void **createWindowSurface** (VkInstance instance, VkSurfaceKHR *surface)
- GLFWwindow * **getGLFWWindow** () const
- VkExtent2D **getExtent** () const
- bool **wasWindowResized** () const
- void **resetWindowResizedFlag** ()

The documentation for this class was generated from the following file:

- include/VEngine/Window.hpp

Index

- descriptorInfo
 - ven::Buffer, [5](#)
- descriptorInfoForIndex
 - ven::Buffer, [6](#)
- flush
 - ven::Buffer, [6](#)
- flushIndex
 - ven::Buffer, [7](#)
- gui::PluginLoader, [16](#)
- gui::PluginLoader::PluginLoaderException, [17](#)
- invalidate
 - ven::Buffer, [7](#)
- invalidateIndex
 - ven::Buffer, [7](#)
- map
 - ven::Buffer, [8](#)
- myLib::Clock, [10](#)
- myLib::Random, [18](#)
- myLib::Time, [21](#)
- unmap
 - ven::Buffer, [8](#)
- ven::Buffer, [5](#)
 - descriptorInfo, [5](#)
 - descriptorInfoForIndex, [6](#)
 - flush, [6](#)
 - flushIndex, [7](#)
 - invalidate, [7](#)
 - invalidateIndex, [7](#)
 - map, [8](#)
 - unmap, [8](#)
 - writeToBuffer, [8](#)
 - writeToIndex, [9](#)
- ven::Camera, [10](#)
- ven::DescriptorPool, [11](#)
- ven::DescriptorPool::Builder, [9](#)
- ven::DescriptorSetLayout, [11](#)
- ven::DescriptorSetLayout::Builder, [9](#)
- ven::DescriptorWriter, [12](#)
- ven::Device, [12](#)
- ven::Engine, [13](#)
- ven::FrameInfo, [13](#)
- ven::GlobalUbo, [13](#)
- ven::KeyboardController, [14](#)
- ven::KeyboardController::KeyMappings, [14](#)
- ven::Model, [14](#)
- ven::Model::Builder, [10](#)
- ven::Model::Vertex, [22](#)
- ven::Object, [15](#)
- ven::PipelineConfigInfo, [16](#)
- ven::PointLight, [17](#)
- ven::PointLightComponent, [17](#)
- ven::PointLightSystem, [18](#)
- ven::QueueFamilyIndices, [18](#)
- ven::Renderer, [19](#)
- ven::RenderSystem, [19](#)
- ven::Shaders, [19](#)
- ven::SimplePushConstantData, [20](#)
- ven::SwapChain, [20](#)
- ven::SwapChainSupportDetails, [21](#)
- ven::Transform3DComponent, [21](#)
- ven::Window, [22](#)
- writeToBuffer
 - ven::Buffer, [8](#)
- writeToIndex
 - ven::Buffer, [9](#)