OBLIGATION WARHOUSE

ISO DO INPUT MESSAGE LAYOUTS

SEPTEMBER 1, 2009



TABLE OF CONTENTS

MT542 - Free Deliver Order 3

MT543 - Valued Deliver Order 8

MT542 - Free IPO Deliver Order 13

MT543 - Valued IPO Deliver Order 19

MT542 - Free ADR Deliver Order 25

MT543 - Valued ADR Deliver Order 28

MT542 - Free Security Holder Tracked Deliver Order 33

MT543 - Valued Security Holder Tracked Deliver Order 38

MT542 - FREE DELIVER ORDER

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
Mandatory Sequence A General Information						
M	:16R:	GENL	Start of Block		:16R:GENL	
M	:20C:	:SEME//	Senders Reference Number	:4!c//16x	:20C::SEME//xxxxxxxxxxxxxxx	Senders reference number.
M	:23G:	NEWM	Message Function - New	4!c	:23G:NEWM	
Repetitive Optional Subsequence A1 Linkages (Used for reclaims only)						
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:RELA//	IMS TID	:4!c//16x	:20C::RELA//xxxxxxxxxxxxxxx	IMS Transaction ID for transaction being reclaimed
M	:16S:	LINK	End of Block		:16S:LINK	
Repetitive Optional Subsequence A1 Linkages (Used for Obligation Warehouse Delivery Orders)						
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:COMM//	Obligation Warehouse Control Number	:4!c//16x	:20C::COMM//xxxxxxxxxxxxxxx	Obligation Warehouse Control Number for Obligation Warehouse Delivery Orders (Dos).
M	:16S:	LINK	End of Block		:16S:LINK	
End of Subsequence A1 Linkages						
M	:16S:	GENL	End of Block		:16S:GENL	
End of Sequence A General Information						

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
Mandatory Sequence B Trade Details						
M	:16R:	TRADDET	Start of Block		:16R:TRADDET	
M	:98A:	:SETT//	Settlement Date	:4!c//8!n	:98A::SETT//20060109	Settlement date
M	:35B:	:ISIN	ISIN	ISIN1!e12!c	:35B:ISIN XXXXXXXXXXXX	ISIN The literal ISIN followed by a space followed by the 12 character ISIN. Example: ISIN US1234567891 DTC does not accept Non-U.S. ISINs.
Optional Subsequence B1 Financial Instrument Attributes						
M	:16R:	FIA	Start of Block		:16R:FIA	
O	:92A:	:CUFC:	CMO Factor	:4!c//[N]15d	:92A::CUFC//00,000000000000	CMO Factor
M	:16S:	FIA	End of Block		:16S:FIA	
End of Subsequence B1 Financial Instrument Attributes						
M	:22F:	:PROC/DTCY	Business Transaction ID	:4!c/[8c]/4!c	:22F::PROC/DTCY/DO02	
O	:22F:	:RPOR/DTCY	Fail Tracking Indicator	:4!c/[8c]/4!c	:22F::RPOR/DTCY/DBLY or DBLN	Formerly known as Due Bill indicator Indicates whether due bills are carried on this issue. DBLY - due bills are carried DBLN - due bills are not carried If the field is blank, DBLY is assumed.
O	:70E:	:SPRO/	Narrative - DTC DO Comments	:4!c//10*35x	:70E::SPRO//xxxxxxxxxxxxxxxxetc. (The maximum length DTC accepts for this field is 210, 6 lines of 35 characters each.)	Comments - maximum DTCC length of 210
M	:16S:	TRADDET	End of Block		:16S:TRADDET	
End of Sequence B Trade Details						

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
Mandatory Sequence C Financial Instrument/Account						
M	:16R:	FIAC	Start of Block		:16R:FIAC	
M	:36B:	:SETT	Quantity expressed as units	:4!c//4!c/15d	:36B::SETT//UNIT/0000000050000,0	Share quantity.
M	:97A:	:SAFE	Deliverers Account Number	:4!c//35x	:SAFE//xxxxxxxx	Deliverer DTCC participant number.
M	:16S:	FIAC	End of Block		:16S:FIAC	
End of Sequence C Financial Instrument/Account						
Mandatory Sequence E Settlement Details						
M	:16R:	SETDET	Start of Block		:16R:SETDET	
O	:22F:	STCO/DTCY	Settlement Today Only Indicator	:4!c/[8c]/4!c	:22F::STCO/DTCY/STOY or STON	Indicates if the transaction: • STOY - transaction can only settle on settlement date included in the 98A::SETT field. • STON - transaction can attempt the next settlement date if the current is already past the cutoff. IMS Reintroduce Profile is also overridden if the field is populated with an N. • space - transaction can attempt the next settlement date if the current is already past the cutoff. IMS Reintroduce Profile is not overridden if the transaction drops.

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
O	:22F:	STCO/DTCY	PTA Indicator	:4!c/[8c]/4!c	:22F::STCO/DTCY/PTAY or PTAN	Indicates if the transaction should affect the Protected Transaction Account. • PTAY - Should affect the account • PTAN - Should not affect the account If the field is blank, N is assumed.
M	:22F:	SETR/DTCYREAS	Reason Code	:4!c/[8c]/4!c	:22F::SETR/DTCYREAS/xxxx	Reason Code Padded to the left with zeroes
O	:22F:	SETS/DTCY	Prevent Pend	:4!c/[8c]/4!c	:22F::SETS/DTCY/PNDY or PNDN	Indicates if the transaction should be prevented from recycling. • PNDY - Do not permit recycling • PNDN - Allow recycling
Repetitive Mandatory Subsequence E1 Settlement Parties						
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95R:	DEAG/DTCYPART	Delivering Participant	:4!c/8c/34x	:95R::DEAG/DTCYPART/0000nnnn	DTCC Participant number for the deliverer.
O	:97A:	SAFE	Deliverers Account Number	:4!c//35x	:97A::SAFE//nnnnnnnnnnnnnnnn	Deliverer internal account number (maximum 35 bytes)
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95R:	REAG/DTCYPART	Receiving Participant	:4!c/8c/34x	:95R::REAG/DTCYPART/0000nnnn	DTCC Participant number for receiver.
O	:97A:	SAFE	Receivers Account Number	:4!c//35x	:97A::SAFE//nnnnnnnnnnnnnnnn	Receiver internal account number (maximum 35 bytes)
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95P:	:PSET	Place of Settlement	:4!c//4!a2!a2!c[3	:95P::PSET//DTCYUS33	DTCC BIC Number

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
End of Subsequence E1 Settlement Parties						
M	:16S:	SETDET	End of Block		:16S:SETDET	
End of Sequence E Settlement Details						

MT543 - VALUED DELIVER ORDER

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
Mandatory Sequence A General Information						
M	:16R:	GENL	Start of Block		:16R:GENL	
M	:20C:	:SEME//	Senders Reference Number	:4!c//16x	:20C::SEME//xxxxxxxxxxxxxxxx	Senders reference number.
M	:23G:	NEWM	Message Function - New	4!c	:23G:NEWM	
Repetitive Optional Subsequence A1 Linkages (Used for reclaims only)						
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:RELA//	IMS TID	:4!c//16x	:20C::RELA//xxxxxxxxxxxxxxxx	IMS Transaction ID for transaction being reclaimed.
M	:16S:	LINK	End of Block		:16S:LINK	
Repetitive Optional Subsequence A1 Linkages (Used for Obligation Warehouse Delivery Orders)						
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:COMM//	Obligation Warehouse Control Number	:4!c//16x	:20C::COMM//xxxxxxxxxxxxxxxx	Obligation Warehouse Control Number for Obligation Warehouse Delivery Orders.
M	:16S:	LINK	End of Block		:16S:LINK	
End of Subsequence A1 Linkages						
M	:16S:	GENL	End of Block		:16S:GENL	
End of Sequence A General Information						
Mandatory Sequence B Trade Details						
M	:16R:	TRADDET	Start of Block		:16R:TRADDET	

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
M	:98A:	:SETT//	Settlement Date	:4!c//8!n	:98A::SETT//20060109	Settlement date
M	:35B:	:ISIN	ISIN	ISIN1!e12!c	:35B:ISIN XXXXXXXXXXXX	• ISIN The literal ISIN followed by a space followed by the 12 character ISIN. Example: ISIN US1234567891 DTC does not accept Non-U.S. ISINs.
Optional Subsequence B1 Financial Instrument Attributes						
M	:16R:	FIA	Start of Block		:16R:FIA	
O	:92A:	:CUFC:	CMO Factor	:4!c//[N]15d	:92A::CUFC//00,000000000000	CMO Factor
M	:16S:	FIA	End of Block		:16S:FIA	
End of Subsequence B1 Financial Instrument Attributes						
M	:22F:	:PROC/DTCY	Business Transaction ID	:4!c/[8c]/4!c	:22F::PROC/DTCY/DO01	
O	:22F:	:RPOR/DTCY	Fail Tracking Indicator	:4!c/[8c]/4!c	:22F::RPOR/DTCY/DBLY or DBLN	Formerly known as Due Bill indicator Indicates whether due bills are carried on this issue. • DBLY - due bills are carried • DBLN - due bills are not carried If the field is blank, DBLY is assumed.
O	:70E:	:SPRO/	Narrative - DTC DO Comments	:4!c//10*35x	:70E::SPRO//xxxxxxxxxxxxxxxxetc. (The maximum length DTC accepts for this field is 210, 6 lines of 35 characters each.)	
M	:16S:	TRADDET	End of Block		:16S:TRADDET	
End of Sequence B Trade Details						
Mandatory Sequence C Financial Instrument/Account						

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
M	:16R:	FIAC	Start of Block		:16R:FIAC	
M	:36B:	:SETT	Quantity expressed as units	:4!c//4!c/15d	:36B::SETT//UNIT/0000000050000,0	Share quantity.
M	:97A:	:SAFE	Deliverers Account Number	:4!c//35x	:SAFE//xxxxxxxx	Deliverer DTCC participant number.
M	:16S:	FIAC	End of Block		:16S:FIAC	
End of Sequence C Financial Instrument/Account						
Mandatory Sequence E Settlement Details						
M	:16R:	SETDET	Start of Block		:16R:SETDET	
O	:22F:	STCO/DTCY	Settlement Today Only Indicator	:4!c/[8c]/4!c	:22F::STCO/DTCY/STOY or STON	Indicates if the transaction: • STOY - Transaction can only settle on settlement date included in the 98A::SETT field. • STON - Transaction can attempt the next settlement date if the current is already past the cutoff. IMS Reintroduce Profile is also overridden if field is populated with an N. • space - Transaction can attempt the next settlement date if the current is already past the cutoff. IMS Reintroduce Profile is not overridden if the transaction drops.
O	:22F:	STCO/DTCY	PTA Indicator	:4!c/[8c]/4!c	:22F::STCO/DTCY/PTAY or PTAN	Indicates if the transaction should affect the Protected Transaction Account. • PTAY - Should affect the account • PTAN - Should not affect the account

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
						If the field is blank, N is assumed.
M	:22F:	SETR/DTCYREAS	Reason Code	:4!c/[8c]/4!c	:22F::SETR/DTCYREAS/xxxx	Reason Code Padded to the left with zeroes
O	:22F:	SETS/DTCY	Prevent Pend	:4!c/[8c]/4!c	:22F::SETS/DTCY/PNDY or PNDN	Indicates if the transaction should be prevented from recycling. • PNDY - Do not permit recycling • PNDN - Allow recycling
Repetitive Mandatory Subsequence E1 Settlement Parties						
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95R:	DEAG/DTCYPART	Delivering Participant	:4!c/8c/34x	:95R::DEAG/DTCYPART/0000nnnn	DTCC Participant number for the deliverer.
O	:97A:	SAFE	Deliverers Account Number	:4!c//35x	:97A::SAFE//nnnnnnnnnnnnnnnn	Deliverer internal account number (maximum 35 bytes)
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95R:	REAG/DTCYPART	Receiving Participant	:4!c/8c/34x	:95R::REAG/DTCYPART/0000nnnn	DTCC Participant number for receiver
O	:97A:	SAFE	Receivers Account Number	:4!c//35x	:97A::SAFE//nnnnnnnnnnnnnnnn	Receiver internal account number (maximum 35 bytes)
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95P:	:PSET	Place of Settlement	:4!c//4!a2!a2!c[3!c]	:95P::PSET//DTCYUS33	DTCC BIC Number
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
End of Subsequence E1 Settlement Parties						
Repetitive Mandatory Subsequence E3 Amounts						

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
M	:16R:	AMT	Start of Block		:16R:AMT	
M	:19A:	SETT//	Settlement Amount	:4!c//[N]3!a15d	:19A::SETT//USD000000000000,00	Settlement amount.
M	:16S:	AMT	End of Block		:16S:AMT	
End of Subsequence E3 Amounts						
M	:16S:	SETDET	End of Block		:16S:SETDET	
End of Sequence E Settlement Details						

MT542 - FREE IPO DELIVER ORDER

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
Mandatory Sequence A General Information						
M	:16R:	GENL	Start of Block		:16R:GENL	
M	:20C:	:SEME//	Senders Reference Number	:4!c//16x	:20C::SEME//xxxxxxxxxxxxxxx	Senders reference number.
M	:23G:	NEWM	Message Function - New	4!c	:23G:NEWM	
Repetitive Optional Subsequence A1 Linkages (Used for reclaims only)						
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:RELA//	IMS TID	:4!c//16x	:20C::RELA//xxxxxxxxxxxxxxx	IMS Transaction ID for transaction being reclaimed
M	:16S:	LINK	End of Block		:16S:LINK	
Repetitive Optional Subsequence A1 Linkages (Used for Obligation Warehouse Delivery Orders)						
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:COMM//	Obligation Warehouse Control Number	:4!c//16x	:20C::COMM//xxxxxxxxxxxxxxx	Obligation Warehouse Control Number for Obligation Warehouse Delivery Orders.
M	:16S:	LINK	End of Block		:16S:LINK	
End of Subsequence A1 Linkages						
M	:16S:	GENL	End of Block		:16S:GENL	
End of Sequence A General Information						
Mandatory Sequence B Trade Details						
M	:16R:	TRADDET	Start of Block		:16R:TRADDET	

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
M	:98A:	:SETT//	Settlement Date	:4!c//8!n	:98A::SETT//20060109	Settlement date
O	:98A:	:TRAD//	Trade Date	:4!c//8!n	:98A::TRAD//20060109	Trade date
M	:35B:	:ISIN	ISIN	ISIN1!e12!c	:35B:ISIN XXXXXXXXXXXX	• ISIN The literal ISIN followed by a space followed by the 12 character ISIN. Example: ISIN US1234567891 DTC does not accept Non-U.S. ISINs.
Optional Subsequence B1 Financial Instrument Attributes						
M	:16R:	FIA	Start of Block		:16R:FIA	
O	:92A:	:CUFC:	CMO Factor	:4!c//[N]15d	:92A::CUFC//00,000000000000	CMO Factor
M	:16S:	FIA	End of Block		:16S:FIA	
End of Subsequence B1 Financial Instrument Attributes						
M	:22F:	:PROC/DTCY	Business Transaction ID	:4!c/[8c]/4!c	:22F::PROC/DTCY/DO06	
O	:22F:	:RPOR/DTCY	Fail Tracking Indicator	:4!c/[8c]/4!c	:22F::RPOR/DTCY/DBLY or DBLN	Formerly known as Due Bill indicator Indicates whether due bills are carried on this issue. • DBLY - due bills are carried • DBLN - due bills are not carried If the field is blank, DBLY is assumed.
O	:70E:	:SPRO/	Narrative - DTC DO Comments	:4!c//10*35x	:70E::SPRO//xxxxxxxxxxxxxxxxetc. The maximum length DTC accepts for this field is 210, 6 lines of 35 characters each.	Comments - maximum DTCC length of 210
M	:16S:	TRADDET	End of Block		:16S:TRADDET	
End of Sequence B Trade Details						

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
Mandatory Sequence C Financial Instrument/Account						
M	:16R:	FIAC	Start of Block		:16R:FIAC	
M	:36B:	:SETT	Quantity expressed as units	:4!c//4!c/15d	:36B::SETT//UNIT/0000000050000,0	Share quantity.
M	:97A:	:SAFE	Deliverers Account Number	:4!c//35x	:SAFE//xxxxxxxx	Deliverer DTCC participant number.
M	:16S:	FIAC	End of Block		:16S:FIAC	
End of Sequence C Financial Instrument/Account						
Mandatory Sequence E Settlement Details						
M	:16R:	SETDET	Start of Block		:16R:SETDET	
O	:22F:	STCO/DTCY	Settlement Today Only Indicator	:4!c/[8c]/4!c	:22F::STCO/DTCY/STOY or STON	Indicates if the transaction: • STOY - Transaction can only settle on settlement date included in the 98A::SETT field. • STON - Transaction can attempt the next settlement date if the current is already past the cutoff. IMS Reintroduce Profile is also overridden if the field is populated with an N. • space - Transaction can attempt the next settlement date if the current is already past the cutoff. IMS Reintroduce Profile is not overridden if the transaction drops.

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
M	:22F:	STCO/DTCY	PTA Indicator	:4!c/[8c]/4!c	:22F::STCO/DTCY/PTAY or PTAN	Indicates if the transaction should affect the Protected Transaction Account. • PTAY - Should affect the account • PTAN - Should not affect the account If the field is blank, N is assumed.
M	:22F:	SETR/DTCYREAS	Reason Code	:4!c/[8c]/4!c	:22F::SETR/DTCYREAS/xxxx	Reason Code Padded to the left with zeroes.
M	:22F:	SETS/DTCY	Prevent Pend	:4!c/[8c]/4!c	:22F::SETS/DTCY/PNDY or PNDN	Indicates if the transaction should be prevented from recycling. • PNDY - Do not permit recycling • PNDN - Allow recycling
M	:22F:	TRCA/DTCY	Buy/Sell Indicator	:4!c/[8c]/4!c	:22F::TRCA/DTCY/BUYX or SELL	Indicates that the Prime Broker is buying or selling. • BUYX - Buy • SELL - Sell
Repetitive Mandatory Subsequence E1 Settlement Parties						
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95R:	DEAG/DTCYPART	Delivering Participant	:4!c/8c/34x	:95R::DEAG/DTCYPART/0000nnnn	DTCC Participant number for the deliverer.
O	:97A	SAFE//	Delivering Agent Internal Account #	:4!c//35x	:97A::SAFE//xxxxxxxxxxx	Deliverer internal account number (maximum 35 bytes). This field is **mandatory** any secondary trade (all reason codes except 530, 540, 550, 560, 570 and 50) in the following cases: • Deliverer is a bank. • Deliverer is a broker and the buy/sell indicator is SELL.

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95R:	REAG/DTCYPART	Receiving Participant	:4!c/8c/34x	:95R::REAG/DTCYPART/0000nnnn	DTCC Participant number for the receiver.
O	:97A	SAFE//	Receiving Agent Internal Account #	:4!c//35x	:97A::SAFE//xxxxxxxxxxx	Receiver internal account number (maximum 35 bytes) This field is mandatory for the following reason codes: • 030 and the receiver is a bank • 050 • 530 • 550
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95P:	:PSET	Place of Settlement	:4!c//4!a2!a2!c[3!c]	:95P::PSET//DTCYUS33	DTCC BIC Number
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
End of Subsequence E1 Settlement Parties						
M	:16S:	SETDET	End of Block		:16S:SETDET	
End of Sequence E Settlement Details						
Repetitive Optional Sequence F Other Parties						
M	:16R:	OTHRPRTY	Start of Block		:16R:OTHRPRTY	
M	:95R:	:MEOR	Correspondent Account #	:4!c/8c/34x	:95R::MEOR/DTCY/xxxxxxxxxx	Correspondent account number, mandatory for reason codes 570, 50 when the deliverer is a bank.
M	:16S:	OTHRPRTY	End of Block		:16S:OTHRPRTY	

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
M	:16R:	OTHRPRTY	Start of Block		:16R:OTHRPRTY	
M	:95R:	:INVE	Broker Internal Account #	:4!c/8c/34x	:95R::INVE/DTCY/xxxxxxxxxx	Broker internal account number, mandatory for reason codes 50, 530 and 550.
M	:16S:	OTHRPRTY	End of Block		:16S:OTHRPRTY	

MT543 - VALUED IPO DELIVER ORDER

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
Mandatory Sequence A General Information						
M	:16R:	GENL	Start of Block		:16R:GENL	
M	:20C:	:SEME//	Senders Reference Number	:4!c//16x	:20C::SEME//xxxxxxxxxxxxxxxx	Senders reference number.
M	:23G:	NEWM	Message Function - New	4!c	:23G:NEWM	
Repetitive Optional Subsequence A1 Linkages (Used for reclaims only)						
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:RELA//	IMS TID	:4!c//16x	:20C::RELA//xxxxxxxxxxxxxxxx	IMS Transaction ID for transaction being reclaimed
M	:16S:	LINK	End of Block		:16S:LINK	
Repetitive Optional Subsequence A1 Linkages (Used for Obligation Warehouse Delivery Orders)						
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:COMM//	Obligation Warehouse Control Number	:4!c//16x	:20C::COMM//xxxxxxxxxxxxxxxx	Obligation Warehouse Control Number for Obligation Warehouse Delivery Orders.
M	:16S:	LINK	End of Block		:16S:LINK	
End of Subsequence A1 Linkages						
M	:16S:	GENL	End of Block		:16S:GENL	
End of Sequence A General Information						
Mandatory Sequence B Trade Details						
M	:16R:	TRADDET	Start of Block		:16R:TRADDET	

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
M	:98A:	:SETT//	Settlement Date	:4!c//8!n	:98A::SETT//20060109	Settlement date.
O	:98A:	:TRAD//	Trade Date	:4!c//8!n	:98A::TRAD//20060109	Trade date.
M	:35B:	:ISIN	ISIN	ISIN1!e12!c	:35B:ISIN XXXXXXXXXXXX	• ISIN The literal ISIN followed by a space followed by the 12 character ISIN. Example: ISIN US1234567891 DTC does not accept Non-U.S. ISINs.
Optional Subsequence B1 Financial Instrument Attributes						
M	:16R:	FIA	Start of Block		:16R:FIA	
O	:92A:	:CUFC:	CMO Factor	:4!c//[N]15d	:92A::CUFC//00,000000000000	CMO Factor
M	:16S:	FIA	End of Block		:16S:FIA	
End of Subsequence B1 Financial Instrument Attributes						
M	:22F:	:PROC/DTCY	Business Transaction ID	:4!c/[8c]/4!c	:22F::PROC/DTCY/DO05	
O	:22F:	:RPOR/DTCY	Fail Tracking Indicator	:4!c/[8c]/4!c	:22F::RPOR/DTCY/DBLY or DBLN	Formerly known as Due Bill indicator Indicates whether due bills are carried on this issue. • DBLY - Due bills are carried. • DBLN - Due bills are not carried. If the field is blank, DBLY is assumed.
O	:70E:	:SPRO/	Narrative - DTC DO Comments	:4!c//10*35x	:70E::SPRO//xxxxxxxxxxxxxxxxetc. (The maximum length DTC accepts for this field is 210, 6 lines of 35 characters each.)	Comments Maximum DTCC length of 210.
M	:16S:	TRADDET	End of Block		:16S:TRADDET	
End of Sequence B Trade Details						

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
Mandatory Sequence C Financial Instrument/Account						
M	:16R:	FIAC	Start of Block		:16R:FIAC	
M	:36B:	:SETT	Quantity expressed as units	:4!c//4!c/15d	:36B::SETT//UNIT/0000000050000,0	Share quantity.
M	:97A:	:SAFE	Deliverers Account Number	:4!c//35x	:SAFE//xxxxxxxx	Deliverer DTCC participant number.
M	:16S:	FIAC	End of Block		:16S:FIAC	
End of Sequence C Financial Instrument/Account						
Mandatory Sequence E Settlement Details						
M	:16R:	SETDET	Start of Block		:16R:SETDET	
O	:22F:	STCO/DTCY	Settlement Today Only Indicator	:4!c/[8c]/4!c	:22F::STCO/DTCY/STOY or STON	Indicates if the transaction: • STOY - Transaction can only settle on settlement date included in the 98A::SETT field. • STON - Transaction can attempt the next settlement date if the current is already past the cutoff. IMS Reintroduce Profile is also overridden if the field is populated with an N. • space - Transaction can attempt the next settlement date if the current is already past the cutoff. IMS Reintroduce Profile is not overridden if the transaction drops.
M	:22F:	STCO/DTCY	PTA Indicator	:4!c/[8c]/4!c	:22F::STCO/DTCY/PTAY or PTAN	Indicates if the transaction should affect the Protected Transaction Account. • PTAY - Should affect the account

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
						• PTAN - Should not affect the account If the field is blank, N is assumed.
M	:22F:	SETR/DTCYREAS	Reason Code	:4!c/[8c]/4!c	:22F::SETR/DTCYREAS/xxxx	Reason Code Padded to the left with zeroes.
M	:22F:	SETS/DTCY	Prevent Pend	:4!c/[8c]/4!c	:22F::SETS/DTCY/PNDY or PNDN	Indicates if the transaction should be prevented from recycling. • PNDY - Do not permit recycling • PNDN - Allow recycling
M	:22F:	TRCA/DTCY	Buy/Sell Indicator	:4!c/[8c]/4!c	:22F::TRCA/DTCY/BUYX or SELL	Indicates that the Prime Broker is buying or selling. • BUYX - Buy • SELL - Sell
Repetitive Mandatory Subsequence E1 Settlement Parties						
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95R:	DEAG/DTCYPART	Delivering Participant	:4!c/8c/34x	:95R::DEAG/DTCYPART/0000nnnn	DTCC Participant number for the deliverer.
O	:97A	SAFE//	Delivering Agent Internal Account #	:4!c//35x	:97A::SAFE//xxxxxxxxxxx	Deliverer internal account number (maximum 35 bytes) This field is mandatory any secondary trade (all reason codes except 530, 540, 550, 560, 570 and 50) in the following cases: • Deliverer is a bank. • Deliverer is a broker and the buy/sell indicator is SELL.
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
M	:95R:	REAG/DTCYPART	Receiving Participant	:4!c/8c/34x	:95R::REAG/DTCYPART/0000nnnn	DTCC Participant number for receiver
O	:97A	SAFE//	Receiving Agent Internal Account #	:4!c//35x	:97A::SAFE//xxxxxxxxxxxx	Receiver internal account number (maximum 35 bytes) This field is mandatory for the following reason codes: • 030 and the receiver is a bank • 050 • 530 • 550
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95P:	:PSET	Place of Settlement	:4!c//4!a2!a2!c[3!c]	:95P::PSET//DTCYUS33	DTCC BIC number.
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
End of Subsequence E1 Settlement Parties						
Repetitive Mandatory Subsequence E3 Amounts						
M	:16R:	AMT	Start of Block		:16R:AMT	
M	:19A:	SETT//	Settlement Amount	:4!c//[N]3!a15d	:19A::SETT//USD000000000000,00	Settlement amount.
M	:16S:	AMT	End of Block		:16S:AMT	
End of Subsequence E3 Amounts						
M	:16S:	SETDET	End of Block		:16S:SETDET	
End of Sequence E Settlement Details						
Repetitive Optional Sequence F Other Parties						

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
M	:16R:	OTHRPRTY	Start of Block		:16R:OTHRPRTY	
M	:95R:	:MEOR	Correspondent Account #	:4!c/8c/34x	:95R::MEOR/DTCY/xxxxxxxxxx	Correspondent account number, mandatory for reason codes 570, 50 when the deliverer is a bank.
M	:16S:	OTHRPRTY	End of Block		:16S:OTHRPRTY	
M	:16R:	OTHRPRTY	Start of Block		:16R:OTHRPRTY	
M	:95R:	:INVE	Broker Internal Account #	:4!c/8c/34x	:95R::INVE/DTCY/xxxxxxxxxx	Broker internal account number, mandatory for reason codes 50, 530, and 550.
M	:16S:	OTHRPRTY	End of Block		:16S:OTHRPRTY	

MT542 - FREE ADR DELIVER ORDER

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
Mandatory Sequence A General Information						
M	:16R:	GENL	Start of Block		:16R:GENL	
M	:20C:	:SEME//	Senders Reference Number	:4!c//16x	:20C::SEME//xxxxxxxxxxxxxxx	Senders reference number.
M	:23G:	NEWM	Message Function - New	4!c	:23G:NEWM	
Repetitive Optional Subsequence A1 Linkages (Used for reclaims only)						
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:RELA//	IMS TID	:4!c//16x	:20C::RELA//xxxxxxxxxxxxxxx	IMS Transaction ID for transaction being reclaimed.
M	:16S:	LINK	End of Block		:16S:LINK	
End of Subsequence A1 Linkages						
M	:16S:	GENL	End of Block		:16S:GENL	
End of Sequence A General Information						
Mandatory Sequence B Trade Details						
M	:16R:	TRADDET	Start of Block		:16R:TRADDET	
M	:98A:	:SETT//	Settlement Date	:4!c//8!n	:98A::SETT//20060109	Settlement date
M	:35B:	:ISIN	ISIN	ISIN1!e12!c	:35B:ISIN XXXXXXXXXXXX	ISIN The literal ISIN followed by a space followed by the 12 character ISIN. Example: ISIN US1234567891 DTC does not accept Non-U.S. ISINs.
Optional Subsequence B1 Financial Instrument Attributes						

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
M	:16R:	FIA	Start of Block		:16R:FIA	
O	:92A:	:CUFC:	CMO Factor	:4!c//[N]15d	:92A::CUFC//00,000000000000	CMO Factor
M	:16S:	FIA	End of Block		:16S:FIA	
End of Subsequence B1 Financial Instrument Attributes						
M	:22F:	:PROC/DTCY	Business Transaction ID	:4!c/[8c]/4!c	:22F::PROC/DTCY/DO04	
O	:22F:	:RPOR/DTCY	Fail Tracking Indicator	:4!c/[8c]/4!c	:22F::RPOR/DTCY/DBLY or DBLN	Formerly known as Due Bill indicator Indicates whether due bills are carried on this issue. • DBLY - due bills are carried • DBLN - due bills are not carried If the field is blank, DBLY is assumed.
O	:70E:	:SPRO/	Narrative - DTC DO Comments	:4!c//10*35x	:70E::SPRO//xxxxxxxxxxxxxxxxetc. The maximum length DTC accepts for this field is 130, 3 lines of 35 characters each and one line of 25 characters.	Comments Maximum DTCC length of 130.
M	:16S:	TRADDET	End of Block		:16S:TRADDET	
End of Sequence B Trade Details						
Mandatory Sequence C Financial Instrument/Account						
M	:16R:	FIAC	Start of Block		:16R:FIAC	
M	:36B:	:SETT	Quantity expressed as units	:4!c//4!c/15d	:36B::SETT//UNIT/0000000050000,0	Share quantity.

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
M	:97A:	:SAFE	Deliverers Account Number	:4!c//35x	:SAFE//xxxxxxxx	Deliverer DTCC participant number
M	:16S:	FIAC	End of Block		:16S:FIAC	
End of Sequence C Financial Instrument/Account						
Mandatory Sequence E Settlement Details						
M	:16R:	SETDET	Start of Block		:16R:SETDET	
O	:22F:	STCO/DTCY	Settlement Today Only Indicator	:4!c/[8c]/4!c	:22F::STCO/DTCY/STOY or STON	Indicates if the transaction: • STOY - Transaction can only settle on settlement date included in the 98A::SETT field. • STON - Transaction can attempt the next settlement date if the current is already past the cutoff. IMS Reintroduce Profile is also overridden if the field is populated with an N. • space - Transaction can attempt the next settlement date if the current is already past the cutoff. IMS Reintroduce Profile is not overridden if the transaction drops.
O	:22F:	STCO/DTCY	PTA Indicator	:4!c/[8c]/4!c	:22F::STCO/DTCY/PTAY or PTAN	Indicates if the transaction should affect the Protected Transaction Account. • PTAY - Should affect the account • PTAN - Should not affect the account If the field is blank, N is assumed.

MT543 - VALUED ADR DELIVER ORDER

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
Mandatory Sequence A General Information						
M	:16R:	GENL	Start of Block		:16R:GENL	
M	:20C:	:SEME//	Senders Reference Number	:4!c//16x	:20C::SEME//xxxxxxxxxxxxxxxx	Senders reference number.
M	:23G:	NEWM	Message Function - New	4!c	:23G:NEWM	
Repetitive Optional Subsequence A1 Linkages (Used for reclaims only)						
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:RELA//	IMS TID	:4!c//16x	:20C::RELA//xxxxxxxxxxxxxxxx	IMS Transaction ID for transaction being reclaimed
M	:16S:	LINK	End of Block		:16S:LINK	
End of Subsequence A1 Linkages						
M	:16S:	GENL	End of Block		:16S:GENL	
End of Sequence A General Information						
Mandatory Sequence B Trade Details						
M	:16R:	TRADDET	Start of Block		:16R:TRADDET	
M	:98A:	:SETT//	Settlement Date	:4!c//8!n	:98A::SETT//20060109	Settlement date.
M	:35B:	:ISIN	ISIN	ISIN1!e12!c	:35B:ISIN XXXXXXXXXXXX	• ISIN The literal ISIN followed by a space followed by the 12 character ISIN. Example: ISIN US1234567891 DTC does not accept Non-U.S. ISINs.
Optional Subsequence B1 Financial Instrument Attributes						

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
M	:16R:	FIA	Start of Block		:16R:FIA	
O	:92A:	:CUFC:	CMO Factor	:4!c//[N]15d	:92A::CUFC//00,000000000000	CMO Factor
M	:16S:	FIA	End of Block		:16S:FIA	
End of Subsequence B1 Financial Instrument Attributes						
M	:22F:	:PROC/DTCY	Business Transaction ID	:4!c/[8c]/4!c	:22F::PROC/DTCY/DO03	
O	:22F:	:RPOR/DTCY	Fail Tracking Indicator	:4!c/[8c]/4!c	:22F::RPOR/DTCY/DBLY or DBLN	Formerly known as Due Bill indicator Indicates whether due bills are carried on this issue. • DBLY - Due bills are carried • DBLN - Due bills are not carried If the field is blank, DBLY is assumed.
O	:70E:	:SPRO/	Narrative - DTC DO Comments	:4!c//10*35x	:70E::SPRO//xxxxxxxxxxxxxxxxetc. The maximum length DTC accepts for this field is 130, 3 lines of 35 characters each and one line of 25 characters.	Comments Maximum DTCC length of 130.
M	:16S:	TRADDET	End of Block		:16S:TRADDET	
End of Sequence B Trade Details						
Mandatory Sequence C Financial Instrument/Account						
M	:16R:	FIAC	Start of Block		:16R:FIAC	
M	:36B:	:SETT	Quantity expressed as units	:4!c//4!c/15d	:36B::SETT//UNIT/0000000050000,0	Share quantity.
M	:97A:	:SAFE	Deliverers Account Number	:4!c//35x	:SAFE//xxxxxxxx	Deliverer DTCC participant number.
M	:16S:	FIAC	End of Block		:16S:FIAC	

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
End of Sequence C Financial Instrument/Account						
Mandatory Sequence E Settlement Details						
M	:16R:	SETDET	Start of Block		:16R:SETDET	
O	:22F:	STCO/DTCY	Settlement Today Only Indicator	:4!c/[8c]/4!c	:22F::STCO/DTCY/STOY or STON	Indicates if the transaction: • STOY - transaction can only settle on settlement date included in the 98A::SETT field. • STON - transaction can attempt the next settlement date if the current is already past the cutoff. IMS Reintroduce Profile is also overridden if the field is populated with an N. • space - transaction can attempt the next settlement date if the current is already past the cutoff. IMS Reintroduce Profile is not overridden if the transaction drops.
O	:22F:	STCO/DTCY	PTA Indicator	:4!c/[8c]/4!c	:22F::STCO/DTCY/PTAY or PTAN	Indicates if the transaction should affect the Protected Transaction Account. • PTAY - Should affect the account • PTAN - Should not affect the account If the field is blank, N is assumed.
O	:22F:	STCO/DTCY	Certification Flag	:4!c/[8c]/4!c	:22F::STCO/DTCY/CERY or CERN	To allow brokers to warrant that they have the applicable certificate/papers. • CERY - Yes • CERN - No

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
M	:22F:	SETR/DTCYREAS	Reason Code	:4!c/[8c]/4!c	:22F::SETR/DTCYREAS/xxxx	Reason Code Padded to the left with zeroes.
O	:22F:	SETS/DTCY	Prevent Pend	:4!c/[8c]/4!c	:22F::SETS/DTCY/PNDY or PNDN	Indicates if the transaction should be prevented from recycling. • PNDY - Do not permit recycling • PNDN - Allow recycling
Repetitive Mandatory Subsequence E1 Settlement Parties						
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95R:	DEAG/DTCYPART	Delivering Participant	:4!c/8c/34x	:95R::DEAG/DTCYPART/0000nnnn	DTCC Participant number for the deliverer.
O	:97A:	SAFE	Deliverers Account Number	:4!c//35x	:97A::SAFE//nnnnnnnnnnnnnnnn	Deliverer internal account number (maximum 35 bytes)
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95R:	REAG/DTCYPART	Receiving Participant	:4!c/8c/34x	:95R::REAG/DTCYPART/0000nnnn	DTCC Participant number for receiver.
O	:97A:	SAFE	Receivers Account Number	:4!c//35x	:97A::SAFE//nnnnnnnnnnnnnnnn	Receiver internal account number (maximum 35 bytes)
M	:20C:	PROC	Account Number	:4!c//16x	:20C:PROC//xxxxxxxxxxxxxxxx	Account information of institution receiving the shares.
M	:70D:	REGI	BIC	:4!c//4*35x	:70D::REGI//xxxxxxxxxxx	BIC of institution where shares are to be sent.
O	:70C:	PACO	Free Format Text	:4!c//4*35x	:70C::PACO//xxxxxxxxxxxxxxxxxxxxx	Free Format Text - maximum DTCC length of 22 bytes.
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
M	:95P:	:PSET	Place of Settlement	:4!c//4!a2!a2!c[3!c]	:95P::PSET//DTCYUS33	DTCC BIC number.
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
End of Subsequence E1 Settlement Parties						
Repetitive Mandatory Subsequence E3 Amounts						
M	:16R:	AMT	Start of Block		:16R:AMT	
M	:19A:	SETT//	Settlement Amount	:4!c//[N]3!a15d	:19A::SETT//USD000000000000,00	Settlement amount.
M	:16S:	AMT	End of Block		:16S:AMT	
End of Subsequence E3 Amounts						
M	:16S:	SETDET	End of Block		:16S:SETDET	
End of Sequence E Settlement Details						

MT542 - FREE SECURITY HOLDER TRACKED DELIVER ORDER

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
Mandatory Sequence A General Information						
M	:16R:	GENL	Start of Block		:16R:GENL	
M	:20C:	:SEME//	Senders Reference Number	:4!c//16x	:20C::SEME//xxxxxxxxxxxxxxx	Senders reference number.
M	:23G:	NEWM	Message Function - New	4!c	:23G:NEWM	
Repetitive Optional Subsequence A1 Linkages (Used for reclaims only)						
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:RELA//	IMS TID	:4!c//16x	:20C::RELA//xxxxxxxxxxxxxxx	IMS Transaction ID for transaction being reclaimed.
M	:16S:	LINK	End of Block		:16S:LINK	
Repetitive Optional Subsequence A1 Linkages (Used for Obligation Warehouse Delivery Orders)						
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:COMM//	Obligation Warehouse Control Number	:4!c//16x	:20C::COMM//xxxxxxxxxxxxxxx	Obligation Warehouse Control Number for Obligation Warehouse Delivery Orders.
M	:16S:	LINK	End of Block		:16S:LINK	
End of Subsequence A1 Linkages						
M	:16S:	GENL	End of Block		:16S:GENL	
End of Sequence A General Information						
Mandatory Sequence B Trade Details						
M	:16R:	TRADDET	Start of Block		:16R:TRADDET	

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
M	:98A:	:SETT//	Settlement Date	:4!c//8!n	:98A::SETT//20060109	Settlement date
M	:35B:	:ISIN	ISIN	ISIN1!e12!c	:35B:ISIN XXXXXXXXXXXX	• ISIN The literal ISIN followed by a space followed by the 12 character ISIN. Example: ISIN US1234567891 DTC does not accept Non-U.S. ISINs.
Optional Subsequence B1 Financial Instrument Attributes						
M	:16R:	FIA	Start of Block		:16R:FIA	
O	:92A:	:CUFC:	CMO Factor	:4!c//[N]15d	:92A::CUFC//00,000000000000	CMO factor.
M	:16S:	FIA	End of Block		:16S:FIA	
End of Subsequence B1 Financial Instrument Attributes						
M	:22F:	:PROC/DTCY	Business Transaction ID	:4!c/[8c]/4!c	:22F::PROC/DTCY/DO10	
O	:22F:	:RPOR/DTCY	Fail Tracking Indicator	:4!c/[8c]/4!c	:22F::RPOR/DTCY/DBLY or DBLN	Formerly known as Due Bill indicator Indicates whether due bills are carried on this issue. • DBLY - due bills are carried • DBLN - due bills are not carried If the field is blank, DBLY is assumed.
O	:70E:	:SPRO/	Narrative - DTC DO Comments	:4!c//10*35x	:70E::SPRO//xxxxxxxxxxxxxxxxetc. (The maximum length DTC accepts for this field is 210, 6 lines of 35 characters each.)	Comments Maximum DTCC length of 210.
M	:16S:	TRADDET	End of Block		:16S:TRADDET	
End of Sequence B Trade Details						
Mandatory Sequence C Financial Instrument/Account						

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
M	:16R:	FIAC	Start of Block		:16R:FIAC	
M	:36B:	:SETT	Quantity expressed as units	:4!c//4!c/15d	:36B::SETT//UNIT/0000000050000,0	Share quantity.
M	:97A:	:SAFE	Deliverers Account Number	:4!c//35x	:SAFE//xxxxxxxx	Deliverer DTCC participant number.
M	:16S:	FIAC	End of Block		:16S:FIAC	
End of Sequence C Financial Instrument/Account						
Mandatory Sequence E Settlement Details						
M	:16R:	SETDET	Start of Block		:16R:SETDET	
O	:22F:	STCO/DTCY	Settlement Today Only Indicator	:4!c/[8c]/4!c	:22F::STCO/DTCY/STOY or STON	Indicates if the transaction: • STOY - transaction can only settle on settlement date included in the 98A::SETT field. • STON - transaction can attempt the next settlement date if the current is already past the cutoff. IMS Reintroduce Profile is also overridden if the field is populated with an N. • space - transaction can attempt the next settlement date if the current is already past the cutoff. IMS Reintroduce Profile is not overridden if the transaction drops.
O	:22F:	STCO/DTCY	PTA Indicator	:4!c/[8c]/4!c	:22F::STCO/DTCY/PTAY or PTAN	Indicates if the transaction should affect the Protected Transaction Account. • PTAY - Should affect the account • PTAN - Should not affect the account

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
						If the field is blank, N is assumed.
M	:22F:	SETR/DTCYREAS	Reason Code	:4!c/[8c]/4!c	:22F::SETR/DTCYREAS/xxxx	Reason Code Padded to the left with zeroes
O	:22F:	SETS/DTCY	Prevent Pend	:4!c/[8c]/4!c	:22F::SETS/DTCY/PNDY or PNDN	Indicates if the transaction should be prevented from recycling. • PNDY - Do not permit recycling • PNDN - Allow recycling
Repetitive Mandatory Subsequence E1 Settlement Parties						
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95R:	DEAG/DTCYPART	Delivering Participant	:4!c/8c/34x	:95R::DEAG/DTCYPART/0000nnnn	DTCC Participant number for the deliverer.
O	:97A:	SAFE	Deliverers Account Number	:4!c//35x	:97A::SAFE//nnnnnnnnnnnnnnnn	Deliverer internal account number (maximum 35 bytes)
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95R:	REAG/DTCYPART	Receiving Participant	:4!c/8c/34x	:95R::REAG/DTCYPART/0000nnnn	DTCC Participant number for receiver.
O	:97A:	SAFE	Receivers Account Number	:4!c//35x	:97A::SAFE//nnnnnnnnnnnnnnnn	Receiver internal account number (maximum 35 bytes)
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95P:	:PSET	Place of Settlement	:4!c//4!a2!a2!c[3	:95P::PSET//DTCYUS33	DTCC BIC number.
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
End of Subsequence E1 Settlement Parties						
M	:16S:	SETDET	End of Block		:16S:SETDET	

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
End of Sequence E Settlement Details						

MT543 - VALUED SECURITY HOLDER TRACKED DELIVER ORDER

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
Mandatory Sequence A General Information						
M	:16R:	GENL	Start of Block		:16R:GENL	
M	:20C:	:SEME//	Senders Reference Number	:4!c//16x	:20C::SEME//xxxxxxxxxxxxxxxx	Senders reference number.
M	:23G:	NEWM	Message Function - New	4!c	:23G:NEWM	
Repetitive Optional Subsequence A1 Linkages (Used for reclaims only)						
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:RELA//	IMS TID	:4!c//16x	:20C::RELA//xxxxxxxxxxxxxxxx	IMS Transaction ID for transaction being reclaimed.
M	:16S:	LINK	End of Block		:16S:LINK	
Repetitive Optional Subsequence A1 Linkages (Used for Obligation Warehouse Delivery Orders)						
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:COMM//	Obligation Warehouse Control Number	:4!c//16x	:20C::COMM//xxxxxxxxxxxxxxxx	Obligation Warehouse Control Number for Obligation Warehouse Delivery Orders.
M	:16S:	LINK	End of Block		:16S:LINK	
End of Subsequence A1 Linkages						
M	:16S:	GENL	End of Block	:16S:GENL		
End of Sequence A General Information						
Mandatory Sequence B Trade Details						
M	:16R:	TRADDET	Start of Block		:16R:TRADDET	

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
M	:98A:	:SETT//	Settlement Date	:4!c//8!n	:98A::SETT//20060109	Settlement date.
M	:35B:	:ISIN	ISIN	ISIN1!e12!c	:35B:ISIN XXXXXXXXXXXX	• ISIN The literal ISIN followed by a space followed by the 12 character ISIN. Example: ISIN US1234567891 DTC does not accept Non-U.S. ISINs.
Optional Subsequence B1 Financial Instrument Attributes						
M	:16R:	FIA	Start of Block		:16R:FIA	
O	:92A:	:CUFC:	CMO Factor	:4!c//[N]15d	:92A::CUFC//00,000000000000	CMO factor.
M	:16S:	FIA	End of Block		:16S:FIA	
End of Subsequence B1 Financial Instrument Attributes						
M	:22F:	:PROC/DTCY	Business Transaction ID	:4!c/[8c]/4!c	:22F::PROC/DTCY/DO09	
O	:22F:	:RPOR/DTCY	Fail Tracking Indicator	:4!c/[8c]/4!c	:22F::RPOR/DTCY/DBLY or DBLN	Formerly known as Due Bill indicator. Indicates whether due bills are carried on this issue. • DBLY - due bills are carried • DBLN - due bills are not carried If the field is blank, DBLY is assumed.
O	:70E:	:SPRO/	Narrative - DTC DO Comments	:4!c//10*35x	:70E::SPRO//xxxxxxxxxxxxxxxxetc. (The maximum length DTC accepts for this field is 210, 6 lines of 35 characters each.)	Comments Maximum DTCC length of 210.
M	:16S:	TRADDET	End of Block		:16S:TRADDET	
End of Sequence B Trade Details						

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
Mandatory Sequence C Financial Instrument/Account						
M	:16R:	FIAC	Start of Block		:16R:FIAC	
M	:36B:	:SETT	Quantity expressed as units	:4!c//4!c/15d	:36B::SETT//UNIT/0000000050000,0	Share quantity.
M	:97A:	:SAFE	Deliverers Account Number	:4!c//35x	:SAFE//xxxxxxxx	Deliverer DTCC participant number.
M	:16S:	FIAC	End of Block		:16S:FIAC	
End of Sequence C Financial Instrument/Account						
Mandatory Sequence E Settlement Details						
M	:16R:	SETDET	Start of Block		:16R:SETDET	
O	:22F:	STCO/DTCY	Settlement Today Only Indicator	:4!c/[8c]/4!c	:22F::STCO/DTCY/STOY or STON	Indicates if the transaction: • STOY - transaction can only settle on settlement date included in the 98A::SETT field. • STON - transaction can attempt the next settlement date if the current is already past the cutoff. IMS Reintroduce Profile is also overridden if the field is populated with an N. • space - transaction can attempt the next settlement date if the current is already past the cutoff. IMS Reintroduce Profile is not overridden if the transaction drops.
O	:22F:	STCO/DTCY	PTA Indicator	:4!c/[8c]/4!c	:22F::STCO/DTCY/PTAY or PTAN	Indicates if the transaction should affect the Protected Transaction Account. • PTAY - Should affect the account.

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
						• PTAN - Should not affect the account. If the field is blank, N is assumed.
M	:22F:	SETR/DTCYREAS	Reason Code	:4!c/[8c]/4!c	:22F::SETR/DTCYREAS/xxxx	Reason Code Padded to the left with zeroes
O	:22F:	SETS/DTCY	Prevent Pend	:4!c/[8c]/4!c	:22F::SETS/DTCY/PNDY or PNDN	Indicates if the transaction should be prevented from recycling. • PNDY - Do not permit recycling • PNDN - Allow recycling
Repetitive Mandatory Subsequence E1 Settlement Parties						
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95R:	DEAG/DTCYPART	Delivering Participant	:4!c/8c/34x	:95R::DEAG/DTCYPART/0000nnnn	DTCC Participant number for the deliverer.
O	:97A:	SAFE	Deliverers Account Number	:4!c//35x	:97A::SAFE//nnnnnnnnnnnnnnnn	Deliverer internal account number (maximum 35 bytes)
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95R:	REAG/DTCYPART	Receiving Participant	:4!c/8c/34x	:95R::REAG/DTCYPART/0000nnnn	DTCC Participant number for receiver
O	:97A:	SAFE	Receivers Account Number	:4!c//35x	:97A::SAFE//nnnnnnnnnnnnnnnn	Receiver internal account number (maximum 35 bytes)
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95P:	:PSET	Place of Settlement	:4!c//4!a2!a2!c[3!c]	:95P::PSET//DTCYUS33	DTCC BIC number.

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
End of Subsequence E1 Settlement Parties						
Repetitive Mandatory Subsequence E3 Amounts						
M	:16R:	AMT	Start of Block		:16R:AMT	
M	:19A:	SETT//	Settlement Amount	:4!c//[N]3!a15d	:19A::SETT//USD000000000000,00	Settlement amount.
M	:16S:	AMT	End of Block		:16S:AMT	
End of Subsequence E3 Amounts						
M	:16S:	SETDET	End of Block		:16S:SETDET	
End of Sequence E Settlement Details						

© 2022 DTCC. All rights reserved. DTCC, DTCC (Stylized), ADVANCING FINANCIAL MARKETS. TOGETHER, and the Interlocker graphic are registered and unregistered trademarks of The Depository Trust & Clearing Corporation.

The services described herein are provided under the DTCC brand name by certain affiliates of The Depository Trust & Clearing Corporation (DTCC). DTCC itself does not provide such services. Each of these affiliates is a separate legal entity, subject to the laws and regulations of the particular country or countries in which such entity operates. Please see www.dtcc.com for more information on DTCC, its affiliates and the services they offer.

Doc Date: August 31, 2022
Publication Code: OW147
Service: Obligation Warehouse
Title: ISO DO Input Message Layouts (MT542, MT543)

FOR MORE INFORMATION

Email DTCC Learning at:
DTCCLearning@dtcc.com

or visit us on the web at:
www.dtcclearning.com