OBLIGATION WAREHOUSE

ISO DO OUTPUT MESSAGE LAYOUTS

JULY 9, 2008



TABLE OF CONTENTS

MT544: Receive Free Confirmation 3

MT545: Receive Against Payment Confirmation 7

MT546: Deliver Free Confirmation 11

MT547: Deliver Against Payment Confirmation 15

MT548: Settlement Status (Long Version) 19

MT548: Settlement Status (SHORT version) 24

MT548: Settlement Status 26

Codes 27

MT544: RECEIVE FREE CONFIRMATION

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
Mandatory Sequence A General Information						
M	:16R:	GENL	Start of Block		:16R:GENL	
M	:20C:	:SEME//	CDTS Tracking Number	:4!c//16x	:20C::SEME//xxxxxxxxxxxxxxxx	DTCC Generated, used to track transaction from submission to final state.
M	:23G:	NEWM	Message Function - New	4!c	:23G:NEWM	Identifies the function of the message.
O	:98C:	:PREP//	Transaction Update Date/Time	:4!c//8!n6!n	:98C::PREP//yyyymmddhhmmss	Date/time at which message was prepared.
Repetitive Mandatory Subsequence A1 Linkages						
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:RELA//	IMS Transaction ID	:4!c//16x	:20C::RELA//xxxxxxxxxxxxxxxx	IMS generated - used to track/update transaction from the time it is processed in IMS to final state.
M	:16S:	LINK	End of Block		:16S:LINK	
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:COMM//	ID Control Number	:4!c//16x	:20C::COMM//xxxxxxxxxxxxxxxx	ITP generated - used to identify, link. and update ID transactions.
M	:16S:	LINK	End of Block		:16S:LINK	
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:COMM//	Obligation Warehouse Control Number	:4!c//16x	:20C::COMM//xxxxxxxxxxxxxxxx	Obligation Warehouse Control Number for Obligation Warehouse DOs.

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
M	:16S:	LINK	End of Block		:16S:LINK	
M	:16R:	LINK	Start of Block		:16R:LINK	Only for Reclaimed transactions.
M	:20C:	:PREV//	IMS TID of Reclaimed trans	:4!c//16x	:20C::PREV//xxxxxxxxxxxxxxxx	Only for Reclaimed transactions
M	:16S:	LINK	End of Block		:16S:LINK	Only for Reclaimed transactions
End of Subsequence A1 Linkages						
M	:16S	GENL	End of Block		:16S:GENL	
End of Sequence A General Information						
Mandatory Sequence B Trade Details						
M	:16R:	TRADDET	Start of Block		:16R:TRADDET	
O	:98A:	:SETT//	Original Settlement Date	:4!c//8!n	:98A::SETT//yyyymmdd	Date at which the transaction is suppose to be settled on.
O	:98A:	:TRAD//	Contract/Trade Date	:4!c//8!n	:98A::TRAD//yyyymmdd	SPO, PPO, and IPO only.
M	:98A:	:ESET//	Actual Settlement Date	:4!c//8!n	:98A::ESET//yyyymmdd	Date at which the transaction was actually settled on.
M	:35B:	ISIN	ISIN	ISIN1!e12!c	:35B:ISIN XXXXXXXXXXXX	Country Code, CUSIP and Check Digit DTC does not accept Non-U.S. ISINs.
Optional Subsequence B1 Financial Instrument Attributes						
M	:16R:	FIA	Start of Block		:16R:FIA	
O	:92A:	:CUFC//	CMO Factor	:4!c//[N]15d	:92A::CUFC//00,000000000000	DO only
M	:16S:	FIA	End of Block		:16S:FIA	
End of Subsequence B1 Financial Instrument Attributes						
O	:22F:	:RPOR/DTCY/	Fail Tracking Indicator	:4!c/[8c]/4!c	:22F::RPOR/DTCY/DBLY or DBLN	DO only. Formerly known as Due Bill Indicator.

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
O	:70E:	:SPRO//	Narrative - DTC DO Comments	:4!c//10*35x	:70E::SPRO//xxxxxxxxxxxxxxxxetc.	
M	:16S:	TRADDET	End of Block		:16S:TRADDET	
End of Sequence B Trade Details						
Mandatory Sequence C Financial Instrument/Account						
M	:16R:	FIAC	Start of Block		:16R:FIAC	
M	:36B:	:ESTT//	Quanity expressed as units	:4!c//4!c/15d	:36B::ESTT//UNIT/0000000050000,0	Shares associated with ISIN, must be greater than zero.
M	:97A:	:SAFE//	Safekeeper	:4!c//35x	:97A::SAFE//xxxxxxxxxxxxxxxxetc.	Identifies account where financial instruments are maintained.
M	:16S:	FIAC	End of Block		:16S:FIAC	
End of Sequence C Financial Instrument/Account						
Mandatory Sequence E Settlement Details						
M	:16R:	SETDET	Start of Block		:16R:SETDET	
O	:22F:	STCO/DTCY	PTA Indicator	:4!c/[8c]/4!c	:22F::STCO/DTCY/PTAY or PTAN	DO only.
O	:22F:	STCO/DTCY	Activity Code	:4!c/[8c]/4!c	:22F::STCO/DTCYACTV/xxx	Activity Code of the transaction.
M	:22F:	SETR/DTCYREAS	Reason Code	:4!c/[8c]/4!c	:22F::SETR/DTCYREAS/xxxx	Reason Code of the transaction.
Repetitive Mandatory Subsequence E1 Settlement Parties						
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95R:	:DEAG/	Deliverer (Payee)	:4!c/8c/34x	:95R::DEAG/DTCYPART/0000nnnn	Delivering Participant
O	:97A:	:SAFE//	Deliverers Account Number	:4!c//35x	:97A::SAFE//nnnnnnnnnnnnnnnn	Deliverer Account Number
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
M	:95R:	:REAG/	Receiver (Payor)	:4!c/8c/34x	:95R::REAG/DTCYPART/0000nnnn	Receiving Participant
O	:97A:	:SAFE//	Receivers Account Number	:4!c//35x	:97A::SAFE//nnnnnnnnnnnnnnnn	Receiver Account Number
O	:20C:	:PROC//	Receivers Serial Number	:4!c//16x	:20C::PROC//nnnnnnn	Receiver Serial Number
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95Q:	:PSET//	Place of Settlement	:4!c//4*35x	:95Q::PSET//DTCYUS33	Place of Settlement
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
End of Subsequence E1 Settlement Parties						
Repetitive Mandatory Subsequence E3 Amounts						
M	:16R:	AMT	Start of Block		:16R:AMT	
M	:19A:	:ESTT//	Settlement Amount	:4!c//[N]3!a15d	:19A::ESTT//USD000000000000,00	Dollar Amount that was settled with regards to this transaction – is always zero.
M	:16S:	AMT	End of Block		:16S:AMT	
End of Subsequence E3 Amounts						
M	:16S:	SETDET	End of Block		:16S:SETDET	
End of Sequence E Settlement Details						
Repetitive Optional Sequence F Other Parties						
M	:16R:	OTHRPRTY	Start of Block		:16R:OTHRPRTY	
M	:95R:	:TRAG/	Third Party	:4!c/8c/34x	:95R::TRAG/DTCYPART/0000nnnn	Depository Third Party field is displayed if the receiver number = 719.
M	:16S:	OTHRPRTY	End of Block		:16S:OTHRPRTY	

MT545: RECEIVE AGAINST PAYMENT CONFIRMATION

M/O	Tag	Block/ Qualifier	Field Description	Data Field Format	Example	Description
Mandatory Sequence A General Information						
M	:16R:	GENL	Start of Block		:16R:GENL	
M	:20C:	:SEME//	CDTS Tracking Number	:4!c//16x	:20C::SEME//xxxxxxxxxxxxxxx	DTCC Generated, used to track transaction from submission to final state.
M	:23G:	NEWM	Message Function - New	4!c	:23G:NEWM	This field identifies the function of the message.
O	:98C:	:PREP//	Transaction Update Date/Time	:4!c//8!n6!n	:98C::PREP//yyyymmddhhmmss	Date/time at which message was prepared.
Repetitive Mandatory Subsequence A1 Linkages						
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:RELA//	IMS Transaction ID	:4!c//16x	:20C::RELA//xxxxxxxxxxxxxxx	IMS generated - used to track/update transaction from the time it is processed in IMS to final state.
M	:16S:	LINK	End of Block		:16S:LINK	
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:COMM//	ID Control Number	:4!c//16x	:20C::COMM//xxxxxxxxxxxxxxx	ITP generated - used to identify, link and update ID transactions.
M	:16S:	LINK	End of Block		:16S:LINK	
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:COMM//	Obligation Warehouse Control Number	:4!c//16x	:20C::COMM//xxxxxxxxxxxxxxx	Obligation Warehouse Control Number for Obligation Warehouse DOs.

M/O	Tag	Block/ Qualifier	Field Description	Data Field Format	Example	Description
M	:16S:	LINK	End of Block		:16S:LINK	
M	:16R:	LINK	Start of Block		:16R:LINK	Only for Reclaimed transactions.
M	:20C:	:PREV//	IMS TID of Reclaimed trans	:4!c//16x	:20C::PREV//xxxxxxxxxxxxxxxx	Only for Reclaimed transactions.
M	:16S:	LINK	End of Block		:16S:LINK	Only for Reclaimed transactions.
End of Subsequence A1 Linkages						
M	:16S	GENL	End of Block		:16S:GENL	
End of Sequence A General Information						
Mandatory Sequence B Trade Details						
M	:16R:	TRADDET	Start of Block		:16R:TRADDET	
O	:98A:	:SETT//	Original Settlement Date	:4!c//8!n	:98A::SETT//yyyymmdd	Date at which the transaction is suppose to be settled on.
O	:98A:	:TRAD//	Contract/Trade Date	:4!c//8!n	:98A::TRAD//yyyymmdd	SPO, PPO, and IPO only.
M	:98A:	:ESET//	Actual Settlement Date	:4!c//8!n	:98A::ESET//yyyymmdd	Date at which the transaction was actually settled on
M	:35B:	ISIN	ISIN	ISIN1!e12!c	:35B:ISIN XXXXXXXXXXXX	Country Code, CUSIP and Check Digit DTC does not accept Non-U.S. ISINs.
Optional Subsequence B1 Financial Instrument Attributes						
M	:16R:	FIA	Start of Block		:16R:FIA	
O	:92A:	:CUFC:	CMO Factor	:4!c//[N]15d	:92A::CUFC//00,000000000000	DO only
M	:16S:	FIA	End of Block		:16S:FIA	
End of Subsequence B1 Financial Instrument Attributes						
O	:22F:	:RPOR/DTCY	Fail Tracking Indicator	:4!c/[8c]/4!c	:22F::RPOR/DTCY/DBLY or DBLN	DO only. Formerly known as Due Bill Indicator.

M/O	Tag	Block/ Qualifier	Field Description	Data Field Format	Example	Description
O	:70E:	:SPRO//	Narrative - DTC DO Comments	:4!c//10*35x	:70E::SPRO//xxxxxxxxxxxxxxxxetc.	
M	:16S:	TRADDET	End of Block		:16S:TRADDET	
End of Sequence B Trade Details						
Mandatory Sequence C Financial Instrument/Account						
M	:16R:	FIAC	Start of Block		:16R:FIAC	
M	:36B:	:ESTT//	Quanity expressed as units	:4!c//4!c/15d	:36B::ESTT//UNIT/0000000050000,0	Shares associated with ISIN, must be greater than zero.
M	:97A:	:SAFE//	Safekeeper	:4!c//35x	:97A::SAFE//xxxxxxxxxxxxxxxxetc.	Identifies account where financial instruments are maintained.
M	:16S:	FIAC	End of Block		:16S:FIAC	
End of Sequence C Financial Instrument/Account						
Mandatory Sequence E Settlement Details						
M	:16R:	SETDET	Start of Block		:16R:SETDET	
O	:22F:	STCO/DTCY	PTA Indicator	:4!c/[8c]/4!c	:22F::STCO/DTCY/PTAY or PTAN	DO only
O	:22F:	STCO/DTCY	Activity Code	:4!c/[8c]/4!c	:22F::STCO/DTCYACTV/xxx	Activity Code of the transaction.
M	:22F:	SETR/DTCYREAS	Reason Code	:4!c/[8c]/4!c	:22F::SETR/DTCYREAS/xxxx	Reason Code of the transaction.
Repetitive Mandatory Subsequence E1 Settlement Parties						
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95R:	:DEAG/	Deliverer (Payee)	:4!c/8c/34x	:95R::DEAG/DTCYPART/0000nnnn	Delivering Participant
O	:97A:	:SAFE//	Deliverers Account Number	:4!c//35x	:97A::SAFE//nnnnnnnnnnnnnnnn	Deliverer Account Number
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95R:	:REAG/	Receiver (Payor)	:4!c/8c/34x	:95R::REAG/DTCYPART/0000nnnn	Receiving Participant

M/O	Tag	Block/ Qualifier	Field Description	Data Field Format	Example	Description
O	:97A:	:SAFE//	Receivers Account Number	:4!c//35x	:97A::SAFE//nnnnnnnnnnnnnnnn	Receiver Account Number
O	:20C:	:PROC//	Receivers Serial Number	:4!c//16x	:20C::PROC//nnnnnnn	Receiver Serial Number
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95Q:	:PSET	Place of Settlement	:4!c//4*35x	:95Q::PSET//DTCYUS33	Place of Settlement
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
End of Subsequence E1 Settlement Parties						
Repetitive Mandatory Subsequence E3 Amounts						
M	:16R:	AMT	Start of Block		:16R:AMT	
M	:19A:	:ESTT//	Settlement Amount	:4!c//[N]3!a15d	:19A::ESTT//USD000000000000,00	Dollar Amount that was settled with regards to this transaction - is always greater than zero.
M	:16S:	AMT	End of Block		:16S:AMT	
End of Subsequence E3 Amounts						
M	:16S:	SETDET	End of Block		:16S:SETDET	
End of Sequence E Settlement Details						
Repetitive Optional Sequence F Other Parties						
M	:16R:	OTHRPRTY	Start of Block		:16R:OTHRPRTY	
M	:95R:	:TRAG/	Third Party	:4!c/8c/34x	:95R::TRAG/DTCYPART/0000nnnn	Depository Third Party field is displayed if the receiver number = 719.
M	:16S:	OTHRPRTY	End of Block		:16S:OTHRPRTY	

MT546: DELIVER FREE CONFIRMATION

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
Mandatory Sequence A General Information						
M	:16R:	GENL	Start of Block		:16R:GENL	
M	:20C:	:SEME//	CDTS Tracking Number	:4!c//16x	:20C::SEME//xxxxxxxxxxxxxxxx	DTCC Generated, used to track transaction from submission to final state.
M	:23G:	NEWM	Message Function - New	4!c	:23G:NEWM	This field identifies the function of the message.
O	:98C:	:PREP//	Transaction Update Date/Time	:4!c//8!n6!n	:98C::PREP//yyyymmddhhmmss	Date/time at which message was prepared.
Repetitive Mandatory Subsequence A1 Linkages						
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:RELA//	IMS Transaction ID	:4!c//16x	:20C::RELA//xxxxxxxxxxxxxxxx	IMS generated - used to track/update transaction from the time it is processed in IMS to final state.
M	:16S:	LINK	End of Block		:16S:LINK	
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:COMM//	ID Control Number	:4!c//16x	:20C::COMM//xxxxxxxxxxxxxxxx	ITP generated - used to identify, link and update ID transactions.
M	:16S:	LINK	End of Block		:16S:LINK	
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:COMM//	Obligation Warehouse Control Number	:4!c//16x	:20C::COMM//xxxxxxxxxxxxxxxx	Obligation Warehouse Control Number for Obligation Warehouse DOs.
M	:16S:	LINK	End of Block		:16S:LINK	
M	:16R:	LINK	Start of Block		:16R:LINK	

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
M	:20C:	:TRRF//	Deliverer's Reference Number	:4!c//16x	:20C::TRRF//xxxxxxxxxxxxxxx	Assigned by deliverer for audit trail.
M	:16S:	LINK	End of Block		:16S:LINK	
M	:16R:	LINK	Start of Block		:16R:LINK	Only for Reclaimed transactions.
M	:20C:	:PREV//	IMS TID of Reclaimed trans	:4!c//16x	:20C::PREV//xxxxxxxxxxxxxxx	Only for Reclaimed transactions
M	:16S:	LINK	End of Block		:16S:LINK	Only for Reclaimed transactions
End of Subsequence A1 Linkages						
M	:16S	GENL	End of Block		:16S:GENL	
End of Sequence A General Information						
Mandatory Sequence B Trade Details						
M	:16R:	TRADDET	Start of Block		:16R:TRADDET	
O	:98A:	:SETT//	Original Settlement Date	:4!c//8!n	:98A::SETT//yyyymmdd	Date at which the transaction is suppose to be settled on.
O	:98A:	:TRAD//	Contract/Trade Date	:4!c//8!n	:98A::TRAD//yyyymmdd	SPO, PPO, and IPO only.
M	:98A:	:ESET//	Actual Settlement Date	:4!c//8!n	:98A::ESET//yyyymmdd	Date at which the transaction was actually settled on.
M	:35B:	ISIN	ISIN	ISIN1!e12!c	:35B:ISIN XXXXXXXXXXXX	Country Code, CUSIP and Check Digit DTC does not accept Non-U.S. ISINs.
Optional Subsequence B1 Financial Instrument Attributes						
M	:16R:	FIA	Start of Block		:16R:FIA	
O	:92A:	:CUFC:	CMO Factor	:4!c//[N]15d	:92A::CUFC//00,000000000000	DO only
M	:16S:	FIA	End of Block		:16S:FIA	
End of Subsequence B1 Financial Instrument Attributes						
O	:22F:	:RPOR/DTCY	Fail Tracking Indicator	:4!c/[8c]/4!c	:22F::RPOR/DTCY/DBLY or DBLN	DO only Formerly known as Due Bill Indicator.

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
O	:70E:	:SPRO//	Narrative - DTC DO Comments	:4!c//10*35x	:70E::SPRO//xxxxxxxxxxxxxxxxetc.	
M	:16S:	TRADDET	End of Block		:16S:TRADDET	
End of Sequence B Trade Details						
Mandatory Sequence C Financial Instrument/Account						
M	:16R:	FIAC	Start of Block		:16R:FIAC	
M	:36B:	:ESTT//	Quanity expressed as units	:4!c//4!c/15d	:36B::ESTT//UNIT/0000000050000,0	Shares associated with ISIN, must be greater than zero.
M	:97A:	:SAFE//	Safekeeper	:4!c//35x	:97A::SAFE//xxxxxxxxxxxxxxxxetc.	Identifies account where financial instruments are maintained.
M	:16S:	FIAC	End of Block		:16S:FIAC	
End of Sequence C Financial Instrument/Account						
Mandatory Sequence E Settlement Details						
M	:16R:	SETDET	Start of Block		:16R:SETDET	
O	:22F:	STCO/DTCY	PTA Indicator	:4!c/[8c]/4!c	:22F::STCO/DTCY/PTAY or PTAN	DO only
O	:22F:	STCO/DTCY	Activity Code	:4!c/[8c]/4!c	:22F::STCO/DTCYACTV/xxx	Activity Code of the transaction.
M	:22F:	SETR/DTCYREAS	Reason Code	:4!c/[8c]/4!c	:22F::SETR/DTCYREAS/xxxx	Reason Code of the transaction.
Repetitive Mandatory Subsequence E1 Settlement Parties						
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95R:	:DEAG/	Deliverer (Payee)	:4!c/8c/34x	:95R::DEAG/DTCYPART/0000nnnn	Delivering Participant
O	:97A:	:SAFE//	Deliverers Account Number	:4!c//35x	:97A::SAFE//nnnnnnnnnnnnnnnn	Deliverer Account Number
O	:20C:	:PROC//	Deliverers Serial Number	:4!c//16x	:20C::PROC//nnnnnnn	Deliverers Serial Number
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95R:	:REAG/	Receiver (Payor)	:4!c/8c/34x	:95R::REAG/DTCYPART/0000nnnn	Receiving Participant
O	:97A:	:SAFE//	Receivers Account Number	:4!c//35x	:97A::SAFE//nnnnnnnnnnnnnnnn	Receiver Account Number
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95Q:	:PSET	Place of Settlement	:4!c//4*35x	:95Q::PSET//DTCYUS33	Place of Settlement
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
End of Subsequence E1 Settlement Parties						
Repetitive Mandatory Subsequence E3 Amounts						
M	:16R:	AMT	Start of Block		:16R:AMT	
M	:19A:	:ESTT//	Settlement Amount	:4!c//[N]3!a15d	:19A::ESTT//USD000000000000,00	Dollar Amount that was settled with regards to this transaction - is always zero.
M	:16S:	AMT	End of Block		:16S:AMT	
End of Subsequence E3 Amounts						
M	:16S:	SETDET	End of Block		:16S:SETDET	
End of Sequence E Settlement Details						
Repetitive Optional Sequence F Other Parties						
M	:16R:	OTHRPRTY	Start of Block		:16R:OTHRPRTY	
M	:95R:	:TRAG/	Third Party	:4!c/8c/34x	:95R::TRAG/DTCYPART/0000nnnn	Depository Third Party field is displayed if the deliverer number = 919.
M	:16S:	OTHRPRTY	End of Block		:16S:OTHRPRTY	

MT547: DELIVER AGAINST PAYMENT CONFIRMATION

M/O	Tag	Block/ Qualifier	Field Description	Data Field Format	Example	Description
Mandatory Sequence A General Information						
M	:16R:	GENL	Start of Block		:16R:GENL	
M	:20C:	:SEME//	CDTS Tracking Number	:4!c//16x	:20C::SEME//xxxxxxxxxxxxxxxx	DTCC Generated, used to track transaction from submission to final state.
M	:23G:	NEWM	Message Function - New	4!c	:23G:NEWM	This field identifies the function of the message.
O	:98C:	:PREP//	Transaction Update Date/Time	:4!c//8!n6!n	:98C::PREP//yyyymmddhhmmss	Date/time at which message was prepared.
Repetitive Mandatory Subsequence A1 Linkages						
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:RELA//	IMS Transaction ID	:4!c//16x	:20C::RELA//xxxxxxxxxxxxxxxx	IMS generated - used to track/update transaction from the time it is processed in IMS to final state.
M	:16S:	LINK	End of Block		:16S:LINK	
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:COMM//	ID Control Number	:4!c//16x	:20C::COMM//xxxxxxxxxxxxxxxx	ITP generated - used to identify, link and update ID transactions.
M	:16S:	LINK	End of Block		:16S:LINK	
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:COMM//	Obligation Warehouse Control Number	:4!c//16x	:20C::COMM//xxxxxxxxxxxxxxxx	Obligation Warehouse Control Number for Obligation Warehouse DOs.
M	:16S:	LINK	End of Block		:16S:LINK	
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:TRRF//	Deliverer's Reference Number	:4!c//16x	:20C::TRRF//xxxxxxxxxxxxxxxx	Assigned by deliverer for audit trail.

M/O	Tag	Block/ Qualifier	Field Description	Data Field Format	Example	Description
M	:16S:	LINK	End of Block		:16S:LINK	
M	:16R:	LINK	Start of Block		:16R:LINK	Only for Reclaimed transactions.
M	:20C:	:PREV//	IMS TID of Reclaimed trans	:4!c//16x	:20C::PREV//xxxxxxxxxxxxxxx	Only for Reclaimed transactions.
M	:16S:	LINK	End of Block		:16S:LINK	Only for Reclaimed transactions.
End of Subsequence A1 Linkages						
M	:16S	GENL	End of Block		:16S:GENL	
End of Sequence A General Information						
Mandatory Sequence B Trade Details						
M	:16R:	TRADDET	Start of Block		:16R:TRADDET	
O	:98A:	:SETT//	Original Settlement Date	:4!c//8!n	:98A::SETT//yyyymmdd	Date at which the transaction is suppose to be settled on.
O	:98A:	:TRAD//	Contract/Trade Date	:4!c//8!n	:98A::TRAD//yyyymmdd	SPO, PPO, and IPO only.
M	:98A:	:ESET//	Actual Settlement Date	:4!c//8!n	:98A::ESET//yyyymmdd	Date at which the transaction was actually settled on.
M	:35B:	ISIN	ISIN	ISIN1!e12!c	:35B:ISIN XXXXXXXXXXXX	Country Code, CUSIP and Check Digit DTC does not accept Non-U.S. ISINs.
Optional Subsequence B1 Financial Instrument Attributes						
M	:16R:	FIA	Start of Block		:16R:FIA	
O	:92A:	:CUFC:	CMO Factor	:4!c//[N]15d	:92A::CUFC//00,000000000000	DO only
M	:16S:	FIA	End of Block		:16S:FIA	
End of Subsequence B1 Financial Instrument Attributes						
O	:22F:	:RPOR/DTCY	Fail Tracking Indicator	:4!c/[8c]/4!c	:22F::RPOR/DTCY/DBLY or DBLN	DO only. Formerly known as Due Bill Indicator.
O	:70E:	:SPRO//	Narrative - DTC DO Comments	:4!c//10*35x	:70E::SPRO//xxxxxxxxxxxxxxxxetc.	

M/O	Tag	Block/ Qualifier	Field Description	Data Field Format	Example	Description
M	:16S:	TRADDET	End of Block		:16S:TRADDET	
End of Sequence B Trade Details						
Mandatory Sequence C Financial Instrument/Account						
M	:16R:	FIAC	Start of Block		:16R:FIAC	
M	:36B:	:ESTT//	Quanity expressed as units	:4!c//4!c/15d	:36B::ESTT//UNIT/0000000050000,0	Shares associated with ISIN, must be greater than zero.
M	:97A:	:SAFE//	Safekeeper	:4!c//35x	:97A::SAFE//xxxxxxxxxxxxxxxxxxetc.	Identifies account where financial instruments are maintained.
M	:16S:	FIAC	End of Block		:16S:FIAC	
End of Sequence C Financial Instrument/Account						
Mandatory Sequence E Settlement Details						
M	:16R:	SETDET	Start of Block		:16R:SETDET	
O	:22F:	STCO/DTCY	PTA Indicator	:4!c/[8c]/4!c	:22F::STCO/DTCY/PTAY or PTAN	DO only
O	:22F:	STCO/DTCY	Activity Code	:4!c/[8c]/4!c	:22F::STCO/DTCYACTV/xxx	Activity Code of the transaction.
M	:22F:	SETR/DTCYREAS	Reason Code	:4!c/[8c]/4!c	:22F::SETR/DTCYREAS/xxxx	Reason Code of the transaction.
Repetitive Mandatory Subsequence E1 Settlement Parties						
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95R:	:DEAG/	Deliverer (Payee)	:4!c/8c/34x	:95R::DEAG/DTCYPART/0000nnnn	Delivering Participant
O	:97A:	:SAFE//	Deliverers Account Number	:4!c//35x	:97A::SAFE//nnnnnnnnnnnnnnnn	Deliverer Account Number
O	:20C:	:PROC//	Deliverers Serial Number	:4!c//16x	:20C::PROC//nnnnnnn	Deliverers Serial Number
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95R:	:REAG/	Receiver (Payor)	:4!c/8c/34x	:95R::REAG/DTCYPART/0000nnnn	Receiving Participant

M/O	Tag	Block/ Qualifier	Field Description	Data Field Format	Example	Description
O	:97A:	:SAFE//	Receivers Account Number	:4!c//35x	:97A::SAFE//nnnnnnnnnnnnnnnn	Receiver Account Number
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95Q:	:PSET	Place of Settlement	:4!c//4*35x	:95Q::PSET//DTCYUS33	Place of Settlement
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
End of Subsequence E1 Settlement Parties						
Repetitive Mandatory Subsequence E3 Amounts						
M	:16R:	AMT	Start of Block		:16R:AMT	
M	:19A:	:ESTT//	Settlement Amount	:4!c//[N]3!a15d	:19A::ESTT//USD000000000000,00	Dollar Amount that was settled with regards to this transaction - is always greater than zero.
M	:16S:	AMT	End of Block		:16S:AMT	
End of Subsequence E3 Amounts						
M	:16S:	SETDET	End of Block		:16S:SETDET	
End of Sequence E Settlement Details						
Repetitive Optional Sequence F Other Parties						
M	:16R:	OTHRPRTY	Start of Block		:16R:OTHRPRTY	
M	:95R:	:TRAG/	Third Party	:4!c/8c/34x	:95R::TRAG/DTCYPART/0000nnnn	Depository Third Party field is displayed if the deliverer number = 919.
M	:16S:	OTHRPRTY	End of Block		:16S:OTHRPRTY	

MT548: SETTLEMENT STATUS (LONG VERSION)

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
Mandatory Sequence A General Information						
M	:16R:	GENL	Start of Block		:16R:GENL	
M	:20C:	:SEME//	CDTS Tracking Number	:4!c//16x	:20C::SEME//xxxxxxxxxxxxxxxx	DTCC Generated, used to track transaction from submission to final state.
M	:23G:	INST	Message Function - INST	4!c[/4!c]	:23G:INST	This field identifies the function of the message.
M	:98C:	:PREP//	Transaction Update Date/Time	:4!c//8!n6!n	:98C::PREP//yyyymmddhhmmss	Date/time at which message was prepared.
Repetitive Mandatory Subsequence A1 Linkages						
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:RELA//	IMS Transaction ID	:4!c//16x	:20C::RELA//xxxxxxxxxxxxxxxx	IMS generated - used to track/update transaction from the time it is processed in IMS to final state.
M	:16S:	LINK	End of Block		:16S:LINK	
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:COMM//	ID Control Number	:4!c//16x	:20C::COMM//xxxxxxxxxxxxxxxx	ITP generated - used to identify, link and update ID transactions.
M	:16S:	LINK	End of Block		:16S:LINK	
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:COMM//	Obligation Warehouse Control Number	:4!c//16x	:20C::COMM//xxxxxxxxxxxxxxxx	Obligation Warehouse Control Number for Obligation Warehouse DOs.
M	:16S:	LINK	End of Block		:16S:LINK	
M	:16R:	LINK	Start of Block		:16R:LINK	

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
M	:20C:	:TRRF//	Deliverer's Reference Number	:4!c//16x	:20C::TRRF//xxxxxxxxxxxxxxx	Assigned by the deliverer for audit trail. Displayed only if you are the deliverer.
M	:16S:	LINK	End of Block		:16S:LINK	
M	:16R:	LINK	Start of Block		:16R:LINK	Only for Reclaimed transactions.
M	:20C:	:PREV//	IMS TID of Reclaimed trans	:4!c//16x	:20C::PREV//xxxxxxxxxxxxxxx	Only for Reclaimed transactions.
M	:16S:	LINK	End of Block		:16S:LINK	Only for Reclaimed transactions.
End of Subsequence A1 Linkages						
Repetitive Mandatory Subsequence A2 Status						
M	:16R:	STAT	Start of Block		:16R:STAT	
M	:25D:	SETT/	Status Code	:4!c/[8c]/4!c	:25D:SETT/DTCY/AUTH, SUBA, etc.	IMS or ATP State, states are assigned as transaction is processed through IMS and ATP.
Repetitive Optional Subsequence A2a Reason						
M	:16R:	REAS	Start of Block		:16R:REAS	
M	:24B:	:REJT/	CAND, PEND, REJT, or PENF	:4!c/[8c]/4!c	:24B::REJT/DTCY/xxxx	The IMS or ATP State that falls under the category of Cancelled, Pending, Rejected, or Dropped.
O	:70D:	:REAS//	Error message	:4!c//6*35x	:70D::REAS//xxxxxxxxxxxxxxxxetc.	Provides explanation for the reject, pend, drop, or cancel.
M	:16S:	REAS	End of Block		:16S::REAS	
End of Subsequence A2a Reason						
M	:16S:	STAT	End of Block		:16S:STAT	
End of Subsequence A2 Status						
M	:16S:	GENL	End of Block		:16S:GENL	

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
End of Sequence A General Information						
Optional Sequence B Settlement Transaction Details						
M	:16R:	SETTRAN	Start of Block		:16R:SETTRAN	
M	:35B:	ISIN	ISIN	ISIN1!e12!c	:35B:ISIN XXXXXXXXXXXX	Country Code, CUSIP and Check Digit DTC does not accept Non-U.S. ISINs.
M	:36B:	:SETT//	Quanity expressed as units	:4!c//4!c/15d	:36B::SETT//UNIT/0000000050000,0	Shares associated with ISIN, must be greater than zero.
O	:19A:	:SETT//	Settlement Amount	:4!c//[N]3!a15d	:19A::SETT//USD000000000000,00	Dollar Amount associated with ISIN.
M	:97A:	:SAFE//	Safekeeper	:4!c//35x	:97A::SAFE//xxxxxxxxxxxxxxxxxetc.	Identifies account where financial instruments are maintained
M	:22F:	:SETR/	Reason Code	:4!c/[8c]/4!c	:22F::SETR/DTCYREAS/xxxx	DTC Reason Code, identifies purpose of the transaction.
M	:22H:	:REDE/	Receiver/Deliverer Indicator	:4!c//4!c	:22H::REDE//xxxx	DELI is used if you are the deliverer. RECE is used if you are the receiver.
M	:22H:	:PAYM/	Payment Indicator	:4!c//4!c	:22H::PAYM//xxxx	APMT for valued transactions or FREE for free transactions.
O	:22F:	:STCO/	Internal Source Code	:4!c/[8c]/4!c	:22F::STCO/DTCYISRC/xxxx	Identifies the input media for the transaction.
O	:22F:	:STCO/	Transaction Type	:4!c/[8c]/4!c	:22F::STCO/DTCYTXNT/xxxx	IMS Transaction type, OTHR
O	:22F:	:STCO/	Activity Code	:4!c/[8c]/4!c	:22F::STCO/DTCYACTV/xxxx	Activity Code of the transaction
O	:22F:	:STCO/	3rd Party Status Indicator	:4!c/[8c]/4!c	:22F::STCO/DTCY/xxxx	IMS state for Third Party approvals: TRDP - Pending Approval TRDA - Approved TRDD - Disapproved
O	:22F:	:SETS/	CNS Level Indicator	:4!c/[8c]/4!c	:22F::SETS/DTCY/LVL1, LVL2, LVL3, LVL4, or LVLL	Only applicable for CNS transactions.

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
O	:98A:	:EXSE//	Actual Settlement Date	:4!c//8!n	:98A::EXSE//yyyymmdd	Date at which the transaction was actually settled on
M	:98A:	:SETT//	Original Settlement Date	:4!c//8!n	:98A::SETT//yyyymmdd	Date at which the transaction is suppose to be settled on.
O	:98A:	:TRAD//	Contract/Trade Date	:4!c//8!n	:98A::TRAD//yyyymmdd	SPO, PPO, and IPO only.
O	:70E:	:SPRO//	Narrative - DTC Comments	:4!c//10*35x	:70E::SPRO//xxxxxxxxxxxxxxxxetc.	Provides additional settlement processing information.
Repetitive Optional Subsequence B1 Settlement Parties						
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95R:	:DEAG/DTCYPART	Delivering Participant	:4!c/8c/34x	:95R::DEAG/DTCYPART/0000nnnn	Delivering Participant
O	:97A:	:SAFE//	Deliverers Account Number	:4!c//35x	:97A::SAFE//nnnnnnnnnnnnnnnn	Deliverer Account Number
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95R:	:REAG/DTCYPART	Receiving Participant	:4!c/8c/34x	:95R::REAG/DTCYPART/0000nnnn	Receiving Participant
O	:97A:	:SAFE//	Receivers Account Number	:4!c//35x	:97A::SAFE//nnnnnnnnnnnnnnnn	Receiver Account Number
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95P:	:PSET//	Place of Settlement	:4!c//4!a2!a2!c[3!c]	:95P::PSET//DTCYUS33	Place of Settlement
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95R:	:DEI1/DTCYPART	Deliverer's Intermediary	:4!c/8c/34x	:95R::DEI1/DTCYPART/0000nnnn	Depository Third Party field is displayed if the deliverer number = 919.
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	

M/O	Tag	Block/Qualifier	Field Description	Data Field Format	Example	Description
OR						
M	:16R:	SETPRTY	Start of Block		:16R:SETPRTY	
M	:95R:	:REI1/DTCYPART	Receiver's Intermediary	:4!c/8c/34x	:95R::REI1/DTCYPART/0000nnnn	Depository Third Party field is displayed if the receiver number = 719.
M	:16S:	SETPRTY	End of Block		:16S:SETPRTY	
End of Sequence B1 Settlement Parties						
M	:16S:	SETTRAN	End of Block		:16S:SETTRAN	
End of Sequence B Settlement Transaction Details						

MT548: SETTLEMENT STATUS (SHORT VERSION)

M/O	Tag	Block/ Qualifier	Field Description	Data Field Format	Example	Description
Mandatory Sequence A General Information						
M	:16R:	GENL	Start of Block		:16R:GENL	
M	:20C:	SEME	CDTS Tracking Number	:4!c//16x	:20C::SEME//xxxxxxxxxxxxxxxx	DTCC Generated, used to track transaction from submission to final state.
M	:23G:	INST	Message Function - INST	4!c[/4!c]	:23G:INST	This field identifies the function of the message.
M	:98C:	:PREP//	Transaction Update Date/Time	:4!c//8!n6!n	:98C::PREP//yyyymmddhhmmss	Date/time at which message was prepared.
Repetitive Mandatory Subsequence A1 Linkages						
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:RELA//	IMS Transaction ID	:4!c//16x	:20C::RELA//xxxxxxxxxxxxxxxx	IMS generated - used to track/update transaction from the time it is processed in IMS to final state.
M	:16S:	LINK	End of Block		:16S:LINK	
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:COMM//	ID Control Number	:4!c//16x	:20C::COMM//xxxxxxxxxxxxxxxx	ITP generated - used to identify, link and update ID transactions.
M	:16S:	LINK	End of Block		:16S:LINK	
M	:16R:	LINK	Start of Block		:16R:LINK	
M	:20C:	:COMM//	Obligation Warehouse Control Number	:4!c//16x	:20C::COMM//xxxxxxxxxxxxxxxx	Obligation Warehouse Control Number for Obligation Warehouse DOs.
M	:16S:	LINK	End of Block		:16S:LINK	
M	:16R:	LINK	Start of Block		:16R:LINK	Only for Reclaimed transactions.

M/O	Tag	Block/ Qualifier	Field Description	Data Field Format	Example	Description
M	:20C:	:PREV//	IMS TID of Reclaimed trans	:4!c//16x	:20C::PREV//xxxxxxxxxxxxxxx	Only for Reclaimed transactions.
M	:16S:	LINK	End of Block		:16S:LINK	Only for Reclaimed transactions.
End of Subsequence A1 Linkages						
Repetitive Mandatory Subsequence A2 Status						
M	:16R:	STAT	Start of Block		:16R:STAT	
M	:25D:	SETT/	Status Code	:4!c/[8c]/4!c	:25D:SETT/DTCY/AUTH, SUBA, etc.	IMS or ATP State, states are assigned as transaction is processed through IMS and ATP.
Repetitive Optional Subsequence A2a Reason						
M	:16R:	REAS	Start of Block		:16R:REAS	
M	:24B:	Status	CAND, PEND, REJT, or PENF	:4!c/[8c]/4!c	:24B::REJT/DTCY/xxxx	The IMS or ATP State that falls under the category of Cancelled, Pending, Rejected, or Dropped.
O	:70D:	REAS	Reject Error message	:4!c//6*35x	:70D::REAS//xxxxxxxxxxxxxxxxetc.	Provides explanation for the reject, pend, drop, or cancel.
M	:16S:	REAS	End of Block		:16S::REAS	
End of Subsequence A2a Reason						
M	:16S:	STAT	End of Block		:16S::STAT	
End of Subsequence A2 Status						
M	:16S:	GENL	End of Block		:16S:GENL	
End of Sequence A General Information						

MT548: SETTLEMENT STATUS

M/O	Tag	Block/ Qualifier	Field Description	Data Field Format	Example
Mandatory Sequence A General Information					
M	:16R:	GENL	Start of Block		:16R:GENL
M	:20C:	:SEME//	CDTS Tracking Number	:4!c//16x	:20C::SEME//xxxxxxxxxxxxxxx
M	:23G:	INST	Message Function - INST	4!c	:23G:INST
Repetitive Mandatory Subsequence A1 Linkages					
M	:16R:	LINK	Start of Block		:16R:LINK
M	:20C:	RELA	Sender's Reference Number	:4!c//16x	:20C::RELA//xxxxxxxxxxxxxxx
M	:16S:	LINK	End of Block		:16S:LINK
End of Subsequence A1 Linkages					
Repetitive Mandatory Subsequence A2 Status					
M	:16R:	STAT	Start of Block		:16R:STAT
M	:25D:	IPRC	Status (Nak)	:4!c/[8c]/4!c	:25D:IPRC/DTCY/REJT
Repetitive Optional Subsequence A2a Reason (can repeat up to 5 times)					
M	:16R:	REAS	Start of Block		:16R:REAS
M	:24B:	REJT	Reject Code - field code	:4!c/[8c]/4!c	:24B::REJT/DTCY/xxxx
M	:70D:	REAS	Reject Field - error code	:4!c//6*35x	:70D::REAS//yyyy
M	:16S:	REAS	End of Block		:16S::REAS
End of Subsequence A2a Reason					
End of Subsequence A2 Status					
M	:16S:	GENL	End of Block		:16S:GENL
End of Sequence A General Information					

CODES

Code	Description	Subsequence A2a Reason	If Yes, then the Qualifier is	ID Net Status Code
AUTH	Authorized	No		0002 = Authorized
CANA	ATP Canceled	YES	CAND	000K = ATP Cancel (Kill of pending DO; Canceled after recycling in ATP)
CANC	IMS Canceled	YES	CAND	0005 = IMS Canceled (Canceled before being sent to ATP)
MAKD	Made	* MT547 or MT546 is sent *		0000 = DO Made … 000X = DO made after originally pending
NAL1	CNS Level 1 received	No		
NAL2	CNS Level 2 received	No		
PDRI	IMS Permanently Dropped	YES	PENF	
PDRP	Dropped Permanent	YES	PENF	
PREA	Pre-Authorized	No		
PREX	Pre-Exempted	No		
RATP	PDC Reduction Processed	No		
RAUT	RAD Authorized	No		
RDPR	ATP Dropped Reintroduced	YES	PENF	
RGRN	Recycling Green	YES	PEND	000P = DO Pending (recycling)
RJCF	IMS Rejected to File	YES	REJT	
RJCT	ATP rejected	YES	REJT	0006 = ATP Rejected
RJCI	IMS rejected	YES	REJT	0004 = IMS Rejected
RLSD	Released	No		0007 = Released
RSUB	Submitted to RAD	No		

Code	Description	Subsequence A2a Reason	If Yes, then the Qualifier is	ID Net Status Code
SUBA	Submitted to ATP	No		
UNPR	Unprocessed	No		0001 = Unprocessed
XMPT	Exempted	No		0003 = Exempted
XPER	Recycling Express	YES	PEND	000P = DO Pending (recycling)
				0008 = PDQ COE 0009 = CNS Participant Ineligible 000A = CNS CUSIP Reg-Sho 000B = CNS CUSIP Muni 000C = CNS deliver DO drop, that is, Reclaims due to overage 000D = SDFS prevent-pend drop 000E = CNS CUSIP MMI 000F = CNS CUSIP Corporate Bond 000G = CNS CUSIP Reorg 000H = CNS CUSIP Buy-in 000I = CNS CUSIP New Issue 000J = DTC Ineligible Participant 000L = DTC Ineligible CUSIP 000M = Other 000N = Broker Receiver Exemption

© 2022 DTCC. All rights reserved. DTCC, DTCC (Stylized), ADVANCING FINANCIAL MARKETS. TOGETHER, and the Interlocker graphic are registered and unregistered trademarks of The Depository Trust & Clearing Corporation.

The services described herein are provided under the "DTCC" brand name by certain affiliates of The Depository Trust & Clearing Corporation ("DTCC"). DTCC itself does not provide such services. Each of these affiliates is a separate legal entity, subject to the laws and regulations of the particular country or countries in which such entity operates. Please see www.dtcc.com for more information on DTCC, its affiliates and the services they offer.

Doc Date: August 31, 2022
Publication Code: OW148
Service: Obligation Warehouse
Title: ISO Deliver Order (DO) Output Message Layouts

FOR MORE INFORMATION

Email DTCC Learning at:
DTCCLearning@dtcc.com

or visit us on the web at:
www.dtcclearning.com