

Java Software Development Homework 9

Scoring Criteria and Usage Scenario

2015/05/22

In the following usage scenarios, [EXPR] denotes the current calculation (e.g. [123 + 456]), and <BUTTON> denotes the specific button pressed (e.g. <+> means pressing the + button once).

[Part I] Basic Functions

✓ Numerical buttons (4%)

- Corresponding numbers can display correctly on the screen when the numerical buttons (0-9) are pressed.
- If the current number contains no dot (i.e. an integer), the first digit cannot be 0 except the number is indeed 0 (e.g. the number 012 is invalid). The leading digits can contain at most one zero (e.g. the numbers 000 and 00.12 are both invalid).

Below is an example scenario. [123 +] is the current calculation shown on the screen, and after the button 0 is pressed, the current calculation becomes [123 + 0], and so on.

[EXPR]	[123 +] → [123 + 0] → [123 + 0] → [123 + 1] → [123 + 12]
<BUTTON>	<0> → <0> → <1> → <2>

✓ Dot button (4%)

- Dot can occur at most once in a number.
- Dot can occur neither before the first digit nor after the last digit (e.g. the numbers 123. and .123 are both invalid). For these cases, you should append a zero before and after the dot, respectively.

[EXPR]	[123] → [123.] → [123.] → [123.4] → [123.4] → [123.40]
<BUTTON>	<.> → <.> → <4> → <.> → <0>
[EXPR]	[123 +] → [123 + 0.] → [123 + 0.0 +]
<BUTTON>	<.> → <+>

✓ +/- button (4%)

- This button only applies to a non-zero number.

[EXPR]	[1 +] → [1 +] → [1 + 1] → [1 + -1] → [1 + 1]
<BUTTON>	<+/-> → <1> → <+/-> → <+/->
[EXPR]	[0] → [0] → [0.] → [0.] → [0.0] → [0.0] → [0.01] → [-0.01] → [log(-0.01)] → [log(-0.01)]
<BUTTON>	<+/-> → <.> → <+/-> → <0> → <+/-> → <1> → <+/-> → <log> → <+/->

✓ Unary operation buttons (8%)

- Use function-like expression for displaying unary operations (e.g. log(3) or sqrt(5.0)).
- Unary operations only apply to a number or unary operation.
- If the current number is a unary operation, when you press a numerical button, the unary operation should be replaced by the number.

[EXPR]	[1 +] → [1 +] → [1 + 2] → [1 + log(2)] → [1 + sqrt(log(2))] → [1 + 3]
<BUTTON>	<log> → <2> → <log> → <√> → <3>

✓ Binary operation buttons (6%)

- Binary operators can only occur before or after a number or unary operation.
- If the last token is a binary operator, when you press a binary operation button again, the last binary operator will be overwritten.

[EXPR]	[log(10)] → [log(10) +] → [log(10) +] → [log(10) *] → [log(10) ^]
<BUTTON>	<+> → <+> → <*> → <exp>

✓ Equals button (3%)

- The calculation result will show on the screen after pressing this button.

[EXPR]	[1 + 2 + 3] → [6]
<BUTTON>	<=>
[EXPR]	[1 + 2 +] → [3]
<BUTTON>	<=>
[EXPR]	[1 +] → [1]
<BUTTON>	<=>
[EXPR]	[0] → [0]
<BUTTON>	<=>

✓ Memory function buttons (6%)

- When you press M+ or M-, you should show a label "M" indicates that the stored value in the memory is non-empty. When you press MC, you should clear the stored value in the memory and also clear the label.

[EXPR]	[1 + 2] → [1 + 2] → [1 + 2] → [1 + 4] → [1 + 4] → [1 + 0] → [1 + 3] → [1 + 3] → [1 + 3] → [1 + 6] → [1 + 6] → [1 + 0]
<BUTTON>	<M+> → <M+> → <MR> → <M-> → <MR> → <3> → <MS> → <M+> → <MR> → <MC> → <MR>

✓ Undo button (3%)

- This button deletes a digit from the current number.

[EXPR]	[0 + 1.23] → [0 + 1.2] → [0 + 1.] → [0 + 1] → [0 +] → [0 +]
<BUTTON>	<←> → <←> → <←> → <←> → <←>

✓ C button (2%)

- This button reset the calculator to the initial state. (Note that this button will not clear the stored value in the memory.)

[EXPR]	[123 + 456 +] → [0]
<BUTTON>	<C>

✓ CE button (3%)

- This button clears the current entry.

[EXPR]	[1 +] → [1 +] → [1 + 2] → [1 + 2.] → [1 +]
<BUTTON>	<CE> → <2> → <.> → <CE>

- ✓ Show image / show history / clear history (15%)
 - There are three buttons which can show an image, show the calculation history, clear the calculation history, respectively.
 - The image and history list are both inside the same JScrollPane (i.e. it has a scroll bar) so they will not appear at the same time.
 - You should also record the calculation result to the history list. For example, if the current calculation is $[1 + 2]$ and after pressing $\leq=>$, you should append " $1 + 2 = 3$ " to the history list.

[Part 2] Calculation Correctness

- ✓ Binary operations are correct (18%, each operation for 3%)
 - All operators have the same precedence (i.e. evaluate the expression from left to right) except that the exponential operation should be evaluated first.
 - For example, the expression $[1 + 2 * 3 + 2 ^ 5 / 10]$ should be evaluated to 4.1.
- ✓ Unary operations are correct (9%, each operation for 3%)
 - Note that by definition the factorial operation only applies to a non-negative integer.

[Part 3] Other Requirements

- ✓ Coding style, UI design (5%)
 - All required GUI components display correctly.
 - Functional buttons (in total 30) are arranged properly using GridLayout.
- ✓ If the calculation result is not a number (e.g. NaN or Infinity, etc.), you should disable all the functional buttons except the button C. You can press the button C to reset the calculator. (5%)
- ✓ The current calculation result will be adapted to the next calculation. In the next calculation, if you press a numerical button first, the former calculation result will be overwritten. (5%)

[EXPR]	$[1 + 2] \rightarrow [3] \rightarrow [3 +] \rightarrow [3 + 2] \rightarrow [5] \rightarrow [\log(5)] \rightarrow [0.69897] \rightarrow [1]$
<BUTTON>	$\leq=> \rightarrow <+> \rightarrow <2> \rightarrow \leq=> \rightarrow <\log> \rightarrow \leq=> \rightarrow <1>$