Leicht·Facile by Team Röstigraben Bridgers

Easy-language drafts of Swiss official texts with Apertus, with every fact checked by code

TEAM
Alexander Bobrovsky (bobrovsky@seznam.cz)
Ivan Kuzmych (i.kuzmych@hotmail.com)

REPOSITORY
github.com/bobrovsky420/leicht-facile

DEMO VIDEO
youtu.be/5el7q6Xtgik

MATURITY
Deployable prototype for German and French drafts of public texts and letters. Proof of concept for decisions of child and adult protection authorities (KESB) and courts; these decisions contain strictly confidential personal data (a person's name with details of their family, health and finances) and are a main reason for a sovereign model.

100 % vs 82 %	**97 %** vs 85 %	**0 %** vs 15 %	**3.7** vs 15.0
fact coverage must-keep facts found	**hard facts kept** the source's countable values	**silent losses** values lost without a trace	**rule errors** per 100 blocks

Our pipeline compared to a chatbot: the same model with a strong single prompt, on 20 German test documents.

1. Summary

Problem. About 1.25 million adults in Switzerland aged 16 to 65 (22%) have low reading skills (Swiss Federal Statistical Office, PIAAC 2022/23); people with intellectual disabilities, language learners and people with dementia need easy language too.

Disability law (Behindertengleichstellungsgesetz BehiG and the UN disability convention) asks authorities for accessible information, and cantons have begun to publish in Leichte Sprache, FALC or lingua facile; each version is written by hand by a few trained writers, who must check every deadline, amount and phone number against the original.

Approach. Leicht·Facile is a drafting assistant for the people who write official texts: trained writers, and the case workers, clerks and physicians who write decisions and letters themselves. One rule: **Apertus does everything that needs language understanding; plain code does everything that can be counted.** Apertus turns the document into a fact sheet, writes a draft with provenance for every sentence, judges meaning with a second, larger model, repairs only the flagged sentences and asks again for each value still missing. Code checks the published easy-language rules (45 checks for German, 41 for French), including the exact presence of every fact value. A person reviews source and draft side by side and exports with an audit trail.


One container plus an OpenAI-compatible Apertus endpoint runs on-premise, air-gapped or on a Swiss cloud, as letters under official, medical or tax secrecy require; for those, only Apertus fits (§3).

The baselines are single prompts on the same model, with no list of the facts that must survive, no provenance and no independent check: a plain one ("rewrite this in Leichte Sprache") and a strong one, the Canton of Zurich's published prompt.

Headline result. Our pipeline compared to the strong single prompt (defined in §5), on the same model and 20 German test documents. Pipeline first, prompt second:

- **Must-keep facts found:** 100 against 82 percent.
- **Countable values kept** (dates, amounts, phone numbers, addresses): 97 against 85 percent. The official easy-language versions keep 67 percent; they drop values on purpose.
- **Values lost without a trace:** none against 15 percent. The pipeline lists every value it loses for the reviewer.
- **Rule errors per 100 blocks:** 3.7 against 15.0.
- **Invented values per 100 blocks:** 0.0 against 0.0, rare on both sides.
- **Review time:** about 3.5 minutes per 250-word page from opening the draft to the export, in our own timing of three drafts.

2. Architecture



Stage	Done by	Output
Ingest	Code: trafilatura, pdfplumber, spaCy	`SourceDocument`: segments with stable ids (`s0001`)
Understand	Apertus 8B, thinking	`FactSheet`: the reader's core questions, typed facts with normalised values and source ids; code adds every date, amount, contact, address, period or identifier the model missed
Write	Apertus 8B	`Draft`: blocks with the facts and source segments they carry, omissions with reasons, glossary
Rule check	Code: spaCy, regex, wordfreq	Findings with rule id, severity, evidence, suggestion
Judge	Apertus 70B, thinking	Each fact present, missing or distorted; unsupported blocks; meaning findings. The judge never rewrites
Repair	Apertus 8B	New text for flagged blocks only; up to 3 rounds; every version kept
Recover	Apertus 8B	One sentence for each must-keep value still missing (at most 10), checked and judged like a round
Review, export	Human, then code	Per-block decisions; Markdown, HTML, Word and a JSON audit bundle

Key decisions

Meaning in the model, countable rules in code (exact, free, reproducible, no self-grading).

Every must-keep value must appear in an accepted form (`31. März 2026`, `31.3.2026`), so a deadline that became `30 March` is caught; every value the source does not contain is flagged.

Typed artifacts in SQLite let a failed job resume and the UI and the evaluation show every intermediate result.

One service: FastAPI, a server-rendered UI, one worker thread by default; no Node build, no CDN.

Target architecture

Leicht·Facile is deployable in all three architectures. Its only runtime dependency is the Apertus endpoint in `LLM_BASE_URL`; changing the deployment means changing that variable.

What the running system contacts:

Service	When	What it receives
Apertus endpoint (`LLM_BASE_URL`)	Every model call; its model list once per process	Document text, fact sheet and drafts, inside prompts
The server of a URL the user enters	Only for URL input	A request for that page; no document data

Architecture	How it is met	Tested on
a) On-premise	`docker compose --profile local-llm up` adds a vLLM service from the official image `ghcr.io/swiss-ai/vllm_apertus_1.5_release` serving Apertus 1.5 8B on one GPU; the app points at `http://vllm:8000/v1`.	vLLM on one NVIDIA L4 24 GB (rented AWS g6.xlarge in Zurich, Ubuntu 24.04, 10 October 2026): `make run` from a clean clone, two jobs end to end. llama.cpp on a laptop RTX 4060 8 GB.
b) Air-gapped	As (a), with images and weights pulled in advance. Python packages, spaCy models and UI assets are baked into the image; no telemetry, no CDN, no installs at runtime.	Not run without a network. Tests check that the UI loads nothing from another host; CI starts the image against an unreachable endpoint.
c) Sovereign Swiss cloud	`LLM_BASE_URL` points at a Swiss-operated Apertus endpoint.	The CSCS inference API in Lugano: every run evaluated in §5 and the two example letters.

Nothing else: no telemetry, CDN, outside fonts or scripts, update check or login provider; on-premise or air-gapped, no data leaves the organisation at runtime. Build time: PyPI (`uv.lock`), spaCy wheels from GitHub, images from Docker Hub and GHCR. The container runs without root rights and by default can be reached only from the machine it runs on. On the network it requires a login: a shared token, or the organisation's own login through its reverse proxy.

Licences and providers

Apertus 1.5 Apache 2.0 with an acceptable use policy (accepted once for the gated download), code Apache 2.0, spaCy models MIT (German) and LGPL-LR (French), fonts OFL. Any OpenAI-compatible server works (used: CSCS, Public AI, llama.cpp; vLLM on-premise): no single provider is needed.

Hardware	Model and server	Memory	Speed
NVIDIA L4 24 GB	8B in bf16, vLLM	17.2 GiB of weights; with the FP8 KV cache, one 32k request fits	16 tokens per second, near the limit of the card's memory bandwidth
Laptop RTX 4060 8 GB	8B in 4-bit, llama.cpp	5.1 GB of weights	About 37 tokens per second

3. Use of Apertus

- **Models:** `swiss-ai/Apertus-v1.5-8B` writes (Understand, Write, Repair, Recover, baseline) and `swiss-ai/Apertus-v1.5-70B` judges, set by `LLM_NAME` and `LLM_JUDGE_NAME`.
- **How it is used:** inference, as a structured-output agent pipeline without tool calling (the thinking variants are served with tools disabled). No fine-tuning.
- **Where it runs, and why only Apertus:** the CSCS inference API for the hackathon; the same client works unchanged with vLLM, llama.cpp or a Swiss cloud endpoint. Letters that name a person fall under official, medical or tax secrecy and may not go to a foreign cloud, so the organisation must run the model itself and account for what it learned. Only Apertus combines open weights, open training data (website opt-outs honoured), Swiss public origin and German, French and Italian.
- **Why these sizes:** the 8B is enough to read and write. It finds the must-keep facts as well as the 70B does, at half the price per page (§5). The 70B judges, because meaning needs a second, larger model than the one that wrote the draft.

Stage	Model	Thinking	Temperature	Max tokens
Understand	8B	on	0.1	12000
Write	8B	off	0.3	8000
Judge	70B	on	0.0	12000
Repair	8B	off	0.2	6000
Recover	8B	off	0.2	1500
Baseline prompts	8B	off	0.3	6000

Prompts and parsing (track_2b/docs/prompts.md), in the document's language, each with one filled JSON example instead of the schema. Sentences and blocks carry ids (`s0004`, `b007`): the model cites, code verifies; the judge's unsupported verdicts must quote words that stand in the draft. The writer plans first (the reader's questions as headings) with the level's style guide and two example pairs written by the team; repair gets only the flagged blocks, their findings and facts. Answers are parsed leniently and validated with pydantic (one retry with the error); calls are streamed, retried on broken streams, 429 and 5xx, and logged.

Where Apertus fell short, and what we did about it:

- The 8B drops must-keep facts while writing, ignored compound splits it was given, copied values from the prompt's example and broke JSON: code completes the fact sheet, splits compounds, returns answers with values the document lacks and repairs the JSON; facts rounds and the recover round ask again, a polish round repairs the sentences they add (track_2b/docs/prompts.md).
- Every fact number comes from code, not from the judge: the 70B judge's fact verdicts agree with blind labels hardly better than chance (kappa 0.08, §5).
- On the local 4-bit build, Write with thinking took 24 minutes and paraphrased; without, 28 seconds and easy language. Write runs without thinking.
- The 8B's drafts are harder to read than the official easy-language versions: their readability score is 51 against 62 (Amstad; higher is easier). With the 70B in every step, the drafts score 56, at twice the price per page.
- On a scanned page sent as one image, both models change digits (in an IBAN or a phone number, for example); cut into strips, the 8B reads every digit right, but names and e-mail addresses are unsafe in every setting. Image input is not built (track_2b/docs/image-input.md).

Other models and coding assistants. No other model at runtime; spaCy's statistical parsers and wordfreq serve the checker. The 59 labels for the judge's agreement (§5) were made by Claude (Anthropic), blind to the verdicts; no pipeline score depends on them. The code, tests and documents were written with AI coding assistants (Claude Code, Anthropic), directed and reviewed by the team; the

assistants also ran the tests and the evaluation scripts; the design, the decisions and every claim here are the team's.

4. Data

Data	Origin	Licence and handling
Reference pairs: **35** documents with an official easy-language version (**30** German: 20 eval, 10 dev; **5** French: 3 eval, 2 dev)	Cantons Zürich, Bern, St. Gallen, Luzern, Basel-Stadt, Graubünden, Zug, Geneva, Neuchâtel; federal offices BAG, BWL, EBGB	Personal use only. The repository holds only the manifest (`track_2b/data/pairs/manifest.jsonl`: URLs, licence notes); `eval fetch` caches the texts, git-ignored, with a fetch date
Example documents, few-shot examples, hard texts for tests	Written by the team: invented municipality, reserved `.example` domains	In the repository, under the project licence

Dev pairs serve prompt development and calibration; eval pairs are held out. No personal data is used. Evaluating against protected pages needs no consent as long as neither the texts nor our rewrites are published (Copyright Act art. 24a and 24d; our reading, not legal advice; track_2b/docs/sources.md §4).

5. Evaluation

Task. Simplify a standard-language official text to Leichte Sprache and keep every fact. Each held-out pair runs under these conditions:

Code	Condition	Measures
P0	One prompt: "Schreibe diesen Text in Leichter Sprache:"	What a user gets from a chatbot
P0-ZH	The Canton of Zurich's public Leichte Sprache prompt, verbatim; German only	The strong single prompt: Zurich's published prompt, the only public Swiss one we found
P1	Understand, Write, rule check; no judge, no repair	Fact sheet, planning, provenance
P2	Full pipeline with judge and repair	Checking and repairing

Two rows need no model: SOURCE (the original, scored as if it were a draft) and REF (the official easy-language version written by professionals).

Metrics, on every row's final text: **fact coverage** (must-keep facts with a source value found); **hard facts kept** (the source's countable values, by code, so comparable with REF); **silent losses** (hard values lost without a trace; for the pipeline, the gaps of its code completion); **values not in the source**; **unsupported blocks** (70B judge); **rule errors**; **readability** (Amstad, the German Flesch); **SARI** against the official version (a port of `SARI.py`, checked bit for bit); cost at Public AI's token prices and speed per 250-word page.

Results on the 20 held-out German pairs, final run on the CSCS endpoint, 12 October 2026; the strong prompt's two rows were sampled on 11 October and scored again against this run's fact sheets, since their templates did not change. Each number is the mean over the pairs; "/100" means per 100 blocks. P1 and the last row reused answers from the cache: P1's time is not measured, the last row's is too low.

Setup	Fact coverage	Hard facts kept	Silent losses	Values not in source /100	Unsupported /100 (judge)	Rule errors /100	Amstad	SARI	USD / page	s / page
SOURCE	-	100 %	0 %	0.0	-	31.3	36	-	-	-
REF (official)	-	67 %	33 %	2.8	-	2.7	62	-	-	-
P0	94 %	95 %	5 %	0.2	-	24.9	49	44.3	0.0001	2.8
P0-ZH complete	82 %	85 %	15 %	0.0	-	15.0	47	43.0	0.0003	2.4
P0-ZH complete, 70B	85 %	90 %	10 %	0.3	-	7.0	50	44.7	0.0028	6.0
P0-ZH condensed	65 %	67 %	33 %	0.0	-	9.0	46	41.5	0.0002	1.4
P1	61 %	59 %	1 %	0.1	-	9.7	50	39.6	0.0012	-
P2 (ours)	**100 %**	**97 %**	**0 %**	**0.0**	**2.7**	**3.7**	**52**	**42.2**	**0.0159**	**59.6**
P2, 70B everywhere	100 %	96 %	0 %	0.0	1.0	0.5	57	42.9	0.0250	60.0
P2, 70B reads, 8B writes	99 %	94 %	0 %	0.0	1.4	3.0	53	42.3	0.0145	31.8

Reading the table:

- The one-sentence prompt and the strong prompt's complete mode keep most values because they rewrite little (8.0 and 7.0 words per sentence; SARI rewards closeness to the source) and lose the rest without a trace; the condensed mode, its default, simplifies more and drops a third of the values.
- The pipeline keeps more hard facts than the official versions: 97 against 67 percent, and 97 against 61 on the 17 pairs with 3 or more hard facts; the official versions drop values on purpose. It nears their sentence length (7.0 words against 6.1) but is harder to read (Amstad 52 against 62).
- Judge, repair and the recover round (P1 to P2) raise fact coverage from 61 to 100 percent and cut rule errors from 9.7 to 3.7 per 100 blocks; 19 of the 20 final drafts miss no must-keep fact, the twentieth misses 2 of its 23 (one behind the per-round cap of missing facts, one asked for and not written).
- A third of P2's rule errors (13 of 38) come from one two-page health-insurance text; the 7-page source that gave two fifths of the errors on 11 October, rewritten in full into 140 blocks, came out as a 44-block draft with one error this time.
- A single prompt varies from run to run: on unchanged templates, P0-ZH complete found 91 percent of the facts on 10 October and 83 on 11 October (one answer per pair at temperature 0.3); on 12 October its rows were scored again, not sampled again.
- French (3 pairs): 100 percent fact coverage, 72 percent of the hard facts (one draft of 117 words for a 489-word source kept 4 of 15, every one listed for the reviewer), 3.5 errors, readability 70 (official 85).

Cost and scale. At Public AI's list prices our pipeline costs 0.0159 USD (about 1.6 US cents) per 250-word page, the recover and polish rounds included; with the 70B everywhere, 0.0250 USD. The cost grows linearly with the number of pages: 10 times the volume costs 10 times as much. On own hardware the GPU is a fixed cost until it is busy. Speed is the limit: at 10 times the volume, jobs wait in a queue, as one runs at a time; running several at once is a setting we have not measured. The writer's time is the cost that matters: our own review of three P2 drafts in the UI (the two example letters and one dev pair, 1,079 source words together), from opening the review to the export, took 15 minutes by stopwatch, about 3.5 minutes per 250-word page (the team, not experts).

Judge reliability. The judge's fact verdicts are a hint for the reviewer, not a measure: every fact number here comes from code, and the review page shows a verdict that code contradicts as a doubt. Its block verdicts, the basis of the "Unsupported" column, agree with blind labels far better. 30 facts and 30 blocks from the P2 dev drafts of 6 October (70B judge), drawn evenly over the verdicts and labelled blind to them (`eval sample`, `eval kappa`). Blocks, supported or not: agreement 80 %, Cohen's kappa 0.60. Facts, present, missing or distorted: 38 %, kappa 0.08 (present or not: 62 %, kappa 0.22).

Checker calibration and tests. On official pages each error is a real deviation or a false positive to fix; calibration cut errors per 100 blocks from 12.6 to 2.0 (30 German pages) and from 5.3 to 2.2 (5 French). 1,454 offline tests include golden sentences for every rule (two or more that fire, one that must not).

6. Limitations

- **Readability with an 8B model.** At level A2 the drafts do not yet read as easily as the official versions: their sentences are almost as short (7.0 against 6.1 words), but their readability score is lower (Amstad 52 against 62). The facts are not the problem: the drafts keep all must-keep facts and 97 percent of the countable values, and list every value they lose (20 German eval pairs, CSCS).
- **Not a certification.** Easy-language texts must be tested by readers from the target group; the tool prepares that test, it does not replace it.
- **Italian** gets only the language-independent rules (facts, layout, readability). The B1 thresholds are our own; no official Swiss B1 rule set exists.
- **The judge is a model**, and obligations and conditions without a value rely on it alone; many pages carry few countable facts, so the fact-rich subset is reported too.
- **Decision mode v1** is calibrated on one team-written KESB decision and one published court decision; no authority and no reader has seen its output.
- **Not yet supported:** scanned PDFs and photos (§3), an air-gapped image bundle, user accounts and roles.
- **Unmeasured:** the rewrite recipes the checker hands the writer for a subordinate clause, in German and French; the dev runs measured the rounds, not them.

7. Reproducibility

- **Run:** `LLM_BASE_URL`, `LLM_API_KEY` and `LLM_NAME` in the shell or in `.env`, then `make run`, which opens http://localhost:8000 in the browser once the app is up; `make smoke` runs a bundled letter end to end.
- **Numbers:** `make eval` fetches the pairs, runs P0, P0-ZH, P1 and P2 with the response cache (an interrupted run resumes) and writes the tables; `make calibrate` runs the checker on the official pages without a model.
- **Environment:** Python 3.14 in `python:3.14-slim`, dependencies locked in `uv.lock`, spaCy models pinned by wheel URL; CI runs the linter, the tests and a start of the Docker image on every push.
- **Seeds:** temperatures above zero are not seeded; reruns reproduce exact outputs through the response cache, and each result stores the hash of its prompt template.
- **Hardware and commit:** the evaluation numbers come from the CSCS endpoint, the hardware figures in §2 from our own runs (the L4 run in `track_2b/eval/hardware/`); commit **[PENDING: hash]** (the final run of 12 October 2026, on the prompt templates that address the model informally and the value extractor fixed the same day; the strong prompt's rows from the run of 11 October on commit `663b609`, scored again).

8. Next steps

- **Into use.** For a canton's public texts and standard letters, a cloud endpoint is enough, even Public AI; the canton needs no GPU server. Two steps remain before the first text goes out. The canton's IT puts its login proxy in front of the app; the app already reads the logged-in user from a header the proxy adds. Then the setup must pass the canton's IT security review. Letters that name people need more: the model on the canton's own GPU server and a data protection assessment. Testing the texts with readers from the target group stays with the canton; the tool does not replace it.
- **The same need elsewhere.** Every canton and federal office that publishes easy language, and texts under secrecy, where only Apertus fits: decisions of KESB and courts (decision mode v1 exists; next an anonymisation step), patient letters, penal and payment orders, social, school and tax decisions. Most depend on a period, a reference number, an address or a dose; code already checks these like a date.
- **Patient letters.** Code already checks doses and dosing schemes; left are a drug list, a medical judge (Apertus-70B-MeditronFO, EPFL's medical Apertus, not yet tried here) and an assessment under the Medical Devices Ordinance.
- **Italian.** Rules and prompts for lingua facile; today Italian texts get only the language-independent checks and no drafts.
- **Scanned letters.** Image input, with the 8B reading each page in strips (on a whole page the models misread digits) and a person checking every name and address against the original.
- **Air-gapped installation.** A one-step package for a network without internet access; today the images and the weights are moved by hand.
- **Fine-tuning.** A LoRA on the 8B, trained on the drafts that writers approved and the edits they made.

License

Code: Apache License 2.0. This report: Creative Commons Attribution 4.0 (CC-BY-4.0).

References

- Apertus v1.5 model card: https://huggingface.co/swiss-ai/Apertus-v1.5-8B
- EPFL LiGHT, Apertus-70B-MeditronFO model card: https://huggingface.co/EPFLiGHT/Apertus-70B-MeditronFO
- CSCS LLM inference API: https://docs.cscs.ch/services/inference/api/
- Canton of Zürich, rules for Leichte Sprache
- Canton of Zürich, simply-simplify-language (the prompt of P0-ZH)
- EBGB, Leitfaden Leichte Sprache
- EBGB, Behindertengleichstellungsgesetz BehiG (SR 151.3)
- Inclusion Europe, "Information for all" (German, French and Italian editions)
- Swiss Federal Statistical Office (2024): PIAAC 2022/2023, first results
- Amstad, T. (1978): Wie verständlich sind unsere Zeitungen? (German readability index)
- Xu, W. et al. (2016): Optimizing SMT for Text Simplification. TACL 4 (SARI)
- Swiss Copyright Act (URG), art. 5, 24a, 24d