

Giving Shape to Ideas









bizhub C554e

Ideal for high-speed color output and fast scanning to multiple destinations, the bizhub C554e can power up your workflow with 55 ppm output in both color and B&W, enhanced touch-screen convenience and multiple finishing options for creating high-impact color documents in-house.

System Overview

System overview			
System memory	2,048 MB		
System hard disk	250 GB		
Interface	10-BASE-T/100-BASE-TX/1,000-BASE-T Ethernet, USB 2.0		
Network protocols	TCP/IP (IPv4/IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS		
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP		
Dual scan	Up to 100 originals / 5.5" x 8.5" to 11" x 17" / 35-163 gsm		
document feeder			
Printable paper size	Scanning/Copying: up to 11" x 17"		
	Printing: up to 11" x 17" full bleed on 12" x 18" paper Custom paper sizes		
	Banner paper max: 11.75" x 47.25"		
Printable paper weight	52-300 gsm		
Paper input capacity	Standard: 1,150 sheets / Max.: 6,650 sheets		
Tray 1	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm		
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm		
Tray 3 (optional)	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm		
Tray 4 (optional)	2 x 500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm		
Large capacity tray	2,500 sheets / 8.5" x 11" / 52-256 qsm		
PC-410 (optional)	, 		
Large capacity tray LU-301 (optional)	3,000 sheets / 8.5" x 11" / 52-256 gsm		
Large capacity tray LU-204 (optional)	2,500 sheets / 8.5" x 11" to 12" x 18" / 52-256 gsm		
Manual bypass	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes / 50-300 gsm		
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52-256 gsm		
Finishing modes	Offset, group, sort, punch, post insertion, z-fold, half-fold, tri-fold, booklet		
Output capacity	Max. with finisher: 3,300 sheets		
	Max. without finisher: 250 sheets		
Stapling (optional)	Max.: 100 sheets or 94 sheets + 2 cover sheets (up to 209 gsm)		
Stapling output capacity	Max.: 1000 sheets		
Tri-fold	Up to 3 sheets		
Tri-fold capacity	Max.: 30 sheets (tray), unlimited		
Booklet	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)		
Booklet output capacity	Max.: 100 sheets (tray), unlimited		
Copy/print volume	Max.: 200,000 pages/month ¹		
Toner lifetime	Black: 27,000 pages / CMY: 26,000 pages		
Imaging unit lifetime	Black: 135,000 pages / 590,000 pages (Drum / Developer) CMY: 95,000 pages		
Power consumption	120 V / 50/60 Hz, less than 1.92 kW (system)		
System dimensions	24.2" x 27" x 36.3" (W x D x H)		
System weight	Approx. 220.5 lb		

Conier	Specif	ications

Copying process	Electrostatic laser copy, tandem, indirect	
Toner system	Simitri® HD Polymerized Toner	
Print speed (8.5" x 11")	B&W / Color: up to 55 ppm (Portrait)	
Print speed (11" x 17")	B&W / Color: up to 27 ppm (Portrait)	
Autoduplex speed (8.5" x 11")	B&W / Color: up to 55 ppm (Portrait)	
1st copy out time	B&W: 4.1 sec. / Color: 4.6 sec.	
Warm-up time	Approx. 22 sec. ²	
Copy resolution	600 x 600 dpi	
Gradations	256 gradations	
Multi-copy	1-9,999	
Original format	Up to 11" x 17"	
Magnification	25-400% in 0.1% steps, auto zooming	
Copy functions	Chapter, cover and page insertion, proof copy (print and screen), adjustment test print, digital art functions, job setting memory, poster mode, image repeat, overlay (optional), stamping, copy protection	

Printer Specifications

Print resolution	1,800 x 600 dpi, 1,200 x 1,200 dpi	
PDL	PCL6 (XL 3.0), PCL5c, PostScript 3 (ver. 3016), XPS	
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 ³ / 2012 ³ Macintosh OS X 10.2.8 or later UNIX / Linux / Citrix	
Printer fonts	80 PCL Latin, 137 PostScript 3	
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print	

Printer Specifications (Optional)

Print controller	Embedded Fiery IC-414	
Memory/HDD	2 GB / 160 GB	
PDL	PostScript 3 (ver. 3019) PCL 6/5c	
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 ³ / 2012 ³ Macintosh OS X 10.2.8 or later	

Scanner Specifications

Scan speed	B&W / Color: up to 160 ipm
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job programs, realtime scan preview

Fax Specifications

Fax	Super G3 (optional)	
Transmission	Analog, i-Fax, Color i-Fax, IP-fax	
Resolution	Max.: 600 x 600 dpi (ultra-fine)	
Compression	MH, MR, MMR, JBIG	
Modem	Up to 33.6 Kbps	
Destinations	2,100 (single + group)	
Functions	Polling, time shift, PC-fax, receipt to confidential box, receipt to	
	Email/FTP/SMB, up to 400 job programs	

User Box Specifications

Storable documents	Max.: 3,000 documents or 10,000 pages		
Type of user boxes	Public		
	Personal (with password or authentication)		
	Group (with authentication)		
Type of system boxes	Secure print, encrypted PDF, fax receipt, fax polling, annotation		
User box functionality	Reprint, combination, download, sending (Email/FTP/SMB and fax),		
	copy box-to-box		

		ıres

Security	ISO 15408 EAL
	IEEE 2600.1
	IP filtering and port blocking
	SSL2, SSL3 and TSL1.0 network communication
	IPsec support
	IEEE 802.1x support
	User authentication
	Authentication log
	Secure print
	Hard disk overwrite (8 standard types)
	Hard disk data encryption (AES 128)
	Memory data auto deletion
	Confidential fax receipt,
	Print user data encryption
	Copy protection (Copy Guard, Password Copy) optional
Accounting	Up to 1,000 user accounts
	Active Directory support
	(user name + password + Email + SMB folder)
	User function access definition
	Optional Biometric authentication (finger vein scanner)
	Optional ID card authentication (ID card reader)
Software	PageScope Net Care Device Manager
	PageScope Data Administrator
	PageScope Box Operator
	PageScope Direct Print
	Print Status Notifier
	Driver Packaging Utility
	Log Management Utility

Log wariagement durity

Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis.

This specification is a guidline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs

Warm-up time may vary depending on the operating environment and usage

Supports x64 only

Components and Options	S	
AU-102 Biometric	Finger vein scanner	
authentication		
EK-606 USB I/F kit	USB keyboard connection	
EK-607 USB I/F kit	USB keyboard connection, Bluetooth	
DK-510 Copier desk	Provides storage space for print media and other materials	
FK-508 Fax board	Super G3 fax, digital fax functionality, lines 3 & 4 support	
FK-511 Fax board	Super G3 fax, digital fax functionality	
FS-533 Staple finisher	50-sheet stapling, 500 sheets max. output	
FS-534 Staple finisher	50-sheet stapling, 3,300 sheets max. output	
FS-534 + SD-511	50-sheet staple finisher, 20-sheet booklet finisher,	
Booklet finisher	3,300 sheets max. output	
FS-535 Staple finisher	100-sheet stapling, 3,200 sheets max. output	
IC-414 Fiery controller	Professional color print controller	
ID card reader	Various ID card technologies	
JS-506 Job separator	Separation for fax output, etc.	
JS-602 Job separator	Separation for fax output, etc.	
for FS-535	To also a HOD Last and	
KH-102 Keyboard holder	To place USB keyboard	
KP-101 10-Key pad	For use instead of touchscreen	
LK-101 v3	Web browser	
Web browser		
LK-102 v3	PDF/A, PDF encryption, digital signature	
PDF enhancements		
LK-104 v3	Provides voice guidance functions	
Voice guidance	0 111 005	
LK-105 v3 OCR text recognition	Searchable PDF	
LK-106	Supports native barcode printing	
Barcode fonts	oupports native baroode printing	
LK-107	Supports native Unicode printing	
Unicode fonts		
LK-108	Supports native OCR A and B font printing	
OCR A and B fonts		
LK-110 Enhanced	Generates various file formats incl. DOCX, XLSX and combines LK-102 (encrypted PDF) + LK-105 (searchable PDF/OCR functionality)	
image support LK-111	Print data compression for reduced network impact	
ThinPrint® Client	Fillit data compression for reduced network impact	
LU-204	8.5" x 11" to 12" x 18", 2,500 sheets, 52-256 gsm	
Large capacity tray		
LU-301	8.5" x 11", 3,000 sheets, 52-256 gsm	
Large capacity tray		
MK-728 Mount kit	Installation kit for FK-508 fax board	
MK-735 Mount kit	Installation kit for ID card reader	
OT-506 Output tray	Output tray used instead of finisher	
PC-110	5.5" x 8.5" to 11" x 17", 500 sheets, 52-256 gsm	
Universal tray (x1) PC-210	5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52-256 gsm	
Universal tray (x2)	3.3 x 0.3 to 11 x 17 , 2 x 300 sheets, 32-230 yshi	
PC-410 Large	8.5" x 11", 2,500 sheets, 52-256 gsm	
capacity tray	, ,,,	
PI-505 Post inserter	Cover insertion, post finishing	
for FS-535		
PK-519 Punch kit	2/3-hole punching, autoswitching	
for FS-533 PK-520 Punch kit	2/3-hole punching, autoswitching	
for FS-534	2/3-note puricing, autoswitching	
PK-521 Punch kit	2/3-hole punching, autoswitching	
for FS-535	2.0 note partoning, dataontoning	
SC-508 Security kit	Copy Guard function (2x required)	
SD-512 Saddle kit for	Booklet finishing, half-fold, tri-fold	
FS-535		
UK-204	Memory extension for i-Options	
i-Option memory	Mindon LANIA askind someth	
UK-208 Wireless LAN	Wireless LAN to network connector	
VI-506 Interface kit for IC-414	Fiery controller interface card	
WT-506 Working table	Authentication device placement	
ZU-606 Z-fold unit	Z-fold for 11" x 17" prints, 2/3 hole punching	
for FS-535	·	



KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446





