Giving Shape to Ideas





bizhub C308

Ideal for growing businesses, the bizhub C308 is a powerful, affordable color MFP with superior Simitri HD image quality and fast 30 ppm print/copy output. Optional dual scanning at up to 160 opm brings information into your workflow faster— and enhanced touch-screen simplicity never slows you down.

System Overview

System Overview	
System memory	4 GB
System hard disk	250 GB Standard
Interface	10-BASE-T/100-BASE-TX/1,000-BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4/IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Document feeder	Up to 100 originals / 5.5" x 8.5" to 11" x 17" / 35-163 gsm
(optional)	Reversing automatic document feeder or dual scan document
B.C. Labella and a construction	feeder available
Printable paper size	Scanning/Copying: up to 11" x 17" Printing: up to 11" x 17" full bleed on 12" x 18" paper
	Custom paper sizes
	Banner paper max.: 11.75" x 47.25"
Printable paper weight	52-300 gsm
Paper input capacity	Standard: 1,150 sheets / Max.: 6,650 sheets
Tray 1	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
Tray 3 (optional)	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
Tray 4 (optional)	2 x 500 sheets / 5.5" x 8.5" to 8.5" x 11" / 52-256 gsm
Large capacity tray	3,000 sheets / 8.5" x 11" / 52-256 gsm
LU-302 (optional)	•
Large capacity tray	2,500 sheets / 8.5" x 11" / 52-256 gsm
PC-410 (optional)	
Manual bypass	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes / 50-300 gsm
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52-256 gsm
Finishing modes	Offset, group, sort, punch, half-fold, tri-fold, booklet
Output capacity	Max. with finisher: 3,300 sheets
Ctanling (antional)	Max. without finisher: 250 sheets
Stapling (optional) Stapling output	Max.: 50 sheets or 48 sheets + 2 cover sheet (up to 209 gsm) Max.: 1,000 sheets
capacity	wax.: 1,000 sheets
Tri-fold (optional)	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray)
Booklet (optional)	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output	Max.: 100 sheets (tray)
capacity	main roo onoto (aug)
Copy/print volume	Max.: 100,000 pages/month ¹
Toner lifetime	Black: 28,000 pages / CMY: 26,000 pages
Imaging unit lifetime	Black: 120,000 pages / 600,000 pages (Drum / Developer) CMY: 75,000 pages / 600,000 pages (Drum / Developer)
Power consumption	120 V / 60 Hz, less than 1.5 kW (system)
System dimensions	24.2" x 27" x 31" (W x D x H)
System weight	Approx. 187.39 lb

Caniar	Cnor	aifina	tiono
Copier	อมชเ	JIIIGa	นบทร

pi		
Copying process	Electrostatic laser copy, tandem, indirect	
Toner system	Simitri® HD Polymerized Toner	
Print speed (8.5" x 11")	B&W / Color: up to 30 ppm (Portrait)	
Print speed (11" x 17")	B&W / Color: up to 15 ppm (Portrait)	
Autoduplex speed	B&W / Color: up to 30 ppm (Portrait)	
(8.5" x 11")		
1st copy out time	B&W: 5.6 sec. / Color: 7.3 sec.	
Warm-up time	Approx. 20 sec. ²	
Copy resolution	600 x 600 dpi	
Gradations	256 gradations	
Multi-copy	1-9,999	
Original format	Up to 11" x 17"	
Magnification	25-400% in 0.1% steps, auto zooming	
Copy functions	Electronic sorting, multi-job, adjustments (contrast, sharpness, image density), proof copy, interrupt mode, color mode, separate scan, sort/group, combination, original selection, ID card copy, 2-in-1, 4-in-1	

Printer Specifications

i ilittoi opooliiloutiolio	
Print resolution	1,800 x 600 dpi, 1,200 x 1,200 dpi
PDL	PCL6 (XL 3.0), PCL5c, PostScript 3 (ver. 3016), XPS
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 ³ / 2012 ³ Macintosh OS X 10.6 or later Linux / Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print

Printer Specifications (Optional)

Print controller	Embedded Fiery IC-416
Memory/HDD	2 GB / 160 GB
PDL	PostScript 3 (ver. 3019) PCL 6/5c
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 ³ / 2012 ³ Macintosh OS X 10.8 or later

Scanner Specifications

Scan speed	B&W / Color: up to 160 ipm with optional DF-704
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job programs, realtime scan preview

Fax Specifications

Fax	Super G3 (optional)	
Transmission	Analog, Internet fax, Color i-Fax, IP-Fax	
Resolution	Max.: 600 x 600 dpi (ultra-fine)	
Compression	MH, MR, MMR, JBIG	
Modem	Up to 33.6 Kbps	
Destinations	2,100 (single + group)	
Functions	Polling, time shift, PC-fax, receipt to confidential box, receipt to	

User Box Specifications

Storable documents	Max.: 3,000 documents or 10,000 pages	
Type of user boxes	Public Pu	
	Personal (with password or authentication)	
	Group (with authentication)	
Type of system boxes	Secure print, encrypted PDF, fax receipt, fax polling, annotation	
User box functionality	Reprint, combination, download, sending (Email/FTP/SMB and fax), copy box-to-box	

System Features

Security	ISO 15408 EAL	
	IEEE 2600.1	
	IP filtering and port blocking	
	SSL2, SSL3 and TSL1.0 network communication	
	IPsec support	
	IEEE 802.1x support	
	FIPS 140-2	
	User authentication	
	Authentication log	
	Secure print	
	Hard disk overwrite (8 standard types)	
	Hard disk data encryption (AES 128)	
	Memory data auto deletion	
	Confidential fax receipt,	
	Print user data encryption	
	Copy protection (Copy Guard, Password Copy) optional	
Accounting	Up to 1,000 user accounts	
	Active Directory support	
	(user name + password + Email + SMB folder)	
	User function access definition	
	Optional Biometric authentication (finger vein scanner)	
	Optional ID card authentication (ID card reader)	
Software	PageScope Net Care Device Manager	
	PageScope Data Administrator	
	PageScope Box Operator	
	PageScope Direct Print	
	Print Status Notifier	
	Driver Packaging Utility	
	Log Management Utility	

¹ Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis.

This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs

2 Warm-up time may vary depending on the operating environment and usage

3 Supports x64 only

Components and Options

Components and Option		
AU-102 Biometric	Finger vein scanner	
authentication		
AU-204H Magnetic	Requires WT-506 Working Table	
stripe card reader	V 1 15 11 1 1 1	
AU-205H Universal	Various ID card technologies	
ID card reader	B. I. WE COOK II. TH	
AU-211 CA/PIV	Requires WT-506 Working Table	
solution	December 1 and State and 1 feet and 1 400 at 1 feet	
DF-629 Document feeder	Reversing automatic document feeder, capacity 100 originals	
DF-704	Dual coop automatic decument feeder coppeits 100 originals	
Dr-704 Document feeder	Dual scan automatic document feeder, capacity 100 originals	
DK-510 Copier desk	Provides storage space for print media and other materials	
FK-514 Fax board	Super G3 fax, digital fax functionality	
FK-515 Fax board	Super G3 fax, digital fax functionality, lines 3 & 4 support	
FS-533 Staple finisher	50-sheet stapling, 500 sheets max. output	
FS-534 Staple finisher	50-sheet stapling, 3,300 sheets max. output	
FS-534 + SD-511	50-sheet staple finisher, 20-sheet booklet finisher,	
Booklet finisher	3,300 sheets max. output	
HD-524 Hard disk	Hard disk mirroring, 250 GB	
IC-416 Fiery	Embedded image controller for graphics-intensive applications	
image controller	Occupies for for the body	
JS-506 Job separator	Separation for fax output, etc.	
KH-102	To place USB keyboard	
Keyboard holder	The second of the second	
KP-101 10-Key pad	For use instead of touchscreen	
LK-102 v3	PDF/A, PDF encryption, digital signature	
PDF enhancements	Describes an ideas of a stirm	
LK-104 v3	Provides voice guidance functions	
Voice guidance	Searchable PDF	
LK-105 v4 OCR text recognition	Searchable PDF	
LK-106	Supports native barcode printing	
Barcode fonts	Supports flative barcode printing	
LK-107	Supports native Unicode printing	
Unicode fonts	oupports native officede printing	
LK-108	Supports native OCR A and B font printing	
OCR A and B fonts		
LK-110 v2 Enhanced	Generates various file formats incl. DOCX, XLSX and combines	
image support	LK-102 (encrypted PDF) + LK-105 (searchable PDF/OCR functionality)	
LK-111	Print data compression for reduced network impact	
ThinPrint® Client		
LU-302	8.5" x 11", 3,000 sheets / 52-256 gsm	
Large capacity unit		
MK-730 Mount kit	Banner paper guide	
MK-735 Mount kit	Installation kit for ID card reader	
MK-742 Mount kit	Installation kit for FK-515 fax board	
OC-511 Original cover	Cover instead of auto document feeder	
PC-110	5.5" x 8.5" to 11" x 17", 500 sheets, 52-256 gsm	
Universal tray (x1)		
PC-210	5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52-256 gsm	
Universal tray (x2)		
PC-410	8.5" x 11", 2,500 sheets, 52-256 gsm	
Large capacity tray		
PK-519 Punch kit	2/3-hole punching, autoswitching	
for FS-533		
PK-520 Punch kit	2/3-hole punching, autoswitching	
for FS-534		
RU-513 Relay unit	Required for the FS-534	
SC-508 Security kit	Copy Guard function (2x required when DF-701 is installed)	
SK-602 Staple kit	Added stapling functionality kit	
SP-501 Stamp unit	Added fax stamp capability kit	
UK-212 Wireless LAN	Wireless LAN to network connector	
VI-508 Interface kit	Fiery controller interface card	
for IC-416		
WT-506 Working table	Authentication device placement	



KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446





