



KONICA MINOLTA

Giving Shape to Ideas



Blazing fast output of 85 ppm in color and B&W
Long-running reliability, 750,000-page monthly duty cycle
Enhanced Simitri® HD ² toner for superior halftone and skin-tone reproduction
Image quality that rivals offset printing at a fraction of the cost
Optimized 1200 x 1200 dpi resolution with 8-bit processing
SEAD IV screen processing to continuously maintain image stability over long press runs
Hybrid decurling function for higher productivity
Increased paper handling with 13,890-Sheet capacity and weights from 55 to 350 gsm
Air suction paper handling that ensures virtually jam-free printing
200-Page face-trimmed saddle-stitched booklet option
600-Page perfect-bound books with post-fusing cover insertion
15" Color lcd touch-panel – can be placed anywhere on unit
Fiery®, Creo® and Konica Minolta image controller options

bizhub PRESS C1085

FULL COLOR DIGITAL PRODUCTION PRINTER

press



bizhub PRESS C1085

FULL COLOR DIGITAL PRODUCTION PRINTER

press



Descriptions

bizhub PRESS C1085 Overview

The bizhub® PRESS C1085 can boost your output power, improve your color quality and reduce your costs – delivering up to 85 ppm, simplifying production setup and accepting a wide range of paper stocks and pro-quality finishing options to benefit both commercial printers and in-plant print producers.

System Specifications

Resolution	1,200 x 1,200 dpi x 8 bit 1,200 x 3,600 dpi equivalent
Paper weight	55–350 gsm
Duplex unit	Non-stack type; 55–350 gsm
Paper sizes	330 x 487 mm (up to 13" x 19.2")
Maximum image area	321 x 480 mm
Paper input capacity	Max.: 13,890 sheets
Paper output capacity	Max.: 13,600 sheets
Main unit dimensions	35.5" x 37.5" x 52" (W x D x H)
Main unit weight	948 lb

Productivity

8.5" x 11"	Max. per minute: 85 ppm
11" x 17"	Max. per minute: 46 ppm
12" x 18"	Max. per minute: 43 ppm
8.5" x 11"	Max. per hour: 4,413 pph
11" x 17"	Max. per hour: 2,399 pph
12" x 18"	Max. per hour: 2,243 pph

Controller

IC-308	External EFI Fiery Controller
IC-310	External EFI Fiery Controller
IC-312*	External CREO Controller
IC-602	Internal Konica Minolta Controller

Scanner Specifications

Scan speed A4	Up to 42 opm
Scan resolution	600 x 600 dpi
Scan modes	TWAIN scan; Scan-to-HDD; Scan-to-FTP; Scan-to-SMB; Scan-to-eMail
Scan formats	TIFF (single and multi page); PDF

Copier Specifications

Gradations	256
Magnification	25–400%, in 0.1% steps
Multiple copies	1–9,999

Options

HM-101	Humidification unit for RU-511
HT-506	Heating unit for PF-707/8
FD-503	Folding and punching unit
FS-532	100-sheet Stapling unit
GP-501	Multi (GBC) punching unit
GP-502	Auto ring binding unit
LS-506	Stacking unit
PB-503	Perfect binding unit
PF-707	Air suction paper feed unit
PF-708	Air suction paper feed unit with ADF
PI-502	Post inserter for FS-532
PK-522	Punch kit for FS-532
RU-510	Reversing Relay unit
RU-511	Decurling Relay unit
SD-506	Saddle stitch unit
SD-510	Saddle stitch unit for FS-532
WT-512	Working Table

*Not available at time of launch.



KONICA MINOLTA

© 2014 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo, Count on Konica Minolta, bizhub, bizhub PRESS, PageScope, Simitri, and Giving Shape to Ideas are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.

KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC.
100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com



Item #: C1085SS
1/15 - S