

Giving Shape to Ideas





High-speed print/copy output: 60 ppm color, 75 ppm B&W Standard dual scanning handles up to 180 originals per minute INFO-Palette display for instant access to more information Large 9" color display with quick tablet-like interface Downloadable apps to improve your productivity Built-in Emperon® print system, universal printer drivers Simitri® HD toner guarantees excellent print quality Scan to email and ftp, scan-to-me, scan-to-home convenience 6,650-Sheet capacity, tab printing support, carbon-copy printing Standard 250 GB HDD for on-board document storage Finishing options for 80-page booklet-making, up to 100-sheet stapling Options for 2/3-hole punch, tri-fold, z-fold, post-insertion and more Internal card reader and other advanced security options ISO 15408 and IEEE 2600.1 Security standards PageScope® suite, optional voice guidance, PDF/A formatting Multiple i-Options to suit the needs of your workflow Fiery image control option for graphics-intensive applications Low power consumption, eco-indicator to help cut costs **EPEAT Gold-certified** Mobile printing support (AirPrint, Google Cloud Print, NFC)

bizhub C754e

COLOR HIGH-VOLUME MULTIFUNCTION PRINTER







bizhub C754e

Superior color, spectacular speed and simple touch-and-swipe operation make the bizhub C754e an ideal document solution for high-volume applications. Output of 60 ppm in color and 75 ppm in B&W keeps work flowing — and you'll have powerful, scalable options to increase your productivity and help control your costs.

System Overview

System Overview	
System memory	2,048 MB
System hard disk	250 GB
Interface	10-BASE-T/100-BASE-TX/1,000-BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4/IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Dual scan	Up to 150 originals / 5.5" x 8.5" to 11" x 17" / 35-210 gsm
document feeder	
Printable paper size	Scanning/Copying: up to 11" x 17"
	Printing: up to 11" x 17" full bleed on 12" x 18" paper Custom paper sizes
	Banner paper max: 11.75" x 47.25"
Printable paper weight	52-300 gsm
Paper input capacity	Standard: 3,650 sheets / Max.: 6,650 sheets
Tray 1	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
Tray 3	1,500 sheets / 8.5" x 11", 5.5" x 8.5", 4" x 6" / 52-256 gsm
Tray 4	1,000 sheets / 8.5" x 11", 5.5" x 8.5", 4" x 6" / 52-256 gsm
Large capacity tray	3,000 sheets / 8.5" x 11" / 52-256 gsm
LU-301 (optional)	
Large capacity tray	2,500 sheets / 8.5" x 11" to 12" x 18" / 52-256 gsm
LU-204 (optional)	
Manual bypass	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes / 50-300 gsm
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52-256 gsm
Finishing modes	Offset, group, sort, punch, post insertion, z-fold, half-fold, tri-fold, booklet
Output capacity	Max. with finisher: 3,300 sheets Max. without finisher: 250 sheets
Stapling (optional)	Max.: 100 sheets or 94 sheets + 2 cover sheets (up to 209 gsm)
Stapling output capacity	Max.: 1000 sheets
Tri-fold	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray), unlimited
Booklet	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output capacity	Max.: 100 sheets (tray), unlimited
Copy/print volume	Max.: 278,000 pages/month ¹
Toner lifetime	Black: 47,200 pages / CMY: 31,500 pages
Imaging unit lifetime	Black: 300,000 pages / 1,200,000 pages (Drum / Developer) CMY: 155,000 pages
Power consumption	120 V / 50/60 Hz, less than 2.1 kW (system)
System dimensions	25.5" x 31.5" x 45.5" (W x D x H)
System weight	Approx. 487.25 lb
, , ,	

Copier	Specifi	cations

Copying process	Electrostatic laser copy, tandem, indirect
Toner system	Simitri® HD Polymerized Toner
Print speed (8.5" x 11")	B&W: Up to 75 ppm (Portrait) / Color: Up to 60 ppm (Portrait)
Print speed (11" x 17")	B&W: Up to 37 ppm (Portrait) / Color: Up to 30 ppm (Portrait)
Autoduplex speed	B&W: Up to 75 ppm (Portrait) / Color: Up to 60 ppm (Portrait)
(8.5" x 11")	
1st copy out time	B&W: 3.6 sec. / Color: 5.3 sec.
Warm-up time	Approx. 22 sec. ²
Copy resolution	600 x 600 dpi
Gradations	256 gradations
Multi-copy	1-9,999
Original format	Up to 11" x 17"
Magnification	25-400% in 0.1% steps, auto zooming
Copy functions	Chapter, cover and page insertion, proof copy (print and screen), adjustment test print, digital art functions, job setting memory, poster mode, image repeat, overlay (optional), stamping, copy protection

Printer Specifications

Print resolution	1,800 x 600 dpi, 1,200 x 1,200 dpi
PDL	PCL6 (XL 3.0), PCL5c, PostScript 3 (ver. 3016), XPS
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 / 2012 ³ Macintosh OS X 10.2.8 or later UNIX / Linux / Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3 emulation
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print

Printer Specifications (Optional)

	(-)
Print controller	Embedded Fiery IC-414
Memory / HDD	2 GB / 160 GB
PDL	PostScript 3 (ver. 3019) PCL 6/5c
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 ³ / 2012 ³ Macintosh OS X 10 2 8 pr later

Scanner Specifications

Scan speed	B&W / Color: up to 180 ipm
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job programs, realtime scan preview

Fax Specifications

Fax	Super G3 (optional)
Transmission	Analog, i-Fax, Color i-Fax, IP-fax
Resolution	Max.: 600 x 600 dpi (ultra-fine)
Compression	MH, MR, MMR, JBIG
Modem	Up to 33.6 Kbps
Destinations	2,100 (single + group)
Functions	Polling, time shift, PC-fax, receipt to confidential box, receipt to

User Box Specifications

ooo. Don opoomounomo	
Storable documents	Max.: 3,000 documents or 10,000 pages
Type of user boxes	Public
	Personal (with password or authentication)
	Group (with authentication)
Type of system boxes	Secure print, encrypted PDF, fax receipt, fax polling, annotation
User box functionality	Reprint, combination, download, sending (Email/FTP/SMB and fax), copy box-to-box

Features

ISO 15408 EAL3
IEEE 2600.1
IP filtering and port blocking
SSL2, SSL3 and TSL1.0 network communication
IPsec support
IEEE 802.1x support
User authentication
Authentication log
Secure print
Hard disk overwrite (8 standard types)
Hard disk data encryption (AES 128)
Memory data auto deletion
Confidential fax receipt,
Print user data encryption
Copy protection (Copy Guard, Password Copy) optional
Up to 1,000 user accounts
Active Directory support
(user name + password + Email + SMB folder)
User function access definition
Optional Biometric authentication (finger vein scanner)
Optional ID card authentication (ID card reader)
PageScope Net Care Device Manager
PageScope Data Administrator
PageScope Box Operator
PageScope Direct Print
Print Status Notifier
Driver Packaging Utility
Log Management Utility

Log Mariagerifient Unity

1 Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis.

This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs

2 Warm-up time may vary depending on the operating environment and usage

3 Supports x64 only

Components and Options

Components and Option	S
AU-102 Biometric	Finger vein scanner
authentication	
EK-604 USB I/F kit	USB keyboard connection
EK-605 USB I/F kit	USB keyboard connection, Bluetooth
FK-508 Fax board	Super G3 fax, digital fax functionality, lines 3 & 4 support
FK-511 Fax board	Super G3 fax, digital fax functionality
FS-534 Staple finisher	50-sheet stapling, 3,300 sheets max. output
FS-534 + SD-511	50-sheet staple finisher, 20-sheet booklet finisher,
Booklet finisher	3,300 sheets max. output
FS-535 Staple finisher	100-sheet stapling, 3,200 sheets max. output
IC-414 Fiery controller	Professional color print controller
ID card reader	Various ID card technologies
JS-602 Job separator	Separation for fax output, etc.
for FS-535	T 1 100 1 1 1
KH-102	To place USB keyboard
Keyboard holder	
KP-101 10-Key pad	For use instead of touchscreen
LK-101 v3	Web browser
Web browser	DDE/A DDE accombine divided size of
LK-102 v3	PDF/A, PDF encryption, digital signature
PDF enhancements	Building Control (Control
LK-104 v3	Provides voice guidance functions
Voice guidance	O I . I I
LK-105 v3 OCR text recognition	Searchable PDF
	Companies and the bound of autobian
LK-106 Barcode fonts	Supports native barcode printing
	Curporte native Unicada printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108	Supports native OCR A and B font printing
OCR A and B fonts	Supports fidure Out A and B fort printing
LK-110 Enhanced	Generates various file formats incl. DOCX, XLSX and combines
image support	LK-102 (encrypted PDF) + LK-105 (searchable PDF/OCR functionality)
LK-111	Print data compression for reduced network impact
ThinPrint® Client	Thirt data compression for reduced network impact
LU-204	8.5" x 11" to 12" x 18", 2,500 sheets, 52-256 gsm
Large capacity tray	0.0 X 11 10 12 X 10 , 2,000 011000, 02 200 goin
LU-301	8.5" x 11", 3,000 sheets, 52-256 gsm
Large capacity tray	0.0 X 11 , 0,000 thota, 02 200 gtm
MK-728 Mount kit	Installation kit for FK-508 fax board
MK-735 Mount kit	Installation kit for ID card reader
OT-503 Output tray	Output tray used instead of finisher
PI-505 Post inserter	Cover insertion, post finishing
for FS-535	Cover insertion, post innshing
PK-520 Punch kit	2/3-hole punching, autoswitching
for FS-534	270 Hole parterning, autoswiterning
PK-521 Punch kit	2/3-hole punching, autoswitching
for FS-535	270 Holo partolling, datoowtoning
SC-508 Security kit	Copy Guard function (2x required)
SD-512 Saddle kit for	Booklet finishing, half-fold, tri-fold
FS-535	bookiet iiiisiiirig, riaii-ioid, tii-ioid
SX-4600WAN	Wireless LAN to network connector
Wireless LAN	WITO1030 EAR TO HOUWORK CONTIDUTOR
UK-204	Memory extension for i-Options
i-Option memory	Mornory extension for a options
VI-506 Interface kit	Fiery controller interface card
for IC-414	1.5. j SS. A OHOT HILOTIAGO GALA
WT-506 Working table	Authentication device placement
ZU-606 Z-fold unit	Z-fold for 11" x 17" prints, 2/3-hole punching
for FS-535	2.000 to 1.1. A 17 printe, 20 note performing



KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446





