

Week 9 Code along & Challenge

Lew Bo Cong

2023-10-16

1. Code Along

I. Tidy data

```
library(tidyverse)
```

Slide #8

```
## -- Attaching core tidyverse packages ----- tidyverse 2.0.0 --
## v dplyr      1.1.3      v readr      2.1.4
## v forcats    1.0.0      v stringr   1.5.0
## v ggplot2    3.4.3      v tibble    3.2.1
## v lubridate  1.9.3      v tidyr     1.3.0
## v purrr      1.0.2
## -- Conflicts ----- tidyverse_conflicts() --
## x dplyr::filter() masks stats::filter()
## x dplyr::lag()     masks stats::lag()
## i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all conflicts to become errors
```

```
tidydata <- tribble(
  ~country, ~year, ~cases, ~population,
  "Afghanistan", 1999, 745, 19987071,
  "Afghanistan", 2000, 2666, 20595360,
  "Brazil", 1999, 37737, 172006362,
  "Brazil", 2000, 80488, 174504898,
  "China", 1999, 212258, 1272915272,
  "China", 2000, 213766, 1280428583)
```

tidydata

```
## # A tibble: 6 x 4
##   country      year  cases population
##   <chr>      <dbl> <dbl>      <dbl>
## 1 Afghanistan 1999     745  19987071
## 2 Afghanistan 2000    2666  20595360
## 3 Brazil      1999   37737  172006362
## 4 Brazil      2000   80488  174504898
## 5 China       1999 212258 1272915272
## 6 China       2000 213766 1280428583
```

```
nontidydata <- tribble(
  ~country, ~year, ~rate,
  "Afghanistan", 1999, "745/19987071",
  "Afghanistan", 2000, "2666/20595360",
  "Brazil", 1999, "37737/172006362",
  "Brazil", 2000, "80488/174504898",
  "China", 1999, "212258/1272915272",
  "China", 2000, "213766/1280428583")
```

```
nontidydata
```

```
## # A tibble: 6 x 3
##   country      year rate
##   <chr>      <dbl> <chr>
## 1 Afghanistan 1999 745/19987071
## 2 Afghanistan 2000 2666/20595360
## 3 Brazil      1999 37737/172006362
## 4 Brazil      2000 80488/174504898
## 5 China       1999 212258/1272915272
## 6 China       2000 213766/1280428583
```

```
tidydata %>%
  group_by(year) %>%
  summarize(total_cases = sum(cases))
```

Slide 9

```
## # A tibble: 2 x 2
##   year total_cases
##   <dbl>      <dbl>
## 1 1999      250740
## 2 2000      296920
```

II. Tidy-ing data

```
nontidydata
```

Slide 11

```
## # A tibble: 6 x 3
##   country      year rate
##   <chr>      <dbl> <chr>
## 1 Afghanistan 1999 745/19987071
## 2 Afghanistan 2000 2666/20595360
## 3 Brazil      1999 37737/172006362
## 4 Brazil      2000 80488/174504898
## 5 China       1999 212258/1272915272
## 6 China       2000 213766/1280428583
```

```
tidieddata <- nontidydata %>%
  separate(rate, into = c("cases",
                          "population"),
           sep = "/")
```

```
tidieddata
```

```
## # A tibble: 6 x 4
##   country      year cases population
##   <chr>      <dbl> <chr>   <chr>
## 1 Afghanistan 1999  745    19987071
## 2 Afghanistan 2000 2666    20595360
## 3 Brazil       1999 37737   172006362
## 4 Brazil       2000 80488   174504898
## 5 China        1999 212258  1272915272
## 6 China        2000 213766  1280428583
```

```
newtidieddata <- tidieddata %>%
  pivot_longer(
    cols = cases:population,
    names_to = "measurement",
    values_to = "value"
  )
```


```
newtidieddata
```

Slide 12

```
## # A tibble: 12 x 4
##   country      year measurement value
##   <chr>      <dbl> <chr>      <chr>
## 1 Afghanistan 1999 cases      745
## 2 Afghanistan 1999 population 19987071
## 3 Afghanistan 2000 cases      2666
## 4 Afghanistan 2000 population 20595360
## 5 Brazil       1999 cases      37737
## 6 Brazil       1999 population 172006362
## 7 Brazil       2000 cases      80488
## 8 Brazil       2000 population 174504898
## 9 China        1999 cases      212258
## 10 China       1999 population 1272915272
## 11 China       2000 cases      213766
## 12 China       2000 population 1280428583
```

```
ggplot(newtidieddata) +
  aes(x = year, y = value, colour = country) +
  geom_point() +
```

```
geom_line(aes(group = country)) +
facet_wrap(~measurement) +
theme_bw()
```



Slide 13

```
df <- tribble(
  ~id, ~bp1, ~bp2,
  "A", 100, 120,
  "B", 140, 115,
  "C", 120, 125
)

df
```

Slide 14

```
## # A tibble: 3 x 3
##   id      bp1  bp2
##   <chr> <dbl> <dbl>
## 1 A      100   120
## 2 B      140   115
## 3 C      120   125
```

```
df %>%
  pivot_longer(
    cols = bp1:bp2,
    names_to = "measurement",
    values_to = "value"
  )
```

```
## # A tibble: 6 x 3
##   id   measurement value
##   <chr> <chr>      <dbl>
## 1 A     bp1         100
## 2 A     bp2         120
## 3 B     bp1         140
## 4 B     bp2         115
## 5 C     bp1         120
## 6 C     bp2         125
```

```
newtidieddata
```

Slide 18

```
## # A tibble: 12 x 4
##   country      year measurement value
##   <chr>      <dbl> <chr>      <chr>
## 1 Afghanistan 1999 cases      745
## 2 Afghanistan 1999 population 19987071
## 3 Afghanistan 2000 cases      2666
## 4 Afghanistan 2000 population 20595360
## 5 Brazil       1999 cases      37737
## 6 Brazil       1999 population 172006362
## 7 Brazil       2000 cases      80488
## 8 Brazil       2000 population 174504898
## 9 China        1999 cases      212258
## 10 China       1999 population 1272915272
## 11 China       2000 cases      213766
## 12 China       2000 population 1280428583
```

```
newtidieddata %>%
  pivot_wider(names_from = "measurement",
              values_from = "value")
```

```
## # A tibble: 6 x 4
##   country      year cases population
##   <chr>      <dbl> <chr>      <chr>
## 1 Afghanistan 1999 745      19987071
## 2 Afghanistan 2000 2666     20595360
## 3 Brazil       1999 37737    172006362
## 4 Brazil       2000 80488    174504898
## 5 China        1999 212258   1272915272
## 6 China        2000 213766   1280428583
```

```
df <- tribble(
  ~id, ~measurement, ~value,
  "A", "bp1", 100,
  "B", "bp1", 140,
  "B", "bp2", 115,
  "A", "bp2", 120,
  "A", "bp3", 105
)

df
```

Slide 19

```
## # A tibble: 5 x 3
##   id      measurement value
##   <chr> <chr>         <dbl>
## 1 A      bp1           100
## 2 B      bp1           140
## 3 B      bp2           115
## 4 A      bp2           120
## 5 A      bp3           105
```

```
df %>%
  pivot_wider(
    names_from = measurement,
    values_from = value
  )
```

```
## # A tibble: 2 x 4
##   id      bp1      bp2      bp3
##   <chr> <dbl> <dbl> <dbl>
## 1 A      100    120    105
## 2 B      140    115     NA
```

III. Scraping data

```
library(rvest)
```

Slide 22

```
##
## Attaching package: 'rvest'

## The following object is masked from 'package:readr':
##
##   guess_encoding
```

```
webpage <- read_html("https://books.toscrape.com")
table <- html_elements(webpage, "body")
```

IV. Access & Collect data using APIs in R

```
library(c(httr, jsonlite))

# current data
current_county_data_url <-
  "https://api.covidactnow.org/v2/counties.csv?apiKey=YOUR_KEY_HERE"
raw_data <- GET(current_county_data_url)
raw_data$status
raw_data$content

# historic data
historic_county_data_url <-
  "https://api.covidactnow.org/v2/counties.timeseries.csv?apiKey=YOUR_KEY_HERE"
raw_data <- GET(historic_county_data_url)
raw_data$status
raw_data$content

# individual location data
individual_loc_data_url <-
  "https://api.covidactnow.org/v2/county/{state}.csv?apiKey=YOUR_KEY_HERE"
raw_data <- GET(individual_loc_data_url)
raw_data$status
raw_data$content
```

Slide 25


2. Challenge

Part 1

```
library(tidyverse)

tidiedbill <- billboard %>%
  pivot_longer(
    cols = starts_with("wk"),
    names_to = "week",
    values_to = "rank",
    values_drop_na = TRUE
  ) %>% mutate(week = parse_number(week))

ggplot(tidiedbill) +
  aes(x = week, y = rank) +
  geom_line()
```



Part 2

```
tidiedcms <- cms_patient_experience %>%
  pivot_wider(
    id_cols = starts_with("org"),
    names_from = measure_cd,
    values_from = prf_rate
  )
```

tidiedcms

```
## # A tibble: 95 x 8
##   org_pac_id org_nm CAHPS_GRP_1 CAHPS_GRP_2 CAHPS_GRP_3 CAHPS_GRP_5 CAHPS_GRP_8
##   <chr>      <chr>      <dbl>      <dbl>      <dbl>      <dbl>      <dbl>
## 1 0446157747 USC C~         63         87         86         57         85
## 2 0446162697 ASSOC~         59         85         83         63         88
## 3 0547164295 BEAVE~         49        NA         75         44         73
## 4 0749333730 CAPE ~         67         84         85         65         82
## 5 0840104360 ALLIA~         66         87         87         64         87
## 6 0840109864 REX H~         73         87         84         67         91
## 7 0840513552 SCL H~         58         83         76         58         78
## 8 0941545784 GRITM~         46         86         81         54        NA
## 9 1052612785 COMMU~         65         84         80         58         87
## 10 1254237779 OUR L~         61        NA         NA         65        NA
```



```
## # i 85 more rows
## # i 1 more variable: CAHPS_GRP_12 <dbl>
```