"Bodh", BPIT's International Journal of Technology & Management ISSN: 2454-8421, Volume 1 Issue IV, July to December, 2017



Multimodal Medical Image Informatics with Lifting wavelet Transform based **Fusion Scheme**

JayantBhardwaj¹, Member, IEEE, Abhijit Nayak²

¹ECE Department, ²Physics Department, ^{1,2}BPIT, ^{1,2}Delhi,India ¹jayantbhardwaj89@yahoo.in ² nayakabhijit1972@gmail.com

Image informatics means maintaining and extracting useful and relevant information of an image and especially aiming for medical images. This paper is based on the concept of fusion of digital medical images and further comparative assessment of individual images with fused image. Fusion of images is done using a unique wavelet transform called Lifting. Images are assessed by calculating their individual mean value, standard deviation, average information entropy, average gradient and cross entropy.

Keywords -fusion, digital, medical images, wavelet transform, lifting, mean value, standard deviation, information entropy, gradient, cross entropy.

Due to image sensor malfunction and physical limitations valuable information in any medical image can be I. Introduction noised [1],[2]. Many de-noising schemes are generally used to improve visual features in an image. Many a times more than one image is taken for a particular scene to enhance the information level and then combined and mingled into a single image so to improve richness of combined image according to featured information's expressed in individual medical images [2]. This process of feature extraction and combined into a single image is called image fusion [3],[7]. Now this fused image has all the information from both images[4]. This type of fusion is called feature level fusion as the features like edges ,boundaries and patches etc can get finally extracted[31]. Note here that feature level fusion emphasizes on the features like any crack, patch and boundary wall etc as an anomaly in any medical image[17],[20]. The increased contrast, entropy (information) and average gradient value in the fused image explains the usefulness of fused image as compared to individual images[5],[6],[8],[11].

II. Overview of wavelet Transform

Continuous wavelet Transform (CWT)

The CWT or continuous-time wavelet transform of f(t) with respect to a wavelet $\psi(t)$ is defined as

© "BBIJTM 2017", All rights Reserved

$$W(a,b) = \int_{-\infty}^{+\infty} f(t) \frac{1}{\sqrt{|a|}} \psi * (\frac{t-b}{a}) dt$$
 (1)

 $W(a,b)=\int_{-\infty}^{\infty} f(t) \sqrt{|a|} \psi^{-1}(a) dt$ Where a and b are real and * denotes complex conjugation. Thus , the wavelet transform is a function of two Where a and b are real and * denotes complete to be while b is called translation variable .The mother variables[9],[10],[28]. The a is called dilation variable while b is called translation variable .The mother wavelet should posses following properties[29],[30].

(a) The function integrates to zero.

$$\int_{-\infty}^{+\infty} (t) dt = 0$$
 (2)

(b) It is square integrable or equivalently has finite energy

$$\int_{-\infty}^{+\infty} |(t)|^2 dt < \infty$$
 (3)

Discrete Wavelet Transform (DWT)

This equation (4) is a type of non redundant wavelet representation[27],[30].

$$f(t) = \sum_{k=-\infty}^{\infty} \sum_{l=-\infty}^{\infty} d(k, l) 2^{-k/2} \psi(2^{-k}t - l)$$
 (4)

 $f(t) = \sum_{k=-\infty}^{\infty} \sum_{l=-\infty}^{\infty} d(k, l) \ge -\frac{1}{2} \psi(z) t$ Equation (4) uses discrete values for dilation and translation parameters. The dilation takes values of the form a = 2^k where k is an integer. At any dilation 2^k , the translation parameter takes values of the form $2^k l$ where lis again an integer[12],[14]. The values d(k, l) are related to values of the wavelet transform

$$W(a,b) = W[f(t)]$$
 (5)

at $a = 2^k$ and $b = 2^k l$. This corresponding to sampling the coordinates (a,b) on a grid. The two-dimentional sequence d(k, l) is referred to as the discrete wavelet transform (DWT) of f(t) [13].

III. Lifting Wavelet Transform

Lifting wavelet transform is a multi resolution analysis used for the construction of the second generation wavelets. It is an efficient implementation of the wavelet transform algorithm. The discrete wavelet transform (DWT) can be viewed as a predictor-error decomposition[15],[16]. The scaling coefficients at a given scale (j) are "predictors" for the data at the next higher resolution or scale (j-1). The wavelet Coefficients are simply the "prediction errors" between the scaling coefficients and the higher resolution data that they are attempting to predict[18]. This interpretation has led to a new framework for DWT known as the lifting scheme[17]. It lifts the wavelet transform to a more sophisticated level and is implemented by factoring the wavelet transforms into lifting steps. The lifting scheme consists of the iteration of the following three steps[17][19].

(i)Lazy wavelet transform: This step divides the original data $(x[n]) \in R, n \in Z$) into its even and odd polyphase components $x_e[n]$ and $x_o[n]$ respectively where

$$x_e[n]=x[2n]$$
 (6)
 $x_o[n]=x[2n+1]$ (7)

(7)(ii) Predict: This is also called as dual lifting. In this step the odd poly phase coefficients are predicted from the neighbouring even coefficients using a predictor P and the wavelet coefficients (high pass) or details are generated as the error in predicting the odd samples from the even using prediction operator[19],[21].

$$d=x_0-P(x_e) \qquad (8)$$

using these details one can recover the odd components as [20].

$$x_o = P(x_e) + d \tag{9}$$

iii)Update:This is also termed as primal lifting. This step updates the even set using the wavelet coefficients to compute the scaling function coefficients (low pass). It applies an update operator U to detail coefficients obtained in previous step [21],[22],[23].

$$S=x_e+U(d) \qquad (10)$$

This step is also invertible and reproduces x_e as $x_e = s_e U(d)$

Lifting scheme has the advantage of fast implementation of wavelet transform as it makes use of similarities between high possible by standard implementation even though they are lossless in principle. It helps in saving auxiliary possible by such possible by such possible by an end of inverse transform as the inverse transform [26]. Lifting scheme has further advantage of memory as the signs in forward lifting steps[25],[27]. It also not the signs in forward lifting steps[25],[27]. It also not the signs in forward lifting steps[25],[27]. It also not the signs in forward lifting steps[25],[27]. It also not the signs in forward lifting steps[25],[27]. It also not the signs in forward lifting steps[25],[27]. It also not the signs in forward lifting steps[25],[27]. It also not the signs in forward lifting steps[25],[27]. simplicity of the signs in forward lifting steps[25],[27]. It also reduces the computational complexity by a factor of inverting the non-lifting wavelet transform is obtained by reverting the order of operations and inverting the second to non-lifting wavelet transform. It also provides flexibility as compared to classical wavelets[19][24].

IV. Proposed Scheme

- 1. Decomposition of input images using lifting wavelet transform.
- 2. Calculation for Modulus of gradient of lifting wavelet transform.
- 3. Fusion based on threshold value of gradient of wavelet coefficients.
- 4. Inverse lifting wavelet transform of fused image is done.
- 5. Evaluation of image fusion performance.

V. Result Analysis We performed experiments on two teeth x-ray images using Matlab software R2015a. The images are original tooth X-ray of one of co-author of this paper. We named Image 1 as M1 and image 2 as M2. The fused image F1 is obtained with all improved evaluation parameters. The parameters calculated for discussed images are mean value (shows average intensity), average gradient (detail information) ,average entropy (information) , cross entropy (fidelity) and standard deviation(contrast in image). The high value has been found for all discussed parameters except cross entropy in case of fused image as compare to individual images M1 and M2. Low value of cross entropy for fused image shows its fidelity with individual images.

TABLE I. Assessment Result for Images

Paramete rs	Image (M1)	Image(M	Fused Image (F1)
Mean Value	12.8434	13.7624	16.1981
Average Gradient	0.2794	0.3213	0.3821
Standard Deviation	157.8302	158.830 2	163.214
Informatio n Entropy	2.27	2.37	3.680
Cross Entropy	-	-	0.746




Figure.1. Image 1(M1)



Figure.2. Image 2 (M2)



Figure.3 Fused Image (F1)

References

[1] Pengfei Chai, Xiaoqing Luo and Zhancheng Zhang, "Image Fusion Using Quaternion Wavelet Transform and Multiple Features", *IEEE Trans. Image Process.*, vol. 17, no. 4, pp. 500–511, 2017.

[2] K. Raghesh Krishnan, Sudhakar Radhakrishnan, "Hybrid approach to classification of focal and diffused liver disorders using ultrasound images with wavelets and texture features", *IET Image Process.*, vol. 11, pp. 530-

[3] Zhenxuan Li, Wenzhong Shi, Hua Zhang, and Ming Hao, "Change Detection Based on Gabor Wavelet Features for Very High Resolution Remote Sensing Images", IEEE Geosci. And Remote Sensing Letters, vol. 17, no. 4, pp. 1–5, 2017.

- Yang, Yue Que, and Pan Lin, "Multiple Visual Features Measurement With Gradient Domain Guided Filtering for Multisensor Image Fusion", IEEE Trans. Instrumentation and Measurement., 2017.
- [5] Naushad Ansari, Anubha Gupta, "Image Reconstruction using Matched Wavelet Estimated from Data Sensed Compressively using Partial Canonical Identity Matrix", *IEEE Trans. Image Process.*, vol. 17, no. 4, pp. 500–511, 2016.
- [6] Paul Hill, Mohammed E. Al-Mualla and David Bull,"Perceptual Image Fusion using Wavelets", IEEE Trans. Image Process., vol. 17, no. 4, pp. 1-13, 2016.
- [7] Zhangkai Ni, Lin Ma, Huanqiang Zeng, Canhui Cai, and Kai-Kuang Ma, "Gradient Direction for Screen Content Image Quality Assessment", IEEE Signal Process. Letters, pp.1-5,2016.
- [8] Jorge Guevara Escobedo and Krikor B. Ozanyan, "Tiled-Block Image Reconstruction by Wavelet-Based, parallel Filtered Back-Projection", *IEEE Sensors journal*, pp.1-8,2016.
- [9] Li-juan Wang, Jing Han, Yi Zhang, Lian-fa Bai,"Image fusion via feature residual and statistical matching", IET computer vision.,vol. 10, pp. 551-558,2016.
- [10] Francesc Auli-Llinas, "Entropy-based evaluation of context models for wavelet-transformed images", *IEEE Trans. Image Process.*, vol. 24, no. 1, pp. 57-67, Jan. 2015.
- [11] Qingsong Zhu, Jiaming Mai, and Ling Shao,"A fast single image haze removal algorithm using color attenuation prior", *IEEE Trans. Image Process.*, vol. 24, NO. 11, NOV. 2015.
- [12] T.B. Tang, C.K. Lu, A. Laude, B. Dhillon and A.F. Murray," Noise reduction for ellipse fitting on medical images", *Electronics Letters* vol. 49, No. 3,Jan. 2013.
- [13] A. Padma Nanthagopal, R. Sukanesh, "Wavelet statistical texture features-based segmentation and classification of brain computed tomography images", *IET Image Process.*, vol. 7, pp. 25–32, 2013.
- [14] Tao Wan, Nishan Canagarajah ,and Alin Achim," Segmentation-driven image fusion based on alpha-stable modeling of wavelet coefficients", *IEEE Trans. Multi.*, vol. 11, NO. 4,pp. 624-633,June 2009.
- [15] Li Jing, Huang Peikang, Wang Xiaohu & Pan Xudong," Image edge detection based on beamlet transform", *Journal of Systems Eng. and Elec.* vol. 20, No. 1, pp. 1-5,2009.
- [16] Hossein Rabbani, Mansur Vafadust, Purang Abolmaesumi, and Saeed Gazor, "Speckle noise reduction of medical ultrasound images in complex wavelet domain using mixture priors", *IEEE Trans. Bio.Med. Eng.*, vol. 55, NO. 9, pp. 2152-2160, Sept. 2008.
- [17] Guan-Hao Chen, Chun-Ling Yang, Sheng Li Xie, "Gradient based structural similarity for image quality assessment", *Proc. Int. Conf. Image Process.*, pp. 2929-2932,2006.
- [18] S. Alkaabi and F. Deravi, "Gradient direction similarity measure", Elect. Letters, vol. 39, No. 23, Nov. 2003.

- [19] Javier Portilla, Vasily Strela, Martin J. Wainwright, and Eero P. Simoncelli, "Image Denoising Using Scale Mixtures of Gaussians in the Wavelet Domain", *IEEE Trans. Image Process.*, vol. 12, no.11, pp. 1338-1351, Nov 2003.
- [20] Sabine Dippel, Martin Stahl, Rafael Wiemker, and Thomas Blaffert, "Multiscale contrast enhancement for radiographies: laplacian pyramid versus fast wavelet transform", *IEEE Trans.Medical Imag.*, vol. 21, no. 4, pp.343-353, Apr. 2002.
- [21] Anca Dima, Michael Scholz, and Klaus Obermayer,"Automatic segmentation and skeletonization of neurons from confocal microscopy images based on the 3-D wavelet transform", *IEEE Trans. Image Process.*,vol. 11, no. 7, pp.790-801,Jul. 2002.
- [22] Jean-Luc Starck, Emmanuel J. Candes, and David L. Donoho," The Curvelet Transform for Image Denoising", *IEEE Trans. Image Process.*, vol.11, no. 6,pp. 670-684, June 2002.
- [23] Zhao Jian, Li Daojing1, Yu Bianzhang and Geng Junping," A new wavelet-based document image segmentation scheme", *Journal of System. Eng. and Elect.*,vol .13, no. 3,pp. 86 90,2002.
- [24] S. Grace Chang, Bin Yu, and Martin Vetterli," Adaptive wavelet thresholding for image denoising and compression", *IEEE Trans. Image Process.*, vol. 9, no. 9, pp. 1532-1546, sept. 2000.
- [25] Crouse MS, Nowak RD and Baraniuk RG, "Wavelet-based statistical signal processing using hidden Markov models", *IEEE Trans. on Signal Processing*.,vol 4,no.38,pp.886-902,1998.
- [26] Stephane Mallat and Wen Liang Hwang, "Singularity Detection and Processing with wavelets", *IEEE Trans. Info. Theory*, vol.38, no. 2, pp.617-643,march 1992.
- [27] Stephane Mallat and Sifen Zhong, "Characterization of signals from multiscale edges", *IEEE Trans. Patt. Analysis.*, vol.14, no. 7, pp.710-732, July 1992.
- [28] Antonini A, Barlaud M, Mathieu P and Daubechies I.,"Image coding using wavelet transform", *IEEE Trans. on Image Processing*.vol.1 no.2, pp. 205-220,1992.
- [29] DeVore RA, Jawerth B and Lucier BJ."Image compression through wavelet transform coding", *IEEE Trans. on Inform.Theory.* vol.38 pp.719-46,1992.
- [30] Lewis A, Knowles G."Image compression using 2-D wavelet transform", *IEEE Trans. Image Processing*. vol.1, no.2,pp.244-50. April,1992.
- [31] Stephane Mallat. "A theory for multiresolution signal decomposition: The wavelet representation", *IEEE Trans. Patt. Analysis.* vol.11. no. 7, pp.674-693, July 1989.



Jayant Bhardwaj is a member of IEEE and OSA. He received the B.Tech (ECE) degree from Guru Gobind Singh Indraprastha university (GGSIPU), Delhi, India, in 2008, and the M.Tech. degree from DTU, Delhi, India, in 2013 in ECE with specialization in Signal Processing. He is

© "BBIJTM 2017", All rights Reserved

phD from GGSIPU, Delhi. He is presently serving as an Assistant Professor in ECE department of Parshuram Institute of Technology, Delhi, India and has 09 years of academic teaching experience. His research interests include digital image & video processing, computer vision, bio-medical imaging & signal processing, machine learning, pattern analysis & recognition.

Abhijit Nayak is presently serving as a HOD and Professor in Applied Physics department of Bhagwan Parshuram Institute of Technology(BPIT), Delhi,India.He is also at the position of Dean (Administration) and has 21 years of academic teaching experience. He has published a book on Applied Physics a decade before and has published many research papers in reputed journals.He completed his PhD in Semiconductor Physics from Delhi University and also served as a faculty in Deen Dayal Upadayay College of same University.He has guided one PhD student and currently doing same for scholars.Along with physics his research interests are signal processing, Medical Image Processing, Semiconductor Physics and Microelectronics.