CASE STUDY: INTELLIGENT SYSTEMS IN PRODUCTION

REVISED TOPIC

AI-powered Quality Control and Defect Detection in Electronics Assembly

Reducing false calls of automated optical inspection (AOI) with Siemens production data

Yu Han · Melisa Subasi · Meron Hagos · Alejandro Rivas

Team 1 · Guided by Dr. Hamidreza Heidari · 23 October 2026 · github.com/bodhi584/aoi-decision-gate

INTRODUCTION

Too many false alarms after automated inspection

98 %

of the boards flagged by the AOI machine are fine (false calls) in real Siemens production data.

Every flagged board goes to a manual inspection station.

Based on the lecture example (p. 18)

“Siemens – Quality Control and Defect Detection”. Key motivations: reduce dependence on manual quality checks, keep product quality, increase efficiency.

A current problem: Siemens and NVIDIA, Erlangen, 21 Oct 2026

AI second check of AOI results: real defect or false call? Target: about 40 % fewer false calls.

Our goal

Fewer false calls sent to manual inspection, without releasing defective boards.

TECHNISCHE HOCHSCHULE DEGGENDORF

ONE GOAL: FEWER FALSE CALLS, WITHOUT RELEASING DEFECTS

Input → System → Output

INPUT

AOI data of a flagged board

about 70 measurements per solder joint

component type, AOI error code

SYSTEM (OURS)

AI decision gate

classifier trained on past manual-inspection results

threshold: ≤ 1 % defective boards released

OUTPUT

Release

likely false call → next step

Manual inspection

possible defect → operator checks

Key factors

False calls

each one costs operator time at the manual station

Missed defects

a released defective board reaches the customer

Changes over time

the line changes; a model must keep up

TECHNISCHE HOCHSCHULE DEGGENDORF

PROJECT SCOPE

What we will and will not do

Aim

This project aims to reduce false calls after automated optical inspection with an AI decision gate, while at most 1 % of defective boards are released.

Includes

- Data preprocessing: Siemens AOI data
- Training three models
- Day-by-day simulation of the line
- Evaluation using standard metrics

Out of scope (current phase)

- Real hardware deployment
- Integration with physical AOI machines
- Changing the AOI camera images

Conditions and limitations

- One Siemens line, 132 days
- Measurements anonymised (no physical names)
- Labels from operators may contain errors
- Licence: non-commercial (course use)

TECHNISCHE HOCHSCHULE DEGGENDORF

What the project will achieve, and how we measure it

1. Reduce false calls: train three models to separate false calls from real defects.
2. Keep quality: set a threshold so that at most 1 % of defective boards are released.
3. Test on the line: integrate the models into a day-by-day simulation of the Siemens line.
4. Compare the three models and identify the most suitable one.

Requirements (two KPIs)

≥ 20 % false-call boards released, i.e. manual inspections saved (baseline 6.4 %)

≤ 1 % defective boards released


TECHNOLOGY STACK

Data science tools from the lecture (p. 22)

Process	Tool / Framework	Purpose
Data preparation	Python, pandas	Load the Siemens AOI data, group joints into boards, keep time order
Model training	scikit-learn	Logistic regression, random forest, neural network (one hidden layer)
Simulation	Python	Day-by-day simulation of the line: release or manual inspection
Evaluation	scikit-learn, pandas	Precision, recall, confusion matrix, boards released
Visualization	matplotlib, Jupyter	Graphical result representation, step-by-step notebook
Code sharing and tests	GitHub, pytest	Repository, tests on every change

PROJECT FLOW CHART

From the Siemens data to the KPIs



Blue boxes: the system we build. White boxes: data and project steps.

WORKING METHODOLOGY

CRISP-DM in four steps

Step 1 · Data preparation

Collected Siemens AOI data: flagged boards, defective & false call

Grouped solder joints into boards; encoded categories

Split data in time order into train, validate, test sets

Step 2 · Model development

Trained logistic regression as baseline

Trained random forest and a neural network (one hidden layer)

Set the threshold: ≤ 1 % defective boards released

Step 3 · Simulation integration

Simulated the line day by day

Each day decided by a model trained on earlier days only

Boards are virtually routed to release or manual inspection

Step 4 · Evaluation and comparison


Analyzed precision, recall, defects released, inspections saved

Compared the three models to identify the best-performing one

Error analysis; demo video and report

TECHNISCHE HOCHSCHULE DEGGENDORF

Day-by-day simulation of the line: three models running



What it shows

Today: 6–15 % of false-call boards released (manual inspections saved).

But 2.2–3.7 % of defective boards slip through: above the 1 % limit.

Next: ≥ 20 % released at ≤ 1 % defects.

BILL OF MATERIALS (BOM)

What the project needs

Component	Specification	Quantity	Cost
Data set	Siemens AOI data, Mendeley (CC BY-NC 3.0), 333 MB	1	Free
Computer	Normal laptop or Google Colab (no graphics card needed)	4	Free
Software	Python and open-source libraries	–	Free
Code hosting	GitHub	1 repository	Free

Total cost: 0 €

TECHNISCHE HOCHSCHULE DEGGENDORF

EXPECTED OUTCOMES

What we hand in

- ✓ Successfully trained AI decision gate (Python software prototype)
- ✓ Functional day-by-day simulation of the line with decision routing
- ✓ Comparative performance metrics for the three models
- ✓ Identification of the most suitable model, with limits and error analysis
- ✓ Demo video, run instructions, report, public GitHub repository

TECHNISCHE HOCHSCHULE DEGGENDORF THD

SAFETY & ETHICAL CHECKLIST

Keeping it safe and realistic

- ✓ Simulation-only environment; no physical machinery risk
- ✓ Dataset is anonymized by Siemens (no personal data); used under its licence
- ✓ Ethical AI principles followed: transparency, fairness, accountability
- ✓ Avoid dataset bias (time-ordered split) and ensure reproducibility of results
- ✓ Safety first in the design: limit on released defective boards

TECHNISCHE HOCHSCHULE DEGGENDORF

FUTURE WORK

From the public data set to a real line

1 · Industry partner

An electronics plant shares AOI and manual-inspection records.

2 · AOI interface

Read each board’s AOI result from the machine; send the decision to the repair station.

3 · Shadow mode

The gate runs next to the operators and only logs its decisions.

4 · Approval

Quality engineers compare the logs before any board is released.

BIBLIOGRAPHY

Sources

Pfab, K., Eichler, R., Mallandur, A., Rothering, M. (2024). Data of automated optical inspection of surface-mounted technology electronic production. Data in Brief 53, 110110.

Siemens (21 Oct 2026). Siemens and NVIDIA advance AI-powered PCB inspection from digital twin to factory. Press release.


Albayari, J., Patra, P., Patel, D., Santos, D. (2025). Enhancing false call detection in automated optical inspection using XGBoost classifier and XAI algorithms. FAIM 2025, Springer.

Pedregosa, F. et al. (2011). Scikit-learn: Machine learning in Python. Journal of Machine Learning Research 12, 2825–2830.

Chapman, P. et al. (2000). CRISP-DM 1.0: Step-by-step data mining guide. SPSS.

Lecture slides, Case Study Intelligent Systems in Production, p. 8, 12, 18, 22, 33.

Software & Simulation project, S1–S6 (lecture p. 8, 33)



Repository link

github.com/bodhi584/aoi-decision-gate

Thank you

Team 1 · Yu Han · Melisa Subasi · Meron Hagos · Alejandro Rivas