

```

No.      Time      Source      Destination      Protocol Length Info
 158 19.731421    192.168.1.109 128.119.245.12  HTTP      454    GET /wireshark-labs/INTRO-wireshark-file1.html HTTP/1.1
Frame 158: 454 bytes on wire (3632 bits), 454 bytes captured (3632 bits) on interface \Device\NPF_{49DF0F62-4813-4384-9C3C-CAAE385DA4BA}, id 0
Ethernet II, Src: HonHaiPr_d6:62:3b (d8:9c:67:d6:62:3b), Dst: Tp-LinkT_98:38:a0 (90:f6:52:98:38:a0)
Internet Protocol Version 4, Src: 192.168.1.109, Dst: 128.119.245.12
Transmission Control Protocol, Src Port: 53377, Dst Port: 80, Seq: 1, Ack: 1, Len: 400
Hypertext Transfer Protocol
No.      Time      Source      Destination      Protocol Length Info
 162 19.866580    128.119.245.12 192.168.1.109  HTTP      491    HTTP/1.1 200 OK (text/html)
Frame 162: 491 bytes on wire (3928 bits), 491 bytes captured (3928 bits) on interface \Device\NPF_{49DF0F62-4813-4384-9C3C-CAAE385DA4BA}, id 0
Ethernet II, Src: Tp-LinkT_98:38:a0 (90:f6:52:98:38:a0), Dst: HonHaiPr_d6:62:3b (d8:9c:67:d6:62:3b)
Internet Protocol Version 4, Src: 128.119.245.12, Dst: 192.168.1.109
Transmission Control Protocol, Src Port: 80, Dst Port: 53377, Seq: 1, Ack: 401, Len: 437
Hypertext Transfer Protocol
Line-based text data: text/html (3 lines)
No.      Time      Source      Destination      Protocol Length Info
 165 19.977756    192.168.1.109 128.119.245.12  HTTP      334    GET /favicon.ico HTTP/1.1
Frame 165: 334 bytes on wire (2672 bits), 334 bytes captured (2672 bits) on interface \Device\NPF_{49DF0F62-4813-4384-9C3C-CAAE385DA4BA}, id 0
Ethernet II, Src: HonHaiPr_d6:62:3b (d8:9c:67:d6:62:3b), Dst: Tp-LinkT_98:38:a0 (90:f6:52:98:38:a0)
Internet Protocol Version 4, Src: 192.168.1.109, Dst: 128.119.245.12
Transmission Control Protocol, Src Port: 53376, Dst Port: 80, Seq: 1, Ack: 1, Len: 280
Hypertext Transfer Protocol
No.      Time      Source      Destination      Protocol Length Info
 169 20.116358    128.119.245.12 192.168.1.109  HTTP      538    HTTP/1.1 404 Not Found (text/html)
Frame 169: 538 bytes on wire (4304 bits), 538 bytes captured (4304 bits) on interface \Device\NPF_{49DF0F62-4813-4384-9C3C-CAAE385DA4BA}, id 0
Ethernet II, Src: Tp-LinkT_98:38:a0 (90:f6:52:98:38:a0), Dst: HonHaiPr_d6:62:3b (d8:9c:67:d6:62:3b)
Internet Protocol Version 4, Src: 128.119.245.12, Dst: 192.168.1.109
Transmission Control Protocol, Src Port: 80, Dst Port: 53376, Seq: 1, Ack: 281, Len: 484
Hypertext Transfer Protocol
Line-based text data: text/html (7 lines)
No.      Time      Source      Destination      Protocol Length Info
 208 28.420884    192.168.1.109 149.154.167.51  HTTP      94     POST /api HTTP/1.1 (application/x-www-form-urlencoded)
Frame 208: 94 bytes on wire (752 bits), 94 bytes captured (752 bits) on interface \Device\NPF_{49DF0F62-4813-4384-9C3C-CAAE385DA4BA}, id 0
Ethernet II, Src: HonHaiPr_d6:62:3b (d8:9c:67:d6:62:3b), Dst: Tp-LinkT_98:38:a0 (90:f6:52:98:38:a0)
Internet Protocol Version 4, Src: 192.168.1.109, Dst: 149.154.167.51
Transmission Control Protocol, Src Port: 53380, Dst Port: 80, Seq: 227, Ack: 1, Len: 40
[2 Reassembled TCP Segments (266 bytes): #205(226), #208(40)]
Hypertext Transfer Protocol
HTML Form URL Encoded: application/x-www-form-urlencoded
No.      Time      Source      Destination      Protocol Length Info
 209 28.421224    192.168.1.109 149.154.167.51  HTTP      94     POST /api HTTP/1.1 (application/x-www-form-urlencoded)
Frame 209: 94 bytes on wire (752 bits), 94 bytes captured (752 bits) on interface \Device\NPF_{49DF0F62-4813-4384-9C3C-CAAE385DA4BA}, id 0
Ethernet II, Src: HonHaiPr_d6:62:3b (d8:9c:67:d6:62:3b), Dst: Tp-LinkT_98:38:a0 (90:f6:52:98:38:a0)
Internet Protocol Version 4, Src: 192.168.1.109, Dst: 149.154.167.51
Transmission Control Protocol, Src Port: 53381, Dst Port: 80, Seq: 227, Ack: 1, Len: 40
[2 Reassembled TCP Segments (266 bytes): #202(226), #209(40)]
Hypertext Transfer Protocol
HTML Form URL Encoded: application/x-www-form-urlencoded
No.      Time      Source      Destination      Protocol Length Info
 657 31.631451    192.168.1.109 149.154.167.51  HTTP      94     POST /api HTTP/1.1 (application/x-www-form-urlencoded)
Frame 657: 94 bytes on wire (752 bits), 94 bytes captured (752 bits) on interface \Device\NPF_{49DF0F62-4813-4384-9C3C-CAAE385DA4BA}, id 0
Ethernet II, Src: HonHaiPr_d6:62:3b (d8:9c:67:d6:62:3b), Dst: Tp-LinkT_98:38:a0 (90:f6:52:98:38:a0)
Internet Protocol Version 4, Src: 192.168.1.109, Dst: 149.154.167.51
Transmission Control Protocol, Src Port: 53385, Dst Port: 80, Seq: 227, Ack: 1, Len: 40
[2 Reassembled TCP Segments (266 bytes): #654(226), #657(40)]
Hypertext Transfer Protocol
HTML Form URL Encoded: application/x-www-form-urlencoded
No.      Time      Source      Destination      Protocol Length Info
 658 31.631531    192.168.1.109 149.154.167.51  HTTP      94     POST /api HTTP/1.1 (application/x-www-form-urlencoded)
Frame 658: 94 bytes on wire (752 bits), 94 bytes captured (752 bits) on interface \Device\NPF_{49DF0F62-4813-4384-9C3C-CAAE385DA4BA}, id 0
Ethernet II, Src: HonHaiPr_d6:62:3b (d8:9c:67:d6:62:3b), Dst: Tp-LinkT_98:38:a0 (90:f6:52:98:38:a0)
Internet Protocol Version 4, Src: 192.168.1.109, Dst: 149.154.167.51
Transmission Control Protocol, Src Port: 53384, Dst Port: 80, Seq: 227, Ack: 1, Len: 40
[2 Reassembled TCP Segments (266 bytes): #653(226), #658(40)]
Hypertext Transfer Protocol
HTML Form URL Encoded: application/x-www-form-urlencoded

```