speedtest

Benjamin Christoffersen

2017-07-20

Setup

```
library(dynamichazard); library(microbenchmark)
```

```
## Loading required package: survival
```

```
sim_func <- function(n, p){
  func <- asNamespace("dynamichazard")$test_sim_func_logit
  set.seed(101)
  t_max <- 30L
  func(n_series = n, n_vars = p, t_max = t_max, x_range = 1, x_mean = 0,
       beta_start = runif(p, -1.5, 1.5),
       intercept_start = -3, sds = c(.1, rep(.25, p)),
       tstart_sampl_func = function(t0, t_max)
         max(0, runif(1, -t_max, t_max - 1L)),
       lambda = 1 / 10)
}

get_rune_time_summary <- function(n, p){
  sims <- sim_func(n, p)

  out <- summary(microbenchmark(
    EKF_one_correction_step =
      suppressMessages(ddhazard(
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1e6, p + 1L),
        Q = diag(1e-1, p + 1L))),

    EKF_more_correction_step =
      suppressMessages(ddhazard(
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1, p + 1L),
        Q = diag(1e-1, p + 1L),
        control = list(NR_eps = 1e-3))),

    SMA = suppressMessages(ddhazard(
```

```
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1e6, p + 1L),
        Q = diag(1e-1, p + 1L),
        control = list(method = "SMA"))),

    GMA = suppressMessages(ddhazard(
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1, p + 1L),
        Q = diag(1e-1, p + 1L),
        control = list(method = "GMA"))),

    UKF = suppressMessages(ddhazard(
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1, p + 1L),
        Q = diag(1e-1, p + 1L),
        control = list(method = "UKF"))),

    times = 5
  ))

  cat("(n, p) = (", n, ", ", p, ")",
      ". Units is ", sQuote(attr(out, "unit")), "\n", sep = "")

  print(out[, c("expr", "lq", "median", "uq", "cld")], row.names = FALSE)

  cat("\n\n")

  invisible()
}
```

Test

```
grid_vals <- expand.grid(
  n = c(250, 1000, 10000),
  p = c(5, 10, 15))
```

```r
invisible(
  mapply(get_rune_time_summary, n = grid_vals$n, p = grid_vals$p))
```

```
## (n, p) = (250, 5). Units is 'milliseconds'
##                       expr   lq median    uq cld
##   EKF_one_correction_step 22.8   23.9  24.2   a
##  EKF_more_correction_step 35.2   36.2  36.4   a
##                       SMA 92.5   93.4 100.1   a
##                       GMA 39.0   44.1  44.8   a
##                       UKF 83.1   84.4  86.8   a
##
##
## (n, p) = (1000, 5). Units is 'milliseconds'
##                       expr    lq median    uq  cld
##   EKF_one_correction_step  33.6   34.5  35.8 a
##  EKF_more_correction_step  54.8   55.2  64.5   c
##                       SMA  63.1   67.6  71.3   c
##                       GMA  47.8   47.9  49.0  b
##                       UKF 116.6  117.2 122.4    d
##
##
## (n, p) = (10000, 5). Units is 'milliseconds'
##                       expr  lq median  uq cld
##   EKF_one_correction_step 176    258 263 a
##  EKF_more_correction_step 338    349 437  b
##                       SMA 536    614 637   c
##                       GMA 217    230 306 a
##                       UKF 613    698 705   c
##
##
## (n, p) = (250, 10). Units is 'milliseconds'
##                       expr    lq median    uq  cld
##   EKF_one_correction_step  46.8   48.9  50.1 a
##  EKF_more_correction_step  86.9   87.2  92.1  b
##                       SMA 157.9  162.5 170.9   c
##                       GMA  79.8   82.8  84.7  b
##                       UKF 376.0  377.9 381.2    d
##
##
## (n, p) = (1000, 10). Units is 'milliseconds'
##                       expr    lq median    uq  cld
##   EKF_one_correction_step  44.0   45.8  50.5 a
##  EKF_more_correction_step  63.8   69.6  73.5  b
##                       SMA 118.2  120.2 124.0   c
##                       GMA  57.5   59.9  64.9 ab
##                       UKF 237.0  238.6 241.7    d
##
##
## (n, p) = (10000, 10). Units is 'milliseconds'
##                       expr   lq median   uq  cld
##   EKF_one_correction_step  335    343  345 a
##  EKF_more_correction_step  413    413  529  b
##                       SMA  849    853  866   c
##                       GMA  304    385  392 a
```

```
##                       UKF 1142   1180 1191    d
##
##
## (n, p) = (250, 15). Units is 'milliseconds'
##                      expr    lq median    uq  cld
##   EKF_one_correction_step 111.8  113.0 116.7  b
##  EKF_more_correction_step  99.0  103.6 106.2 ab
##                       SMA 195.6  200.8 203.6   c
##                       GMA  90.2   92.2  92.2 a
##                       UKF 489.3  490.3 494.7    d
##
##
## (n, p) = (1000, 15). Units is 'milliseconds'
##                      expr    lq median    uq  cld
##   EKF_one_correction_step  90.7   92.5  94.4 a
##  EKF_more_correction_step 164.5  172.4 173.1  b
##                       SMA 378.0  439.0 456.1   c
##                       GMA 136.0  138.7 139.8  b
##                       UKF 587.9  591.4 598.4    d
##
##
## (n, p) = (10000, 15). Units is 'milliseconds'
##                      expr   lq median   uq  cld
##   EKF_one_correction_step  264    365  374 a
##  EKF_more_correction_step  562    566  576  b
##                       SMA 1021   1087 1133   c
##                       GMA  460    469  477 ab
##                       UKF 2035   2151 2176    d
```

Session info

- R version 3.4.1 (2017-06-30), `x86_64-w64-mingw32`
- Locale: `LC_COLLATE=English_United Kingdom.1252`, `LC_CTYPE=English_United Kingdom.1252`, `LC_MONETARY=English_United Kingdom.1252`, `LC_NUMERIC=C`, `LC_TIME=English_United Kingdom.1252`
- Running under: `Windows 10 x64 (build 15063)`
- Matrix products: default
- Base packages: base, datasets, graphics, grDevices, methods, stats, utils
- Other packages: dynamichazard 0.3.5, microbenchmark 1.4-2.1, survival 2.41-3
- Loaded via a namespace (and not attached): backports 1.1.0, boot 1.3-19, codetools 0.2-15, colorspace 1.3-2, compiler 3.4.1, data.table 1.10.4, digest 0.6.12, evaluate 0.10, ggplot2 2.2.1, grid 3.4.1, gtable 0.2.0, htmltools 0.3.6, knitr 1.16, lattice 0.20-35, lazyeval 0.2.0, magrittr 1.5, MASS 7.3-47, Matrix 1.2-10, multcomp 1.4-6, munsell 0.4.3, mvtnorm 1.0-6, plyr 1.8.4, Rcpp 0.12.11, rlang 0.1.1, rmarkdown 1.5, rprojroot 1.2, sandwich 2.3-4, scales 0.4.1, speedglm 0.3-2, splines 3.4.1, stringi 1.1.5, stringr 1.2.0, TH.data 1.0-8, tibble 1.3.3, tools 3.4.1, yaml 2.1.14, zoo 1.8-0