

speedtest

Benjamin Christoffersen

2017-10-14

Setup

```
library(dynamichazard); library(microbenchmark)

## Loading required package: survival

sim_func <- function(n, p){
  func <- asNamespace("dynamichazard")$test_sim_func_logit
  set.seed(101)
  t_max <- 30L
  func(n_series = n, n_vars = p, t_max = t_max, x_range = 1, x_mean = 0,
       beta_start = runif(p, -1.5, 1.5),
       intercept_start = -3, sds = c(.1, rep(.25, p)),
       tstart_sampl_func = function(t0, t_max)
         max(0, runif(1, -t_max, t_max - 1L)),
       lambda = 1 / 10)
}

get_rune_time_summary <- function(n, p){
  sims <- sim_func(n, p)

  out <- summary(microbenchmark(
    EKF_one_correction_step =
      suppressMessages(ddhazard(
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1e6, p + 1L),
        Q = diag(1e-1, p + 1L))),
    EKF_more_correction_step =
      suppressMessages(ddhazard(
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1, p + 1L),
        Q = diag(1e-1, p + 1L),
        control = list(NR_eps = 1e-3))),
    SMA = suppressMessages(ddhazard(
```

```

    formula = Surv(tstart, tstop, event) ~ . - id,
    data = sims$res,
    model = "logit",
    id = sims$res$id,
    by = 1L,
    max_T = 30L,
    Q_0 = diag(1e6, p + 1L),
    Q = diag(1e-1, p + 1L),
    control = list(method = "SMA"))),

GMA = suppressMessages(ddhazard(
  formula = Surv(tstart, tstop, event) ~ . - id,
  data = sims$res,
  model = "logit",
  id = sims$res$id,
  by = 1L,
  max_T = 30L,
  Q_0 = diag(1, p + 1L),
  Q = diag(1e-1, p + 1L),
  control = list(method = "GMA"))),

UKF = suppressMessages(ddhazard(
  formula = Surv(tstart, tstop, event) ~ . - id,
  data = sims$res,
  model = "logit",
  id = sims$res$id,
  by = 1L,
  max_T = 30L,
  Q_0 = diag(1, p + 1L),
  Q = diag(1e-1, p + 1L),
  control = list(method = "UKF"))),

  times = 5
))

cat("(n, p) = (", n, ", ", p, ")",
    ". Units is ", sQuote(attr(out, "unit")), "\n", sep = "")

print(out[, c("expr", "lq", "median", "uq")], row.names = FALSE)

cat("\n\n")

invisible()
}

```

Test

```

grid_vals <- expand.grid(
  n = c(250, 1000, 10000),
  p = c(5, 10, 15))

```

```
invisible(
  mapply(get_rune_time_summary, n = grid_vals$n, p = grid_vals$p))
```

```
## (n, p) = (250, 5). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  64.9   71.9  73.4
## EKF_more_correction_step 134.7  139.9 140.1
##           SMA 164.5  173.6 175.2
##           GMA 169.5  169.9 172.4
##           UKF 191.3  193.8 194.3
##
##
## (n, p) = (1000, 5). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  213    229 230
## EKF_more_correction_step 590    604 612
##           SMA 474    484 486
##           GMA 326    332 338
##           UKF 432    433 440
##
##
## (n, p) = (10000, 5). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  411    415 499
## EKF_more_correction_step 961    963 964
##           SMA 1962   1983 1990
##           GMA  623    656 721
##           UKF 1953   1962 1968
##
##
## (n, p) = (250, 10). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  115    119 126
## EKF_more_correction_step 256    260 268
##           SMA 391    393 398
##           GMA 336    337 338
##           UKF 501    509 512
##
##
## (n, p) = (1000, 10). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  157    160 161
## EKF_more_correction_step 345    347 348
##           SMA 460    478 481
##           GMA 242    242 243
##           UKF 562    564 564
##
##
## (n, p) = (10000, 10). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  550    601 604
## EKF_more_correction_step 988   1102 1121
##           SMA 2884   2926 2965
##           GMA  717    727 809
```

```

##           UKF 3181   3210 3271
##
##
## (n, p) = (250, 15). Units is 'milliseconds'
##           expr   lq median   uq
##   EKF_one_correction_step 298   306 306
##   EKF_more_correction_step 346   348 351
##           SMA 822   897 913
##           GMA 420   423 436
##           UKF 1099  1100 1112
##
##
## (n, p) = (1000, 15). Units is 'milliseconds'
##           expr   lq median   uq
##   EKF_one_correction_step 241   245 247
##   EKF_more_correction_step 464   469 492
##           SMA 947  1025 1070
##           GMA 392   394 398
##           UKF 1032  1040 1048
##
##
## (n, p) = (10000, 15). Units is 'milliseconds'
##           expr   lq median   uq
##   EKF_one_correction_step 530   532 549
##   EKF_more_correction_step 1063  1066 1078
##           SMA 3821  3872 3883
##           GMA 850   863 867
##           UKF 4157  4166 4166

```

Session info

- R version 3.4.1 (2017-06-30), x86_64-w64-mingw32
- Locale: LC_COLLATE=English_United States.1252, LC_CTYPE=C, LC_MONETARY=English_United States.1252, LC_NUMERIC=C, LC_TIME=English_United States.1252
- Running under: Windows 10 x64 (build 15063)
- Matrix products: default
- Base packages: base, datasets, graphics, grDevices, methods, stats, utils
- Other packages: dynamichazard 0.4.0, microbenchmark 1.4-2.1, survival 2.41-3
- Loaded via a namespace (and not attached): backports 1.1.0, boot 1.3-19, colorspace 1.3-2, compiler 3.4.1, data.table 1.10.4, digest 0.6.12, evaluate 0.10.1, ggplot2 2.2.1, grid 3.4.1, gtable 0.2.0, htmltools 0.3.6, knitr 1.17, lattice 0.20-35, lazyeval 0.2.0, magrittr 1.5, Matrix 1.2-10, munsell 0.4.3, plyr 1.8.4, Rcpp 0.12.12, rlang 0.1.2, rmarkdown 1.6, rprojroot 1.2, scales 0.5.0, splines 3.4.1, stringi 1.1.5, stringr 1.2.0, tibble 1.3.4, tools 3.4.1, yaml 2.1.14