speedtest

Benjamin Christoffersen

2017-06-18

Setup

```
library(dynamichazard); library(microbenchmark)
```

```
## Loading required package: survival
```

```
sim_func <- function(n, p){
  func <- asNamespace("dynamichazard")$test_sim_func_logit
  set.seed(101)
  t_max <- 30L
  func(n_series = n, n_vars = p, t_max = t_max, x_range = 1, x_mean = 0,
       beta_start = runif(p, -1.5, 1.5),
       intercept_start = -3, sds = c(.1, rep(.25, p)),
       tstart_sampl_func = function(t0, t_max)
         max(0, runif(1, -t_max, t_max - 1L)),
       lambda = 1 / 10)
}

get_rune_time_summary <- function(n, p){
  sims <- sim_func(n, p)

  out <- summary(microbenchmark(
    EKF_one_correction_step =
      suppressMessages(ddhazard(
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1e6, p + 1L),
        Q = diag(1e-1, p + 1L))),

    EKF_more_correction_step =
      suppressMessages(ddhazard(
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1, p + 1L),
        Q = diag(1e-1, p + 1L),
        control = list(NR_eps = 1e-3))),

    SMA = suppressMessages(ddhazard(
```

```
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1e6, p + 1L),
        Q = diag(1e-1, p + 1L),
        control = list(method = "SMA"))),

    GMA = suppressMessages(ddhazard(
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1, p + 1L),
        Q = diag(1e-1, p + 1L),
        control = list(method = "GMA"))),

    UKF = suppressMessages(ddhazard(
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1, p + 1L),
        Q = diag(1e-1, p + 1L),
        control = list(method = "UKF"))),

    times = 5
  ))

  cat("(n, p) = (", n, ", ", p, ")",
      ". Units is ", sQuote(attr(out, "unit")), "\n", sep = "")

  print(out[, c("expr", "lq", "median", "uq", "cld")], row.names = FALSE)

  cat("\n\n")

  invisible()
}
```

Test

```
grid_vals <- expand.grid(
  n = c(250, 1000, 10000),
  p = c(5, 10, 15))
```

```r
invisible(
  mapply(get_rune_time_summary, n = grid_vals$n, p = grid_vals$p))
```

```
## (n, p) = (250, 5). Units is 'milliseconds'
##                       expr   lq median   uq cld
##   EKF_one_correction_step 20.0   20.5 22.2   a
##  EKF_more_correction_step 33.7   34.0 35.9   a
##                       SMA 86.5   95.1 95.3   a
##                       GMA 38.8   39.5 40.5   a
##                       UKF 88.0   88.9 97.5   a
##
##
## (n, p) = (1000, 5). Units is 'milliseconds'
##                       expr    lq median    uq cld
##   EKF_one_correction_step  34.5   44.1  58.2 a
##  EKF_more_correction_step  55.2   55.4  58.0 ab
##                       SMA  59.6   59.7  66.1  b
##                       GMA  43.6   46.0  54.5 ab
##                       UKF 106.2  108.6 112.0   c
##
##
## (n, p) = (10000, 5). Units is 'milliseconds'
##                       expr  lq median  uq cld
##   EKF_one_correction_step 251    254 258 a
##  EKF_more_correction_step 410    424 430  b
##                       SMA 500    582 582   c
##                       GMA 204    208 217 a
##                       UKF 387    410 498  b
##
##
## (n, p) = (250, 10). Units is 'milliseconds'
##                       expr    lq median    uq  cld
##   EKF_one_correction_step  43.5   47.1  53.2 a
##  EKF_more_correction_step  73.7   74.3  93.5  b
##                       SMA 142.4  147.0 147.2   c
##                       GMA  68.0   69.9  70.6  b
##                       UKF 373.0  381.6 382.1    d
##
##
## (n, p) = (1000, 10). Units is 'milliseconds'
##                       expr    lq median    uq  cld
##   EKF_one_correction_step  37.9   38.1  39.8 a
##  EKF_more_correction_step  57.2   57.2  61.4  b
##                       SMA 118.0  123.1 128.8   c
##                       GMA  50.5   52.3  68.2  b
##                       UKF 194.5  194.8 197.6    d
##
##
## (n, p) = (10000, 10). Units is 'milliseconds'
##                       expr  lq median  uq cld
##   EKF_one_correction_step 308    341 343  a
##  EKF_more_correction_step 415    416 418  a
##                       SMA 859    860 864   b
##                       GMA 303    314 384  a
```

```
##                       UKF 780    841 858   b
##
##
## (n, p) = (250, 15). Units is 'milliseconds'
##                      expr    lq median  uq  cld
##   EKF_one_correction_step 108.3  110.9 113  b
##  EKF_more_correction_step 102.4  106.7 111  b
##                       SMA 204.2  205.6 206   c
##                       GMA  86.3   94.6  97 a
##                       UKF 500.3  502.8 510    d
##
##
## (n, p) = (1000, 15). Units is 'milliseconds'
##                      expr    lq median    uq  cld
##   EKF_one_correction_step  90.5   94.7  96.6 a
##  EKF_more_correction_step 171.4  173.3 173.5  b
##                       SMA 367.8  418.0 461.3   c
##                       GMA 133.6  134.9 135.8 ab
##                       UKF 505.1  506.5 508.1    d
##
##
## (n, p) = (10000, 15). Units is 'milliseconds'
##                      expr   lq median   uq  cld
##   EKF_one_correction_step  343    374  374 a
##  EKF_more_correction_step  573    601  610  b
##                       SMA 1053   1138 1158   c
##                       GMA  435    474  479 ab
##                       UKF 1403   1526 1555    d
```

Session info

- R version 3.4.0 (2017-04-21), `x86_64-w64-mingw32`
- Locale: `LC_COLLATE=English_United Kingdom.1252`, `LC_CTYPE=English_United Kingdom.1252`, `LC_MONETARY=English_United Kingdom.1252`, `LC_NUMERIC=C`, `LC_TIME=English_United Kingdom.1252`
- Running under: `Windows 10 x64 (build 15063)`
- Matrix products: default
- Base packages: base, datasets, graphics, grDevices, methods, stats, utils
- Other packages: dynamichazard 0.3.3, microbenchmark 1.4-2.1, survival 2.41-3
- Loaded via a namespace (and not attached): backports 1.1.0, boot 1.3-19, codetools 0.2-15, colorspace 1.3-2, compiler 3.4.0, data.table 1.10.4, digest 0.6.12, evaluate 0.10, ggplot2 2.2.1, grid 3.4.0, gtable 0.2.0, htmltools 0.3.6, knitr 1.16, lattice 0.20-35, lazyeval 0.2.0, magrittr 1.5, MASS 7.3-47, Matrix 1.2-9, multcomp 1.4-6, munsell 0.4.3, mvtnorm 1.0-6, plyr 1.8.4, Rcpp 0.12.11, rlang 0.1.1, rmarkdown 1.5, rprojroot 1.2, sandwich 2.3-4, scales 0.4.1, speedglm 0.3-2, splines 3.4.0, stringi 1.1.5, stringr 1.2.0, TH.data 1.0-8, tibble 1.3.3, tools 3.4.0, yaml 2.1.14, zoo 1.8-0