

speedtest

Benjamin Christoffersen

2018-08-07

Setup

```
library(dynamichazard); library(microbenchmark)

## Loading required package: survival

sim_func <- function(n, p){
  func <- asNamespace("dynamichazard")$test_sim_func_logit
  set.seed(101)
  t_max <- 30L
  func(n_series = n, n_vars = p, t_max = t_max, x_range = 1, x_mean = 0,
       beta_start = runif(p, -1.5, 1.5),
       intercept_start = -3, sds = c(.1, rep(.25, p)),
       tstart_sampl_func = function(t0, t_max)
         max(0, runif(1, -t_max, t_max - 1L)),
       lambda = 1 / 10)
}

get_rune_time_summary <- function(n, p){
  sims <- sim_func(n, p)

  out <- summary(microbenchmark(
    EKF_one_correction_step =
      suppressMessages(ddhazard(
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1e6, p + 1L),
        Q = diag(1e-1, p + 1L))),
    EKF_more_correction_step =
      suppressMessages(ddhazard(
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1, p + 1L),
        Q = diag(1e-1, p + 1L),
        control = list(NR_eps = 1e-3))),
    SMA = suppressMessages(ddhazard(
```

```

    formula = Surv(tstart, tstop, event) ~ . - id,
    data = sims$res,
    model = "logit",
    id = sims$res$id,
    by = 1L,
    max_T = 30L,
    Q_0 = diag(1e6, p + 1L),
    Q = diag(1e-1, p + 1L),
    control = list(method = "SMA"))),

  GMA = suppressMessages(ddhazard(
    formula = Surv(tstart, tstop, event) ~ . - id,
    data = sims$res,
    model = "logit",
    id = sims$res$id,
    by = 1L,
    max_T = 30L,
    Q_0 = diag(1, p + 1L),
    Q = diag(1e-1, p + 1L),
    control = list(method = "GMA"))),

  UKF = suppressMessages(ddhazard(
    formula = Surv(tstart, tstop, event) ~ . - id,
    data = sims$res,
    model = "logit",
    id = sims$res$id,
    by = 1L,
    max_T = 30L,
    Q_0 = diag(1, p + 1L),
    Q = diag(1e-1, p + 1L),
    control = list(method = "UKF"))),

  times = 1
))

cat("(n, p) = (", n, ", ", p, ")",
    ". Units is ", sQuote(attr(out, "unit")), "\n", sep = "")

print(out[, c("expr", "lq", "median", "uq")], row.names = FALSE)

cat("\n\n")

invisible()
}

```

Test

```

grid_vals <- expand.grid(
  n = c(250, 1000, 10000),
  p = c(5, 10, 15))

```

```
invisible(
  mapply(get_rune_time_summary, n = grid_vals$n, p = grid_vals$p))
```

```
## (n, p) = (250, 5). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  64.1   64.1  64.1
## EKF_more_correction_step 121.0  121.0 121.0
##           SMA 192.2   192.2 192.2
##           GMA 189.4   189.4 189.4
##           UKF 330.7   330.7 330.7
##
##
## (n, p) = (1000, 5). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  197    197 197
## EKF_more_correction_step 548    548 548
##           SMA 607    607 607
##           GMA 288    288 288
##           UKF 511    511 511
##
##
## (n, p) = (10000, 5). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  379    379 379
## EKF_more_correction_step 933    933 933
##           SMA 2419   2419 2419
##           GMA 865    865 865
##           UKF 2543   2543 2543
##
##
## (n, p) = (250, 10). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  116    116 116
## EKF_more_correction_step 259    259 259
##           SMA 583    583 583
##           GMA 389    389 389
##           UKF 937    937 937
##
##
## (n, p) = (1000, 10). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  140    140 140
## EKF_more_correction_step 303    303 303
##           SMA 890    890 890
##           GMA 215    215 215
##           UKF 775    775 775
##
##
## (n, p) = (10000, 10). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  546    546 546
## EKF_more_correction_step 995    995 995
##           SMA 3101   3101 3101
##           GMA 1025   1025 1025
```

```

##           UKF 4075    4075 4075
##
##
## (n, p) = (250, 15). Units is 'milliseconds'
##           expr    lq median    uq
##   EKF_one_correction_step 296    296 296
##   EKF_more_correction_step 339    339 339
##           SMA  904    904 904
##           GMA  418    418 418
##           UKF 2047    2047 2047
##
##
## (n, p) = (1000, 15). Units is 'milliseconds'
##           expr    lq median    uq
##   EKF_one_correction_step 220    220 220
##   EKF_more_correction_step 459    459 459
##           SMA  937    937 937
##           GMA  338    338 338
##           UKF 1475    1475 1475
##
##
## (n, p) = (10000, 15). Units is 'milliseconds'
##           expr    lq median    uq
##   EKF_one_correction_step 428    428 428
##   EKF_more_correction_step 923    923 923
##           SMA 4119    4119 4119
##           GMA 1170    1170 1170
##           UKF 4946    4946 4946

```

Session info

- R version 3.5.0 (2018-04-23), x86_64-w64-mingw32
- Locale: LC_COLLATE=English_United States.1252, LC_CTYPE=C, LC_MONETARY=English_United States.1252, LC_NUMERIC=C, LC_TIME=English_United States.1252
- Running under: Windows 10 x64 (build 17134)
- Matrix products: default
- Base packages: base, datasets, graphics, grDevices, methods, stats, utils
- Other packages: dynamichazard 0.6.0, microbenchmark 1.4-4, survival 2.41-3
- Loaded via a namespace (and not attached): backports 1.1.2, boot 1.3-20, compiler 3.5.0, digest 0.6.15, evaluate 0.10.1, grid 3.5.0, htmltools 0.3.6, knitr 1.20, lattice 0.20-35, magrittr 1.5, Matrix 1.2-14, parallel 3.5.0, Rcpp 0.12.17, rmarkdown 1.9, rprojroot 1.3-2, splines 3.5.0, stringi 1.1.7, stringr 1.3.0, tools 3.5.0, yaml 2.1.18