

# speedtest

*Benjamin Christoffersen*

*2018-07-30*

## Setup

```
library(dynamichazard); library(microbenchmark)

## Loading required package: survival

sim_func <- function(n, p){
  func <- asNamespace("dynamichazard")$test_sim_func_logit
  set.seed(101)
  t_max <- 30L
  func(n_series = n, n_vars = p, t_max = t_max, x_range = 1, x_mean = 0,
       beta_start = runif(p, -1.5, 1.5),
       intercept_start = -3, sds = c(.1, rep(.25, p)),
       tstart_sampl_func = function(t0, t_max)
         max(0, runif(1, -t_max, t_max - 1L)),
       lambda = 1 / 10)
}

get_rune_time_summary <- function(n, p){
  sims <- sim_func(n, p)

  out <- summary(microbenchmark(
    EKF_one_correction_step =
      suppressMessages(ddhazard(
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1e6, p + 1L),
        Q = diag(1e-1, p + 1L))),
    EKF_more_correction_step =
      suppressMessages(ddhazard(
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1, p + 1L),
        Q = diag(1e-1, p + 1L),
        control = list(NR_eps = 1e-3))),
    SMA = suppressMessages(ddhazard(
```

```

    formula = Surv(tstart, tstop, event) ~ . - id,
    data = sims$res,
    model = "logit",
    id = sims$res$id,
    by = 1L,
    max_T = 30L,
    Q_0 = diag(1e6, p + 1L),
    Q = diag(1e-1, p + 1L),
    control = list(method = "SMA"))),

GMA = suppressMessages(ddhazard(
  formula = Surv(tstart, tstop, event) ~ . - id,
  data = sims$res,
  model = "logit",
  id = sims$res$id,
  by = 1L,
  max_T = 30L,
  Q_0 = diag(1, p + 1L),
  Q = diag(1e-1, p + 1L),
  control = list(method = "GMA"))),

UKF = suppressMessages(ddhazard(
  formula = Surv(tstart, tstop, event) ~ . - id,
  data = sims$res,
  model = "logit",
  id = sims$res$id,
  by = 1L,
  max_T = 30L,
  Q_0 = diag(1, p + 1L),
  Q = diag(1e-1, p + 1L),
  control = list(method = "UKF"))),

  times = 1
))

cat("(n, p) = (", n, ", ", p, ")",
    ". Units is ", sQuote(attr(out, "unit")), "\n", sep = "")

print(out[, c("expr", "lq", "median", "uq")], row.names = FALSE)

cat("\n\n")

invisible()
}

```

## Test

```

grid_vals <- expand.grid(
  n = c(250, 1000, 10000),
  p = c(5, 10, 15))

```

```
invisible(
  mapply(get_rune_time_summary, n = grid_vals$n, p = grid_vals$p))
```

```
## (n, p) = (250, 5). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  70.3   70.3  70.3
## EKF_more_correction_step 137.6  137.6 137.6
##           SMA 197.4  197.4 197.4
##           GMA 211.4  211.4 211.4
##           UKF 333.9  333.9 333.9
##
##
## (n, p) = (1000, 5). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  198    198 198
## EKF_more_correction_step 567    567 567
##           SMA 589    589 589
##           GMA 282    282 282
##           UKF 507    507 507
##
##
## (n, p) = (10000, 5). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  372    372 372
## EKF_more_correction_step 945    945 945
##           SMA 2406   2406 2406
##           GMA  894    894 894
##           UKF 2547   2547 2547
##
##
## (n, p) = (250, 10). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  103    103 103
## EKF_more_correction_step 259    259 259
##           SMA 442    442 442
##           GMA 358    358 358
##           UKF 832    832 832
##
##
## (n, p) = (1000, 10). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  137    137 137
## EKF_more_correction_step 322    322 322
##           SMA 505    505 505
##           GMA 213    213 213
##           UKF 764    764 764
##
##
## (n, p) = (10000, 10). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  592    592 592
## EKF_more_correction_step 963    963 963
##           SMA 3334   3334 3334
##           GMA  986    986 986
```

```

##          UKF 4283    4283 4283
##
##
## (n, p) = (250, 15). Units is 'milliseconds'
##      expr    lq median    uq
## EKF_one_correction_step 293    293 293
## EKF_more_correction_step 345    345 345
##          SMA 975    975 975
##          GMA 440    440 440
##          UKF 2090   2090 2090
##
##
## (n, p) = (1000, 15). Units is 'milliseconds'
##      expr    lq median    uq
## EKF_one_correction_step 219    219 219
## EKF_more_correction_step 475    475 475
##          SMA 1027   1027 1027
##          GMA 377    377 377
##          UKF 1648   1648 1648
##
##
## (n, p) = (10000, 15). Units is 'milliseconds'
##      expr    lq median    uq
## EKF_one_correction_step 415    415 415
## EKF_more_correction_step 905    905 905
##          SMA 5437   5437 5437
##          GMA 1258   1258 1258
##          UKF 5198   5198 5198

```

## Session info

- R version 3.5.0 (2018-04-23), x86\_64-w64-mingw32
- Locale: LC\_COLLATE=English\_United States.1252, LC\_CTYPE=C, LC\_MONETARY=English\_United States.1252, LC\_NUMERIC=C, LC\_TIME=English\_United States.1252
- Running under: Windows 10 x64 (build 17134)
- Matrix products: default
- Base packages: base, datasets, graphics, grDevices, methods, stats, utils
- Other packages: dynamichazard 0.6.0, microbenchmark 1.4-4, survival 2.41-3
- Loaded via a namespace (and not attached): backports 1.1.2, boot 1.3-20, compiler 3.5.0, digest 0.6.15, evaluate 0.10.1, grid 3.5.0, htmltools 0.3.6, knitr 1.20, lattice 0.20-35, magrittr 1.5, Matrix 1.2-14, parallel 3.5.0, Rcpp 0.12.17, rmarkdown 1.9, rprojroot 1.3-2, splines 3.5.0, stringi 1.1.7, stringr 1.3.0, tools 3.5.0, yaml 2.1.18