

speedtest

Benjamin Christoffersen

2018-07-16

Setup

```
library(dynamichazard); library(microbenchmark)

## Loading required package: survival

sim_func <- function(n, p){
  func <- asNamespace("dynamichazard")$test_sim_func_logit
  set.seed(101)
  t_max <- 30L
  func(n_series = n, n_vars = p, t_max = t_max, x_range = 1, x_mean = 0,
       beta_start = runif(p, -1.5, 1.5),
       intercept_start = -3, sds = c(.1, rep(.25, p)),
       tstart_sampl_func = function(t0, t_max)
         max(0, runif(1, -t_max, t_max - 1L)),
       lambda = 1 / 10)
}

get_rune_time_summary <- function(n, p){
  sims <- sim_func(n, p)

  out <- summary(microbenchmark(
    EKF_one_correction_step =
      suppressMessages(ddhazard(
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1e6, p + 1L),
        Q = diag(1e-1, p + 1L))),
    EKF_more_correction_step =
      suppressMessages(ddhazard(
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1, p + 1L),
        Q = diag(1e-1, p + 1L),
        control = list(NR_eps = 1e-3))),
    SMA = suppressMessages(ddhazard(
```

```

    formula = Surv(tstart, tstop, event) ~ . - id,
    data = sims$res,
    model = "logit",
    id = sims$res$id,
    by = 1L,
    max_T = 30L,
    Q_0 = diag(1e6, p + 1L),
    Q = diag(1e-1, p + 1L),
    control = list(method = "SMA"))),

GMA = suppressMessages(ddhazard(
  formula = Surv(tstart, tstop, event) ~ . - id,
  data = sims$res,
  model = "logit",
  id = sims$res$id,
  by = 1L,
  max_T = 30L,
  Q_0 = diag(1, p + 1L),
  Q = diag(1e-1, p + 1L),
  control = list(method = "GMA"))),

UKF = suppressMessages(ddhazard(
  formula = Surv(tstart, tstop, event) ~ . - id,
  data = sims$res,
  model = "logit",
  id = sims$res$id,
  by = 1L,
  max_T = 30L,
  Q_0 = diag(1, p + 1L),
  Q = diag(1e-1, p + 1L),
  control = list(method = "UKF"))),

  times = 1
))

cat("(n, p) = (", n, ", ", p, ")",
    ". Units is ", sQuote(attr(out, "unit")), "\n", sep = "")

print(out[, c("expr", "lq", "median", "uq")], row.names = FALSE)

cat("\n\n")

invisible()
}

```

Test

```

grid_vals <- expand.grid(
  n = c(250, 1000, 10000),
  p = c(5, 10, 15))

```

```
invisible(
  mapply(get_rune_time_summary, n = grid_vals$n, p = grid_vals$p))
```

```
## (n, p) = (250, 5). Units is 'milliseconds'
##      expr    lq median    uq
## EKF_one_correction_step 68.9   68.9 68.9
## EKF_more_correction_step 122.7  122.7 122.7
##      SMA 175.6   175.6 175.6
##      GMA 182.1   182.1 182.1
##      UKF 352.4   352.4 352.4
##
##
## (n, p) = (1000, 5). Units is 'milliseconds'
##      expr    lq median    uq
## EKF_one_correction_step 198     198 198
## EKF_more_correction_step 565     565 565
##      SMA 590     590 590
##      GMA 261     261 261
##      UKF 477     477 477
##
##
## (n, p) = (10000, 5). Units is 'milliseconds'
##      expr    lq median    uq
## EKF_one_correction_step 387     387 387
## EKF_more_correction_step 967     967 967
##      SMA 4145    4145 4145
##      GMA 865     865 865
##      UKF 2507    2507 2507
##
##
## (n, p) = (250, 10). Units is 'milliseconds'
##      expr    lq median    uq
## EKF_one_correction_step 112     112 112
## EKF_more_correction_step 244     244 244
##      SMA 657     657 657
##      GMA 378     378 378
##      UKF 837     837 837
##
##
## (n, p) = (1000, 10). Units is 'milliseconds'
##      expr    lq median    uq
## EKF_one_correction_step 137     137 137
## EKF_more_correction_step 303     303 303
##      SMA 759     759 759
##      GMA 216     216 216
##      UKF 710     710 710
##
##
## (n, p) = (10000, 10). Units is 'milliseconds'
##      expr    lq median    uq
## EKF_one_correction_step 517     517 517
## EKF_more_correction_step 901     901 901
##      SMA 2888    2888 2888
##      GMA 928     928 928
```

```

##           UKF 3700   3700 3700
##
##
## (n, p) = (250, 15). Units is 'milliseconds'
##           expr   lq median   uq
##   EKF_one_correction_step 264   264 264
##   EKF_more_correction_step 299   299 299
##           SMA 1158   1158 1158
##           GMA 399    399 399
##           UKF 1875   1875 1875
##
##
## (n, p) = (1000, 15). Units is 'milliseconds'
##           expr   lq median   uq
##   EKF_one_correction_step 207   207 207
##   EKF_more_correction_step 457   457 457
##           SMA 947    947 947
##           GMA 321    321 321
##           UKF 1422   1422 1422
##
##
## (n, p) = (10000, 15). Units is 'milliseconds'
##           expr   lq median   uq
##   EKF_one_correction_step 414   414 414
##   EKF_more_correction_step 908   908 908
##           SMA 4118   4118 4118
##           GMA 1069   1069 1069
##           UKF 4739   4739 4739

```

Session info

- R version 3.5.0 (2018-04-23), x86_64-w64-mingw32
- Locale: LC_COLLATE=English_United States.1252, LC_CTYPE=C, LC_MONETARY=English_United States.1252, LC_NUMERIC=C, LC_TIME=English_United States.1252
- Running under: Windows 10 x64 (build 17134)
- Matrix products: default
- Base packages: base, datasets, graphics, grDevices, methods, stats, utils
- Other packages: dynamichazard 0.6.0, microbenchmark 1.4-4, survival 2.41-3
- Loaded via a namespace (and not attached): backports 1.1.2, boot 1.3-20, compiler 3.5.0, digest 0.6.15, evaluate 0.10.1, grid 3.5.0, htmltools 0.3.6, knitr 1.20, lattice 0.20-35, magrittr 1.5, Matrix 1.2-14, parallel 3.5.0, Rcpp 0.12.17, rmarkdown 1.9, rprojroot 1.3-2, splines 3.5.0, stringi 1.1.7, stringr 1.3.0, tools 3.5.0, yaml 2.1.18