

speedtest

Benjamin Christoffersen

2017-11-16

Setup

```
library(dynamichazard); library(microbenchmark)

## Loading required package: survival

sim_func <- function(n, p){
  func <- asNamespace("dynamichazard")$test_sim_func_logit
  set.seed(101)
  t_max <- 30L
  func(n_series = n, n_vars = p, t_max = t_max, x_range = 1, x_mean = 0,
       beta_start = runif(p, -1.5, 1.5),
       intercept_start = -3, sds = c(.1, rep(.25, p)),
       tstart_sampl_func = function(t0, t_max)
         max(0, runif(1, -t_max, t_max - 1L)),
       lambda = 1 / 10)
}

get_rune_time_summary <- function(n, p){
  sims <- sim_func(n, p)

  out <- summary(microbenchmark(
    EKF_one_correction_step =
      suppressMessages(ddhazard(
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1e6, p + 1L),
        Q = diag(1e-1, p + 1L))),
    EKF_more_correction_step =
      suppressMessages(ddhazard(
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1, p + 1L),
        Q = diag(1e-1, p + 1L),
        control = list(NR_eps = 1e-3))),
    SMA = suppressMessages(ddhazard(
```

```

    formula = Surv(tstart, tstop, event) ~ . - id,
    data = sims$res,
    model = "logit",
    id = sims$res$id,
    by = 1L,
    max_T = 30L,
    Q_0 = diag(1e6, p + 1L),
    Q = diag(1e-1, p + 1L),
    control = list(method = "SMA"))),

  GMA = suppressMessages(ddhazard(
    formula = Surv(tstart, tstop, event) ~ . - id,
    data = sims$res,
    model = "logit",
    id = sims$res$id,
    by = 1L,
    max_T = 30L,
    Q_0 = diag(1, p + 1L),
    Q = diag(1e-1, p + 1L),
    control = list(method = "GMA"))),

  UKF = suppressMessages(ddhazard(
    formula = Surv(tstart, tstop, event) ~ . - id,
    data = sims$res,
    model = "logit",
    id = sims$res$id,
    by = 1L,
    max_T = 30L,
    Q_0 = diag(1, p + 1L),
    Q = diag(1e-1, p + 1L),
    control = list(method = "UKF"))),

  times = 5
))

cat("(n, p) = (", n, ", ", p, ")",
    ". Units is ", sQuote(attr(out, "unit")), "\n", sep = "")

print(out[, c("expr", "lq", "median", "uq")], row.names = FALSE)

cat("\n\n")

invisible()
}

```

Test

```

grid_vals <- expand.grid(
  n = c(250, 1000, 10000),
  p = c(5, 10, 15))

```

```
invisible(
  mapply(get_rune_time_summary, n = grid_vals$n, p = grid_vals$p))
```

```
## (n, p) = (250, 5). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step 63.8   66.1  68.7
## EKF_more_correction_step 119.5  122.1 124.5
##           SMA 171.7   184.7 196.4
##           GMA 160.8   165.8 174.5
##           UKF 225.4   226.5 232.9
##
##
## (n, p) = (1000, 5). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step 203     208 209
## EKF_more_correction_step 546     552 554
##           SMA 516     518 526
##           GMA 271     272 274
##           UKF 473     474 476
##
##
## (n, p) = (10000, 5). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step 421     504 506
## EKF_more_correction_step 1055    1055 1060
##           SMA 2125    2128 2130
##           GMA 899     921 1003
##           UKF 2337    2357 2415
##
##
## (n, p) = (250, 10). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step 115     119 127
## EKF_more_correction_step 243     249 253
##           SMA 409     431 433
##           GMA 320     324 336
##           UKF 601     601 602
##
##
## (n, p) = (1000, 10). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step 152     154 155
## EKF_more_correction_step 332     333 337
##           SMA 488     512 516
##           GMA 219     221 225
##           UKF 687     689 695
##
##
## (n, p) = (10000, 10). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step 499     572 587
## EKF_more_correction_step 993    1000 1083
##           SMA 3011    3029 3031
##           GMA 1212    1213 1219
```

```

##          UKF 3819   3827 3842
##
##
## (n, p) = (250, 15). Units is 'milliseconds'
##      expr   lq median   uq
## EKF_one_correction_step 311   327 329
## EKF_more_correction_step 324   330 339
##          SMA 918   956 963
##          GMA 407   418 420
##          UKF 1262  1263 1265
##
##
## (n, p) = (1000, 15). Units is 'milliseconds'
##      expr   lq median   uq
## EKF_one_correction_step 240   246 250
## EKF_more_correction_step 495   496 496
##          SMA 992  1101 1121
##          GMA 365   369 374
##          UKF 1256  1263 1266
##
##
## (n, p) = (10000, 15). Units is 'milliseconds'
##      expr   lq median   uq
## EKF_one_correction_step 451   459 537
## EKF_more_correction_step 1081  1101 1103
##          SMA 3985  4024 4065
##          GMA 1322  1335 1367
##          UKF 4899  4999 5036

```

Session info

- R version 3.4.2 (2017-09-28), x86_64-w64-mingw32
- Locale: LC_COLLATE=English_United States.1252, LC_CTYPE=C, LC_MONETARY=English_United States.1252, LC_NUMERIC=C, LC_TIME=English_United States.1252
- Running under: Windows 10 x64 (build 15063)
- Matrix products: default
- Base packages: base, datasets, graphics, grDevices, methods, stats, utils
- Other packages: dynamichazard 0.5.0, microbenchmark 1.4-2.1, survival 2.41-3
- Loaded via a namespace (and not attached): backports 1.1.0, boot 1.3-20, codetools 0.2-15, colorspace 1.3-2, compiler 3.4.2, data.table 1.10.4-2, digest 0.6.12, evaluate 0.10.1, ggplot2 2.2.1, grid 3.4.2, gtable 0.2.0, htmltools 0.3.6, knitr 1.17, lattice 0.20-35, lazyeval 0.2.0, magrittr 1.5, MASS 7.3-47, Matrix 1.2-11, multcomp 1.4-7, munsell 0.4.3, mvtnorm 1.0-6, parallel 3.4.2, plyr 1.8.4, Rcpp 0.12.13, rlang 0.1.4, rmarkdown 1.6, rprojroot 1.2, sandwich 2.4-0, scales 0.5.0, splines 3.4.2, stringi 1.1.5, stringr 1.2.0, TH.data 1.0-8, tibble 1.3.4, tools 3.4.2, yaml 2.1.14, zoo 1.8-0