

speedtest

Benjamin Christoffersen

2017-09-14

Setup

```
library(dynamichazard); library(microbenchmark)

## Loading required package: survival

sim_func <- function(n, p){
  func <- asNamespace("dynamichazard")$test_sim_func_logit
  set.seed(101)
  t_max <- 30L
  func(n_series = n, n_vars = p, t_max = t_max, x_range = 1, x_mean = 0,
       beta_start = runif(p, -1.5, 1.5),
       intercept_start = -3, sds = c(.1, rep(.25, p)),
       tstart_sampl_func = function(t0, t_max)
         max(0, runif(1, -t_max, t_max - 1L)),
       lambda = 1 / 10)
}

get_rune_time_summary <- function(n, p){
  sims <- sim_func(n, p)

  out <- summary(microbenchmark(
    EKF_one_correction_step =
      suppressMessages(ddhazard(
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1e6, p + 1L),
        Q = diag(1e-1, p + 1L))),
    EKF_more_correction_step =
      suppressMessages(ddhazard(
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1, p + 1L),
        Q = diag(1e-1, p + 1L),
        control = list(NR_eps = 1e-3))),
    SMA = suppressMessages(ddhazard(
```

```

    formula = Surv(tstart, tstop, event) ~ . - id,
    data = sims$res,
    model = "logit",
    id = sims$res$id,
    by = 1L,
    max_T = 30L,
    Q_0 = diag(1e6, p + 1L),
    Q = diag(1e-1, p + 1L),
    control = list(method = "SMA"))),

GMA = suppressMessages(ddhazard(
  formula = Surv(tstart, tstop, event) ~ . - id,
  data = sims$res,
  model = "logit",
  id = sims$res$id,
  by = 1L,
  max_T = 30L,
  Q_0 = diag(1, p + 1L),
  Q = diag(1e-1, p + 1L),
  control = list(method = "GMA"))),

UKF = suppressMessages(ddhazard(
  formula = Surv(tstart, tstop, event) ~ . - id,
  data = sims$res,
  model = "logit",
  id = sims$res$id,
  by = 1L,
  max_T = 30L,
  Q_0 = diag(1, p + 1L),
  Q = diag(1e-1, p + 1L),
  control = list(method = "UKF"))),

  times = 5
))

cat("(n, p) = (", n, ", ", p, ")",
    ". Units is ", sQuote(attr(out, "unit")), "\n", sep = "")

print(out[, c("expr", "lq", "median", "uq")], row.names = FALSE)

cat("\n\n")

invisible()
}

```

Test

```

grid_vals <- expand.grid(
  n = c(250, 1000, 10000),
  p = c(5, 10, 15))

```

```
invisible(
  mapply(get_rune_time_summary, n = grid_vals$n, p = grid_vals$p))
```

```
## (n, p) = (250, 5). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  62.1   62.6  67.9
## EKF_more_correction_step 118.5  123.7 130.0
##           SMA 162.1  162.4 167.8
##           GMA 168.3  168.9 171.1
##           UKF 182.1  182.8 185.6
##
##
## (n, p) = (1000, 5). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  182    193 202
## EKF_more_correction_step 529    530 532
##           SMA 447    464 465
##           GMA 300    306 307
##           UKF 378    381 381
##
##
## (n, p) = (10000, 5). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  368    448 472
## EKF_more_correction_step 918    948 994
##           SMA 1914   1978 2034
##           GMA  608    690 696
##           UKF 1882   1944 1973
##
##
## (n, p) = (250, 10). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  115    118 119
## EKF_more_correction_step 252    252 255
##           SMA 370    387 394
##           GMA 324    327 327
##           UKF 498    500 501
##
##
## (n, p) = (1000, 10). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  153    154 156
## EKF_more_correction_step 326    329 331
##           SMA 446    457 463
##           GMA 234    236 240
##           UKF 539    540 544
##
##
## (n, p) = (10000, 10). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  457    459 461
## EKF_more_correction_step 901    974 1014
##           SMA 2587   2683 2691
##           GMA  809    818 824
```

```

##          UKF 2928   2962 3004
##
##
## (n, p) = (250, 15). Units is 'milliseconds'
##      expr   lq median   uq
## EKF_one_correction_step 289   309 329
## EKF_more_correction_step 355   366 374
##          SMA 872   891 902
##          GMA 442   451 459
##          UKF 1029  1030 1152
##
##
## (n, p) = (1000, 15). Units is 'milliseconds'
##      expr   lq median   uq
## EKF_one_correction_step 229   235 235
## EKF_more_correction_step 467   471 474
##          SMA 894   969 1021
##          GMA 361   375 378
##          UKF 967   982 987
##
##
## (n, p) = (10000, 15). Units is 'milliseconds'
##      expr   lq median   uq
## EKF_one_correction_step 426   443 508
## EKF_more_correction_step 969   970 995
##          SMA 3748  3929 3951
##          GMA 816   822 861
##          UKF 3978  4021 4045

```

Session info

- R version 3.4.1 (2017-06-30), x86_64-w64-mingw32
- Locale: LC_COLLATE=English_United States.1252, LC_CTYPE=C, LC_MONETARY=English_United States.1252, LC_NUMERIC=C, LC_TIME=English_United States.1252
- Running under: Windows 10 x64 (build 10586)
- Matrix products: default
- Base packages: base, datasets, graphics, grDevices, methods, stats, utils
- Other packages: dynamichazard 0.4.0, microbenchmark 1.4-2.1, survival 2.41-3
- Loaded via a namespace (and not attached): backports 1.1.0, boot 1.3-19, colorspace 1.3-2, compiler 3.4.1, data.table 1.10.4, digest 0.6.12, evaluate 0.10.1, ggplot2 2.2.1, grid 3.4.1, gtable 0.2.0, htmltools 0.3.6, knitr 1.17, lattice 0.20-35, lazyeval 0.2.0, magrittr 1.5, Matrix 1.2-10, munsell 0.4.3, plyr 1.8.4, Rcpp 0.12.12, rlang 0.1.2, rmarkdown 1.6, rprojroot 1.2, scales 0.5.0, splines 3.4.1, stringi 1.1.5, stringr 1.2.0, tibble 1.3.4, tools 3.4.1, yaml 2.1.14