speedtest

Benjamin Christoffersen

2017-06-23

Setup

```
library(dynamichazard); library(microbenchmark)
```

```
## Loading required package: survival
```

```
sim_func <- function(n, p){
  func <- asNamespace("dynamichazard")$test_sim_func_logit
  set.seed(101)
  t_max <- 30L
  func(n_series = n, n_vars = p, t_max = t_max, x_range = 1, x_mean = 0,
       beta_start = runif(p, -1.5, 1.5),
       intercept_start = -3, sds = c(.1, rep(.25, p)),
       tstart_sampl_func = function(t0, t_max)
         max(0, runif(1, -t_max, t_max - 1L)),
       lambda = 1 / 10)
}

get_rune_time_summary <- function(n, p){
  sims <- sim_func(n, p)

  out <- summary(microbenchmark(
    EKF_one_correction_step =
      suppressMessages(ddhazard(
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1e6, p + 1L),
        Q = diag(1e-1, p + 1L))),

    EKF_more_correction_step =
      suppressMessages(ddhazard(
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1, p + 1L),
        Q = diag(1e-1, p + 1L),
        control = list(NR_eps = 1e-3))),

    SMA = suppressMessages(ddhazard(
```

```
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1e6, p + 1L),
        Q = diag(1e-1, p + 1L),
        control = list(method = "SMA"))),

    GMA = suppressMessages(ddhazard(
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1, p + 1L),
        Q = diag(1e-1, p + 1L),
        control = list(method = "GMA"))),

    UKF = suppressMessages(ddhazard(
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1, p + 1L),
        Q = diag(1e-1, p + 1L),
        control = list(method = "UKF"))),

    times = 5
  ))

  cat("(n, p) = (", n, ", ", p, ")",
      ". Units is ", sQuote(attr(out, "unit")), "\n", sep = "")

  print(out[, c("expr", "lq", "median", "uq", "cld")], row.names = FALSE)

  cat("\n\n")

  invisible()
}
```

Test

```
grid_vals <- expand.grid(
  n = c(250, 1000, 10000),
  p = c(5, 10, 15))
```

```
invisible(
  mapply(get_rune_time_summary, n = grid_vals$n, p = grid_vals$p))
```

```
## (n, p) = (250, 5). Units is 'milliseconds'
##                       expr   lq median    uq cld
##   EKF_one_correction_step 19.4   25.1  25.6   a
##  EKF_more_correction_step 37.8   41.5  43.1   a
##                       SMA 93.5   95.6 105.9   a
##                       GMA 32.6   33.7  34.3   a
##                       UKF 87.2   90.1  93.4   a
##
##
## (n, p) = (1000, 5). Units is 'milliseconds'
##                       expr   lq median    uq  cld
##   EKF_one_correction_step 32.3   33.2  36.1 a
##  EKF_more_correction_step 44.7   47.6  54.2  b
##                       SMA 61.7   63.5  65.9   c
##                       GMA 42.6   44.6  47.5  b
##                       UKF 99.3   99.7 102.0    d
##
##
## (n, p) = (10000, 5). Units is 'milliseconds'
##                       expr  lq median  uq cld
##   EKF_one_correction_step 170    270 271 a
##  EKF_more_correction_step 339    431 457  b
##                       SMA 591    598 619   c
##                       GMA 223    312 328 ab
##                       UKF 584    661 717   c
##
##
## (n, p) = (250, 10). Units is 'milliseconds'
##                       expr    lq median    uq cld
##   EKF_one_correction_step  44.7   48.2  48.8 a
##  EKF_more_correction_step  77.8   77.8  85.4 a
##                       SMA 131.9  148.6 157.0  b
##                       GMA  70.6   77.9  90.3 a
##                       UKF 347.6  356.7 360.3   c
##
##
## (n, p) = (1000, 10). Units is 'milliseconds'
##                       expr    lq median    uq  cld
##   EKF_one_correction_step  37.8   38.2  53.2 a
##  EKF_more_correction_step  60.9   63.9  76.3  b
##                       SMA 118.5  121.6 144.3   c
##                       GMA  58.2   64.6  67.4 ab
##                       UKF 215.0  217.3 219.8    d
##
##
## (n, p) = (10000, 10). Units is 'milliseconds'
##                       expr   lq median   uq  cld
##   EKF_one_correction_step  348    372  375 a
##  EKF_more_correction_step  480    493  526  b
##                       SMA  778    789  841   c
##                       GMA  386    387  388 a
```

```
##                       UKF 1098   1104 1109    d
##
##
## (n, p) = (250, 15). Units is 'milliseconds'
##                      expr    lq median    uq cld
##   EKF_one_correction_step 105.4  109.6 110.3 a
##  EKF_more_correction_step  89.1   91.4  93.5 a
##                       SMA 190.0  190.8 209.5  b
##                       GMA  85.2   86.9  99.3 a
##                       UKF 510.3  530.8 551.0   c
##
##
## (n, p) = (1000, 15). Units is 'milliseconds'
##                      expr    lq median  uq cld
##   EKF_one_correction_step  87.8    111 112 a
##  EKF_more_correction_step 153.5    154 164 a
##                       SMA 399.5    416 447  b
##                       GMA 140.5    142 143 a
##                       UKF 554.5    556 569   c
##
##
## (n, p) = (10000, 15). Units is 'milliseconds'
##                      expr   lq median   uq  cld
##   EKF_one_correction_step  374    377  397 a
##  EKF_more_correction_step  518    635  657  b
##                       SMA 1146   1195 1235   c
##                       GMA  459    503  514 ab
##                       UKF 2159   2160 2241    d
```

Session info

- R version 3.4.0 (2017-04-21), `x86_64-w64-mingw32`
- Locale: `LC_COLLATE=English_United Kingdom.1252`, `LC_CTYPE=English_United Kingdom.1252`, `LC_MONETARY=English_United Kingdom.1252`, `LC_NUMERIC=C`, `LC_TIME=English_United Kingdom.1252`
- Running under: `Windows 10 x64 (build 15063)`
- Matrix products: default
- Base packages: base, datasets, graphics, grDevices, methods, stats, utils
- Other packages: dynamichazard 0.3.4, microbenchmark 1.4-2.1, survival 2.41-3
- Loaded via a namespace (and not attached): backports 1.1.0, boot 1.3-19, codetools 0.2-15, colorspace 1.3-2, compiler 3.4.0, data.table 1.10.4, digest 0.6.12, evaluate 0.10, ggplot2 2.2.1, grid 3.4.0, gtable 0.2.0, htmltools 0.3.6, knitr 1.16, lattice 0.20-35, lazyeval 0.2.0, magrittr 1.5, MASS 7.3-47, Matrix 1.2-9, multcomp 1.4-6, munsell 0.4.3, mvtnorm 1.0-6, plyr 1.8.4, Rcpp 0.12.11, rlang 0.1.1, rmarkdown 1.5, rprojroot 1.2, sandwich 2.3-4, scales 0.4.1, speedglm 0.3-2, splines 3.4.0, stringi 1.1.5, stringr 1.2.0, TH.data 1.0-8, tibble 1.3.3, tools 3.4.0, yaml 2.1.14, zoo 1.8-0