

# speedtest

*Benjamin Christoffersen*

*2018-08-13*

## Setup

```
library(dynamichazard); library(microbenchmark)

## Loading required package: survival

sim_func <- function(n, p){
  func <- asNamespace("dynamichazard")$test_sim_func_logit
  set.seed(101)
  t_max <- 30L
  func(n_series = n, n_vars = p, t_max = t_max, x_range = 1, x_mean = 0,
       beta_start = runif(p, -1.5, 1.5),
       intercept_start = -3, sds = c(.1, rep(.25, p)),
       tstart_sampl_func = function(t0, t_max)
         max(0, runif(1, -t_max, t_max - 1L)),
       lambda = 1 / 10)
}

get_rune_time_summary <- function(n, p){
  sims <- sim_func(n, p)

  out <- summary(microbenchmark(
    EKF_one_correction_step =
      suppressMessages(ddhazard(
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1e6, p + 1L),
        Q = diag(1e-1, p + 1L))),
    EKF_more_correction_step =
      suppressMessages(ddhazard(
        formula = Surv(tstart, tstop, event) ~ . - id,
        data = sims$res,
        model = "logit",
        id = sims$res$id,
        by = 1L,
        max_T = 30L,
        Q_0 = diag(1, p + 1L),
        Q = diag(1e-1, p + 1L),
        control = list(NR_eps = 1e-3))),
    SMA = suppressMessages(ddhazard(
```

```

    formula = Surv(tstart, tstop, event) ~ . - id,
    data = sims$res,
    model = "logit",
    id = sims$res$id,
    by = 1L,
    max_T = 30L,
    Q_0 = diag(1e6, p + 1L),
    Q = diag(1e-1, p + 1L),
    control = list(method = "SMA"))),

  GMA = suppressMessages(ddhazard(
    formula = Surv(tstart, tstop, event) ~ . - id,
    data = sims$res,
    model = "logit",
    id = sims$res$id,
    by = 1L,
    max_T = 30L,
    Q_0 = diag(1, p + 1L),
    Q = diag(1e-1, p + 1L),
    control = list(method = "GMA"))),

  UKF = suppressMessages(ddhazard(
    formula = Surv(tstart, tstop, event) ~ . - id,
    data = sims$res,
    model = "logit",
    id = sims$res$id,
    by = 1L,
    max_T = 30L,
    Q_0 = diag(1, p + 1L),
    Q = diag(1e-1, p + 1L),
    control = list(method = "UKF"))),

  times = 1
))

cat("(n, p) = (", n, ", ", p, ")",
    ". Units is ", sQuote(attr(out, "unit")), "\n", sep = "")

print(out[, c("expr", "lq", "median", "uq")], row.names = FALSE)

cat("\n\n")

invisible()
}

```

## Test

```

grid_vals <- expand.grid(
  n = c(250, 1000, 10000),
  p = c(5, 10, 15))

```

```
invisible(
  mapply(get_rune_time_summary, n = grid_vals$n, p = grid_vals$p))
```

```
## (n, p) = (250, 5). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  65.6   65.6  65.6
## EKF_more_correction_step 127.0  127.0 127.0
##           SMA 193.6   193.6 193.6
##           GMA 207.6   207.6 207.6
##           UKF 334.6   334.6 334.6
##
##
## (n, p) = (1000, 5). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  202    202 202
## EKF_more_correction_step 589    589 589
##           SMA 633    633 633
##           GMA 297    297 297
##           UKF 543    543 543
##
##
## (n, p) = (10000, 5). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  383    383 383
## EKF_more_correction_step 961    961 961
##           SMA 2597   2597 2597
##           GMA 896    896 896
##           UKF 2686   2686 2686
##
##
## (n, p) = (250, 10). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  110    110 110
## EKF_more_correction_step 276    276 276
##           SMA 488    488 488
##           GMA 370    370 370
##           UKF 981    981 981
##
##
## (n, p) = (1000, 10). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  141    141 141
## EKF_more_correction_step 304    304 304
##           SMA 926    926 926
##           GMA 212    212 212
##           UKF 919    919 919
##
##
## (n, p) = (10000, 10). Units is 'milliseconds'
##           expr    lq median    uq
## EKF_one_correction_step  448    448 448
## EKF_more_correction_step 1043   1043 1043
##           SMA 3498   3498 3498
##           GMA 1170   1170 1170
```

```

##          UKF 4323   4323 4323
##
##
## (n, p) = (250, 15). Units is 'milliseconds'
##      expr   lq median   uq
## EKF_one_correction_step 289   289 289
## EKF_more_correction_step 348   348 348
##          SMA 1017   1017 1017
##          GMA 438    438 438
##          UKF 2122   2122 2122
##
##
## (n, p) = (1000, 15). Units is 'milliseconds'
##      expr   lq median   uq
## EKF_one_correction_step 209   209 209
## EKF_more_correction_step 455   455 455
##          SMA 970    970 970
##          GMA 352    352 352
##          UKF 1507   1507 1507
##
##
## (n, p) = (10000, 15). Units is 'milliseconds'
##      expr   lq median   uq
## EKF_one_correction_step 597   597 597
## EKF_more_correction_step 962   962 962
##          SMA 4539   4539 4539
##          GMA 1267   1267 1267
##          UKF 5501   5501 5501

```

## Session info

- R version 3.5.0 (2018-04-23), x86\_64-w64-mingw32
- Locale: LC\_COLLATE=English\_United States.1252, LC\_CTYPE=C, LC\_MONETARY=English\_United States.1252, LC\_NUMERIC=C, LC\_TIME=English\_United States.1252
- Running under: Windows 10 x64 (build 17134)
- Matrix products: default
- Base packages: base, datasets, graphics, grDevices, methods, stats, utils
- Other packages: dynamichazard 0.6.0, microbenchmark 1.4-4, survival 2.41-3
- Loaded via a namespace (and not attached): backports 1.1.2, boot 1.3-20, compiler 3.5.0, digest 0.6.15, evaluate 0.10.1, grid 3.5.0, htmltools 0.3.6, knitr 1.20, lattice 0.20-35, magrittr 1.5, Matrix 1.2-14, parallel 3.5.0, Rcpp 0.12.17, rmarkdown 1.9, rprojroot 1.3-2, splines 3.5.0, stringi 1.1.7, stringr 1.3.0, tools 3.5.0, yaml 2.1.18