ESP8266 CH340 Micro USB Interface

Product Description:

The product is a development board the ESP-12E WiFi module. We added peripheral circuits to it to facilitate learning, development and use. The CH340G serial port chip used in the peripheral circuit has stable performance and is very convenient for debugging. Just connect it to the computer with micro USB cable, you can download the program for debugging, and burn the firmware with special software.

WiFi module parameters:

1. 802.11 b/g/n
2. FCC Wireless Certification
3. Built in Tensilica L106 ultra-low power 32-bit micro MCU, the main frequency supports 80 MHz and 160 MHz, and supports RTOS
4. Built in 10bit high-precision ADC
5. Built in TCP/IP protocol stack
6. Built in TR switch, balun, LNA, power amplifier and matching network
7. Built in PLL, voltage regulator and power management components, in 802.11b mode +20dBm output power
8. Aggregation of A-MPDU and A-MSDU and protection interval of 0.4s
9. WiFi @ 2.4GHz, supporting WPA /WPA2 security mode
10. Support AT remote upgrade and cloud OTA upgrade
11. Support STA/AP/STA+AP working mode
12. Support smart config function (including Android and IOS devices)
13. HSPI, UART, I2C, I2S, IR Remote Control, PWM, GPIO
14. The deep sleep holding current is 10uA, and the off current is less than 5uA
15. Wake up, connect and transfer data packets within 15.2ms
16. Power consumption in standby state is less than 1.0mW (DTM3)
17. Operating temperature range: - 40 °C - 125 °C



Application Circuit:

