


COUNT, DISTINCT, NVL

What Will I Learn?

In this lesson, you will learn to:

- Construct and execute a SQL query using the COUNT group function
- Use DISTINCT and the NVL function with group functions





Why Learn It?

Being able to aggregate data using SQL functions enables businesses to do calculations that would otherwise have to be done by hand.

Remember the example of having to count all the students in your school? A daunting task! There just aren't enough hands to accomplish it manually.

Fortunately, the SQL group functions can easily process these types of requests.





Tell Me / Show Me

COUNT

COUNT(expression) returns the number of non-null values in the expression column

```
SELECT COUNT (YEAR)
FROM d_cds
WHERE year < 2001;
```

COUNT (YEAR)
5

COUNT(DISTINCT expression) returns the number of unique non-null values in the expression column.

```
SELECT COUNT (DISTINCT year)
FROM d_cds
WHERE year < 2001;
```

COUNT (DISTINCT YEAR)
4



Tell Me / Show Me

COUNT

Why are null values returned in the query shown? There are six comments listed, but the count function returned only five. Why?

Because COUNT ignores the null value in the column.

```
SELECT comments  
FROM d_play_list_items;
```

COMMENTS
Play late
(null)
Play early
Play after cake cutting
Play first
Play for the father

```
SELECT COUNT(comments)  
FROM d_play_list_items;
```

COUNT (COMMENTS)
5



Tell Me / Show Me

COUNT

COUNT(*) returns the number of rows in a table that satisfy the criteria of the SELECT statement.

For example, to find out how many of DJs on Demand's CDs were produced before 2001, COUNT can be used in the SELECT statement.

We use COUNT(*) when we want to make sure that we count all the rows, including those that may have nulls in one or more columns.

```
SELECT COUNT (*)  
FROM d_cds  
WHERE year < 2001;
```

COUNT (*)
5



Tell Me / Show Me

DISTINCT

The keyword DISTINCT is used to return only nonduplicate values or combinations of nonduplicate values in a query.

Examine the query on the right. Without using the keyword DISTINCT, the query returned all of the year values from the DJs on Demand D_CDS table.

```
SELECT year as 'CD Year'  
FROM d_cds;
```

CD Year
1997
2000
2002
1999
2000
2001
1998
2004



Tell Me / Show Me

To eliminate duplicate rows, use the **DISTINCT** keyword as shown here.

Using the **DISTINCT** keyword returned all the CD years exactly once, with no duplicate values.

```
SELECT DISTINCT year AS 'CD Year'  
FROM d_cds;
```

CD Years
1997
1998
1999
2000
2001
2002
2004

Tell Me / Show Me

The keyword **DISTINCT**, when used in a query selecting more than one column, will return nonduplicate combinations of the columns. Examine the two results sets shown here. Can you tell which query used the **DISTINCT** keyword?

In this case, it's hard to tell, isn't it? The results set on the top was returned using the **DISTINCT** keyword. In both examples, there are no duplicate combinations of year and title even though there are duplicate years.

YEAR	TITLE
1997	The Celebrants Live in Concert
1998	Graduation Songbook
1999	Songs from My Childhood
2000	Cape Diem
2000	Party Music for All Occasions
2001	Here Comes the Bride
2002	Back to the Shire
2004	Whirled Peas

```
SELECT DISTINCT year, title  
FROM d_cds;
```

YEAR	TITLE
1997	The Celebrants Live in Concert
2000	Party Music for All Occasions
2002	Back to the Shire
1999	Songs from My Childhood
2000	Carpe Diem
2001	Here Comes the Bride
1998	Graduation Songbook
2004	Whirled Peas



Tell Me / Show Me

Using DISTINCT

The keyword DISTINCT can be used with all group functions. Using DISTINCT makes the function consider only nonduplicate values.

Why do the two statements on the right produce different results?

```
SELECT SUM(salary)
FROM employees
WHERE department_id = 90;
```

SALARY	SUM(SALARY)
24000	58000
17000	
17000	

```
SELECT SUM(DISTINCT salary)
FROM employees
WHERE department_id = 90;
```

SALARY	SUM(DISTINCT SALARY)
24000	41000
17000	
17000	



Tell Me / Show Me

When using DISTINCT with a group function such as COUNT, the result set will return the number of nonduplicate column values.

How many different jobs do our employees do ?

```
SELECT COUNT (DISTINCT job_id)
FROM employees;
```

COUNT (DISTINCT job_id)
12

How many different salaries are there ?

```
SELECT COUNT (DISTINCT salary)
FROM employees;
```

COUNT (DISTINCT salary)
18



Tell Me / Show Me

NVL

Sometimes it is desirable to include null values in group functions. For example, knowing the average number of customer orders served each day could be used to judge how much food to order each month. Some days the restaurant is closed and there are no customers, but the owner has found that computing the average including every day is a better indicator than just counting the days with customers. The SELECT statement to include null values could be written starting with:

```
SELECT AVG(NVL(customer_orders, 0))
```

Tell Me / Show Me


Terminology

Key terms used in this lesson include:

COUNT (expression)

COUNT (DISTINCT expression)

DISTINCT






Summary

In this lesson you have learned to:

- Construct and execute a SQL query using the COUNT group function
- Use DISTINCT and the NVL function with group functions



Summary

Practice Guide

The link for the lesson practice guide can be found in the course resources in Section 0.

