

Application

Used in PDA, DSC, DVC, Wireless communication, Mobile phone, PC, and more.

Features

- 3225 size miniature and light SMD crystal resonator with a low profile of 0.7mm
- Wide frequency range form a comparatively low 12MHz up to 48MHz
- High precision and high frequency stability
- Excellent heat resistance and environmental characteristics
- · Automatic mounting and reflow soldering

Electrical Specifications

Frequency Range : 12 ~ 48MHz

Frequency Tolerance (at 25°C) : ±10ppm, ±30ppm

Frequency Stability Over Operating

Temperature Range

: ±10ppm ~ ±30ppm


Operating Temperature Range : -20°C ~ +70°C


 $Shunt \ Capacitance(C_0) \\ \hspace{2cm} : 3pF \ Max.$


Drive Level : 1~200μW Max. (100μW Typical)


Aging (at 25°C) : ± 3 ppm / year Max. Storage Temperature Range : -55°C $\sim +125$ °C

Diagram









Dimensions: Millimetres





Part Number Table

Description	Part Number
Crystal Resonator, 3225, 12MHz/ ±10ppm, 80Ω, ±10ppm, -20 ~ +70°C, 10pF	MCSJK-7U-12.00-10-10-80-B-10
Crystal Resonator, 3225, 12MHz/ ±30ppm, 80Ω, ±30ppm, -20 ~ +70°C, 10pF	MCSJK-7U-12.00-10-30-80-B-30
Crystal Resonator, 3225, 12MHz/ ±10ppm, 80Ω, ±10ppm, -20 ~ +70°C, 12pF	MCSJK-7U-12.00-12-10-80-B-10
Crystal Resonator, 3225, 12MHz/ ±30ppm, 80Ω, ±30ppm, -20 ~ +70°C, 12pF	MCSJK-7U-12.00-12-30-80-B-30
Crystal Resonator, 3225, 12.288MHz/ ±10ppm, 80Ω, ±10ppm, -20 ~ +70°C, 10pF	MCSJK-7U-12.288-10-10-80-B-10
Crystal Resonator, 3225, 12.288MHz/ ±30ppm, 80Ω, ±30ppm, -20 ~ +70°C, 10pF	MCSJK-7U-12.288-10-30-80-B-30
Crystal Resonator, 3225, 12.288MHz/ ±10ppm, 80Ω, ±10ppm, -20 ~ +70°C, 12pF	MCSJK-7U-12.288-12-10-80-B-10
Crystal Resonator, 3225, 12.288MHz/ ±30ppm, 80Ω, ±30ppm, -20 ~ +70°C, 12pF	MCSJK-7U-12.288-12-30-80-B-30
Crystal Resonator, 3225, 13.56MHz/ ±10ppm, 80Ω, ±10ppm, -20 ~ +70°C, 10pF	MCSJK-7U-13.56-10-10-80-B-10
Crystal Resonator, 3225, 13.56MHz/ \pm 30ppm, 80 Ω , \pm 30ppm, -20 \sim +70 $^{\circ}$ C, 10pF	MCSJK-7U-13.56-10-30-80-B-30
Crystal Resonator, 3225, 13.56MHz/ \pm 10ppm, 80 Ω , \pm 10ppm, -20 \sim +70 $^{\circ}$ C, 12pF	MCSJK-7U-13.56-12-10-80-B-10
Crystal Resonator, 3225, 13.56MHz/ ±30ppm, 80Ω, ±30ppm, -20 ~ +70°C, 12pF	MCSJK-7U-13.56-12-30-80-B-30
Crystal Resonator, 3225, 14.31818MHz/ \pm 10ppm, 80 Ω , \pm 10ppm, -20 \sim +70°C, 10pF	MCSJK-7U-14.31818-10-10-80-B-10
Crystal Resonator, 3225, 14.31818MHz/ \pm 30ppm, 80Ω , \pm 30ppm, $-20 \sim +70^{\circ}$ C, 10pF	MCSJK-7U-14.31818-10-30-80-B-30
Crystal Resonator, 3225, 14.31818MHz/ \pm 10ppm, 80Ω , \pm 10ppm, $-20 \sim +70^{\circ}$ C, 12pF	MCSJK-7U-14.31818-12-10-80-B-10
Crystal Resonator, 3225, 14.31818MHz/ \pm 30ppm, 80Ω , \pm 30ppm, $-20 \sim +70^{\circ}$ C, 12pF	MCSJK-7U-14.31818-12-30-80-B-30
Crystal Resonator, 3225, 14.7456MHz/ \pm 10ppm, 80 Ω , \pm 10ppm, -20 \sim +70°C, 10pF	MCSJK-7U-14.7456-10-10-80-B-10
Crystal Resonator, 3225, 14.7456MHz/ \pm 30ppm, 80 Ω , \pm 30ppm, -20 ~ +70°C, 10pF	MCSJK-7U-14.7456-10-30-80-B-30
Crystal Resonator, 3225, 14.7456MHz/ \pm 10ppm, 80 Ω , \pm 10ppm, -20 \sim +70 $^{\circ}$ C, 12pF	MCSJK-7U-14.7456-12-10-80-B-10
Crystal Resonator, 3225, 14.7456MHz/ \pm 30ppm, 80 Ω , \pm 30ppm, -20 \sim +70 $^{\circ}$ C, 12pF	MCSJK-7U-14.7456-12-30-80-B-30
Crystal Resonator, 3225, 16MHz/ ±10ppm, 80Ω, ±10ppm, -20 ~ +70°C, 10pF	MCSJK-7U-16.00-10-10-80-B-10
Crystal Resonator, 3225, 16MHz/ ±30ppm, 80Ω, ±30ppm, -20 ~ +70°C, 10pF	MCSJK-7U-16.00-10-30-80-B-30
Crystal Resonator, 3225, 16MHz/ ±10ppm, 80Ω, ±10ppm, -20 ~ +70°C, 12pF	MCSJK-7U-16.00-12-10-80-B-10
Crystal Resonator, 3225, 16MHz/ ±30ppm, 80Ω, ±30ppm, -20 ~ +70°C, 12pF	MCSJK-7U-16.00-12-30-80-B-30
Crystal Resonator, 3225, 16.384MHz/ ±10ppm, 80Ω, ±10ppm, -20 ~ +70°C, 10pF	MCSJK-7U-16.384-10-10-80-B-10
Crystal Resonator, 3225, 16.384MHz/ ±30ppm, 80Ω, ±30ppm, -20 ~ +70°C, 10pF	MCSJK-7U-16.384-10-30-80-B-30
Crystal Resonator, 3225, 16.384MHz/ ±10ppm, 80Ω, ±10ppm, -20 ~ +70°C, 12pF	MCSJK-7U-16.384-12-10-80-B-10
Crystal Resonator, 3225, 16.384MHz/ ±30ppm, 80Ω, ±30ppm, -20 ~ +70°C, 12pF	MCSJK-7U-16.384-12-30-80-B-30
Crystal Resonator, 3225, 16.934MHz/ ±10ppm, 80Ω, ±10ppm, -20 ~ +70°C, 10pF	MCSJK-7U-16.934-10-10-80-B-10
Crystal Resonator, 3225, 16.934MHz/ ±30ppm, 80Ω, ±30ppm, -20 ~ +70°C, 10pF	MCSJK-7U-16.934-10-30-80-B-30
Crystal Resonator, 3225, 16.934MHz/ ±10ppm, 80Ω, ±10ppm, -20 ~ +70°C, 12pF	MCSJK-7U-16.934-12-10-80-B-10
Crystal Resonator, 3225, 16.934MHz/ ±30ppm, 80Ω, ±30ppm, -20 ~ +70°C, 12pF	MCSJK-7U-16.934-12-30-80-B-30
Crystal Resonator, 3225, 18.432MHz/ ±10ppm, 80Ω, ±10ppm, -20 ~ +70°C, 10pF	MCSJK-7U-18.432-10-10-80-B-10
Crystal Resonator, 3225, 18.432MHz/ ±30ppm, 80Ω, ±30ppm, -20 ~ +70°C, 10pF	MCSJK-7U-18.432-10-30-80-B-30
Crystal Resonator, 3225, 18.432MHz/ ±10ppm, 80Ω, ±10ppm, -20 ~ +70°C, 12pF	MCSJK-7U-18.432-12-10-80-B-10
Crystal Resonator, 3225, 18.432MHz/ ±30ppm, 80Ω, ±30ppm, -20 ~ +70°C, 12pF	MCSJK-7U-18.432-12-30-80-B-30
Crystal Resonator, 3225, 19.2MHz/ ±10ppm, 80Ω, ±10ppm, -20 ~ +70°C, 10pF	MCSJK-7U-19.20-10-10-80-B-10
Crystal Resonator, 3225, 19.2MHz/ ±30ppm, 80Ω, ±30ppm, -20 ~ +70°C, 10pF	MCSJK-7U-19.20-10-30-80-B-30





Description	Part Number
Crystal Resonator, 3225, 19.2MHz/ ±10ppm, 80Ω, ±10ppm, -20 ~ +70°C, 12pF	MCSJK-7U-19.20-12-10-80-B-10
Crystal Resonator, 3225, 19.2MHz/ ±30ppm, 80Ω, ±30ppm, -20 ~ +70°C, 12pF	MCSJK-7U-19.20-12-30-80-B-30
Crystal Resonator, 3225, 20MHz/ ±10ppm, 60Ω, ±10ppm, -20 ~ +70°C, 10pF	MCSJK-7U-20.00-10-10-60-B-10
Crystal Resonator, 3225, 20MHz/ ±30ppm, 60Ω, ±30ppm, -20 ~ +70°C, 10pF	MCSJK-7U-20.00-10-30-60-B-30
Crystal Resonator, 3225, 20MHz/ ±10ppm, 60Ω, ±10ppm, -20 ~ +70°C, 12pF	MCSJK-7U-20.00-12-10-60-B-10
Crystal Resonator, 3225, 20MHz/ ±30ppm, 60Ω, ±30ppm, -20 ~ +70°C, 12pF	MCSJK-7U-20.00-12-30-60-B-30
Crystal Resonator, 3225, 24MHz/ ±10ppm, 60Ω, ±10ppm, -20 ~ +70°C, 10pF	MCSJK-7U-24.00-10-10-60-B-10
Crystal Resonator, 3225, 24MHz/ ±30ppm, 60Ω, ±30ppm, -20 ~ +70°C, 10pF	MCSJK-7U-24.00-10-30-60-B-30
Crystal Resonator, 3225, 24MHz/ ±10ppm, 60Ω, ±10ppm, -20 ~ +70°C, 12pF	MCSJK-7U-24.00-12-10-60-B-10
Crystal Resonator, 3225, 24MHz/ ±30ppm, 60Ω, ±30ppm, -20 ~ +70°C, 12pF	MCSJK-7U-24.00-12-30-60-B-30
Crystal Resonator, 3225, 24.576MHz/ ±10ppm, 60Ω, ±10ppm, -20 ~ +70°C, 10pF	MCSJK-7U-24.576-10-10-60-B-10
Crystal Resonator, 3225, 24.576MHz/ ±30ppm, 60Ω, ±30ppm, -20 ~ +70°C, 10pF	MCSJK-7U-24.576-10-30-60-B-30
Crystal Resonator, 3225, 24.576MHz/ ±10ppm, 60Ω, ±10ppm, -20 ~ +70°C, 12pF	MCSJK-7U-24.576-12-10-60-B-10
Crystal Resonator, 3225, 24.576MHz/ ±30ppm, 60Ω, ±30ppm, -20 ~ +70°C, 12pF	MCSJK-7U-24.576-12-30-60-B-30
Crystal Resonator, 3225, 25MHz/ ±10ppm, 60Ω, ±10ppm, -20 ~ +70°C, 10pF	MCSJK-7U-25.00-10-10-60-B-10
Crystal Resonator, 3225, 25MHz/ ±30ppm, 60Ω, ±30ppm, -20 ~ +70°C, 10pF	MCSJK-7U-25.00-10-30-60-B-30
Crystal Resonator, 3225, 25MHz/ ±10ppm, 60Ω, ±10ppm, -20 ~ +70°C, 12pF	MCSJK-7U-25.00-12-10-60-B-10
Crystal Resonator, 3225, 25MHz/ ±30ppm, 60Ω, ±30ppm, -20 ~ +70°C, 12pF	MCSJK-7U-25.00-12-30-60-B-30
Crystal Resonator, 3225, 26MHz/ ±10ppm, 60Ω, ±10ppm, -20 ~ +70°C, 10pF	MCSJK-7U-26.00-10-10-60-B-10
Crystal Resonator, 3225, 26MHz/ ±30ppm, 60Ω, ±30ppm, -20 ~ +70°C, 10pF	MCSJK-7U-26.00-10-30-60-B-30
Crystal Resonator, 3225, 26MHz/ ±10ppm, 60Ω, ±10ppm, -20 ~ +70°C, 12pF	MCSJK-7U-26.00-12-10-60-B-10
Crystal Resonator, 3225, 26MHz/ ±30ppm, 60Ω, ±30ppm, -20 ~ +70°C, 12pF	MCSJK-7U-26.00-12-30-60-B-30
Crystal Resonator, 3225, 27MHz/ ±10ppm, 60Ω, ±10ppm, -20 ~ +70°C, 10pF	MCSJK-7U-27.00-10-10-60-B-10
Crystal Resonator, 3225, 27MHz/ ±30ppm, 60Ω, ±30ppm, -20 ~ +70°C, 10pF	MCSJK-7U-27.00-10-30-60-B-30
Crystal Resonator, 3225, 27MHz/ ±10ppm, 60Ω, ±10ppm, -20 ~ +70°C, 12pF	MCSJK-7U-27.00-12-10-60-B-10
Crystal Resonator, 3225, 27MHz/ ±30ppm, 60Ω, ±30ppm, -20 ~ +70°C, 12pF	MCSJK-7U-27.00-12-30-60-B-30
Crystal Resonator, 3225, 27.12MHz/ \pm 10ppm, 60 Ω , \pm 10ppm, -20 \sim +70 $^{\circ}$ C, 10pF	MCSJK-7U-27.12-10-10-60-B-10
Crystal Resonator, 3225, 27.12MHz/ ±30ppm, 60Ω, ±30ppm, -20 ~ +70°C, 10pF	MCSJK-7U-27.12-10-30-60-B-30
Crystal Resonator, 3225, 27.12MHz/ ±10ppm, 60Ω, ±10ppm, -20 ~ +70°C, 12pF	MCSJK-7U-27.12-12-10-60-B-10
Crystal Resonator, 3225, 27.12MHz/ ±30ppm, 60Ω, ±30ppm, -20 ~ +70°C, 12pF	MCSJK-7U-27.12-12-30-60-B-30
Crystal Resonator, 3225, 28.63636MHz/ ±10ppm, 60Ω, ±10ppm, -20 ~ +70°C, 10pF	MCSJK-7U-28.63636-10-10-60-B-10
Crystal Resonator, 3225, 28.63636MHz/ ±30ppm, 60Ω, ±30ppm, -20 ~ +70°C, 10pF	MCSJK-7U-28.63636-10-30-60-B-30
Crystal Resonator, 3225, 28.63636MHz/ ±10ppm, 60Ω, ±10ppm, -20 ~ +70°C, 12pF	MCSJK-7U-28.63636-12-10-60-B-10
Crystal Resonator, 3225, 28.63636MHz/ \pm 30ppm, 60 Ω , \pm 30ppm, -20 \sim +70°C, 12pF	MCSJK-7U-28.63636-12-30-60-B-30
Crystal Resonator, 3225, 30MHz/ ±10ppm, 60Ω, ±10ppm, -20 ~ +70°C, 10pF	MCSJK-7U-30.00-10-10-60-B-10
Crystal Resonator, 3225, 30MHz/ ±30ppm, 60Ω, ±30ppm, -20 ~ +70°C, 10pF	MCSJK-7U-30.00-10-30-60-B-30
Crystal Resonator, 3225, 30MHz/ ±10ppm, 60Ω, ±10ppm, -20 ~ +70°C, 12pF	MCSJK-7U-30.00-12-10-60-B-10
Crystal Resonator, 3225, 30MHz/ \pm 30ppm, 60 Ω , \pm 30ppm, -20 \sim +70 $^{\circ}$ C, 12pF	MCSJK-7U-30.00-12-30-60-B-30





Description	Part Number
Crystal Resonator, 3225, 32MHz/ ±10ppm, 60Ω, ±10ppm, -20 ~ +70°C, 10pF	MCSJK-7U-32.00-10-10-60-B-10
Crystal Resonator, 3225, 32MHz/ ±30ppm, 60Ω, ±30ppm, -20 ~ +70°C, 10pF	MCSJK-7U-32.00-10-30-60-B-30
Crystal Resonator, 3225, 32MHz/ ±10ppm, 60Ω, ±10ppm, -20 ~ +70°C, 12pF	MCSJK-7U-32.00-12-10-60-B-10
Crystal Resonator, 3225, 32MHz/ ±30ppm, 60Ω, ±30ppm, -20 ~ +70°C, 12pF	MCSJK-7U-32.00-12-30-60-B-30
Crystal Resonator, 3225, 36MHz/ ±10ppm, 60Ω, ±10ppm, -20 ~ +70°C, 10pF	MCSJK-7U-36.00-10-10-60-B-10
Crystal Resonator, 3225, 36MHz/ ±30ppm, 60Ω, ±30ppm, -20 ~ +70°C, 10pF	MCSJK-7U-36.00-10-30-60-B-30
Crystal Resonator, 3225, 36MHz/ ±10ppm, 60Ω, ±10ppm, -20 ~ +70°C, 12pF	MCSJK-7U-36.00-12-10-60-B-10
Crystal Resonator, 3225, 36MHz/ ±30ppm, 60Ω, ±30ppm, -20 ~ +70°C, 12pF	MCSJK-7U-36.00-12-30-60-B-30
Crystal Resonator, 3225, 38.4MHz/ ± 10 ppm, 60Ω , ± 10 ppm, $-20 \sim +70$ °C, 10 pF	MCSJK-7U-38.4-10-10-60-B-10
Crystal Resonator, 3225, 38.4MHz/ \pm 30ppm, 60 Ω , \pm 30ppm, -20 \sim +70 $^{\circ}$ C, 10pF	MCSJK-7U-38.4-10-30-60-B-30
Crystal Resonator, 3225, 38.4MHz/ ±10ppm, 60Ω, ±10ppm, -20 ~ +70°C, 12pF	MCSJK-7U-38.4-12-10-60-B-10
Crystal Resonator, 3225, 38.4MHz/ \pm 30ppm, 60 Ω , \pm 30ppm, -20 \sim +70 $^{\circ}$ C, 12pF	MCSJK-7U-38.4-12-30-60-B-30
Crystal Resonator, 3225, 40MHz/ ±10ppm, 60Ω, ±10ppm, -20 ~ +70°C, 10pF	MCSJK-7U-40.00-10-10-60-B-10
Crystal Resonator, 3225, 40MHz/ \pm 30ppm, 60 Ω , \pm 30ppm, -20 \sim +70°C, 10pF	MCSJK-7U-40.00-10-30-60-B-30
Crystal Resonator, 3225, 40MHz/ \pm 10ppm, 60 Ω , \pm 10ppm, -20 \sim +70°C, 12pF	MCSJK-7U-40.00-12-10-60-B-10
Crystal Resonator, 3225, 40MHz/ \pm 30ppm, 60 Ω , \pm 30ppm, -20 \sim +70 $^{\circ}$ C, 12pF	MCSJK-7U-40.00-12-30-60-B-30
Crystal Resonator, 3225, 48MHz/ ±10ppm, 60Ω, ±10ppm, -20 ~ +70°C, 10pF	MCSJK-7U-48.00-10-10-60-B-10
Crystal Resonator, 3225, 48MHz/ ±30ppm, 60Ω, ±30ppm, -20 ~ +70°C, 10pF	MCSJK-7U-48.00-10-30-60-B-30
Crystal Resonator, 3225, 48MHz/ ±10ppm, 60Ω, ±10ppm, -20 ~ +70°C, 12pF	MCSJK-7U-48.00-12-10-60-B-10
Crystal Resonator, 3225, 48MHz/ ±30ppm, 60Ω, ±30ppm, -20 ~ +70°C, 12pF	MCSJK-7U-48.00-12-30-60-B-30

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

