Comprehension Questions: Function C2

Direction A: Basic Protocol and Host Handling

A1. If self.conn_type='my_db', how is the initial URI prefix constructed?

A. my_db://

B. my-db://

C. MY_DB://

D. //my_db

A2. If self.host contains a protocol that differs from self.conn_type, how does the code handle it?

A. Ignore the protocol in host.

B. Store the protocol from host in protocol_to_add and use host with that protocol removed.

C. Raise an exception immediately.

D. Replace conn_type with the protocol from host.

A3. What happens if self.host does not contain '://'?

A. host_to_use uses the original host, and protocol_to_add is None.

B. host is set to an empty string.

C. The host must be regenerated from conn_type.

D. A parsing exception is raised.

Direction B: Authentication and Host-Block Assembly

B1. If both login and password are present, how is the authentication information assembled?

A. login@password

B. login:password@

C. password:login@

D. @login/password

B2. If a port is present but both host and authentication information are empty, what is added to host_block?

A. ':port'

B. '@:port'

C. '//port'

D. '?port=port'

B3. If schema is present, how is it appended?

A. It is added to the URI query.

B. It is appended to host_block as an escaped path segment.

C. It replaces host.

D. It is appended to authority_block as authentication information.

Direction C: Extra Parameters and Fallback

C1. Under what condition can extra_dict be expanded directly into ordinary query parameters?

A. All values in extra_dict are strings, and encoding followed by parsing reconstructs the original dictionary.

B. Whenever self.extra is non-empty.

C. Whenever schema is present.

D. Whenever urlencode raises an exception.

C2. If the extra parameters cannot be expanded safely, what does the code do?

A. Discard the extra parameters.

B. Place the original self.extra under EXTRA_KEY and then encode it.

C. Raise an exception.

D. Append extra to host.

C3. What determines the prefix used to append the extra query?

A. Whether login is present.

B. Whether password is present.

C. Whether schema is present: use '?' when schema exists, otherwise use '/?'.

D. Whether a port is present.

Overall Question

T1. Which option best summarizes the function?

A. It only assembles the hostname and port.

B. It assembles the protocol, optional authentication information, host block, schema, and extra query in stages, using fallback encoding when extra cannot be expanded directly.

C. It only checks whether the URI complies with RFC 3986.

D. It only handles Airflow logs.