Comprehension Questions: B2 (Warehouse)

Direction A: Branch Conditions

A1. If the same file is identified as both ZIP and TAR, how does the function handle it?

A. It prioritizes ZIP processing.

B. It prioritizes TAR processing.

C. It returns failure and indicates that the file belongs to both formats.

D. It continues security scanning before deciding.

A2. If a filename ends with .whl but zipfile.is_zipfile(filename) is false, what happens?

A. The function continues by trying to process it as TAR.

B. It returns failure and indicates that the file is not a ZIP file.

C. It returns success.

D. It raises BadZipFile.

A3. If the file extension is neither .zip, .whl, nor .tar.gz, and no earlier failure condition has been triggered, what does the function ultimately return?

A. (False, "Unsupported file type")

B. (False, None)

C. (True, None)

D. It raises an exception.

Direction B: Differences Between Processing Paths

B1. In which processing path does the compression-ratio check occur?

A. Only in the .tar.gz path.

B. Only in the .zip and .whl paths.

C. In all paths.

D. Only when security scanning is enabled.

B2. Which option correctly describes the key metadata files required for different formats?

A. .zip and .tar.gz check PKG-INFO; .whl checks WHEEL.

B. All three formats check only PKG-INFO.

C. All three formats check only WHEEL.

D. .zip checks WHEEL; .whl checks PKG-INFO.

B3. When is zipfiles.validate_zipfile(filename) called?

A. Only in the .tar.gz path.

B. After the internal checks for .zip or .whl are completed.

C. At the beginning of every function call.

D. Only after YARA scanning fails.

Direction C: Common Checks and Path Convergence

C1. When scan=False, which operation is still performed?

A. All YARA scans.

B. Archive-structure and metadata-file checks.

C. Only Sentry logging.

D. The function immediately returns success.

C2. What does the function do if a YARA rule matches?

A. It only logs the event but still returns success.

B. It deletes the file and continues.

C. It records a message and returns failure with the error information from the scan result.

D. It automatically disables subsequent scans.

C3. Which structural validation is shared by ZIP source distributions and .tar.gz packages?

A. Both must parse the wheel filename.

B. Both check the common top-level directory and verify that PKG-INFO exists within it.

C. Both call validate_zipfile.

D. Both require ZIP_DEFLATED compression.

Overall Question

T1. Which option best summarizes the function?

A. It determines file validity based only on the extension.

B. It selects validation paths by package format and combines format detection, structure checks, compression-safety checks, and optional scanning.

C. It only checks whether a file can be opened.

D. It only scans for malicious files.