

Profile LOKOM

Ref. A05553



IP20

IP65



- Hardly visible aluminum elements
- Easy maintenance
- Possibility to mount the power supply in the luminous part of the luminaire
- Small bending radius
- Possibility to use current modules with efficiency up to 190lm/W and CRI>90. Available upon request.

APPLICATION

- main and decorative lighting


MOUNTING

- recessed, using a dedicated mounting track

ADDITIONAL INFORMATION

- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

Material	aluminum
Possible fixture IP	20, 65
Possible fixture shapes	linear, polygonal
Profile cross-section	rectangular
Width	30.2 mm
Height	24.5 mm
LED gluing width A	24 mm
Number of LED strips A (8 mm wide)	2
Width of the glow	22 mm
Max power of a single KLUŚ LED strip	24 W/m
Possibility of obtaining a line of light	yes
Possibility of bending	yes
Radius of the light arc	yes
Inward	3000 mm
Outdoor	3000 mm
Building type	Commercial, Entertainment/ Arts, HoReCa object

Color	Length	Ref
■ silver anodized	1000 mm	A05553A_1
	2005 mm	A05553A_2
	3010 mm	A05553A_3
■ black anodized	1000 mm	A05553A07_1
	2005 mm	A05553A07_2
	3010 mm	A05553A07_3
□ white lacquered	3010 mm	A05553L10OD_3
	2005 mm	A05553L10OD_2
	1000 mm	A05553L10OD_1
■ black lacquered	3010 mm	A05553L07OD_3

Standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance ± 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance ± 5 mm)

Profile LOKOM

Ref. A05553

Facility zone	office, lobby / foyer, media rooms / av
The cover is cut to the length of the profile	yes
Can be easily connected into runs	yes
Mounting to drywall	yes
Wire out back of extrusion	yes

LINE OF LIGHT TABLE

LED tape	LIGER-22 satin	LIGER-22 black	HS-22 frosted	G-22R satin	G-22S satin
K-1275-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-0480-24	✓ (1)	X	X	X	X
K-0960-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-1440-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-HD-0480-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-HD-0960-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-HD-1440-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-0360-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-0720-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-1080-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-0500-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-1000-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-HD-0430-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-1500-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-CB-1000-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-HD-0830-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-HD-1260-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
KWP-0360-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
KWP-0720-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
KWP-1080-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
KWP-0500-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
KWP-1000-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
KWP-1500-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
KWP-CB-1000-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
KWP-GHD-0430-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
KWP-GHD-0830-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
KWP-HD-0430-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
KWP-HD-0830-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
KWP-HD-1260-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-2300-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)

K-2400-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-CR-1210-24	✓ (1)	X	X	X	X
K-CR-1220-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-CR-1275-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-CRHD-1820-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-CRHD-1910-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-CR-0480-24	✓ (1)	X	X	X	X
K-CR-0960-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-CR-1440-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-HEHD-0480-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-HEHD-0960-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-HEHD-1440-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-HEHD-1920-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-VHE-0480-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-VHE-0960-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-VHE-1440-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-RGB27T65-1200-24	✓ (1)	X	X	X	X
K-RGBW-1530-24	✓ (1)	X	X	X	X
KWP-GRGB-1530-24	✓ (1)	X	X	X	X
K-RGB-1200-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
KWP-RGB-1200-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-18D30-0960-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
KWP-18D30-0960-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-27T50-1440-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
K-VBT-0720-24	✓ (1)	X	X	X	X
K-SD-1440-24	✓ (1)	✓ (2)	✓ (2)	✓ (1)	✓ (1)
KWP-RGBW-1530-24	✓ (1)	X	X	X	X

Description


✓ - Line of Light for a number (X) of rows - Pixel free imaging

X - Visible Dotting from Diodes


HL - Centered Line of Light - Concentrated in middle

HL (X) - Centered Line of Light for a number (X) of rows - Concentrated in middle

Line of Light Guide



Clean Line of Light (Pixel free imaging)



Centered Line of Light



Visible Dotting from Diodes

Profile LOKOM

Ref. A05553

SAMPLE PROJECTS



SIMILAR PROFILES



Profile KOZEL
A06454



Profile LARKO
A05552



Profile LIPOD
A05554

RELATED ACCESSORIES > COVERS

NAME	KEY FEATURES	MATERIAL	MATERIAL TRANSMITTANCE	COLOR	REF.
Optics DOT-22	NEW 	- constant voltage version		■ black	B20L07-ML30-0900-24
					B20L07-ML40-0900-24
					B34L07-ML30-0900-24
					B34L07-ML40-0900-24
					B48L07-ML30-0900-24
					B48L07-ML40-0900-24
				□ white	B20L10-ML30-0900-24
					B20L10-ML40-0900-24
					B34L10-ML30-0900-24
					B34L10-ML40-0900-24
					B48L10-ML30-0900-24
					B48L10-ML40-0900-24

Profile LOKOM

Ref. A05553

NAME	KEY FEATURES	MATERIAL	MATERIAL TRANSMITTANCE	COLOR	REF.
					B48L10-ML40-0900-24
Cover G-22R		- indoor use - Perfectly diffusing PMMA	20 %	black	B17006B
			71 %	satın	B17006S
			89 %	semi-transparent	B17006T
			94 %	clear	B17006C
Cover G-22S		- indoor use - Perfectly diffusing PMMA	15 %	black	B17013B
			86 %	satın	B17013S
			89 %	semi-transparent	B17013T
Cover HS-22		- For indoor and outdoor applications - UV resistant PC	65 %	frosted	B17011F
			88 %	clear	B17011C
			90.5 %	microprism	B17011M
Cover LIGER-22		- high light quality - For indoor and outdoor applications - Ease of obtaining a line of light - Perfectly diffusing PC	22 %	black	B17032B
			70 %	satın	B17032S
Cover BENCO-22		- For indoor and outdoor applications - UV resistant Silikon	62 %	frosted	B17209F

RELATED ACCESSORIES > END CAPS

NAME	MATERIAL	COLOR	REF.
End cap LOKOM		■ black	C24005C07
		■ gray	C24005C02
		■ silver	C24005L01
		■ black	C28285C07
		■ gray	C28285C02
		□ white	C28285L10

RELATED ACCESSORIES > PROFILE TECHNICZNE

Name	Material	Color	Ref.
Profile TEKUS	aluminum	 silver non anodized	A06638V
Profile TEKUS-ZM	aluminum	 silver non anodized	A01293
Profile TEKNIK-ZM-TK	aluminum	 silver non anodized	A01554

RELATED ACCESSORIES > RELATED LED > WHITE MONO

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape K-0360-24 3.6 W/m, IP20 		20	3.6 W/m	K-27-0360-24 K-30-0360-24 K-35-0360-24 K-40-0360-24 K-50-0360-24
LED tape K-HD-0430-24 4.3 W/m, IP20 		20	4.3 W/m	K-HD27-0430-24 K-HD30-0430-24 K-HD35-0430-24 K-HD40-0430-24 K-HD50-0430-24
LED tape K-0480-24	- universal for basic applications	20	4.8 W/m	K-27-0480-24 K-30-0480-24 K-35-0480-24 K-40-0480-24 K-50-0480-24
LED tape K-HD-0480-24	- high LED density - Ease of obtaining a line of light	20	4.8 W/m	K-HD27-0480-24 K-HD30-0480-24 K-HD35-0480-24 K-HD40-0480-24 K-HD50-0480-24
LED tape K-0500-24 5 W/m, IP20 		20	5 W/m	K-30-0500-24 K-40-0500-24
LED tape K-0720-24 7.2 W/m, IP20 		20	7.2 W/m	K-27-0720-24 K-30-0720-24 K-35-0720-24 K-40-0720-24 K-50-0720-24
LED tape K-HD-0830-24 8.3 W/m, IP20 		20	8.3 W/m	K-HD27-0830-24 K-HD30-0830-24 K-HD35-0830-24 K-HD40-0830-24 K-HD50-0830-24
LED tape K-0960-24	- universal for basic applications	20	9.6 W/m	K-27-0960-24 K-30-0960-24 K-30-0960-24-R30 K-35-0960-24 K-40-0960-24 K-40-0960-24-R30 K-50-0960-24 K-65-0960-24
LED tape K-HD-0960-24	- high LED density - Ease of obtaining a line of light	20	9.6 W/m	K-HD27-0960-24 K-HD30-0960-24 K-HD35-0960-24 K-HD40-0960-24 K-HD50-0960-24
LED tape K-1000-24 10 W/m, IP20 		20	10 W/m	K-30-1000-24 K-40-1000-24
LED tape K-CB-1000-24 10 W/m, IP20 		20	10 W/m	K-CB27-1000-24 K-CB30-1000-24 K-CB40-1000-24 K-CB50-1000-24

Profile LOKOM

Ref. A05553

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape K-1080-24 10.8 W/m, IP20 NEW		20	10.8 W/m	K-27-1080-24 K-30-1080-24 K-35-1080-24 K-40-1080-24 K-50-1080-24
LED tape K-HD-1260-24 12.6 W/m, IP20 NEW		20	12.6 W/m	K-HD27-1260-24 K-HD30-1260-24 K-HD35-1260-24 K-HD40-1260-24 K-HD50-1260-24
LED tape K-1275-24	- universal for basic applications	20	14.4 W/m	K-22-1275-24 K-25-1275-24 K-27-1275-24 K-30-1275-24 K-35-1275-24 K-40-1275-24 K-50-1275-24
LED tape K-1440-24	- universal for basic applications	20	14.4 W/m	K-27-1440-24 K-30-1440-24 K-30-1440-24-R30 K-35-1440-24 K-40-1440-24 K-40-1440-24-R30 K-50-1440-24
LED tape K-HD-1440-24	- high LED density - Ease of obtaining a line of light	20	14.4 W/m	K-HD27-1440-24 K-HD30-1440-24 K-HD35-1440-24 K-HD40-1440-24 K-HD50-1440-24
LED tape K2-1440-24 14.4 W/m, IP20 NEW		20	14.4 W/m	K2-27-1440-24 K2-30-1440-24 K2-35-1440-24 K2-40-1440-24 K2-50-1440-24
LED tape K-1500-24 15 W/m, IP20 NEW		20	15 W/m	K-30-1500-24 K-40-1500-24
LED tape K2-1920-24	- LED double-row strip - quick installation	20	19.2 W/m	K2-27-1920-24 K2-30-1920-24 K2-35-1920-24 K2-40-1920-24 K2-50-1920-24
LED tape K3-2160-24 21.6 W/m, IP20 NEW	- Three-row LED strip - quick installation	20	21.6 W/m	K3-27-2160-24 K3-30-2160-24 K3-35-2160-24 K3-40-2160-24 K3-50-2160-24
LED tape K-2300-24	- high power	20	23 W/m	K-30-2300-24 K-40-2300-24
LED tape K-2400-24	- high power	20	24 W/m	K-27-2400-24 K-30-2400-24 K-35-2400-24 K-40-2400-24 K-50-2400-24
LED tape K3-2880-24	- Three-row LED strip - quick installation	20	28.8 W/m	K3-27-2880-24 K3-30-2880-24 K3-35-2880-24 K3-40-2880-24 K3-50-2880-24
LED tape KWP-0360-24 3.6 W/m, IP65 NEW		65	3.6 W/m	KWP-27-0360-24 KWP-30-0360-24 KWP-35-0360-24 KWP-40-0360-24 KWP-50-0360-24

Profile LOKOM

Ref. A05553

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape KWP-GHD-0430-24 4.3 W/m, IP65 NEW		65	4.3 W/m	KWP-GHD27-0430-24 KWP-GHD30-0430-24 KWP-GHD35-0430-24 KWP-GHD40-0430-24 KWP-GHD50-0430-24
LED tape KWP-HD-0430-24 4.3 W/m, IP65 NEW		65	4.3 W/m	KWP-HD27-0430-24 KWP-HD30-0430-24 KWP-HD35-0430-24 KWP-HD40-0430-24 KWP-HD50-0430-24
LED tape KWP-0480-24	- universal for basic applications	65	4.8 W/m	KWP-27-0480-24 KWP-30-0480-24 KWP-35-0480-24 KWP-40-0480-24 KWP-50-0480-24
LED tape KWP-GHD-0480-24	- high LED density - Ease of obtaining a line of light	65	4.8 W/m	KWP-GHD27-0480-24 KWP-GHD30-0480-24 KWP-GHD35-0480-24 KWP-GHD40-0480-24 KWP-GHD50-0480-24
LED tape KWP-0500-24 5 W/m, IP65 NEW		65	5 W/m	KWP-30-0500-24 KWP-40-0500-24
LED tape KWP-0720-24 7.2 W/m, IP65 NEW		65	7.2 W/m	KWP-27-0720-24 KWP-30-0720-24 KWP-35-0720-24 KWP-40-0720-24 KWP-50-0720-24
LED tape KWP-GHD-0830-24 8.3 W/m, IP65 NEW		65	8.3 W/m	KWP-GHD27-0830-24 KWP-GHD30-0830-24 KWP-GHD35-0830-24 KWP-GHD40-0830-24 KWP-GHD50-0830-24
LED tape KWP-HD-0830-24 8.3 W/m, IP65 NEW		65	8.3 W/m	KWP-HD27-0830-24 KWP-HD30-0830-24 KWP-HD35-0830-24 KWP-HD40-0830-24 KWP-HD50-0830-24
LED tape KWP-0960-24	- universal for basic applications	65	9.6 W/m	KWP-27-0960-24 KWP-30-0960-24 KWP-35-0960-24 KWP-40-0960-24 KWP-50-0960-24 KWP-65-0960-24
LED tape KWP-GHD-0960-24	- high LED density - Ease of obtaining a line of light	65	9.6 W/m	KWP-GHD27-0960-24 KWP-GHD30-0960-24 KWP-GHD35-0960-24 KWP-GHD40-0960-24 KWP-GHD50-0960-24
LED tape KWP-1000-24 10 W/m, IP65 NEW		65	10 W/m	KWP-30-1000-24 KWP-40-1000-24
LED tape KWP-CB-1000-24 10 W/m, IP65 NEW		65	10 W/m	KWP-CB27-1000-24 KWP-CB30-1000-24 KWP-CB40-1000-24 KWP-CB50-1000-24
LED tape KWP-1080-24 10.8 W/m, IP65 NEW		65	10.8 W/m	KWP-27-1080-24 KWP-30-1080-24 KWP-35-1080-24 KWP-40-1080-24 KWP-50-1080-24

Profile LOKOM

Ref. A05553

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape KWP-GHD-1260-24 12.6 W/m, IP65		65	12.6 W/m	KWP-GHD27-1260-24 KWP-GHD30-1260-24 KWP-GHD35-1260-24 KWP-GHD40-1260-24 KWP-GHD50-1260-24
LED tape KWP-HD-1260-24 12.6 W/m, IP65 NEW		65	12.6 W/m	KWP-HD27-1260-24 KWP-HD30-1260-24 KWP-HD35-1260-24 KWP-HD40-1260-24 KWP-HD50-1260-24
LED tape KWP-1440-24	- universal for basic applications	65	14.4 W/m	KWP-27-1440-24 KWP-30-1440-24 KWP-35-1440-24 KWP-40-1440-24 KWP-50-1440-24
LED tape KWP-GHD-1440-24	- high LED density - Ease of obtaining a line of light	65	14.4 W/m	KWP-GHD27-1440-24 KWP-GHD30-1440-24 KWP-GHD35-1440-24 KWP-GHD40-1440-24 KWP-GHD50-1440-24
LED tape KWP-1500-24 15 W/m, IP65 NEW		65	15 W/m	KWP-30-1500-24 KWP-40-1500-24

RELATED ACCESSORIES > RELATED LED > HIGH EFFICACY

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape K-HEHD-0480-24	- CRI over 95 - High Efficacy	20	4.8 W/m	K-HEHD22-0480-24 K-HEHD25-0480-24 K-HEHD27-0480-24 K-HEHD30-0480-24 K-HEHD35-0480-24 K-HEHD40-0480-24 K-HEHD50-0480-24
LED tape K-VHE-0480-24	- universal for basic applications - high efficacy - High Efficacy	20	4.8 W/m	K-VHE27-0480-24 K-VHE30-0480-24 K-VHE35-0480-24 K-VHE40-0480-24 K-VHE50-0480-24
LED tape K-HEHD-0960-24	- CRI over 95 - High Efficacy	20	9.6 W/m	K-HEHD22-0960-24 K-HEHD25-0960-24 K-HEHD27-0960-24 K-HEHD30-0960-24 K-HEHD35-0960-24 K-HEHD40-0960-24 K-HEHD50-0960-24
LED tape K-VHE-0960-24	- universal for basic applications - high efficacy - High Efficacy	20	9.6 W/m	K-VHE27-0960-24 K-VHE30-0960-24 K-VHE35-0960-24 K-VHE40-0960-24 K-VHE50-0960-24
LED tape K-HEHD-1440-24	- CRI over 95 - High Efficacy	20	14.4 W/m	K-HEHD22-1440-24 K-HEHD25-1440-24 K-HEHD27-1440-24 K-HEHD30-1440-24 K-HEHD35-1440-24 K-HEHD40-1440-24 K-HEHD50-1440-24
LED tape K-VHE-1440-24	- universal for basic applications - high efficacy - High Efficacy	20	14.4 W/m	K-VHE27-1440-24 K-VHE30-1440-24 K-VHE35-1440-24 K-VHE40-1440-24 K-VHE50-1440-24

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape K-HEHD-1920-24	- CRI over 95 - High Efficacy	20	19.2 W/m	K-HEHD22-1920-24 K-HEHD25-1920-24 K-HEHD27-1920-24 K-HEHD30-1920-24 K-HEHD35-1920-24 K-HEHD40-1920-24 K-HEHD50-1920-24

RELATED ACCESSORIES > RELATED LED > RGB / RGB-W / RGB-CCT

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape K-RGB-0700-24V	- RGB	20	7 W/m	K-RGB-0700-24V
LED tape K-RGB-1200-24	- RGB	20	12 W/m	K-RGB-1200-24
LED tape K-RGB27T65-1200-24	- RGB+Tunable White	20	12 W/m	K-RGB27T65-1200-24
LED tape KWP-RGB-0700-24	- RGB	65	7 W/m	KWP-RGB-0700-24
LED tape KWP-RGB-1200-24	- RGB	65	12 W/m	KWP-RGB-1200-24
LED tape KWP-GRGB-1530-24 15.3 W/m, IP65 NEW	- RGBW - high LED density	65	15.3 W/m	KWP-GRGB30-1530-24 KWP-GRGB40-1530-24

RELATED ACCESSORIES > RELATED LED > CRI 95+

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape K-CR-0480-24	- universal for basic applications - CRI over 95	20	4.8 W/m	K-CR27-0480-24 K-CR30-0480-24 K-CR35-0480-24 K-CR40-0480-24 K-CR50-0480-24
LED tape K-CR-1210-24	- CRI over 95	20	4.8 W/m	K-CR22-1210-24 K-CR25-1210-24 K-CR27-1210-24 K-CR30-1210-24 K-CR35-1210-24 K-CR40-1210-24 K-CR50-1210-24
LED tape K-CRHD-1910-24	- CRI over 95 - high LED density	20	9.1 W/m	K-CRHD22-1910-24 K-CRHD25-1910-24 K-CRHD27-1910-24 K-CRHD30-1910-24 K-CRHD35-1910-24 K-CRHD40-1910-24 K-CRHD50-1910-24
LED tape K-CR-0960-24	- universal for basic applications - CRI over 95	20	9.6 W/m	K-CR27-0960-24 K-CR30-0960-24 K-CR35-0960-24 K-CR40-0960-24 K-CR50-0960-24
LED tape K-CR-1220-24	- CRI over 95	20	9.6 W/m	K-CR22-1220-24 K-CR25-1220-24 K-CR27-1220-24 K-CR30-1220-24 K-CR35-1220-24 K-CR40-1220-24 K-CR50-1220-24

Profile LOKOM

Ref. A05553

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape K-CR-1275-24	- CRI over 95	20	14.4 W/m	K-CR22-1275-24 K-CR25-1275-24 K-CR27-1275-24 K-CR30-1275-24 K-CR35-1275-24 K-CR40-1275-24 K-CR50-1275-24
LED tape K-CR-1440-24	- universal for basic applications - CRI over 95	20	14.4 W/m	K-CR27-1440-24 K-CR30-1440-24 K-CR35-1440-24 K-CR40-1440-24 K-CR50-1440-24
LED tape K-CRHD-1820-24	- CRI over 95 - high LED density	20	18.25 W/m	K-CRHD22-1820-24 K-CRHD25-1820-24 K-CRHD27-1820-24 K-CRHD30-1820-24 K-CRHD35-1820-24 K-CRHD40-1820-24 K-CRHD50-1820-24
LED tape KWP-CR-0480-24	- universal for basic applications - CRI over 95	65	4.8 W/m	KWP-CR27-0480-24 KWP-CR30-0480-24 KWP-CR35-0480-24 KWP-CR40-0480-24 KWP-CR50-0480-24
LED tape KWP-CR-0960-24	- universal for basic applications - CRI over 95	65	9.6 W/m	KWP-CR27-0960-24 KWP-CR30-0960-24 KWP-CR35-0960-24 KWP-CR40-0960-24 KWP-CR50-0960-24

RELATED ACCESSORIES > RELATED LED > BENDABLE

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape K-VBT-0720-24	- LED tape for bent profiles	20	7.2 W/m	K-VBT27-0720-24 K-VBT30-0720-24 K-VBT35-0720-24 K-VBT40-0720-24 K-VBT50-0720-24
LED tape K-BTRGB40-1510-24		20	15.1 W/m	K-BTRGB40-1510-24

RELATED ACCESSORIES > RELATED LED

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape K-SD-1440-24		20	14.4 W/m	K-SD27-1440-24 K-SD30-1440-24 K-SD35-1440-24 K-SD40-1440-24
LED tape KWP-RGB27T50-1200-24, 2700K, 390 lm/m, 12 W/m, IP65		65	12 W/m	KWP-RGB27T50-1200-24
LED tape KWP-RGBW-1530-24 15.3 W/m, IP65 NEW	- RGBW - high LED density	65	15.3 W/m	KWP-RGB30-1530-24 KWP-RGB40-1530-24

RELATED ACCESSORIES > RELATED LED > ADJUSTABLE WHITE / DIM TO WARM

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape K-18D30-0960-24	- Dim To Warm LED Tape	20	9.6 W/m	K-18D30-0960-24

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape K-27T50-1440-24	- RGB+Tunable White	20	14.4 W/m	K-27T50-1440-24
LED tape KWP-18D30-0960-24		65	9.6 W/m	KWP-18D30-0960-24

RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > LATCHES

Name	Material	Color	Ref.
Latch TEKNIK	PP	 white	C24003C10

RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > PROFILE MASKING COVERS

Name	Key features	Material	Color	Ref.
Masking cover MP-22	- Lightproof	PC	 gray metalized	C28261L01_1
			 gray metalized	C28261L01_0.25
			 white lacquered	C28261L10_1
			 white lacquered	C28261L10_0.25
			 black lacquered	C28261L07_1
			 black lacquered	C28261L07_0.25

RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > OTHER

Name	Key features	Material	Color	Ref.
Gland 9x1,5		Material, Material, multiselect		C42295C07
Gland 11x1,5		rubber		C42296C07
Gland 6,4x1,6		rubber		C24518C07
Gland M10x1	- metal housing - with M10x1 thread	mosiądz niklowany		C28275N00
Hermetic coupler THB.391.A4A, 4 pin	- 4 power terminals - compact dimensions	PA		C42268C10
Hermetic coupler THB.381, 2pin	- 2 power terminals - compact dimensions	PA		C28125C07
Hermetic coupler THB.391.A5A, 5 pin	- 5 power terminals - compact dimensions	PA		C28156C07
Joint connector THB.200.E5E, 5 pin	- 5 power terminals - 3-line branch	Material, Material, multiselect		C28157C07

RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > CONNECTORS

Name	Material	Color	Ref.
------	----------	-------	------

Profile LOKOM

Ref. A05553

Name	Material	Color	Ref.
Connector ZM	stainless steel	 silver	42716
		 silver	42717
		 silver	42720
		 silver	42728
		 black colored	C24797C07
		colorless non colored	C24797N00
		 black colored	C28070C07
		 silver	C28070N00
		 black colored	C28071C07
		 silver	C28071N00
		 black colored	C28072C07
		 silver	C28072N00
		 black colored	C28073C07
		 silver	C28073N00
		 black colored	C28074C07
		 silver	C28074N00
		 black colored	C28075C07
		 silver	C28075N00
		 silver	C28243N00
Connector ZM-NA	stainless steel	 silver	42305
			42339
			42723
			42724
			42725
Connector ZM-Y	stainless steel	 black colored	C28082C07
		 silver	C28082N00
Connector ZM-X	stainless steel	 black colored	C28079C07
		 silver	C28079N00
		 black colored	C28080C07
		 silver	C28080N00
		 black colored	C28081C07
Connector ZM-T	stainless steel	 silver	C28081N00
		 black colored	C28076C07
		 silver	C28076N00
		 black colored	C28077C07
		 silver	C28077N00
Connector ZM-PION	stainless steel	 black colored	C28078C07
		 silver	C28078N00
		 silver	42314
		 silver	42316
		 silver	42320
		 silver	42718
		 silver	42719
		 black colored	C28084C07
		 silver	C28084N00
		 black colored	C28085C07
		 silver	C28085N00
		 black colored	C28086C07
		 silver	C28086N00
		 black colored	C28087C07
		 silver	C28087N00
		 black colored	C28088C07
		 silver	C28088N00
Connector ZM-NA-PION	stainless steel	 silver	42315
			42317
			42321
			42726
			42727

RELATED ACCESSORIES > OTHER RELATED ACCESSORIES > SPRINGS FOR RECESSED MOUNT AND MOUNTING TRACKS

Name	Material	Color	Ref.
Spring KMA	stainless steel	 silver	C24503N00

RELATED ACCESSORIES > ELECTRONICS > SWITCHES

Name	Key features	IP protection rating	Ref.
Proximity switch UNI-11 	- touchless switch - width 11mm	20	E61603
Proximity switch UNI-11P 	- touchless switch - width 11mm - factory pre-soldered wires	20	E61604
Proximity switch UNI-P	- touchless switch - width only 7mm - factory pre-soldered wires	20	E61580
Proximity switch UNI	- touchless switch - width only 7mm	20	E61579