

## MONKEY ISLAND API

Operation	HTTP Method	Parameter	URL
List	GET	N/A	http://localhost:1234/api/cuddly_toys
		N/A	http://localhost:1234/api/cuddly_toys/dogs
		N/A	http://localhost:1234/api/cuddly_toys/monkeys
		N/A	http://localhost:1234/api/weapons
		N/A	http://localhost:1234/ghosts
Read	GET	id	http://localhost:1234/api/cuddly_toys/dogs/{id}
		id	http://localhost:1234/api/cuddly_toys/monkeys/{id}
		id	http://localhost:1234/api/weapons/{id}
Create	POST	JSON	http://localhost:1234/api/cuddly_toys/dogs
		JSON	http://localhost:1234/api/cuddly_toys/monkeys
		JSON	http://localhost:1234/api/weapons
Update	PUT	JSON, id	http://localhost:1234/api/cuddly_toys/dogs/{id}
		JSON, id	http://localhost:1234/api/cuddly_toys/monkeys/{id}
		JSON, id	http://localhost:1234/api/weapons/{id}
Delete	DELETE	id	http://localhost:1234/api/cuddly_toys/dogs/{id}
		id	http://localhost:1234/api/cuddly_toys/monkeys/{id}
		id	http://localhost:1234/api/weapons/{id}

### Examples:

GET /api/cuddly\_toys/dogs      -> retrieves a list of dogs

```
[{
  "id": 1,
  "name" : "Test Dog 1"
  "energy_level": 3
}, {
  "id": 1,
  "name" : "Test Dog 2"
  "energy_level": 5
} ....
]
```

## MONKEY ISLAND API

GET /api/cuddly_toys/monkeys	-> retrieves a list of monkeys
GET /api/weapons	-> retrieves a list of weapons
GET /api/cuddly_toys	-> retrieves a list of cuddly toys (dogs and monkeys combined)
GET /ghosts	-> retrieves random list of ghosts (MAX 10)

---

GET /api/cuddly_toys/dogs/1	-> retrieves a single dog with id 1
GET /api/cuddly_toys/monkeys/1	-> retrieves a single monkey with id 1
GET /api/weapons/1	-> retrieves a single weapon with id 1

---

POST /api/cuddly_toys/dogs	-> creates new dog and assigns ID automatically
----------------------------	---

```
{  
  "name" : "New Dog"  
  "energy_level": 4  
}
```

POST /api/cuddly_toys/monkeys	-> creates new monkey and assigns ID automatically
-------------------------------	--

```
{  
  "name" : "New Monkeys"  
  "energy_level": 4  
}
```

POST /api/weapons	-> creates new weapon and assigns ID automatically
-------------------	--

```
{  
  "name" : "New Weapon"  
  "power_level": 4  
}
```

---

PUT /api/cuddly_toys/dogs/1	-> updates the dog with id 1
-----------------------------	------------------------------

```
{  
  "name" : "Updated Dog"  
  "energy_level": 2  
}
```

## MONKEY ISLAND API

```
}
```

PUT /api/cuddly\_toys/monkeys/1 -> updates the monkey with id 1

```
{  
  "name" : "Updated Monkey"  
  "energy_level": 5  
}
```

PUT /api/weapons/1 -> updates the monkey with id 1

```
{  
  "name" : "Updated Monkey"  
  "power_level": 8  
}
```

---

DELETE /api/cuddly\_toys/dogs/1 -> deletes a single dog with id 1

DELETE /api/cuddly\_toys/monkeys/1 -> deletes a single monkey with id 1

DELETE /api/weapons/1 -> deletes a single weapon with id 1

---