

MONKEY ISLAND API

Operation	HTTP Method	Parameter	URL
List	GET	N/A	http://localhost:1234/api/cuddly_toys
		N/A	http://localhost:1234/api/cuddly_toys/dogs
		N/A	http://localhost:1234/api/cuddly_toys/monkeys
		N/A	http://localhost:1234/api/weapons
Read	GET	id	http://localhost:1234/api/cuddly_toys/dogs/{id}
		id	http://localhost:1234/api/cuddly_toys/monkeys/{id}
		id	http://localhost:1234/api/weapons/{id}
Create	POST	JSON	http://localhost:1234/api/cuddly_toys/dogs
		JSON	http://localhost:1234/api/cuddly_toys/monkeys
		JSON	http://localhost:1234/api/weapons
Update	PUT	JSON, id	http://localhost:1234/api/cuddly_toys/dogs/{id}
		JSON, id	http://localhost:1234/api/cuddly_toys/monkeys/{id}
		JSON, id	http://localhost:1234/api/weapons/{id}
Delete	DELETE	id	http://localhost:1234/api/cuddly_toys/dogs/{id}
		id	http://localhost:1234/api/cuddly_toys/monkeys/{id}
		id	http://localhost:1234/api/weapons/{id}

Examples:

GET /api/cuddly_toys/dogs -> retrieves a list of dogs

```
[{
  "id": 1,
  "name": "Test Dog 1"
  "energy_level": 3
}, {
  "id": 1,
  "name": "Test Dog 2"
  "energy_level": 5
}, ...
]
```

MONKEY ISLAND API

GET /api/cuddly_toys/monkeys -> retrieves a list of monkeys

GET /api/weapons -> retrieves a list of weapons

GET /api/cuddly_toys -> retrieves all the dogs and monkeys in one place

GET /api/cuddly_toys/dogs/1 -> retrieves a single dog with id 1

GET /api/cuddly_toys/monkeys/1 -> retrieves a single monkey with id 1

GET /api/weapons/1 -> retrieves a single weapon with id 1

POST /api/cuddly_toys/dogs -> creates new dog and assigns ID automatically

```
{  
  "name": "New Dog"  
  "energy_level": 4  
}
```

POST /api/cuddly_toys/monkeys -> creates new monkey and assigns ID automatically

```
{  
  "name": "New Monkeys"  
  "energy_level": 4  
}
```

POST /api/weapons -> creates new weapon and assigns ID automatically

```
{  
  "name": "New Weapon"  
  "power_level": 4  
}
```

PUT /api/cuddly_toys/dogs/1 -> updates the dog with id 1

```
{  
  "name": "Updated Dog"  
  "energy_level": 2  
}
```

MONKEY ISLAND API

PUT /api/cuddly_toys/monkeys/1 -> updates the monkey with id 1

```
{  
  "name" : "Updated Monkey"  
  "energy_level": 5  
}
```

PUT /api/weapons/1 -> updates the monkey with id 1

```
{  
  "name" : "Updated Monkey"  
  "power_level": 8  
}
```

DELETE /api/cuddly_toys/dogs/1 -> deletes a single dog with id 1

DELETE /api/cuddly_toys/monkeys/1 -> deletes a single monkey with id 1

DELETE /api/weapons/1 -> deletes a single weapon with id 1
