

H323FrameworkStack

objsys Version 0.5.1 3/3/2005 4:09 PM

Table of Contents

Module Index	
Data Structure Index	V
File Index	
Module Documentation	
Asn1CEventHandler	
C Runtime Common Functions	10
Memory Allocation Macros and Functions	16
Context Management Functions	18
Linked List Utility Functions	21
Error Formatting and Print Functions	26
Call Management	29
Capability Management	36
Channel Management	39
H245 Message Handling	44
H323 Endpoint management functions	55
Q931/H.2250 Message Handling	
RAS Channel and Message handling	
Media plug-in Interface definitions	
Media plugin support functions	77
Socket Layer	
Stack Control Commands	
Rtmem	
Data Structure Documentation	
Asn1NamedCEventHandler	
H245Message	
ooCallData	
ooCommand	
ooEndPoint	
ooH323EpCapability	
ooH323Ports	
ooLogicalChannel	
ooRasMessage	
Q931Message	
File Documentation	
asn1CEvtHndlr.h	
00.h	
ooasn1.h	
ooCalls.h	
ooCapability.h	
oochannels.h.	
ooCommon.h	
ooDateTime.h	
ooh245.h	
ooh323.h	
ooh323ep.h	
ooports.h	
ooq931.h	
ooras.h	
oosndrtp.h.	
ooSocket.h	
ooStackCmds.h.	
ootypes.h	
VVI PVVIII	. 11/

printHandler.h	
rtctype.h	
SList.h	
Index	

H323FrameworkStack Module Index

H323FrameworkStack Modules

Here is a list of all modules:

C Runtime Common Functions	10
Asn1CEventHandler	2
Memory Allocation Macros and Functions	16
Context Management Functions	18
Linked List Utility Functions	21
Error Formatting and Print Functions	26
Rtmem	91
Call Management	29
Capability Management	36
Channel Management	39
H245 Message Handling	44
H323 Endpoint management functions	55
Q931/H.2250 Message Handling.	61
RAS Channel and Message handling	72
Media plug-in Interface definitions	76
Media plugin support functions	77
Socket Layer	82
Stack Control Commands	89

H323FrameworkStack Data Structure Index

H323FrameworkStack Data Structures

Here are the data structures with brief descriptions:

Asn1NamedCEventHandler (This is a basic C based event handler structure, which can to define user-defined event handlers)	
H245Message (Defines the H245 message structure)	
ooCallData (Structure to store all the information related to a particular call)	
ooCommand (Structure for stack commands)	122
ooEndPoint (Structure to store all the config information related to the endpoint created application)	•
${f ooH323EpCapability}$ (Structure to store information related to end point capability)	125
ooH323Ports (This structure is used to define the port ranges to be used by the applicat	ion)126
ooLogicalChannel (Structure to store information of logical channels for call)	127
ooRasMessage (Defines the RAS message structure)	128
O931Message (Defines the O931 message structure)	129

H323FrameworkStack File Index

H323FrameworkStack File List

Here is a list of all documented files with brief descriptions:

asn1CEvtHndlr.h (C event handler structure)	130
memheap.h Error! Bookmark no	ot defined.
oo.h (This file defines the trace functionality)	133
ooasn1.h (Common ASN.1 runtime constants, data structure definitions, and run-time f	
to support BER/DER/PER as defined in the ITU-T standards)	
ooCalls.h (This file contains Call management functions)	
ooCapability.h (This file contains Capability management functions)	151
oochannels.h (This file contains functions to create and use channels)	153
ooCommon.h (Common runtime constant and type definitions)	155
${f ooDateTime.h}$ (Time functions that reconcile differences between Windows and UNIX)	157
ooh245.h (This file contains functions to support H245 negotiations)	158
ooh323.h (This file contains functions to support H.225 messages)	161
ooh323ep.h (This file contains H323 endpoint related functions)	162
oohdr.h Error! Bookmark no	ot defined.
ooper.h Error! Bookmark no	ot defined.
ooports.h (This file contains functions to manage ports used by the stack)	164
ooq931.h (This file contains functions to support call signalling)	167
ooras.h (This file contains functions to support RAS protocol)	170
oosndrtp.h (This file contains functions to read from sound device and playback)	172
ooSocket.h (Common runtime constants, data structure definitions, and run-time functi support the sockets' operations)	
ooStackCmds.h (This file contains stack commands which an user application can use to call, hang call etc)	
ootypes.h (This file contains the definitions of common constants and data structures) .	179
printHandler.h (This is an implementation of a simple print handler)	
rtctype.h	
SList.h (Singly Linked list header file)	

H323FrameworkStack Module Documentation

Asn1CEventHandler

Asn1CEventHandler is a structure type used for user-defined event handlers.

Data Structures

struct Asn1NamedCEventHandler

This is a basic C based event handler structure, which can be used to define user-defined event handlers.

Typedefs

• typedef void(* rtStartElement)(const char *name, int index)

This is a function pointer for a callback function which is invoked from within a decode function when an element of a SEQUENCE, SET, SEQUENCE OF, SET OF, or CHOICE construct is parsed.

• typedef void(* **rtEndElement**)(const char *name, int index)

This is a function pointer for a callback function which is invoked from within a decode function when parsing is complete on an element of a SEQUENCE, SET, SEQUENCE OF, SET OF, or CHOICE construct.

• typedef void(* **rtBoolValue**)(ASN1BOOL value)

This is a function pointer for a callback function which is invoked from within a decode function when a value of the BOOLEAN ASN.1 type is parsed.

typedef void(* rtIntValue)(ASN1INT value)

This is a function pointer for a callback function which is invoked from within a decode function when a value of the INTERGER ASN.1 type is parsed.

• typedef void(* **rtUIntValue**)(ASN1UINT value)

This is a function pointer for a callback function which is invoked from within a decode function when a value of the INTEGER ASN.1 type is parsed.

typedef void(* rtBitStrValue)(ASN1UINT numbits, const ASN1OCTET *data)

This is a function pointer for a callback function which is invoked from within a decode function when a value of the BIT STRING ASN.1 type is parsed.

• typedef void(* rtOctStrValue)(ASN1UINT numocts, const ASN1OCTET *data)

This is a function pointer for a callback function which is invoked from within a decode function when a value of one of the OCTET STRING ASN.1 type is parsed.

typedef void(* rtCharStrValue)(const char *value)

This is a function pointer for a callback function which is invoked from within a decode function when a value of one of the 8-bit ASN.1 character string types is parsed.

• typedef void(* rtCharStrValue16Bit)(ASN1UINT nchars, ASN116BITCHAR *data)

This is a function pointer for a callback function which is invoked from within a decode function when a value of one of the 16-bit ASN.1 character string types is parsed.

• typedef void(* rtCharStrValue32Bit)(ASN1UINT nchars, ASN132BITCHAR *data)

This is a function pointer for a callback function which is invoked from within a decode function when a value of one of the 32-bit ASN.1 characer string types is parsed.

• typedef void(* rtNullValue)()

This is a function pointer for a callback function which is invoked from within a decode function when a value of the NULL ASN.1 type is parsed.

• typedef void(* rtOidValue)(ASN1UINT numSubIds, ASN1UINT *pSubIds)

This is a function pointer for a callback function which is invoked from within a decode function whn a value the OBJECT IDENTIFIER ASN.1 type is parsed.

• typedef void(* **rtRealValue**)(double value)

This is a function pointer for a callback function which is invoked from within a decode function when a value the REAL ASN.1 type is parsed.

• typedef void(* **rtEnumValue**)(ASN1UINT value)

This is a function pointer for a callback function which is invoked from within a decode function when a value of the ENUMERATED ASN.1 type is parsed.

typedef void(* rtOpenTypeValue)(ASN1UINT numocts, const ASN1OCTET *data)
 This is a function pointer for a callback function which is invoked from within a decode function when an ASN.1 open type is parsed.

• typedef Asn1NamedCEventHandler Asn1NamedCEventHandler

This is a basic C based event handler structure, which can be used to define user-defined event handlers.

Functions

- EXTERN void **rtAddEventHandler** (OOCTXT *pCtxt, **Asn1NamedCEventHandler** *pHandler) *This function is called to add a new event handler to the context event handler list.*
- EXTERN void rtRemoveEventHandler (OOCTXT *pCtxt, Asn1NamedCEventHandler *pHandler)

This function is called to remove an event handler from the context event handler list.

• EXTERN void **rtInvokeStartElement** (OOCTXT *pCtxt, const char *name, int index)

The following functions are invoked from within the generated code to call the various user-defined event handler methods ...

- EXTERN void **rtInvokeEndElement** (OOCTXT *pCtxt, const char *name, int index)
- EXTERN void **rtInvokeBoolValue** (OOCTXT *pCtxt, ASN1BOOL value)
- EXTERN void **rtInvokeIntValue** (OOCTXT *pCtxt, ASN1INT value)
- EXTERN void **rtInvokeUIntValue** (OOCTXT *pCtxt, ASN1UINT value)
- EXTERN void rtInvokeBitStrValue (OOCTXT *pCtxt, ASN1UINT numbits, const ASN1OCTET *data)
- EXTERN void rtInvokeOctStrValue (OOCTXT *pCtxt, ASN1UINT numocts, const ASN1OCTET *data)
- EXTERN void **rtInvokeCharStrValue** (OOCTXT *pCtxt, const char *value)
- EXTERN void **rtInvokeCharStr16BitValue** (OOCTXT *pCtxt, ASN1UINT nchars, ASN116BITCHAR *data)
- EXTERN void **rtInvokeCharStr32BitValue** (OOCTXT *pCtxt, ASN1UINT nchars, ASN132BITCHAR *data)
- EXTERN void **rtInvokeNullValue** (OOCTXT *pCtxt)
- EXTERN void rtInvokeOidValue (OOCTXT *pCtxt, ASN1UINT numSubIds, ASN1UINT *pSubIds)
- EXTERN void **rtInvokeRealValue** (OOCTXT *pCtxt, double value)
- EXTERN void **rtInvokeEnumValue** (OOCTXT *pCtxt, ASN1UINT value)
- EXTERN void **rtInvokeOpenTypeValue** (OOCTXT *pCtxt, ASN1UINT numocts, const ASN1OCTET *data)

Detailed Description

Asn1CEventHandler is a structure type used for user-defined event handlers.

Typedef Documentation

typedef void(* rtBitStrValue)(ASN1UINT numbits, const ASN1OCTET* data)

This is a function pointer for a callback function which is invoked from within a decode function when a value of the BIT STRING ASN.1 type is parsed.

Parameters:

numbits - Number of bits in the parsed value. *data* - Pointer to a byte array that contains the bit string data.

Returns:

- none

Definition at line 126 of file asn1CEvtHndlr.h.

typedef void(* rtBoolValue)(ASN1BOOL value)

This is a function pointer for a callback function which is invoked from within a decode function when a value of the BOOLEAN ASN.1 type is parsed.

Parameters:

value Parsed value.

Returns:

- none

Definition at line 94 of file asn1CEvtHndlr.h.

typedef void(* rtCharStrValue)(const char* value)

This is a function pointer for a callback function which is invoked from within a decode function when a value of one of the 8-bit ASN.1 character string types is parsed.

Parameters:

value Null terminated character string value.

Returns:

- none

Definition at line 148 of file asn1CEvtHndlr.h.

typedef void(* rtCharStrValue16Bit)(ASN1UINT nchars, ASN116BITCHAR* data)

This is a function pointer for a callback function which is invoked from within a decode function when a value of one of the 16-bit ASN.1 character string types is parsed.

This is used for the ASN.1 BmpString type.

Parameters:

nchars Number of characters in the parsed value.

data Pointer to an array containing 16-bit values. These are represented using unsigned short integer values.

Returns:

- none

Definition at line 163 of file asn1CEvtHndlr.h.

typedef void(* rtCharStrValue32Bit)(ASN1UINT nchars, ASN132BITCHAR* data)

This is a function pointer for a callback function which is invoked from within a decode function when a value of one of the 32-bit ASN.1 characer string types is parsed.

This is used for the ASN.1 UniversalString type.

Parameters:

nchars Number of characters in the parsed value. *data* Pointer to an array containing 32-bit values. Each 32-bit integer value is a universal character.

Returns:

- none

Definition at line 177 of file asn1CEvtHndlr.h.

typedef void(* rtEndElement)(const char* name, int index)

This is a function pointer for a callback function which is invoked from within a decode function when parsing is complete on an element of a SEQUENCE, SET, SEQUENCE OF, SET OF, or CHOICE construct.

Parameters:

name For SEQUENCE, SET, or CHOICE, this is the name of the element as defined in the ASN.1 defination. For SEQUENCE OF or SET OF, this is set to the name "element". index For SEQUENCE, SET, or CHOICE, this is not used and is set to the value -1. For SEQUENCE OF or SET OF, this contains the zero-based index of the element in the conceptual array associated with the construct.

Returns:

- none

Definition at line 84 of file asn1CEvtHndlr.h.

typedef void(* rtEnumValue)(ASN1UINT value)

This is a function pointer for a callback function which is invoked from within a decode function when a value of the ENUMERATED ASN.1 type is parsed.

Parameters:

value - Parsed enumerated value

Returns:

- none

Definition at line 216 of file asn1CEvtHndlr.h.

typedef void(* rtIntValue)(ASN1INT value)

This is a function pointer for a callback function which is invoked from within a decode function when a value of the INTERGER ASN.1 type is parsed.

Parameters:

value Parsed value.

Returns:

- none

Definition at line 103 of file asn1CEvtHndlr.h.

typedef void(* rtNullValue)()

This is a function pointer for a callback function which is invoked from within a decode function when a value of the NULL ASN.1 type is parsed.

Parameters:

- none

Returns:

- none

Definition at line 186 of file asn1CEvtHndlr.h.

typedef void(* rtOctStrValue)(ASN1UINT numocts, const ASN1OCTET* data)

This is a function pointer for a callback function which is invoked from within a decode function when a value of one of the OCTET STRING ASN.1 type is parsed.

Parameters:

numocts Number of octets in the parsed value. *data* Pointer to byte array containing the octet string data.

Returns:

- none

Definition at line 138 of file asn1CEvtHndlr.h.

typedef void(* rtOidValue)(ASN1UINT numSubIds, ASN1UINT* pSubIds)

This is a function pointer for a callback function which is invoked from within a decode function whn a value the OBJECT IDENTIFIER ASN.1 type is parsed.

Parameters:

numSubIds Number of subidentifiers in the object identifier. *pSubIds* Pointer to array containing the subidentifier values.

Returns:

-none

Definition at line 197 of file asn1CEvtHndlr.h.

typedef void(* rtOpenTypeValue)(ASN1UINT numocts, const ASN1OCTET* data)

This is a function pointer for a callback function which is invoked from within a decode function when an ASN.1 open type is parsed.

Parameters:

numocts Number of octets in the parsed value. *data* Pointer to byet array contain in tencoded ASN.1 value.

Returns:

- none

Definition at line 227 of file asn1CEvtHndlr.h.

typedef void(* rtRealValue)(double value)

This is a function pointer for a callback function which is invoked from within a decode function when a value the REAL ASN.1 type is parsed.

Parameters:

value Parsed value.

Returns:

- none

Definition at line 206 of file asn1CEvtHndlr.h.

typedef void(* rtStartElement)(const char* name, int index)

This is a function pointer for a callback function which is invoked from within a decode function when an element of a SEQUENCE, SET, SEQUENCE OF, SET OF, or CHOICE construct is parsed.

Parameters:

name For SEQUENCE, SET, or CHOICE, this is the name of the element as defined in the ASN.1 defination. For SEQUENCE OF or SET OF, this is set to the name "element". index For SEQUENCE, SET, or CHOICE, this is not used and is set to the value -1. For SEQUENCE OF or SET OF, this contains the zero-based index of the element in the conceptual array associated with the construct.

Returns:

- none

Definition at line 65 of file asn1CEvtHndlr.h.

typedef void(* rtUIntValue)(ASN1UINT value)

This is a function pointer for a callback function which is invoked from within a decode function when a value of the INTEGER ASN.1 type is parsed.

In this case, constraints on the integer value forced the use of unsigned integer C type to represent the value.

Parameters:

value Parsed value.

Returns:

- none

Definition at line 114 of file asn1CEvtHndlr.h.

Function Documentation

EXTERN void rtAddEventHandler (OOCTXT * pCtxt, Asn1NamedCEventHandler * pHandler)

This function is called to add a new event handler to the context event handler list.

Parameters:

pCtxt Context to which event handler has to be added. *pHandler* Pointer to the event handler structure.

Returns:

none

EXTERN void rtRemoveEventHandler (OOCTXT * pCtxt, Asn1NamedCEventHandler * pHandler)

This function is called to remove an event handler from the context event handler list.

Note that it does not delete the event handler object.

Parameters:

pCtxt Context from which event handler has to be removed. *pHandler* Pointer to event handler structure.

Returns:

none

C Runtime Common Functions

Modules

• groupAsn1CEventHandler

Asn1CEventHandler is a structure type used for user-defined event handlers.

•

- groupMemory Allocation Macros and Functions
- groupContext Management Functions
- groupLinked List Utility Functions

Linked list and stack utility functions are used to maintain linked lists and stacks used within the ASN.1 run-time library functions.

•

Data Structures

- struct ASN1OBJID
- struct ASN1OctStr
- struct ASN1DynOctStr
- struct **ASN1DynBitStr**
- struct ASN1SeqOf
- struct ASN1SeqOfOctStr
- struct ASN1OpenType
- struct Asn116BitCharString
- struct Asn132BitCharString
- struct Asn1CharArray
- struct Asn1CharSet
- struct Asn116BitCharSet
- struct _SListNode
- struct _SList
- struct _**DListNode**
- struct _**DList**
- struct _Asn1SizeCnst
- struct ASN1BUFFER
- struct ASN1BUFSAVE
- struct ASN1ErrLocn
- struct ASN1ErrInfo
- struct OOCTXT

Defines

```
#define TV_UNIV 0
                      /* universal
#define TV_APPL 1
                      /* application-wide
#define TV CTXT 2
                       /* context-specific
#define TV_PRIV 3
                      /* private-use
#define TV_PRIM 0
                      /* primitive
#define TV CONS 1
                       /* constructor
#define TM UNIV 0x00000000 /* universal class
#define TM_APPL 0x40000000 /* application-wide class */
#define TM_CTXT 0x80000000 /* context-specific class */
#define TM PRIV 0xC0000000 /* private-use class
#define TM_PRIM 0x00000000 /* primitive form
                                                   */
#define TM CONS 0x20000000 /* constructor form
#define TM_IDCODE 0x1FFFFFFF /* ID code mask
#define ASN K BADTAG 0xFFFFFFFF /* invalid tag code
#define ASN_K_NOTAG 0xFFFFFFF /* no tag input parameter */
#define TM_CLASS 0xC0 /* class mask
#define TM_FORM 0x20 /* form mask
#define TM_CLASS_FORM 0xE0 /* class/form mask
#define TM B IDCODE 0x1F /* id code mask (byte)
                          /* minimum message length
#define MINMSGLEN 8
#define ASN OK 0
                     /* normal completion status
                            /* message fragment detected
#define ASN_OK_FRAG 2
#define ASN_E_BUFOVFLW -1
                                 /* encode buffer overflow
#define ASN E ENDOFBUF -2
                                 /* unexpected end of buffer on decode */
#define ASN E IDNOTFOU -3
                                /* identifer not found
                                                             */
#define ASN_E_INVOBJID -4
                               /* invalid object identifier
#define ASN_E_INVLEN -5
                             /* invalid field length
                               /* enumerated value not in defined set */
#define ASN E INVENUM -6
                               /* duplicate element in set
#define ASN E SETDUPL -7
#define ASN_E_SETMISRQ -8
                                /* missing required element in set
#define ASN E NOTINSET -9
                                /* element not part of set
#define ASN_E_SEQOVFLW -10
                                 /* sequence of field overflow
#define ASN_E_INVOPT -11
                              /* invalid option encountered in choice */
#define ASN E NOMEM -12
                              /* no dynamic memory available
#define ASN_E_INVHEXS -14
                               /* invalid hex string
                                                           */
#define ASN_E_INVBINS -15
                              /* invalid binary string
#define ASN_E_INVREAL -16
                               /* invalid real value
#define ASN E STROVFLW -17
                                  /* octet or bit string field overflow
#define ASN E BADVALUE -18
                                 /* invalid value specification
                                 /* no def found for ref'd defined value */
#define ASN_E_UNDEFVAL -19
#define ASN_E_UNDEFTYP -20
                                 /* no def found for ref'd defined type */
#define ASN E BADTAG -21
                               /* invalid tag value
#define ASN_E_TOODEEP -22
                                /* nesting level is too deep
#define ASN_E_CONSVIO -23
                               /* value constraint violation
                                                              */
#define ASN_E_RANGERR -24
                                /* invalid range (lower > upper)
#define ASN E ENDOFFILE -25
                                  /* end of file on file decode
                                 invalid UTF-8 encoding
#define ASN E INVUTF8 -26
                                  /* Concurrent list modification
#define ASN_E_CONCMODF -27
                                /* Illegal state error
#define ASN E ILLSTATE -28
#define ASN_E_OUTOFBND -29
                                  /* out of bounds (of array, etc)
#define ASN_E_INVPARAM -30
                                 /* invalid parameter
```

```
#define ASN E INVFORMAT -31
                                  /* invalid time string format
#define ASN E NOTINIT -32
                              /* not initialized
                              /* value is too big for given data type */
#define ASN E TOOBIG -33
                               /* invalid character (not in char set) */
#define ASN E INVCHAR -34
#define ASN E XMLSTATE -35
                                 /* XML state error
                                                             */
                                                              */
                                 /* XML parse error
#define ASN E XMLPARSE -36
#define ASN_E_SEQORDER -37
                                 /* SEQUENCE elements not in order
#define ASN_E_INVINDEX -38
                                /* invalid index for TC id
                                                               */
#define ASN_E_INVTCVAL -39
                                 /* invalid value for TC field
#define ASN_E_FILNOTFOU -40
                                 /* file not found
                                                               */
#define ASN E FILEREAD -41
                                /* error occurred reading file
#define ASN E FILEWRITE -42
                                 /* error occurred writing file
#define ASN_E_INVBASE64 -43
                                 /* invalid base64 encoding
                                                                */
#define ASN_E_INVSOCKET -44
                                  /* invalid socket operation
#define ASN E XMLLIBNFOU -45
                                    /* XML library is not found
                                                                */
#define ASN_E_XMLLIBINV -46 /* XML library is invalid
#define ASN_E_NOTSUPP -99 /* non-supported ASN construct
                                                                 */
#define ASN_K_INDEFLEN -9999 /* indefinite length message indicator */
#define ASN ID EOC 0
                          /* end of contents
                                                 */
#define ASN_ID_BOOL 1
                            /* boolean
#define ASN_ID_INT 2
                         /* integer
#define ASN ID BITSTR 3
                             /* bit string
#define ASN_ID_OCTSTR 4
                              /* byte (octet) string
#define ASN ID NULL 5
#define ASN ID OBJID 6
                            /* object ID
#define ASN_ID_OBJDSC 7
                              /* object descriptor
#define ASN_ID_EXTERN 8
                              /* external type
#define ASN_ID_REAL 9
                           /* real
#define ASN ID ENUM 10
                            /* enumerated value
#define ASN ID EPDV 11
                            /* EmbeddedPDV type
                                                       */
#define ASN_ID_RELOID 13
                                                      */
                              /* relative object ID
#define ASN_ID_SEQ 16
                          /* sequence, sequence of
#define ASN ID SET 17
                          /* set, set of
#define ASN_SEQ_TAG 0x30 /* SEQUENCE universal tag byte */
#define ASN_SET_TAG 0x31 /* SET universal tag byte
#define ASN_ID_NumericString 18
#define ASN ID PrintableString 19
#define ASN ID TeletexString 20
#define ASN_ID_T61String ASN_ID_TeletexString
#define ASN_ID_VideotexString 21
#define ASN_ID_IA5String 22
#define ASN_ID_UTCTime 23
#define ASN ID GeneralTime 24
#define ASN_ID_GraphicString 25
#define ASN_ID_VisibleString 26
#define ASN ID GeneralString 27
#define ASN ID UniversalString 28
#define ASN_ID_BMPString 30
#define XM_SEEK 0x01 /* seek match until found or end-of-buf */
#define XM_ADVANCE 0x02 /* advance pointer to contents on match */
#define XM DYNAMIC 0x04 /* alloc dyn mem for decoded variable */
#define XM_SKIP 0x08 /* skip to next field after parsing tag */
```

#define ASN K MAXDEPTH 32 /* maximum nesting depth for messages */

- #define ASN_K_MAXSUBIDS 128 /* maximum sub-id's in an object ID */
- #define ASN_K_MAXENUM 100 /* maximum enum values in an enum type */
- #define **ASN_K_MAXERRP** 5 /* maximum error parameters */
- #define **ASN_K_MAXERRSTK** 8 /* maximum levels on error ctxt stack */
- #define **ASN K ENCBUFSIZ** 16*1024 /* dynamic encode buffer extent size */
- #define **ASN_K_MEMBUFSEG** 1024 /* memory buffer extent size
- #define **NUM_ABITS** 4
- #define **NUM_UBITS** 4
- #define **NUM_CANSET** " 0123456789"
- #define **PRN ABITS** 8
- #define PRN UBITS 7
- #define **PRN_CANSET** " '()+,- ./0123456789:=?ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz"
- #define **VIS_ABITS** 8
- #define **VIS UBITS** 7
- #define VIS CANSET
- #define **T61_ABITS** 8
- #define **T61_UBITS** 7
- #define **T61_CANSET**
- #define **IA5_ABITS** 8
- #define **IA5_UBITS** 7
- #define IA5 CANSET
- #define IA5_RANGE1_LOWER 0
- #define IA5_RANGE2_LOWER 0x5f
- #define **GEN ABITS** 8
- #define **GEN UBITS** 7
- #define **GEN_CANSET**
- #define **BMP_ABITS** 16
- #define **BMP_UBITS** 16
- #define **BMP_FIRST** 0
- #define **BMP_LAST** 0xffff
- #define UCS ABITS 32
- #define **UCS_UBITS** 32
- #define **UCS FIRST** 0
- #define UCS_LAST 0xfffffffful
- #define **ASN1TAG_LSHIFT** 24
- #define **ASN1UINT_MAX** 4294967295U
- #define **ASN1INT_MAX** ((ASN1INT)2147483647L)
- #define **ASN1INT_MIN** ((ASN1INT)(-ASN1INT_MAX-1))
- #define **ASN1INT64** long
- #define **XM_K_MEMBLKSIZ** (4*1024)
- #define **ASN1DYNCTXT** 0x8000
- #define ASN1INDEFLEN 0x4000
- #define **ASN1TRACE** 0x2000
- #define **ASN1LASTEOC** 0x1000
- #define **ASN1FASTCOPY** 0x0800 /* turns on the "fast copy" mode */
- #define ASN1CONSTAG 0x0400 /* form of last parsed tag
- #define **ASN1CANXER** 0x0200 /* canonical XER
- #define **ASN1SAVEBUF** 0x0100 /* do not free dynamic encode buffer */
- #define **ASN1OPENTYPE** 0x0080 /* item is an open type field */
- #define **ASN1MAX**(a, b) (((a)>(b))?(a):(b))
- #define **ASN1MIN**(a, b) (((a)<(b))?(a):(b))
- #define ASN1BUFCUR(cp) (cp)->buffer.data[(cp)->buffer.byteIndex]

- #define **ASN1BUFPTR**(cp) &(cp)->buffer.data[(cp)->buffer.byteIndex]
- #define **ASN1CRTMALLOC0**(nbytes) malloc(nbytes)
- #define **ASN1CRTFREE0**(ptr) free(ptr)
- #define **ASN1CRTMALLOC** memHeapAlloc
- #define **ASN1CRTFREE** ASN1MEMFREEPTR
- #define **DE INCRBITIDX**(pctxt)
- #define **DE_BIT**(pctxt, pvalue)
- #define **encodeIA5String**(pctxt, value, permCharSet) encodeConstrainedStringEx (pctxt, value, permCharSet, 8, 7, 7)
- #define **encodeGeneralizedTime** encodeIA5String
- #define **decodeIA5String**(pctxt, pvalue, permCharSet) decodeConstrainedStringEx (pctxt, pvalue, permCharSet, 8, 7, 7)
- #define **decodeGeneralizedTime** decodeIA5String

Typedefs

- typedef char **ASN1CHAR**
- typedef unsigned char **ASN1OCTET**
- typedef ASN1OCTET **ASN1BOOL**
- typedef signed char **ASN1INT8**
- typedef unsigned char ASN1UINT8
- typedef int ASN1INT
- typedef unsigned int **ASN1UINT**
- typedef ASN1INT **ASN1ENUM**
- typedef double ASN1REAL
- typedef short ASN1SINT
- typedef unsigned short **ASN1USINT**
- typedef ASN1UINT ASN1TAG
- typedef ASN1USINT **ASN116BITCHAR**
- typedef ASN1UINT **ASN132BITCHAR**
- typedef void * ASN1ANY
- typedef const char * **ASN1GeneralizedTime**
- typedef const char * ASN1GeneralString
- typedef const char * ASN1GraphicString
- typedef const char * ASN1IA5String
- typedef const char * ASN1ISO646String
- typedef const char * ASN1NumericString
- typedef const char * ASN1ObjectDescriptor
- typedef const char * ASN1PrintableString
- typedef const char * ASN1TeletexString
- typedef const char * ASN1T61String
- typedef const char * ASN1UTCTime
- typedef const char * **ASN1UTF8String**
- typedef const char * ASN1VideotexString
- typedef const char * ASN1VisibleString
- typedef Asn116BitCharString **ASN1BMPString**
- typedef Asn132BitCharString ASN1UniversalString
- typedef SListNode SListNode
- typedef _SList **SList**
- typedef DListNode DListNode
- typedef _DList **DList**
- typedef _Asn1SizeCnst Asn1SizeCnst

• typedef OOCTXT OOCTXT

Define Documentation

#define DE_BIT(pctxt, pvalue)

Value:

```
((DE_INCRBITIDX (pctxt) != ASN_OK) ? ASN_E_ENDOFBUF : ((pvalue) ? \
((*(pvalue) = (((pctxt)->buffer.data[(pctxt)->buffer.byteIndex]) & \
(1 << (pctxt)->buffer.bitOffset)) != 0), ASN_OK) : ASN_OK ))
```

Definition at line 603 of file ooasn1.h.

#define DE INCRBITIDX(pctxt)

Value:

```
((--(pctxt)->buffer.bitOffset < 0) ? \
((++(pctxt)->buffer.byteIndex >= (pctxt)->buffer.size) ? ASN_E_ENDOFBUF : \
((pctxt)->buffer.bitOffset = 7, ASN_OK)) : ASN_OK)
```

Definition at line 597 of file ooasn1.h.

#define GEN CANSET

Value:

Definition at line 212 of file ooasn1.h.

#define IA5 CANSET

Value:

```
"\000\001\002\003\004\005\006\007\010\011\012\013\014\015\016\017"\
"\020\021\022\023\024\025\026\027\030\031\032\033\034\035\036\037"\
"!\"#$%&'()*+,-./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\\]"\
"^_`abcdefghijklmnopqrstuvwxyz{|}~"
```

Definition at line 201 of file ooasn1.h.

#define T61 CANSET

Value:

```
"!\"%&'()*+,-./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[]"\
```

```
"_abcdefghijklmnopqrstuvwxyz"
```

Definition at line 195 of file ooasn1.h.

#define VIS_CANSET

Value:

```
" !\"#$%&'()*+,-./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\\]"\
"^_`abcdefghijklmnopqrstuvwxyz{|}~"
```

Definition at line 189 of file ooasn1.h.

Memory Allocation Macros and Functions

Defines

- #define **ALLOC_ASN1ARRAY**(pctxt, pseqof, type) *Allocate a dynamic array*.
- #define **ALLOC_ASN1ELEM**(pctxt, type) (type*) memHeapAllocZ (&(pctxt)->pTypeMemHeap, sizeof(type))

Allocate and zero an ASN.1 element.

- #define **ALLOC ASN1ELEMDNODE**(pctxt, type)
- #define **ASN1MALLOC**(pctxt, nbytes) memHeapAlloc(&(pctxt)->pTypeMemHeap, nbytes) *Allocate memory*.
- #define **ASN1MEMFREE**(pctxt) memHeapFreeAll(&(pctxt)->pTypeMemHeap) *Free memory associated with a context.*
- #define **ASN1MEMFREEPTR**(pctxt, pmem) memHeapFreePtr(&(pctxt)->pTypeMemHeap, (void*)pmem)

Free memory pointer.

Detailed Description

Memory allocation functions and macros handle memory management for the ASN1C run-time. Special algorithms are used for allocation and deallocation of memory to improve the run-time performance.

Define Documentation

#define ALLOC ASN1ARRAY(pctxt, pseqof, type)

Value:

```
do {\
  if (sizeof(type)*(pseqof)->n < (pseqof)->n) return ASN_E_NOMEM; \
  if (((pseqof)->elem = (type*) memHeapAlloc \
  (&(pctxt)->pTypeMemHeap, sizeof(type)*(pseqof)->n)) == 0) return ASN_E_NOMEM; \
} while (0)
```

Allocate a dynamic array. This macro allocates a dynamic array of records of the given type. This version of the macro will return the ASN_E_NOMEM error status if the memory request cannot be fulfilled.

Parameters:

```
pctxt - Pointer to a context block pseqof - Pointer to a generated SEQUENCE OF array structure. The n member variable must be set to the number of records to allocate. type - Data type of an array record
```

Definition at line 497 of file ooasn1.h.

#define ALLOC_ASN1ELEM(pctxt, type) (type*) memHeapAllocZ (&(pctxt)->pTypeMemHeap, sizeof(type))

Allocate and zero an ASN.1 element.

This macro allocates and zeros a single element of the given type.

Parameters:

```
pctxt - Pointer to a context blocktype - Data type of record to allocate
```

Definition at line 510 of file ooasn1.h.

#define ALLOC_ASN1ELEMDNODE(pctxt, type)

Value:

```
(type*) (((char*)memHeapAllocZ (&(pctxt)->pTypeMemHeap, sizeof(type) + \
sizeof(DListNode))) + sizeof(DListNode))
```

Definition at line 513 of file ooasn1.h.

#define ASN1MALLOC(pctxt, nbytes) memHeapAlloc(&(pctxt)->pTypeMemHeap, nbytes)

Allocate memory.

This macro allocates the given number of bytes. It is similar to the C malloc run-time function.

Parameters:

pctxt - Pointer to a context blocknbytes - Number of bytes of memory to allocate

Returns:

- Void pointer to allocated memory or NULL if insufficient memory was available to fulfill the request.

Definition at line 527 of file ooasn1.h.

#define ASN1MEMFREE(pctxt) memHeapFreeAll(&(pctxt)->pTypeMemHeap)

Free memory associated with a context.

This macro frees all memory held within a context. This is all memory allocated using the ASN1MALLOC (and similar macros) and the mem memory allocation functions using the given context variable.

Parameters:

pctxt - Pointer to a context block

Definition at line 538 of file ooasn1.h.

#define ASN1MEMFREEPTR(pctxt, pmem) memHeapFreePtr(&(pctxt)->pTypeMemHeap, (void*)pmem)

Free memory pointer.

This macro frees memory at the given pointer. The memory must have been allocated using the ASN1MALLOC (or similar) macros or the mem memory allocation functions. This macro is similar to the C free function.

Parameters:

pctxt - Pointer to a context block

pmem - Pointer to memory block to free. This must have been allocated using the ASN1MALLOC macro or the memHeapAlloc function.

Definition at line 552 of file ooasn1.h.

Context Management Functions

Defines

• #define **ZEROCONTEXT**(pctxt) memset(pctxt,0,sizeof(OOCTXT))

Functions

- EXTERN int **initContextBuffer** (OOCTXT *pctxt, const ASN1OCTET *bufaddr, ASN1UINT bufsiz) *This function assigns a buffer to a context block.*
- EXTERN int **initContext** (OOCTXT *pctxt)

This function initializes a context block.

• EXTERN void **freeContext** (OOCTXT *pctxt)

This function frees all dynamic memory associated with a context.

EXTERN OOCTXT * newContext (void)

This function allocates a new OOCTXT block and initializes it.

- EXTERN void **copyContext** (OOCTXT *pdest, OOCTXT *psrc)
- EXTERN int **initSubContext** (OOCTXT *pctxt, OOCTXT *psrc)
- EXTERN void **setCtxtFlag** (OOCTXT *pctxt, ASN1USINT mask)
- EXTERN void **clearCtxtFlag** (OOCTXT *pctxt, ASN1USINT mask)
- EXTERN int **setPERBuffer** (OOCTXT *pctxt, ASN1OCTET *bufaddr, ASN1UINT bufsiz, ASN1BOOL aligned)
- EXTERN int setPERBufferUsingCtxt (OOCTXT *pTarget, OOCTXT *pSource)

Detailed Description

Context initialization functions handle the allocation, initialization, and destruction of ASN.1 context variables (variables of type OOCTXT). These variables hold all of the working data used during the process of encoding or decoding a message. The context provides thread safe operation by isolating what would otherwise be global variables within this structure. The context variable is passed from function to function as a message is encoded or decoded and maintains state information on the encoding or decoding process.

Function Documentation

EXTERN void freeContext (OOCTXT * pctxt)

This function frees all dynamic memory associated with a context.

This includes all memory inside the block (in particular, the list of memory blocks used by the mem functions).

Parameters:

pctxt A pointer to a context structure.

EXTERN int initContext (OOCTXT * pctxt)

This function initializes a context block.

It makes sure that if the block was not previously initialized, that all key working parameters are set to thier correct initial state values (i.e. declared within a function as a normal working variable), it is required that they invoke this function before using it.

Parameters:

pctxt The pointer to the context structure variable to be initialized.

Returns:

Completion status of operation:

- 0 (ASN_OK) = success,
- negative return value is error.

EXTERN int initContextBuffer (OOCTXT * pctxt, const ASN1OCTET * bufaddr, ASN1UINT bufsiz)

This function assigns a buffer to a context block.

The block should have been previously initialized by initContext.

Parameters:

pctxt The pointer to the context structure variable to be initialized.

bufaddr For encoding, the address of a memory buffer to receive and encode a message. For decoding the address of a buffer that contains the message data to be decoded. This address will be stored within the context structure. For encoding it might be zero, the dynamic buffer will be used in this case.

bufsiz The size of the memory buffer. For encoding, it might be zero; the dynamic buffer will be used in this case.

Returns:

Completion status of operation:

- 0 (ASN_OK) = success,
- negative return value is error.

EXTERN OOCTXT* newContext (void)

This function allocates a new OOCTXT block and initializes it.

Although the block is allocated from the standard heap, it should not be freed using free. The freeContext function should be used because this frees items allocated within the block before freeing the block itself.

Returns:

Pointer to newly created context

Linked List Utility Functions

Linked list and stack utility functions are used to maintain linked lists and stacks used within the ASN.1 run-time library functions.

Modules

- groupError Formatting and Print Functions
- groupRtmem

Defines

- #define **RT_MH_DONTKEEPFREE** 0x1
- #define **OSRTMH_PROPID_DEFBLKSIZE** 1
- #define **OSRTMH_PROPID_SETFLAGS** 2
- #define **OSRTMH_PROPID_CLEARFLAGS** 3
- #define **OSRTMH_PROPID_USER** 10

Functions

- EXTERN DListNode * **dListAppend** (OOCTXT *pctxt, DList *pList, void *pData) *This function appends an item to the linked list structure.*
- EXTERN DListNode * **dListAppendNode** (OOCTXT *pctxt, DList *pList, void *pData)
- EXTERN DListNode * **dListFindByIndex** (DList *pList, int index)

EXTERN void **dListFreeNodes** (OOCTXT *pctxt, DList *pList)

- EXTERN void **dListInit** (DList *pList)

 This function initializes a doubly linked list structure.

This function removes all nodes from the linked list and releases the memory that was allocated for storing the node structures (DListNode).

• EXTERN void **dListFreeAll** (OOCTXT *pctxt, DList *pList)

This function removes all nodes from the linked list structure and releases the memory that was allocated for storing the node structures (DListNode) and for data.

- EXTERN void **dListRemove** (DList *pList, DListNode *node)
 - This function removes a node from the linked list structure.
- EXTERN void **sListInit** (SList *pList)

This function is used to initialize a singly-linked list.

• EXTERN void **sListInitEx** (OOCTXT *pctxt, SList *pList)

This function is used to initialize a singly-linked list and assigns a context to be used for the list.

EXTERN void sListFree (SList *pList)

This function is used to free-up all the nodes in the singly-linked list.

• EXTERN SList * **sListCreate** (void)

This function is used to create a new singly-linked list.

• EXTERN SList * **sListCreateEx** (OOCTXT *pctxt)

This function is used to create a singly-linked list.

• EXTERN SListNode * **sListAppend** (SList *pList, void *pData)

This function is used to append a new data member to the list.

• EXTERN ASN1BOOL **sListFind** (SList *pList, void *pData)

This function is used to search for a particular data in the list.

• EXTERN void **sListRemove** (SList *pList, void *pData)

This function is used to remove a particular data member from the list.

Detailed Description

Linked list and stack utility functions are used to maintain linked lists and stacks used within the ASN.1 run-time library functions.

Function Documentation

EXTERN DListNode* dListAppend (OOCTXT * pctxt, DList * pList, void * pData)

This function appends an item to the linked list structure.

The data item is passed into the function as a void pointer that can point to any object of any type. The memAlloc function is used to allocated the memory for the list node structure; therefore, all internal list memory will be released whenever memFree is called. The pointer to the data item itself is stored in the node structure - a copy is not made.

Parameters:

pctxt A pointer to a context structure. This provides a storage area for the function to store all working variables that must be maintained between function calls.

pList A pointer to a linked list structure onto which the data item is to be appended. A pointer to an updated linked list structure.

pData A pointer to a data item to be appended to the list.

Returns:

A pointer to an allocated node structure used to link the given data value into the list.

EXTERN void dListFreeAll (OOCTXT * pctxt, DList * pList)

This function removes all nodes from the linked list structure and releases the memory that was allocated for storing the node structures (DListNode) and for data.

The memory for data in each node must have been previously allocated with calls to memAlloc, memAllocZ, or memRealloc functions.

Parameters:

pctxt Pointer to a context structure. This provides a storage area for the function to store all working variables that must be maintained between function calls. *pList* Pointer to a linked list structure.

EXTERN void dListFreeNodes (OOCTXT * pctxt, DList * pList)

This function removes all nodes from the linked list and releases the memory that was allocated for storing the node structures (DListNode).

The data will not be released.

Parameters:

pctxt A pointer to a context structure. This provides a storage area for the function to store all working variables that must be maintained between function calls. pList A pointer to a linked list structure onto which the data item is to be appended. A pointer to an updated linked list structure.

EXTERN void dListInit (DList * pList)

This function initializes a doubly linked list structure.

It sets the number of elements to zero and sets al internal pointer values to NULL. A doubly linked-list structure is described by the DList type defined in **ooasn1.h**. Nodes of the list are of type DListNode.

Memory for the structures is allocated using the memAlloc run-time function and is maintained within the context structure that is a required parameter to all dList functions. This memory is released when memFree is called or the Context is released. Unless otherwise noted, all data passed into the list functions is simply stored on the list by value (i.e. a deep-copy of the data is not done).

Parameters:

pList A pointer to a linked list structure to be initialized.

EXTERN void dListRemove (DList * pList, DListNode * node)

This function removes a node from the linked list structure.

The memAlloc function was used to allocate the memory for the list node structure, therefore, all internal list memory will be released whenever memFree or memFreePtr is called.

Parameters:

pList A pointer to a linked list structure onto which the data item is to be appended. A pointer to an updated linked list structure.

node A pointer to the node that is to be removed. It should already be in the linked list structure.

EXTERN SListNode* sListAppend (SList * pList, void * pData)

This function is used to append a new data member to the list.

Parameters:

pList Pointer to the list to which data has to be appended. *pData* Pointer to the data to be appended.

Returns:

Returns pointer to the newly appended list node.

EXTERN SList* sListCreate (void)

This function is used to create a new singly-linked list.

Parameters:

None

Returns:

Pointer to the newly created list.

EXTERN SList* sListCreateEx (OOCTXT * pctxt)

This function is used to create a singly-linked list.

The memory for the list is allocated using the context pointer passed to this function and also the same context will be used for any further memory required by the list.

Parameters:

pctxt Pointer to the OOCTXT context which will be used for list creation

Returns:

Pointer to the newly created list structure.

EXTERN ASN1BOOL sListFind (SList * pList, void * pData)

This function is used to search for a particular data in the list.

Parameters:

pList Pointer to the list in which data has to be searched. *pData* Pointer to the data to be searched.

Returns:

1 if found, 0 otherwise.

EXTERN void sListFree (SList * pList)

This function is used to free-up all the nodes in the singly-linked list.

Parameters:

pList Pointer to the list to be freed.

Returns:

None

EXTERN void sListInit (SList * pList)

This function is used to initialize a singly-linked list.

Parameters:

pList Pointer to the SList structure.

Returns:

None

EXTERN void sListInitEx (OOCTXT * pctxt, SList * pList)

This function is used to initialize a singly-linked list and assigns a context to be used for the list.

Parameters:

pctxt Pointer to the context which will be used for memory allocations related to the list. *pList* Pointer to the SList structure to be initialized.

Returns:

EXTERN void sListRemove (SList * pList, void * pData)

This function is used to remove a particular data member from the list.

Parameters:

pList Pointer to the list from which the data has to be removed. *pData* Pointer to the data to be removed.

Returns:

None

Error Formatting and Print Functions

Defines

- #define LOG_ASN1ERR(ctxt, stat) errSetData(&(ctxt)->errInfo,stat,__FILE__,__LINE__)
- #define LOG_ASN1ERR_AND_FREE(pctxt, stat, lctxt) freeContext ((lctxt)), LOG_ASN1ERR(pctxt, stat)

Functions

- EXTERN int **errAddIntParm** (ASN1ErrInfo *pErrInfo, int errParm)

 This function adds an integer parameter to an error information structure.
- EXTERN int **errAddStrParm** (ASN1ErrInfo *pErrInfo, const char *errprm_p) *This function adds an string parameter to an error information structure.*
- EXTERN int **errAddUIntParm** (ASN1ErrInfo *pErrInfo, unsigned int errParm) This function adds an unsigned integer parameter to an error information structure.
- EXTERN int errCopyData (ASN1ErrInfo *pSrcErrInfo, ASN1ErrInfo *pDestErrInfo)
- EXTERN void errFreeParms (ASN1ErrInfo *pErrInfo)

 This function frees memory associated with the storage of parameters associated with an error message.
- EXTERN char * errFmtMsg (ASN1ErrInfo *pErrInfo, char *bufp)
- EXTERN char * errGetText (OOCTXT *pctxt)

 This function gets the text of the error.

• EXTERN void **errPrint** (ASN1ErrInfo *pErrInfo)

This function prints error information to the standard output device.

• EXTERN int **errReset** (ASN1ErrInfo *pErrInfo)

This function resets the error information in the error information sturcture.

• EXTERN int errSetData (ASN1ErrInfo *pErrInfo, int status, const char *module, int lno)

This function sets error information in an error information structure.

Detailed Description

Error formatting and print functions allow information about the encode/decode errors to be added to a context block structure and then printed out when the error is propagated to the top level.

Function Documentation

EXTERN int errAddIntParm (ASN1ErrInfo * pErrInfo, int errParm)

This function adds an integer parameter to an error information structure.

Parameter substitution is done in much the same way as it is done in C printf statments. The base error message specification that goes along with a particular status code may have variable fields built in using '%' modifiers. These would be replaced with actual parameter data.

Parameters:

pErrInfo A pointer to a structure containing information on the error to be printed. Typically, the error info structure referred to is the one inside the OOCTXT structure. (i.e. &pctxt->errInfo). *errParm* The typed error parameter.

Returns:

The status of the operation.

EXTERN int errAddStrParm (ASN1ErrInfo * pErrInfo, const char * errprm_p)

This function adds an string parameter to an error information structure.

Parameter substitution is done in much the same way as it is done in C printf statments. The base error message specification that goes along with a particular status code may have variable fields built in using '%' modifiers. These would be replaced with actual parameter data.

Parameters:

pErrInfo A pointer to a structure containing information on the error to be printed. Typically, the error info structure referred to is the one inside the OOCTXT structure. (i.e. &pctxt->errInfo). *errprm p* The typed error parameter.

Returns:

The status of the operation.

EXTERN int errAddUIntParm (ASN1ErrInfo * pErrInfo, unsigned int errParm)

This function adds an unsigned integer parameter to an error information structure.

Parameter substitution is done in much the same way as it is done in C printf statments. The base error message specification that goes along with a particular status code may have variable fields built in using '%' modifiers. These would be replaced with actual parameter data.

Parameters:

pErrInfo A pointer to a structure containing information on the error to be printed. Typically, the error info structure referred to is the one inside the OOCTXT structure. (i.e. &pctxt->errInfo). *errParm* The typed error parameter.

Returns:

The status of the operation.

EXTERN void errFreeParms (ASN1ErrInfo * pErrInfo)

This function frees memory associated with the storage of parameters associated with an error message.

These parameters are maintained on an internal linked list maintained within the error information structure. The list memory must be freed when error processing is complete. This function is called from within errPrint after teh error has been printed out. It is also called in teh freeContext function.

Parameters:

pErrInfo A pointer to a structure containing information on the error to be printed. Typically, the error info structure referred to is the one inside the OOCTXT structure. (i.e. &pctxt->errInfo).

EXTERN char* errGetText (OOCTXT * pctxt)

This function gets the text of the error.

Parameters:

pctxt A pointer to a context structure.

EXTERN void errPrint (ASN1ErrInfo * pErrInfo)

This function prints error information to the standard output device.

The error information is stored in a structure of type ASN1ErrInfo. A structure of the this type is part f the OOCTXT structure. This is where error information is stored within the ASN1C generated and low-level encode/decode functions.

Parameters:

pErrInfo A pointer to a structure containing information on the error to be printed. Typically, the error info structure referred to is the one inside the OOCTXT structure. (i.e. &pctxt->errInfo).

EXTERN int errReset (ASN1ErrInfo * pErrInfo)

This function resets the error information in the error information sturcture.

Parameters:

pErrInfo A pointer to a structure containing information on the error to be printed. Typically, the error info structure referred to is the one inside the OOCTXT structure. (i.e. &pctxt->errInfo).

EXTERN int errSetData (ASN1ErrInfo * pErrInfo, int status, const char * module, int Ino)

This function sets error information in an error information structure.

The information set includes status code, module name, and line number. Location information (i.e. module name and line number) is pushed onto a stack within the error information structure to provide a complete stack trace when the information is printed out.

Parameters:

pErrInfo A pointer to a structure containing information on the error to be printed. Typically, the error info structure referred to is the one inside the OOCTXT structure. (i.e. &pctxt->errInfo). status The error status code. This is one of the negative error status codes. module The name of the module (C or C++ source file) in which the module occurred. This is typically obtained by using the _FILE_ macro. Into The line number at which the error occurred. This is typically obtained by using the _LINE

lno The line number at which the error occurred. This is typically obtained by using the _LINE_macro.

Returns:

The status value passed to the operation in the third argument. This makes it possible to set the error information and return the status value in one line of code.

Call Management

Functions

• EXTERN **ooCallData** * **ooCreateCall** (char *type, char *callToken) *This function is used to create a new call entry*.

• EXTERN int ooAddCallToList (ooEndPoint *h323ep, ooCallData *call)

This function is used to add a call to the list of existing calls.

• EXTERN ooCallData * ooFindCallByToken (char *callToken)

This function is used to find a call by using the unique token for the call.

• EXTERN int ooEndCall (ooCallData *call)

This function is used to clear a call.

• EXTERN int ooRemoveCallFromList (ooEndPoint *h323ep, ooCallData *call)

This function is used to remove a call from the list of existing calls.

• EXTERN int ooCleanCall (ooCallData *call)

This function is used to clean a call.

• EXTERN ooLogicalChannel * ooAddNewLogicalChannel (ooCallData *call, int channelNo, int sessionID, char *type, char *dir, ooH323EpCapability *epCap)

This function is used to add a new logical channel entry into the list of currently active logical channels.

• EXTERN ooLogicalChannel * ooFindLogicalChannelByLogicalChannelNo (ooCallData *call, int channelNo)

This function is used to find a logical channel by logical channel number.

• EXTERN int **ooOnLogicalChannelEstablished** (**ooCallData** *call, **ooLogicalChannel** *pChannel) *This function is called when a new logical channel is established.*

• EXTERN ASN1BOOL **ooIsSessionEstablished** (**ooCallData** *call, int sessionID, char *dir) This fuction is used to check whether a specified session in specified direction is active for the call.

 $\bullet \quad \text{EXTERN } \textbf{ooLogicalChannel} * \textbf{ooGetLogicalChannel} \; (\textbf{ooCallData} * \textbf{call}, \textbf{int } \textbf{sessionID}) \\$

This function is used to retrieve a logical channel with particular sessionID.

• EXTERN int **ooRemoveLogicalChannel** (**ooCallData** *call, int ChannelNo)

This function is used to remove a logical channel from the list of logical channels.

• EXTERN int ooClearLogicalChannel (ooCallData *call, int channelNo)

This function is used to cleanup a logical channel.

• EXTERN int ooClearAllLogicalChannels (ooCallData *call)

This function is used to cleanup all the logical channels associated with the call.

• EXTERN int **ooAddMediaInfo** (**ooCallData** *call, ooMediaInfo mediaInfo)

This function can be used by an application to specify media endpoint information for different types of media.

• EXTERN ooLogicalChannel * ooFindLogicalChannelByOLC (ooCallData *call,

H245OpenLogicalChannel *olc)

This function is used to find a logical channel from a received olc.

• EXTERN ooLogicalChannel * ooFindLogicalChannel (ooCallData *call, int sessionID, char *dir, H245DataType *dataType)

This function is used to find a logical channel based on session Id, direction of channel and datatype.

Function Documentation

EXTERN int ooAddCallToList (ooEndPoint * h323ep, ooCallData * call)

This function is used to add a call to the list of existing calls.

Parameters:

h323ep Pointer to the H323 Endpoint structure. *call* Pointer to the call to be added.

Returns:

OO_OK, on success. OO_FAILED, on failure

EXTERN int ooAddMediaInfo (ooCallData * call, ooMediaInfo mediaInfo)

This function can be used by an application to specify media endpoint information for different types of media.

The stack by default uses local IP and port for media. An application can provide mediainfo if it wants to override default.

Parameters:

call Handle to the call

mediaInfo mediainfo structure which defines the media endpoint to be used.

Returns:

EXTERN ooLogicalChannel* ooAddNewLogicalChannel (ooCallData * call, int channelNo, int sessionID, char * type, char * dir, ooH323EpCapability * epCap)

This function is used to add a new logical channel entry into the list of currently active logical channels.

Parameters:

call Pointer to the call for which new logical channel entry has to be created. channelNo Channel number for the new channel entry. sessionID Session identifier for the new channel. type Type of the channel(audio/video/data) dir Direction of the channel(transmit/receive) epCap Capability to be used for the new channel.

Returns:

Pointer to logical channel, on success. NULL, on failure

EXTERN int ooCleanCall (ooCallData * call)

This function is used to clean a call.

It closes all associated sockets, removes call from list and frees up associated memory.

Parameters:

call Pointer to the call to be cleared.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooClearAllLogicalChannels (ooCallData * call)

This function is used to cleanup all the logical channels associated with the call.

Parameters:

call Handle to the call which owns the channels.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooClearLogicalChannel (ooCallData * call, int channelNo)

This function is used to cleanup a logical channel.

It first stops media, if it is still active and then removes the channel from the list, freeing up all the associated memory.

Parameters:

call Handle to the call which owns the logical channel. *channelNo* Channel number identifying the channel.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN ooCallData* ooCreateCall (char * type, char * callToken)

This function is used to create a new call entry.

Parameters:

type Type of the call (incoming/outgoing) *callToken* Call Token, an uniques identifier for the call

Returns:

Pointer to a newly created call

EXTERN int ooEndCall (ooCallData * call)

This function is used to clear a call.

Based on what stage of clearance the call is it takes appropriate action.

Parameters:

call Handle to the call which has to be cleared.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN ooCallData* ooFindCallByToken (char * callToken)

This function is used to find a call by using the unique token for the call.

Parameters:

callToken The unique token for the call.

Returns:

Pointer to the call if found, NULL otherwise.

EXTERN ooLogicalChannel* ooFindLogicalChannel (ooCallData * call, int sessionID, char * dir, H245DataType * dataType)

This function is used to find a logical channel based on session Id, direction of channel and datatype.

Parameters:

call Handle to the call sessionID Session ID for the channel to be searched. dir Direction of the channel wrt local endpoint. (transmit/receive) dataType Handle to the data type for the channel.

Returns:

Logical channel, if found, NULL otherwise.

EXTERN ooLogicalChannel* ooFindLogicalChannelByLogicalChannelNo (ooCallData * call, int channelNo)

This function is used to find a logical channel by logical channel number.

Parameters:

call Pointer to the call for which logical channel is required. channelNo Forward Logical Channel number for the logical channel

Returns:

Pointer to the logical channel if found, NULL otherwise.

EXTERN ooLogicalChannel* ooFindLogicalChannelByOLC (ooCallData * call, H245OpenLogicalChannel * olc)

This function is used to find a logical channel from a received olc.

Parameters:

call Handle to the related call. *olc* Handle to the received OLC.

Returns:

Returns the corresponding logical channel if found, else returns NULL.

EXTERN ooLogicalChannel* ooGetLogicalChannel (ooCallData * call, int sessionID)

This function is used to retrieve a logical channel with particular sessionID.

Note that there can be two entries of logical channel, one in each direction. This function will return the first channel which has the same session ID.

Parameters:

call Handle to the call which owns the channels to be searched. *sessionID* Session id of the session which is to be searched for.

Returns:

Returns a pointer to the logical channel if found, NULL otherwise.

EXTERN ASN1BOOL oolsSessionEstablished (ooCallData * call, int sessionID, char * dir)

This fuction is used to check whether a specified session in specified direction is active for the call.

Parameters:

call Handle to call for which session has to be queried.

*sessionID Session id to identify the type of session(1 for audio, 2 for voice and 3 for data)

*dir Direction of the session(transmit/receive)

Returns:

1, if session active. 0, otherwise.

EXTERN int ooOnLogicalChannelEstablished (ooCallData * call, ooLogicalChannel * pChannel)

This function is called when a new logical channel is established.

It is particularly useful in case of faststart. When the remote endpoint selects one of the proposed alternatives, other channels for the same session type need to be closed. This function is used for that.

Parameters:

call Handle to the call which owns the logical channel. *pChannel* Handle to the newly established logical channel.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooRemoveCallFromList (ooEndPoint * h323ep, ooCallData * call)

This function is used to remove a call from the list of existing calls.

Parameters:

h323ep Pointer to the H323 Endpoint. *call* Pointer to the call to be removed.

Returns:

EXTERN int ooRemoveLogicalChannel (ooCallData * call, int ChannelNo)

This function is used to remove a logical channel from the list of logical channels.

Parameters:

call Pointer to the call from which logical channel has to be removed. *ChannelNo* Forward logical channel number of the channel to be removed.

Capability Management

Functions

- EXTERN int ooAddCapability (int cap, int dir, cb_StartReceiveChannel startReceiveChannel, cb_StartTransmitChannel startTransmitChannel, cb_StopReceiveChannel stopReceiveChannel, cb_StopTransmitChannel stopTransmitChannel)
 - This function is used to add a new capability to the endpoint.
- H245AudioCapability * ooCreateAudioCapability (int cap, OOCTXT *pctxt)
 This function is used to create a audio capability structure using the capability type.
- H245AudioCapability * **ooCreateG711Capability** (int cap, OOCTXT *pctxt) *This function is used to create a g711 audio capability structure.*
- ooH323EpCapability * ooIsAudioCapSupported (ooCallData *call, H245AudioCapability *audioCap, int dir)
 This function is used to determine whether a particular capability can be supported by the endpoint.
- int **ooCompareAudioCaps** (int cap, H245AudioCapability *audioCap, int dir) *This function is used to determine a capability match.*
- int **ooCompareUlawCaps** (int cap, H245AudioCapability *audioCap, int dir) *This function is used to determine a ulaw capability match.*
- int **ooCompareAlawCaps** (int cap, H245AudioCapability *audioCap, int dir) *This function is used to determine a Alaw capability match.*
- **ooH323EpCapability** * **ooIsDataTypeSupported** (**ooCallData** *call, H245DataType *data, int dir) *This function is used to determine whether a particular datatype can be supported by the endpoint.*

Function Documentation

EXTERN int ooAddCapability (int *cap*, int *dir*, cb_StartReceiveChannel *startReceiveChannel*, cb_StartTransmitChannel *startTransmitChannel*, cb_StopReceiveChannel, cb_StopTransmitChannel *stopTransmitChannel*)

This function is used to add a new capability to the endpoint.

Parameters:

cap Type of capability to be added.
dir Direction - Indicates whether endpoint has receive capability, or transmit capability or both.ex
T_H245Capability_receiveAudioCapability.
startReceiveChannel Callback function to start receive channel.
startTransmitChannel Callback function to start transmit channel.
stopReceiveChannel Callback function to stop receive channel.
stopTransmitChannel Callback function to stop transmit channel.

Returns:

OO_OK, on success. OO_FAILED, on failure.

int ooCompareAlawCaps (int cap, H245AudioCapability * audioCap, int dir)

This function is used to determine a Alaw capability match.

Parameters:

cap Local capability to be matched. audioCap Remote capability to be matched. dir Direction for local capability.

Returns:

OO_OK, on success. OO_FAILED, on failure.

int ooCompareAudioCaps (int cap, H245AudioCapability * audioCap, int dir)

This function is used to determine a capability match.

Parameters:

cap Local capability to be matched. audioCap Remote capability to be matched. dir Direction for local capability.

Returns:

int ooCompareUlawCaps (int cap, H245AudioCapability * audioCap, int dir)

This function is used to determine a ulaw capability match.

Parameters:

```
cap Local capability to be matched. audioCap Remote capability to be matched. dir Direction for local capability.
```

Returns:

OO_OK, on success. OO_FAILED, on failure.

struct H245AudioCapability* ooCreateAudioCapability (int cap, OOCTXT * pctxt)

This function is used to create a audio capability structure using the capability type.

Parameters:

```
cap Capability.

pctxt Handle to OOCTXT which will be used to allocate memory for new audio capability.
```

Returns:

Newly created audio capability on success, NULL on failure.

struct H245AudioCapability* ooCreateG711Capability (int cap, OOCTXT * pctxt)

This function is used to create a g711 audio capability structure.

Parameters:

```
cap Capability pctxt Handle to OOCTXT which will be used to allocate memory for new audio capability.
```

Returns:

Newly created audio capability on success, NULL on failure.

ooH323EpCapability* oolsAudioCapSupported (ooCallData * call, H245AudioCapability * audioCap, int dir)

This function is used to determine whether a particular capability can be supported by the endpoint.

Parameters:

```
call Handle to the call. audioCap Handle to the audio capability. dir Direction in which support is desired.
```

Returns:

Handle to the capability which supports audioCap, Null if none found

ooH323EpCapability* oolsDataTypeSupported (ooCallData * call, H245DataType * data, int dir)

This function is used to determine whether a particular datatype can be supported by the endpoint.

Parameters:

call Handle to the call.
data Handle to the data type.
dir Direction in which support is desired.

Returns:

Handle to the capability which supports 'data', Null if none found

Channel Management

Functions

• EXTERN int ooCreateH323Listener (void)

This function is used to create a listener for incoming calls.

• EXTERN int ooCreateH245Listener (ooCallData *call)

This function is used to create a listener for incoming H.245 connections.

• EXTERN int **ooAcceptH225Connection** (void)

This function is used to accept incoming H.225 connections.

• EXTERN int ooAcceptH245Connection (ooCallData *call)

This function is used to accept an incoming H.245 connection.

• EXTERN int ooCreateH225Connection (ooCallData *call)

This function is used to create an H.225 connection to the remote end point.

• EXTERN int ooCreateH245Connection (ooCallData *call)

This function is used to setup an H.245 connection with the remote endpoint for control negotiations.

• EXTERN int ooCloseH225Connection (ooCallData *call)

This function is used to close an H.225 connection.

• EXTERN int ooCloseH245Connection (ooCallData *call)

This function is used to close an H.245 connection for a call.

• EXTERN int **ooMonitorChannels** (void)

This function is used to start monitoring channels for the calls.

• EXTERN int ooStopMonitorCalls (void)

This function is called to stop the monitor channels thread.

• EXTERN int ooH2250Receive (ooCallData *call)

This function is used to receive an H.2250 message received on a calls H.225 channel.

• EXTERN int ooH245Receive (ooCallData *call)

This function is used to receive an H.245 message received on a calls H.245 channel.

• EXTERN int ooSendH225Msg (ooCallData *call, Q931Message *msg)

This function is used to enqueue an H.225 message into an outgoing queue for the call.

• EXTERN int ooSendH245Msg (ooCallData *call, H245Message *msg)

This function is used to enqueue an H.245 message into an outgoing queue for the call.

• EXTERN int ooSendMsg (ooCallData *call, int type)

This function is used to Send a message on the channel, when channel is available for write.

• EXTERN int ooOnSendMsg (ooCallData *call, int msgType)

This function is called after a message is sent on the call's channel.

Function Documentation

EXTERN int ooAcceptH225Connection (void)

This function is used to accept incoming H.225 connections.

Parameters:

None

Returns:

EXTERN int ooAcceptH245Connection (ooCallData * call)

This function is used to accept an incoming H.245 connection.

Parameters:

call Pointer to a call for which H.245 connection request has arrived.

Returns:

OO_OK, on succes. OO_FAILED, on failure.

EXTERN int ooCloseH225Connection (ooCallData * call)

This function is used to close an H.225 connection.

Parameters:

call Pointer to the call for which H.225 connection has to be closed.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooCloseH245Connection (ooCallData * call)

This function is used to close an H.245 connection for a call.

Parameters:

call Pointer to call for which H.245 connection has to be closed.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooCreateH225Connection (ooCallData * call)

This function is used to create an H.225 connection to the remote end point.

Parameters:

call Pointer to the call for which H.225 connection has to be setup.

Returns:

EXTERN int ooCreateH245Connection (ooCallData * call)

This function is used to setup an H.245 connection with the remote endpoint for control negotiations.

Parameters:

call Pointer to call for which H.245 connection has to be setup.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooCreateH245Listener (ooCallData * call)

This function is used to create a listener for incoming H.245 connections.

Parameters:

call Pointer to call for which H.245 listener has to be created

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooCreateH323Listener (void)

This function is used to create a listener for incoming calls.

Parameters:

None

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooH2250Receive (ooCallData * call)

This function is used to receive an H.2250 message received on a calls H.225 channel.

It receives the message, decodes it and calls 'ooHandleH2250Message' to process the message.

Parameters:

call Pointer to the call for which the message has to be received.

Returns:

EXTERN int ooH245Receive (ooCallData * call)

This function is used to receive an H.245 message received on a calls H.245 channel.

It receives the message, decodes it and calls 'ooHandleH245Message' to process it.

Parameters:

call Pointer to the call for which the message has to be received.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooMonitorChannels (void)

This function is used to start monitoring channels for the calls.

It has an infinite loop which uses select to monitor various channels.

Parameters:

None

EXTERN int ooOnSendMsg (ooCallData * call, int msgType)

This function is called after a message is sent on the call's channel.

It can be used to some followup action after message has been sent.

Parameters:

call Pointer to call for which message has been sent. *msgType* Type of message

Returns:

OO OK, on success. OO FAILED, on failure

EXTERN int ooSendH225Msg (ooCallData * call, Q931Message * msg)

This function is used to enqueue an H.225 message into an outgoing queue for the call.

Parameters:

call Pointer to call for which message has to be enqueued. *msg* Pointer to the H.225 message to be sent.

Returns:

EXTERN int ooSendH245Msg (ooCallData * call, H245Message * msg)

This function is used to enqueue an H.245 message into an outgoing queue for the call.

Parameters:

call Pointer to call for which message has to be enqueued. *msg* Pointer to the H.245 message to be sent.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooSendMsg (ooCallData * call, int type)

This function is used to Send a message on the channel, when channel is available for write.

Parameters:

call Pointer to call for which message has to be sent. *type* Type of the message.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooStopMonitorCalls (void)

This function is called to stop the monitor channels thread.

It cleans up all the active calls, before stopping monitor thread.

Parameters:

None

Returns:

OO_OK, on success. OO_FAILED, on failure

H245 Message Handling

Functions

• EXTERN int ooCreateH245Message (H245Message **msg, int type)

Creates an outgoing H245 message of the type specified by the type argument for the Application context.

• EXTERN int ooFreeH245Message (H245Message *pmsg)

Frees up the memory used by the H245 message.

• EXTERN int **ooGetOutgoingH245Msgbuf** (**ooCallData** *call, ASN1OCTET *msgbuf, int *len, int *msgType)

This function is used to retrieve an H.245 message enqueued in the outgoing queue.

EXTERN int ooSendTermCapMsg (ooCallData *call)

This function is used to send out a treminal capability set message.

• EXTERN ASN1UINT ooGenerateStatusDeterminationNumber ()

This function is used to generate a random status determination number for MSD procedure.

• EXTERN int **ooHandleMasterSlave** (**ooCallData** *call, void *pmsg, int msgType)

This fuction is used to handle received MasterSlaveDetermination procedure messages.

• EXTERN int ooSendMasterSlaveDetermination (ooCallData *call)

This function is used to send MSD message.

• EXTERN int ooSendMasterSlaveDeterminationAck (ooCallData *call, char *status)

This function is used to send a MasterSlaveDeterminationAck message.

• EXTERN int ooHandleOpenLogicalChannel (ooCallData *call, H245OpenLogicalChannel *olc)

This function is used to handle received OpenLogicalChannel message.

• EXTERN int ooHandleOpenLogicalAudioChannel (ooCallData *call, H245OpenLogicalChannel

*olc)

This function is used to handle a received OpenLogicalChannel message which is trying to open a audio channel.

• EXTERN int ooOnReceivedOpenLogicalChannelAck (ooCallData *call,

H245OpenLogicalChannelAck *olcAck)

This function is used to handle a received OpenLogicalChannelAck message.

• int ooOnReceivedOpenLogicalChannelRejected (ooCallData *call,

H245OpenLogicalChannelReject *olcRejected)

This function is used to handle the received OpenLogicalChannelReject message.

• EXTERN int ooSendEndSessionCommand (ooCallData *call)

This message is used to send an EndSession command.

EXTERN int ooHandleH245Command (ooCallData *call, H245CommandMessage *command)

This function is used to handle a received H245Command message.

• EXTERN int ooOnReceivedTerminalCapabilitySetAck (ooCallData *call)

This function is called on receiving a TreminalCapabilitySetAck message.

• EXTERN int ooCloseAllLogicalChannels (ooCallData *call)

This function is called to close all the open logical channels.

• EXTERN int ooSendCloseLogicalChannel (ooCallData *call, ooLogicalChannel *logicalChan)

This function is used to send out a CloseLogicalChannel message for a particular logical channel.

• EXTERN int ooOnReceivedCloseLogicalChannel (ooCallData *call, H245CloseLogicalChannel *call)

This function is used to process a received closeLogicalChannel request.

• EXTERN int ooOnReceivedCloseChannelAck (ooCallData *call, H245CloseLogicalChannelAck *clcAck)

This function is used to process a received CloseLogicalChannelAck message.

• EXTERN int ooHandleH245Message (ooCallData *call, H245Message *pmsg)

This function is used to handle received H245 message.

• EXTERN int ooOnReceivedTerminalCapabilitySet (ooCallData *call, H245Message *pmsg)

This function is used to process received TCS message.

• EXTERN int ooH245AcknowledgeTerminalCapabilitySet (ooCallData *call)

This function is used to send a TCSAck message to remote endpoint.

• EXTERN int ooOpenLogicalChannels (ooCallData *call)

This function is used to start OpenLogicalChannel procedure for all the channels to be opened for the call.

• EXTERN int ooOpenLogicalAudioChannel (ooCallData *call)

This function is used to send OpenLogicalChannel message for audio channel.

EXTERN int ooOpenG711ULaw64KChannel (ooCallData *call, ooH323EpCapability *epCap)

This function is used to build a OpenLogicalChannel message using G711ULaw64K capability.

 $\bullet \quad \text{EXTERN int } \textbf{ooSendRequestCloseLogicalChannel } (\textbf{ooCallData} * \textbf{call, ooLogicalChannel}$

*logicalChan)

This function is used to request a remote end point to close a logical channel.

• EXTERN int ooOnReceivedRequestChannelClose (ooCallData *call, H245RequestChannelClose

*rclc)

This function handles the received RequestChannelClose message, verifies that the requested channel is forward channel.

• EXTERN int **ooBuildOpenLogicalChannelAudio** (**ooCallData** *call, H245OpenLogicalChannel *olc, **ooH323EpCapability** *epCap, OOCTXT *pctxt)

Builds an OLC with an audio capability passed as parameter.

• EXTERN int ooSendAsTunneledMessage (ooCallData *call, ASN1OCTET *msgbuf, int len, int msgType)

This function sends an encoded H.245 message buffer as a tunneled H.245 message.

Function Documentation

EXTERN int ooBuildOpenLogicalChannelAudio (ooCallData * call, H245OpenLogicalChannel * o/c, ooH323EpCapability * epCap, OOCTXT * pctxt)

Builds an OLC with an audio capability passed as parameter.

Parameters:

call Handle to call for which OLC has to be built.

olc Pointer to an OLC structure which will be populated.

epCap Pointer to the capability which will be used to build OLC.

pctxt Pointer to an OOCTXT structure which will be used to allocate additional memory for OLC.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooCloseAllLogicalChannels (ooCallData * call)

This function is called to close all the open logical channels.

It sends CloseLogicalChannel message for all the forward channels and sends RequestCloseLogicalChannel message for all the reverse channels.

Parameters:

call Pointer to call for which logical channels have to be closed.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooCreateH245Message (H245Message ** msg, int type)

Creates an outgoing H245 message of the type specified by the type argument for the Application context.

Parameters:

msg A pointer to message which will be assigned to allocated memory.

type Type of the message to be created. (Request/Response/Command/Indication)

Returns:

Completion status of operation: 0 (OO_OK) = success, negative return value is error.

EXTERN int ooFreeH245Message (H245Message * pmsg)

Frees up the memory used by the H245 message.

Parameters:

pmsg Pointer to an H245 message structure.

Returns:

OO_OK, on success. OO_FAILED, on failure

EXTERN ASN1UINT ooGenerateStatusDeterminationNumber ()

This function is used to generate a random status determination number for MSD procedure.

Parameters:

None

Returns:

Generated status determination number.

EXTERN int ooGetOutgoingH245Msgbuf (ooCallData * call, ASN1OCTET * msgbuf, int * len, int * msgType)

This function is used to retrieve an H.245 message enqueued in the outgoing queue.

Parameters:

call Pointer to the call for which message has to be retrieved.

msgbuf Pointer to a buffer in which the message will be returned.

len Pointer to an int variable which will contain length of the message data after returning.

msgType Pointer to an int variable, which will contain message type on return from the function.

Returns:

EXTERN int ooH245AcknowledgeTerminalCapabilitySet (ooCallData * call)

This function is used to send a TCSAck message to remote endpoint.

Parameters:

call Pointer to call on which TCSAck has to be sent.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooHandleH245Command (ooCallData * call, H245CommandMessage * command)

This function is used to handle a received H245Command message.

Parameters:

call Pointer to call for which an H245Command is received. *command* Pointer to a command message.

Returns:

OO_OK, on success. OO_FAILED, on failure

EXTERN int ooHandleH245Message (ooCallData * call, H245Message * pmsg)

This function is used to handle received H245 message.

Based on the type of message received, it calls helper functions to process those messages.

Parameters:

call Pointer to call for which a message is received. *pmsg* Pointer to the received H245 message.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooHandleMasterSlave (ooCallData * call, void * pmsg, int msgType)

This fuction is used to handle received MasterSlaveDetermination procedure messages.

Parameters:

```
call Pointer to the call for which a message is received.

pmsg Pointer to MSD message

msgType Message type indicating whether received message is MSD, MSDAck, MSDReject etc...
```

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooHandleOpenLogicalAudioChannel (ooCallData * call, H245OpenLogicalChannel * olc)

This function is used to handle a received OpenLogicalChannel message which is trying to open a audio channel.

Parameters:

call Pointer to cll for which OLC was received. olc The received OpenLogicalChannel message.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooHandleOpenLogicalChannel (ooCallData * call, H245OpenLogicalChannel * olc)

This function is used to handle received OpenLogicalChannel message.

Parameters:

call Pointer to call for which OpenLogicalChannel message is received. olc Pointer to the received OpenLogicalChannel message.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooOnReceivedCloseChannelAck (ooCallData * call, H245CloseLogicalChannelAck * clcAck)

This function is used to process a received CloseLogicalChannelAck message.

It closes the channel and removes it from the list of active logical channels.

Parameters:

call Pointer to call for which CLCAck message is received. clcAck Pointer to the received CloseLogicalChannelAck message.

Returns:

EXTERN int ooOnReceivedCloseLogicalChannel (ooCallData * call, H245CloseLogicalChannel * clc)

This function is used to process a received closeLogicalChannel request.

It closes the logical channel and removes the logical channel entry from the list. It also, sends closeLogicalChannelAck message to the remote endpoint.

Parameters:

call Pointer to call for which CloseLogicalChannel message is received. clc Pointer to received CloseLogicalChannel message.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooOnReceivedOpenLogicalChannelAck (ooCallData * call, H245OpenLogicalChannelAck * olcAck)

This function is used to handle a received OpenLogicalChannelAck message.

Parameters:

call Pointer to call for which OLCAck is received olcAck Pointer to received olcAck message.

Returns:

OO OK, on success. OO FAILED, on failure.

int ooOnReceivedOpenLogicalChannelRejected (ooCallData * call, H245OpenLogicalChannelReject * olcRejected)

This function is used to handle the received OpenLogicalChannelReject message.

Parameters:

call Handle to the call for which the message is received. *olcRejected* Pointer to received OpenLogicalChannelReject message.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooOnReceivedRequestChannelClose (ooCallData * call, H245RequestChannelClose * rclc)

This function handles the received RequestChannelClose message, verifies that the requested channel is forward channel.

It sends an acknowledgement for the message followed by CloseLogicalChannel message.

Parameters:

call Pointer to the call for which RequestChannelClose is received. rclc Pointer to the received message.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooOnReceivedTerminalCapabilitySet (ooCallData * call, H245Message * pmsg)

This function is used to process received TCS message.

It builds TCSAck message and queues it into the calls outgoing queue. Also, starts Logical channel opening procedure if TCS and MSD procedures have finished.

Parameters:

call Pointer to call for which TCS is received. *pmsg* Pointer to the received message.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooOnReceivedTerminalCapabilitySetAck (ooCallData * call)

This function is called on receiving a TreminalCapabilitySetAck message.

If the MasterSlaveDetermination process is also over, this function initiates the process of opening logical channels.

Parameters:

call Pointer to call for which TCSAck is received.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooOpenG711ULaw64KChannel (ooCallData * call, ooH323EpCapability * epCap)

This function is used to build a OpenLogicalChannel message using G711ULaw64K capability.

Parameters:

call Pointer to call for which OpenLogicalChannel message have to be built. *epCap* Pointer to G711ULaw capability

Returns:

EXTERN int ooOpenLogicalAudioChannel (ooCallData * call)

This function is used to send OpenLogicalChannel message for audio channel.

It uses the first capability match in the local and remote audio capabilities for the audio channel and calls corresponding helper function.

Parameters:

call Pointer to call for which audio channel ahs to be opened.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooOpenLogicalChannels (ooCallData * call)

This function is used to start OpenLogicalChannel procedure for all the channels to be opened for the call.

Parameters:

call Pointer to call for which logical channels have to be opened.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooSendAsTunneledMessage (ooCallData * call, ASN1OCTET * msgbuf, int len, int msgType)

This function sends an encoded H.245 message buffer as a tunneled H.245 message.

If there is an outgoing H.225 message, it is used to tunnel the H.245 message and if there is no H.225 message, then a new Facility message is created for tunneling purpose.

Parameters:

```
call Pointer to the call for which H.245 message has to be tunneled. msgbuf Pointer to the encoded H.245 message to be tunneled. len Length of the encoded H.245 message buffer. msgType Type of the H245 message
```

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooSendCloseLogicalChannel (ooCallData * call, ooLogicalChannel * logicalChan)

This function is used to send out a CloseLogicalChannel message for a particular logical channel.

Parameters:

call Pointer to a call, to which logical channel to be closed belongs. *logicalChan* Pointer to the logical channel to be closed.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooSendEndSessionCommand (ooCallData * call)

This message is used to send an EndSession command.

It builds a EndSession command message and queues it into the calls outgoing queue.

Parameters:

call Pointer to call for which EndSession command has to be sent.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooSendMasterSlaveDetermination (ooCallData * call)

This function is used to send MSD message.

Parameters:

call Pointer to call for which MasterSlaveDetermination has to be sent.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooSendMasterSlaveDeterminationAck (ooCallData * call, char * status)

This function is used to send a MasterSlaveDeterminationAck message.

Parameters:

call Pointer to call for which MasterSlaveDeterminationAck has to be sent. *status* Result of the determination process(Master/Slave as it applies to remote endpoint)

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooSendRequestCloseLogicalChannel (ooCallData * call, ooLogicalChannel * logicalChan)

This function is used to request a remote end point to close a logical channel.

Parameters:

call Pointer to call for which the logical channel has to be closed. *logicalChan* Pointer to the logical channel structure which needs to be closed.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooSendTermCapMsg (ooCallData * call)

This function is used to send out a treminal capability set message.

Parameters:

call Pointer to a call, for which TerminalCapabilitySet message has to be sent.

Returns:

OO_OK, on success. OO_FAILED, on failure.

H323 Endpoint management functions

Functions

- EXTERN int **ooInitializeH323Ep** (const char *tracefile, int h245Tunneling, int fastStart, int termType, int t35CountryCode, int t35Extension, int manufacturer, char *productID, char *versionID, int callType, int listenport, char *callerid, char *callername, int callMode)

 This function is the first function to be invoked before using stack.
- EXTERN int **ooSetLocalCallSignallingAddress** (char *localip, int listenport) *This function is used to assign a local ip address to be used for call signalling.*
- EXTERN int ooSetAliasH323ID (char *h323id)
 This function is used to set the h323id alias for the endpoint.
- EXTERN int ooSetAliasDialedDigits (char *dialedDigits)
 This function is used to set the dialed digits alias for the endpoint.
- EXTERN int ooSetAliasURLID (char *url)
 This function is used to set the url alias for the endpoint.
- EXTERN int **ooSetAliasEmailID** (char *email)

This function is used to set an email id as an alias for the endpoint.

• EXTERN int **ooSetAliasTransportID** (char *ipaddress)

This function is used to set an ip address as an alias.

• EXTERN int ooH323EpRegisterCallbacks (cb_OnAlerting onAlerting, cb_OnIncomingCall onIncomingCall, cb_OnOutgoingCallAdmitted onOutgoingCallAdmitted, cb_OnOutgoingCall onOutgoingCall, cb_OnCallEstablished onCallEstablished, cb_OnCallCleared onCallCleared) This function is used to register the H323 Endpoint callback functions.

• EXTERN int **ooDestroyH323Ep** (void)

This function is the last function to be invoked after done using the stack.

• EXTERN int ooEnableAutoAnswer (void)

This function is used to enable the auto answer feature for incoming calls.

• EXTERN int **ooDisableAutoAnswer** (void)

This function is used to disable the auto answer feature for incoming calls.

• EXTERN int **ooSetFastStart** (int fastStart)

This function is used to enable/disable faststart.

• EXTERN int **ooSetH245Tunneling** (int tunneling)

This function is used to enable/disable tunneling.

• EXTERN int **ooSetProductID** (char *productID)

This function is used to set the product ID.

• EXTERN int **ooSetVersionID** (char *versionID)

This function is used to set version id.

• EXTERN int **ooSetCallerID** (char *callerID)

This function is used to set callerid to be used for outbound calls.

• EXTERN int ooSetCallerName (char *callerName)

This function is used to set the caller name, which is used for display purposes.

Function Documentation

EXTERN int ooDestroyH323Ep (void)

This function is the last function to be invoked after done using the stack.

It closes the H323 Endpoint for an application, releasing all the associated memory.

Parameters:

None

Returns:

OO_OK on success OO_FAILED on failure

EXTERN int ooDisableAutoAnswer (void)

This function is used to disable the auto answer feature for incoming calls.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooEnableAutoAnswer (void)

This function is used to enable the auto answer feature for incoming calls.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooH323EpRegisterCallbacks (cb_OnAlerting onAlerting, cb_OnIncomingCall onIncomingCall, cb_OnOutgoingCallAdmitted onOutgoingCallAdmitted, cb_OnOutgoingCall onOutgoingCall, cb_OnCallEstablished onCallEstablished, cb_OnCallCleared onCallCleared)

This function is used to register the H323 Endpoint callback functions.

Parameters:

onAlerting Callback function to be called when alerting message is sent. onIncomingCall Callback function to be called when a new incoming call is accepted. onOutgoingCallAdmitted Callback function to be called when a outgoing call is admitted by gk. onOutgoingCall Callback function to be called when an outgoing call is placed on behalf of the application.

on CallEstablished Callback function to be called when a call is established with the remote end point.

onCallCleared Callback function to be called when a call is cleared.

Returns:

EXTERN int oolnitializeH323Ep (const char * tracefile, int h245Tunneling, int fastStart, int termType, int t35CountryCode, int t35Extension, int manufacturer, char * productID, char * versionID, int callType, int listenport, char * callerid, char * callername, int callMode)

This function is the first function to be invoked before using stack.

It initializes the H323 Endpoint.

Parameters:

tracefile Absolute path to the trace file to be used for storing traces h245Tunneling Indicates whether h245Tunneling enabled(1)/disabled(0) fastStart Indicates whether fast start is enabled(1)/disabled(0) termType Terminal type of the endpoint. t35CountryCode Country code to be used t35Extension t35Extension value manufacturer manufacturer code productID Product ID to be used versionID Version Id of the software callType Type of the call ex. T_H225CallType_pointToPoint listenport Port on which to listen for incoming calls callerid ID to be used for outgoing calls. callername Caller name to be used for outgoing calls callMode Type of calls to be made(audio/video/fax). (OO_CALLMODE_AUDIO, OO_CALLMODE_VIDEO)

Returns:

OO_OK, on success. OO_FAILED, on failure

EXTERN int ooSetAliasDialedDigits (char * dialedDigits)

This function is used to set the dialed digits alias for the endpoint.

Parameters:

dialedDigits Dialed-Digits to be set as alias.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooSetAliasEmailID (char * email)

This function is used to set an email id as an alias for the endpoint.

Parameters:

email Email id to be set as an alias.

Returns:

EXTERN int ooSetAliasH323ID (char * h323id)

This function is used to set the h323id alias for the endpoint.

Parameters:

h323id H323-ID to be set as alias.

Returns:

OO OK, on success. OO FAILED, on failure.

EXTERN int ooSetAliasTransportID (char * ipaddress)

This function is used to set an ip address as an alias.

Parameters:

ipaddress IP address to be set as an alias.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooSetAliasURLID (char * url)

This function is used to set the url alias for the endpoint.

Parameters:

url URL to be set as an alias.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooSetCallerID (char * callerID)

This function is used to set callerid to be used for outbound calls.

Parameters:

callerID New value for the caller id.

Returns:

EXTERN int ooSetCallerName (char * callerName)

This function is used to set the caller name, which is used for display purposes.

Parameters:

callerName New value for the caller name.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooSetFastStart (int fastStart)

This function is used to enable/disable faststart.

Parameters:

fastStart 1, to enable and 0, to disable faststart

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooSetH245Tunneling (int tunneling)

This function is used to enable/disable tunneling.

Parameters:

tunneling 1, to enable and 0, to disable tunneling.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooSetLocalCallSignallingAddress (char * localip, int listenport)

This function is used to assign a local ip address to be used for call signalling.

Parameters:

localip Dotted IP address to be used for call signalling. *listenport* Port to be used for listening for incoming calls.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooSetProductID (char * productID)

This function is used to set the product ID.

Parameters:

productID New value for the product id.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooSetVersionID (char * versionID)

This function is used to set version id.

Parameters:

versionID New value for the version id.

Returns:

OO_OK, on success. OO_FAILED, on failure.

Q931/H.2250 Message Handling

Data Structures

• struct Q931InformationElement

Defines

- #define **Q931_E_TOOSHORT** (-1001)
- #define **Q931_E_INVCALLREF** (-1002)
- #define **Q931_E_INVLENGTH** (-1003)

Typedefs

• typedef Q931InformationElement **Q931InformationElement**

Enumerations

- enum Q931MsgTypes { Q931NationalEscapeMsg = 0x00, Q931AlertingMsg = 0x01, Q931CallProceedingMsg = 0x02, Q931ConnectMsg = 0x07, Q931ConnectAckMsg = 0x0f, Q931ProgressMsg = 0x03, Q931SetupMsg = 0x05, Q931SetupAckMsg = 0x0d, Q931ResumeMsg = 0x26, Q931ResumeAckMsg = 0x2e, Q931ResumeRejectMsg = 0x22, Q931SuspendMsg = 0x25, Q931SuspendAckMsg = 0x2d, Q931SuspendRejectMsg = 0x21, Q931UserInformationMsg = 0x20, Q931DisconnectMsg = 0x45, Q931ReleaseMsg = 0x4d, Q931ReleaseCompleteMsg = 0x5a, Q931RestartMsg = 0x46, Q931RestartAckMsg = 0x4e, Q931SegmentMsg = 0x60, Q931CongestionCtrlMsg = 0x79, Q931InformationMsg = 0x7b, Q931NotifyMsg = 0x6e, Q931StatusMsg = 0x7d, Q931StatusEnquiryMsg = 0x75, Q931FacilityMsg = 0x62 }
- enum Q931IECodes { Q931BearerCapabilityIE = 0x04, Q931CauseIE = 0x08, Q931FacilityIE = 0x1c, Q931ProgressIndicatorIE = 0x1e, Q931CallStateIE = 0x14, Q931DisplayIE = 0x28, Q931SignalIE = 0x34, Q931CallingPartyNumberIE = 0x6c, Q931CalledPartyNumberIE = 0x70, Q931RedirectingNumberIE = 0x74, Q931UserUserIE = 0x7e }
- enum Q931InformationTransferCapability { Q931TransferSpeech,
 Q931TransferUnrestrictedDigital = 8, Q931TransferRestrictedDigital = 9,
 Q931Transfer3_1kHzAudio = 16, Q931TrasnferUnrestrictedDigitalWithTones = 17,
 Q931TransferVideo = 24 }
- enum Q931CauseValues { Q931NoRouteToNetwork = 0x02, Q931NoRouteToDestination = 0x03, Q931ChannelUnacceptable = 0x06, Q931NormalCallClearing = 0x10, Q931UserBusy = 0x11, Q931NoResponse = 0x12, Q931NoAnswer = 0x13, Q931SubscriberAbsent = 0x14, Q931CallRejected = 0x15, Q931NumberChanged = 0x16, Q931Redirection = 0x17, Q931DestinationOutOfOrder = 0x1b, Q931InvalidNumberFormat = 0x1c, Q931StatusEnquiryResponse = 0x1e, Q931NoCircuitChannelAvailable = 0x22, Q931Congestion = 0x2a, Q931InvalidCallReference = 0x51, Q931ErrorInCauseIE = 0 }
- enum Q931SignalInfo { Q931SignalDialToneOn, Q931SignalRingBackToneOn,
 Q931SignalInterceptToneOn, Q931SignalNetworkCongestionToneOn, Q931SignalBusyToneOn,
 Q931SignalConfirmToneOn, Q931SignalAnswerToneOn, Q931SignalCallWaitingTone,
 Q931SignalOffhookWarningTone, Q931SignalPreemptionToneOn, Q931SignalTonesOff = 0x3f,
 Q931SignalAlertingPattern0 = 0x40, Q931SignalAlertingPattern1, Q931SignalAlertingPattern2,
 Q931SignalAlertingPattern3, Q931SignalAlertingPattern4, Q931SignalAlertingPattern5,
 Q931SignalAlertingPattern6, Q931SignalAlertingPattern7, Q931SignalAlertingOff = 0x4f,
 O931SignalErrorInIE = 0x100 }
- enum Q931NumberingPlanCodes { Q931UnknownPlan = 0x00, Q931ISDNPlan = 0x01, Q931DataPlan = 0x03, Q931TelexPlan = 0x04, Q931NationalStandardPlan = 0x08, Q931PrivatePlan = 0x09, Q931ReservedPlan = 0x0f }
- enum Q931TypeOfNumberCodes { Q931UnknownType = 0x00, Q931InternationalType = 0x01, Q931NationalType = 0x02, Q931NetworkSpecificType = 0x03, Q931SubscriberType = 0x04, Q931AbbreviatedType = 0x06, Q931ReservedType = 0x07 }

Functions

- EXTERN int **ooOnReceivedSetup** (**ooCallData** *call, **Q931Message** *q931Msg) *This function is used to process a received SETUP message.*
- EXTERN int **ooOnReceivedSignalConnect** (**ooCallData** *call, **Q931Message** *q931Msg) *This function is used to process a received CONNECT message.*
- EXTERN int **ooHandleH2250Message** (**ooCallData** *call, **Q931Message** *q931Msg) *This function is used to handle received H.2250 messages.*

- EXTERN int **ooOnReceivedFacility** (**ooCallData** *call, **Q931Message** *pQ931Msg) *This function is used to process a received Facility message.*
- EXTERN int ooHandleTunneledH245Messages (ooCallData *call, H225H323_UU_PDU *pH323UUPdu)

This function is used to process tunneled H245 messages.

- EXTERN int **ooHandleStartH245FacilityMessage** (**ooCallData** *call, H225Facility_UUIE *facility) *This is a helper function used to handle an startH245 Facility message.*
- EXTERN int **ooRetrieveAliases** (**ooCallData** *call, H225_SeqOfH225AliasAddress *pAddresses) *This function is used to retrieve the aliases from Sequence of alias addresses.*
- EXTERN int **ooQ931Decode** (**Q931Message** *msg, int length, ASN1OCTET *data) *This function is invoked to decode a Q931 message.*
- EXTERN int **ooDecodeUUIE** (**Q931Message** *q931Msg)

 This function is used to decode the UUIE of the message from the list of ies.
- EXTERN int **ooEncodeUUIE** (**Q931Message** *q931msg)

 This function is used to encode the UUIE field of the Q931 message.
- EXTERN Q931InformationElement * **ooQ931GetIE** (const **Q931Message** *q931msg, int ieCode) *This function is invoked to retrieve an IE element from a Q931 message.*
- EXTERN void **ooQ931Print** (const **Q931Message** *q931msg) *This function is invoked to print a Q931 message.*
- EXTERN int ooCreateQ931Message (Q931Message **msg, int msgType) This function is invoked to create an outgoing Q931 message.
- EXTERN ASN1USINT **ooGenerateCallReference** ()

 This function is invoked to generate a unique call reference number.
- EXTERN int **ooGenerateCallIdentifier** (H225CallIdentifier *callid) *This function is used to generate a unique call identifier for the call.*
- EXTERN int ooFreeQ931Message (Q931Message *q931Msg)

 This function is invoked to release the memory used up by a Q931 message.
- EXTERN int **ooGetOutgoingQ931Msgbuf** (**ooCallData** *call, ASN1OCTET *msgbuf, int *len, int *msgType)

This function is invoked to retrive the outgoing message buffer for Q931 message.

• EXTERN int ooSendReleaseComplete (ooCallData *call)

This function is invoked to send a ReleaseComplete message for the currently active call.

• EXTERN int ooSendCallProceeding (ooCallData *call)

This function is invoked to send a call proceeding message in response to received setup message.

• EXTERN int ooSendAlerting (ooCallData *call)

This function is invoked to send alerting message in response to received setup message.

• EXTERN int **ooSendFacility** (**ooCallData** *call)

This function is invoked to send Facility message.

• EXTERN int ooSendConnect (ooCallData *call)

This function is invoked to send a Connect message in response to received setup message.

• EXTERN int **ooH323MakeCall** (char *dest, char *callToken)

This function is used to send a SETUP message for outgoing call.

• int ooH323CallAdmitted (ooCallData *call)

Helper function used to make a call once it is approved by the Gk.

• EXTERN int **ooH323HangCall** (char *callToken)

This function is used to handup a currently active call.

• EXTERN int ooAcceptCall (ooCallData *call)

Function to accept a call by sending connect.

• EXTERN int ooH323MakeCall_helper (ooCallData *call)

An helper function to ooMakeCall.

• int **ooParseDestination** (**ooCallData** *call, char *dest)

This function is used to parse the destination.

Function Documentation

EXTERN int ooAcceptCall (ooCallData * call)

Function to accept a call by sending connect.

This function is used as a helper function to ooSendConnect.

Parameters:

call Pointer to the call for which connect has to be sent

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooCreateQ931Message (Q931Message ** msg, int msgType)

This function is invoked to create an outgoing Q931 message.

Parameters:

msg Reference to the pointer of type Q931 message. msgType Type of Q931 message to be created

Returns:

Completion status - 0 on success, -1 on failure

EXTERN int ooDecodeUUIE (Q931Message * q931Msg)

This function is used to decode the UUIE of the message from the list of ies.

It decodes the User-User ie and populates the userInfo field of the message.

Parameters:

q931Msg Pointer to the message whose User-User ie has to be decoded.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooEncodeUUIE (Q931Message * q931msg)

This function is used to encode the UUIE field of the Q931 message.

It encodes UUIE and adds the encoded data to the list of ies.

Parameters:

q931msg Pointer to the Q931 message whose UUIE field has to be encoded.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooFreeQ931Message (Q931Message * q931Msg)

This function is invoked to release the memory used up by a Q931 message.

Parameters:

q931Msg Pointer to a Q931 message which has to be freed.

Returns:

Completion status - 0 on success, -1 on failure

EXTERN int ooGenerateCallIdentifier (H225CallIdentifier * callid)

This function is used to generate a unique call identifier for the call.

Parameters:

callid Pointer to the callid structure, which will be populated with the generated callid.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN ASN1USINT ooGenerateCallReference ()

This function is invoked to generate a unique call reference number.

Parameters:

None

Returns:

- call reference number

EXTERN int ooGetOutgoingQ931Msgbuf (ooCallData * call, ASN1OCTET * msgbuf, int * len, int * msgType)

This function is invoked to retrive the outgoing message buffer for Q931 message.

Parameters:

call Pointer to call for which outgoing Q931 message has to be retrieved.

msgbuf Pointer to a buffer in which retrieved message will be returned.

len Pointer to int in which length of the buffer will be returned.

msgType Pointer to integer in which message type of the ougoing message is returned.

Returns:

Completion status - 0 on success, -1 on failure

int ooH323CallAdmitted (ooCallData * call)

Helper function used to make a call once it is approved by the Gk.

In case of no gk, this function is directly called to make a call.

Parameters:

call Handle to the new call.

Returns:

OO_OK, on success. OO_FAILED, on failure

EXTERN int ooH323HangCall (char * callToken)

This function is used to handup a currently active call.

It sets the call state to CLEARING and initiates closing of all logical channels.

Parameters:

callToken Unique token of the call to be hanged.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooH323MakeCall (char * dest, char * callToken)

This function is used to send a SETUP message for outgoing call.

It first creates an H.225 TCP connection with the remote end point and then sends SETUP message over this connection.

Parameters:

dest Destination - IP:Port/alias. callToken Unique token for the new call.

Returns:

OO_OK, on success. OO_FAILED, on failure

EXTERN int ooH323MakeCall_helper (ooCallData * call)

An helper function to ooMakeCall.

Parameters:

call Pointer to the new call.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooHandleH2250Message (ooCallData * call, Q931Message * q931Msg)

This function is used to handle received H.2250 messages.

It calls helper functions based on the type of message received.

Parameters:

call Pointer to the call for which a H.2250 message is received q931Msg Pointer to the received q931Msg

Returns:

OO_OK, on success. OO_FAILED, on failure

EXTERN int ooHandleStartH245FacilityMessage (ooCallData * call, H225Facility_UUIE * facility)

This is a helper function used to handle an startH245 Facility message.

Parameters:

call Handle to the call *facility* Pointer to the facility message.

EXTERN int ooHandleTunneledH245Messages (ooCallData * call, H225H323_UU_PDU * pH323UUPdu)

This function is used to process tunneled H245 messages.

Parameters:

call Handle to the call *pH323UUPdu* Pointer to the pdu containing tunneled messages.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooOnReceivedFacility (ooCallData * call, Q931Message * pQ931Msg)

This function is used to process a received Facility message.

Parameters:

call Handle to the call for which message has been received. *pQ931Msg* Pointer the the received Facility message.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooOnReceivedSetup (ooCallData * call, Q931Message * q931Msg)

This function is used to process a received SETUP message.

Parameters:

call Pointer to call for which SETUP message is received. *q931Msg* Pointer to the received SETUP message.

Returns:

OO OK, on success. OO FAILED, on failure.

EXTERN int ooOnReceivedSignalConnect (ooCallData * call, Q931Message * q931Msg)

This function is used to process a received CONNECT message.

It creates H.245 negotiation channel, and starts TCS and MSD procedures.

Parameters:

call Pointer to call for which CONNECT message is received. *q931Msg* Pointer to the received q931Msg

Returns:

OO_OK, on success. OO_FAILED, on failure.

int ooParseDestination (ooCallData * call, char * dest)

This function is used to parse the destination.

Parameters:

call Handle to the call dest Destination string to be parsed.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooQ931Decode (Q931Message * msg, int length, ASN1OCTET * data)

This function is invoked to decode a Q931 message.

Parameters:

msg Pointer to the Q931 message length Length of the encoded data data Pointer to the data to be decoded

Completion status - 0 on success, -1 on failure

EXTERN Q931InformationElement* ooQ931GetIE (const Q931Message * q931msg, int ieCode)

This function is invoked to retrieve an IE element from a Q931 message.

Parameters:

q931msg Pointer to the Q931 message *ieCode* IE code for the IE element to be retrieved

Returns:

Pointer to a Q931InformationElement contating the IE element.

EXTERN void ooQ931Print (const Q931Message * q931msg)

This function is invoked to print a Q931 message.

Parameters:

q931msg Pointer to the Q931 message

Returns:

- none

EXTERN int ooRetrieveAliases (ooCallData * call, H225_SeqOfH225AliasAddress * pAddresses)

This function is used to retrieve the aliases from Sequence of alias addresses.

Parameters:

call Handle to the call. *pAddresses* Pointer to the sequence of alias addresses.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooSendAlerting (ooCallData * call)

This function is invoked to send alerting message in response to received setup message.

Parameters:

call Pointer to the call for which Alerting message have to be sent.

Returns:

Completion status - 0 on success, -1 on failure

EXTERN int ooSendCallProceeding (ooCallData * call)

This function is invoked to send a call proceeding message in response to received setup message.

Parameters:

call Pointer to the call for which CallProceeding message have to be sent.

Returns:

Completion status - 0 on success, -1 on failure

EXTERN int ooSendConnect (ooCallData * call)

This function is invoked to send a Connect message in response to received setup message.

Parameters:

call Pointer to the call for which connect message has to be sent.

Returns:

Completion status - 0 on success, -1 on failure

EXTERN int ooSendFacility (ooCallData * call)

This function is invoked to send Facility message.

Parameters:

call Pointer to the call for which Facility message have to be sent.

Returns:

Completion status - 0 on success, -1 on failure

EXTERN int ooSendReleaseComplete (ooCallData * call)

This function is invoked to send a ReleaseComplete message for the currently active call.

Parameters:

call Pointer to the call for which ReleaseComplete message have to be sent.

Returns:

Completion status - 0 on success, -1 on failure

RAS Channel and Message handling

Data Structures

- struct ooRasMessage

 Defines the RAS message structure.
- struct ooRasParams

Typedefs

• typedef **ooRasMessage ooRasMessage**Defines the RAS message structure.

Enumerations

- enum RasGatekeeperMode { RasNoGatekeeper = 0, RasDiscoverGatekeeper = 1, RasUseSpecificGatekeeper = 2 }
- enum RasCallModel { RasDirect = 0, RasGkRouted }
- enum RasCallType { RasPointToPoint = 0, RasOneToN, RasnToOne, RasnToN }

Functions

 EXTERN int ooInitRas (int localRasPort, enum RasGatekeeperMode eGkMode, char *szGkAddr, int iGkPort)

This function is used to initialize the Ras module by setting gatekeeper mode and Creating Ras Channel.

EXTERN int ooDestroyRas (void)

This function is used to destroy RasModule.

• EXTERN void **ooRasExplorer** ()

This function is called periodically to monitor the process the RAS channel.

• EXTERN int **ooRasFillAlias** (OOCTXT *psContext, ooAliases *psAliases, H225_SeqOfH225AliasAddress *psAliasList)

Populate Alias list.

• EXTERN OOSOCKET ooRasGetSocket ()

This function is invoked to get current RAS socket.

• EXTERN int ooRasReceive ()

This function is invoked receive data from RAS port.

 EXTERN int ooRasSetGatekeeperMode (enum RasGatekeeperMode eGkMode, char *szGkAddr, int iGkPort)

This function is invoked to set a gatekeeper mode.

• EXTERN enum RasGatekeeperMode ooRasGetGatekeeperMode ()

This function is invoked to get current gatekeeper mode.

• EXTERN ASN1BOOL ooRasIsRegistered ()

This function is used to determine the registration status of the endpoint with the gatekeeper.

EXTERN int ooRasSendAdmissionRequest (ooCallData *call, enum RasCallModel eModel, ooAliases *psSrcAliases, ooAliases *psDestAliases)
 This function is invoked to request bandwith admission for a call.

• EXTERN int ooRasSendDisengageRequest (ooCallData *call)

This function is invoked to request call disengage to gatekeeper.

Typedef Documentation

typedef struct ooRasMessage ooRasMessage

Defines the RAS message structure.

Contains context for memory allocation, protocol Discriminator, call reference, meesage type and list of user user IEs.

Function Documentation

EXTERN int ooDestroyRas (void)

This function is used to destroy RasModule.

It releases all the associated memory.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int oolnitRas (int *localRasPort*, enum RasGatekeeperMode eGkMode, char * szGkAddr, int iGkPort)

This function is used to initialize the Ras module by setting gatekeeper mode and Creating Ras Channel.

Parameters:

localRasPort local port to be used for RAS channeleGkMode Gatekeeper mode.szGkAddr Dotted gk ip address, if gk has to be specified.iGkPort Gk port.

Returns:

OO OK, on success. OO FAILED, on failure.

EXTERN int ooRasFillAlias (OOCTXT * psContext, ooAliases * psAliases, H225_SeqOfH225AliasAddress * psAliasList)

Populate Alias list.

Parameters:

psContext Context to be used for allocating memory for alias list. psAliases List of aliases from which alias list structure has to be populated. psAliasList Alias list structure which has to be populated.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN enum RasGatekeeperMode ooRasGetGatekeeperMode ()

This function is invoked to get current gatekeeper mode.

Returns:

Gatekeeper mode selected. One of the following:

- RasNoGatekeeper (DEFAULT), No Gatekeeper.
- RasDiscoverGatekeeper, to discover a gatekeeper automatically.
- RasUseSpecificGatekeeper, to use a specific gatekeeper.

EXTERN OOSOCKET ooRasGetSocket ()

This function is invoked to get current RAS socket.

Returns:

RAS socket.

EXTERN ASN1BOOL ooRasIsRegistered ()

This function is used to determine the registration status of the endpoint with the gatekeeper.

Returns:

TRUE, if registered, FALSE otherwise.

EXTERN int ooRasReceive ()

This function is invoked receive data from RAS port.

Returns:

Completion status - 0 on success, -1 on failure

EXTERN int ooRasSendAdmissionRequest (ooCallData * call, enum RasCallModel eModel, ooAliases * psSrcAliases, ooAliases * psDestAliases)

This function is invoked to request bandwith admission for a call.

Parameters:

call Handle to the call.

eModel Call Model (RasDirect/RasGkRouted)

psSrcAliases Pointer to the calling party's aliases.

psDestAliases Pointer to the called party's aliases.

Returns:

OO_OK, on success. OO_FAILED, on failure. Completion status - 0 on success, -1 on failure

EXTERN int ooRasSendDisengageRequest (ooCallData * call)

This function is invoked to request call disengage to gatekeeper.

Parameters:

call Call Handle

Returns:

Completion status - 0 on success, -1 on failure

EXTERN int ooRasSetGatekeeperMode (enum RasGatekeeperMode eGkMode, char * szGkAddr, int iGkPort)

This function is invoked to set a gatekeeper mode.

Parameters:

eGkMode Gatekeeper mode selected. One of the following:

- RasNoGatekeeper (DEFAULT), No Gatekeeper.
- RasDiscoverGatekeeper, to discover a gatekeeper automatically.
- RasUseSpecificGatekeeper, to use a specific gatekeeper.

szGkAddr Gatekeeper address (only when using specific gatekeeper). iGkPort Gatekeeper RAS port

Returns:

Completion status - 0 on success, -1 on failure

Media plug-in Interface definitions

Typedefs

- typedef int(* **MediaAPI_CreateTxRTPChan**)(int *channelId, char *destip, int port) Signature for function to Create Tx RTP channel.
- typedef int(* **MediaAPI_CloseTxRTPChan**)(int) Signature for function to Close Tx RTP channel.
- typedef int(* **MediaAPI_CreateRecvRTPChan**)(int *channelId, char *localip, int localport) Signature for function to Create Rx RTP channel.
- typedef int(* **MediaAPI_CloseRecvRTPChan**)(int) Signature for function to Close Rx RTP channel.

- typedef int(* **MediaAPI_StartTxWaveFile**)(int channelId, char *filename)

 Signature for function to Start transmission of media file.
- typedef int(* MediaAPI_StopTxWaveFile)(int channelld)
 Signature for function to Stop transmission of media file.
- typedef int(* **MediaAPI_StartTxMic**)(int channelId)

 Signature for function to Start transmitting captured audio from microphone.
- typedef int(* MediaAPI_StopTxMic)(int channelId)
 Signature for function to Stop transmitting microphone data.
- typedef int(* MediaAPI_StartRecvAndPlayback)(int channelId) Signature for function to Start receiving rtp data and playback.
- typedef int(* **MediaAPI_StopRecvAndPlayback**)(int channelId) Signature for function to stop receiving rtp data.
- typedef int(* MediaAPI_InitializePlugin)(void) Signature for function to Initialize the media plug-in.

Media plugin support functions

Functions

- EXTERN int **ooLoadSndRTPPlugin** (char *name) *Loads the media plugin into the process space.*
- EXTERN int **ooReleaseSndRTPPlugin** (void) *Unloads the plug-in from process space.*
- EXTERN int **ooCreateTransmitRTPChannel** (char *destip, int port) *Creates a transmit RTP channel.*
- EXTERN int **ooCloseTransmitRTPChannel** (void) *Closes a transmit RTP channel*.
- EXTERN int **ooCreateReceiveRTPChannel** (char *localip, int localport) *Creates a receive RTP channel*.
- EXTERN int **ooCloseReceiveRTPChannel** (void) *Closes a receive RTP channel*.

• EXTERN int **ooStartTransmitWaveFile** (char *filename)

Start transmitting a audio file.

• EXTERN int ooStopTransmitWaveFile (void)

Stop transmission of a audio file.

• EXTERN int ooStartTransmitMic (void)

Starts capturing audio data from mic and transmits it as rtp stream.

• EXTERN int ooStopTransmitMic (void)

Stop transmission of mic audio data.

• EXTERN int ooStartReceiveAudioAndPlayback (void)

Starts receiving rtp stream data and play it on the speakers.

• EXTERN int ooStopReceiveAudioAndPlayback (void)

Stop receiving rtp stream data. This calls corresponding interface function of the plug-in library.

• EXTERN int ooStartReceiveAudioAndRecord (void)

Not supported currently.

• EXTERN int ooStopReceiveAudioAndRecord (void)

Not supported currently.

• EXTERN int ooSetLocalRTPAndRTCPAddrs (void)

Set local RTP and RTCP addresses for the session.

• EXTERN int ooRTPShutDown (void)

Closes transmit and receive RTP channels, if open.

Variables

• void * media

Function Documentation

EXTERN int ooCloseReceiveRTPChannel (void)

Closes a receive RTP channel.

Basically calls the corresponding function of the plug-in library.

Completion status - 0 on success, -1 on failure

EXTERN int ooCloseTransmitRTPChannel (void)

Closes a transmit RTP channel.

Basically calls the corresponding function of the plug-in library.

Returns:

Completion status - 0 on success, -1 on failure

EXTERN int ooCreateReceiveRTPChannel (char * localip, int localport)

Creates a receive RTP channel.

Basically calls the corresponding function of the plug-in library.

Parameters:

localip IP address of the endpoint where RTP data will be received. *localport* Port number of the local endpoint

Returns:

Completion status - 0 on success, -1 on failure

EXTERN int ooCreateTransmitRTPChannel (char * destip, int port)

Creates a transmit RTP channel.

Basically calls the corresponding function of the plug-in library.

Parameters:

destip IP address of the destination endpoint. *port* Destination port number.

Returns:

Completion status - 0 on success, -1 on failure

EXTERN int ooLoadSndRTPPlugin (char * name)

Loads the media plugin into the process space.

Parameters:

name Name of the media plug-in library.

Completion status - 0 on success, -1 on failure

EXTERN int ooReleaseSndRTPPlugin (void)

Unloads the plug-in from process space.

Returns:

Completion status - 0 on success, -1 on failure

EXTERN int ooRTPShutDown (void)

Closes transmit and receive RTP channels, if open.

This calls corresponding interface functions to close the channels.

Returns:

Completion status - 0 on success, -1 on failure

EXTERN int ooSetLocalRTPAndRTCPAddrs (void)

Set local RTP and RTCP addresses for the session.

This function gets next available ports for RTP and RTCP communication.

Returns:

Completion status - 0 on success, -1 on failure

EXTERN int ooStartReceiveAudioAndPlayback (void)

Starts receiving rtp stream data and play it on the speakers.

This calls corresponding interface function of the plug-in library.

Returns:

Completion status - 0 on success, -1 on failure

EXTERN int ooStartTransmitMic (void)

Starts capturing audio data from mic and transmits it as rtp stream.

This calls corresponding interface function of the plug-in library.

Completion status - 0 on success, -1 on failure

EXTERN int ooStartTransmitWaveFile (char * filename)

Start transmitting a audio file.

This calls corresponding function of the plug-in library.

Parameters:

filename Name of the file to be played.

Returns:

Completion status - 0 on success, -1 on failure

EXTERN int ooStopReceiveAudioAndPlayback (void)

Stop receiving rtp stream data. This calls corresponding interface function of the plug-in library.

Returns:

Completion status - 0 on success, -1 on failure

EXTERN int ooStopTransmitMic (void)

Stop transmission of mic audio data.

This calls corresponding interface function of the plug-in library.

Returns:

Completion status - 0 on success, -1 on failure

EXTERN int ooStopTransmitWaveFile (void)

Stop transmission of a audio file.

This calls corresponding function of the plug-in library.

Returns:

Completion status - 0 on success, -1 on failure

Socket Layer

Defines

- #define OOSOCKET INVALID ((OOSOCKET)-1)
- #define OOIPADDR_ANY ((OOIPADDR)0)
- #define **OOIPADDR_LOCAL** ((**OOIPADDR**)0x7f000001UL) /* 127.0.0.1 */

Typedefs

• typedef int OOSOCKET

Socket's handle.

typedef unsigned long OOIPADDR

The IP address represented as unsigned long value.

Functions

 EXTERN int ooSocketAccept (OOSOCKET socket, OOSOCKET *pNewSocket, OOIPADDR *destAddr, int *destPort)

This function permits an incoming connection attempt on a socket.

 $\bullet \quad \text{EXTERN int } \textbf{ooSocketAddrToStr} \ (\textbf{OOIPADDR} \ \text{ipAddr, char *pbuf, int bufsize}) \\$

This function converts an IP address to its string representation.

• EXTERN int ooSocketBind (OOSOCKET socket, OOIPADDR addr, int port)

This function associates a local address with a socket.

• EXTERN int ooSocketClose (OOSOCKET socket)

This function closes an existing socket.

• EXTERN int ooSocketConnect (OOSOCKET socket, const char *host, int port)

This function establishes a connection to a specified socket.

• EXTERN int ooSocketCreate (OOSOCKET *psocket)

This function creates a socket.

• EXTERN int ooSocketCreateUDP (OOSOCKET *psocket)

This function creates a UDP datagram socket.

• EXTERN int ooSocketsInit (void)

This function initiates use of sockets by an application.

• EXTERN int ooSocketsCleanup (void)

This function terminates use of sockets by an application.

• EXTERN int **ooSocketListen** (**OOSOCKET** socket, int maxConnection)

This function places a socket a state where it is listening for an incoming connection.

• EXTERN int ooSocketRecv (OOSOCKET socket, ASN1OCTET *pbuf, ASN1UINT bufsize)

This function receives data from a connected socket.

• EXTERN int **ooSocketRecvFrom** (**OOSOCKET** socket, ASN1OCTET *pbuf, ASN1UINT bufsize, char *remotehost, int *remoteport)

This function receives data from a connected/unconnected socket.

 $\bullet \quad \text{EXTERN int } \textbf{ooSocketSend} \ (\textbf{OOSOCKET} \ \text{socket, const ASN1OCTET} \ *p \text{data, ASN1UINT size}) \\$

This function sends data on a connected socket.

• EXTERN int ooSocketSendTo (OOSOCKET socket, const ASN1OCTET *pdata, ASN1UINT size,

const char *remotehost, int remoteport)

This function sends data on a connected or unconnected socket.

• EXTERN int **ooSocketSelect** (int nfds, fd_set *readfds, fd_set *writefds, fd_set *exceptfds, struct timeval *timeout)

This function is used for synchronous monitoring of multiple sockets.

• EXTERN int ooSocketStrToAddr (const char *pIPAddrStr, OOIPADDR *pIPAddr)

This function converts the string with IP address to a double word representation.

• EXTERN int **ooGetLocalIPAddress** (char *pIPAddrs)

This function retrives the IP address of the local host.

- EXTERN long **ooHTONL** (long val)
- EXTERN short **ooHTONS** (short val)

Typedef Documentation

typedef unsigned long OOIPADDR

The IP address represented as unsigned long value.

The most significant 8 bits in this unsigned long value represent the first number of the IP address. The least significant 8 bits represent the last number of the IP address.

Definition at line 79 of file ooSocket.h.

Function Documentation

EXTERN int ooGetLocallPAddress (char * pIPAddrs)

This function retrives the IP address of the local host.

Parameters:

pIPAddrs Pointer to a char buffer in which local IP address will be returned.

Returns:

Completion status of operation: 0 (ASN OK) = success, negative return value is error.

EXTERN int ooSocketAccept (OOSOCKET socket, OOSOCKET * pNewSocket, OOIPADDR * destAddr, int * destPort)

This function permits an incoming connection attempt on a socket.

It extracts the first connection on the queue of pending connections on socket. It then creates a new socket and returns a handle to the new socket. The newly created socket is the socket that will handle the actual connection and has the same properties as original socket. See description of 'accept' socket function for further details.

Parameters:

socket The socket's handle created by call to ::rtSocketCreate function.

pNewSocket The pointer to variable to receive the new socket's handle.

destAddr Optional pointer to a buffer that receives the IP address of the connecting entity. It may be NULL.

destPort Optional pointer to a buffer that receives the port of the connecting entity. It may be NULL.

Returns:

Completion status of operation: 0 (ASN_OK) = success, negative return value is error.

EXTERN int ooSocketAddrToStr (OOIPADDR ipAddr, char * pbuf, int bufsize)

This function converts an IP address to its string representation.

Parameters:

ipAddr The IP address to be converted.

 $\it pbuf$ Pointer to the buffer to receive a string with the IP address.

bufsize Size of the buffer.

Returns:

Completion status of operation: 0 (ASN_OK) = success, negative return value is error.

EXTERN int ooSocketBind (OOSOCKET socket, OOIPADDR addr, int port)

This function associates a local address with a socket.

It is used on an unconnected socket before subsequent calls to the ::rtSocketConnect or ::rtSocketListen functions. See description of 'bind' socket function for further details.

Parameters:

socket The socket's handle created by call to ::rtSocketCreate function. addr The local IP address to assign to the socket.

port The local port number to assign to the socket.

Returns:

Completion status of operation: 0 (ASN_OK) = success, negative return value is error.

EXTERN int ooSocketClose (OOSOCKET socket)

This function closes an existing socket.

Parameters:

socket The socket's handle created by call to ::rtSocketCreate or ::rtSocketAccept function.

Returns:

Completion status of operation: 0 (ASN_OK) = success, negative return value is error.

EXTERN int ooSocketConnect (OOSOCKET socket, const char * host, int port)

This function establishes a connection to a specified socket.

It is used to create a connection to the specified destination. When the socket call completes successfully, the socket is ready to send and receive data. See description of 'connect' socket function for further details.

Parameters:

socket The socket's handle created by call to ::rtSocketCreate function. host The null-terminated string with the IP address in the following format: "NNN.NNN.NNN.NNN", where NNN is a number in the range (0..255). port The destination port to connect.

Returns:

Completion status of operation: 0 (ASN_OK) = success, negative return value is error.

EXTERN int ooSocketCreate (OOSOCKET * psocket)

This function creates a socket.

The only streaming TCP/IP sockets are supported at the moment.

Parameters:

psocket The pointer to the socket's handle variable to receive the handle of new socket.

Returns:

Completion status of operation: 0 (ASN_OK) = success, negative return value is error.

EXTERN int ooSocketCreateUDP (OOSOCKET * psocket)

This function creates a UDP datagram socket.

Parameters:

psocket The pointer to the socket's handle variable to receive the handle of new socket.

Returns:

Completion status of operation: 0 (ASN OK) = success, negative return value is error.

EXTERN int ooSocketListen (OOSOCKET socket, int maxConnection)

This function places a socket a state where it is listening for an incoming connection.

To accept connections, a socket is first created with the ::rtSocketCreate function and bound to a local address with the ::rtSocketBind function, a maxConnection for incoming connections is specified with ::rtSocketListen, and then the connections are accepted with the ::rtSocketAccept function. See description of 'listen' socket function for further details.

Parameters:

socket The socket's handle created by call to ::rtSocketCreate function. *maxConnection* Maximum length of the queue of pending connections.

Returns:

Completion status of operation: 0 (ASN_OK) = success, negative return value is error.

EXTERN int ooSocketRecv (OOSOCKET socket, ASN1OCTET * pbuf, ASN1UINT bufsize)

This function receives data from a connected socket.

It is used to read incoming data on sockets. The socket must be connected before calling this function. See description of 'recv' socket function for further details.

Parameters:

socket The socket's handle created by call to ::rtSocketCreate or ::rtSocketAccept function. pbuf Pointer to the buffer for the incoming data. bufsize Length of the buffer.

Returns:

If no error occurs, returns the number of bytes received. Otherwise, the negative value is error code.

EXTERN int ooSocketRecvFrom (OOSOCKET socket, ASN1OCTET * pbuf, ASN1UINT bufsize, char * remotehost, int * remoteport)

This function receives data from a connected/unconnected socket.

It is used to read incoming data on sockets. It populates the remotehost and remoteport parameters with information of remote host. See description of 'recvfrom' socket function for further details.

Parameters:

socket The socket's handle created by call to ooSocketCreate
pbuf Pointer to the buffer for the incoming data.
bufsize Length of the buffer.
remotehost Pointer to a buffer in which remote ip address will be returned.
remoteport Pointer to an int in which remote port number will be returned.

Returns:

If no error occurs, returns the number of bytes received. Otherwise, the negative value is error code.

EXTERN int ooSocketsCleanup (void)

This function terminates use of sockets by an application.

This function must be called after done with sockets.

Returns:

Completion status of operation: 0 (ASN_OK) = success, negative return value is error.

EXTERN int ooSocketSelect (int *nfds*, fd_set * *readfds*, fd_set * *writefds*, fd_set * *exceptfds*, struct timeval * *timeout*)

This function is used for synchronous monitoring of multiple sockets.

For more information refer to documnetation of "select" system call.

Parameters:

nfds The highest numbered descriptor to be monitored plus one.

readfds The descriptors listed in readfds will be watched for whether read would block on them. writefds The descriptors listed in writefds will be watched for whether write would block on them. exceptfds The descriptors listed in exceptfds will be watched for exceptions. timeout Upper bound on amout of time elapsed before select returns.

Returns:

Completion status of operation: 0 (ASN_OK) = success, negative return value is error.

EXTERN int ooSocketSend (OOSOCKET socket, const ASN1OCTET * pdata, ASN1UINT size)

This function sends data on a connected socket.

It is used to write outgoing data on a connected socket. See description of 'send' socket function for further details.

Parameters:

socket The socket's handle created by call to ::rtSocketCreate or ::rtSocketAccept function. pdata Buffer containing the data to be transmitted. size Length of the data in pdata.

Returns:

Completion status of operation: 0 (ASN_OK) = success, negative return value is error.

EXTERN int ooSocketSendTo (OOSOCKET socket, const ASN1OCTET * pdata, ASN1UINT size, const char * remotehost, int remoteport)

This function sends data on a connected or unconnected socket.

See description of 'sendto' socket function for further details.

Parameters:

socket The socket's handle created by call to ::rtSocketCreate or ::rtSocketAccept function. pdata Buffer containing the data to be transmitted.

size Length of the data in pdata.

remotehost Remote host ip address to which data has to be sent. remoteport Remote port ip address to which data has to be sent.

Returns:

Completion status of operation: 0 (ASN_OK) = success, negative return value is error.

EXTERN int ooSocketsInit (void)

This function initiates use of sockets by an application.

This function must be called first before use sockets.

Completion status of operation: 0 (ASN_OK) = success, negative return value is error.

EXTERN int ooSocketStrToAddr (const char * pIPAddrStr, OOIPADDR * pIPAddr)

This function converts the string with IP address to a double word representation.

The converted address may be used with the ::rtSocketBind function.

Parameters:

pIPAddrStr The null-terminated string with the IP address in the following format: "NNN.NNN.NNN.NNN", where NNN is a number in the range (0..255). *pIPAddr* Pointer to the converted IP address.

Returns:

Completion status of operation: 0 (ASN_OK) = success, negative return value is error.

Stack Control Commands

Functions

- EXTERN int **ooMakeCall** (char *dest, char *callToken) *This function is used by an application to place a call.*
- EXTERN int **ooAnswerCall** (char *callToken) *This function is used to answer a call.*
- EXTERN int **ooRejectCall** (char *callToken, int cause) *This function is used to reject an incoming call.*
- EXTERN int **ooHangCall** (char *callToken)

 This function is used by an user application to hang a call.
- EXTERN int ooStopMonitor (void)
 This function is used by the user application to stop monitoring calls.

Function Documentation

EXTERN int ooAnswerCall (char * callToken)

This function is used to answer a call.

Parameters:

callToken Unique token for the call

Returns:

OO_OK, on success. OO_FAILED, otherwise.

EXTERN int ooHangCall (char * callToken)

This function is used by an user application to hang a call.

Parameters:

callToken The uinque token for the call.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooMakeCall (char * dest, char * callToken)

This function is used by an application to place a call.

Parameters:

dest Call Destination - IP:port / alias callToken Pointer to a buffer in which callToken will be returned

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooRejectCall (char * callToken, int cause)

This function is used to reject an incoming call.

Parameters:

callToken Unique token for the call. *cause* Cause for rejecting the call.

Returns:

OO_OK, on success. OO_FAILED, on failure.

EXTERN int ooStopMonitor (void)

This function is used by the user application to stop monitoring calls.

Parameters:

None

Returns:

OO_OK, on success. OO_FAILED, on failure.

Rtmem

Defines

- #define **memAlloc**(pctxt, nbytes) memHeapAlloc(&(pctxt)->pTypeMemHeap,nbytes) *Allocate memory*.
- #define **memAllocZ**(pctxt, nbytes) memHeapAllocZ(&(pctxt)->pTypeMemHeap,nbytes) *Allocate and zero memory*.
- #define memRealloc(pctxt, mem_p, nbytes) memHeapRealloc(&(pctxt)->pTypeMemHeap, (void*)mem_p, nbytes)
 Reallocate memory.
- #define **memFreePtr**(pctxt, mem_p)

Free memory pointer.

- #define **memFree**(pctxt) memHeapFreeAll(&(pctxt)->pTypeMemHeap) *Free memory associated with a context.*
- #define **memReset**(pctxt) memHeapReset(&(pctxt)->pTypeMemHeap) *Reset memory associated with a context.*
- #define **OSCDECL**
- #define **INCRBITIDX**(pctxt)
- #define **DECODEBIT**(pctxt, pvalue)
- #define decodeUnconsInteger(pctxt, pvalue) decodeSemiConsInteger(pctxt, pvalue, ASN1INT_MIN)

This function will decode an unconstrained integer.

- #define **decodeUnconsUnsigned**(pctxt, pvalue) decodeSemiConsUnsigned(pctxt, pvalue, 0U) *This function will decode an unconstrained unsigned integer*.
- #define encodeUnconsInteger(pctxt, value) encodeSemiConsInteger(pctxt,value,ASN1INT_MIN)
 This function encodes an unconstrained integer.

Typedefs

- typedef void *OSCDECL * **OSMallocFunc** (size_t size)
- typedef void *OSCDECL * **OSReallocFunc** (void *ptr, size_t size)

Functions

- typedef **void** (OSCDECL *OSFreeFunc)(void *ptr)
- EXTERN void **memHeapAddRef** (void **ppvMemHeap)
- EXTERN void * memHeapAlloc (void **ppvMemHeap, int nbytes)
- EXTERN void * memHeapAllocZ (void **ppvMemHeap, int nbytes)
- EXTERN int memHeapCheckPtr (void **ppvMemHeap, void *mem_p)
- EXTERN int memHeapCreate (void **ppvMemHeap)
- EXTERN void **memHeapFreeAll** (void **ppvMemHeap)
- EXTERN void **memHeapFreePtr** (void **ppvMemHeap, void *mem_p)
- EXTERN void * memHeapRealloc (void **ppvMemHeap, void *mem_p, int nbytes_)
- EXTERN void **memHeapRelease** (void **ppvMemHeap)
- EXTERN void **memHeapReset** (void **ppvMemHeap)
- EXTERN void * memHeapMarkSaved (void **ppvMemHeap, const void *mem_p, ASN1BOOL saved)
- EXTERN void memHeapSetProperty (void **ppvMemHeap, ASN1UINT propId, void *pProp)
- EXTERN void memSetAllocFuncs (OSMallocFunc malloc_func, OSReallocFunc realloc_func, OSFreeFunc free_func)

This function sets the pointers to standard allocation functions.

- EXTERN void memFreeOpenSegExt (OOCTXT *pctxt, DList *pElemList)
- EXTERN void memHeapSetFlags (OOCTXT *pctxt, ASN1UINT flags)
- EXTERN void memHeapClearFlags (OOCTXT *pctxt, ASN1UINT flags)
- EXTERN void memHeapSetDefBlkSize (OOCTXT *pctxt, ASN1UINT blkSize) This function sets the pointer to standard allocation functions.
- EXTERN ASN1UINT memHeapGetDefBlkSize (OOCTXT *pctxt) This function returns the actual granularity of memory blocks.
- EXTERN int **decodeBits** (OOCTXT *pctxt, ASN1UINT *pvalue, ASN1UINT nbits)

 This function will decode a series of multiple bits and place the results in an unsigned integer variable.
- EXTERN int decodeBitString (OOCTXT *pctxt, ASN1UINT *numbits_p, ASN1OCTET *buffer, ASN1UINT bufsiz)

This function will decode a value of the ASN.1 bit string type whose maximum size is is known in advance.

• EXTERN int **decodeBMPString** (OOCTXT *pctxt, ASN1BMPString *pvalue, Asn116BitCharSet *permCharSet)

This function will decode a variable of the ASN.1 BMP character string.

• EXTERN int **decodeByteAlign** (OOCTXT *pctxt)

This function will position the decode bit cursor on the next byte boundary.

• EXTERN int **decodeConsInteger** (OOCTXT *pctxt, ASN1INT *pvalue, ASN1INT lower, ASN1INT upper)

This function will decode an integer constrained either by a value or value range constraint.

• EXTERN int **decodeConsUnsigned** (OOCTXT *pctxt, ASN1UINT *pvalue, ASN1UINT lower, ASN1UINT upper)

This function will decode an unsigned integer constrained either by a value or value range constraint.

• EXTERN int **decodeConsUInt8** (OOCTXT *pctxt, ASN1UINT8 *pvalue, ASN1UINT lower, ASN1UINT upper)

This function will decode an 8-bit unsigned integer constrained either by a value or value range constraint.

 EXTERN int decodeConsUInt16 (OOCTXT *pctxt, ASN1USINT *pvalue, ASN1UINT lower, ASN1UINT upper)

This function will decode a 16-bit unsigned integer constrained either by a value or value range constraint.

• EXTERN int **decodeConsWholeNumber** (OOCTXT *pctxt, ASN1UINT *padjusted_value, ASN1UINT range_value)

This function decodes a constrained whole number as specified in Section 10.5 of the X.691 standard.

• EXTERN int **decodeConstrainedStringEx** (OOCTXT *pctxt, const char **string, const char *charSet, ASN1UINT abits, ASN1UINT ubits, ASN1UINT canSetBits)

This function decodes a constrained string value.

• EXTERN int **decodeDynBitString** (OOCTXT *pctxt, ASN1DynBitStr *pBitStr) *This function will decode a variable of thr ASN.1 BIT STRING type.*

• EXTERN int decodeDynOctetString (OOCTXT *pctxt, ASN1DynOctStr *pOctStr)

This function will decode a value of the ASN.1 octet string type whose maximum size is known in advance.

• EXTERN int **decodeLength** (OOCTXT *pctxt, ASN1UINT *pvalue) *This function will decode a length determinant value.*

- EXTERN int **moveBitCursor** (OOCTXT *pctxt, int bitOffset)
- EXTERN int **decodeObjectIdentifier** (OOCTXT *pctxt, ASN1OBJID *pvalue) *This function decodes a value of the ASN.1 object identifier type.*
- EXTERN int decodeOctetString (OOCTXT *pctxt, ASN1UINT *numocts_p, ASN1OCTET *buffer, ASN1UINT bufsiz)

This function will decode a value of the ASN.1 octet string type whose maximun size is known in advance.

• EXTERN int **decodeOpenType** (OOCTXT *pctxt, const ASN1OCTET **object_p2, ASN1UINT *numocts_p)

This function will decode an ASN.1 open type.

- EXTERN int decodeSmallNonNegWholeNumber (OOCTXT *pctxt, ASN1UINT *pvalue)

 This function will decode a small non-negative whole number as specified in Section 10.6 of the X.691 standard.
- EXTERN int **decodeSemiConsInteger** (OOCTXT *pctxt, ASN1INT *pvalue, ASN1INT lower) *This function will decode a semi-constrained integer.*
- EXTERN int **decodeSemiConsUnsigned** (OOCTXT *pctxt, ASN1UINT *pvalue, ASN1UINT lower) *This function will decode a semi-constrained unsigned integer.*
- EXTERN int **decodeVarWidthCharString** (OOCTXT *pctxt, const char **pvalue)
- EXTERN int **encodeBit** (OOCTXT *pctxt, ASN1BOOL value)

 This function will encode a variable of the ASN.1 BOOLEAN type in a single bit.
- EXTERN int **encodeBits** (OOCTXT *pctxt, ASN1UINT value, ASN1UINT nbits) *This function encodes multiple bits.*
- EXTERN int **encodeBitString** (OOCTXT *pctxt, ASN1UINT numocts, const ASN1OCTET *data) *This function will encode a value of the ASN.1 bit string type.*
- EXTERN int **encodeBMPString** (OOCTXT *pctxt, ASN1BMPString value, Asn116BitCharSet *permCharSet)

This function will encode a variable of the ASN.1 BMP character string.

- EXTERN int encodeByteAlign (OOCTXT *pctxt)
 This function will position the encode bit cursor on the next byte boundry.
- EXTERN int **encodeCheckBuffer** (OOCTXT *pctxt, ASN1UINT nbytes)

 This function will determine if the given number of bytes will fit in the encode buffer.
- EXTERN int **encodeConstrainedStringEx** (OOCTXT *pctxt, const char *string, const char *charSet, ASN1UINT abits, ASN1UINT ubits, ASN1UINT canSetBits)

This function encodes a constrained string value.

• EXTERN int **encodeConsInteger** (OOCTXT *pctxt, ASN1INT value, ASN1INT lower, ASN1INT upper)

This function encodes an integer constrained either by a value or value range constraint.

• EXTERN int **encodeConsUnsigned** (OOCTXT *pctxt, ASN1UINT value, ASN1UINT lower, ASN1UINT upper)

This function encodes an unsigned integer constrained either by a value or value range constraint.

EXTERN int encodeConsWholeNumber (OOCTXT *pctxt, ASN1UINT adjusted_value, ASN1UINT range_value)

This function encodes a constrained whole number as specified in Section 10.5 of the X.691 standard.

- EXTERN int **encodeExpandBuffer** (OOCTXT *pctxt, ASN1UINT nbytes) *This function will expand the buffer to hold the given number of bytes.*
- EXTERN ASN1OCTET * encodeGetMsgPtr (OOCTXT *pctxt, int *pLength) This function will return the message pointer and length of an encoded message.
- EXTERN int **encodeLength** (OOCTXT *pctxt, ASN1UINT value) *This function will encode a length determinant value.*
- EXTERN int **encodeObjectIdentifier** (OOCTXT *pctxt, ASN1OBJID *pvalue) *This function encodes a value of the ASN.1 object identifier type.*
- EXTERN int **encodebitsFromOctet** (OOCTXT *pctxt, ASN1OCTET value, ASN1UINT nbits) *This function encodes bits from a given octet to the output buffer.*
- EXTERN int **encodeOctets** (OOCTXT *pctxt, const ASN1OCTET *pvalue, ASN1UINT nbits) *This fuction will encode an array of octets.*
- EXTERN int **encodeOctetString** (OOCTXT *pctxt, ASN1UINT numocts, const ASN1OCTET *data) *This function will encode a value of the ASN.1 octet string type.*
- EXTERN int **encodeOpenType** (OOCTXT *pctxt, ASN1UINT numocts, const ASN1OCTET *data) *This function will encode an ASN.1 open type.*
- EXTERN int **encodeOpenTypeExt** (OOCTXT *pctxt, DList *pElemList) *This function will encode an ASN.1 open type extension.*
- EXTERN int **encodeOpenTypeExtBits** (OOCTXT *pctxt, DList *pElemList)
- EXTERN int encodeSmallNonNegWholeNumber (OOCTXT *pctxt, ASN1UINT value)

 This function will endcode a small, non-negative whole number as specified in Section 10.6 of teh X.691 standard.

- EXTERN int **encodeSemiConsInteger** (OOCTXT *pctxt, ASN1INT value, ASN1INT lower) *This function encodes a semi-constrained integer.*
- EXTERN int **encodeSemiConsUnsigned** (OOCTXT *pctxt, ASN1UINT value, ASN1UINT lower) *This function encodes an semi-constrained unsigned integer.*
- EXTERN int **encodeVarWidthCharString** (OOCTXT *pctxt, const char *value)
- EXTERN int addSizeConstraint (OOCTXT *pctxt, Asn1SizeCnst *pSize)
- EXTERN ASN1BOOL alignCharStr (OOCTXT *pctxt, ASN1UINT len, ASN1UINT nbits, Asn1SizeCnst *pSize)
- EXTERN int **bitAndOctetStringAlignmentTest** (Asn1SizeCnst *pSizeList, ASN1UINT itemCount, ASN1BOOL bitStrFlag, ASN1BOOL *pAlignFlag)
- EXTERN int **getPERMsgLen** (OOCTXT *pctxt)
- EXTERN Asn1SizeCnst * getSizeConstraint (OOCTXT *pctxt, ASN1BOOL extbit)
- EXTERN int **checkSizeConstraint** (OOCTXT *pctxt, int size)
- EXTERN ASN1UINT getUIntBitCount (ASN1UINT value)
- EXTERN Asn1SizeCnst * checkSize (Asn1SizeCnst *pSizeList, ASN1UINT value, ASN1BOOL *pExtendable)
- EXTERN void **init16BitCharSet** (Asn116BitCharSet *pCharSet, ASN116BITCHAR first, ASN116BITCHAR last, ASN1UINT abits, ASN1UINT ubits)
- EXTERN ASN1BOOL isExtendableSize (Asn1SizeCnst *pSizeList)
- EXTERN void **set16BitCharSet** (OOCTXT *pctxt, Asn116BitCharSet *pCharSet, Asn116BitCharSet *pAlphabet)
- EXTERN const char * rtBitStrToString (ASN1UINT numbits, const ASN1OCTET *data, char *buffer, size_t bufsiz)
- EXTERN const char * rtOctStrToString (ASN1UINT numocts, const ASN1OCTET *data, char *buffer, size t bufsiz)

Define Documentation

#define DECODEBIT(pctxt, pvalue)

Value:

```
((INCRBITIDX (pctxt) != ASN_OK) ? ASN_E_ENDOFBUF : ((pvalue) ? \
((*(pvalue) = (((pctxt)->buffer.data[(pctxt)->buffer.byteIndex]) & \
(1 << (pctxt)->buffer.bitOffset)) != 0), ASN_OK) : ASN_OK ))
```

Definition at line 1232 of file ooasn1.h.

#define decodeUnconsInteger(pctxt, pvalue) decodeSemiConsInteger(pctxt, pvalue, ASN1INT_MIN)

This function will decode an unconstrained integer.

Parameters:

pctxt Pointer to context block structure.pvalue Pointer to integer variable to receive decoded value.

Completion status of operation:

- 0 (ASN_OK) = success,
- negative return value is error.

Definition at line 1614 of file ooasn1.h.

#define decodeUnconsUnsigned(pctxt, pvalue) decodeSemiConsUnsigned(pctxt, pvalue, 0U)

This function will decode an unconstrained unsigned integer.

Parameters:

pctxt Pointer to context block structure.
pvalue Pointer to unsigned integer variable to receive decoded value.

Returns:

Completion status of operation:

- 0 (ASN_OK) = success,
- negative return value is error.

Definition at line 1627 of file ooasn1.h.

#define encodeUnconsInteger(pctxt, value) encodeSemiConsInteger(pctxt, value, ASN1INT_MIN)

This function encodes an unconstrained integer.

Parameters:

pctxt Pointer to context block structure. value Value to be encoded.

Returns:

Completion status of operation:

- 0 (ASN_OK) = success,
- negative return value is error.

Definition at line 2001 of file ooasn1.h.

#define INCRBITIDX(pctxt)

Value:

```
((--(pctxt)->buffer.bitOffset < 0) ? \
((++(pctxt)->buffer.byteIndex >= (pctxt)->buffer.size) ? ASN_E_ENDOFBUF : \
```

```
((pctxt)->buffer.bitOffset = 7, ASN_OK)) : ASN_OK)
```

Definition at line 1227 of file ooasn1.h.

#define memAlloc(pctxt, nbytes) memHeapAlloc(&(pctxt)->pTypeMemHeap,nbytes)

Allocate memory.

This macro allocates the given number of bytes. It is similar to the C malloc run-time function.

Parameters:

```
pctxt - Pointer to a context blocknbytes - Number of bytes of memory to allocate
```

Returns:

- Void pointer to allocated memory or NULL if insufficient memory was available to fulfill the request.

Definition at line 1046 of file ooasn1.h.

#define memAllocZ(pctxt, nbytes) memHeapAllocZ(&(pctxt)->pTypeMemHeap,nbytes)

Allocate and zero memory.

This macro allocates the given number of bytes and then initializes the memory block to zero.

Parameters:

```
pctxt - Pointer to a context blocknbytes - Number of bytes of memory to allocate
```

Returns:

- Void pointer to allocated memory or NULL if insufficient memory was available to fulfill the request.

Definition at line 1058 of file ooasn1.h.

#define memFree(pctxt) memHeapFreeAll(&(pctxt)->pTypeMemHeap)

Free memory associated with a context.

This macro frees all memory held within a context. This is all memory allocated using the memHeapAlloc (and similar macros) and the mem memory allocation functions using the given context variable.

Parameters:

pctxt - Pointer to a context block

Definition at line 1101 of file ooasn1.h.

#define memFreePtr(pctxt, mem_p)

Value:

```
if (memHeapCheckPtr (&(pctxt)->pTypeMemHeap, (void*)mem_p)) \
memHeapFreePtr(&(pctxt)->pTypeMemHeap, (void*)mem_p)
```

Free memory pointer. This macro frees memory at the given pointer. The memory must have been allocated using the memHeapAlloc (or similar) macros or the mem memory allocation macros. This macro is similar to the C free function.

Parameters:

pctxt - Pointer to a context blockmem_p - Pointer to memory block to free. This must have been allocated using the memHeapAlloc or memAlloc macro or the memHeapAlloc function.

Definition at line 1089 of file ooasn1.h.

#define memRealloc(pctxt, mem_p, nbytes) memHeapRealloc(&(pctxt)->pTypeMemHeap, (void*)mem_p, nbytes)

Reallocate memory.

This macro reallocates a memory block (either expands or contracts) to the given number of bytes. It is similar to the C realloc run-time function.

Parameters:

pctxt - Pointer to a context block
 mem_p - Pointer to memory block to reallocate. This must have been allocated using the memHeapAlloc macro or the memHeapAlloc function.
 nbytes - Number of bytes of memory to which the block is to be resized.

Returns:

- Void pointer to allocated memory or NULL if insufficient memory was available to fulfill the request. This may be the same as the pmem pointer that was passed in if the block did not need to be relocated.

Definition at line 1075 of file ooasn1.h.

#define memReset(pctxt) memHeapReset(&(pctxt)->pTypeMemHeap)

Reset memory associated with a context.

This macro resets all memory held within a context. This is all memory allocated using the memHeapAlloc (and similar macros) and the mem memory allocation functions using the given context variable.

The difference between this and the ASN1MEMFREE macro is that the memory blocks held within the context are not actually freed. Internal pointers are reset so the existing blocks can be reused. This can provide a performace improvement for repetitive tasks such as decoding messages in a loop.

Parameters:

pctxt - Pointer to a context block

Definition at line 1118 of file ooasn1.h.

Function Documentation

EXTERN int decodeBits (OOCTXT * pctxt, ASN1UINT * pvalue, ASN1UINT nbits)

This function will decode a series of multiple bits and place the results in an unsigned integer variable.

Parameters:

pctxt A pointer to a context structure. This provides a storage area for the function to store all working variables that must be maintained between function calls.pvalue A pointer to an unsigned integer variable to receive the decoded result.nbits The number of bits to decode.

Returns:

Completion status of operation:

- $0 \text{ (ASN_OK)} = \text{success},$
- negative return value is error.

EXTERN int decodeBitString (OOCTXT * pctxt, ASN1UINT * numbits_p, ASN1OCTET * buffer, ASN1UINT bufsiz)

This function will decode a value of the ASN.1 bit string type whose maximum size is is known in advance.

The ASN1C complier generates a call to this function to decode bit string productions or elements that contain a size constraint.

Parameters:

pctxt A pointer to a context structure. This provides a storage area for the function to store all working variables that must be maintained between function calls.
 numbits_p Pointer to an unsigned integer variable to receive decoded number of bits.
 buffer Pointer to a fixed-size or pre-allocated array of bufsiz octets to receive a decoded bit string.
 bufsiz Length (in octets) of the buffer to receive the decoded bit string.

Returns:

Completion status of operation:

- 0 (ASN OK) = success,
 - negative return value is error.

EXTERN int decodeBMPString (OOCTXT * pctxt, ASN1BMPString * pvalue, Asn116BitCharSet * permCharSet)

This function will decode a variable of the ASN.1 BMP character string.

This differs from the decode routines for the character strings previously described in that the BMP string type is based on 16-bit characters. A 16-bit character string is modeled using an array of unsigned short integers.

Parameters:

pctxt A pointer to a context structure. This provides a storage area for the function to store all working variables that must be maintained between function calls.

pvalue Pointer to character string structure to receive the decoded result The structure includes a count field containing the number of characters and an array of unsigned short integers to hold the 16-bit character values.

permCharSet A pointer to the constraining character set. This contains an array containing all valid characters in the set as well as the aligned and unaligned bit counts required to encode the characters.

Returns:

Completion status of operation:

- $0 \text{ (ASN_OK)} = \text{success},$
- negative return value is error.

EXTERN int decodeByteAlign (OOCTXT * pctxt)

This function will position the decode bit cursor on the next byte boundary.

Parameters:

pctxt A pointer to a context structure. This provides a storage area for the function to store all working variables that must be maintained between function calls.

Returns:

Completion status of operation:

- $0 \text{ (ASN_OK)} = \text{success},$
- negative return value is error.

EXTERN int decodeConsInteger (OOCTXT * pctxt, ASN1INT * pvalue, ASN1INT lower, ASN1INT upper)

This function will decode an integer constrained either by a value or value range constraint.

Parameters:

pctxt Pointer to context block structure.pvalue Pointer to integer variable to receive decoded value.lower Lower range value.upper Upper range value.

Returns:

Completion status of operation:

- $0 \text{ (ASN_OK)} = \text{success},$
- negative return value is error.

EXTERN int decodeConstrainedStringEx (OOCTXT * pctxt, const char ** string, const char * charSet, ASN1UINT abits, ASN1UINT ubits, ASN1UINT canSetBits)

This function decodes a constrained string value.

This version of the function allows all of the required permitted alphabet constraint parameters to be passed in as arguments.

Parameters:

pctxt Pointer to context block structure.

string Pointer to const char* to receive decoded string. Memory will be allocated for this variable using internal memory management functions.

charSet String containing permitted alphabet character set. Can be null if no character set was specified.

abits Number of bits in a character set character (aligned).

ubits Number of bits in a character set character (unaligned).

canSetBits Number of bits in a character from the canonical set representing this string.

Returns:

Completion status of operation:

- 0 (ASN OK) = success,
- negative return value is error.

EXTERN int decodeConsUInt16 (OOCTXT * pctxt, ASN1USINT * pvalue, ASN1UINT lower, ASN1UINT upper)

This function will decode a 16-bit unsigned integer constrained either by a value or value range constraint.

Parameters:

pctxt Pointer to context block structure.pvalue Pointer to 16-bit unsigned integer variable to receive decoded value.lower Lower range value.upper Upper range value.

Returns:

Completion status of operation:

- 0 (ASN_OK) = success,
- negative return value is error.

EXTERN int decodeConsUInt8 (OOCTXT * pctxt, ASN1UINT8 * pvalue, ASN1UINT lower, ASN1UINT upper)

This function will decode an 8-bit unsigned integer constrained either by a value or value range constraint.

Parameters:

```
pctxt Pointer to context block structure.
pvalue Pointer to 8-bit unsigned integer variable to receive decoded value.
lower Lower range value.
upper Upper range value.
```

Returns:

Completion status of operation:

- 0 (ASN OK) = success,
- negative return value is error.

EXTERN int decodeConsUnsigned (OOCTXT * pctxt, ASN1UINT * pvalue, ASN1UINT lower, ASN1UINT upper)

This function will decode an unsigned integer constrained either by a value or value range constraint.

Parameters:

```
pctxt Pointer to context block structure.
pvalue Pointer to unsigned integer variable to receive decoded value.
lower Lower range value.
upper Upper range value.
```

Returns:

Completion status of operation:

- 0 (ASN_OK) = success,
- negative return value is error.

EXTERN int decodeConsWholeNumber (OOCTXT * pctxt, ASN1UINT * padjusted_value, ASN1UINT range_value)

This function decodes a constrained whole number as specified in Section 10.5 of the X.691 standard.

Parameters:

pctxt Pointer to context block structure.

padjusted_value Pointer to unsigned adjusted integer value to receive decoded result. To get the final value, this value is added to the lower boundary of the range.

range_value Unsigned integer value specifying the total size of the range. This is obtained by subtracting the lower range value from the upper range value.

Returns:

Completion status of operation:

- $0 \text{ (ASN_OK)} = \text{success},$
- negative return value is error.

EXTERN int decodeDynBitString (OOCTXT * pctxt, ASN1DynBitStr * pBitStr)

This function will decode a variable of thr ASN.1 BIT STRING type.

This function allocates dynamic memory t store the decoded result. The ASN1C complier generates a call to this function to decode an unconstrained bit string production or element.

Parameters:

pctxt A pointer to a context structure. This provides a storage area for the function to store all working variables that must be maintained between function calls.

pBitStr Pointer to a dynamic bit string structure to receive the decoded result. This structure contains a field to hold the number of decoded bits and a pointer to an octet string to hold the decoded data. Memory is allocated by the decoder using the memAlloc function. This memory is tracked within the context and released when the freeContext function is invoked.

Returns:

Completion status of operation:

- 0 (ASN OK) = success,
- negative return value is error.

EXTERN int decodeDynOctetString (OOCTXT * pctxt, ASN1DynOctStr * pOctStr)

This function will decode a value of the ASN.1 octet string type whose maximum size is known in advance.

The ASN1C complier generates a call to this function to decode octet string productions or elements that contain a size constraint.

Parameters:

pctxt A pointer to a context structure. This provides a storage area for the function to store all working variables that must be maintained between function calls. pOctStr A pointer to a dynamic octet string to receive the decoded result.

Returns:

Completion status of operation:

- 0 (ASN_OK) = success,
- negative return value is error.

EXTERN int decodeLength (OOCTXT * pctxt, ASN1UINT * pvalue)

This function will decode a length determinant value.

Parameters:

pctxt A pointer to a context structure. This provides a storage area for the function to store all working variables that must be maintained between function calls. pvalue A pointer to an unsigned integer variable to receive the decoded length value.

Returns:

Completion status of operation:

- $0 \text{ (ASN_OK)} = \text{success},$
- negative return value is error.

EXTERN int decodeObjectIdentifier (OOCTXT * pctxt, ASN10BJID * pvalue)

This function decodes a value of the ASN.1 object identifier type.

Parameters:

pctxt Pointer to context block structure.

pvalue Pointer to value to receive decoded result. The ASN1OBJID structure contains an integer to hold the number of subidentifiers and an array to hold the subidentifier values.

Returns:

Completion status of operation:

- $0 \text{ (ASN_OK)} = \text{success},$
- negative return value is error.

EXTERN int decodeOctetString (OOCTXT * pctxt, ASN1UINT * numocts_p, ASN1OCTET * buffer, ASN1UINT bufsiz)

This function will decode a value of the ASN.1 octet string type whose maximun size is known in advance.

The ASN1C compiler generates a call to this function to decode octet string productions or elements that contain a size constraint.

Parameters:

pctxt Pointer to a context structure. This provides a storage area for the function to store all working variables that must be maintained between function calls.
numocts_p A pointer to an unsigned buffer of bufsiz octets to receive decoded data.
buffer A pointer to a pre-allocated buffer of size octets to receive the decoded data.
bufsiz The size of the buffer to receive the decoded result.

Returns:

Completion status of operation:

- 0 (ASN_OK) = success,
- negative return value is error.

EXTERN int decodeOpenType (OOCTXT * pctxt, const ASN1OCTET ** object_p2, ASN1UINT * numocts_p)

This function will decode an ASN.1 open type.

This used to be the ASN.1 ANY type, but now is used in a variety of applications requiring an encoding that can be interpreted by a decoder without prior knowledge of the type of the variable.

Parameters:

pctxt Pointer to a context structure. This provides a storage area for the function to store all working variables that must be maintained between function calls.

numocts_p A pointer to an unsigned buffer of bufsiz octets to receive decoded data.

object_p2 A pointer to an open type variable to receive the decoded data.

Returns:

Completion status of operation:

- 0 (ASN OK) = success,
- negative return value is error.

EXTERN int decodeSemiConsInteger (OOCTXT * pctxt, ASN1INT * pvalue, ASN1INT lower)

This function will decode a semi-constrained integer.

Parameters:

pctxt Pointer to context block structure.pvalue Pointer to integer variable to receive decoded value.lower Lower range value, represented as signed integer.

Returns:

Completion status of operation:

- 0 (ASN OK) = success,
- negative return value is error.

EXTERN int decodeSemiConsUnsigned (OOCTXT * pctxt, ASN1UINT * pvalue, ASN1UINT lower)

This function will decode a semi-constrained unsigned integer.

Parameters:

pctxt Pointer to context block structure.
pvalue Pointer to unsigned integer variable to receive decoded value.
lower Lower range value, represented as unsigned integer.

Returns:

Completion status of operation:

- 0 (ASN_OK) = success,
- negative return value is error.

EXTERN int decodeSmallNonNegWholeNumber (OOCTXT * pctxt, ASN1UINT * pvalue)

This function will decode a small non-negative whole number as specified in Section 10.6 of the X.691 standard.

This is a number that is expected to be small, but whose size is potentially unlimited due to the presence of an extension maker.

Parameters:

pctxt Pointer to a context structure. This provides a storage area for the function to store all workings variables that must be maintained between function calls. pvalue Pointer to an unsigned integer value t receive decoded results.

Returns:

Completion status of operation:

- $0 \text{ (ASN_OK)} = \text{success},$
- negative return value is error.

EXTERN int encodeBit (OOCTXT * pctxt, ASN1BOOL value)

This function will encode a variable of the ASN.1 BOOLEAN type in a single bit.

Parameters:

pctxt Pointer to a context structure. This provides a storage area for the function to store all working variables that must be maintained between function calls. value The BOOLEAN value to be encoded.

EXTERN int encodeBits (OOCTXT * pctxt, ASN1UINT value, ASN1UINT nbits)

This function encodes multiple bits.

Parameters:

pctxt Pointer to context block structure.
value Unsigned integer containing the bits to be encoded.
nbits Number of bits in value to encode.

Returns:

Completion status of operation:

- $0 \text{ (ASN_OK)} = \text{success},$
- negative return value is error.

EXTERN int encodebitsFromOctet (OOCTXT * pctxt, ASN1OCTET value, ASN1UINT nbits)

This function encodes bits from a given octet to the output buffer.

Parameters:

pctxt Pointer to ASN.1 PER context structure value Value of bits to be encoded nbits Number of bits to be encoded

Returns:

Status of operation

EXTERN int encodeBitString (OOCTXT * pctxt, ASN1UINT numocts, const ASN1OCTET * data)

This function will encode a value of the ASN.1 bit string type.

Parameters:

pctxt A pointer to a context structure. This provides a storage area for the function to store all working variables that must be maintained between function calls.numocts The number of bits n the string to be encoded.data Pointer to the bit string data to be encoded.

Returns:

Completion status of operation:

- $0 \text{ (ASN_OK)} = \text{success},$
- negative return value is error.

EXTERN int encodeBMPString (OOCTXT * pctxt, ASN1BMPString value, Asn116BitCharSet * permCharSet)

This function will encode a variable of the ASN.1 BMP character string.

This differs from the encode routines for the character strings previously described in that the BMP string type is based on 16-bit characters. A 16-bit character string is modeled using an array of unsigned short integers.

Parameters:

pctxt A pointer to a context structure. This provides a storage area for the function to store all working variables that must be maintained between function calls.

value Character string to be encoded. This structure includes a count field containing the number of characters to encode and an array of unsigned short integers to hold the 16-bit characters to be encoded.

permCharSet Pointer to the constraining character set. This contains an array containing all valid characters in the set as well as the aligned and unaligned bit counts required to encode the characters.

Returns:

Completion status of operation:

- 0 (ASN OK) = success,
- negative return value is error.

EXTERN int encodeByteAlign (OOCTXT * pctxt)

This function will position the encode bit cursor on the next byte boundry.

Parameters:

pctxt A pointer to a context structure. This provides a storage area for the function to store all working variables that must be maintained between function calls.

Returns:

Completion status of operation:

- $0 \text{ (ASN_OK)} = \text{success},$
- negative return value is error.

EXTERN int encodeCheckBuffer (OOCTXT * pctxt, ASN1UINT nbytes)

This function will determine if the given number of bytes will fit in the encode buffer.

If not, either the buffer is expanded (if it is a dynamic buffer) or an error is signaled.

Parameters:

pctxt A pointer to a context structure. This provides a storage area for the function to store all working variables that must be maintained between function calls. nbytes Number of bytes of space required to hold the variable to be encoded.

Returns:

Completion status of operation:

- 0 (ASN OK) = success,
- negative return value is error.

EXTERN int encodeConsInteger (OOCTXT * pctxt, ASN1INT value, ASN1INT lower, ASN1INT upper)

This function encodes an integer constrained either by a value or value range constraint.

Parameters:

pctxt Pointer to context block structure.value Value to be encoded.lower Lower range value.upper Upper range value.

Returns:

Completion status of operation:

- $0 \text{ (ASN_OK)} = \text{success},$
- negative return value is error.

EXTERN int encodeConstrainedStringEx (OOCTXT * pctxt, const char * string, const char * charSet, ASN1UINT abits, ASN1UINT ubits, ASN1UINT canSetBits)

This function encodes a constrained string value.

This version of the function allows all of the required permitted alphabet constraint parameters to be passed in as arguments.

Parameters:

```
pctxt Pointer to context block structure.
string Pointer to string to be encoded.
charSet String containing permitted alphabet character set. Can be null if no character set was specified.
abits Number of bits in a character set character (aligned).
ubits Number of bits in a character set character (unaligned).
canSetBits Number of bits in a character from the canonical set representing this string.
```

Returns:

Completion status of operation:

• $0 \text{ (ASN_OK)} = \text{success},$

negative return value is error.

EXTERN int encodeConsUnsigned (OOCTXT * pctxt, ASN1UINT value, ASN1UINT lower, ASN1UINT upper)

This function encodes an unsigned integer constrained either by a value or value range constraint.

The constrained unsigned integer option is used if:

1. The lower value of the range is \geq 0, and 2. The upper value of the range is \geq MAXINT

Parameters:

pctxt Pointer to context block structure. value Value to be encoded. lower Lower range value. upper Upper range value.

Returns:

Completion status of operation:

- 0 (ASN_OK) = success,
- negative return value is error.

EXTERN int encodeConsWholeNumber (OOCTXT * pctxt, ASN1UINT adjusted_value, ASN1UINT range_value)

This function encodes a constrained whole number as specified in Section 10.5 of the X.691 standard.

Parameters:

pctxt Pointer to context block structure.
adjusted_value Unsigned adjusted integer value to be encoded. The adjustment is done by subtracting the lower value of the range from the value to be encoded.
range_value Unsigned integer value specifying the total size of the range. This is obtained by subtracting the lower range value from the upper range value.

Returns:

Completion status of operation:

- $0 \text{ (ASN_OK)} = \text{success},$
- negative return value is error.

EXTERN int encodeExpandBuffer (OOCTXT * pctxt, ASN1UINT nbytes)

This function will expand the buffer to hold the given number of bytes.

Parameters:

pctxt Pointer to a context structure. This provides a storage area for the function to store all working variables that must be maintained between function calls. nbytes The number of bytes the buffer is to be expanded by. Note that the buffer will be expanded by ASN_K_ENCBIFXIZ or nbytes (whichever is larger.

Returns:

Completion status of operation:

- $0 \text{ (ASN_OK)} = \text{success},$
- negative return value is error.

EXTERN ASN1OCTET* encodeGetMsgPtr (OOCTXT * pctxt, int * pLength)

This function will return the message pointer and length of an encoded message.

This function is called after a complier generated encode function to get the pointer and length of the message. It is normally used when dynamic encoding is specified because the message pointer is not known until encoding is complete. If static encoding is used, the message starts at the beginning of the specified buffer adn the encodeGetMsgLen function can be used to obtain the length of the message.

Parameters:

pctxt Pointer to a context structure. This provides a storage area for the function to store all working variables that must be maintained between function calls. pLength Pointer to variable to receive length of the encoded message.

Returns:

Completion status of operation:

- $0 \text{ (ASN_OK)} = \text{success},$
- negative return value is error.

EXTERN int encodeLength (OOCTXT * pctxt, ASN1UINT value)

This function will encode a length determinant value.

Parameters:

pctxt Pointer to a context structure. This provides a storage area for the function to store all working variables that must be maintained between function calls. value Length value to be encoded.

Returns:

Completion status of operation:

- 0 (ASN_OK) = success,
- negative return value is error.

EXTERN int encodeObjectIdentifier (OOCTXT * pctxt, ASN1OBJID * pvalue)

This function encodes a value of the ASN.1 object identifier type.

Parameters:

pctxt Pointer to context block structure.

pvalue Pointer to value to be encoded. The ASN1OBJID structure contains a numids fields to hold the number of subidentifiers and an array to hold the subidentifier values.

Returns:

Completion status of operation:

- $0 \text{ (ASN_OK)} = \text{success},$
- negative return value is error.

EXTERN int encodeOctets (OOCTXT * pctxt, const ASN1OCTET * pvalue, ASN1UINT nbits)

This fuction will encode an array of octets.

The Octets will be encoded unaligned starting at the current bit offset within the encode buffer.

Parameters:

pctxt A pointer to a context structure. The provides a storage area for the function to store all working variables that must be maintained between function calls.pvalue A pointer to an array of octets to encodenbits The number of Octets to encode

Returns:

Completion status of operation:

- 0 (ASN OK) = success,
- negative return value is error.

EXTERN int encodeOctetString (OOCTXT * pctxt, ASN1UINT numocts, const ASN1OCTET * data)

This function will encode a value of the ASN.1 octet string type.

Parameters:

pctxt A pointer to a context structure. The provides a storage area for the function to store all working variables that must be maintained between function calls.numocts Number of octets in the string to be encoded.data Pointer to octet string data to be encoded.

Returns:

Completion status of operation:

- 0 (ASN OK) = success,
- negative return value is error.

EXTERN int encodeOpenType (OOCTXT * pctxt, ASN1UINT numocts, const ASN1OCTET * data)

This function will encode an ASN.1 open type.

This used to be the ANY type, but now is used in a variety of applications requiring an encoding that can be interpreted by a decoder without a prior knowledge of the type of the variable.

Parameters:

pctxt A pointer to a context structure. The provides a storage area for the function to store all working variables that must be maintained between function calls.numocts Number of octets in the string to be encoded.data Pointer to octet string data to be encoded.

Returns:

Completion status of operation:

- 0 (ASN_OK) = success,
- negative return value is error.

EXTERN int encodeOpenTypeExt (OOCTXT * pctxt, DList * pElemList)

This function will encode an ASN.1 open type extension.

An open type extension field is the data that potentially resides after the ... marker in a version-1 message. The open type structure contains a complete encoded bit set including option element bits or choice index, length, and data. Typically, this data is populated when a version-1 system decodes a version-2 message. The extension fields are retained and can then be re-encoded if a new message is to be sent out (for example, in a store and forward system).

Parameters:

pctxt A pointer to a context structure. The provides a storage area for the function to store all working variables that must be maintained between function calls. pElemList A pointer to the open type to be encoded.

Returns:

Completion status of operation:

- $0 \text{ (ASN_OK)} = \text{success},$
- negative return value is error.

EXTERN int encodeSemiConsInteger (OOCTXT * pctxt, ASN1INT value, ASN1INT lower)

This function encodes a semi-constrained integer.

Parameters:

pctxt Pointer to context block structure.value Value to be encoded.lower Lower range value, represented as signed integer.

Returns:

Completion status of operation:

- $0 \text{ (ASN_OK)} = \text{success},$
- negative return value is error.

EXTERN int encodeSemiConsUnsigned (OOCTXT * pctxt, ASN1UINT value, ASN1UINT lower)

This function encodes an semi-constrained unsigned integer.

Parameters:

pctxt Pointer to context block structure.value Value to be encoded.lower Lower range value, represented as unsigned integer.

Returns:

Completion status of operation:

- $0 \text{ (ASN_OK)} = \text{success},$
- negative return value is error.

EXTERN int encodeSmallNonNegWholeNumber (OOCTXT * pctxt, ASN1UINT value)

This function will endcode a small, non-negative whole number as specified in Section 10.6 of teh X.691 standard.

This is a number that is expected to be small, but whose size is potentially unlimited due to the presence of an extension marker.

Parameters:

pctxt A pointer to a context structure. The provides a storage area for the function to store all working variables that must be maintained between function calls. value An unsigned integer value to be encoded.

Returns:

Completion status of operation:

• $0 \text{ (ASN_OK)} = \text{success},$

• negative return value is error.

EXTERN ASN1UINT memHeapGetDefBlkSize (OOCTXT * pctxt)

This function returns the actual granularity of memory blocks.

Parameters:

pctxt Pointer to a context block.

EXTERN void memHeapSetDefBlkSize (OOCTXT * pctxt, ASN1UINT blkSize)

This function sets the pointer to standard allocation functions.

These functions are used to allocate/reallocate/free the memory blocks. By default, standard C functions - malloc, realloc, and free - are used. But if some platforms do not support these functions or some other reasons exist) they can be overloaded. The functions being overloaded should have the same prototypes as standard ones.

Parameters:

pctxt Pointer to a context block.

blkSize The currently used minimum size and the granularity of memory blocks.

EXTERN void memSetAllocFuncs (OSMallocFunc malloc_func, OSReallocFunc realloc_func, OSFreeFunc free_func)

This function sets the pointers to standard allocation functions.

These functions are used to allocate/reallocate/free the memory blocks. By default, standard C functions - 'malloc', 'realloc' and 'free' - are used. But if some platforms do not support these functions (or some other reasons exist) they can be overloaded. The functions being overloaded should have the same prototypes as standard ones.

Parameters:

malloc_func Pointer to the memory allocation function ('malloc' by default). *realloc_func* Pointer to the memory reallocation function ('realloc' by default). *free func* Pointer to the memory deallocation function ('free' by default).

EXTERN int moveBitCursor (OOCTXT * pctxt, int bitOffset)

Parameters:

pctxt A pointer to a context structure. This provides a storage area for the function to store all working variables that must be maintained between function calls.

bitOffset The bit offset inside the message buffer.

H323FrameworkStack Data Structure Documentation

Asn1NamedCEventHandler Struct Reference

This is a basic C based event handler structure, which can be used to define user-defined event handlers.

#include <asn1CEvtHndlr.h>

Data Fields

- rtStartElement startElement
- rtEndElement endElement
- rtBoolValue boolValue
- rtIntValue intValue
- rtUIntValue uIntValue
- rtBitStrValue bitStrValue
- rtOctStrValue octStrValue
- rtCharStrValue charStrValue
- rtCharStrValue16Bit charStrValue16Bit
- rtCharStrValue32Bit charStrValue32Bit
- rtNullValue nullValue
- rtOidValue oidValue
- rtRealValue realValue
- rtEnumValue enumValue
- rtOpenTypeValue openTypeValue

Detailed Description

This is a basic C based event handler structure, which can be used to define user-defined event handlers.

Definition at line 234 of file asn1CEvtHndlr.h.

The documentation for this struct was generated from the following file:

• asn1CEvtHndlr.h

H245Message Struct Reference

Defines the H245 message structure.

#include <ootypes.h>

Data Fields

- OOCTXT * pctxt
- H245MultimediaSystemControlMessage h245Msg
- ASN1UINT msgType

Detailed Description

Defines the H245 message structure.

All request/response and command messages are represented using this structure.

Definition at line 244 of file ootypes.h.

The documentation for this struct was generated from the following file:

• ootypes.h

ooCallData Struct Reference

Structure to store all the information related to a particular call.

#include <ootypes.h>

Data Fields

- OOCTXT * pctxt
- char **callToken** [20]
- char callType [10]
- ASN1USINT callReference
- H225CallIdentifier callIdentifier
- H225ConferenceIdentifier confIdentifier
- int callState
- int callEndReason
- int h245SessionState
- int isTunnelingActive
- int isFastStartActive
- int gkEngaged
- ooMediaInfo * mediaInfo
- char **localIP** [20]
- OOSOCKET * h225Channel
- int * h225ChanPort
- OOSOCKET * h245Channel
- int * h245ChanPort
- OOSOCKET * h245listener
- int * h245listenport
- char **remoteIP** [20]
- int remotePort
- int remoteH245Port
- int sendH225
- int sendH245
- DList outH225Queue
- DList outH245Queue
- ASN1OCTET * remoteDisplayName
- ooAliases * remoteAliases
- int masterSlaveState
- ASN1UINT statusDeterminationNumber
- int localTermCapState
- int remoteTermCapState
- H245Message * remoteTermCapSet
- DList remoteFastStartOLCs
- ASN1UINT8 remoteTermCapSeqNo
- ASN1UINT8 localTermCapSeqNo
- ooLogicalChannel * logicalChans
- int noOfLogicalChannels
- int logicalChanNoBase
- int logicalChanNoMax
- int logicalChanNoCur

- int isAudioActive
- ooCallData * next
- ooCallData * prev

Detailed Description

Structure to store all the information related to a particular call.

Definition at line 292 of file ootypes.h.

The documentation for this struct was generated from the following file:

• ootypes.h

ooCommand Struct Reference

Structure for stack commands.

#include <ootypes.h>

Data Fields

- int **type**
- void * param1 void * param2
- void * param3

Detailed Description

Structure for stack commands.

Definition at line 206 of file ootypes.h.

The documentation for this struct was generated from the following file:

• ootypes.h

ooEndPoint Struct Reference

Structure to store all the config information related to the endpoint created by an application.

#include <ootypes.h>

Data Fields

- OOCTXT ctxt
- FILE * fptraceFile
- ooH323Ports tcpPorts

Range of port numbers to be used for TCP connections.

• ooH323Ports udpPorts

Range of port numbers to be used for UDP connections.

• ooH323Ports rtpPorts

Range of port numbers to be used for RTP connections.

- int h245Tunneling
- int fastStart
- int termType
- int t35CountryCode
- int t35Extension
- int manufacturerCode
- char * productID
- char * versionID
- char * callerid
- char * callername
- OOSOCKET * stackSocket
- ooAliases * aliases
- int callType
- ooH323EpCapability * myCaps
- int noOfCaps
- cb_OnAlerting onAlerting
- cb_OnIncomingCall onIncomingCall
- cb_OnOutgoingCall onOutgoingCall
- cb_OnCallEstablished onCallEstablished
- cb_OnCallCleared onCallCleared
- cb_OnOutgoingCallAdmitted onOutgoingCallAdmitted
- char **signallingIP** [20]
- int listenPort
- OOSOCKET * listener
- ooCallData * callList
- int autoAnswer
- int callMode

Detailed Description

Structure to store all the config information related to the endpoint created by an application. Definition at line 385 of file ootypes.h.

The documentation for this struct was generated from the following file:

• ootypes.h

ooH323EpCapability Struct Reference

Structure to store information related to end point capability.

#include <ootypes.h>

Data Fields

- int dir
- int cap
- int capType
- cb_StartReceiveChannel startReceiveChannel
- cb_StartTransmitChannel startTransmitChannel
- cb_StopReceiveChannel stopReceiveChannel
- cb_StopTransmitChannel stopTransmitChannel
- ooH323EpCapability * next

Detailed Description

Structure to store information related to end point capability.

Definition at line 364 of file ootypes.h.

The documentation for this struct was generated from the following file:

ootypes.h

ooH323Ports Struct Reference

This structure is used to define the port ranges to be used by the application.

#include <ootypes.h>

Data Fields

- int start
- int max
- int current

Detailed Description

This structure is used to define the port ranges to be used by the application.

Definition at line 216 of file ootypes.h.

The documentation for this struct was generated from the following file:

ootypes.h

ooLogicalChannel Struct Reference

Structure to store information of logical channels for call.

#include <ootypes.h>

Data Fields

- int channelNo
- int sessionID
- char **type** [10]
- char **dir** [10]
- char remoteIP [20]
- int remoteRtpPort
- int remoteRtcpPort
- int localRtpPort
- int localRtcpPort
- char **localIP** [20]
- int state
- ooH323EpCapability * chanCap
- ooLogicalChannel * next

Detailed Description

Structure to store information of logical channels for call.

Definition at line 266 of file ootypes.h.

The documentation for this struct was generated from the following file:

ootypes.h

ooRasMessage Struct Reference

Defines the RAS message structure.

#include <ooras.h>

Data Fields

- OOCTXT * psContext
- unsigned char ucBuilt
- H225RasMessage **sMessage**

Detailed Description

Defines the RAS message structure.

Contains context for memory allocation, protocol Discriminator, call reference, meesage type and list of user user IEs.

Definition at line 103 of file ooras.h.

The documentation for this struct was generated from the following file:

• ooras.h

Q931Message Struct Reference

Defines the Q931 message structure.

#include <ootypes.h>

Data Fields

- OOCTXT * pctxt
- unsigned **protocolDiscriminator**
- unsigned callReference
- ASN1BOOL fromDestination
- unsigned messageType
- DList ies
- H225H323_UserInformation * **userInfo**

Detailed Description

Defines the Q931 message structure.

Contains context for memory allocation, protocol Discriminator, call reference, meesage type and list of user user IEs.

Definition at line 228 of file ootypes.h.

The documentation for this struct was generated from the following file:

• ootypes.h

H323FrameworkStack File Documentation

asn1CEvtHndlr.h File Reference

C event handler structure.

#include <stdio.h>
#include "ooasn1.h"

Data Structures

• struct Asn1NamedCEventHandler

This is a basic C based event handler structure, which can be used to define user-defined event handlers.

Typedefs

- typedef void(* **rtStartElement**)(const char *name, int index)

 This is a function pointer for a callback function which is invoked from within a decode function when
- an element of a SEQUENCE, SET, SEQUENCE OF, SET OF, or CHOICE construct is parsed.
- typedef void(* rtEndElement)(const char *name, int index)
 This is a function pointer for a callback function which is invoked from within a decode function when parsing is complete on an element of a SEQUENCE, SET, SEQUENCE OF, SET OF, or CHOICE construct.
- typedef void(* rtBoolValue) (ASN1BOOL value)
 This is a function pointer for a callback function which is invoked from within a decode function when a value of the BOOLEAN ASN.1 type is parsed.
- typedef void(* rtIntValue)(ASN1INT value)
 This is a function pointer for a callback function which is invoked from within a decode function when a value of the INTERGER ASN. I type is parsed.
- typedef void(* rtUIntValue) (ASN1UINT value)
 This is a function pointer for a callback function which is invoked from within a decode function when a value of the INTEGER ASN.1 type is parsed.
- typedef void(* rtBitStrValue)(ASN1UINT numbits, const ASN1OCTET *data)

 This is a function pointer for a callback function which is invoked from within a decode function when a value of the BIT STRING ASN.1 type is parsed.
- typedef void(* rtOctStrValue)(ASN1UINT numocts, const ASN1OCTET *data)

This is a function pointer for a callback function which is invoked from within a decode function when a value of one of the OCTET STRING ASN.1 type is parsed.

• typedef void(* rtCharStrValue)(const char *value)

This is a function pointer for a callback function which is invoked from within a decode function when a value of one of the 8-bit ASN.1 character string types is parsed.

• typedef void(* rtCharStrValue16Bit)(ASN1UINT nchars, ASN116BITCHAR *data)

This is a function pointer for a callback function which is invoked from within a decode function when a value of one of the 16-bit ASN.1 character string types is parsed.

typedef void(* rtCharStrValue32Bit)(ASN1UINT nchars, ASN132BITCHAR *data)

This is a function pointer for a callback function which is invoked from within a decode function when a value of one of the 32-bit ASN.1 characer string types is parsed.

typedef void(* rtNullValue)()

This is a function pointer for a callback function which is invoked from within a decode function when a value of the NULL ASN.1 type is parsed.

• typedef void(* rtOidValue)(ASN1UINT numSubIds, ASN1UINT *pSubIds)

This is a function pointer for a callback function which is invoked from within a decode function whn a value the OBJECT IDENTIFIER ASN.1 type is parsed.

• typedef void(* **rtRealValue**)(double value)

This is a function pointer for a callback function which is invoked from within a decode function when a value the REAL ASN.1 type is parsed.

• typedef void(* **rtEnumValue**)(ASN1UINT value)

This is a function pointer for a callback function which is invoked from within a decode function when a value of the ENUMERATED ASN.1 type is parsed.

• typedef void(* rtOpenTypeValue)(ASN1UINT numocts, const ASN1OCTET *data)

This is a function pointer for a callback function which is invoked from within a decode function when an ASN.1 open type is parsed.

• typedef Asn1NamedCEventHandler Asn1NamedCEventHandler

This is a basic C based event handler structure, which can be used to define user-defined event handlers.

Functions

• EXTERN void **rtAddEventHandler** (OOCTXT *pCtxt, **Asn1NamedCEventHandler** *pHandler) *This function is called to add a new event handler to the context event handler list.*

• EXTERN void **rtRemoveEventHandler** (OOCTXT *pCtxt, **Asn1NamedCEventHandler** *pHandler)

This function is called to remove an event handler from the context event handler list.

- EXTERN void **rtInvokeStartElement** (OOCTXT *pCtxt, const char *name, int index)

 The following functions are invoked from within the generated code to call the various user-defined event handler methods ..
- EXTERN void **rtInvokeEndElement** (OOCTXT *pCtxt, const char *name, int index)
- EXTERN void **rtInvokeBoolValue** (OOCTXT *pCtxt, ASN1BOOL value)
- EXTERN void **rtInvokeIntValue** (OOCTXT *pCtxt, ASN1INT value)
- EXTERN void **rtInvokeUIntValue** (OOCTXT *pCtxt, ASN1UINT value)
- EXTERN void **rtInvokeBitStrValue** (OOCTXT *pCtxt, ASN1UINT numbits, const ASN1OCTET *data)
- EXTERN void **rtInvokeOctStrValue** (OOCTXT *pCtxt, ASN1UINT numocts, const ASN1OCTET *data)
- EXTERN void **rtInvokeCharStrValue** (OOCTXT *pCtxt, const char *value)
- EXTERN void **rtInvokeCharStr16BitValue** (OOCTXT *pCtxt, ASN1UINT nchars, ASN116BITCHAR *data)
- EXTERN void **rtInvokeCharStr32BitValue** (OOCTXT *pCtxt, ASN1UINT nchars, ASN132BITCHAR *data)
- EXTERN void **rtInvokeNullValue** (OOCTXT *pCtxt)
- EXTERN void **rtInvokeOidValue** (OOCTXT *pCtxt, ASN1UINT numSubIds, ASN1UINT *pSubIds)
- EXTERN void **rtInvokeRealValue** (OOCTXT *pCtxt, double value)
- EXTERN void **rtInvokeEnumValue** (OOCTXT *pCtxt, ASN1UINT value)
- EXTERN void **rtInvokeOpenTypeValue** (OOCTXT *pCtxt, ASN1UINT numocts, const ASN1OCTET *data)

Detailed Description

C event handler structure.

The ASN1CEventHandler is a structure type which can be used to define event handlers by the user.

Definition in file asn1CEvtHndlr.h.

oo.h File Reference

This file defines the trace functionality. #include "ooCommon.h"

Defines

- #define **OOTRCLVLERR** 1
- #define **OOTRCLVLWARN** 2
- #define **OOTRCLVLINFO** 3
- #define OOTRCLVLDBGA 4
- #define **OOTRCLVLDBGB** 5
- #define **OOTRCLVLDBGC** 6
- #define TRACELVL 1
- #define **OOTRACEERR1**(a) ooTrace(OOTRCLVLERR,a)
- #define **OOTRACEERR2**(a, b) ooTrace(OOTRCLVLERR,a,b)
- #define **OOTRACEERR3**(a, b, c) ooTrace(OOTRCLVLERR,a,b,c)
- #define **OOTRACEERR4**(a, b, c, d) ooTrace(OOTRCLVLERR,a,b,c,d)
- #define **OOTRACEWARN1**(a) ooTrace(OOTRCLVLWARN,a)
- #define **OOTRACEWARN2**(a, b) ooTrace(OOTRCLVLWARN,a,b)
- #define **OOTRACEWARN3**(a, b, c) ooTrace(OOTRCLVLWARN,a,b,c)
- #define **OOTRACEWARN4**(a, b, c, d) ooTrace(OOTRCLVLWARN,a,b,c,d)
- #define **OOTRACEINFO1**(a) ooTrace(OOTRCLVLINFO, a)
- #define **OOTRACEINFO2**(a, b) ooTrace(OOTRCLVLINFO,a,b)
- #define **OOTRACEINFO3**(a, b, c) ooTrace(OOTRCLVLINFO,a,b,c)
- #define **OOTRACEINFO4**(a, b, c, d) ooTrace(OOTRCLVLINFO,a,b,c,d)
- #define OOTRACEINFO5(a, b, c, d, e) ooTrace(OOTRCLVLINFO,a,b,c,d,e)
- #define **OOTRACEDBGA1**(a) ooTrace(OOTRCLVLDBGA,a)
- #define **OOTRACEDBGA2**(a, b) ooTrace(OOTRCLVLDBGA,a,b)
- #define **OOTRACEDBGA3**(a, b, c) ooTrace(OOTRCLVLDBGA,a,b,c)
- #define **OOTRACEDBGA4**(a, b, c, d) ooTrace(OOTRCLVLDBGA,a,b,c,d)
- #define OOTRACEDBGA5(a, b, c, d, e) ooTrace(OOTRCLVLDBGA,a,b,c,d,e)
- #define **OOTRACEDBGB1**(a) ooTrace(OOTRCLVLDBGB,a)
- #define **OOTRACEDBGB2**(a, b) ooTrace(OOTRCLVLDBGB,a,b)
- #define **OOTRACEDBGB3**(a, b, c) ooTrace(OOTRCLVLDBGB,a,b,c)
- #define **OOTRACEDBGB4**(a, b, c, d) ooTrace(OOTRCLVLDBGB,a,b,c,d)
- #define **OOTRACEDBGC1**(a) ooTrace(OOTRCLVLDBGC,a)
- #define **OOTRACEDBGC2**(a, b) ooTrace(OOTRCLVLDBGC,a,b)
- #define OOTRACEDBGC3(a, b, c) ooTrace(OOTRCLVLDBGC,a,b,c)
- #define OOTRACEDBGC4(a, b, c, d) ooTrace(OOTRCLVLDBGC,a,b,c,d)

Functions

- EXTERN char * **ooGetText** (int code)

 This function is used to retireve the description text for a code.
- EXTERN void ooSetTraceThreshold (OOUINT32 traceLevel)

This function is used to set the trace level.

- EXTERN void **ooTrace** (OOUINT32 traceLevel, const char *fmtspec,...) *This function is used to write the messages to the trace file.*
- void **ooTraceLogMessage** (const char *logMessage) *Helper function for the trace function.*
- int ooLogAsn1Error (int stat, const char *fname, int lno)

Detailed Description

This file defines the trace functionality.

Definition in file **oo.h**.

Function Documentation

EXTERN char* ooGetText (int code)

This function is used to retireve the description text for a code.

Parameters:

code Code for which description is required.

Returns:

The text description string.

EXTERN void ooSetTraceThreshold (OOUINT32 traceLevel)

This function is used to set the trace level.

Parameters:

traceLevel New trace level. Various values are: OOTRCLVLERR, OOTRCLVLWARN, OOTRCLVLINFO, OOTRCLVLDBGA, OOTRCLVLDBGB, OOTRCLVLDBGC

Returns:

None

EXTERN void ooTrace (OOUINT32 traceLevel, const char * fmtspec, ...)

This function is used to write the messages to the trace file.

Parameters:

traceLevel Trace level for the message.fmtspec Printf style format spec.... Printf style variable list of arguments

Returns:

- none

void ooTraceLogMessage (const char * logMessage)

Helper function for the trace function.

This function performs actual writing to file.

Parameters:

logMessage Log message to be writted to file.

Returns:

- none

ooasn1.h File Reference

Common ASN.1 runtime constants, data structure definitions, and run-time functions to support BER/DER/PER as defined in the ITU-T standards.

```
#include <limits.h>
#include <stdio.h>
#include <string.h>
#include <stddef.h>
#include "oo.h"
```

Data Structures

- struct ASN1OBJID
- struct ASN1OctStr
- struct ASN1DynOctStr
- struct ASN1DynBitStr
- struct ASN1SeqOf
- struct ASN1SeqOfOctStr
- struct ASN1OpenType
- struct Asn116BitCharString
- struct Asn132BitCharString
- struct Asn1CharArray
- struct Asn1CharSet
- struct Asn116BitCharSet
- struct _SListNode
- struct _SList
- struct _**DListNode**
- struct _DList
- struct Asn1SizeCnst
- struct ASN1BUFFER
- struct ASN1BUFSAVE
- struct ASN1ErrLocn
- struct ASN1ErrInfo
- struct **OOCTXT**

Defines

```
#define TV_UNIV 0
                      /* universal
                      /* application-wide
#define TV_APPL 1
#define TV CTXT 2
                      /* context-specific
#define TV_PRIV 3
                      /* private-use
#define TV PRIM 0
                       /* primitive
#define TV CONS 1
                       /* constructor
#define TM_UNIV 0x00000000 /* universal class
#define TM_APPL 0x40000000 /* application-wide class */
#define TM CTXT 0x80000000 /* context-specific class */
#define TM PRIV 0xC0000000 /* private-use class
                                                   */
#define TM_PRIM 0x00000000 /* primitive form
```

```
#define TM CONS 0x20000000 /* constructor form
#define TM IDCODE 0x1FFFFFFF /* ID code mask
#define ASN K BADTAG 0xFFFFFFF /* invalid tag code
#define ASN K NOTAG 0xFFFFFFFF /* no tag input parameter
#define TM_CLASS 0xC0 /* class mask
                                                */
#define TM_FORM 0x20 /* form mask
#define TM_CLASS_FORM 0xE0 /* class/form mask
#define TM_B_IDCODE 0x1F /* id code mask (byte)
#define MINMSGLEN 8
                          /* minimum message length
#define ASN OK 0
                    /* normal completion status
                            /* message fragment detected
#define ASN OK FRAG 2
#define ASN E BUFOVFLW -1
                                 /* encode buffer overflow
#define ASN_E_ENDOFBUF -2
                                /* unexpected end of buffer on decode */
#define ASN_E_IDNOTFOU -3
                                /* identifer not found
                               /* invalid object identifier
#define ASN E INVOBJID -4
#define ASN E INVLEN -5
                             /* invalid field length
#define ASN_E_INVENUM -6
                               /* enumerated value not in defined set */
#define ASN_E_SETDUPL -7
                               /* duplicate element in set
                                /* missing required element in set
#define ASN E SETMISRO -8
                                /* element not part of set
#define ASN_E_NOTINSET -9
                                  /* sequence of field overflow
#define ASN_E_SEQOVFLW -10
                              /* invalid option encountered in choice */
#define ASN E INVOPT -11
#define ASN_E_NOMEM -12
                              /* no dynamic memory available
#define ASN_E_INVHEXS -14
                               /* invalid hex string
                                                           */
#define ASN E INVBINS -15
                              /* invalid binary string
                               /* invalid real value
#define ASN_E_INVREAL -16
#define ASN_E_STROVFLW -17
                                  /* octet or bit string field overflow */
                                 /* invalid value specification
#define ASN_E_BADVALUE -18
                                 /* no def found for ref'd defined value */
#define ASN E UNDEFVAL -19
#define ASN_E_UNDEFTYP -20
                                 /* no def found for ref'd defined type */
#define ASN_E_BADTAG -21
                               /* invalid tag value
#define ASN_E_TOODEEP -22
                                /* nesting level is too deep
#define ASN E CONSVIO -23
                                /* value constraint violation
#define ASN_E_RANGERR -24
                                /* invalid range (lower > upper)
#define ASN_E_ENDOFFILE -25
                                  /* end of file on file decode
#define ASN_E_INVUTF8 -26
                               /* invalid UTF-8 encoding
#define ASN_E_CONCMODF -27
                                  /* Concurrent list modification
                                /* Illegal state error
#define ASN E ILLSTATE -28
                                  /* out of bounds (of array, etc)
#define ASN_E_OUTOFBND -29
#define ASN_E_INVPARAM -30
                                 /* invalid parameter
#define ASN_E_INVFORMAT -31
                                   /* invalid time string format
#define ASN_E_NOTINIT -32
                               /* not initialized
#define ASN E TOOBIG -33
                              /* value is too big for given data type */
#define ASN_E_INVCHAR -34
                                /* invalid character (not in char set) */
#define ASN_E_XMLSTATE -35
                                 /* XML state error
                                                              */
#define ASN E XMLPARSE -36
                                 /* XML parse error
                                 /* SEQUENCE elements not in order
#define ASN E SEQORDER -37
#define ASN_E_INVINDEX -38
                                /* invalid index for TC id
#define ASN_E_INVTCVAL -39
                                 /* invalid value for TC field
                                                               */
#define ASN_E_FILNOTFOU -40
                                  /* file not found
                                                               */
#define ASN E FILEREAD -41
                                /* error occurred reading file
                                  /* error occurred writing file
#define ASN_E_FILEWRITE -42
                                 /* invalid base64 encoding
#define ASN_E_INVBASE64 -43
```

```
#define ASN E INVSOCKET -44 /* invalid socket operation
#define ASN E XMLLIBNFOU -45 /* XML library is not found
                                                              */
#define ASN_E_XMLLIBINV -46 /* XML library is invalid
#define ASN_E_NOTSUPP -99 /* non-supported ASN construct
                                                               */
#define ASN_K_INDEFLEN -9999 /* indefinite length message indicator */
#define ASN ID EOC 0
                         /* end of contents
#define ASN_ID_BOOL 1
                           /* boolean
#define ASN_ID_INT 2
                         /* integer
#define ASN_ID_BITSTR 3
                             /* bit string
#define ASN_ID_OCTSTR 4
                             /* byte (octet) string
#define ASN ID NULL 5
                           /* null
#define ASN_ID_OBJID 6
                           /* object ID
#define ASN_ID_OBJDSC 7
                             /* object descriptor
#define ASN_ID_EXTERN 8
                              /* external type
#define ASN ID REAL 9
                           /* real
#define ASN ID ENUM 10
                           /* enumerated value
#define ASN_ID_EPDV 11
                           /* EmbeddedPDV type
#define ASN_ID_RELOID 13
                              /* relative object ID
#define ASN ID SEQ 16
                          /* sequence, sequence of
#define ASN_ID_SET 17
                         /* set, set of
#define ASN_SEQ_TAG 0x30 /* SEQUENCE universal tag byte */
#define ASN SET TAG 0x31 /* SET universal tag byte
#define ASN_ID_NumericString 18
#define ASN ID PrintableString 19
#define ASN_ID_TeletexString 20
#define ASN_ID_T61String ASN_ID_TeletexString
#define ASN_ID_VideotexString 21
#define ASN_ID_IA5String 22
#define ASN ID UTCTime 23
#define ASN ID GeneralTime 24
#define ASN_ID_GraphicString 25
#define ASN ID VisibleString 26
#define ASN ID GeneralString 27
#define ASN_ID_UniversalString 28
#define ASN_ID_BMPString 30
#define XM SEEK 0x01 /* seek match until found or end-of-buf */
#define XM ADVANCE 0x02 /* advance pointer to contents on match */
#define XM DYNAMIC 0x04 /* alloc dyn mem for decoded variable */
#define XM_SKIP 0x08 /* skip to next field after parsing tag */
#define ASN_K_MAXDEPTH 32
                                 /* maximum nesting depth for messages */
#define ASN_K_MAXSUBIDS 128 /* maximum sub-id's in an object ID
#define ASN_K_MAXENUM 100 /* maximum enum values in an enum type */
#define ASN K MAXERRP 5
                               /* maximum error parameters
#define ASN_K_MAXERRSTK 8
                                  /* maximum levels on error ctxt stack */
#define ASN_K_ENCBUFSIZ 16*1024 /* dynamic encode buffer extent size */
#define ASN K MEMBUFSEG 1024 /* memory buffer extent size
#define NUM ABITS 4
#define NUM UBITS 4
#define NUM_CANSET " 0123456789"
#define PRN_ABITS 8
#define PRN UBITS 7
#define PRN CANSET " '()+,-
```

./0123456789:=?ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz"

- #define **VIS ABITS** 8
- #define **VIS UBITS** 7
- #define VIS CANSET
- #define **T61 ABITS** 8
- #define **T61_UBITS** 7
- #define **T61_CANSET**
- #define **IA5_ABITS** 8
- #define **IA5_UBITS** 7
- #define IA5_CANSET
- #define IA5 RANGE1 LOWER 0
- #define IA5_RANGE2_LOWER 0x5f
- #define **GEN_ABITS** 8
- #define **GEN_UBITS** 7
- #define **GEN_CANSET**
- #define **BMP ABITS** 16
- #define **BMP UBITS** 16
- #define **BMP_FIRST** 0
- #define **BMP_LAST** 0xffff
- #define **UCS_ABITS** 32
- #define **UCS UBITS** 32
- #define UCS_FIRST 0
- #define UCS LAST 0xfffffffful
- #define **ASN1TAG_LSHIFT** 24
- #define **ASN1UINT MAX** 4294967295U
- #define **ASN1INT_MAX** ((ASN1INT)2147483647L)
- #define **ASN1INT_MIN** ((ASN1INT)(-ASN1INT_MAX-1))
- #define **ASN1INT64** long
- #define **XM_K_MEMBLKSIZ** (4*1024)
- #define **ASN1DYNCTXT** 0x8000
- #define **ASN1INDEFLEN** 0x4000
- #define **ASN1TRACE** 0x2000
- #define **ASN1LASTEOC** 0x1000
- #define **ASN1FASTCOPY** 0x0800 /* turns on the "fast copy" mode */
- #define **ASN1CONSTAG** 0x0400 /* form of last parsed tag */
- #define **ASN1CANXER** 0x0200 /* canonical XER
- #define **ASN1SAVEBUF** 0x0100 /* do not free dynamic encode buffer */
- #define **ASN10PENTYPE** 0x0080 /* item is an open type field */
- #define **ASN1MAX**(a, b) (((a)>(b))?(a):(b))
- #define **ASN1MIN**(a, b) (((a)<(b))?(a):(b))
- #define **ALLOC_ASN1ARRAY**(pctxt, pseqof, type)

Allocate a dynamic array.

#define ALLOC_ASN1ELEM(pctxt, type) (type*) memHeapAllocZ (&(pctxt)->pTypeMemHeap, sizeof(type))

Allocate and zero an ASN.1 element.

- #define **ALLOC_ASN1ELEMDNODE**(pctxt, type)
- #define **ASN1MALLOC**(pctxt, nbytes) memHeapAlloc(&(pctxt)->pTypeMemHeap, nbytes) *Allocate memory*.
- #define ASN1MEMFREE(pctxt) memHeapFreeAll(&(pctxt)->pTypeMemHeap)

Free memory associated with a context.

 #define ASN1MEMFREEPTR(pctxt, pmem) memHeapFreePtr(&(pctxt)->pTypeMemHeap, (void*)pmem)

Free memory pointer.

- #define **ASN1BUFCUR**(cp) (cp)->buffer.data[(cp)->buffer.byteIndex]
- #define **ASN1BUFPTR**(cp) &(cp)->buffer.data[(cp)->buffer.byteIndex]
- #define **ASN1CRTMALLOC0**(nbytes) malloc(nbytes)
- #define **ASN1CRTFREE0**(ptr) free(ptr)
- #define **ASN1CRTMALLOC** memHeapAlloc
- #define **ASN1CRTFREE** ASN1MEMFREEPTR
- #define **DE_INCRBITIDX**(pctxt)
- #define **DE_BIT**(pctxt, pvalue)
- #define **encodeIA5String**(pctxt, value, permCharSet) encodeConstrainedStringEx (pctxt, value, permCharSet, 8, 7, 7)
- #define encodeGeneralizedTime encodeIA5String
- #define decodeIA5String(pctxt, pvalue, permCharSet) decodeConstrainedStringEx (pctxt, pvalue, permCharSet, 8, 7, 7)
- #define **decodeGeneralizedTime** decodeIA5String
- #define **ZEROCONTEXT**(pctxt) memset(pctxt,0,sizeof(OOCTXT))
- #define LOG_ASN1ERR(ctxt, stat) errSetData(&(ctxt)->errInfo,stat,__FILE__,__LINE__)
- #define LOG_ASN1ERR_AND_FREE(pctxt, stat, lctxt) freeContext ((lctxt)), LOG_ASN1ERR(pctxt, stat)
- #define **RT MH DONTKEEPFREE** 0x1
- #define **OSRTMH_PROPID_DEFBLKSIZE** 1
- #define **OSRTMH_PROPID_SETFLAGS** 2
- #define OSRTMH PROPID CLEARFLAGS 3
- #define **OSRTMH PROPID USER** 10
- #define **memAlloc**(pctxt, nbytes) memHeapAlloc(&(pctxt)->pTypeMemHeap,nbytes) *Allocate memory*.
- #define **memAllocZ**(pctxt, nbytes) memHeapAllocZ(&(pctxt)->pTypeMemHeap,nbytes) *Allocate and zero memory*.
- #define memRealloc(pctxt, mem_p, nbytes) memHeapRealloc(&(pctxt)->pTypeMemHeap, (void*)mem_p, nbytes)

Reallocate memory.

#define memFreePtr(pctxt, mem_p)

Free memory pointer.

#define memFree(pctxt) memHeapFreeAll(&(pctxt)->pTypeMemHeap)

Free memory associated with a context.

• #define **memReset**(pctxt) memHeapReset(&(pctxt)->pTypeMemHeap) *Reset memory associated with a context.*

- #define **OSCDECL**
- #define **INCRBITIDX**(pctxt)
- #define **DECODEBIT**(pctxt, pvalue)
- #define decodeUnconsInteger(pctxt, pvalue) decodeSemiConsInteger(pctxt, pvalue, ASN1INT_MIN)

This function will decode an unconstrained integer.

- #define **decodeUnconsUnsigned**(pctxt, pvalue) decodeSemiConsUnsigned(pctxt, pvalue, 0U) *This function will decode an unconstrained unsigned integer.*
- #define **encodeUnconsInteger**(pctxt, value) encodeSemiConsInteger(pctxt,value,ASN1INT_MIN) *This function encodes an unconstrained integer.*

Typedefs

- typedef char ASN1CHAR
- typedef unsigned char **ASN1OCTET**
- typedef ASN1OCTET **ASN1BOOL**
- typedef signed char ASN1INT8
- typedef unsigned char **ASN1UINT8**
- typedef int ASN1INT
- typedef unsigned int **ASN1UINT**
- typedef ASN1INT ASN1ENUM
- typedef double ASN1REAL
- typedef short ASN1SINT
- typedef unsigned short **ASN1USINT**
- typedef ASN1UINT **ASN1TAG**
- typedef ASN1USINT **ASN116BITCHAR**
- typedef ASN1UINT **ASN132BITCHAR**
- typedef void * ASN1ANY
- typedef const char * **ASN1GeneralizedTime**
- typedef const char * ASN1GeneralString
- typedef const char * ASN1GraphicString
- typedef const char * ASN1IA5String
- typedef const char * ASN1ISO646String
- typedef const char * **ASN1NumericString**
- typedef const char * ASN1ObjectDescriptor
- typedef const char * ASN1PrintableString
- typedef const char * ASN1TeletexString
- typedef const char * ASN1T61String
- typedef const char * ASN1UTCTime
- typedef const char * ASN1UTF8String
- typedef const char * ASN1VideotexString
- typedef const char * ASN1VisibleString
- typedef Asn116BitCharString ASN1BMPString
- typedef Asn132BitCharString ASN1UniversalString
- typedef _SListNode SListNode
- typedef _SList SList
- typedef _DListNode

- typedef DList **DList**
- typedef _Asn1SizeCnst Asn1SizeCnst
- typedef OOCTXT OOCTXT
- typedef void *OSCDECL * **OSMallocFunc** (size_t size)
- typedef void *OSCDECL * **OSReallocFunc** (void *ptr, size_t size)

Functions

- EXTERN int **initContextBuffer** (OOCTXT *pctxt, const ASN1OCTET *bufaddr, ASN1UINT bufsiz) *This function assigns a buffer to a context block.*
- EXTERN int **initContext** (OOCTXT *pctxt)

This function initializes a context block.

• EXTERN void **freeContext** (OOCTXT *pctxt)

This function frees all dynamic memory associated with a context.

• EXTERN OOCTXT * newContext (void)

This function allocates a new OOCTXT block and initializes it.

- EXTERN void **copyContext** (OOCTXT *pdest, OOCTXT *psrc)
- EXTERN int **initSubContext** (OOCTXT *pctxt, OOCTXT *psrc)
- EXTERN void **setCtxtFlag** (OOCTXT *pctxt, ASN1USINT mask)
- EXTERN void **clearCtxtFlag** (OOCTXT *pctxt, ASN1USINT mask)
- EXTERN int **setPERBuffer** (OOCTXT *pctxt, ASN1OCTET *bufaddr, ASN1UINT bufsiz, ASN1BOOL aligned)
- EXTERN int setPERBufferUsingCtxt (OOCTXT *pTarget, OOCTXT *pSource)
- EXTERN DListNode * **dListAppend** (OOCTXT *pctxt, DList *pList, void *pData) *This function appends an item to the linked list structure.*
- EXTERN DListNode * **dListAppendNode** (OOCTXT *pctxt, DList *pList, void *pData)
- EXTERN DListNode * **dListFindByIndex** (DList *pList, int index)
- EXTERN void **dListInit** (DList *pList)

This function initializes a doubly linked list structure.

• EXTERN void **dListFreeNodes** (OOCTXT *pctxt, DList *pList)

This function removes all nodes from the linked list and releases the memory that was allocated for storing the node structures (DListNode).

• EXTERN void **dListFreeAll** (OOCTXT *pctxt, DList *pList)

This function removes all nodes from the linked list structure and releases the memory that was allocated for storing the node structures (DListNode) and for data.

• EXTERN void **dListRemove** (DList *pList, DListNode *node)

This function removes a node from the linked list structure.

EXTERN void sListInit (SList *pList)

This function is used to initialize a singly-linked list.

• EXTERN void **sListInitEx** (OOCTXT *pctxt, SList *pList)

This function is used to initialize a singly-linked list and assigns a context to be used for the list.

• EXTERN void **sListFree** (SList *pList)

This function is used to free-up all the nodes in the singly-linked list.

• EXTERN SList * sListCreate (void)

This function is used to create a new singly-linked list.

• EXTERN SList * **sListCreateEx** (OOCTXT *pctxt)

This function is used to create a singly-linked list.

• EXTERN SListNode * **sListAppend** (SList *pList, void *pData)

This function is used to append a new data member to the list.

• EXTERN ASN1BOOL **sListFind** (SList *pList, void *pData)

This function is used to search for a particular data in the list.

• EXTERN void **sListRemove** (SList *pList, void *pData)

This function is used to remove a particular data member from the list.

• EXTERN int **errAddIntParm** (ASN1ErrInfo *pErrInfo, int errParm)

This function adds an integer parameter to an error information structure.

• EXTERN int errAddStrParm (ASN1ErrInfo *pErrInfo, const char *errprm_p)

This function adds an string parameter to an error information structure.

• EXTERN int **errAddUIntParm** (ASN1ErrInfo *pErrInfo, unsigned int errParm)

This function adds an unsigned integer parameter to an error information structure.

• EXTERN int **errCopyData** (ASN1ErrInfo *pSrcErrInfo, ASN1ErrInfo *pDestErrInfo)

• EXTERN void **errFreeParms** (ASN1ErrInfo *pErrInfo)

This function frees memory associated with the storage of parameters associated with an error message.

• EXTERN char * errFmtMsg (ASN1ErrInfo *pErrInfo, char *bufp)

• EXTERN char * errGetText (OOCTXT *pctxt)

This function gets the text of the error.

• EXTERN void **errPrint** (ASN1ErrInfo *pErrInfo)

This function prints error information to the standard output device.

• EXTERN int **errReset** (ASN1ErrInfo *pErrInfo)

This function resets the error information in the error information sturcture.

• EXTERN int errSetData (ASN1ErrInfo *pErrInfo, int status, const char *module, int lno) This function sets error information in an error information structure.

- typedef **void** (OSCDECL *OSFreeFunc)(void *ptr)
- EXTERN void **memHeapAddRef** (void **ppvMemHeap)
- EXTERN void * memHeapAlloc (void **ppvMemHeap, int nbytes)
- EXTERN void * memHeapAllocZ (void **ppvMemHeap, int nbytes)
- EXTERN int memHeapCheckPtr (void **ppvMemHeap, void *mem p)
- EXTERN int **memHeapCreate** (void **ppvMemHeap)
- EXTERN void **memHeapFreeAll** (void **ppvMemHeap)
- EXTERN void memHeapFreePtr (void **ppvMemHeap, void *mem_p)
- EXTERN void * memHeapRealloc (void **ppvMemHeap, void *mem_p, int nbytes_)
- EXTERN void **memHeapRelease** (void **ppvMemHeap)
- EXTERN void **memHeapReset** (void **ppvMemHeap)
- EXTERN void * memHeapMarkSaved (void **ppvMemHeap, const void *mem_p, ASN1BOOL saved)
- EXTERN void **memHeapSetProperty** (void **ppvMemHeap, ASN1UINT propId, void *pProp)
- EXTERN void **memSetAllocFuncs** (OSMallocFunc malloc_func, OSReallocFunc realloc_func, OSFreeFunc free func)

This function sets the pointers to standard allocation functions.

- EXTERN void **memFreeOpenSeqExt** (OOCTXT *pctxt, DList *pElemList)
- EXTERN void memHeapSetFlags (OOCTXT *pctxt, ASN1UINT flags)
- EXTERN void memHeapClearFlags (OOCTXT *pctxt, ASN1UINT flags)
- EXTERN void memHeapSetDefBlkSize (OOCTXT *pctxt, ASN1UINT blkSize)

This function sets the pointer to standard allocation functions.

• EXTERN ASN1UINT memHeapGetDefBlkSize (OOCTXT *pctxt)

This function returns the actual granularity of memory blocks.

• EXTERN int **decodeBits** (OOCTXT *pctxt, ASN1UINT *pvalue, ASN1UINT nbits)

This function will decode a series of multiple bits and place the results in an unsigned integer variable.

• EXTERN int **decodeBitString** (OOCTXT *pctxt, ASN1UINT *numbits_p, ASN1OCTET *buffer, ASN1UINT bufsiz)

This function will decode a value of the ASN.1 bit string type whose maximum size is is known in advance.

• EXTERN int **decodeBMPString** (OOCTXT *pctxt, ASN1BMPString *pvalue, Asn116BitCharSet *permCharSet)

This function will decode a variable of the ASN.1 BMP character string.

• EXTERN int **decodeByteAlign** (OOCTXT *pctxt)

This function will position the decode bit cursor on the next byte boundary.

• EXTERN int **decodeConsInteger** (OOCTXT *pctxt, ASN1INT *pvalue, ASN1INT lower, ASN1INT upper)

This function will decode an integer constrained either by a value or value range constraint.

• EXTERN int **decodeConsUnsigned** (OOCTXT *pctxt, ASN1UINT *pvalue, ASN1UINT lower, ASN1UINT upper)

This function will decode an unsigned integer constrained either by a value or value range constraint.

• EXTERN int **decodeConsUInt8** (OOCTXT *pctxt, ASN1UINT8 *pvalue, ASN1UINT lower, ASN1UINT upper)

This function will decode an 8-bit unsigned integer constrained either by a value or value range constraint.

• EXTERN int **decodeConsUInt16** (OOCTXT *pctxt, ASN1USINT *pvalue, ASN1UINT lower, ASN1UINT upper)

This function will decode a 16-bit unsigned integer constrained either by a value or value range constraint.

• EXTERN int **decodeConsWholeNumber** (OOCTXT *pctxt, ASN1UINT *padjusted_value, ASN1UINT range_value)

This function decodes a constrained whole number as specified in Section 10.5 of the X.691 standard.

- EXTERN int **decodeConstrainedStringEx** (OOCTXT *pctxt, const char **string, const char *charSet, ASN1UINT abits, ASN1UINT ubits, ASN1UINT canSetBits)

 This function decodes a constrained string value.
- EXTERN int **decodeDynBitString** (OOCTXT *pctxt, ASN1DynBitStr *pBitStr) *This function will decode a variable of thr ASN.1 BIT STRING type.*
- EXTERN int decodeDynOctetString (OOCTXT *pctxt, ASN1DynOctStr *pOctStr)

 This function will decode a value of the ASN.1 octet string type whose maximum size is known in advance.
- EXTERN int **decodeLength** (OOCTXT *pctxt, ASN1UINT *pvalue) *This function will decode a length determinant value.*
- EXTERN int moveBitCursor (OOCTXT *pctxt, int bitOffset)
- EXTERN int **decodeObjectIdentifier** (OOCTXT *pctxt, ASN1OBJID *pvalue) *This function decodes a value of the ASN.1 object identifier type.*
- EXTERN int **decodeOctetString** (OOCTXT *pctxt, ASN1UINT *numocts_p, ASN1OCTET *buffer, ASN1UINT bufsiz)

This function will decode a value of the ASN.1 octet string type whose maximun size is known in advance.

• EXTERN int **decodeOpenType** (OOCTXT *pctxt, const ASN1OCTET **object_p2, ASN1UINT *numocts p)

This function will decode an ASN.1 open type.

- EXTERN int decodeSmallNonNegWholeNumber (OOCTXT *pctxt, ASN1UINT *pvalue)

 This function will decode a small non-negative whole number as specified in Section 10.6 of the X.691 standard.
- EXTERN int **decodeSemiConsInteger** (OOCTXT *pctxt, ASN1INT *pvalue, ASN1INT lower) *This function will decode a semi-constrained integer.*
- EXTERN int **decodeSemiConsUnsigned** (OOCTXT *pctxt, ASN1UINT *pvalue, ASN1UINT lower) *This function will decode a semi-constrained unsigned integer.*
- EXTERN int **decodeVarWidthCharString** (OOCTXT *pctxt, const char **pvalue)
- EXTERN int **encodeBit** (OOCTXT *pctxt, ASN1BOOL value)

 This function will encode a variable of the ASN.1 BOOLEAN type in a single bit.
- EXTERN int **encodeBits** (OOCTXT *pctxt, ASN1UINT value, ASN1UINT nbits) *This function encodes multiple bits.*
- EXTERN int **encodeBitString** (OOCTXT *pctxt, ASN1UINT numocts, const ASN1OCTET *data) *This function will encode a value of the ASN.1 bit string type.*
- EXTERN int **encodeBMPString** (OOCTXT *pctxt, ASN1BMPString value, Asn116BitCharSet *permCharSet)

This function will encode a variable of the ASN.1 BMP character string.

- EXTERN int **encodeByteAlign** (OOCTXT *pctxt)

 This function will position the encode bit cursor on the next byte boundry.
- EXTERN int **encodeCheckBuffer** (OOCTXT *pctxt, ASN1UINT nbytes)

 This function will determine if the given number of bytes will fit in the encode buffer.
- EXTERN int **encodeConstrainedStringEx** (OOCTXT *pctxt, const char *string, const char *charSet, ASN1UINT abits, ASN1UINT abits, ASN1UINT canSetBits)

 This function encodes a constrained string value.
- EXTERN int encodeConsInteger (OOCTXT *pctxt, ASN1INT value, ASN1INT lower, ASN1INT upper)

This function encodes an integer constrained either by a value or value range constraint.

• EXTERN int **encodeConsUnsigned** (OOCTXT *pctxt, ASN1UINT value, ASN1UINT lower, ASN1UINT upper)

This function encodes an unsigned integer constrained either by a value or value range constraint.

EXTERN int encodeConsWholeNumber (OOCTXT *pctxt, ASN1UINT adjusted_value, ASN1UINT range_value)

This function encodes a constrained whole number as specified in Section 10.5 of the X.691 standard.

- EXTERN int **encodeExpandBuffer** (OOCTXT *pctxt, ASN1UINT nbytes) *This function will expand the buffer to hold the given number of bytes.*
- EXTERN ASN1OCTET * encodeGetMsgPtr (OOCTXT *pctxt, int *pLength) This function will return the message pointer and length of an encoded message.
- EXTERN int **encodeLength** (OOCTXT *pctxt, ASN1UINT value) *This function will encode a length determinant value.*
- EXTERN int **encodeObjectIdentifier** (OOCTXT *pctxt, ASN1OBJID *pvalue) *This function encodes a value of the ASN.1 object identifier type.*
- EXTERN int **encodebitsFromOctet** (OOCTXT *pctxt, ASN1OCTET value, ASN1UINT nbits) *This function encodes bits from a given octet to the output buffer.*
- EXTERN int **encodeOctets** (OOCTXT *pctxt, const ASN1OCTET *pvalue, ASN1UINT nbits) *This fuction will encode an array of octets.*
- EXTERN int **encodeOctetString** (OOCTXT *pctxt, ASN1UINT numocts, const ASN1OCTET *data) *This function will encode a value of the ASN.1 octet string type.*
- EXTERN int **encodeOpenType** (OOCTXT *pctxt, ASN1UINT numocts, const ASN1OCTET *data) *This function will encode an ASN.1 open type.*
- EXTERN int **encodeOpenTypeExt** (OOCTXT *pctxt, DList *pElemList) *This function will encode an ASN.1 open type extension.*
- EXTERN int encodeOpenTypeExtBits (OOCTXT *pctxt, DList *pElemList)
- EXTERN int encodeSmallNonNegWholeNumber (OOCTXT *pctxt, ASN1UINT value)

 This function will endcode a small, non-negative whole number as specified in Section 10.6 of teh X.691 standard.
- EXTERN int **encodeSemiConsInteger** (OOCTXT *pctxt, ASN1INT value, ASN1INT lower) *This function encodes a semi-constrained integer*.
- EXTERN int **encodeSemiConsUnsigned** (OOCTXT *pctxt, ASN1UINT value, ASN1UINT lower) *This function encodes an semi-constrained unsigned integer.*
- EXTERN int **encodeVarWidthCharString** (OOCTXT *pctxt, const char *value)

- EXTERN int addSizeConstraint (OOCTXT *pctxt, Asn1SizeCnst *pSize)
- EXTERN ASN1BOOL alignCharStr (OOCTXT *pctxt, ASN1UINT len, ASN1UINT nbits, Asn1SizeCnst *pSize)
- EXTERN int **bitAndOctetStringAlignmentTest** (Asn1SizeCnst *pSizeList, ASN1UINT itemCount, ASN1BOOL bitStrFlag, ASN1BOOL *pAlignFlag)
- EXTERN int **getPERMsgLen** (OOCTXT *pctxt)
- EXTERN Asn1SizeCnst * getSizeConstraint (OOCTXT *pctxt, ASN1BOOL extbit)
- EXTERN int **checkSizeConstraint** (OOCTXT *pctxt, int size)
- EXTERN ASN1UINT getUIntBitCount (ASN1UINT value)
- EXTERN Asn1SizeCnst * checkSize (Asn1SizeCnst *pSizeList, ASN1UINT value, ASN1BOOL *pExtendable)
- EXTERN void **init16BitCharSet** (Asn116BitCharSet *pCharSet, ASN116BITCHAR first, ASN116BITCHAR last, ASN1UINT abits, ASN1UINT ubits)
- EXTERN ASN1BOOL isExtendableSize (Asn1SizeCnst *pSizeList)
- EXTERN void **set16BitCharSet** (OOCTXT *pctxt, Asn116BitCharSet *pCharSet, Asn116BitCharSet *pAlphabet)
- EXTERN const char * **rtBitStrToString** (ASN1UINT numbits, const ASN1OCTET *data, char *buffer, size t bufsiz)
- EXTERN const char * rtOctStrToString (ASN1UINT numocts, const ASN1OCTET *data, char *buffer, size_t bufsiz)

Detailed Description

Common ASN.1 runtime constants, data structure definitions, and run-time functions to support BER/DER/PER as defined in the ITU-T standards.

Definition in file **ooasn1.h**.

ooCalls.h File Reference

This file contains Call management functions. #include "ootypes.h"

Functions

- EXTERN **ooCallData** * **ooCreateCall** (char *type, char *callToken) *This function is used to create a new call entry.*
- EXTERN int **ooAddCallToList** (**ooEndPoint** *h323ep, **ooCallData** *call) This function is used to add a call to the list of existing calls.
- EXTERN **ooCallData** * **ooFindCallByToken** (char *callToken)

 This function is used to find a call by using the unique token for the call.
- EXTERN int **ooEndCall** (**ooCallData** *call) *This function is used to clear a call.*
- EXTERN int **ooRemoveCallFromList** (**ooEndPoint** *h323ep, **ooCallData** *call) This function is used to remove a call from the list of existing calls.
- EXTERN int ooCleanCall (ooCallData *call)

 This function is used to clean a call.
- EXTERN ooLogicalChannel * ooAddNewLogicalChannel (ooCallData *call, int channelNo, int sessionID, char *type, char *dir, ooH323EpCapability *epCap)

 This function is used to add a new logical channel entry into the list of currently active logical channels.
- $\bullet \quad EXTERN \ \textbf{ooLogicalChannel}*\ \textbf{ooFindLogicalChannelByLogicalChannelNo} \ (\textbf{ooCallData}*\ \textbf{call, int channelNo})\\$

This function is used to find a logical channel by logical channel number.

- EXTERN int **ooOnLogicalChannelEstablished** (**ooCallData** *call, **ooLogicalChannel** *pChannel) *This function is called when a new logical channel is established.*
- EXTERN ASN1BOOL **ooIsSessionEstablished** (**ooCallData** *call, int sessionID, char *dir) This fuction is used to check whether a specified session in specified direction is active for the call.
- EXTERN **ooLogicalChannel** * **ooGetLogicalChannel** (**ooCallData** *call, int sessionID) *This function is used to retrieve a logical channel with particular sessionID.*

• EXTERN int **ooRemoveLogicalChannel** (**ooCallData** *call, int ChannelNo) *This function is used to remove a logical channel from the list of logical channels.*

• EXTERN int **ooClearLogicalChannel** (**ooCallData** *call, int channelNo) *This function is used to cleanup a logical channel.*

• EXTERN int ooClearAllLogicalChannels (ooCallData *call)

This function is used to cleanup all the logical channels associated with the call.

• EXTERN int **ooAddMediaInfo** (**ooCallData** *call, ooMediaInfo mediaInfo)

This function can be used by an application to specify media endpoint information for different types of media.

• EXTERN ooLogicalChannel * ooFindLogicalChannelByOLC (ooCallData *call, H245OpenLogicalChannel *olc)

This function is used to find a logical channel from a received olc.

• EXTERN ooLogicalChannel * ooFindLogicalChannel (ooCallData *call, int sessionID, char *dir, H245DataType *dataType)

This function is used to find a logical channel based on session Id, direction of channel and datatype.

Detailed Description

This file contains Call management functions.

Definition in file ooCalls.h.

ooCapability.h File Reference

This file contains Capability management functions.

```
#include "ootypes.h"
#include "ooasn1.h"
```

Defines

- #define OO AUCAPS MIN 1
- #define OO_CAP_ULAW_64k_240 1 /* g711 ulaw 64k 240 frs/pkt */
- #define **OO_CAP_ULAW_64k_180** 2
- #define OO_CAP_ULAW_64k_30 3
- #define OO CAP ULAW 64k MAX 3
- #define OO_CAP_ULAW_56k_MIN 4
- #define OO_CAP_ULAW_56k_240 4
- #define OO CAP ULAW 56k 180 5
- #define OO CAP ULAW 56k 30 6
- #define OO_CAP_ULAW_56k_MAX 6
- #define OO CAP ALAW 64k MIN 7
- #define **OO_CAP_ALAW_64k_240** 7
- #define **OO CAP ALAW 64k 180** 8
- #define **OO CAP ALAW 64k 30** 9
- #define OO CAP ALAW 64k MAX 9
- #define OO_CAP_ALAW_56k_MIN 10
- #define **OO_CAP_ALAW_56k_240** 10
- #define OO CAP ALAW 56k 180 11
- #define **OO CAP ALAW 56k 30** 12
- #define OO_CAP_ALAW_56k_MAX 12
- #define **OO CAP GSM** 13
- #define OO CAP G729A 14
- #define OO CAP SPEEX 15
- #define **OO_CAP_G723 1** 16
- #define OO AUCAPS MAX 16

Functions

• EXTERN int ooAddCapability (int cap, int dir, cb_StartReceiveChannel startReceiveChannel, cb_StartTransmitChannel startTransmitChannel, cb_StopReceiveChannel stopReceiveChannel, cb_StopTransmitChannel stopTransmitChannel)

This function is used to add a new capability to the endpoint.

- H245AudioCapability * ooCreateAudioCapability (int cap, OOCTXT *pctxt)
 This function is used to create a audio capability structure using the capability type.
- H245AudioCapability * **ooCreateG711Capability** (int cap, OOCTXT *pctxt) *This function is used to create a g711 audio capability structure.*

• **ooH323EpCapability** * **ooIsAudioCapSupported** (**ooCallData** *call, H245AudioCapability *audioCap, int dir)

This function is used to determine whether a particular capability can be supported by the endpoint.

- int **ooCompareAudioCaps** (int cap, H245AudioCapability *audioCap, int dir) *This function is used to determine a capability match.*
- int **ooCompareUlawCaps** (int cap, H245AudioCapability *audioCap, int dir) *This function is used to determine a ulaw capability match.*
- int **ooCompareAlawCaps** (int cap, H245AudioCapability *audioCap, int dir) *This function is used to determine a Alaw capability match.*
- **ooH323EpCapability** * **ooIsDataTypeSupported** (**ooCallData** *call, H245DataType *data, int dir) *This function is used to determine whether a particular datatype can be supported by the endpoint.*

Detailed Description

This file contains Capability management functions.

Definition in file ooCapability.h.

oochannels.h File Reference

This file contains functions to create and use channels.

```
#include "H323-MESSAGES.h"
#include "MULTIMEDIA-SYSTEM-CONTROL.h"
#include "ootypes.h"
#include "ooSocket.h"
```

Defines

- #define **OORECEIVER** 1
- #define **OOTRANSMITTER** 2
- #define **OODUPLEX** 3

Functions

- EXTERN int **ooCreateH323Listener** (void)

 This function is used to create a listener for incoming calls.
- EXTERN int ooCreateH245Listener (ooCallData *call)
 This function is used to create a listener for incoming H.245 connections.
- EXTERN int ooAcceptH225Connection (void)
 This function is used to accept incoming H.225 connections.
- EXTERN int **ooAcceptH245Connection** (**ooCallData** *call) *This function is used to accept an incoming H.245 connection.*
- EXTERN int ooCreateH225Connection (ooCallData *call)
 This function is used to create an H.225 connection to the remote end point.
- EXTERN int ooCreateH245Connection (ooCallData *call)

 This function is used to setup an H.245 connection with the remote endpoint for control negotiations.
- EXTERN int ooCloseH225Connection (ooCallData *call) *This function is used to close an H.225 connection.*
- EXTERN int **ooCloseH245Connection** (**ooCallData** *call) *This function is used to close an H.245 connection for a call.*
- EXTERN int **ooMonitorChannels** (void)

 This function is used to start monitoring channels for the calls.

• EXTERN int ooStopMonitorCalls (void)

This function is called to stop the monitor channels thread.

• EXTERN int ooH2250Receive (ooCallData *call)

This function is used to receive an H.2250 message received on a calls H.225 channel.

• EXTERN int **ooH245Receive** (**ooCallData** *call)

This function is used to receive an H.245 message received on a calls H.245 channel.

• EXTERN int ooSendH225Msg (ooCallData *call, Q931Message *msg)

This function is used to enqueue an H.225 message into an outgoing queue for the call.

• EXTERN int ooSendH245Msg (ooCallData *call, H245Message *msg)

This function is used to enqueue an H.245 message into an outgoing queue for the call.

• EXTERN int **ooSendMsg** (**ooCallData** *call, int type)

This function is used to Send a message on the channel, when channel is available for write.

• EXTERN int **ooOnSendMsg** (**ooCallData** *call, int msgType)

This function is called after a message is sent on the call's channel.

Detailed Description

This file contains functions to create and use channels.

Definition in file **oochannels.h**.

ooCommon.h File Reference

Common runtime constant and type definitions.

```
#include <limits.h>
#include <stdio.h>
#include <string.h>
#include <stdlib.h>
#include <sys/types.h>
#include <sys/time.h>
#include <sys/socket.h>
#include <netinet/in.h>
#include <netdb.h>
#include <unistd.h>
#include <arpa/inet.h>
```

Data Structures

• struct **_OOMsgBuf**

Defines

- #define **OOUINT32_MAX** 4294967295U
- #define **OOINT32 MAX** ((OOINT32)2147483647L)
- #define OOINT32_MIN ((OOINT32)(-OOINT32_MAX-1))
- #define **FALSE** 0
- #define **TRUE** 1
- #define **OOERRINVPARAM** (-50) /* Invalid parameter */
- #define **OOERRBUFOVFLW** (-51) /* Buffer overflow */
- #define **OOERRNOMEM** (-52) /* No dynamic memory available */
- #define **OOMEMALLOC** malloc
- #define **OOMEMFREE** free
- #define **OOMAX**(a, b) (((a)>(b))?(a):(b))
- #define **OOMIN**(a, b) (((a)<(b))?(a):(b))
- #define EXTERN

Typedefs

- typedef char OOCHAR cruntime C Runtime Common Constant and Type Definitions.
- typedef unsigned char **OOUCHAR**
- typedef signed char OOINT8
- typedef unsigned char **OOUINT8**
- typedef short **OOINT16**
- typedef unsigned short OOUINT16
- typedef int OOINT32
- typedef unsigned int OOUINT32

- typedef OOUINT8 OOBOOLtypedef _OOMsgBuf OOMsgBuf

Detailed Description

Common runtime constant and type definitions.

Definition in file **ooCommon.h**.

ooDateTime.h File Reference

Time functions that reconcile differences between Windows and UNIX.

```
#include "ooCommon.h"
#include <time.h>
```

Functions

EXTERN int ooGetTimeOfDay (struct timeval *tv, struct timezone *tz)
 This function provides an abstraction for the UNIX 'gettimeofday' function which is not available on Windows.

Detailed Description

Time functions that reconcile differences between Windows and UNIX.

Definition in file **ooDateTime.h**.

Function Documentation

EXTERN int ooGetTimeOfDay (struct timeval * tv, struct timezone * tz)

This function provides an abstraction for the UNIX 'gettimeofday' function which is not available on Windows.

Parameters:

tv Pointer to time value structure to receive current time value.

tz Point to time zone information.

Returns:

Completion status of operation: 0 = success, negative return value is error.

ooh245.h File Reference

This file contains functions to support H245 negotiations.

```
#include "ooasn1.h"
#include "ootypes.h"
#include "oochannels.h"
#include "oo.h"
#include "ooq931.h"
#include "MULTIMEDIA-SYSTEM-CONTROL.h"
```

Functions

- EXTERN int ooCreateH245Message (H245Message **msg, int type)

 Creates an outgoing H245 message of the type specified by the type argument for the Application context.
- EXTERN int **ooFreeH245Message** (**H245Message** *pmsg) *Frees up the memory used by the H245 message*.
- EXTERN int **ooGetOutgoingH245Msgbuf** (**ooCallData** *call, ASN1OCTET *msgbuf, int *len, int *msgType)

This function is used to retrieve an H.245 message enqueued in the outgoing queue.

- EXTERN int **ooSendTermCapMsg** (**ooCallData** *call)

 This function is used to send out a treminal capability set message.
- EXTERN ASN1UINT **ooGenerateStatusDeterminationNumber** ()
 This function is used to generate a random status determination number for MSD procedure.
- EXTERN int **ooHandleMasterSlave** (**ooCallData** *call, void *pmsg, int msgType)

 This fuction is used to handle received MasterSlaveDetermination procedure messages.
- EXTERN int **ooSendMasterSlaveDetermination** (**ooCallData** *call) *This function is used to send MSD message.*
- EXTERN int **ooSendMasterSlaveDeterminationAck** (**ooCallData** *call, char *status) *This function is used to send a MasterSlaveDeterminationAck message.*
- EXTERN int **ooHandleOpenLogicalChannel** (**ooCallData** *call, H245OpenLogicalChannel *olc) *This function is used to handle received OpenLogicalChannel message.*
- EXTERN int **ooHandleOpenLogicalAudioChannel** (**ooCallData** *call, H245OpenLogicalChannel *olc)

This function is used to handle a received OpenLogicalChannel message which is trying to open a audio channel.

• EXTERN int ooOnReceivedOpenLogicalChannelAck (ooCallData *call,

H245OpenLogicalChannelAck *olcAck)

This function is used to handle a received OpenLogicalChannelAck message.

 $\bullet \quad \text{int } \textbf{ooOnReceivedOpenLogicalChannelRejected} \ (\textbf{ooCallData} \ * \textbf{call},$

H245OpenLogicalChannelReject *olcRejected)

This function is used to handle the received OpenLogicalChannelReject message.

• EXTERN int ooSendEndSessionCommand (ooCallData *call)

This message is used to send an EndSession command.

• EXTERN int ooHandleH245Command (ooCallData *call, H245CommandMessage *command)

This function is used to handle a received H245Command message.

• EXTERN int ooOnReceivedTerminalCapabilitySetAck (ooCallData *call)

This function is called on receiving a TreminalCapabilitySetAck message.

• EXTERN int ooCloseAllLogicalChannels (ooCallData *call)

This function is called to close all the open logical channels.

• EXTERN int ooSendCloseLogicalChannel (ooCallData *call, ooLogicalChannel *logicalChan)

This function is used to send out a CloseLogicalChannel message for a particular logical channel.

• EXTERN int ooOnReceivedCloseLogicalChannel (ooCallData *call, H245CloseLogicalChannel

This function is used to process a received closeLogicalChannel request.

• EXTERN int ooOnReceivedCloseChannelAck (ooCallData *call, H245CloseLogicalChannelAck *clcAck)

This function is used to process a received CloseLogicalChannelAck message.

• EXTERN int ooHandleH245Message (ooCallData *call, H245Message *pmsg)

This function is used to handle received H245 message.

• EXTERN int ooOnReceivedTerminalCapabilitySet (ooCallData *call, H245Message *pmsg)

This function is used to process received TCS message.

• EXTERN int ooH245AcknowledgeTerminalCapabilitySet (ooCallData *call)

This function is used to send a TCSAck message to remote endpoint.

• EXTERN int ooOpenLogicalChannels (ooCallData *call)

This function is used to start OpenLogicalChannel procedure for all the channels to be opened for the call.

• EXTERN int ooOpenLogicalAudioChannel (ooCallData *call)

This function is used to send OpenLogicalChannel message for audio channel.

- EXTERN int **ooOpenG711ULaw64KChannel** (**ooCallData** *call, **ooH323EpCapability** *epCap) This function is used to build a OpenLogicalChannel message using G711ULaw64K capability.
- $\bullet \quad \text{EXTERN int } \textbf{ooSendRequestCloseLogicalChannel (ooCallData *call, ooLogicalChannel *logicalChan)} \\$

This function is used to request a remote end point to close a logical channel.

• EXTERN int ooOnReceivedRequestChannelClose (ooCallData *call, H245RequestChannelClose *rclc)

This function handles the received RequestChannelClose message, verifies that the requested channel is forward channel.

- EXTERN int **ooBuildOpenLogicalChannelAudio** (**ooCallData** *call, H245OpenLogicalChannel *olc, **ooH323EpCapability** *epCap, OOCTXT *pctxt)

 Builds an OLC with an audio capability passed as parameter.
- EXTERN int **ooSendAsTunneledMessage** (**ooCallData** *call, ASN1OCTET *msgbuf, int len, int msgType)

This function sends an encoded H.245 message buffer as a tunneled H.245 message.

Detailed Description

This file contains functions to support H245 negotiations.

Definition in file **ooh245.h**.

ooh323.h File Reference

This file contains functions to support H.225 messages.

```
#include "ooasn1.h"
#include "ootypes.h"
#include "oo.h"
#include "ooq931.h"
#include "MULTIMEDIA-SYSTEM-CONTROL.h"
```

Functions

- EXTERN int **ooOnReceivedSetup** (**ooCallData** *call, **Q931Message** *q931Msg) *This function is used to process a received SETUP message.*
- EXTERN int **ooOnReceivedSignalConnect** (**ooCallData** *call, **Q931Message** *q931Msg) *This function is used to process a received CONNECT message.*
- EXTERN int **ooHandleH2250Message** (**ooCallData** *call, **Q931Message** *q931Msg) *This function is used to handle received H.2250 messages.*
- EXTERN int **ooOnReceivedFacility** (**ooCallData** *call, **Q931Message** *pQ931Msg) *This function is used to process a received Facility message.*
- EXTERN int ooHandleTunneledH245Messages (ooCallData *call, H225H323_UU_PDU *pH323UUPdu)
 This function is used to process tunneled H245 messages.
- EXTERN int **ooHandleStartH245FacilityMessage** (**ooCallData** *call, H225Facility_UUIE *facility) *This is a helper function used to handle an startH245 Facility message.*
- EXTERN int **ooRetrieveAliases** (**ooCallData** *call, H225_SeqOfH225AliasAddress *pAddresses) *This function is used to retrieve the aliases from Sequence of alias addresses.*

Detailed Description

This file contains functions to support H.225 messages.

Definition in file **ooh323.h**.

ooh323ep.h File Reference

This file contains H323 endpoint related functions.

#include "ootypes.h"
#include "ooasn1.h"

Functions

- EXTERN int **ooInitializeH323Ep** (const char *tracefile, int h245Tunneling, int fastStart, int termType, int t35CountryCode, int t35Extension, int manufacturer, char *productID, char *versionID, int callType, int listenport, char *callerid, char *callername, int callMode)

 This function is the first function to be invoked before using stack.
- EXTERN int **ooSetLocalCallSignallingAddress** (char *localip, int listenport) *This function is used to assign a local ip address to be used for call signalling.*
- EXTERN int ooSetAliasH323ID (char *h323id)
 This function is used to set the h323id alias for the endpoint.
- EXTERN int **ooSetAliasDialedDigits** (char *dialedDigits)

 This function is used to set the dialed digits alias for the endpoint.
- EXTERN int **ooSetAliasURLID** (char *url)

 This function is used to set the url alias for the endpoint.
- EXTERN int ooSetAliasEmailID (char *email)

 This function is used to set an email id as an alias for the endpoint.
- EXTERN int **ooSetAliasTransportID** (char *ipaddress) *This function is used to set an ip address as an alias.*
- EXTERN int ooH323EpRegisterCallbacks (cb_OnAlerting onAlerting, cb_OnIncomingCall onIncomingCall, cb_OnOutgoingCallAdmitted onOutgoingCallAdmitted, cb_OnOutgoingCall onOutgoingCall, cb_OnCallEstablished onCallEstablished, cb_OnCallCleared onCallCleared) This function is used to register the H323 Endpoint callback functions.
- EXTERN int **ooDestroyH323Ep** (void)

 This function is the last function to be invoked after done using the stack.
- EXTERN int ooEnableAutoAnswer (void)

 This function is used to enable the auto answer feature for incoming calls.
- EXTERN int ooDisableAutoAnswer (void)

This function is used to disable the auto answer feature for incoming calls.

• EXTERN int **ooSetFastStart** (int fastStart)

This function is used to enable/disable faststart.

• EXTERN int **ooSetH245Tunneling** (int tunneling)

This function is used to enable/disable tunneling.

• EXTERN int **ooSetProductID** (char *productID)

This function is used to set the product ID.

• EXTERN int **ooSetVersionID** (char *versionID)

This function is used to set version id.

• EXTERN int **ooSetCallerID** (char *callerID)

This function is used to set callerid to be used for outbound calls.

• EXTERN int **ooSetCallerName** (char *callerName)

This function is used to set the caller name, which is used for display purposes.

Detailed Description

This file contains H323 endpoint related functions.

Definition in file **ooh323ep.h**.

ooports.h File Reference

This file contains functions to manage ports used by the stack. #include "ootypes.h"

Defines

- #define OOTCP 1
- #define **OOUDP** 2
- #define **OORTP** 3

Functions

- EXTERN int **ooSetTCPPorts** (int start, int max)
 Sets the range of ports that can be potentially used for TCP connections.
- EXTERN int **ooSetUDPPorts** (int start, int max)
 Sets the range of ports that can be potentially used for UDP transport.
- EXTERN int **ooSetRTPPorts** (int start, int max)
 Sets the range of ports that can be potentially used for RTP RTCP transport.
- EXTERN int **ooGetNextPort** (**ooEndPoint** *ep, int type)

 Get the next port of type TCP/UDP/RTP from the corresponding range.
- EXTERN int **ooBindPort** (**ooEndPoint** *ep, int type, **OOSOCKET** socket)

 Bind socket to a port within the port range specified by the application at the startup.

Detailed Description

This file contains functions to manage ports used by the stack.

Definition in file **ooports.h**.

Function Documentation

EXTERN int ooBindPort (ooEndPoint * ep, int type, OOSOCKET socket)

Bind socket to a port within the port range specified by the application at the startup.

Parameters:

ep Reference to H323 Endpoint structure. *type* Type of the port required for the socket. *socket* The socket to be bound.

Returns:

In case of success returns the port number to which socket is bound and in case of failure just returns a negative value.

EXTERN int ooGetNextPort (ooEndPoint * ep, int type)

Get the next port of type TCP/UDP/RTP from the corresponding range.

When max value for the range is reached, it starts again from the first port number of the range.

Parameters:

```
ep Reference to the H323 Endpoint structure. type Type of the port to be retrieved(OOTCP/OOUDP/OORTP).
```

Returns:

The next port number for the specified type is returned.

EXTERN int ooSetRTPPorts (int start, int max)

Sets the range of ports that can be potentially used for RTP RTCP transport.

Parameters:

```
start Starting port number for the range. max Ending port number for the range
```

Returns:

Completion status of operation: 0 (OO_OK) = success, negative return value is error.

EXTERN int ooSetTCPPorts (int start, int max)

Sets the range of ports that can be potentially used for TCP connections.

Parameters:

```
start Starting port number for the range. max Ending port number for the range
```

Returns:

Completion status of operation: 0 (OO_OK) = success, negative return value is error.

EXTERN int ooSetUDPPorts (int start, int max)

Sets the range of ports that can be potentially used for UDP transport.

Parameters:

start Starting port number for the range. *max* Ending port number for the range

Returns:

Completion status of operation: 0 (OO_OK) = success, negative return value is error.

ooq931.h File Reference

This file contains functions to support call signalling.

```
#include "ooasn1.h"
#include "ootypes.h"
#include "H323-MESSAGES.h"
```

Data Structures

• struct Q931InformationElement

Defines

- #define **Q931_E_TOOSHORT** (-1001)
- #define **Q931_E_INVCALLREF** (-1002)
- #define **Q931_E_INVLENGTH** (-1003)

Typedefs

• typedef Q931InformationElement Q931InformationElement

Enumerations

- enum Q931MsgTypes { Q931NationalEscapeMsg = 0x00, Q931AlertingMsg = 0x01, Q931CallProceedingMsg = 0x02, Q931ConnectMsg = 0x07, Q931ConnectAckMsg = 0x0f, Q931ProgressMsg = 0x03, Q931SetupMsg = 0x05, Q931SetupAckMsg = 0x0d, Q931ResumeMsg = 0x26, Q931ResumeAckMsg = 0x2e, Q931ResumeRejectMsg = 0x22, Q931SuspendMsg = 0x25, Q931SuspendAckMsg = 0x2d, Q931SuspendRejectMsg = 0x21, Q931UserInformationMsg = 0x20, Q931DisconnectMsg = 0x45, Q931ReleaseMsg = 0x4d, Q931ReleaseCompleteMsg = 0x5a, Q931RestartMsg = 0x46, Q931RestartAckMsg = 0x4e, Q931SegmentMsg = 0x60, Q931CongestionCtrlMsg = 0x79, Q931InformationMsg = 0x7b, Q931NotifyMsg = 0x6e, Q931StatusMsg = 0x7d, Q931StatusEnquiryMsg = 0x75, Q931FacilityMsg = 0x62 }
- enum Q931IECodes { Q931BearerCapabilityIE = 0x04, Q931CauseIE = 0x08, Q931FacilityIE = 0x1c, Q931ProgressIndicatorIE = 0x1e, Q931CallStateIE = 0x14, Q931DisplayIE = 0x28, Q931SignalIE = 0x34, Q931CallingPartyNumberIE = 0x6c, Q931CalledPartyNumberIE = 0x70, Q931RedirectingNumberIE = 0x74, Q931UserUserIE = 0x7e }
- enum Q931InformationTransferCapability { Q931TransferSpeech,
 Q931TransferUnrestrictedDigital = 8, Q931TransferRestrictedDigital = 9,
 Q931Transfer3_1kHzAudio = 16, Q931TransferUnrestrictedDigitalWithTones = 17,
 Q931TransferVideo = 24 }
- enum Q931CauseValues { Q931NoRouteToNetwork = 0x02, Q931NoRouteToDestination = 0x03, Q931ChannelUnacceptable = 0x06, Q931NormalCallClearing = 0x10, Q931UserBusy = 0x11, Q931NoResponse = 0x12, Q931NoAnswer = 0x13, Q931SubscriberAbsent = 0x14, Q931CallRejected = 0x15, Q931NumberChanged = 0x16, Q931Redirection = 0x17, Q931DestinationOutOfOrder = 0x1b, Q931InvalidNumberFormat = 0x1c, Q931StatusEnquiryResponse = 0x1e, Q931NoCircuitChannelAvailable = 0x22, Q931Congestion = 0x2a, Q931InvalidCallReference = 0x51, Q931ErrorInCauseIE = 0 }

- enum Q931SignalInfo { Q931SignalDialToneOn, Q931SignalRingBackToneOn, Q931SignalInterceptToneOn, Q931SignalNetworkCongestionToneOn, Q931SignalBusyToneOn, Q931SignalConfirmToneOn, Q931SignalAnswerToneOn, Q931SignalCallWaitingTone, Q931SignalOffhookWarningTone, Q931SignalPreemptionToneOn, Q931SignalTonesOff = 0x3f, Q931SignalAlertingPattern0 = 0x40, Q931SignalAlertingPattern1, Q931SignalAlertingPattern2, Q931SignalAlertingPattern3, Q931SignalAlertingPattern4, Q931SignalAlertingPattern5, Q931SignalAlertingPattern6, Q931SignalAlertingPattern7, Q931SignalAlertingOff = 0x4f, O931SignalErrorInIE = 0x100 }
- enum Q931NumberingPlanCodes { Q931UnknownPlan = 0x00, Q931ISDNPlan = 0x01, Q931DataPlan = 0x03, Q931TelexPlan = 0x04, Q931NationalStandardPlan = 0x08, Q931PrivatePlan = 0x09, Q931ReservedPlan = 0x0f }
- enum Q931TypeOfNumberCodes { Q931UnknownType = 0x00, Q931InternationalType = 0x01, Q931NationalType = 0x02, Q931NetworkSpecificType = 0x03, Q931SubscriberType = 0x04, Q931AbbreviatedType = 0x06, Q931ReservedType = 0x07 }

Functions

- EXTERN int **ooQ931Decode** (**Q931Message** *msg, int length, ASN1OCTET *data) *This function is invoked to decode a Q931 message.*
- EXTERN int **ooDecodeUUIE** (**Q931Message** *q931Msg)

 This function is used to decode the UUIE of the message from the list of ies.
- EXTERN int ooEncodeUUIE (Q931Message *q931msg)

 This function is used to encode the UUIE field of the Q931 message.
- EXTERN Q931InformationElement * **ooQ931GetIE** (const **Q931Message** *q931msg, int ieCode) *This function is invoked to retrieve an IE element from a Q931 message.*
- EXTERN void **ooQ931Print** (const **Q931Message** *q931msg) *This function is invoked to print a Q931 message.*
- EXTERN int **ooCreateQ931Message** (**Q931Message** **msg, int msgType) *This function is invoked to create an outgoing Q931 message.*
- EXTERN ASN1USINT **ooGenerateCallReference** ()

 This function is invoked to generate a unique call reference number.
- EXTERN int **ooGenerateCallIdentifier** (H225CallIdentifier *callid) *This function is used to generate a unique call identifier for the call.*
- EXTERN int **ooFreeQ931Message** (**Q931Message** *q931Msg)

 This function is invoked to release the memory used up by a Q931 message.
- EXTERN int ooGetOutgoingQ931Msgbuf (ooCallData *call, ASN1OCTET *msgbuf, int *len, int *msgType)

This function is invoked to retrive the outgoing message buffer for Q931 message.

• EXTERN int ooSendReleaseComplete (ooCallData *call)

This function is invoked to send a ReleaseComplete message for the currently active call.

• EXTERN int ooSendCallProceeding (ooCallData *call)

This function is invoked to send a call proceeding message in response to received setup message.

• EXTERN int ooSendAlerting (ooCallData *call)

This function is invoked to send alerting message in response to received setup message.

• EXTERN int ooSendFacility (ooCallData *call)

This function is invoked to send Facility message.

• EXTERN int ooSendConnect (ooCallData *call)

This function is invoked to send a Connect message in response to received setup message.

• EXTERN int **ooH323MakeCall** (char *dest, char *callToken)

This function is used to send a SETUP message for outgoing call.

• int ooH323CallAdmitted (ooCallData *call)

Helper function used to make a call once it is approved by the Gk.

• EXTERN int **ooH323HangCall** (char *callToken)

This function is used to handup a currently active call.

• EXTERN int ooAcceptCall (ooCallData *call)

Function to accept a call by sending connect.

• EXTERN int ooH323MakeCall_helper (ooCallData *call)

An helper function to ooMakeCall.

• int **ooParseDestination** (**ooCallData** *call, char *dest)

This function is used to parse the destination.

Detailed Description

This file contains functions to support call signalling.

Definition in file **ooq931.h**.

ooras.h File Reference

This file contains functions to support RAS protocol.

```
#include "ooasn1.h"
#include "ootypes.h"
#include "H323-MESSAGES.h"
```

Data Structures

• struct **ooRasMessage**Defines the RAS message structure.

• struct ooRasParams

Defines

- #define __USING_RAS
- #define OORAS DEFAULT REMOTE PORT 1719

Typedefs

• typedef **ooRasMessage ooRasMessage**Defines the RAS message structure.

Enumerations

- enum RasGatekeeperMode { RasNoGatekeeper = 0, RasDiscoverGatekeeper = 1,
 RasUseSpecificGatekeeper = 2 }
- enum RasCallModel { RasDirect = 0, RasGkRouted }
- enum RasCallType { RasPointToPoint = 0, RasOneToN, RasnToOne, RasnToN }

Functions

 EXTERN int ooInitRas (int localRasPort, enum RasGatekeeperMode eGkMode, char *szGkAddr, int iGkPort)

This function is used to initialize the Ras module by setting gatekeeper mode and Creating Ras Channel.

EXTERN int ooDestroyRas (void)

This function is used to destroy RasModule.

• EXTERN void **ooRasExplorer** ()

This function is called periodically to monitor the process the RAS channel.

 EXTERN int ooRasFillAlias (OOCTXT *psContext, ooAliases *psAliases, H225_SeqOfH225AliasAddress *psAliasList)
 Populate Alias list.

• EXTERN OOSOCKET ooRasGetSocket ()

This function is invoked to get current RAS socket.

• EXTERN int ooRasReceive ()

This function is invoked receive data from RAS port.

• EXTERN int **ooRasSetGatekeeperMode** (enum RasGatekeeperMode eGkMode, char *szGkAddr, int iGkPort)

This function is invoked to set a gatekeeper mode.

• EXTERN enum RasGatekeeperMode ooRasGetGatekeeperMode ()

This function is invoked to get current gatekeeper mode.

• EXTERN ASN1BOOL ooRasIsRegistered ()

This function is used to determine the registration status of the endpoint with the gatekeeper.

• EXTERN int **ooRasSendAdmissionRequest** (**ooCallData** *call, enum RasCallModel eModel, ooAliases *psSrcAliases, ooAliases *psDestAliases)

This function is invoked to request bandwith admission for a call.

• EXTERN int ooRasSendDisengageRequest (ooCallData *call)

This function is invoked to request call disengage to gatekeeper.

Detailed Description

This file contains functions to support RAS protocol.

Definition in file **ooras.h**.

oosndrtp.h File Reference

This file contains functions to read from sound device and playback.

```
#include <stdlib.h>
#include "ootypes.h"
#include <dlfcn.h>
```

Typedefs

- typedef int(* **MediaAPI_CreateTxRTPChan**)(int *channelId, char *destip, int port) Signature for function to Create Tx RTP channel.
- typedef int(* **MediaAPI_CloseTxRTPChan**)(int) Signature for function to Close Tx RTP channel.
- typedef int(* **MediaAPI_CreateRecvRTPChan**)(int *channelId, char *localip, int localport) Signature for function to Create Rx RTP channel.
- typedef int(* MediaAPI_CloseRecvRTPChan)(int) Signature for function to Close Rx RTP channel.
- typedef int(* MediaAPI_StartTxWaveFile)(int channelId, char *filename)
 Signature for function to Start transmission of media file.
- typedef int(* **MediaAPI_StopTxWaveFile**)(int channelId) Signature for function to Stop transmission of media file.
- typedef int(* MediaAPI_StartTxMic)(int channelId)
 Signature for function to Start transmitting captured audio from microphone.
- typedef int(* MediaAPI_StopTxMic)(int channelId)
 Signature for function to Stop transmitting microphone data.
- typedef int(* MediaAPI_StartRecvAndPlayback)(int channelId)
 Signature for function to Start receiving rtp data and playback.
- typedef int(* **MediaAPI_StopRecvAndPlayback**)(int channelId) Signature for function to stop receiving rtp data.
- typedef int(* MediaAPI_InitializePlugin)(void)
 Signature for function to Initialize the media plug-in.

Functions

• EXTERN int ooLoadSndRTPPlugin (char *name)

Loads the media plugin into the process space.

• EXTERN int ooReleaseSndRTPPlugin (void)

Unloads the plug-in from process space.

• EXTERN int ooCreateTransmitRTPChannel (char *destip, int port)

Creates a transmit RTP channel.

• EXTERN int ooCloseTransmitRTPChannel (void)

Closes a transmit RTP channel.

• EXTERN int ooCreateReceiveRTPChannel (char *localip, int localport)

Creates a receive RTP channel.

• EXTERN int ooCloseReceiveRTPChannel (void)

Closes a receive RTP channel.

• EXTERN int **ooStartTransmitWaveFile** (char *filename)

Start transmitting a audio file.

• EXTERN int ooStopTransmitWaveFile (void)

Stop transmission of a audio file.

• EXTERN int **ooStartTransmitMic** (void)

Starts capturing audio data from mic and transmits it as rtp stream.

• EXTERN int **ooStopTransmitMic** (void)

Stop transmission of mic audio data.

• EXTERN int ooStartReceiveAudioAndPlayback (void)

Starts receiving rtp stream data and play it on the speakers.

• EXTERN int ooStopReceiveAudioAndPlayback (void)

Stop receiving rtp stream data. This calls corresponding interface function of the plug-in library.

• EXTERN int ooStartReceiveAudioAndRecord (void)

Not supported currently.

• EXTERN int ooStopReceiveAudioAndRecord (void)

Not supported currently.

- EXTERN int **ooSetLocalRTPAndRTCPAddrs** (void) Set local RTP and RTCP addresses for the session.
- EXTERN int **ooRTPShutDown** (void) Closes transmit and receive RTP channels, if open.

Variables

• void * media

Detailed Description

This file contains functions to read from sound device and playback.

It also provides a wrapper for oRTP function calls and creates threads for receiving and sending rtp packets.

Definition in file **oosndrtp.h**.

ooSocket.h File Reference

Common runtime constants, data structure definitions, and run-time functions to support the sockets' operations.

```
#include <sys/types.h>
#include "sys/time.h"
#include <sys/socket.h>
#include <netinet/in.h>
#include <netdb.h>
#include <unistd.h>
#include <arpa/inet.h>
#include "ooasn1.h"
```

Defines

- #define OOSOCKET_INVALID ((OOSOCKET)-1)
- #define OOIPADDR_ANY ((OOIPADDR)0)
- #define OOIPADDR_LOCAL ((OOIPADDR)0x7f000001UL) /* 127.0.0.1 */

Typedefs

• typedef int **OOSOCKET**Socket's handle.

• typedef unsigned long **OOIPADDR**

The IP address represented as unsigned long value.

Functions

• EXTERN int **ooSocketAccept** (**OOSOCKET** socket, **OOSOCKET** *pNewSocket, **OOIPADDR** *destAddr, int *destPort)

This function permits an incoming connection attempt on a socket.

- EXTERN int **ooSocketAddrToStr** (**OOIPADDR** ipAddr, char *pbuf, int bufsize) *This function converts an IP address to its string representation.*
- EXTERN int **ooSocketBind** (**OOSOCKET** socket, **OOIPADDR** addr, int port) *This function associates a local address with a socket.*
- EXTERN int **ooSocketClose** (**OOSOCKET** socket) *This function closes an existing socket.*
- EXTERN int ooSocketConnect (OOSOCKET socket, const char *host, int port)

This function establishes a connection to a specified socket.

• EXTERN int ooSocketCreate (OOSOCKET *psocket)

This function creates a socket.

• EXTERN int ooSocketCreateUDP (OOSOCKET *psocket)

This function creates a UDP datagram socket.

• EXTERN int ooSocketsInit (void)

This function initiates use of sockets by an application.

• EXTERN int ooSocketsCleanup (void)

This function terminates use of sockets by an application.

• EXTERN int ooSocketListen (OOSOCKET socket, int maxConnection)

This function places a socket a state where it is listening for an incoming connection.

• EXTERN int ooSocketRecv (OOSOCKET socket, ASN1OCTET *pbuf, ASN1UINT bufsize)

This function receives data from a connected socket.

• EXTERN int ooSocketRecvFrom (OOSOCKET socket, ASN1OCTET *pbuf, ASN1UINT bufsize,

char *remotehost, int *remoteport)

This function receives data from a connected/unconnected socket.

• EXTERN int ooSocketSend (OOSOCKET socket, const ASN1OCTET *pdata, ASN1UINT size)

This function sends data on a connected socket.

• EXTERN int **ooSocketSendTo** (**OOSOCKET** socket, const ASN1OCTET *pdata, ASN1UINT size, const char *remotehost, int remoteport)

This function sends data on a connected or unconnected socket.

EXTERN int ooSocketSelect (int nfds, fd_set *readfds, fd_set *writefds, fd_set *exceptfds, struct timeval *timeout)

This function is used for synchronous monitoring of multiple sockets.

• EXTERN int ooSocketStrToAddr (const char *pIPAddrStr, OOIPADDR *pIPAddr)

This function converts the string with IP address to a double word representation.

• EXTERN int **ooGetLocalIPAddress** (char *pIPAddrs)

This function retrives the IP address of the local host.

• EXTERN long **ooHTONL** (long val)

• EXTERN short **ooHTONS** (short val)

Detailed Description

Common runtime constants, data structure definitions, and run-time functions to support the sockets' operations.

Definition in file **ooSocket.h**.

ooStackCmds.h File Reference

This file contains stack commands which an user application can use to make call, hang call etc. #include "ootypes.h"

Functions

- EXTERN int **ooMakeCall** (char *dest, char *callToken) *This function is used by an application to place a call.*
- EXTERN int **ooAnswerCall** (char *callToken) *This function is used to answer a call.*
- EXTERN int **ooRejectCall** (char *callToken, int cause) *This function is used to reject an incoming call.*
- EXTERN int **ooHangCall** (char *callToken)

 This function is used by an user application to hang a call.
- EXTERN int **ooStopMonitor** (void)

 This function is used by the user application to stop monitoring calls.

Detailed Description

This file contains stack commands which an user application can use to make call, hang call etc.

Definition in file ooStackCmds.h.

ootypes.h File Reference

This file contains the definitions of common constants and data structures.

```
#include "ooSocket.h"
#include "MULTIMEDIA-SYSTEM-CONTROL.h"
#include "H323-MESSAGES.h"
#include "ooasn1.h"
```

Data Structures

• struct ooCommand

Structure for stack commands.

• struct ooH323Ports

This structure is used to define the port ranges to be used by the application.

struct Q931Message

Defines the Q931 message structure.

• struct **H245Message**

Defines the H245 message structure.

- struct ooMediaInfo
- struct ooLogicalChannel

Structure to store information of logical channels for call.

- struct ooAliases
- struct ooCallData

Structure to store all the information related to a particular call.

struct ooH323EpCapability

Structure to store information related to end point capability.

struct ooEndPoint

Structure to store all the config information related to the endpoint created by an application.

Defines

- #define **OO_FAILED** -1
- #define **OO_OK** 1
- #define **OO_MasterSlave_Idle** 2

Various states of master slave determination prcedure.

- #define OO MasterSlave DetermineSent 3
- #define OO_MasterSlave_AckReceived 4
- #define OO MasterSlave Master 5
- #define OO MasterSlave Slave 6
- #define **OO_LocalTermCapExchange_Idle** 9 States for Capability Exchange Procedure.
- #define **OO LocalTermCapSetSent** 10
- #define OO_LocalTermCapSetAckRecvd 11
- #define OO_RemoteTermCapExchange_Idle 12
- #define OO_RemoteTermCapSetRecvd 13
- #define OO_RemoteTermCapSetAckSent 14
- #define **OO_FASTSTART_SENT** 15
- #define OO_FASTSTART_RECEIVED 16
- #define **OO FASTSTART ACCEPTED** 17
- #define **OO_FASTSTART_REFUSED** 18
- #define OO_CALL_ENDREASON_MIN 20 Call Clear Reasons.
- #define **OO UNKNOWN** 20
- #define OO_REMOTE_CLOSED_CONNECTION 21
- #define OO_REMOTE_CLOSED_H245_CONNECTION 22
- #define **OO REMOTE CLEARED** 23
- #define OO HOST CLEARED 24
- #define **OO NORMAL** 25
- #define OO_CALL_ENDREASON_MAX 25
- #define OO_CALL_STATE_MIN 50 call states
- #define **OO_CALL_CREATED** 50
- #define OO_CALL_WAITING_ADMISSION 51
- #define **OO_CALL_CONNECTING** 52
- #define **OO_CALL_CONNECTED** 53
- #define OO_CALL_CLEAR 54 /* call marked for clearing */
- #define OO_CALL_CLEAR_CLOLCS 55 /* Logical Channels closed*/
- #define OO_CALL_CLEAR_CLELCS 56 /* Logical Channels cleared*/
- #define OO_CALL_CLEAR_ENDSESSION 57 /* EndSession command sent*/
- #define OO_CALL_CLEAR_CLOSEH245 58 /* H245 sockets closed*/
- #define OO_CALL_CLEAR_RELEASE 59 /* Release Sent */
- #define OO_CALL_CLEARED 60 /* Call Cleared */
- #define **OO CALL STATE MAX** 60
- #define OO_H245SESSION_INACTIVE 61

H245 Session state.

- #define **OO H245SESSION ACTIVE** 62
- #define **OO_LOGICALCHAN_IDLE** 70

Logical Channel states.

- #define OO LOGICALCHAN PROPOSED 71
- #define OO LOGICALCHAN ESTABLISHED 72
- #define **OOTERMTYPE** 60 *Terminal type of the endpoint.*
- #define MAXLOGMSGLEN 2048
- #define **OO_MSGTYPE_MIN** 101

Various message types for H225 and H245 messages.

- #define OOO931MSG 101
- #define **OOH245MSG** 102
- #define **OOSetup** 103
- #define **OOCallProceeding** 104
- #define **OOAlert** 105
- #define **OOConnect** 106
- #define **OOReleaseComplete** 107
- #define **OOFacility** 108
- #define **OOMasterSlaveDetermination** 109
- #define **OOMasterSlaveAck** 110
- #define OOMasterSlaveReject 111
- #define **OOMasterSlaveRelease** 112
- #define **OOTerminalCapabilitySet** 113
- #define **OOTerminalCapabilitySetAck** 114
- #define OOTerminalCapabilitySetReject 115
- #define **OOOpenLogicalChannel** 116
- #define **OOOpenLogicalChannelAck** 117
- #define OOOpenLogicalChannelReject 118
- #define OOOpenLogicalChannelRelease 119
- #define **OOEndSessionCommand** 120
- #define OOCloseLogicalChannel 121
- #define OOCloseLogicalChannelAck 122
- #define **OORequestChannelClose** 123
- #define OORequestChannelCloseAck 124
- #define OO MSGTYPE MAX 125
- #define TCPPORTSSTART 12030

Default port ranges used.

- #define TCPPORTSEND 12230
- #define **UDPPORTSSTART** 13030
- #define **UDPPORTSEND** 13230
- #define **RTPPORTSSTART** 14030
- #define RTPPORTSEND 14230
- #define MAXMSGLEN 4096

Maximum length for received messages.

- #define OO_CMD_MAKECALL 201
- #define OO_CMD_ANSCALL 202
- #define **OO_CMD_REJECTCALL** 203
- #define **OO CMD HANGCALL** 204
- #define **OO_CMD_STOPMONITOR** 205

- #define OO_CALLMODE_AUDIOCALL 301 Endpoint call modes.
- #define **OO_CALLMODE_AUDIORX** 302
- #define OO_CALLMODE_AUDIOTX 303
- #define OO_CALLMODE_VIDEOCALL 304
- #define **OO_CALLMODE_FAX** 305

Typedefs

- typedef int(* ChannelCallback)(void *)

 Type of callback functions to be registered at the time of channel creation.
- typedef int(* CommandCallback)(void)
 Type of callback function registered at initialization for handling commands.
- typedef **ooCommand ooCommand** Structure for stack commands.
- typedef **Q931Message Q931Message** Defines the Q931 message structure.
- typedef H245Message H245Message Defines the H245 message structure.
- typedef ooMediaInfo ooMediaInfo
- typedef ooLogicalChannel ooLogicalChannel Structure to store information of logical channels for call.
- typedef ooAliases ooAliases
- typedef ooCallData ooCallData
 Structure to store all the information related to a particular call.
- typedef int(* cb_StartReceiveChannel)(ooCallData *call, ooLogicalChannel *pChannel)

 Call back for starting media receive channel.
- typedef int(* cb_StartTransmitChannel)(ooCallData *call, ooLogicalChannel *pChannel) callback for starting media transmit channel
- typedef int(* cb_StopReceiveChannel)(ooCallData *call, ooLogicalChannel *pChannel) callback to stop media receive channel
- typedef int(* cb_StopTransmitChannel)(ooCallData *call, ooLogicalChannel *pChannel) callback to stop media transmit channel

• typedef ooH323EpCapability ooH323EpCapability

Structure to store information related to end point capability.

- typedef int(* cb_OnAlerting)(ooCallData *call)
- typedef int(* cb OnIncomingCall)(ooCallData *call)
- typedef int(* cb_OnOutgoingCall)(ooCallData *call)
- typedef int(* cb_OnCallAnswered)(ooCallData *call)
- typedef int(* cb_OnCallCleared)(ooCallData *call)
- typedef int(* cb_OnCallEstablished)(ooCallData *call)
- typedef int(* cb_OnOutgoingCallAdmitted)(ooCallData *call)
- typedef ooEndPoint ooEndPoint

Structure to store all the config information related to the endpoint created by an application.

Variables

• int gCallTokenBase

Stores base value for generating new call token.

• int gCallTokenMax

Stores Max value for call token, at which token is reset.

• int gCurCallToken

Stores current value for call token generation.

• int **gMonitor**

• DList **gCmdList**

List of stack commands issued by application which have to be processed.

OOCTXT gCtxt

Context for stack commands list.

• pthread_mutex_t gCmdMutex

Mutex to protect access to stack commands list.

ooEndPoint gH323ep

Global endpoint structure.

Detailed Description

This file contains the definitions of common constants and data structures.

Definition in file **ootypes.h**.

Define Documentation

#define OO_CALLMODE_AUDIOCALL 301

Endpoint call modes.

The call mode of the endpoint dictates what type of channels are created for the calls placed by the endpoint or received by the endpoint.

Definition at line 164 of file ootypes.h.

#define OOTERMTYPE 60

Terminal type of the endpoint.

Default is 60.

Definition at line 103 of file ootypes.h.

Typedef Documentation

typedef struct H245Message H245Message

Defines the H245 message structure.

All request/response and command messages are represented using this structure.

typedef struct Q931Message Q931Message

Defines the Q931 message structure.

Contains context for memory allocation, protocol Discriminator, call reference, meesage type and list of user user IEs.

printHandler.h File Reference

This is an implementation of a simple print handler.

#include "asn1CEvtHndlr.h"

Functions

- void initializePrintHandler (Asn1NamedCEventHandler *printHandler, char *varname)
- void **finishPrint** ()
- void indent ()
- void **printStartElement** (const char *name, int index)
- void **printEndElement** (const char *name, int index)
- void **printBoolValue** (ASN1BOOL value)
- void printIntValue (ASN1INT value)
- void **printuIntValue** (ASN1UINT value)
- void **printBitStrValue** (ASN1UINT numbits, const ASN1OCTET *data)
- void **printOctStrValue** (ASN1UINT numocts, const ASN1OCTET *data)
- void **printCharStrValue** (const char *value)
- void printCharStr16BitValue (ASN1UINT nchars, ASN116BITCHAR *data)
- void printCharStr32BitValue (ASN1UINT nchars, ASN132BITCHAR *data)
- void **printNullValue** ()
- void **printOidValue** (ASN1UINT numSubIds, ASN1UINT *pSubIds)
- void **printRealValue** (double value)
- void **printEnumValue** (ASN1UINT value)
- void **printOpenTypeValue** (ASN1UINT numocts, const ASN1OCTET *data)

Variables

- Asn1NamedCEventHandler printHandler
- const char * pVarName
- int gIndentSpaces

Detailed Description

This is an implementation of a simple print handler.

It outputs the fields of an encoded PER message to stdout in a structured output format.. Definition in file **printHandler.h**.

rtctype.h File Reference

#include "ooasn1.h"

Defines

- #define **OS CTYPE UPPER** 0x1
- #define **OS_CTYPE_LOWER** 0x2
- #define **OS_CTYPE_NUMBER** 0x4
- #define OS CTYPE SPACE 0x8
- #define **OS CTYPE PUNCT** 0x10
- #define **OS CTYPE CTRL** 0x20
- #define **OS CTYPE HEX** 0x40
- #define **OS_CTYPE_BLANK** 0x80
- #define **OS_ISALPHA**(c)
 - $(rtCtypeTable[(unsigned)(c)]\&(OS_CTYPE_UPPER|OS_CTYPE_LOWER))\\$
- #define OS_ISUPPER(c) (rtCtypeTable[(unsigned)(c)]&OS_CTYPE_UPPER)
- #define **OS_ISLOWER**(c) (rtCtypeTable[(unsigned)(c)]&OS_CTYPE_LOWER)
- #define **OS_ISDIGIT**(c) (rtCtypeTable[(unsigned)(c)]&OS_CTYPE_NUMBER)
- #define **OS_ISXDIGIT**(c)
 - (rtCtypeTable[(unsigned)(c)]&(OS_CTYPE_HEX|OS_CTYPE_NUMBER))
- #define **OS_ISSPACE**(c) (rtCtypeTable[(unsigned)(c)]&OS_CTYPE_SPACE)
- #define **OS_ISPUNCT**(c) (rtCtypeTable[(unsigned)(c)]&OS_CTYPE_PUNCT)
- #define **OS_ISALNUM**(c) (rtCtypeTable[(unsigned)(c)]&(OS_CTYPE_UPPER|OS_CTYPE_LOWER|OS_CTYPE_NUMBER))
- #define **OS ISPRINT**(c)
- #define **OS ISGRAPH**(c)
- #define **OS_ISCNTRL**(c) (rtCtypeTable[(unsigned)(c)]&OS_CTYPE_CTRL)
- #define **OS_TOLOWER**(c) (OS_ISUPPER(c) ? (c) 'A' + 'a' : (c))
- #define **OS TOUPPER**(c) (OS ISLOWER(c)?(c) 'a' + 'A':(c))

Variables

• EXTERN const ASN1OCTET rtCtypeTable [256]

Detailed Description

Definition in file **rtctype.h**.

Define Documentation

#define OS_ISGRAPH(c)

Value:

```
(rtCtypeTable[(unsigned)(c)]& \
(OS_CTYPE_PUNCT|OS_CTYPE_UPPER|OS_CTYPE_LOWER|OS_CTYPE_NUMBER))
```

Definition at line 57 of file rtctype.h.

#define OS_ISPRINT(c)

Value:

```
(rtCtypeTable[(unsigned)(c)]& \
(OS_CTYPE_PUNCT|OS_CTYPE_UPPER|OS_CTYPE_LOWER|OS_CTYPE_NUMBER|OS_CTYPE_BLANK))
```

Definition at line 54 of file rtctype.h.

SList.h File Reference

```
Singly Linked list header file.
#include "ooasn1.h"
```

Defines

- #define **OSMSGMALLOC**(pctxt, nbytes) memHeapAlloc(&(pctxt)->pMsgMemHeap, nbytes)
- #define **OSMSGREALLOC**(pctxt, pmem, nbytes) memHeapRealloc(&(pctxt)->pMsgMemHeap, pmem, nbytes)
- #define **OSMSGREALLOCARRAY**(pctxt, pseqof, type)
- #define **OSMSGMEMFREE**(pctxt) memHeapFreeAll(&(pctxt)->pMsgMemHeap)
- #define **OSMSGMEMFREEPTR**(pctxt, pmem) memHeapFreePtr(&(pctxt)->pMsgMemHeap, pmem)
- #define **OSMSGMEMRESET**(pctxt) memHeapReset(&(pctxt)->pMsgMemHeap)

Detailed Description

Singly Linked list header file.

Definition in file **SList.h**.

Define Documentation

#define OSMSGREALLOCARRAY(pctxt, pseqof, type)

Value:

```
do {\
  if (sizeof(type)*(pseqof)->n < (pseqof)->n) return ASN_E_NOMEM; \
  if (((pseqof)->elem = (type*) memHeapRealloc \
    (&(pctxt)->pMsgMemHeap, (pseqof)->elem, sizeof(type)*(pseqof)->n)) == 0) \
  return ASN_E_NOMEM; \
} while (0)
```

Definition at line 32 of file SList.h.

Index

ALLOC_ASN1ARRAY	ooRemoveLogicalChannel, 36
mem, 17	Capability Management, 36
ALLOC_ASN1ELEM	capmgmt
mem, 17	ooAddCapability, 37
ALLOC_ASN1ELEMDNODE	ooCompareAlawCaps, 37
mem, 17	ooCompareAudioCaps, 37
Asn1CEventHandler, 2	ooCompareUlawCaps, 38
rtAddEventHandler, 9	ooCreateAudioCapability, 38
rtBitStrValue, 4	ooCreateG711Capability, 38
rtBoolValue, 4	ooIsAudioCapSupported, 38
rtCharStrValue, 5	ooIsDataTypeSupported, 39
rtCharStrValue16Bit, 5	Channel Management, 39
rtCharStrValue32Bit, 5	channels
rtEndElement, 6	ooAcceptH225Connection, 40
rtEnumValue, 6	ooAcceptH245Connection, 41
rtIntValue, 6	ooCloseH225Connection, 41
rtNullValue, 7	ooCloseH245Connection, 41
rtOctStrValue, 7	ooCreateH225Connection, 41
rtOidValue, 7	ooCreateH225Connection, 41
rtOpenTypeValue, 8	ooCreateH245Listener, 42
rtRealValue, 8	ooCreateH323Listener, 42
rtRemoveEventHandler, 9	ooH2250Receive, 42
rtStartElement, 8	ooH245Receive, 43
rtUIntValue, 9	ooMonitorChannels, 43
asn1CEvtHndlr.h, 130	ooOnSendMsg, 43
ASN1MALLOC	ooSendH225Msg, 43
mem, 17	ooSendH245Msg, 44
ASN1MEMFREE	ooSendMsg, 44
mem, 18	ooStopMonitorCalls, 44
ASN1MEMFREEPTR	cmfun
mem, 18	freeContext, 19
Asn1NamedCEventHandler, 118	initContext, 20
C Runtime Common Functions, 10	initContextBuffer, 20
Call Management, 29	newContext, 20
callmgmt	Context Management Functions, 18
ooAddCallToList, 31	cruntime
ooAddMediaInfo, 31	DE BIT, 15
ooAddNewLogicalChannel, 32	DE_INCRBITIDX, 15
ooCleanCall, 32	GEN_CANSET, 15
ooClearAllLogicalChannels, 32	IA5_CANSET, 15
ooClearLogicalChannel, 32	T61_CANSET, 15
ooCreateCall, 33	VIS_CANSET, 16
ooEndCall, 33	DE_BIT
ooFindCallByToken, 33	cruntime, 15
ooFindLogicalChannel, 33	DE_INCRBITIDX
ooFindLogicalChannelByLogicalChannelNo,	cruntime, 15
34	DECODEBIT
ooFindLogicalChannelByOLC, 34	Rtmem, 96
ooGetLogicalChannel, 34	decodeBits
ooIsSessionEstablished, 35	Rtmem, 100
ooOnLogicalChannelEstablished, 35	decodeBitString
ooRemoveCallFromList, 35	Rtmem, 100

decodeBMPString	encodeBMPString
Rtmem, 101	Rtmem, 109
decodeByteAlign	encodeByteAlign
Rtmem, 101	Rtmem, 109
decodeConsInteger	encodeCheckBuffer
Rtmem, 101	Rtmem, 109
decodeConstrainedStringEx	encodeConsInteger
Rtmem, 102	Rtmem, 110
decodeConsUInt16	encodeConstrainedStringEx
Rtmem, 102	Rtmem, 110
decodeConsUInt8	encodeConsUnsigned
Rtmem, 103	Rtmem, 111
decodeConsUnsigned	encodeConsWholeNumber
Rtmem, 103	Rtmem, 111
decodeConsWholeNumber	encodeExpandBuffer
Rtmem, 103	Rtmem, 111
decodeDynBitString Rtmem, 104	encodeGetMsgPtr Rtmem, 112
decodeDynOctetString Rtmem, 104	encodeLength Rtmem, 112
,	*
decodeLength Rtmem, 105	encodeObjectIdentifier
·	Rtmem, 113 encodeOctets
decodeObjectIdentifier	
Rtmem, 105	Rtmem, 113
decodeOctetString	encodeOctetString
Rtmem, 105	Rtmem, 113
decodeOpenType	encodeOpenType
Rtmem, 106	Rtmem, 114
decodeSemiConsInteger	encodeOpenTypeExt
Rtmem, 106	Rtmem, 114
decodeSemiConsUnsigned	encodeSemiConsInteger
Rtmem, 107	Rtmem, 115
decodeSmallNonNegWholeNumber	encodeSemiConsUnsigned
Rtmem, 107	Rtmem, 115
decodeUnconsInteger	encodeSmallNonNegWholeNumber
Rtmem, 96	Rtmem, 115
decodeUnconsUnsigned	encodeUnconsInteger
Rtmem, 97	Rtmem, 97
dListAppend	errAddIntParm
llfuns, 22	errfp, 27
dListFreeAll	errAddStrParm
llfuns, 23	errfp, 27
dListFreeNodes	errAddUIntParm
llfuns, 23	errfp, 28
dListInit	errfp
llfuns, 23	errAddIntParm, 27
dListRemove	errAddStrParm, 27
llfuns, 24	errAddUIntParm, 28
encodeBit	errFreeParms, 28
Rtmem, 107	errGetText, 28
encodeBits	errPrint, 29
Rtmem, 108	errReset, 29
encodebitsFromOctet	errSetData, 29
Rtmem, 108	errFreeParms
encodeBitString	errfp, 28
Rtmem, 108	errGetText

errfp, 28	ooSetAliasH323ID, 59
Error Formatting and Print Functions, 26	ooSetAliasTransportID, 59
errPrint	ooSetAliasURLID, 59
errfp, 29	ooSetCallerID, 59
errReset	ooSetCallerName, 60
errfp, 29	ooSetFastStart, 60
errSetData	ooSetH245Tunneling, 60
errfp, 29	ooSetLocalCallSignallingAddress, 60
freeContext	ooSetProductID, 61
cmfun, 19	ooSetVersionID, 61
GEN_CANSET	IA5_CANSET
cruntime, 15	cruntime, 15
h245	INCRBITIDX
ooBuildOpenLogicalChannelAudio, 47	Rtmem, 97
ooCloseAllLogicalChannels, 47	initContext
ooCreateH245Message, 47	cmfun, 20
ooFreeH245Message, 48	initContextBuffer
ooGenerateStatusDeterminationNumber, 48	cmfun, 20
ooGetOutgoingH245Msgbuf, 48	Linked List Utility Functions, 21
ooH245AcknowledgeTerminalCapabilitySet,	llfuns
49	dListAppend, 22
ooHandleH245Command, 49	dListFreeAll, 23
ooHandleH245Message, 49	dListFreeNodes, 23
ooHandleMasterSlave, 49	dListInit, 23
ooHandleOpenLogicalAudioChannel, 50	dListRemove, 24
ooHandleOpenLogicalChannel, 50	sListAppend, 24
ooOnReceivedCloseChannelAck, 50	sListCreate, 24
ooOnReceivedCloseLogicalChannel, 51	sListCreateEx, 24
ooOnReceivedOpenLogicalChannelAck, 51	sListFind, 25
ooOnReceivedOpenLogicalChannelRejected,	sListFree, 25
51	sListInit, 25
ooOnReceivedRequestChannelClose, 51	sListInitEx, 25
ooOnReceivedTerminalCapabilitySet, 52	sListRemove, 26
ooOnReceivedTerminalCapabilitySetAck, 52	media
ooOpenG711ULaw64KChannel, 52	ooCloseReceiveRTPChannel, 78
ooOpenLogicalAudioChannel, 53	ooCloseTransmitRTPChannel, 79
ooOpenLogicalChannels, 53	ooCreateReceiveRTPChannel, 79
ooSendAsTunneledMessage, 53	ooCreateTransmitRTPChannel, 79
ooSendCloseLogicalChannel, 53	ooLoadSndRTPPlugin, 79
ooSendEndSessionCommand, 54	ooReleaseSndRTPPlugin, 80
ooSendMasterSlaveDetermination, 54	ooRTPShutDown, 80
ooSendMasterSlaveDeterminationAck, 54	ooSetLocalRTPAndRTCPAddrs, 80
ooSendRequestCloseLogicalChannel, 54	ooStartReceiveAudioAndPlayback, 80
ooSendTermCapMsg, 55	ooStartTransmitMic, 80
H245 Message Handling, 44	ooStartTransmitWaveFile, 81
H245Message, 119	ooStopReceiveAudioAndPlayback, 81
ootypes.h, 184	ooStopTransmitMic, 81
H323 Endpoint management functions, 55	ooStopTransmitWaveFile, 81
h323ep	Media plug-in Interface definitions, 76
ooDestroyH323Ep, 56	Media plugin support functions, 77
ooDisableAutoAnswer, 57	mem
ooEnableAutoAnswer, 57	ALLOC_ASN1ARRAY, 17
ooH323EpRegisterCallbacks, 57	ALLOC_ASN1ELEM, 17
ooInitializeH323Ep, 58	ALLOC_ASN1ELEMDNODE, 17
ooSetAliasDialedDigits, 58	ASN1MALLOC, 17
ooSetAliasEmailID, 58	ASN1MEMFREE, 18

ASN1MEMFREEPTR, 18	ooCleanCall
memAlloc	callmgmt, 32
Rtmem, 98	ooClearAllLogicalChannels
memAllocZ	callmgmt, 32
Rtmem, 98	ooClearLogicalChannel
memFree	callmgmt, 32
Rtmem, 98	ooCloseAllLogicalChannels
memFreePtr	h245, 47
Rtmem, 99	ooCloseH225Connection
memHeapGetDefBlkSize	channels, 41
Rtmem, 116	ooCloseH245Connection
memHeapSetDefBlkSize	channels, 41
Rtmem, 116	ooCloseReceiveRTPChannel
Memory Allocation Macros and Functions, 16	media, 78
memRealloc	ooCloseTransmitRTPChannel
Rtmem, 99	media, 79
memReset	ooCommand, 122
Rtmem, 99	ooCommon.h, 155
memSetAllocFuncs	ooCompareAlawCaps
Rtmem, 116	capmgmt, 37
moveBitCursor	ooCompareAudioCaps
Rtmem, 116	capmgmt, 37
newContext	ooCompareUlawCaps
cmfun, 20	capmgmt, 38
oo.h, 133	ooCreateAudioCapability
ooGetText, 134	capmgmt, 38
ooSetTraceThreshold, 134	ooCreateCall
ooTrace, 135	callmgmt, 33
ooTraceLogMessage, 135	ooCreateG711Capability
OO_CALLMODE_AUDIOCALL	capmgmt, 38
ootypes.h, 184	ooCreateH225Connection
ooAcceptCall	channels, 41
q931, 64	ooCreateH245Connection
ooAcceptH225Connection	channels, 42
channels, 40	ooCreateH245Listener
ooAcceptH245Connection	channels, 42
channels, 41	ooCreateH245Message
ooAddCallToList	h245, 47
callmgmt, 31	ooCreateH323Listener
ooAddCapability	channels, 42
capmgmt, 37	ooCreateQ931Message
ooAddMediaInfo	q931, 65
callmgmt, 31	ooCreateReceiveRTPChannel
ooAddNewLogicalChannel	media, 79
callmgmt, 32	ooCreateTransmitRTPChannel
ooAnswerCall	media, 79
stackemds, 90	ooDateTime.h, 157
ooasn1.h, 136	ooGetTimeOfDay, 157
ooBindPort	ooDecodeUUIE
ooports.h, 164	q931, 65
ooBuildOpenLogicalChannelAudio	ooDestroyH323Ep
h245, 47	h323ep, 56
ooCallData, 120	ooDestroyRas
ooCalls.h, 149	ras, 73
ooCapability.h, 151	ooDisableAutoAnswer
oochannels.h, 153	h323ep, 57

ooEnableAutoAnswer	q931, 67
h323ep, 57	ooH323MakeCall_helper
ooEncodeUUIE	q931, 67
q931, 65	ooH323Ports, 126
ooEndCall	ooHandleH2250Message
callmgmt, 33	q931, 68
ooEndPoint, 123	ooHandleH245Command
ooFindCallByToken	h245, 49
callmgmt, 33	ooHandleH245Message
ooFindLogicalChannel	h245, 49
callmgmt, 33	ooHandleMasterSlave
ooFindLogicalChannelByLogicalChannelNo	h245, 49
callmgmt, 34	ooHandleOpenLogicalAudioChannel
ooFindLogicalChannelByOLC	h245, 50
callmgmt, 34	ooHandleOpenLogicalChannel
ooFreeH245Message	h245, 50
h245, 48	ooHandleStartH245FacilityMessage
ooFreeQ931Message	q931, 68
q931, 65	ooHandleTunneledH245Messages
ooGenerateCallIdentifier	q931, 68
q931, 66	-
•	ooHangCall
ooGenerateCallReference	stackemds, 90
q931, 66	ooInitializeH323Ep
ooGenerateStatusDeterminationNumber	h323ep, 58
h245, 48	ooInitRas
ooGetLocalIPAddress	ras, 74
sockets, 84	OOIPADDR
ooGetLogicalChannel	sockets, 83
callmgmt, 34	ooIsAudioCapSupported
ooGetNextPort	capmgmt, 38
ooports.h, 165	ooIsDataTypeSupported
ooGetOutgoingH245Msgbuf	capmgmt, 39
h245, 48	ooIsSessionEstablished
ooGetOutgoingQ931Msgbuf	callmgmt, 35
q931, 66	ooLoadSndRTPPlugin
ooGetText	media, 79
oo.h, 134	ooLogicalChannel, 127
ooGetTimeOfDay	ooMakeCall
ooDateTime.h, 157	stackemds, 90
ooH2250Receive	ooMonitorChannels
channels, 42	channels, 43
ooh245.h, 158	ooOnLogicalChannelEstablished
ooH245AcknowledgeTerminalCapabilitySet	callmgmt, 35
h245, 49	ooOnReceivedCloseChannelAck
ooH245Receive	h245, 50
channels, 43	ooOnReceivedCloseLogicalChannel
ooh323.h, 161	h245, 51
ooH323CallAdmitted	ooOnReceivedFacility
q931, 66	q931, 68
ooh323ep.h, 162	ooOnReceivedOpenLogicalChannelAck
ooH323EpCapability, 125	h245, 51
ooH323EpRegisterCallbacks	ooOnReceivedOpenLogicalChannelRejected
h323ep, 57	h245, 51
ooH323HangCall	ooOnReceivedRequestChannelClose
q931, 67	h245, 51
ooH323MakeCall	ooOnReceivedSetup

q931, 69	callmgmt, 36
ooOnReceivedSignalConnect	ooRetrieveAliases
q931, 69	q931, 70
ooOnReceivedTerminalCapabilitySet	ooRTPShutDown
h245, 52	media, 80
ooOnReceivedTerminalCapabilitySetAck	ooSendAlerting
h245, 52	q931, 70
ooOnSendMsg	ooSendAsTunneledMessage
channels, 43	h245, 53
ooOpenG711ULaw64KChannel	ooSendCallProceeding
h245, 52	q931, 71
ooOpenLogicalAudioChannel	ooSendCloseLogicalChannel
h245, 53	h245, 53
ooOpenLogicalChannels	ooSendConnect
h245, 53	q931, 71
ooParseDestination	ooSendEndSessionCommand
q931, 69	h245, 54
ooports.h, 164	ooSendFacility
ooBindPort, 164	q931, 71
ooGetNextPort, 165	ooSendH225Msg
ooSetRTPPorts, 165	channels, 43
ooSetTCPPorts, 165	ooSendH245Msg
ooSetUDPPorts, 166	channels, 44
ooq931.h, 167	ooSendMasterSlaveDetermination
ooQ931Decode	h245, 54
q931, 69	ooSendMasterSlaveDeterminationAck
ooQ931GetIE	h245, 54
q931, 70	ooSendMsg
ooQ931Print	channels, 44
q931, 70	ooSendReleaseComplete
ooras.h, 170	q931, 71
ooRasFillAlias	ooSendRequestCloseLogicalChannel
ras, 74	h245, 54
ooRasGetGatekeeperMode	ooSendTermCapMsg
ras, 74	h245, 55
ooRasGetSocket	ooSetAliasDialedDigits
ras, 75	h323ep, 58
ooRasIsRegistered	ooSetAliasEmailID
ras, 75	h323ep, 58
ooRasMessage, 128	ooSetAliasH323ID
ras, 73	h323ep, 59
ooRasReceive	ooSetAliasTransportID
ras, 75	h323ep, 59
ooRasSendAdmissionRequest	ooSetAliasURLID
ras, 75	h323ep, 59
ooRasSendDisengageRequest	ooSetCallerID
ras, 75	h323ep, 59
ooRasSetGatekeeperMode	ooSetCallerName
ras, 76	h323ep, 60
ooRejectCall	ooSetFastStart
stackemds, 90	h323ep, 60
ooReleaseSndRTPPlugin	ooSetH245Tunneling
media, 80	h323ep, 60
ooRemoveCallFromList	ooSetLocalCallSignallingAddress
callmgmt, 35	h323ep, 60
ooRemoveLogicalChannel	ooSetLocalRTPAndRTCPAddrs

media, 80	ooStopMonitorCalls
ooSetProductID	channels, 44
h323ep, 61	ooStopReceiveAudioAndPlayback
ooSetRTPPorts	media, 81
ooports.h, 165	ooStopTransmitMic
ooSetTCPPorts	media, 81
ooports.h, 165	ooStopTransmitWaveFile
ooSetTraceThreshold	media, 81
oo.h, 134	OOTERMTYPE
ooSetUDPPorts	ootypes.h, 184
ooports.h, 166	ooTrace
ooSetVersionID	oo.h, 135
h323ep, 61	ooTraceLogMessage
oosndrtp.h, 172	oo.h, 135
ooSocket.h, 175	ootypes.h, 179
ooSocketAccept	H245Message, 184
sockets, 84	OO_CALLMODE_AUDIOCALL, 184
ooSocketAddrToStr	OOTERMTYPE, 184
sockets, 84	Q931Message, 184
ooSocketBind	OS_ISGRAPH
sockets, 85	rtctype.h, 186
ooSocketClose	OS_ISPRINT
sockets, 85	rtctype.h, 187
ooSocketConnect	OSMSGREALLOCARRAY
sockets, 85	SList.h, 188
ooSocketCreate	printHandler.h, 185
sockets, 86	q931
ooSocketCreateUDP	ooAcceptCall, 64
sockets, 86	ooCreateQ931Message, 65
ooSocketListen	ooDecodeUUIE, 65
sockets, 86	ooEncodeUUIE, 65
ooSocketRecv	ooFreeQ931Message, 65
sockets, 86	ooGenerateCallIdentifier, 66
ooSocketRecvFrom	ooGenerateCallReference, 66
sockets, 87	ooGetOutgoingQ931Msgbuf, 66
ooSocketsCleanup	ooH323CallAdmitted, 66
sockets, 87	ooH323HangCall, 67
ooSocketSelect	ooH323MakeCall, 67
sockets, 87	ooH323MakeCall_helper, 67
ooSocketSend	ooHandleH2250Message, 68
sockets, 88	ooHandleStartH245FacilityMessage, 68
ooSocketSendTo	ooHandleTunneledH245Messages, 68
sockets, 88	ooOnReceivedFacility, 68
ooSocketsInit	ooOnReceivedSetup, 69
sockets, 88	ooOnReceivedSignalConnect, 69
ooSocketStrToAddr	ooParseDestination, 69
sockets, 89	ooQ931Decode, 69
ooStackCmds.h, 178	ooQ931GetIE, 70
ooStartReceiveAudioAndPlayback	ooQ931Print, 70
media, 80	ooRetrieveAliases, 70
ooStartTransmitMic	ooSendAlerting, 70
media, 80	ooSendCallProceeding, 71
ooStartTransmitWaveFile	ooSendConnect, 71
media, 81	ooSendFacility, 71
ooStopMonitor	ooSendReleaseComplete, 71
stackends, 91	Q931/H.2250 Message Handling, 61
	2,52,11,2250 1,1055age 11ananing, 01

Q931Message, 129	decodeSmallNonNegWholeNumber, 107
ootypes.h, 184	decodeUnconsInteger, 96
ras	decodeUnconsUnsigned, 97
ooDestroyRas, 73	encodeBit, 107
ooInitRas, 74	encodeBits, 108
ooRasFillAlias, 74	encodebitsFromOctet, 108
ooRasGetGatekeeperMode, 74	encodeBitString, 108
ooRasGetSocket, 75	encodeBMPString, 109
ooRasIsRegistered, 75	encodeByteAlign, 109
ooRasMessage, 73	encodeCheckBuffer, 109
ooRasReceive, 75	encodeConsInteger, 110
ooRasSendAdmissionRequest, 75	encodeConstrainedStringEx, 110
ooRasSendDisengageRequest, 75	encodeConsUnsigned, 111
ooRasSetGatekeeperMode, 76	encodeConsWholeNumber, 111
RAS Channel and Message handling, 72	encodeExpandBuffer, 111
rtAddEventHandler	encodeGetMsgPtr, 112
Asn1CEventHandler, 9	encodeLength, 112
rtBitStrValue	encodeObjectIdentifier, 113
Asn1CEventHandler, 4	encodeOctets, 113
rtBoolValue	encodeOctetString, 113
Asn1CEventHandler, 4	encodeOpenType, 114
rtCharStrValue	encodeOpenTypeExt, 114
Asn1CEventHandler, 5	encodeSemiConsInteger, 115
rtCharStrValue16Bit	encodeSemiConsUnsigned, 115
Asn1CEventHandler, 5	encodeSmallNonNegWholeNumber, 115
rtCharStrValue32Bit	encodeUnconsInteger, 97
Asn1CEventHandler, 5	INCRBITIDX, 97
rtctype.h, 186	memAlloc, 98
OS_ISGRAPH, 186	memAllocZ, 98
OS_ISPRINT, 187 rtEndElement	memFree, 98
	memFreePtr, 99
Asn1CEventHandler, 6	memHeapGetDefBlkSize, 116
rtEnumValue	memHeapSetDefBlkSize, 116
Asn1CEventHandler, 6	memRealloc, 99
rtIntValue	memReset, 99
Asn1CEventHandler, 6	memSetAllocFuncs, 116
Rtmem, 91	moveBitCursor, 116
DECODEBIT, 96	rtNullValue
decodeBits, 100	Asn1CEventHandler, 7
decodeBitString, 100	rtOctStrValue
decodeBMPString, 101	Asn1CEventHandler, 7
decodeByteAlign, 101	rtOidValue
decodeConsInteger, 101	Asn1CEventHandler, 7
decodeConstrainedStringEx, 102	rtOpenTypeValue
decodeConsUInt16, 102	Asn1CEventHandler, 8
decodeConsUInt8, 103	rtRealValue
decodeConsUnsigned, 103	Asn1CEventHandler, 8
decodeConsWholeNumber, 103	rtRemoveEventHandler
decodeDynBitString, 104	Asn1CEventHandler, 9
decodeDynOctetString, 104	rtStartElement
decodeLength, 105	Asn1CEventHandler, 8
decodeObjectIdentifier, 105	rtUIntValue
decodeOctetString, 105	Asn1CEventHandler, 9
decodeOpenType, 106	SList.h, 188
decodeSemiConsInteger, 106	OSMSGREALLOCARRAY, 188
decodeSemiConsUnsigned, 107	sListAppend

llfuns, 24	ooSocketConnect, 85
sListCreate	ooSocketCreate, 86
llfuns, 24	ooSocketCreateUDP, 86
sListCreateEx	ooSocketListen, 86
llfuns, 24	ooSocketRecv, 86
sListFind	ooSocketRecvFrom, 87
llfuns, 25	ooSocketsCleanup, 87
sListFree	ooSocketSelect, 87
llfuns, 25	ooSocketSend, 88
sListInit	ooSocketSendTo, 88
llfuns, 25	ooSocketsInit, 88
sListInitEx	ooSocketStrToAddr, 89
llfuns, 25	Stack Control Commands, 89
sListRemove	stackemds
llfuns, 26	ooAnswerCall, 90
Socket Layer, 82	ooHangCall, 90
sockets	ooMakeCall, 90
ooGetLocalIPAddress, 84	ooRejectCall, 90
OOIPADDR, 83	ooStopMonitor, 91
ooSocketAccept, 84	T61_CANSET
ooSocketAddrToStr, 84	cruntime, 15
ooSocketBind, 85	VIS_CANSET
ooSocketClose, 85	cruntime, 16