Bridge of Life Education

NN Hardware

Lecturer: Hua-Yang Weng

Date: 2022/4/13

[FPGA'17: FINN: A Framework for Fast, Scalable Binarized Neural Network Inference]
(https://arxiv.org/abs/1612.07119)

From AI to Gate Textbook



Overview

- Introduction
- BNNs inference hardware architecture
- BNN specific Operator Optimizations
- FINN Design Flow and Hardware Library
- Folding
- Evaluation

Overview

- Introduction
- BNNs inference hardware architecture
- BNN specific Operator Optimizations
- FINN Design Flow and Hardware Library
- Folding
- Evaluation

Neural Networks in Hardware(1/3)

- Single processing engine
  - Systolic array like processor
- **Streaming architecture**
  - Dedicated hardware per layer
- Vector processor
  - Process with instructions
- Neurosynaptic processor
  - Neurosynaptic like digital neurons and interconnections

- Recent networks evolved very fast
- New categories of networks coming up while some gradually vanished.

To push energy efficiency:
- Zero-skipping
- Weight pruning
- …

Replaces simple systolic array to customized computing algorithm.

Neural Networks in Hardware(2/3)

- Weight stationary
- Output stationary
- Input stationary
- (Row) stationary



Figure 5.15: The taxonomy of commonly seen dataflows for DNN processing. *Act* means input activation. The color gradient is used to note different values of the same data type.

Neural Networks in Hardware(3/3)

- Inference Hardware



FINN is currently designed for inference hardware

- Training Hardware





Roofline model



Figure 1: Roofline model for a ZU19EG.

Accuracy–Computation Tradeoffs

- Fix to 3 fully connected layers
- Scaling the number of neurons in each layer
- As the network size increases, the difference in accuracy between low precision networks and floating point networks decreases

Table 1: Accuracy results - BNN vs NN.

Neurons/layer	Binary Err. (%)	Float Err. (%)	# Params	Ops/frame
128	6.58	2.70	134,794	268,800
256	4.17	1.78	335,114	668,672
512	2.31	1.25	932,362	1,861,632
1024	1.60	1.13	2,913,290	5,820,416
2048	1.32	0.97	10,020,874	20,029,440
4096	1.17	0.91	36,818,954	73,613,312

Overview

- Introduction
- BNNs inference hardware architecture
- BNN specific Operator Optimizations
- FINN Design Flow and Hardware Library
- Folding
- Evaluation

FINN Hardware Architecture

- Custom architecture for each layer
  - Rather than scheduling a operations to a fixed architecture
- Separate compute engines are dedicated to each layer
- All neural network parameters are kept in on-chip memory





Figure 2: Heterogeneous streaming.

Overview

- Introduction
- BNNs inference hardware architecture
- BNN specific Operator Optimizations
  - Popcount for Accumulation
  - Batchnorm-activation as Threshold
  - Boolean OR for Max-pooling
- FINN Design Flow and Hardware Library
- Folding
- Evaluation

BNN-specific Operator Optimizations

- Using 1-bit bipolar values for all input activations, weights and output activations (full binarization)
  - **Set bit (1)** represents value **+1**
  - **Unset bit (0)** represents value **-1**
- Batch normalization prior to the activation function.
- Using the following activation function:

$$Sign(x) = \{+1 \; if \; x \geq 0; \; -1 \; if \; x \; < \; 0\}$$

Some additional optimizations

1. Popcount for Accumulation
2. Batchnorm-activation as Threshold
3. Boolean OR for Max-pooling

Optimizations: Popcount for Accumulation

- XNOR gate to compute bipolar multiplication
  - (1, 1) -> 1 1 x 1 = 1
  - (1, 0) -> 0 1 x -1 = -1
  - (0, 1) -> 0 -1 x 1 = -1
  - (0, 0) -> 1 -1 x -1 = 1

- Binary dot product: popcount (counts the number of set bits)
  - Instead of signed arithmetic.

- Resource utilization
  - Comparing signed-accumulate.
  - LUT and FF resources x 0.5



Optimizations: Batchnorm-activation as Threshold

- $\boldsymbol{a_k}$: Dot product (pre-activation) output of neuron k
- $\boldsymbol{\theta_k} = (\gamma_k, \mu_k, i_k, B_k)$: Batch normalization parameters
- $\boldsymbol{a_k^b} = Sign\big(BatchNorm(a_k, \theta_k)\big)$: Output of this neuron
- $\boldsymbol{BatchNorm(a_k, \theta_k)} = \gamma_k(a_k - \mu_k)i_k + B_k$: BatchNorm

γ_k, B_k: Learnable affine parameters

a_k: input data

μ_k: mean of the data

i_k: equals to $\frac{1}{\sqrt{Var[a_k]+\epsilon}}$

A threshold τ_k for the output activation is always present.

- Solving $\boldsymbol{BatchNorm(a_k, \theta_k) = 0}$ to deduce that

$$\tau_k = \mu_k - B_k/(\gamma_k \cdot i_k)$$

- Avoid computing the batch normalized value during inference

  compute the output activation using an unsigned comparison

Optimizations: Boolean OR for Max-pooling

- Origin: activations after max-pooling
- FINN: max-pooling after the activations
- $a_1, a_2, \ldots, a_Y$: positive dot product outputs

$$a^b = Max(a_1, a_2, \ldots, a_Y) > \gamma^+$$

- Distributivity of $Max(\cdot)$

$$a^b = (a_1 > \gamma^+) \vee (a_2 > \gamma^+) \ldots \vee (a_Y > \gamma^+)$$

- As the threshold comparisons are already computed for the activations, max-pooling can be effectively implemented with the Boolean OR-operator

Overview

- Introduction
- BNNs inference hardware architecture
- BNN specific Operator Optimizations
- FINN Design Flow and Hardware Library
  - Matrix–Vector–Threshold Unit (MVTU)
  - Convolution: The Sliding Window Unit (SWU)
  - Pooling Unit (PU)
- Folding
- Evaluation

FINN Design Flow and Hardware Library(1/2)



Figure 4: Generating an FPGA accelerator from a trained BNN.

FINN Design Flow and Hardware Library(2/2)

1. Matrix–Vector–Threshold Unit (MVTU)
   - Fully-connected layer
   - Matrix-vector multiplication



2. Convolution: The Sliding Window Unit (SWU)
   - Convolutions can be lowered to matrix-matrix multiplications

3. Pooling Unit (PU)

1. Matrix Vector Threshold Unit (MVTU)

- Forms the computational core for our accelerator designs
- BNN can be expressed as matrix–vector operations



The number of PEs **(P)** and number of SIMD lanes **(S)** are configurable to control throughput

1. Matrix Vector Threshold Unit (MVTU): PE datapath

① Fan-in S XNOR computes dot product

② Popcount with bitwitdh T = 1 + $\log_2 S$

③ Accumulate the partial inner-product value

④ compares the result to a threshold $\tau_k^+ \rightarrow$ 1 bit output



The weights are stored in On-Chip Memory

Weight stationary
Output stationary

2. Convolution: The Sliding Window Unit

- Convolutions can be lowered to matrix-matrix multiplications
- Interleave the feature maps
- Each pixel contains all the Input Feature Map (IFM) channel data for that position

This fashion allows:
- Enables the output of the MVTU to be directly fed to the next layer without any transposition.



2. Convolution: The Sliding Window Unit

- **Filter matrix** interleaving is **computed offline**
- The memory locations corresponding to each sliding window
- Read out previous layer to produce the image matrix.



(b) SWU operation.



3. Pooling Unit (PU)

- $k \times k$ max-pooling kernel
- $D_H \times D_W \times C$ binary feature map
- A D_H/k line buffer with D_W bits.





Input Feature map:
8x8
Max pooling kernel:
2x2

Line buffer

output
FIFO



Input Feature map:
8x8
Max pooling kernel:
2x2

Line buffer

output
FIFO



Input Feature map:
8x8
Max pooling kernel:
2x2

Line buffer

output
FIFO



Input Feature map:
8x8
Max pooling kernel:
2x2

Line buffer

output
FIFO



Input Feature map:
8x8
Max pooling kernel:
2x2

Line buffer

output
FIFO



Input Feature map:
8x8
Max pooling kernel:
2x2

Line buffer

output
FIFO



Input Feature map:
8x8
Max pooling kernel:
2x2

Line buffer

output
FIFO



Input Feature map:
8x8
Max pooling kernel:
2x2

Line buffer

output
FIFO



Input Feature map:
8x8
Max pooling kernel:
2x2

Line buffer

output
FIFO



Input Feature map:
8x8
Max pooling kernel:
2x2

Line buffer

output
FIFO



Input Feature map:
8x8
Max pooling kernel:
2x2

Line buffer

output
FIFO



Input Feature map:
8x8
Max pooling kernel:
2x2

Line buffer

output
FIFO



Input Feature map:
8x8
Max pooling kernel:
2x2

Line buffer

output
FIFO



Input Feature map:
8x8
Max pooling kernel:
2x2

Line buffer

output
FIFO



Input Feature map:
8x8
Max pooling kernel:
2x2

Line buffer

output
FIFO



Input Feature map:
8x8
Max pooling kernel:
2x2

Line buffer

output
FIFO



Input Feature map:
8x8
Max pooling kernel:
2x2

Line buffer

output
FIFO



Input Feature map:
8x8
Max pooling kernel:
2x2

Line buffer

output
FIFO



Input Feature map:
8x8
Max pooling kernel:
2x2

Line buffer

output
FIFO



Input Feature map:
8x8
Max pooling kernel:
2x2

Line buffer

output
FIFO



Input Feature map:
8x8
Max pooling kernel:
2x2

Line buffer

output
FIFO



Input Feature map:
8x8
Max pooling kernel:
2x2

Line buffer

output
FIFO

Overview

- Introduction
- BNNs inference hardware architecture
- BNN specific Operator Optimizations
- FINN Design Flow and Hardware Library
- Folding
  - Folding Matrix–Vector Products
  - Determining F^n and F^s
- Evaluation

Folding Matrix-Vector Products

- hardware resources on an FPGA is limited
- Use time-multiplex (or fold) save hardware
- Folding is achieved by controlling two parameters of the MVTU
  - P: the number of PEs
  - S: the number of SIMD lanes per PE



P: 3
S: 2
Matrix: 6x4
Fold neuron: 6/3
Fold synapse: 4/2

$F_n \cdot F_s = (6/3) \cdot (4/2)$
$= 4$ cycles.

Determining F^n and F^s

- Avoiding the “one-size-fits-all“
- Guiding principle: rate-balancing
- **Slowest layer (with II_{max}) will determine the overall throughput**
- For this streaming system, $\text{FPS} \approx \frac{F_{clk}}{II_{max}}$ (e.g. $\frac{100M}{1M} = 100fps$)

- Balancing a fully-connected BNN can be achieved by using F^n and F^s such that $F^n \cdot F^s = \frac{F_{clk}}{FPS}$ for each layer.

- Match the throughput of all other layers to the bottleneck

Examples: 4-Layer Fully-connected

- The PE, SIMD factors are set in a manner
  - What is the II for each layer?

```
fc_layers = model.get_nodes_by_op_type("StreamingFCLayer_Batch")
# (PE, SIMD, in_fifo_depth, out_fifo_depth, ramstyle) for each layer
config = [
    (16, 49, 16, 64, "block"),
    (8, 8, 64, 64, "auto"),
    (8, 8, 64, 64, "auto"),
    (10, 8, 64, 10, "distributed"),
]
for fcl, (pe, simd, ififo, ofifo, ramstyle) in zip(fc_layers, config):
    fcl_inst = getCustomOp(fcl)
    fcl_inst.set_nodeattr("PE", pe)
    fcl_inst.set_nodeattr("SIMD", simd)
    fcl_inst.set_nodeattr("inFIFODepth", ififo)
    fcl_inst.set_nodeattr("outFIFODepth", ofifo)
    fcl_inst.set_nodeattr("ram_style", ramstyle)

# set parallelism for input quantizer to be same as first layer's SIMD
inp_qnt_node = model.get_nodes_by_op_type("Thresholding_Batch")[0]
inp_qnt = getCustomOp(inp_qnt_node)
inp_qnt.set_nodeattr("PE", 49)
```



Examples: 1st Layer

$F^n \cdot F^s = II$ for each layer.

```
# (PE, SIMD, in_fifo_depth, out_fifo_depth, ramstyle) for each layer
config = [
    (16, 49, 16, 64, "block"),
    (8, 8, 64, 64, "auto"),
    (8, 8, 64, 64, "auto"),
    (10, 8, 64, 10, "distributed"),
```





P: 16
S: 49
Matrix: 64x784
Fold neuron: 64/16
Fold synapse: 784/49

$F_n \cdot F_s = (64/16) \cdot (784/49)$
$= 4 \times 16$
$= 64$ cycles

Examples: 2nd Layer

$F^n \cdot F^s = II$ for each layer.

```
# (PE, SIMD, in_fifo_depth, out_fifo_depth, ramstyle) for each layer
config = [
    (16, 49, 16, 64, "block"),
    (8, 8, 64, 64, "auto"),
    (8, 8, 64, 64, "auto"),
    (10, 8, 64, 10, "distributed"),
```





P: 8
S: 8
Matrix: 64x64
Fold neuron: 64/8
Fold synapse: 64/8

$F_n \cdot F_s = (64/8) \cdot (64/8)$
$= 8 \times 8$
$= 64$ cycles

Examples: 3rd Layer

$F^n \cdot F^s = II$ for each layer.

```
# (PE, SIMD, in_fifo_depth, out_fifo_depth, ramstyle) for each layer
config = [
    (16, 49, 16, 64, "block"),
    (8, 8, 64, 64, "auto"),
    (8, 8, 64, 64, "auto"),
    (10, 8, 64, 10, "distributed"),
```





P: 8
S: 8
Matrix: 64x64
Fold neuron: 64/8
Fold synapse: 64/8

$F_n \cdot F_s = (64/8) \cdot (64/8)$
$= 8 \times 8$
$= 64$ cycles

Examples: Last Layer $F^n \cdot F^s = II$ for each layer.

```
# (PE, SIMD, in_fifo_depth, out_fifo_depth, ramstyle) for each layer
config = [
    (16, 49, 16, 64, "block"),
    (8, 8, 64, 64, "auto"),
    (8, 8, 64, 64, "auto"),
    (10, 8, 64, 10, "distributed"),
```





P: 10
S: 8
Matrix: 10x64
Fold neuron: 10/10
Fold synapse: 64/8

$F_n \cdot F_s = (10/10) \cdot (64/8)$
$= 1 \times 8$
$= 8$ cycles

Examples:

- The PE, SIMD factors are set in a manner s.t. II = 64 for each layer (except the last)

```
# change this if you have a different PYNQ board, see list above
pynq_board = "Pynq-Z2"
fpga_part = pynq_part_map[pynq_board]
target_clk_ns = 10
```

- For this streaming system, $\mathrm{FPS} \approx \frac{F_{clk}}{II_{max}} = \frac{100M}{64} = 1562K$
  - Throughput measurement: 958K
  - This is around 61.37% the ideal case

```
Network metrics:
runtime[ms]: 10.427713394165039
throughput[images/s]: 958983.0120950225
DRAM_in_bandwidth[Mb/s]: 751.8426814824976
DRAM_out_bandwidth[Mb/s]: 0.9589830120950226
fclk[mhz]: 100.0
batch_size: 10000
fold_input[ms]: 0.17762184143066406
pack_input[ms]: 0.1728534698486328
copy_input_data_to_device[ms]: 52.44183540344238
copy_output_data_from_device[ms]: 0.5877017974853516
unpack_output[ms]: 1.1982917785644531
unfold_output[ms]: 0.19979476928710938
```

Questions

- What if we modify the parameters as follows?

```
# (PE, SIMD, in_fifo_depth, out_fifo_depth, ramstyle) for each layer
config = [
    (16, 49, 16, 64, "block"),
    (4, 4, 64, 64, "auto"),
    (8, 8, 64, 64, "auto"),
    (10, 8, 64, 10, "distributed"),
]
```

- What would you expect?