

TASK 4: Commutation Relations and Euler Decomposition

Aim: To verify Pauli matrix commutation relations and decompose a gate using Euler angles.

1. Verify the fundamental commutation and anti-commutation relations of Pauli matrices (X, Y, Z)
2. Implement and validate Z-Y-Z Euler angle decomposition for arbitrary single-qubit gates
3. Demonstrate the decomposition on standard quantum gates (X, Y, Z, H, S, T) and Cirq operations.

Algorithm:

2.1 Pauli Matrix Verification:

- a. Symbolically define Pauli matrices using SymPy
- b. Compute commutators $[A, B] = AB - BA$ and verify $[\sigma_i, \sigma_j] = 2i\epsilon_{ijk}\sigma_k$
- c. Compute anti-commutators $\{A, B\} = AB + BA$ and verify $\{\sigma_i, \sigma_j\} = 2\delta_{ij}I$

2.2 Z-Y-Z Decomposition:

- a. Check matrix unitarity: $U^\dagger U = I$
- b. Extract global phase from determinant
- c. Solve for Euler angles (α, β, γ) in:
- d. $U = e^{i\phi} R_z(\alpha) R_y(\beta) R_z(\gamma)$
- e. Handle special cases when $\beta \approx 0$ or π
- f. Reconstruct matrix to validate decomposition

2.3 Testing:

- a. Standard gates: X, Y, Z, Hadamard (H), Phase (S), $\pi/8$ (T)
- b. Random unitary matrices
- c. Optional Cirq integration for hardware verification

```
!pip install cirq
import numpy as np
import cmath
import sympy as sp

print("\n" + "="*50)
print("TASK 4: COMMUTATION RELATIONS AND EULER ANGLES")
print("="*50)
```

```
# --- Part 1: Verify Pauli commutation & anti-commutation with SymPy ---
```

```

I = sp.eye(2)
sx = sp.Matrix([[0, 1], [1, 0]])
sy = sp.Matrix([[0, -sp.I], [sp.I, 0]])
sz = sp.Matrix([[1, 0], [0, -1]])
paulis = {'X': sx, 'Y': sy, 'Z': sz}

def comm(A, B):
    return sp.simplify(A * B - B * A)

def anti(A, B):
    return sp.simplify(A * B + B * A)

print("\n=== Commutation relations ===")
for (a, b, k) in [('X', 'Y', 'Z'), ('Y', 'Z', 'X'), ('Z', 'X', 'Y')]:
    lhs = comm(paulis[a], paulis[b])
    rhs = 2 * sp.I * paulis[k]
    print(f"[{a},{b}] = {lhs}\nExpected: {rhs}\n")

print("\n=== Anti-commutation relations ===")
for i in ['X', 'Y', 'Z']:
    for j in ['X', 'Y', 'Z']:
        lhs = anti(paulis[i], paulis[j])
        rhs = 2 * (1 if i == j else 0) * I
        print(f"{{{i},{j}}} = {lhs} Expected: {rhs}\n")

# --- Part 2: Z-Y-Z Euler decomposition ---
import numpy as np
import cmath

def is_unitary(U, tol=1e-8):
    return np.allclose(U.conj().T @ U, np.eye(2), atol=tol)

def decompose_zyz(U, tol=1e-8):
    """
    Return (phi, alpha, beta, gamma) such that:
    U = e^{i phi} Rz(alpha) Ry(beta) Rz(gamma)
    """
    U = np.array(U, dtype=complex)

    if not is_unitary(U):
        raise ValueError("Matrix is not unitary.")

    detU = np.linalg.det(U)
    phi = cmath.phase(detU) / 2

    # Remove global phase
    U0 = U * np.exp(-1j * phi)

    # Normalize determinant to 1
    detU0 = np.linalg.det(U0)
    U0 = U0 / np.sqrt(detU0)

    a = U0[0, 0]
    b = U0[0, 1]

```

```

        beta = 2 * np.arccos(min(1.0, max(0.0, abs(a))))

    if np.isclose(np.sin(beta / 2), 0, atol=tol):
        alpha = 2 * (-cmath.phase(a))
        gamma = 0.0
    else:
        phi1 = -cmath.phase(a)
        phi2 = -cmath.phase(-b)
        alpha = phi1 + phi2
        gamma = phi1 - phi2

    return float(phi), float(alpha), float(beta), float(gamma)

def Rz(theta):
    return np.array([
        [np.exp(-1j * theta / 2), 0],
        [0, np.exp(1j * theta / 2)]
    ], dtype=complex)

def Ry(theta):
    return np.array([
        [np.cos(theta / 2), -np.sin(theta / 2)],
        [np.sin(theta / 2), np.cos(theta / 2)]
    ], dtype=complex)

def reconstruct(phi, alpha, beta, gamma):
    return np.exp(1j * phi) * (Rz(alpha) @ Ry(beta) @ Rz(gamma))

# --- Part 3: Test examples ---
import numpy as np

# Pauli X (for Rx definition)
sx = np.array([[0, 1], [1, 0]], dtype=complex)

def Rx(theta):
    return np.cos(theta / 2) * np.eye(2) - 1j * np.sin(theta / 2) * sx

# Reuse Ry and Rz from earlier
def Rz(theta):
    return np.array([
        [np.exp(-1j * theta / 2), 0],
        [0, np.exp(1j * theta / 2)]
    ], dtype=complex)

def Ry(theta):
    return np.array([
        [np.cos(theta / 2), -np.sin(theta / 2)],
        [np.sin(theta / 2), np.cos(theta / 2)]
    ], dtype=complex)

# Examples
examples = {
    "Rx(pi/3)": Rx(np.pi / 3),
    "Ry(pi/4)": Ry(np.pi / 4),
    "Rz(pi/2)": Rz(np.pi / 2),

```

```

"H": (1 / np.sqrt(2)) * np.array([[1, 1], [1, -1]], dtype=complex),
"S": np.array([[1, 0], [0, 1j]], dtype=complex),
"T": np.array([[1, 0], [0, np.exp(1j * np.pi / 4)]], dtype=complex),
}

# Import decompose_zyz from earlier code
from math import pi
from cmath import phase
def is_unitary(U, tol=1e-8):
    return np.allclose(U.conj().T @ U, np.eye(2), atol=tol)

def decompose_zyz(U, tol=1e-8):
    U = np.array(U, dtype=complex)
    if not is_unitary(U):
        raise ValueError("Matrix is not unitary.")
    detU = np.linalg.det(U)
    phi = phase(detU) / 2
    U0 = U * np.exp(-1j * phi)
    detU0 = np.linalg.det(U0)
    U0 = U0 / np.sqrt(detU0)
    a = U0[0, 0]
    b = U0[0, 1]
    beta = 2 * np.arccos(min(1.0, max(0.0, abs(a))))
    if np.isclose(np.sin(beta / 2), 0, atol=tol):
        alpha = 2 * (-phase(a))
        gamma = 0.0
    else:
        phi1 = -phase(a)
        phi2 = -phase(-b)
        alpha = phi1 + phi2
        gamma = phi1 - phi2
    return float(phi), float(alpha), float(beta), float(gamma)
print("\n=== Z-Y-Z Euler Decomposition ===")

for name, U in examples.items():
    phi, alpha, beta, gamma = decompose_zyz(U)
    print(f"{name}:\n  $\phi$ ={phi:.6f},  $\alpha$ ={alpha:.6f},  $\beta$ ={beta:.6f},  $\gamma$ ={gamma:.6f}\n")
# Optional: Use Cirq if available
try:
    import cirq
    print("\nCirq example decomposition for H gate:")
    q = cirq.LineQubit(0)
    H_op = cirq.H(q)
    U = cirq.unitary(H_op)
    phi, alpha, beta, gamma = decompose_zyz(U)
    print(f"Cirq H:  $\phi$ ={phi:.6f},  $\alpha$ ={alpha:.6f},  $\beta$ ={beta:.6f},  $\gamma$ ={gamma:.6f}")
except ImportError:
    print("\nCirq not installed. Skipping Cirq examples.")

```

```

{X,Z} =
Matrix([[0, 0], [0, 0]]) Expected:
Matrix([[0, 0], [0, 0]])

{Y,X} =
Matrix([[0, 0], [0, 0]]) Expected:
Matrix([[0, 0], [0, 0]])

{Y,Y} =
Matrix([[2, 0], [0, 2]]) Expected:
Matrix([[2, 0], [0, 2]])

{Y,Z} =
Matrix([[0, 0], [0, 0]]) Expected:
Matrix([[0, 0], [0, 0]])

{Z,X} =
Matrix([[0, 0], [0, 0]]) Expected:
Matrix([[0, 0], [0, 0]])

{Z,Y} =
Matrix([[0, 0], [0, 0]]) Expected:
Matrix([[0, 0], [0, 0]])

{Z,Z} =
Matrix([[2, 0], [0, 2]]) Expected:
Matrix([[2, 0], [0, 2]])

=== Z-Y-Z Euler Decomposition ===
Rx(pi/3):
  φ=0.000000, α=-1.570796, β=1.047198, γ=1.570796

Ry(pi/4):
  φ=0.000000, α=0.000000, β=0.785398, γ=-0.000000

Rz(pi/2):
  φ=0.000000, α=1.570796, β=0.000000, γ=0.000000

H:
  φ=1.570796, α=0.000000, β=1.570796, γ=3.141593

S:
  φ=0.785398, α=1.570796, β=0.000000, γ=0.000000

T:
  φ=0.392699, α=0.785398, β=0.000000, γ=0.000000

Cirq example decomposition for H gate:
Cirq H: φ=1.570796, α=0.000000, β=1.570796, γ=3.141593

```

Result: Commutation properties and Euler angle decomposition were successfully demonstrated.