

A taste of Haskell?

Siddharth Bhat

IIIT Open Source Developers group

October 18th, 2019

What's programming like?

A lot like building a cathedral.

What's programming like?

A lot like building a cathedral.




Figure: First we build

What's programming like?

A lot like building a cathedral.




Figure: First we build



Figure: Then we pray

Why we pray

Why we pray

```
#include <iostream>
#include <climits>
using namespace std;

// f(x) == true ?
bool f(unsigned x) { return (x + 1) > x; }

int main() {
    cout << "f(0): " << f(0) << "\n";
    cout << "f(UINT32_MAX): " << f(UINT32_MAX) << "\n";
}
```

Why we pray

```
#include <iostream>
#include <climits>
using namespace std;

// f(x) == true ?
bool f(unsigned x) { return (x + 1) > x; }

int main() {
    cout << "f(0): " << f(0) << "\n";
    cout << "f(UINT32_MAX): " << f(UINT32_MAX) << "\n";
}

f(0): 1
f(UINT32_MAX): 0
```

Why we pray

```
#include <iostream>
#include <climits>
using namespace std;

// f(x) == true ?
bool f(unsigned x) { return (x + 1) > x; }

int main() {
    cout << "f(0): " << f(0) << "\n";
    cout << "f(UINT32_MAX): " << f(UINT32_MAX) << "\n";
}

f(0): 1
f(UINT32_MAX): 0
```

$$\blacksquare f : \mathbb{N} \rightarrow \mathbb{B}; f(x) \equiv \begin{cases} \text{true} & x + 1 > x \\ \text{false} & \text{otherwise} \end{cases}$$

Why we pray

```
#include <iostream>
#include <climits>
using namespace std;

// f(x) == true ?
bool f(unsigned x) { return (x + 1) > x; }

int main() {
    cout << "f(0): " << f(0) << "\n";
    cout << "f(UINT32_MAX): " << f(UINT32_MAX) << "\n";
}

f(0): 1
f(UINT32_MAX): 0
```

$$\blacksquare f : \mathbb{N} \rightarrow \mathbb{B}; f(x) \equiv \begin{cases} \text{true} & x + 1 > x \\ \text{false} & \text{otherwise} \end{cases}$$

$$\blacksquare f(x) \equiv \text{true}$$

Why we pray

```
#include <iostream>
#include <climits>
using namespace std;

// f(x) == true ?
bool f(unsigned x) { return (x + 1) > x; }

int main() {
    cout << "f(0): " << f(0) << "\n";
    cout << "f(UINT32_MAX): " << f(UINT32_MAX) << "\n";
}

f(0): 1
f(UINT32_MAX): 0
```

- $f : \mathbb{N} \rightarrow \mathbb{B}; f(x) \equiv \begin{cases} \text{true} & x + 1 > x \\ \text{false} & \text{otherwise} \end{cases}$
- $f(x) \equiv \text{true}$
- $f : \mathbb{N} \rightarrow \mathbb{B}; f(x) \equiv \begin{cases} \text{true} & x +_{2^{32}} 1 > x \\ \text{false} & \text{otherwise} \end{cases}$

Why we pray

```
#include <iostream>
#include <climits>
using namespace std;

// f(x) == true ?
bool f(unsigned x) { return (x + 1) > x; }

int main() {
    cout << "f(0): " << f(0) << "\n";
    cout << "f(UINT32_MAX): " << f(UINT32_MAX) << "\n";
}

f(0): 1
f(UINT32_MAX): 0
```

- $f : \mathbb{N} \rightarrow \mathbb{B}; f(x) \equiv \begin{cases} \text{true} & x + 1 > x \\ \text{false} & \text{otherwise} \end{cases}$
- $f(x) \equiv \text{true}$
- $f : \mathbb{N} \rightarrow \mathbb{B}; f(x) \equiv \begin{cases} \text{true} & x +_{2^{32}} 1 > x \\ \text{false} & \text{otherwise} \end{cases}$
- $+_{2^{32}} : \mathbb{N} \times \mathbb{N} \rightarrow \mathbb{N}; x +_{2^{32}} y \equiv (x +_{\mathbb{N}} y) \% 2^{32}$

Why we pray

```
#include <iostream>
#include <climits>
using namespace std;

// f(x) == true ?
bool f(unsigned x) { return (x + 1) > x; }

int main() {
    cout << "f(0): " << f(0) << "\n";
    cout << "f(UINT32_MAX): " << f(UINT32_MAX) << "\n";
}

f(0): 1
f(UINT32_MAX): 0
```

$$\blacksquare f : \mathbb{N} \rightarrow \mathbb{B}; f(x) \equiv \begin{cases} \text{true} & x + 1 > x \\ \text{false} & \text{otherwise} \end{cases}$$

$$\blacksquare f(x) \equiv \text{true}$$

$$\blacksquare f : \mathbb{N} \rightarrow \mathbb{B}; f(x) \equiv \begin{cases} \text{true} & x + {}_{2^{32}}1 > x \\ \text{false} & \text{otherwise} \end{cases}$$

$$\blacksquare +_{{}_{2^{32}}} : \mathbb{N} \times \mathbb{N} \rightarrow \mathbb{N}; x +_{{}_{2^{32}}} y \equiv (x +_N y) \% 2^{32}$$

$$\blacksquare \text{UINT32_MAX} +_{{}_{2^{32}}} 1 = 0$$

Why we pray: A second example

```
int main() {  
    cout << 2 * ((int) getchar()) << "\n";  
}
```

Why we pray: A second example

```
int main() {  
    cout << 2 * ((int) getchar()) << "\n";  
}
```

$$\forall x \in \mathbb{Z}, 2 * x = x + x$$

Why we pray: A second example

```
int main() {  
    cout << 2 * ((int) getchar()) << "\n";  
}
```

$$\forall x \in \mathbb{Z}, 2 * x = x + x$$

```
int main() {  
    cout << ((int) getchar() + (int) getchar()) << "\n";  
}
```

Why we pray: A second example

```
int main() {  
    cout << 2 * ((int) getchar()) << "\n";  
}
```

$$\forall x \in \mathbb{Z}, 2 * x = x + x$$

```
int main() {  
    cout << ((int) getchar() + (int) getchar()) << "\n";  
}
```

```
■ int getchar()
```


Why we pray: A second example

```
int main() {  
    cout << 2 * ((int) getchar()) << "\n";  
}
```

$$\forall x \in \mathbb{Z}, 2 * x = x + x$$

```
int main() {  
    cout << ((int) getchar() + (int) getchar()) << "\n";  
}
```

- `int` `getchar()`
- `getchar` : $\emptyset \rightarrow \text{int}$

Why we pray: A second example

```
int main() {  
    cout << 2 * ((int) getchar()) << "\n";  
}
```

$$\forall x \in \mathbb{Z}, 2 * x = x + x$$

```
int main() {  
    cout << ((int) getchar() + (int) getchar()) << "\n";  
}
```

- `int` `getchar()`
- `getchar` : $\emptyset \rightarrow \text{int}$
- $\{\} \rightarrow \{1, 42, \dots\}$

Why we pray: A second example

```
int main() {  
    cout << 2 * ((int) getchar()) << "\n";  
}
```

$$\forall x \in \mathbb{Z}, 2 * x = x + x$$

```
int main() {  
    cout << ((int) getchar() + (int) getchar()) << "\n";  
}
```

- `int` `getchar()`
- `getchar` : $\emptyset \rightarrow \text{int}$
- $\{\} \rightarrow \{1, 42, \dots\}$
- Such a function can't return an output!

Why we pray: A second example

```
int main() {
  cout << 2 * ((int) getchar()) << "\n";
}
```

$$\forall x \in \mathbb{Z}, 2 * x = x + x$$

```
int main() {
  cout << ((int) getchar() + (int) getchar()) << "\n";
}
```

- `int` `getchar()`
- `getchar` : $\emptyset \rightarrow \text{int}$
- $\{\} \rightarrow \{1, 42, \dots\}$
- Such a function can't return an output!
- `getchar` : $\{\star\} \rightarrow \text{int}$

Why we pray: A second example

```
int main() {
  cout << 2 * ((int) getchar()) << "\n";
}
```

$$\forall x \in \mathbb{Z}, 2 * x = x + x$$

```
int main() {
  cout << ((int) getchar() + (int) getchar()) << "\n";
}
```

- `int` `getchar()`
- `getchar` : $\emptyset \rightarrow \text{int}$
- $\{\} \rightarrow \{1, 42, \dots\}$
- Such a function can't return an output!
- `getchar` : $\{\star\} \rightarrow \text{int}$
- $\{\star\} \rightarrow \{1, 42, \dots\}$

Why we pray: A second example

```
int main() {
  cout << 2 * ((int) getchar()) << "\n";
}
```

$$\forall x \in \mathbb{Z}, 2 * x = x + x$$

```
int main() {
  cout << ((int) getchar() + (int) getchar()) << "\n";
}
```

- `int` `getchar()`
- `getchar` : $\emptyset \rightarrow \text{int}$
- $\{\} \rightarrow \{1, 42, \dots\}$
- Such a function can't return an output!
- `getchar` : $\{\star\} \rightarrow \text{int}$
- $\{\star\} \rightarrow \{1, 42, \dots\}$
- $\{\star\} \rightarrow \{1, 42, \dots\} \star \mapsto 42$

Why we pray: A second example

```
int main() {
  cout << 2 * ((int) getchar()) << "\n";
}
```

$$\forall x \in \mathbb{Z}, 2 * x = x + x$$

```
int main() {
  cout << ((int) getchar() + (int) getchar()) << "\n";
}
```

- `int` `getchar()`
- `getchar` : $\emptyset \rightarrow \text{int}$
- $\{\} \rightarrow \{1, 42, \dots\}$
- Such a function can't return an output!
- `getchar` : $\{\star\} \rightarrow \text{int}$
- $\{\star\} \rightarrow \{1, 42, \dots\}$
- $\{\star\} \rightarrow \{1, 42, \dots\} \star \mapsto 42$
- Such a function will always return the same output!

Why we pray: A second example

```
int main() {
    cout << 2 * ((int) getchar()) << "\n";
}
```

$$\forall x \in \mathbb{Z}, 2 * x = x + x$$

```
int main() {
    cout << ((int) getchar() + (int) getchar()) << "\n";
}
```

- `int` `getchar()`
- `getchar` : $\emptyset \rightarrow \text{int}$
- $\{\} \rightarrow \{1, 42, \dots\}$
- Such a function can't return an output!
- `getchar` : $\{\star\} \rightarrow \text{int}$
- $\{\star\} \rightarrow \{1, 42, \dots\}$
- $\{\star\} \rightarrow \{1, 42, \dots\} \star \mapsto 42$
- Such a function will always return the same output!
- `getchar` can't be a mathematical function.

Why we pray: A second example

```
int main() {
    cout << 2 * ((int) getchar()) << "\n";
}
```

$$\forall x \in \mathbb{Z}, 2 * x = x + x$$

```
int main() {
    cout << ((int) getchar() + (int) getchar()) << "\n";
}
```

- `int` `getchar()`
- `getchar` : $\emptyset \rightarrow \text{int}$
- $\{\} \rightarrow \{1, 42, \dots\}$
- Such a function can't return an output!
- `getchar` : $\{\star\} \rightarrow \text{int}$
- $\{\star\} \rightarrow \{1, 42, \dots\}$
- $\{\star\} \rightarrow \{1, 42, \dots\} \star \mapsto 42$
- Such a function will always return the same output!
- `getchar` can't be a mathematical function.

Why we pray: A third example

```
int K (int x, int y) { return x; } //  $K(x, y) = x$ 
```

Why we pray: A third example

```
int K (int x, int y) { return x; } // K(x, y) = x
int main() { cout << K(10, 20) << "\n" cout << 10; }
```

Why we pray: A third example

```
int K (int x, int y) { return x; } //  $K(x, y) = x$   
int main() { cout << K(10, 20) << "\n" cout << 10; }  
K(10, 20) = 10
```

Why we pray: A third example

```
int K (int x, int y) { return x; } //  $K(x, y) = x$ 
int main() { cout << K(10, 20) << "\n" cout << 10; }
K(10, 20) = 10
int err() { exit(1); return 0; }
int main() { cout << K(10, err()) << "\n" cout << 10; }
```

Why we pray: A third example

```
int K (int x, int y) { return x; } //  $K(x, y) = x$ 

int main() { cout << K(10, 20) << "\n" cout << 10; }

 $K(10, 20) = 10$ 

int err() { exit(1); return 0; }

int main() { cout << K(10, err()) << "\n" cout << 10; }

 $K(10, err()) \neq 10$ 
```

Why we pray: A third example

```
int K (int x, int y) { return x; } //  $K(x, y) = x$ 
int main() { cout << K(10, 20) << "\n" cout << 10; }
K(10, 20) = 10
int err() { exit(1); return 0; }
int main() { cout << K(10, err()) << "\n" cout << 10; }
K(10, err())  $\neq$  10
```

- Mathematically, can replace $K(x, y)$ by x .

Why we pray: A third example

```
int K (int x, int y) { return x; } //  $K(x, y) = x$ 
```

```
int main() { cout << K(10, 20) << "\n" cout << 10; }
```

$K(10, 20) = 10$

```
int err() { exit(1); return 0; }
```

```
int main() { cout << K(10, err()) << "\n" cout << 10; }
```

$K(10, \text{err}()) \neq 10$

- Mathematically, can replace $K(x, y)$ by x .
- In C(++), impossible.

Why we pray: A third example

```
int K (int x, int y) { return x; } //  $K(x, y) = x$ 
```

```
int main() { cout << K(10, 20) << "\n" cout << 10; }
```

$K(10, 20) = 10$

```
int err() { exit(1); return 0; }
```

```
int main() { cout << K(10, err()) << "\n" cout << 10; }
```

$K(10, \text{err}()) \neq 10$

- Mathematically, can replace $K(x, y)$ by x .
- In C(++), impossible.
- cannot **equationally reason** about programs.

Why we pray: A third example

```
int K (int x, int y) { return x; } //  $K(x, y) = x$ 
```

```
int main() { cout << K(10, 20) << "\n" cout << 10; }
```

$K(10, 20) = 10$

```
int err() { exit(1); return 0; }
```

```
int main() { cout << K(10, err()) << "\n" cout << 10; }
```

$K(10, \text{err}()) \neq 10$

- Mathematically, can replace $K(x, y)$ by x .
- In C(++), impossible.
- cannot **equationally reason** about programs.
- **Can we** reason about programs?

Why we pray: A third example

```
int K (int x, int y) { return x; } //  $K(x, y) = x$ 
```

```
int main() { cout << K(10, 20) << "\n" cout << 10; }
```

$K(10, 20) = 10$

```
int err() { exit(1); return 0; }
```

```
int main() { cout << K(10, err()) << "\n" cout << 10; }
```

$K(10, \text{err}()) \neq 10$

- Mathematically, can replace $K(x, y)$ by x .
- In C(++), impossible.
- cannot **equationally reason** about programs.
- **Can we** reason about programs?

Can we reason about C++?

Can we reason about C++?

- Short answer: Yes.

Can we reason about C++?

- Short answer: Yes.
- Longer answer: Yes. It's complicated.

Can we reason about C++?

- Short answer: Yes.
- Longer answer: Yes. It's complicated.
- Name dropping: Operational/Denotational semantics.

Can we reason about C++?

- Short answer: Yes.
- Longer answer: Yes. It's complicated.
- Name dropping: Operational/Denotational semantics.
- Name dropping: Hoare logic/Separation logic.

Can we reason about C++?

- Short answer: Yes.
- Longer answer: Yes. It's complicated.
- Name dropping: Operational/Denotational semantics.
- Name dropping: Hoare logic/Separation logic.

How do we escape having to pray?

How do we escape having to pray?

Define a language,

How do we escape having to pray?

Define a language, where anything that happens,

How do we escape having to pray?

Define a language, where anything that happens, is what **mathematics** says should happen.

How do we escape having to pray?

Define a language, where anything that happens, is what **mathematics** says should happen.



A taste of Haskell

- `[1, 2,..10]`

A taste of Haskell

- `[1, 2,..10]`
- `range(10)`

A taste of Haskell

- `[1, 2, ..10]`
- `range(10)`
- `[1, 2..]`

A taste of Haskell

- `[1, 2, ..10]`
- `range(10)`
- `[1, 2..]`

Philosophical differences

docs.python.org/3/library/stdtypes.html#str.join

hackage.haskell.org/package/base-4.14.0.0/docs/Data-List.html#v:intercalate

```
" ".join(["a", "b", "c", "d"])
```

```
str.join(iterable)
```

Return a string which is the concatenation of the strings in *iterable*. A `TypeError` will be raised if there are any non-string values in *iterable*, including bytes objects. The separator between elements is the string providing this method.

```
intercalate " " ["a", "b", "c", "d"]
```

```
intercalate :: [a] -> [[a]] -> [a]
```

`intercalate xs xss` is equivalent to `(concat (intersperse xs xss))`. It inserts the list `xs` in between the lists in `xss` and concatenates the result.

Why should I learn haskell?

<https://docs.python.org/3/library/functions.html#sum>

hackage.haskell.org/package/base-4.14.0.0/docs/Data-List.html#v:intercalate

```
sum([1, 2, 3, 4])
```

```
sum(iterable, /, start=0)
```

Sums *start* and the items of an *iterable* from left to right and returns the total. The *iterable*'s items are normally numbers, and the start value is not allowed to be a string.

```
sum [1, 2, 3, 4]
```

```
sum :: (Foldable t, Num a) => t a -> a
```

The `sum` function computes the sum of the numbers of a structure.

Foldable in detail

```
class Foldable t where
  -- | Map each element of the structure to a monoid, and combine the results.
  foldMap :: Monoid m => (a -> m) -> t a -> m
```

Foldable instances are expected to satisfy the following laws:

```
foldr f z t = appEndo (foldMap (Endo . f) t) z
foldl f z t = appEndo (getDual (foldMap (Dual . Endo . flip f) t)) z
fold = foldMap id
length = getSum . foldMap (Sum . const 1)
```

<https://hackage.haskell.org/package/base-4.14.0.0/docs/Data-Foldable.html#t:Foldable>

Fibonacci

```
let fib = 0:1:(zipWith (+) fib (tail fib))
```

Equational reasoning

```
k x y = x  
k 10 (error "urk")  
  
def k(x, y): return x  
k(x, input())
```

What is input anyway?

$\emptyset \mapsto \text{char}$

Mathematically impossible!

Effects, or the “M” word

Keep every element, and drop every element.

```
powerset xs = filterM (const [True, False]) xs
```