

# The Yoneda Lemma

Siddharth Bhat

##harmless **Category Theory in Context**

July 25 2021

# The statement

## Given

- A locally small category  $C$
- A functor  $F : C \rightarrow \mathbf{Set}$
- An element  $a \in C$

**Question:** How many natural transformations  $\eta : \text{Hom}(a, -) \Rightarrow F$  are there?

**Answer:** Exactly as many as  $|F(a)|$  (where  $F(a) \in \text{Obj}(\mathbf{Set})$ )

**How?** Establish a bijection between elements  $x \in F(a)$  and natural transformations  $\eta_x : \text{Hom}(a, -) \Rightarrow F$ .

```
type Hom a b = a -> b
type Reader a = Hom a
type Nat f g = forall x. f x -> g x
```

```
yoFwd :: Nat (Hom a) f -> f a
yoBwd :: f a -> Nat (Hom a) f
```

The proof (1) (natural transformations  $\eta : \text{Hom}(a, -) \Rightarrow F$  have an element of  $F(a)$ )

```

type Hom a b = a -> b
type Reader a = Hom a
type Nat f g = forall x. f x -> g x

yoFwd :: Nat (Hom a) f -> f a
yoFwd :: (forall x. (Hom a x) -> f x) -> f a
yoFwd :: (forall x. (a -> x) -> f x) -> f a
yoFwd ak = (ak @ a) (id @ a :: a -> a) :: f a
-- ak @ a :: (a -> a) -> f a; id @ a :: a -> a

yoBwd :: f a -> Nat (Hom a) f

```

- Given the element  $a \in C$ , functor  $F : C \rightarrow \text{Set}$ , natural transformation  $\eta : \text{Hom}(a, -) \Rightarrow F$ , we must produce an element of  $F(a)$ .

The proof (1) (natural transformations  $\eta : \text{Hom}(a, -) \Rightarrow F$  have an element of  $F(a)$ )

```

type Hom a b = a -> b
type Reader a = Hom a
type Nat f g = forall x. f x -> g x

yoFwd :: Nat (Hom a) f -> f a
yoFwd :: (forall x. (Hom a x) -> f x) -> f a
yoFwd :: (forall x. (a -> x) -> f x) -> f a
yoFwd ak = (ak @ a) (id @ a :: a -> a) :: f a
-- ak @ a :: (a -> a) -> f a; id @ a :: a -> a

yoBwd :: f a -> Nat (Hom a) f

```

- Given the element  $a \in C$ , functor  $F : C \rightarrow \text{Set}$ , natural transformation  $\eta : \text{Hom}(a, -) \Rightarrow F$ , we must produce an element of  $F(a)$ .
- Idea: see that  $\text{id}_a \in \text{Hom}(a, a)$ .

The proof (1) (natural transformations  $\eta : \text{Hom}(a, -) \Rightarrow F$  have an element of  $F(a)$ )

```

type Hom a b = a -> b
type Reader a = Hom a
type Nat f g = forall x. f x -> g x

yoFwd :: Nat (Hom a) f -> f a
yoFwd :: (forall x. (Hom a x) -> f x) -> f a
yoFwd :: (forall x. (a -> x) -> f x) -> f a
yoFwd ak = (ak @ a) (id @ a :: a -> a) :: f a
-- ak @ a :: (a -> a) -> f a; id @ a :: a -> a

yoBwd :: f a -> Nat (Hom a) f

```

- Given the element  $a \in C$ , functor  $F : C \rightarrow \text{Set}$ , natural transformation  $\eta : \text{Hom}(a, -) \Rightarrow F$ , we must produce an element of  $F(a)$ .
- Idea: see that  $\text{id}_a \in \text{Hom}(a, a)$ .
- See that the natural transformation at point  $a$  is  $\eta_a : \text{Hom}(a, a) \Rightarrow Fa$ .

The proof (1) (natural transformations  $\eta : \text{Hom}(a, -) \Rightarrow F$  have an element of  $F(a)$ )

```

type Hom a b = a -> b
type Reader a = Hom a
type Nat f g = forall x. f x -> g x

yoFwd :: Nat (Hom a) f -> f a
yoFwd :: (forall x. (Hom a x) -> f x) -> f a
yoFwd :: (forall x. (a -> x) -> f x) -> f a
yoFwd ak = (ak @ a) (id @ a :: a -> a) :: f a
-- ak @ a :: (a -> a) -> f a; id @ a :: a -> a

yoBwd :: f a -> Nat (Hom a) f

```

- Given the element  $a \in C$ , functor  $F : C \rightarrow \text{Set}$ , natural transformation  $\eta : \text{Hom}(a, -) \Rightarrow F$ , we must produce an element of  $F(a)$ .
- Idea: see that  $\text{id}_a \in \text{Hom}(a, a)$ .
- See that the natural transformation at point  $a$  is  $\eta_a : \text{Hom}(a, a) \Rightarrow Fa$ .
- Combine the two, apply  $\eta_a(\text{id}_a) : Fa$ .

The proof (1) (natural transformations  $\eta : \text{Hom}(a, -) \Rightarrow F$  have an element of  $F(a)$ )

```

type Hom a b = a -> b
type Reader a = Hom a
type Nat f g = forall x. f x -> g x

yoFwd :: Nat (Hom a) f -> f a
yoFwd :: (forall x. (Hom a x) -> f x) -> f a
yoFwd :: (forall x. (a -> x) -> f x) -> f a
yoFwd ak = (ak @ a) (id @ a :: a -> a) :: f a
-- ak @ a :: (a -> a) -> f a; id @ a :: a -> a

yoBwd :: f a -> Nat (Hom a) f

```

- Given the element  $a \in C$ , functor  $F : C \rightarrow \text{Set}$ , natural transformation  $\eta : \text{Hom}(a, -) \Rightarrow F$ , we must produce an element of  $F(a)$ .
- Idea: see that  $\text{id}_a \in \text{Hom}(a, a)$ .
- See that the natural transformation at point  $a$  is  $\eta_a : \text{Hom}(a, a) \Rightarrow Fa$ .
- Combine the two, apply  $\eta_a(\text{id}_a) : Fa$ .

The proof (2) (an element  $x \in F(a)$  creates a natural transformation  $\eta_a : \text{Hom}(a, -) \Rightarrow F$ )

```
type Hom a b = a -> b; type Reader a = Hom a; type Nat f g = forall x. f x -> g x
```

```
yoBwd :: f a -> Nat (Hom a) f
yoBwd :: f a -> (forall x. (a -> x) -> f x)
yoBwd :: forall x. f a -> (a -> x) -> f x
yoBwd :: f a -> (a -> x) -> f x
yoBwd fa aUser = (fmap @ f) aUser fa
```

```
yoFwd :: Nat (Hom a) f -> f a
yoFwd ak = (ak @ a) (id @ a :: a -> a) :: f a
```

- Given the element  $a \in C$ , functor  $F : C \rightarrow \text{Set}$ , an element  $fa \in F(a)$ , we must produce a natural transformation  $\eta_{fa} : \text{Hom}(a, -) \Rightarrow F$ .



The proof (2) (an element  $x \in F(a)$  creates a natural transformation  $\eta_a : \text{Hom}(a, -) \Rightarrow F$ )

```
type Hom a b = a -> b; type Reader a = Hom a; type Nat f g = forall x. f x -> g x
```

```
yoBwd :: f a -> Nat (Hom a) f
yoBwd :: f a -> (forall x. (a -> x) -> f x)
yoBwd :: forall x. f a -> (a -> x) -> f x
yoBwd :: f a -> (a -> x) -> f x
yoBwd fa aUser = (fmap @ f) aUser fa
```

```
yoFwd :: Nat (Hom a) f -> f a
yoFwd ak = (ak @ a) (id @ a :: a -> a) :: f a
```

- Given the element  $a \in C$ , functor  $F : C \rightarrow \text{Set}$ , an element  $fa \in F(a)$ , we must produce a natural transformation  $\eta_{fa} : \text{Hom}(a, -) \Rightarrow F$ .
- For each  $fa \in F(a)$ , let's define the natural transformation  $\eta_{fa} : \text{Hom}(a, -) \Rightarrow F$ .

The proof (2) (an element  $x \in F(a)$  creates a natural transformation  $\eta_a : \text{Hom}(a, -) \Rightarrow F$ )

```
type Hom a b = a -> b; type Reader a = Hom a; type Nat f g = forall x. f x -> g x
```

```
yoBwd :: f a -> Nat (Hom a) f
yoBwd :: f a -> (forall x. (a -> x) -> f x)
yoBwd :: forall x. f a -> (a -> x) -> f x
yoBwd :: f a -> (a -> x) -> f x
yoBwd fa aUser = (fmap @ f) aUser fa
```

```
yoFwd :: Nat (Hom a) f -> f a
yoFwd ak = (ak @ a) (id @ a :: a -> a) :: f a
```

- Given the element  $a \in C$ , functor  $F : C \rightarrow \text{Set}$ , an element  $fa \in F(a)$ , we must produce a natural transformation  $\eta_{fa} : \text{Hom}(a, -) \Rightarrow F$ .
- For each  $fa \in F(a)$ , let's define the natural transformation  $\eta_{fa} : \text{Hom}(a, -) \Rightarrow F$ .
- Define it component-wise. For each  $x \in C$ , consider  $\eta_{fa}(x) : \text{Hom}(a, -)(x) \Rightarrow F(x)$ .

The proof (2) (an element  $x \in F(a)$  creates a natural transformation  $\eta_a : \text{Hom}(a, -) \Rightarrow F$ )

```
type Hom a b = a -> b; type Reader a = Hom a; type Nat f g = forall x. f x -> g x
```

```
yoBwd :: f a -> Nat (Hom a) f
yoBwd :: f a -> (forall x. (a -> x) -> f x)
yoBwd :: forall x. f a -> (a -> x) -> f x
yoBwd :: f a -> (a -> x) -> f x
yoBwd fa aUser = (fmap @ f) aUser fa
```

```
yoFwd :: Nat (Hom a) f -> f a
yoFwd ak = (ak @ a) (id @ a :: a -> a) :: f a
```

- Given the element  $a \in C$ , functor  $F : C \rightarrow \text{Set}$ , an element  $fa \in F(a)$ , we must produce a natural transformation  $\eta_{fa} : \text{Hom}(a, -) \Rightarrow F$ .
- For each  $fa \in F(a)$ , let's define the natural transformation  $\eta_{fa} : \text{Hom}(a, -) \Rightarrow F$ .
- Define it component-wise. For each  $x \in C$ , consider  $\eta_{fa}(x) : \text{Hom}(a, -)(x) \Rightarrow F(x)$ .
- Take an arrow  $a \xrightarrow{aUser} x \in \text{Hom}(a, -)(x)$ .

The proof (2) (an element  $x \in F(a)$  creates a natural transformation  $\eta_a : \text{Hom}(a, -) \Rightarrow F$ )

```
type Hom a b = a -> b; type Reader a = Hom a; type Nat f g = forall x. f x -> g x
```

```
yoBwd :: f a -> Nat (Hom a) f
yoBwd :: f a -> (forall x. (a -> x) -> f x)
yoBwd :: forall x. f a -> (a -> x) -> f x
yoBwd :: f a -> (a -> x) -> f x
yoBwd fa aUser = (fmap @ f) aUser fa
```

```
yoFwd :: Nat (Hom a) f -> f a
yoFwd ak = (ak @ a) (id @ a :: a -> a) :: f a
```

- Given the element  $a \in C$ , functor  $F : C \rightarrow \text{Set}$ , an element  $fa \in F(a)$ , we must produce a natural transformation  $\eta_{fa} : \text{Hom}(a, -) \Rightarrow F-$ .
- For each  $fa \in F(a)$ , let's define the natural transformation  $\eta_{fa} : \text{Hom}(a, -) \Rightarrow F-$ .
- Define it component-wise. For each  $x \in C$ , consider  $\eta_{fa}(x) : \text{Hom}(a, -)(x) \Rightarrow F(x)$ .
- Take an arrow  $a \xrightarrow{aUser} x \in \text{Hom}(a, -)(x)$ .
- Send it to  $F(a) \xrightarrow{F(aUser)} F(x)$ .

The proof (2) (an element  $x \in F(a)$  creates a natural transformation  $\eta_a : \text{Hom}(a, -) \Rightarrow F$ )

```
type Hom a b = a -> b; type Reader a = Hom a; type Nat f g = forall x. f x -> g x
```

```
yoBwd :: f a -> Nat (Hom a) f
yoBwd :: f a -> (forall x. (a -> x) -> f x)
yoBwd :: forall x. f a -> (a -> x) -> f x
yoBwd :: f a -> (a -> x) -> f x
yoBwd fa aUser = (fmap @ f) aUser fa
```

```
yoFwd :: Nat (Hom a) f -> f a
yoFwd ak = (ak @ a) (id @ a :: a -> a) :: f a
```

- Given the element  $a \in C$ , functor  $F : C \rightarrow \text{Set}$ , an element  $fa \in F(a)$ , we must produce a natural transformation  $\eta_{fa} : \text{Hom}(a, -) \Rightarrow F$ .
- For each  $fa \in F(a)$ , let's define the natural transformation  $\eta_{fa} : \text{Hom}(a, -) \Rightarrow F$ .
- Define it component-wise. For each  $x \in C$ , consider  $\eta_{fa}(x) : \text{Hom}(a, -)(x) \Rightarrow F(x)$ .
- Take an arrow  $a \xrightarrow{aUser} x \in \text{Hom}(a, -)(x)$ .
- Send it to  $F(a) \xrightarrow{F(aUser)} F(x)$ .
- Apply it on  $fa \in F(a)$ , giving  $F(aUser)(fa) \in F(x)$ .

The proof (2) (an element  $x \in F(a)$  creates a natural transformation  $\eta_a : \text{Hom}(a, -) \Rightarrow F$ )

```
type Hom a b = a -> b; type Reader a = Hom a; type Nat f g = forall x. f x -> g x
```

```
yoBwd :: f a -> Nat (Hom a) f
yoBwd :: f a -> (forall x. (a -> x) -> f x)
yoBwd :: forall x. f a -> (a -> x) -> f x
yoBwd :: f a -> (a -> x) -> f x
yoBwd fa aUser = (fmap @ f) aUser fa
```

```
yoFwd :: Nat (Hom a) f -> f a
yoFwd ak = (ak @ a) (id @ a :: a -> a) :: f a
```

- Given the element  $a \in C$ , functor  $F : C \rightarrow \text{Set}$ , an element  $fa \in F(a)$ , we must produce a natural transformation  $\eta_{fa} : \text{Hom}(a, -) \Rightarrow F$ .
- For each  $fa \in F(a)$ , let's define the natural transformation  $\eta_{fa} : \text{Hom}(a, -) \Rightarrow F$ .
- Define it component-wise. For each  $x \in C$ , consider  $\eta_{fa}(x) : \text{Hom}(a, -)(x) \Rightarrow F(x)$ .
- Take an arrow  $a \xrightarrow{aUser} x \in \text{Hom}(a, -)(x)$ .
- Send it to  $F(a) \xrightarrow{F(aUser)} F(x)$ .
- Apply it on  $fa \in F(a)$ , giving  $F(aUser)(fa) \in F(x)$ .
- Success! elements  $fa \in F(a)$  are natural transformations  $\eta_{fa}$  defined componentwise.

The proof (2) (an element  $x \in F(a)$  creates a natural transformation  $\eta_a : \text{Hom}(a, -) \Rightarrow F$ )

```
type Hom a b = a -> b; type Reader a = Hom a; type Nat f g = forall x. f x -> g x
```

```
yoBwd :: f a -> Nat (Hom a) f
yoBwd :: f a -> (forall x. (a -> x) -> f x)
yoBwd :: forall x. f a -> (a -> x) -> f x
yoBwd :: f a -> (a -> x) -> f x
yoBwd fa aUser = (fmap @ f) aUser fa
```

```
yoFwd :: Nat (Hom a) f -> f a
yoFwd ak = (ak @ a) (id @ a :: a -> a) :: f a
```

- Given the element  $a \in C$ , functor  $F : C \rightarrow \text{Set}$ , an element  $fa \in F(a)$ , we must produce a natural transformation  $\eta_{fa} : \text{Hom}(a, -) \Rightarrow F$ .
- For each  $fa \in F(a)$ , let's define the natural transformation  $\eta_{fa} : \text{Hom}(a, -) \Rightarrow F$ .
- Define it component-wise. For each  $x \in C$ , consider  $\eta_{fa}(x) : \text{Hom}(a, -)(x) \Rightarrow F(x)$ .
- Take an arrow  $a \xrightarrow{aUser} x \in \text{Hom}(a, -)(x)$ .
- Send it to  $F(a) \xrightarrow{F(aUser)} F(x)$ .
- Apply it on  $fa \in F(a)$ , giving  $F(aUser)(fa) \in F(x)$ .
- Success! elements  $fa \in F(a)$  are natural transformations  $\eta_{fa}$  defined componentwise.
- Naturality?

The proof (2) (an element  $x \in F(a)$  creates a natural transformation  $\eta_a : \text{Hom}(a, -) \Rightarrow F$ )

```
type Hom a b = a -> b; type Reader a = Hom a; type Nat f g = forall x. f x -> g x
```

```
yoBwd :: f a -> Nat (Hom a) f
yoBwd :: f a -> (forall x. (a -> x) -> f x)
yoBwd :: forall x. f a -> (a -> x) -> f x
yoBwd :: f a -> (a -> x) -> f x
yoBwd fa aUser = (fmap @ f) aUser fa
```

```
yoFwd :: Nat (Hom a) f -> f a
yoFwd ak = (ak @ a) (id @ a :: a -> a) :: f a
```

- Given the element  $a \in C$ , functor  $F : C \rightarrow \text{Set}$ , an element  $fa \in F(a)$ , we must produce a natural transformation  $\eta_{fa} : \text{Hom}(a, -) \Rightarrow F$ .
- For each  $fa \in F(a)$ , let's define the natural transformation  $\eta_{fa} : \text{Hom}(a, -) \Rightarrow F$ .
- Define it component-wise. For each  $x \in C$ , consider  $\eta_{fa}(x) : \text{Hom}(a, -)(x) \Rightarrow F(x)$ .
- Take an arrow  $a \xrightarrow{aUser} x \in \text{Hom}(a, -)(x)$ .
- Send it to  $F(a) \xrightarrow{F(aUser)} F(x)$ .
- Apply it on  $fa \in F(a)$ , giving  $F(aUser)(fa) \in F(x)$ .
- Success! elements  $fa \in F(a)$  are natural transformations  $\eta_{fa}$  defined componentwise.
- Naturality?



## Proof from the book

$$\text{[KNOWN]} \quad id_a : Hom(a, a) \xrightarrow{\eta} \eta(id_a) : F(a) \quad \text{[CHOSEN]}$$

$$\text{[ARBITRARY]} \quad p \in Hom(a, x) \xrightarrow{\eta} \eta(p) = ? : F(x) \quad \text{[UNKNOWN]}$$

## Proof from the book

$$\text{Hom}(a, a) \xrightarrow{\eta(a): \text{Hom}(a, a) \rightarrow F(a)} F(a)$$

[KNOWN]

$$id_a \xmapsto{\eta(a)} \eta(a)(id_a)$$

[CHOSEN]

## Proof from the book

$$\text{Hom}(a, a) \xrightarrow{\eta(a): \text{Hom}(a, a) \rightarrow F(a)} F(a)$$

[KNOWN]

$$id_a \xrightarrow{\eta(a)} \eta(a)(id_a)$$

[CHOSEN]

[ARBITRARY]

$$p \xrightarrow{\eta(p)} ?$$

[UNKNOWN]

$$\text{Hom}(a, x) \xrightarrow{\eta(x): \text{Hom}(a, x) \rightarrow F(x)} F(x)$$

## Proof from the book

$$\text{Hom}(a, a) \xrightarrow{\eta(a): \text{Hom}(a, a) \rightarrow F(a)} F(a)$$

[KNOWN]

$$id_a \xrightarrow{\eta(a)} \eta(a)(id_a)$$

[CHOSEN]

[ARBITRARY]

$$p \xrightarrow{\eta(x)} ?$$

[UNKNOWN]

$$\text{Hom}(a, x) \xrightarrow{\eta(x): \text{Hom}(a, x) \rightarrow F(x)} F(x)$$

## Proof from the book

$$\begin{array}{ccccc}
 & Hom(a, a) & \xrightarrow{\eta(a): Hom(a, a) \rightarrow F(a)} & F(a) & \\
 & \downarrow Hom(a, -)(p) & & & \\
 [KNOWN] & & id_a \xrightarrow{\eta(a)} \eta(a)(id_a) & & [CHOSEN] \\
 & & \downarrow \lambda f. p \circ f & & \\
 [ARBITRARY] & & p \xrightarrow{\eta(x)} ? & & [UNKNOWN] \\
 & \downarrow & & & \\
 & Hom(a, x) & \xrightarrow{\eta(x): Hom(a, x) \rightarrow F(x)} & F(x) & 
 \end{array}$$

## Proof from the book

