Photon-Mediated Quantum Gate between Two Neutral Atoms in an Optical Cavity

2018/05/14 JOURNAL CLUB HAN JUN SEOK

Gerhard Rempe

- Honorary Professor at the Technical University of Munich
- Director at Max Planck Institute of Quantum Optics

Research Interests

- Cavity Quantum Electrodynamics
- Quantum Information Processing
- Bose Einstein Condensation
- •etc.









Optical Kaleidoscope Using a Single Atom

P. Horak and H. Ritsch

Institut für Theoretische Physik, Universität Innsbruck, Technikerstrasse 25, A-6020 Innsbruck, Austria

T. Fischer, P. Maunz, T. Puppe, P. W. H. Pinkse, and G. Rempe

Max-Planck-Institut für Quantenoptik, Hans-Kopfermann-Strasse 1, D-85748 Garching, Germany

(Received 11 May 2001; published 9 January 2002)

PRL 95, 173602 (2005)

PHYSICAL REVIEW LETTERS

week ending 21 OCTOBER 2005

Submicron Positioning of Single Atoms in a Microcavity

Stefan Nußmann, Markus Hijlkema, Bernhard Weber, Felix Rohde,* Gerhard Rempe, and Axel Kuhn Max-Planck-Institut für Quantenoptik, Hans-Kopfermann-Str. 1, D-85748 Garching, Germany (Received 10 June 2005; published 19 October 2005)



LETTERS

PUBLISHED ONLINE: 29 FEBRUARY 2016 | DOI: 10.1038/NPHOTON.2016.19

Interference and dynamics of light from a distancecontrolled atom pair in an optical cavity

A. Neuzner, M. Körber, O. Morin, S. Ritter* and G. Rempe



A quantum gate between a flying optical photon and a single trapped atom

Andreas Reiserer¹, Norbert Kalb¹, Gerhard Rempe¹ & Stephan Ritter¹

LETTERS

A single-photon server with just one atom

MARKUS HIJLKEMA¹, BERNHARD WEBER¹, HOLGER P. SPECHT¹, SIMON C. WEBSTER¹, AXEL KUHN² AND GERHARD REMPE¹*

¹ Max-Planck-Institut für Quantenoptik, Hans-Kopfermann-Str. 1, D-85748 Garching, Germany

VOLUME 88, NUMBER 16

PHYSICAL REVIEW LETTERS

22 April 2002

Feedback on the Motion of a Single Atom in an Optical Cavity

T. Fischer, P. Maunz, P. W. H. Pinkse, T. Puppe, and G. Rempe

Max-Planck-Institut für Quantenoptik, Hans-Kopfermann-Strasse 1, D-85748 Garching, Germany

(Received 22 January 2002; published 4 April 2002)

²Department of Physics, University of Oxford, Clarendon Laboratory, Parks Road, Oxford OX1 3PU, UK

^{*}e-mail: gerhard.rempe@mpq.mpg.de

Quantum logic gate and qubit

Qubit
$$|\uparrow\rangle = \begin{pmatrix} 1 \\ 0 \end{pmatrix}, |\downarrow\rangle = \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$
 and $|\uparrow\uparrow\rangle = \begin{pmatrix} 1 \\ 0 \\ 0 \end{pmatrix}, |\uparrow\downarrow\rangle = \begin{pmatrix} 0 \\ 1 \\ 0 \end{pmatrix}, |\downarrow\uparrow\rangle = \begin{pmatrix} 0 \\ 0 \\ 1 \end{pmatrix}$

$$-H$$

$$\frac{1}{\sqrt{2}} \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix}$$

SWAP Gate
$$\begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$


$$\begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix}$$



CNOT Gate

Controlled NOT (or X) Gate acts on two qubits


NOT operation executed on second qubit only when first qubit is in $|\downarrow\rangle$




$$\begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 \\ 0 & 0 & 1 & 0 \end{bmatrix}$$

Qubit

$$|1\rangle: |\Psi^{-}\rangle = (|\uparrow\downarrow\rangle - |\downarrow\uparrow\rangle)/\sqrt{2}$$
$$|2\rangle: |\Psi^{+}\rangle = (|\uparrow\downarrow\rangle + |\downarrow\uparrow\rangle)/\sqrt{2}$$
$$|3\rangle: |\Phi^{-}\rangle = (|\uparrow\uparrow\rangle - |\downarrow\downarrow\rangle)/\sqrt{2}$$
$$|4\rangle: |\Phi^{+}\rangle = (|\uparrow\uparrow\rangle + |\downarrow\downarrow\rangle)/\sqrt{2}$$



Method



Two ^{87}Rb atoms in $2{\sim}12\mu m$ distance Weak coherent pulse with $\bar{n}=0.13$

$$|e\rangle$$
: $5^2 P_{3/2} | F' = 3, m_F = 3 \rangle$

$$|\uparrow\rangle$$
: $5^2S_{1/2}|F=2, m_F=2\rangle$

$$|\downarrow\rangle$$
: $5^2S_{1/2}|F=3, m_F=1\rangle$

$$|\uparrow\uparrow\rangle \rightarrow |\uparrow\uparrow\rangle$$
 $|\downarrow\uparrow\rangle \rightarrow |\downarrow\uparrow\rangle$


$$|\uparrow\downarrow\rangle \rightarrow |\uparrow\downarrow\rangle$$
 $|\downarrow\downarrow\rangle \rightarrow -|\downarrow\downarrow\rangle$


Experimental Setup

- Cavity profile
 - Finesse $F = 6 \times 10^4$
 - Asymmetric cavity: high-reflective mirror reflectivity of 99.9994% and out coupling mirror 99.99%
- • $(g, \kappa, \gamma) = 2\pi \times (7.8, 2.5, 3.0)MHz$
- •3D optical lattice with Sisyphus cooling to $100 \mu K$

Preparing States


Cavity Carving






State Detection

 Measuring transmission through high-reflectivity mirror




2. Fluorescence



Parity Oscillation

-Rotate state with Raman laser for ϕ and measure probabilities of each states

-Caluclate
$$\Pi(\phi) = P_{\uparrow\uparrow} + P_{\downarrow\downarrow} - (P_{\uparrow\downarrow} + P_{\downarrow\uparrow})$$



-Fidelity

 $F = \langle \Psi | \rho | \Psi \rangle$, ρ : measured state density matrix, $|\Psi \rangle$: ideal state


$$F(|\Psi^{\pm}\rangle) = \frac{1}{2}(P_{\uparrow\downarrow} + P_{\downarrow\uparrow}) \pm \text{Re}(\rho_{\uparrow\downarrow,\downarrow\uparrow})$$
$$F(|\Phi^{\pm}\rangle) = \frac{1}{2}(P_{\uparrow\uparrow} + P_{\downarrow\downarrow}) \pm \text{Re}(\rho_{\uparrow\uparrow,\downarrow\downarrow})$$


$$F(|\Phi^{\pm}\rangle) = \frac{1}{2}(P_{\uparrow\uparrow} + P_{\downarrow\downarrow}) \pm \operatorname{Re}(\rho_{\uparrow\uparrow,\downarrow\downarrow})$$

Timing


- $\blacksquare \pi$ pulse duration $8\mu s$, Gaussian intensity profile with a full width at half maximum of $0.9\mu s$
- •Two pulses with $\bar{n}=0.33$ for state preparation
- •Length of 5 and $3\mu s$ for a state detection in fluorescence and transmission.
- •Repeat the protocol of length $70\mu s$ at a rate of 1kHz with laser cooling intervals of $0.7\mu s$

Result





Result



2π

2π

Errors

TABLE I. Sources of error for the experimental fidelity of the $|\Phi^-\rangle$ state created by the entangling gate operation. Given values are the absolute decrease in fidelity due to each effect if all other influences are kept constant. The effects are not independent, which has to be taken into account if multiple error sources are summed.

Source of error	Fidelity reduction
Finite mode matching	6%
Erroneous state detection	4%
Multiphoton contributions	3%
Photon loss in the cavity	3%
Heralding detector dark counts	2%
Photon polarization inaccuracy	1%
Atomic state preparation	1%
Atomic state dephasing	1%

With single photon source, fidelity can go up to 82% in ideal case