

Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7






Fig. 8








Fig. 11A




Fig. 11B

SYSTEMS, DEVICES, AND METHODS FOR ELECTRICAL STIMULATION USING FEEDBACK TO ADJUST STIMULATION PARAMETERS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a divisional of U.S. patent application Ser. No. 14/876,708, filed Oct. 6, 2015, which claims the benefit under 35 U.S.C. § 119(e) of U.S. Provisional Patent Application Ser. No. 62/061,069, filed Oct. 7, 2014, both of which are incorporated herein by reference.

FIELD

[0002] The present invention is directed to the area of implantable electrical stimulation systems and methods of making and using the systems. The present invention is also directed to implantable electrical stimulation systems that include devices or methods for electrical stimulation which utilize feedback from one or more sensors to adjust stimulation parameters, as well as methods of making and using the electrical stimulation systems.

BACKGROUND

[0003] Implantable electrical stimulation systems have proven therapeutic in a variety of diseases and disorders. For example, spinal cord stimulation systems have been used as a therapeutic modality for the treatment of chronic pain syndromes. Peripheral nerve stimulation has been used to treat chronic pain syndrome and incontinence, with a number of other applications under investigation. Functional electrical stimulation systems have been applied to restore some functionality to paralyzed extremities in spinal cord injury patients.

[0004] Stimulators have been developed to provide therapy for a variety of treatments. A stimulator can include a control module (with a pulse generator), one or more leads, and an array of stimulator electrodes on each lead. The stimulator electrodes are in contact with or near the nerves, muscles, or other tissue to be stimulated. The pulse generator in the control module generates electrical pulses that are delivered by the electrodes to body tissue.

BRIEF SUMMARY

[0005] One embodiment is an electrical stimulation system including an implantable control module for implantation in a body of a patient and having an antenna and a processor coupled to the antenna. (In other embodiments, the control module is an external control module.) The control module provides electrical stimulation signals to an electrical stimulation lead coupled to the implantable control module for stimulation of patient tissue. The system also includes an external programming unit to communicate with the processor of the implantable control module using the antenna and to provide or update stimulation parameters for production of the electrical stimulation signals; a sensor to be disposed on or within the body of the patient and to measure a biosignal; and a biosignal processor to communicate with the sensor to receive the biosignal and to generate an adjustment to one or more of the stimulation parameters based on the biosignal. The adjustment can be configured and arranged to steer the electrical stimulation signals to stimulate a region of the patient tissue that is

different, at least in part, from a region of the patient tissue stimulated prior to the adjustment. Alternatively or additionally, the biosignal is indicative of a particular patient activity and the adjustment is a pre-determined adjustment selected for the particular patient activity.

[0006] In at least some embodiments, the external programming unit includes the biosignal processor. In at least some embodiments, the biosignal processor is configured and arranged for communication with the external programming unit to deliver the adjustment to the external programming unit. In at least some embodiments, the sensor is disposed on the control module.

[0007] In at least some embodiments, the system also includes a lead coupleable to the control module and having electrodes for delivering the electrical stimulation signals to the patient tissue. In at least some embodiments, the sensor is disposed on the lead.

[0008] In at least some embodiments, the biosignal processor is configured and arranged to perform the following actions: receive the biosignal from the sensor; and determine the adjustment to one or more stimulation parameters based on the biosignal. In at least some embodiments, the biosignal processor is configured and arranged to perform the additional following action: deliver the adjustment to one of the external programming unit or the control module.

[0009] In at least some embodiments, the adjustment is provided to the control module automatically and without user intervention.

[0010] Another embodiment is an electrical stimulation system including a sensor to be disposed on or within the body of the patient and to measure a biosignal; and a control module having a processor. The control module provides electrical stimulation signals to an electrical stimulation lead coupled to the control module for stimulation of patient tissue. The processor is configured and arranged to communicate with the sensor to receive the biosignal and to generate an adjustment to one or more of the stimulation parameters based on the biosignal. The adjustment can be configured and arranged to steer the electrical stimulation signals to stimulate a region of the patient tissue that is different, at least in part, from a region of the patient tissue stimulated prior to the adjustment. Alternatively or additionally, the biosignal is indicative of a particular patient activity and the adjustment is a pre-determined adjustment selected for the particular patient activity.

[0011] In at least some embodiments, the control module is an implantable control module configured and arranged for implantation in a body of a patient, the implantable control module further comprising an antenna coupled to the processor. In at least some embodiments, the sensor is disposed on the control module. In other embodiments, the control module is an external control module.

[0012] In at least some embodiments, the processor is configured and arranged to perform the following actions: receive the biosignal from the sensor; and determine the adjustment to one or more stimulation parameters based on the biosignal.

[0013] In at least some embodiments, the system also includes a lead coupleable to the control module and comprising a plurality of electrodes for delivering the electrical stimulation signals to the patient tissue. In at least some embodiments, the sensor is disposed on the lead.

[0014] Yet another embodiment is a non-transitory computer-readable medium having processor-executable

instructions for adjusting one or more stimulation parameters, the processor-executable instructions when installed onto a device enable the device to perform actions, including: receive a biosignal from one or more sensors; and determine an adjustment to the one or more stimulation parameters based on the biosignal. The adjustment can be configured and arranged to steer the electrical stimulation signals to stimulate a region of the patient tissue that is different, at least in part, from a region of the patient tissue stimulated prior to the adjustment. Alternatively or additionally, the biosignal is indicative of a particular patient activity and the adjustment is a pre-determined adjustment selected for the particular patient activity.

[0015] In at least some embodiments, the processor-executable instructions when installed onto a device enable the device to perform the following additional action: deliver the adjustment to one of an external programming unit or a control module.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] Non-limiting and non-exhaustive embodiments of the present invention are described with reference to the following drawings. In the drawings, like reference numerals refer to like parts throughout the various figures unless otherwise specified.

[0017] For a better understanding of the present invention, reference will be made to the following Detailed Description, which is to be read in association with the accompanying drawings, wherein:

[0018] FIG. 1 is a schematic block diagram of one embodiment of an electrical stimulation system, according to the invention;

[0019] FIG. 2 is a schematic block diagram of another embodiment of an electrical stimulation system, according to the invention;

[0020] FIG. 3 is a schematic block diagram of another embodiment of an electrical stimulation system, according to the invention;

[0021] FIG. 4 is a schematic block diagram of one embodiment of an external programming unit, according to the invention;

[0022] FIG. 5 is a schematic block diagram of one embodiment of a processing unit, according to the invention;

[0023] FIG. 6 is a flowchart of one embodiment of a method for adjusting stimulation parameters, according to the invention;

[0024] FIG. 7 is a flowchart of one embodiment of a method for testing a range of stimulation parameters, according to the invention;

[0025] FIG. 8 is a flowchart of one embodiment of a method for requesting patient authorization for using patient data, according to the invention;

[0026] FIG. 9 is a schematic view of one embodiment of an electrical stimulation system that includes a paddle lead electrically coupled to a control module, according to the invention;

[0027] FIG. 10 is a schematic view of one embodiment of an electrical stimulation system that includes a percutaneous lead electrically coupled to a control module, according to the invention;

[0028] FIG. 11A is a schematic view of one embodiment of the control module of FIG. 9 configured and arranged to electrically couple to an elongated device, according to the invention; and

[0029] FIG. 11B is a schematic view of one embodiment of a lead extension configured and arranged to electrically couple the elongated device of FIG. 10 to the control module of FIG. 9, according to the invention

DETAILED DESCRIPTION

[0030] The present invention is directed to the area of implantable electrical stimulation systems and methods of making and using the systems. The present invention is also directed to implantable electrical stimulation systems that include devices or methods for electrical stimulation which utilize feedback from one or more sensors to adjust stimulation parameters, as well as methods of making and using the electrical stimulation systems.

[0031] Suitable implantable electrical stimulation systems include, but are not limited to, a least one lead with one or more electrodes disposed along a distal end of the lead and one or more terminals disposed along the one or more proximal ends of the lead. Leads include, for example, percutaneous leads, paddle leads, and cuff leads. Examples of electrical stimulation systems with leads are found in, for example, U.S. Pat. Nos. 6,181,969; 6,516,227; 6,609,029; 6,609,032; 6,741,892; 7,949,395; 7,244,150; 7,672,734; 7,761,165; 7,974,706; 8,175,710; 8,224,450; and 8,364,278; and U.S. Patent Application Publication No. 2007/0150036, all of which are incorporated by reference.

[0032] An electrical stimulation system can include one or more sensors that can measure a functional response to electrical stimulation treatment. The measurements can be used in an automated or semi-automated manner to alter one or more stimulation parameters to enhance the treatment. In at least some embodiments, the system may perform these measurements under one or more conditions such as, for example, during a programming session; at regular or irregular intervals during operation of the system; or when initiated by a clinician, patient, or other individual.

[0033] In at least some embodiments, the electrical stimulation system can have a closed-loop feedback function using the one or more sensors and the respective measurements. The feedback function may be automated or semi-automated. In at least some embodiments, the feedback function may be initiated under one or more conditions such as, for example, during a programming session; at regular or irregular intervals during operation of the system; or when directed by a clinician, patient, or other individual.

[0034] In at least some embodiments, the measurements can be used to steer the electrical stimulation (for example, the electrical current). Steering can be performed by, for example, altering the selection of electrode(s) that provide the electrical stimulation; altering the amplitude (or other stimulation parameters such as frequency or duration) of stimulation provided by given electrodes; or the like or any combination thereof. In at least some embodiments, steering of the electrical stimulation can include multiple timing channels which utilize the electrodes of the lead to generate different electric fields. The electric fields for the different timing channels can be interleaved temporally to alter the electrical stimulation of the patient tissue. Stimulation steering can be used to alter the electric field produced by the system and to alter the portion of patient tissue being stimulated or the amount of stimulation provided to a region of patient tissue. This can tailor the stimulation to the patient or to the current condition of the patient. Any combination of these steering methods can also be employed.

[0035] In at least some embodiments, one or more sensors can be used to determine patient postural, positional, or activity changes or to determine changes in disease or disorder progression or modality, or changes in the stimulation system. These measurements can be used to alter one or more electrical stimulation parameters. The system may perform these measurements under one or more conditions such as, for example, during a programming session; at regular or irregular intervals during operation of the system; or when directed by a clinician, patient, or other individual. In at least some embodiments, the electrical stimulation system can have a closed-loop feedback function that allows the system to alter stimulation as a result of changes in patient activity, changes in the disease or disorder, or changes to the components of the system or their surroundings.

[0036] FIG. 1 illustrates schematically one embodiment of an electrical stimulation system 100 that includes an implantable control module (e.g., an implantable electrical stimulator or implantable pulse generator) 102, one or more leads 108 with electrodes, one or more external programming units 106, one or more sensors 107, and a processing unit 104. Alternatively, the implantable control module 102 can be part of a microstimulator with the electrodes disposed on the housing of the microstimulator. The microstimulator may not include a lead or, in other embodiments, a lead may extend from the microstimulator. As yet another alternative, the control module can be external to the patient. One example of an external control module is an external trial stimulator that can be used temporarily during the implantation procedure to test stimulation using the lead.

[0037] It will be understood that the electrical stimulation system can include more, fewer, or different components and can have a variety of different configurations including those configurations disclosed in the references cited herein. For example, although FIG. 1 illustrates one external programming unit 106, one control module 102, and one sensor 107, it will be understood that the system can include more than one external programming unit, more than one control module, more than one sensor, or any combination thereof.

[0038] The lead 108 is coupled, or coupleable, to the implantable control module 102. The implantable control module 102 includes a processor 110, an antenna 112 (or other communications arrangement), a power source 114, and a memory 116, as illustrated in FIG. 1.

[0039] FIGS. 2 and 3 illustrate other embodiments in which the processing unit is omitted and the external programming unit 106, sensor(s) 107, or control module 102 or any combination thereof can perform the functions of the processing unit. In the embodiment of FIG. 2, the sensor 107 is in communication with the external programming unit 106. In the embodiment of FIG. 3, the sensor 107 is in communication with the control module 102.

[0040] One example of an external programming unit 106 is illustrated in FIG. 4 and includes a processor 160, a memory 162, a communications arrangement 164 (such as an antenna or any other suitable communications device such as those described below), and a user interface 166. Suitable devices for use as an external programming unit can include, but are not limited to, a computer, a tablet, a mobile telephone, a personal desk assistant, a dedicated device for external programming, remote control, or the like. It will be understood that the external programming unit 106 can include a power supply or receive power from an external

source or any combination thereof. The external programming unit 106 can be a home station or unit at a clinician's office or any other suitable device. In some embodiments, the external programming unit 106 can be a device that is worn on the skin of the user or can be carried by the user and can have a form similar to a pager, cellular phone, or remote control, if desired. The external programming unit 106 can be any unit that can provide information to the control module 102. One example of a suitable external programming unit 106 is a computer operated by the clinician or patient to send signals to the control module 102. Another example is a mobile device or an application on a mobile device that can send signals to the control module 102.

[0041] One example of a processing unit 104 is illustrated in FIG. 5 and includes a processor 140, a memory 142, a communications arrangement 144 (such as an antenna or any other suitable communications device such as those described below), and an optional user interface 146. Suitable devices for use as a processing unit can include, but are not limited to, a computer, a tablet, a server or server farm, or the like. It will be understood that the processing unit 104 can include a power supply or receive power from an external source or any combination thereof.

[0042] Methods of communication between devices or components of a system can include wired (including, but not limited to, USB, mini/micro USB, HDMI, and the like) or wireless (e.g., RF, optical, infrared, near field communication (NFC), Bluetooth™, or the like) communications methods or any combination thereof. By way of further example, communication methods can be performed using any type of communication media or any combination of communication media including, but not limited to, wired media such as twisted pair, coaxial cable, fiber optics, wave guides, and other wired media and wireless media such as acoustic, RF, optical, infrared, NFC, Bluetooth™ and other wireless media. These communication media can be used for communications units 144, 164 or as antenna 112 or as an alternative or supplement to antenna 112.

[0043] Turning to the control module 102, some of the components (for example, a power source 114, an antenna 112, and a processor 110) of the electrical stimulation system can be positioned on one or more circuit boards or similar carriers within a sealed housing of the control module (implantable pulse generator,) if desired. Any power source 114 can be used including, for example, a battery such as a primary battery or a rechargeable battery. Examples of other power sources include super capacitors, nuclear or atomic batteries, mechanical resonators, infrared collectors, thermally-powered energy sources, flexural powered energy sources, bioenergy power sources, fuel cells, bioelectric cells, osmotic pressure pumps, and the like including the power sources described in U.S. Pat. No. 7,437,193, incorporated herein by reference.

[0044] As another alternative, power can be supplied by an external power source through inductive coupling via the antenna 112 or a secondary antenna. The external power source can be in a device that is mounted on the skin of the user or in a unit that is provided near the user on a permanent or periodic basis.

[0045] If the power source 114 is a rechargeable battery, the battery may be recharged using the antenna 112, if desired. Power can be provided to the battery for recharging by inductively coupling the battery through the antenna to a recharging unit external to the user.

[0046] A stimulation signal, such as electrical current in the form of electrical pulses, is emitted by the electrodes of the lead **108** (or a microstimulator) to stimulate neurons, nerve fibers, muscle fibers, or other body tissues near the electrical stimulation system. Examples of leads are described in more detail below. The processor **110** is generally included to control the timing and electrical characteristics of the electrical stimulation system. For example, the processor **110** can, if desired, control one or more of the timing, frequency, strength, duration, and waveform of the pulses. In addition, the processor **110** can select which electrodes can be used to provide stimulation, if desired. In some embodiments, the processor **110** selects which electrode(s) are cathodes and which electrode(s) are anodes. In some embodiments, the processor **110** is used to identify which electrodes provide the most useful stimulation of the desired tissue.

[0047] With respect to the control module **102**, external programming unit **106**, and database unit **104**, any suitable processor **110**, **140**, **160** can be used in these devices. For the control module **102**, the processor **110** is capable of receiving and interpreting instructions from an external programming unit **106** that, for example, allows modification of pulse characteristics. In the illustrated embodiment, the processor **110** is coupled to the antenna **112**. This allows the processor **110** to receive instructions from the external programming unit **106** to, for example, direct the pulse characteristics and the selection of electrodes, if desired. The antenna **112**, or any other antenna described herein, can have any suitable configuration including, but not limited to, a coil, looped, or loopless configuration, or the like. In one embodiment, the antenna **112** is capable of receiving signals (e.g., RF signals) from the external programming unit **106** or sensor **107**.

[0048] The signals sent to the processor **110** via the antenna **112** can be used to modify or otherwise direct the operation of the electrical stimulation system. For example, the signals may be used to modify the pulses of the electrical stimulation system such as modifying one or more of pulse duration, pulse frequency, pulse waveform, and pulse strength. The signals may also direct the control module **102** to cease operation, to start operation, to start charging the battery, or to stop charging the battery.

[0049] Optionally, the control module **102** may include a transmitter (not shown) coupled to the processor **110** and the antenna **112** for transmitting signals back to the external programming unit **106** or another unit capable of receiving the signals. For example, the control module **102** may transmit signals indicating whether the control module **102** is operating properly or not or indicating when the battery needs to be charged or the level of charge remaining in the battery. The processor **110** may also be capable of transmitting information about the pulse characteristics so that a user or clinician can determine or verify the characteristics.

[0050] Any suitable memory **116**, **142**, **162** can be used for the respective components of the system **100**. The memory **116**, **142**, **162** illustrates a type of computer-readable media, namely computer-readable storage media. Computer-readable storage media may include, but is not limited to, nonvolatile, removable, and non-removable media implemented in any method or technology for storage of information, such as computer readable instructions, data structures, program modules, or other data. Examples of computer-readable storage media include RAM, ROM,

EEPROM, flash memory, or other memory technology, CD-ROM, digital versatile disks (“DVD”) or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by a computing device.

[0051] Communication methods provide another type of computer readable media; namely communication media. Communication media typically embodies computer-readable instructions, data structures, program modules, or other data in a modulated data signal such as a carrier wave, data signal, or other transport mechanism and include any information delivery media. The terms “modulated data signal,” and “carrier-wave signal” includes a signal that has one or more of its characteristics set or changed in such a manner as to encode information, instructions, data, and the like, in the signal. By way of example, communication media includes wired media such as twisted pair, coaxial cable, fiber optics, wave guides, and other wired media and wireless media such as acoustic, RF, infrared, and other wireless media.

[0052] The user interface **166** of the external programming unit **106** and optional user interface **146** of the processing unit **104** can be, for example, a keyboard, mouse, touch screen, track ball, joystick, voice recognition system, or any combination thereof, and the like. Alternatively or additionally, the user interface **166** of the external programming unit **106** can include one or more microphones, sensors, cameras, or the like to obtain clinician or patient input. For example, the clinician or patient may provide input verbally (e.g. voice command recognition, voice recordings) or visually (e.g. video of patient, non-touch gesture recognition, or the like). In at least some embodiments, patient feedback can be provided by the clinician or other user through the external programming unit **106**.

[0053] The one or more sensors **107** can be any suitable sensors for measuring a biosignal (which can include a variable biological condition such as, for example, skin resistance, skin or tissue impedance, temperature, or the like). Examples of biosignals include EEG, electrocochleograph (ECOG), electromyography, skin resistance, skin or tissue impedance, muscle tone, heart rate, ECG, blood pressure, electrical signals traversing the spinal cord or a nerve or group of nerves, tremors or other movement (which can be measured using, for example, displacement, velocity, acceleration, direction of movement, and the like), muscle contraction or relaxation, vibration, temperature, breathing, oxygen levels, chemical concentrations, gait, skin tone, or the like.

[0054] Any sensor suitable for measuring the corresponding biosignal can be used. The sensor can be a mechanical, electrical, chemical, or biological sensor or any combination thereof. The sensor can be inserted in, implanted in, positioned on, or otherwise coupled to the body of the patient. In some embodiments, at least one sensor is provided on the lead or control module and can be, for example, a separate recording electrode for recording electrical signals or can be one or more stimulating electrodes that also are used for recording electrical signals. In other embodiments, the sensor can be attached to the body of the patient using, for example, a band, cuff, belt, clamp, clip, friction, adhesive, or the like or any combination thereof. In some embodiments,

the sensor can be provided on, or attached to, the external programming unit or a patient remote control or a charging unit for the control module.

[0055] The sensor **107** can be in communication with the external programming unit **106**, the control module **102**, the processing unit **104**, or any combination thereof. Such communication can be wired or wireless or any combination thereof using any of the communication methods described above. In at least some embodiments, the sensor **107** can include a processor, a memory, or both.

[0056] In at least some embodiments, the sensor **107** is deployed and used only during a programming session. In other embodiments, the sensor **107** may be deployed on or within the patient for an extended period of time (for example, at least one day, one week, one month, six months, one year, or longer). In at least some embodiments, the sensor **107** may be in regular or constant communication with the control module **102** or external programming unit **106**. In at least some embodiments, the sensor **107** may contact the control module **102**, external programming unit **106**, or processing unit **104** when requested, when a change in the biosignal exceeds a threshold, at regular or irregular intervals, or any combination thereof.

[0057] As an example, in at least some embodiments, the system includes a sensor that detects or measures muscle tremors or rigidity. For example, the sensor can be an accelerometer or the like and can be a fingertip sensor or a sensor disposed on a band, belt, adhesive, or other fastener so that the sensor can be mounted on the leg, arm, or other portion of the patient. Such a sensor could be used, for example, with an electrical stimulation system for treating Parkinson's disease, essential tremor, dystonia, hemiballismus, Tourette's syndrome, Huntington's disease, urge incontinence, or any other disease or disorder that causes muscle tremors or other involuntary muscle actions or rigidity or for treating symptoms such as, for example, tremor, rigidity, bradykinesia, freezing of gait, dyskinesias, or the like.

[0058] As another example, in at least some embodiments, the system includes a sensor that detects or measures blood pressure. For example, the sensor can be a cuff or other blood pressure measurement device, such as a fingertip sensor or a sensor disposed on a band, belt, adhesive, or other fastener so that the sensor can be mounted on the leg, arm, or other portion of the patient. Such a sensor could be used, for example, with an electrical stimulation system for carotid sinus stimulation, deep brain stimulation, or the like.

[0059] Yet another example, in at least some embodiments, the sensor includes a sensor that detects or measures heart rate and parameters associated heart rate, such as heart rate variability (HR variability). HR variability can be correlated with anxiety or sources that cause anxiety (pain, PTSD, OCD, and the like). Heart Rate is also a surrogate for activity monitoring. In at least some embodiments, the heart rate can be monitored by a sensor disposed on a lead implanted in or near the spinal cord and used for electrical stimulation of the spinal cord.

[0060] In at least some embodiments, the system includes a sensor that detects or measures movement. For example, the sensor can be a global positioning sensor (GPS), accelerometer, heart rate or pulse rate monitor, blood pressure cuff or other blood pressure measurement device such as a fingertip sensor, or the like. Such a sensor could be used, for example, with an electrical stimulation system to adjust one

or more stimulation parameters based on patient activity. For example, the sensor may detect when a patient is walking, running, climbing, driving, sitting, resting, sleeping, or the like. Sleeping longevity and interruptions to sleep may be very relevant for some indications. In at least some instances, Parkinson's patients have shorter sleep. Also, individuals with overactive bladder or interstitial cystitis have disrupted sleep for urination. Sensing attributes of sleep can be used to adjust one or more stimulation parameters.

[0061] The electrical stimulation system **100** can use the measurements from the sensor(s) **107** to modify one or more stimulation parameters. In some embodiments, the modification of stimulation parameters results in steering the electrical stimulation (for example, a stimulation current) to stimulate different portions of the patient tissue or produce a different stimulation field. In some embodiments, this steering can be accomplished by changing the selection of one or more electrodes on the lead used to deliver the electrical stimulation or adjusting the relative amplitudes, frequency, or duration of stimulation from the electrode(s) or any combination thereof. In other embodiments, one or more stimulation parameters can be changed including, but not limited to, amplitude, pulse width, pulse frequency, electrode configuration, electrode polarity, and the like. In at least some embodiments, steering of the electrical stimulation can include multiple timing channels which utilize the electrodes of the lead to generate different electric fields. The electric fields for the different timing channels can be interleaved temporally to alter the electrical stimulation of the patient tissue.

[0062] In at least some embodiments, the measurements from the sensor(s) **107** are provided to the processing unit **104**. The processing unit **104** includes an algorithm or other computer program that utilizes the sensor measurements and the current stimulation parameters and, optionally, other information regarding the patient, disease or disorder, and the like to determine adjustment to one or more of the stimulation parameters. The processing unit **104** can communicate the adjustment to a clinician or other user or to the external programming unit **106** or control module **102**.

[0063] In other embodiments, the external programming unit **106** or control module **102** receives the measurements from the sensor(s) **107** and includes an algorithm or other computer program that utilizes the sensor measurements and the current stimulation parameters and, optionally, other information regarding the patient, disease or disorder, and the like to determine adjustment to one or more of the stimulation parameters. In yet other embodiments, the sensor includes the algorithm or other computer program that determines adjustment to one or more of the stimulation parameters based on the sensor measurements.

[0064] In addition to the sensor measurements, the algorithm or computer program also receives the current stimulation parameters from, for example, the external programming unit or the control module or any other suitable source. The system can also incorporate one or more of medication information, demographics (for example, age, gender, ethnicity, height, weight, or the like), disease-specific details (for example, pain etiology(ies), number of prior back surgeries, relevant diagnoses, imaging findings, or the like) in the information used to determine adjustments to the stimulation parameters. The algorithm or computer program may determine adjustments based on patient-specific

response to previous adjustments, based on population response to previous adjustments, based on patient activity or disease/disorder status determined from the sensor measurements, or any combination thereof. In at least some embodiments, the clinician may direct the patient to perform a particular activity (for example, finger tapping, drawing a spiral or other shape, walking, or the like) and the system uses the sensor measurements during this activity to evaluate and determine adjustments to the stimulation parameters.

[0065] In at least some embodiments, the system may utilize a step-wise methodology to altering the stimulation parameters. For example, the system may alter one or more stimulation parameters based on the sensor measurements and then observe the results of the alteration as measured using the sensor (or based on other input such as patient or clinician feedback.) In at least some embodiments, the system waits for a latency period to allow the clinical effect to be measureable by the sensor. For example, for tremor response, the latency period may be less than one minute or five minutes. For blood pressure measurements, the latency period may be five or ten minutes or longer.

[0066] In some embodiments, the system may have the objective of improving or optimizing stimulation to produce a desired sensed clinical effect or may improve or co-optimize multiple sensed clinical effects or may improve or co-optimize one or more clinical effects and energy usage. Any suitable algorithmic technique can be used including, but not limited to, brute force parameter space searching, gradient search methods, genetic or simulated annealing methods, machine learning or support vector machine methods, or the like. Such general techniques for algorithms are known.

[0067] In some embodiments, the system may have one or more specific stimulation parameter sets designated for specific patient activities, disease states, or the like. When the system detects the specific patient activity (e.g., walking, running, resting, sleeping, or the like) or disease state using the sensor measurements, the system can set the stimulation parameters to the corresponding set. In some embodiments, the system may also determine a preferred set of stimulation parameters associated with patient activity, disease state, or sensor measurement value or range using the algorithmic techniques described above and may adjust the stimulation parameters to that preferred set upon detecting the patient activity, disease state, or sensor measurement value or range.

[0068] FIG. 6 is a flowchart of one embodiment of a method of adjusting stimulation parameters. In step 602, a biosignal is sensed by one or more sensors. In some embodiments, more than one biosignal can be sensed or biosignals from two or more locations on the body of the patient can be sensed.

[0069] In step 604, the biosignal is analyzed and an adjustment to one or more stimulation parameters is generated. Examples of stimulation parameters that can be adjusted include, but are not limited to, pulse frequency, pulse width, electrode field selection (anodes and cathodes which may also affect the location of stimulation), pulse amplitude, pulse burst frequency or duration, pulse patterns, other pulse timing parameters, and the like. The analysis and generation of the adjustment can be performed by the processing unit 104, external programming unit 106, control module 102, or sensor 107 or any combination thereof. The biosignal can be communicated to the processing unit 104,

external programming unit 106, control module 102, or sensor 107 or any combination thereof.

[0070] In step 606, a user (such as a clinician or patient) inputs the adjusted stimulation parameter(s) into the external programming unit 106. This process is semi-automated because it includes participation by the user. This participation may be desirable to provide user analysis of the adjusted stimulation parameters. This procedure may be useful, for example, during a control module programming session with a clinician. In such a procedure, the patient may also provide feedback regarding the adjusted stimulation.

[0071] In step 608, the external programming unit 106 transmits the adjusted stimulation parameters to the control module 102. The control module 102 then proceeds to deliver electrical stimulation using the adjusted stimulation parameters.

[0072] In step, 610, it is determined whether to repeat the process. If so, steps 602-610 are repeated. If not, the method terminates. In some embodiments, the process will automatically repeat without any formal decision to do so. In some embodiments, the process may repeat at regular or irregular intervals.

[0073] FIG. 7 is a flowchart of another embodiment of a method of adjusting stimulation parameters. In step 702, a biosignal is sensed by one or more sensors. In some embodiments, more than one biosignal can be sensed or biosignals from two or more locations on the body of the patient can be sensed.

[0074] In step 704, the biosignal is analyzed and an adjustment to one or more stimulation parameters is generated. Examples of stimulation parameters that can be adjusted include, but are not limited to, pulse frequency, pulse width, electrode field selection (anodes and cathodes which may also affect the location of stimulation), pulse amplitude, pulse burst frequency or duration, pulse patterns, other pulse timing parameters, and the like. The analysis and generation of the adjustment can be performed by the processing unit 104, external programming unit 106, control module 102, or sensor 107 or any combination thereof. The biosignal can be communicated to the processing unit 104, external programming unit 106, control module 102, or sensor 107 or any combination thereof.

[0075] In step 706, the stimulation parameter(s) are automatically adjusted at the external programming unit 106. In some embodiments, such as during a control module programming session, the external programming unit 106 may optionally display the adjusted parameters so that the clinician or patient can halt the process, if desired, or observe or direct the path of tested parameters.

[0076] In step 708, the external programming unit 106 transmits the adjusted stimulation parameters to the control module 102. The control module 102 then proceeds to deliver electrical stimulation using the adjusted stimulation parameters.

[0077] In step, 710, it is determined whether to repeat the process. If so, steps 702-710 are repeated. If not, the method terminates. In some embodiments, the process will automatically repeat without any formal decision to do so. In some embodiments, the process may repeat at regular or irregular intervals.

[0078] FIG. 8 is a flowchart of another embodiment of a method of adjusting stimulation parameters. In step 802, a biosignal is sensed by one or more sensors. In some embodi-

ments, more than one biosignal can be sensed or biosignals from two or more locations on the body of the patient can be sensed.

[0079] In step 804, the biosignal is analyzed and an adjustment to one or more stimulation parameters is generated. Examples of stimulation parameters that can be adjusted include, but are not limited to, pulse frequency, pulse width, electrode field selection (anodes and cathodes which may also affect the location of stimulation), pulse amplitude, pulse burst frequency or duration, pulse patterns, other pulse timing parameters, and the like. The analysis and generation of the adjustment can be performed by the processing unit 104, external programming unit 106, control module 102, or sensor 107 or any combination thereof. The biosignal can be communicated to the processing unit 104, external programming unit 106, control module 102, or sensor 107 or any combination thereof.

[0080] In step 806, the stimulation parameters are automatically adjusted in the control module 102. The control module 102 then proceeds to deliver electrical stimulation using the adjusted stimulation parameters. This process may be particularly useful where the control module 102 receives the measurements or the adjustment to the stimulation parameters directly from the sensor 107.

[0081] In step, 810, it is determined whether to repeat the process. If so, steps 802-810 are repeated. If not, the method terminates. In some embodiments, the process will automatically repeat without any formal decision to do so. In some embodiments, the process may repeat at regular or irregular intervals.

[0082] The processes illustrated in FIGS. 6-8 can be used as a feedback loop to adjust stimulation parameters. The feedback loop may be part of a programming session. Alternatively or additionally, the electrical stimulation system may initiate the feedback loop on a regular or irregular basis or when requested by a user, clinician, or other individual to adjust stimulation parameters.

[0083] It will be understood that the system can include one or more of the methods described hereinabove with respect to FIGS. 6-8 in any combination. The methods, systems, and units described herein may be embodied in many different forms and should not be construed as limited to the embodiments set forth herein. Accordingly, the methods, systems, and units described herein may take the form of an entirely hardware embodiment, an entirely software embodiment or an embodiment combining software and hardware aspects. The methods described herein can be performed using any type of processor or any combination of processors where each processor performs at least part of the process.

[0084] It will be understood that each block of the flowchart illustrations, and combinations of blocks in the flowchart illustrations and methods disclosed herein, can be implemented by computer program instructions. These program instructions may be provided to a processor to produce a machine, such that the instructions, which execute on the processor, create means for implementing the actions specified in the flowchart block or blocks or described for the control modules, external programming units, sensors, systems and methods disclosed herein. The computer program instructions may be executed by a processor to cause a series of operational steps to be performed by the processor to produce a computer implemented process. The computer program instructions may also cause at least some of the

operational steps to be performed in parallel. Moreover, some of the steps may also be performed across more than one processor, such as might arise in a multi-processor computer system. In addition, one or more processes may also be performed concurrently with other processes, or even in a different sequence than illustrated without departing from the scope or spirit of the invention.

[0085] The computer program instructions can be stored on any suitable computer-readable medium including, but not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks ("DVD") or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by a computing device.

[0086] FIG. 9 illustrates one embodiment of a control module 402 and lead 403. The lead 403 includes a paddle body 444 and one or more lead bodies 446. In FIG. 9, the lead 403 is shown having two lead bodies 446. It will be understood that the lead 403 can include any suitable number of lead bodies including, for example, one, two, three, four, five, six, seven, eight or more lead bodies 446. An array of electrodes 433, such as electrode 434, is disposed on the paddle body 444, and one or more terminals (e.g., 560 in FIG. 11A and 11B) are disposed along each of the one or more lead bodies 446. In at least some embodiments, the lead has more electrodes than terminals.

[0087] FIG. 10 illustrates schematically another embodiment in which the lead 403 is a percutaneous lead. In FIG. 10, the electrodes 434 are shown disposed along the one or more lead bodies 446. In at least some embodiments, the lead 403 is isodiametric along a longitudinal length of the lead body 446.

[0088] The lead 403 can be coupled to the implantable control module 402 in any suitable manner. In FIG. 9, the lead 403 is shown coupling directly to the implantable control module 402. In at least some other embodiments, the lead 403 couples to the implantable control module 402 via one or more intermediate devices (500 in FIGS. 11A and 11B). For example, in at least some embodiments one or more lead extensions 524 (see e.g., FIG. 11B) can be disposed between the lead 403 and the implantable control module 402 to extend the distance between the lead 403 and the implantable control module 402. Other intermediate devices may be used in addition to, or in lieu of, one or more lead extensions including, for example, a splitter, an adaptor, or the like or combinations thereof. It will be understood that, in the case where the electrical stimulation system includes multiple elongated devices disposed between the lead 403 and the implantable control module 402, the intermediate devices may be configured into any suitable arrangement.

[0089] In FIG. 10, the electrical stimulation system 400 is shown having a splitter 457 configured and arranged for facilitating coupling of the lead 403 to the implantable control module 402. The splitter 457 includes a splitter connector 458 configured to couple to a proximal end of the lead 403, and one or more splitter tails 459a and 459b configured and arranged to couple to the implantable control module 402 (or another splitter, a lead extension, an adaptor, or the like).

[0090] The implantable control module 402 includes a connector housing 448 and a sealed electronics housing 450.

An electronic subassembly **452** (which includes the processor **110** (see, FIGS. 1-3) and the power source **414** are disposed in the electronics housing **450**. A connector **445** is disposed in the connector housing **448**. The connector **445** is configured and arranged to make an electrical connection between the lead **403** and the electronic subassembly **452** of the implantable control module **402**.

[0091] The electrical stimulation system or components of the electrical stimulation system, including the paddle body **444**, the one or more of the lead bodies **446**, and the implantable control module **402**, are typically implanted into the body of a patient. The electrical stimulation system can be used for a variety of applications including, but not limited to deep brain stimulation, neural stimulation, spinal cord stimulation, muscle stimulation, and the like.

[0092] The electrodes **434** can be formed using any conductive, biocompatible material. Examples of suitable materials include metals, alloys, conductive polymers, conductive carbon, and the like, as well as combinations thereof. In at least some embodiments, one or more of the electrodes **434** are formed from one or more of: platinum, platinum iridium, palladium, palladium rhodium, or titanium.

[0093] Any suitable number of electrodes **434** can be disposed on the lead including, for example, four, five, six, seven, eight, nine, ten, eleven, twelve, fourteen, sixteen, twenty-four, thirty-two, or more electrodes **434**. In the case of paddle leads, the electrodes **434** can be disposed on the paddle body **444** in any suitable arrangement. In FIG. 9, the electrodes **434** are arranged into two columns, where each column has eight electrodes **434**.

[0094] The electrodes of the paddle body **444** (or one or more lead bodies **446**) are typically disposed in, or separated by, a non-conductive, biocompatible material such as, for example, silicone, polyurethane, polyetheretherketone ("PEEK"), epoxy, and the like or combinations thereof. The one or more lead bodies **446** and, if applicable, the paddle body **444** may be formed in the desired shape by any process including, for example, molding (including injection molding), casting, and the like. The non-conductive material typically extends from the distal ends of the one or more lead bodies **446** to the proximal end of each of the one or more lead bodies **446**.

[0095] In the case of paddle leads, the non-conductive material typically extends from the paddle body **444** to the proximal end of each of the one or more lead bodies **446**. Additionally, the non-conductive, biocompatible material of the paddle body **444** and the one or more lead bodies **446** may be the same or different. Moreover, the paddle body **444** and the one or more lead bodies **446** may be a unitary structure or can be formed as two separate structures that are permanently or detachably coupled together.

[0096] One or more terminals (e.g., **560** in FIGS. 11A-11B) are typically disposed along the proximal end of the one or more lead bodies **446** of the electrical stimulation system **400** (as well as any splitters, lead extensions, adaptors, or the like) for electrical connection to corresponding connector contacts (e.g., **564** in FIGS. 11A-11B). The connector contacts are disposed in connectors (e.g., **445** in FIGS. 9-11B; and **572** FIG. 11B) which, in turn, are disposed on, for example, the implantable control module **402** (or a lead extension, a splitter, an adaptor, or the like). One or more electrically conductive wires, cables, or the like (i.e., "conductors"—not shown) extend from the terminal(s) to the electrode(s). In at least some embodiments, there is at

least one (or exactly one) terminal conductor for each terminal which extends to at least one (or exactly one) of the electrodes.

[0097] The one or more conductors are embedded in the non-conductive material of the lead body **446** or can be disposed in one or more lumens (not shown) extending along the lead body **446**. For example, any of the conductors may extend distally along the lead body **446** from the terminals **560**.

[0098] FIG. 11A is a schematic side view of one embodiment of a proximal end of one or more elongated devices **500** configured and arranged for coupling to one embodiment of the connector **445**. The one or more elongated devices may include, for example, one or more of the lead bodies **446** of FIG. 9, one or more intermediate devices (e.g., a splitter, the lead extension **524** of FIG. 11B, an adaptor, or the like or combinations thereof), or a combination thereof.

[0099] The connector **445** defines at least one port into which a proximal ends **446A**, **446B** of the elongated device **500** can be inserted, as shown by directional arrows **562a**, **562b**. In FIG. 11A (and in other figures), the connector housing **448** is shown having two ports **554a**, **554b**. The connector housing **448** can define any suitable number of ports including, for example, one, two, three, four, five, six, seven, eight, or more ports.

[0100] The connector **445** also includes one or more connector contacts, such as connector contact **564**, disposed within each port **554a**, **554b**. When the elongated device **500** is inserted into the ports **554a**, **554b**, the connector contact (s) **564** can be aligned with the terminal(s) **560** disposed along the proximal end(s) of the elongated device(s) **500** to electrically couple the implantable control module **402** to the electrodes (**434** of FIG. 9) disposed on the paddle body **445** of the lead **403**. Examples of connectors in implantable control modules are found in, for example, U.S. Pat. Nos. 7,244,150 and 8,224,450, which are incorporated by reference.

[0101] FIG. 11B is a schematic side view of another embodiment that includes a lead extension **524** that is configured and arranged to couple one or more elongated devices **500** (e.g., one of the lead bodies **446** of FIGS. 9 and 10, the splitter **457** of FIG. 10, an adaptor, another lead extension, or the like or combinations thereof) to the implantable control module **402**. In FIG. 11B, the lead extension **524** is shown coupled to a single port **554** defined in the connector **445**. Additionally, the lead extension **524** is shown configured and arranged to couple to a single elongated device **500**. In alternate embodiments, the lead extension **524** is configured and arranged to couple to multiple ports **554** defined in the connector **445**, or to receive multiple elongated devices **500**, or both.

[0102] A lead extension connector **572** is disposed on the lead extension **524**. In FIG. 11B, the lead extension connector **572** is shown disposed at a distal end **576** of the lead extension **524**. The lead extension connector **572** includes a connector housing **578**. The connector housing **578** defines at least one port **530** into which terminal(s) **560** of the elongated device **500** can be inserted, as shown by directional arrow **538**. The connector housing **578** also includes a plurality of connector contacts, such as connector contact **580**. When the elongated device **500** is inserted into the port **530**, the connector contacts **580** disposed in the connector housing **578** can be aligned with the terminal(s) **560** of the elongated device **500** to electrically couple the lead exten-

sion 524 to the electrodes (434 of FIGS. 9 and 10) disposed along the lead (403 in FIGS. 9 and 10).

[0103] In at least some embodiments, the proximal end of the lead extension 524 is similarly configured and arranged as a proximal end of the lead 403 (or other elongated device 500). The lead extension 524 may include one or more electrically conductive wires (not shown) that electrically couple the connector contact(s) 580 to a proximal end 548 of the lead extension 524 that is opposite to the distal end 576. The conductive wire(s) disposed in the lead extension 524 can be electrically coupled to one or more terminals (not shown) disposed along the proximal end 548 of the lead extension 524. The proximal end 548 of the lead extension 524 is configured and arranged for insertion into a connector disposed in another lead extension (or another intermediate device). As shown in FIG. 11B, the proximal end 548 of the lead extension 524 is configured and arranged for insertion into the connector 445.

[0104] The embodiments of FIGS. 9-11B illustrate a control module 402 with a connector 445 into which a proximal end portion of the lead or lead extension can be removably inserted. It will be recognized, however, that other embodiments of a control module and lead can have the lead or lead extension permanently attached to the control module. Such an arrangement can reduce the size of the control module as the conductors in the lead can be permanently attached to the electronic subassembly. It will also be recognized that, in at least some embodiments, more than one lead can be attached to a control module.

[0105] The above specification and examples provide a description of the manufacture and use of the invention. Since many embodiments of the invention can be made without departing from the spirit and scope of the invention, the invention also resides in the claims hereinafter appended.

What is claimed as new and desired to be protected by Letters Patent of the United States is:

1. An electrical stimulation system, comprising:
 - an implantable control module configured for implantation in a body of a patient and comprising an antenna and a processor coupled to the antenna, wherein the implantable control module is configured to provide electrical stimulation signals to an electrical stimulation lead coupled to the implantable control module for stimulation of patient tissue;
 - an external programming unit configured to communicate with the processor of the implantable control module using the antenna and to provide or update stimulation parameters for production of the electrical stimulation signals;
 - a sensor configured to be disposed on or within the body of the patient and to measure a biosignal; and
 - a biosignal processor configured to communicate with the sensor to receive the biosignal and to generate an adjustment to one or more of the stimulation parameters based on the biosignal, wherein the adjustment is configured to steer the electrical stimulation signals to stimulate a region of the patient tissue that is different, at least in part, from a region of the patient tissue stimulated prior to the adjustment.
2. The electrical stimulation system of claim 1, wherein the external programming unit comprises the biosignal processor.
3. The electrical stimulation system of claim 1, wherein the biosignal processor is configured for communication with the external programming unit to deliver the adjustment to the external programming unit.
4. The electrical stimulation system of claim 1, wherein the biosignal processor is configured to deliver the adjustment to at least one of the external programming unit or the control module.
5. The electrical stimulation system of claim 1, further comprising a lead coupleable to the control module and comprising a plurality of electrodes for delivering the electrical stimulation signals to the patient tissue.
6. The electrical stimulation system of claim 5, wherein the sensor is disposed on the lead.
7. The electrical stimulation system of claim 1, wherein the sensor is disposed on the control module.
8. The electrical stimulation system of claim 1, wherein the adjustment is provided to the control module automatically and without user intervention.
9. The electrical stimulation system of claim 1, wherein the biosignal processor is configured so that when the biosignal is indicative of a particular patient activity, the adjustment is a pre-determined adjustment selected for the particular patient activity.
10. The electrical stimulation system of claim 1, wherein the biosignal processor is configured so that when the biosignal is indicative of a disease or disorder status, the adjustment is followed by the biosignal processor waiting for a predetermined latency period after which the biosignal processor is configured to communicate with the sensor to observe a result of the adjustment using the biosignal and determine whether to provide a further adjustment of the stimulation parameters to improve the stimulation.
11. The electrical stimulation system of claim 10, wherein, subsequent to the predetermined latency period, the biosignal processor directs the patient to perform a pre-determined activity.
12. The electrical stimulation system of claim 1, wherein the biosignal processor is configured to generate the adjustment based, at least in part, on medication information.
13. The electrical stimulation system of claim 1, wherein the sensor comprises a global positioning sensor.
14. An electrical stimulation system, comprising:
 - a sensor configured to be disposed on or within the body of the patient and to measure a biosignal; and
 - a control module comprising a processor, wherein the control module is configured to use stimulation parameters to provide electrical stimulation signals to an electrical stimulation lead coupled to the control module for stimulation of patient tissue, wherein the processor is configured to communicate with the sensor to receive the biosignal and to generate an adjustment to one or more of the stimulation parameters based on the biosignal, wherein the adjustment is configured to steer the electrical stimulation signals to stimulate a region of the patient tissue that is different, at least in part, from a region of the patient tissue stimulated prior to the adjustment.
15. The electrical stimulation system of claim 14, wherein the control module is an implantable control module configured and arranged for implantation in a body of a patient, the implantable control module further comprising an antenna coupled to the processor.

16. The electrical stimulation system of claim **14**, further comprising a lead coupleable to the control module and comprising a plurality of electrodes for delivering the electrical stimulation signals to the patient tissue.

17. The electrical stimulation system of claim **16**, wherein the sensor is disposed on the lead.

18. The electrical stimulation system of claim **14**, wherein the sensor is disposed on the control module.

19. The electrical stimulation system of claim **14**, wherein the processor is configured so that when the biosignal is indicative of a particular patient activity, the adjustment is a pre-determined adjustment selected for the particular patient activity.

20. The electrical stimulation system of claim **14**, wherein the processor is configured so that when the biosignal is indicative of a disease or disorder status, the adjustment is followed by the processor waiting for a predetermined latency period after which the processor is configured to communicate with the sensor to observe a result of the adjustment using the biosignal and determine whether to provide a further adjustment of the stimulation parameters to improve the stimulation.

* * * * *