

SESSION – 2

```
koumudi@Koumudi:~/OSSP/PRACTICAL/Session_1$ cd ~/OSSP/PRACTICAL/Session_2
koumudi@Koumudi:~/OSSP/PRACTICAL/Session_2$ pwd
/home/koumudi/OSSP/PRACTICAL/Session_2
koumudi@Koumudi:~/OSSP/PRACTICAL/Session_2$ nano file_copy.c
koumudi@Koumudi:~/OSSP/PRACTICAL/Session_2$ echo "This is a sample file for Practical Session 2." > source.txt
koumudi@Koumudi:~/OSSP/PRACTICAL/Session_2$ cat source.txt
This is a sample file for Practical Session 2.
koumudi@Koumudi:~/OSSP/PRACTICAL/Session_2$ gcc file_copy.c -o file_copy
koumudi@Koumudi:~/OSSP/PRACTICAL/Session_2$ ./file_copy
File copied successfully.
koumudi@Koumudi:~/OSSP/PRACTICAL/Session_2$ cat destination.txt
This is a sample file for Practical Session 2.
koumudi@Koumudi:~/OSSP/PRACTICAL/Session_2$ |
```

```
koumudi@Koumudi: ~/OSSP/   
This is a sample file for Practical Session 2.
koumudi@Koumudi:~/OSSP/PRACTICAL/Session_2$ echo "This is a sample file for strace." > sample.txt
koumudi@Koumudi:~/OSSP/PRACTICAL/Session_2$ cat sample.txt
This is a sample file for strace.
koumudi@Koumudi:~/OSSP/PRACTICAL/Session_2$ strace cat sample.txt
execve("/usr/bin/cat", ["cat", "sample.txt"], 0x7ffc155c7398 /* 26 vars */) = 0
brk(NULL) = 0x57c539392000
mmap(NULL, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) = 0x7e087db97000
access("/etc/ld.so.preload", R_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/etc/ld.so.cache", O_RDONLY|O_CLOEXEC) = 3
fstat(3, {st_mode=S_IFREG|0644, st_size=19007, ...}) = 0
mmap(NULL, 19007, PROT_READ, MAP_PRIVATE, 3, 0) = 0x7e087db92000
close(3) = 0
openat(AT_FDCWD, "/lib/x86_64-linux-gnu/libc.so.6", O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\3\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\220\243\2\0\0\0\0"..., 832) = 832
pread64(3, "\6\0\0\0\4\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"..., 784, 64) = 784
fstat(3, {st_mode=S_IFREG|0755, st_size=2125328, ...}) = 0
pread64(3, "\6\0\0\0\4\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0"..., 784, 64) = 784
mmap(NULL, 2170256, PROT_READ, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) = 0x7e087d800000
mmap(0x7e087d828000, 1605632, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x28000) = 0x7e087d828000
mmap(0x7e087d9b0000, 323584, PROT_READ, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1b0000) = 0x7e087d9b0000
mmap(0x7e087d9ff000, 24576, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1fe000) = 0x7e087d9ff000
mmap(0x7e087da05000, 52624, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x7e087da05000
close(3) = 0
mmap(NULL, 12288, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) = 0x7e087db8f000
arch_prctl(ARCH_SET_FS, 0x7e087db8f740) = 0
set_tid_address(0x7e087db8fa10) = 1406
set_robust_list(0x7e087db8fa20, 24) = 0
rseq(0x7e087db90060, 0x20, 0, 0x53053053) = 0
mprotect(0x7e087d9ff000, 16384, PROT_READ) = 0
mprotect(0x57c514ae6000, 4096, PROT_READ) = 0
mprotect(0x7e087dbd7000, 8192, PROT_READ) = 0
```

```

koumudi@Koumudi: ~/OSSP/ × + ∨
close(3) = 0
openat(AT_FDCWD, "/usr/lib/locale/C.UTF-8/LC_MESSAGES", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/locale/C.utf8/LC_MESSAGES", O_RDONLY|O_CLOEXEC) = 3
fstat(3, {st_mode=S_IFDIR|0755, st_size=4096, ...}) = 0
close(3) = 0
openat(AT_FDCWD, "/usr/lib/locale/C.utf8/LC_MESSAGES/SYS_LC_MESSAGES", O_RDONLY|O_CLOEXEC) = 3
fstat(3, {st_mode=S_IFREG|0644, st_size=48, ...}) = 0
mmap(NULL, 48, PROT_READ, MAP_PRIVATE, 3, 0) = 0x7e087db86000
close(3) = 0
openat(AT_FDCWD, "/usr/lib/locale/C.UTF-8/LC_MONETARY", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/locale/C.utf8/LC_MONETARY", O_RDONLY|O_CLOEXEC) = 3
fstat(3, {st_mode=S_IFREG|0644, st_size=270, ...}) = 0
mmap(NULL, 270, PROT_READ, MAP_PRIVATE, 3, 0) = 0x7e087db85000
close(3) = 0
openat(AT_FDCWD, "/usr/lib/locale/C.UTF-8/LC_COLLATE", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/locale/C.utf8/LC_COLLATE", O_RDONLY|O_CLOEXEC) = 3
fstat(3, {st_mode=S_IFREG|0644, st_size=1406, ...}) = 0
mmap(NULL, 1406, PROT_READ, MAP_PRIVATE, 3, 0) = 0x7e087db84000
close(3) = 0
openat(AT_FDCWD, "/usr/lib/locale/C.UTF-8/LC_TIME", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/locale/C.utf8/LC_TIME", O_RDONLY|O_CLOEXEC) = 3
fstat(3, {st_mode=S_IFREG|0644, st_size=3360, ...}) = 0
mmap(NULL, 3360, PROT_READ, MAP_PRIVATE, 3, 0) = 0x7e087db83000
close(3) = 0
openat(AT_FDCWD, "/usr/lib/locale/C.UTF-8/LC_NUMERIC", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/locale/C.utf8/LC_NUMERIC", O_RDONLY|O_CLOEXEC) = 3
fstat(3, {st_mode=S_IFREG|0644, st_size=50, ...}) = 0
mmap(NULL, 50, PROT_READ, MAP_PRIVATE, 3, 0) = 0x7e087db82000
close(3) = 0
openat(AT_FDCWD, "/usr/lib/locale/C.UTF-8/LC_CTYPE", O_RDONLY|O_CLOEXEC) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/usr/lib/locale/C.utf8/LC_CTYPE", O_RDONLY|O_CLOEXEC) = 3
fstat(3, {st_mode=S_IFREG|0644, st_size=360460, ...}) = 0
mmap(NULL, 360460, PROT_READ, MAP_PRIVATE, 3, 0) = 0x7e087db29000
close(3) = 0
fstat(1, {st_mode=S_IFCHR|0620, st_rdev=makedev(0x88, 0), ...}) = 0
openat(AT_FDCWD, "sample.txt", O_RDONLY) = 3
fstat(3, {st_mode=S_IFREG|0644, st_size=34, ...}) = 0
fadvise64(3, 0, 0, POSIX_FADV_SEQUENTIAL) = 0
mmap(NULL, 139264, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) = 0x7e087db07000
read(3, "This is a sample file for strace"... , 131072) = 34
write(1, "This is a sample file for strace"... , 34This is a sample file for strace.
) = 34
read(3, "", 131072) = 0
munmap(0x7e087db07000, 139264) = 0
close(3) = 0
close(1) = 0
close(2) = 0
exit_group(0) = ?
+++ exited with 0 +++

```