Validating Data for a Linguistic Resource

Error analysis, agreement, and giving back

Francis **Bond**

Computational Linguistics Lab

Palacký University, Olomouc, Czechia

JPC3 — Improving the Czech Wordnet

November 3, 2026

Faculty of Arts

Overview

- Why be sure about the data
- Error analysis: beyond one number
- Why two annotators
- Cohen's κ, worked through
- Giving fixes back to ARASAAC, Wikidata, …

Roadmap

1. Why be sure?
2. The new bottleneck
3. Building an explainer
4. Error analysis
5. Agreement
6. Cohen's kappa
7. Giving back

Faculty of Arts

Why be sure?

- A wordnet is a **trusted source**
- Many tools read it; few check it
- An error you add, everyone inherits
  - e.g. a wrong hypernym copied into every OMW language
- Once released, it is copied, and hard to recall
- The Czech wordnet feeds OMW, sense tagging, AAC, …

The cost of one wrong link

- Project 4 links pictographs for **AAC** users
- A wrong synset tag $\rightarrow$ the wrong picture
- A child who cannot speak is handed the wrong word

Roadmap

1. Why be sure?
2. The new bottleneck
3. Building an explainer
4. Error analysis
5. Agreement
6. Cohen's kappa
7. Giving back

Understanding Is the Bottleneck

- The starter code generates candidates in seconds
  - feminine candidates for all 1,919 role-noun synsets at once
- Machines already verify themselves well
- The slow part is **understanding** what came out
- “Cognitive debt”: skip it and you lose the plot
- Generation got cheap; understanding did not (Litt, 2026)

https://www.geoffreylitt.com/2026/07/02/understanding-is-the-new-bottleneck.html

Faculty of Arts

Staying in the Loop

Three ways to keep understanding ahead of the machine:

- Explain before you trust: write what the data *says*
- Plot it: a chart shows the outliers a table hides
- **Spot-check** a sample before trusting the whole
  - judge 20 by hand before you generate 2,000

Look at Your Data as You Go

- Check the output at every step of the work
- Dump it in a **viewable format**: TOML, CSV, a plot
- A wrong turn caught early is cheap to undo
- A literate program shows its output inline, by habit

"Actually look at your data!"

Explainers as Literate Programming

- Knuth (1984): write code for **humans** to read
- Prose and code woven together, explanation first
- Litt's explainer is the same idea, authorship flipped
- The agent writes the code; you write the understanding
- Your report is the literate layer over the scripts

Revived for LLMs: "Natural Language Outlines" (2024), "Verifiable Literate Programming" for validating generated code (2026)

Roadmap

1. Why be sure?
2. The new bottleneck
3. Building an explainer
4. Error analysis
5. Agreement
6. Cohen's kappa
7. Giving back

Faculty of Arts

An Explainer, From the Code

- Generate an HTML explainer **from** the finished script
- Four parts: background, intuition, a code tour, a quiz
- One self-contained page, one link to share
- The script stays a normal file, with nothing to keep in sync
- Both starter scripts now have one, on the course site

Build It Interactively

- React to a draft; each reply refines the same page
- The link stays stable, so you share it once
- Keep every version in the repo: `v0` to `v4`
- The actual prompts behind this explainer:
  - `v0`: “build an explainer for this script”
  - `v1`: “where do the ILI mappings come from? add a SPARQL appendix”
  - `v2`: “add a glossary”
  - `v3`: “add caveats: it is AI-generated and can be wrong”
  - `v4`: “hyperlink the key terms; stamp the provenance”

Make It Repeatable

The same **recipe** works for any project script:

- Point at a script: ask for background, intuition, code, quiz
- Read it, then ask for the next fix
- Keep each version; link the latest

Packaged as the `code-explainer` skill in the repo

Guarding an Explainer

It is AI-generated, so treat it like any other data:

- A visible caveat on the page: it can be wrong, so check the code
- `explainer_check.py`: identifiers, line refs, and links against the source
  - on ours it found nothing wrong, and one unreachable link
- A **provenance** stamp: date, model, source commit
- A second reader, human or model, checks the prose

Faculty of Arts

Roadmap

1. Why be sure?
2. The new bottleneck
3. Building an explainer
4. Error analysis
5. Agreement
6. Cohen's kappa
7. Giving back

Faculty of Arts

Error Analysis

- Take a **random** sample (aim for 200)
- Judge each by hand: right or wrong?
- Precision = correct / judged
- But the single number is the least of it
- Group the mistakes into **types**: that is the payoff
- One real example per type, with a count

Running example: přechylování

Candidate: add a feminine form to a role-noun synset.

(1) Czech [ces]
učitel → *učitel-ka*
teacher.M teacher-F
“(male) teacher → (female) teacher”

- 1,919 role-noun synsets to work from (`noun.person`)
- Easy to generate; the question is which are **right**

Faculty of Arts

An Error Taxonomy

A sample of 200 generated feminine candidates:

Error type	Count	Example
Correct	171	*lékař* → *lékařka*
Coincidental suffix	12	*past* (not a base + *-ka*)
Wrong sense	9	feminine of a non-personal reading
Already present	8	lemma was in the synset

Precision 0.86 — but the four rows tell the next team where to look

Faculty of Arts

Roadmap

1. Why be sure?
2. The new bottleneck
3. Building an explainer
4. Error analysis
5. Agreement
6. Cohen's kappa
7. Giving back

Faculty of Arts

Why Two Annotators?

- One judge can be **consistently** wrong
  - e.g. always accepting a coincidental *-ka* (*past*→ *pastka*)
- A second judge tests whether the scheme is learnable
- Agreement ≈ reliability of the guidelines
- You work in pairs, so measure it
- Report how you resolved the disagreements

Raw Agreement Overcounts

- “We agreed 85% of the time” sounds good
- But some agreement happens by **chance**
- Two coin-flippers agree half the time
- If almost everything is “correct”, agreeing is easy
- Correct for chance $\rightarrow$ Cohen’s κ

Roadmap

1. Why be sure?
2. The new bottleneck
3. Building an explainer
4. Error analysis
5. Agreement
6. Cohen's kappa
7. Giving back

Faculty of Arts

Cohen's Kappa

Agreement above what chance would give:

$$\kappa = \frac{p_o - p_e}{1 - p_e}$$

- p_o: observed agreement (the proportion you both called the same)
- p_e: expected agreement **by chance**, from each annotator's rates
  - if you both say "good" 90% of the time, chance agreement is high
- $\kappa = 1$ perfect; $\kappa = 0$ no better than chance

A Worked Example

200 candidates, two annotators, good vs. bad:

	B: good	B: bad	total
A: good	130	20	150
A: bad	10	40	50
total	140	60	200

- $p_o = (130 + 40)/200 = 0.85$
- $p_e = 0.75 \times 0.70 + 0.25 \times 0.30 = 0.60$

$$\kappa = \frac{0.85 - 0.60}{1 - 0.60} = \mathbf{0.63}$$

Reading Kappa

- Rough scale (Landis & Koch, 1977): > 0.8 very good, 0.6–0.8 substantial
- Our 0.63 is **substantial**: the guidelines mostly work
- Low κ? Fix the guidelines, then re-annotate
- Beware: few categories or a skewed split inflate it
- Report κ together with the raw table

Roadmap

1. Why be sure?
2. The new bottleneck
3. Building an explainer
4. Error analysis
5. Agreement
6. Cohen's kappa
7. Giving back

Faculty of Arts

Why Open? — Not Just the Warm Inner Glow

- Our goal: a better Czech wordnet, *and* a **contribution**
- Open data others can build on
- Your fixes reach every downstream user
- A result that outlives the course

Feedback Upstream

Every error you find is a **gift** to the source.

- ARASAAC: report wrong synset tags; send Czech keywords back
- Wikidata: add or fix the ILI (P5063) and WordNet id (P8814)
- Global Symbols / ARAWN: contribute the matches you validated
- CILI: report synsets with no ILI; DeriNet: report gaps
- PDT: the unmapped residue is data for the maintainers

Give Back: ARASAAC

Project 4 — pictographs for AAC.

- Found a **wrong** synset tag? Report it to ARASAAC
- Missing Czech keyword? Submit the translation
- Note colour and gender variants you matched
  - e.g. the generated xkcd swatch for *chestnut*
- Their pictograms carry synsets, so a fix helps every language

Give Back: Wikidata

Project 5 — Wikidata → ILI → Czech.

- Only a WordNet id (P8814)? Add the **ILI** (P5063)
- Linked to the wrong sense? Correct the statement
- Confirmed a Czech label? Add it, with a reference
  - e.g. add *Nizozemsko* to the *Holandsko* synset
- Cite the wordnet as the source: statements need one

Give Back: PDT and CILI

Project 3 — the sense-tag residue.

- The **unmapped** tags are a bug list for the maintainers
- Split or merged senses? Propose the current synset
- Share your 1.5 → current mapping table
- New concept with no ILI? Ask CILI to mint one

Give Back: DeriNet

Project 2 — derivational relations.

- Validated feminine-motion pairs? Offer them back
  - e.g. *učitel*→ *učitelka*
- A family the wordnet **lacks**? Flag the gap
- A DeriNet error you caught? Report it
- Both resources improve from the same checking

The Virtuous Cycle

- Open data gets better only when fixes **flow back**
- A pull request or an issue beats a private fix
- Cite what you used; credit who made it
- Release under an open licence, loadable with `wn`
- Next year's class starts from your cleaner data

Every new wordnet makes the network richer

Conclusion

- Extraction is scaffolded: **validation** is the work
- Sample, judge, and report precision
- Categorise the errors; the taxonomy guides the next step
- Two annotators, and κ with the table
- Push every fix back upstream

Thanks

- Validate carefully: others will trust your data
- Actually look at your data!
- Code and template: the JPC3 repository

Questions welcome — and so are pull requests

References I

- Cohen, J. (1960). A coefficient of agreement for nominal scales. *Educational and Psychological Measurement* 20(1), 37–46.
- Landis, J. R. & Koch, G. G. (1977). The measurement of observer agreement for categorical data. *Biometrics* 33(1), 159–174.
- Artstein, R. & Poesio, M. (2008). Inter-coder agreement for computational linguistics. *Computational Linguistics* 34(4), 555–596.
- Litt, G. (2026). Understanding is the new bottleneck. https://www.geoffreylitt.com/2026/07/02/understanding-is-the-new-bottleneck.html
- Knuth, D. E. (1984). Literate programming. *The Computer Journal* 27(2), 97–111.
- Shi, K. et al. (2024). Natural Language Outlines for Code: Literate Programming in the LLM Era. FSE'25 Industry Track. https://arxiv.org/abs/2408.04820
- Yuan, Z. et al. (2026). Guiding Human Validation of LLM-Generated Code via Verifiable Literate Programming. https://arxiv.org/abs/2607.02333

Faculty of Arts