

# 1 Object Language

## 1.1 Raw Terms

The untyped syntax for CBPV OSum, add separating connectives, remove error.

Add  $\forall X. \underline{B}$  ?

|                   |                 |       |   |
|-------------------|-----------------|-------|---|
| Value Types       | $A$             | $::=$ | $X$<br>$\text{Unit}$<br>$\text{Case } A$<br>$\text{OSum}$<br>$A \times A$<br>$A * A$<br>$\exists X. A$<br>$U \underline{B}$   |
| Computation Types | $\underline{B}$ | $::=$ | $A \rightarrow \underline{B}$<br>$A \multimap \underline{B}$<br>$\forall X. \underline{B}$<br>$FA$  |
| Values            | $V$             | $::=$ | $x$<br>$tt$<br>$\sigma$<br>$\text{inj}_V V$<br>$(V, V)$<br>$(V * V)$<br>$\text{pack } (A, V) \text{ as } \exists X. A$<br>$\text{thunk } M$   |
| Computations      | $M$             | $::=$ | $\lambda x: A. M$<br>$MV$<br>$\alpha x: A. M$<br>$M @ V$<br>$\Lambda X. M$<br>$M[A]$<br>$\text{ret } V$<br>$x \leftarrow M; N$<br>$\text{force } V$<br>$\text{newcase}_A x; M$<br>$\text{match } V \text{ with } V \{ \text{inj } x. M \parallel N \}$<br>$\text{let } (x, x) = V; M$<br>$\text{let } (x * x) = V; M$<br>$\text{unpack } (X, x) = V; M$ |
| Value Context     | $\Gamma$        | $::=$ | $\cdot$<br>$\Gamma, x: A$<br>$\Gamma * x: A$  |
| Type Context      | $\Xi$           | $::=$ | $\cdot$<br>$\Xi, X$   |

## 1.2 Typed Terms

$$\begin{array}{c}
\frac{}{\Xi; \Gamma, x : A \vdash_v x : A} \\
\\
\frac{}{\Xi; \Gamma * x : A \vdash_v x : A} \\
\\
\frac{}{\Xi; \Gamma \vdash_v \text{tt} : \text{Unit}} \\
\\
\frac{\Xi; \Gamma \vdash_v \sigma : \text{Case}A \quad \Xi; \Gamma \vdash_v V : A}{\Xi; \Gamma \vdash_v \text{inj}_\sigma V : \text{OSum}} \\
\\
\frac{\Xi; \Gamma \vdash_v V_1 : A_1 \quad \Xi; \Gamma \vdash_v V_2 : A_2}{\Xi; \Gamma \vdash_v (V_1, V_2) : A_1 \times A_2} \\
\\
\frac{\Xi; \Gamma_1 \vdash_v V_1 : A_1 \quad \Xi; \Gamma_2 \vdash_v V_2 : A_2}{\Xi; \Gamma_1 * \Gamma_2 \vdash_v (V_1 * V_2) : A_1 * A_2} \\
\\
\frac{\Xi; \Gamma \vdash_v V : A[A'/X]}{\Xi; \Gamma \vdash_v \text{pack}(A', V) \text{ as } \exists X.A : \exists X.A} \\
\\
\frac{\Xi; \Gamma \vdash_c M : \underline{B}}{\Xi; \Gamma \vdash_v \text{thunk } M : U\underline{B}} \\
\\
\frac{\Xi; \Gamma, x : A \vdash_c M : \underline{B}}{\Xi; \Gamma \vdash_c \lambda x : A. M : A \rightarrow \underline{B}} \\
\\
\frac{\Xi; \Gamma \vdash_c M : A \rightarrow \underline{B} \quad \Xi; \Gamma \vdash_v N : A}{\Xi; \Gamma \vdash_c MN : \underline{B}} \\
\\
\frac{\Xi; \Gamma * x : A \vdash_c M : \underline{B}}{\Xi; \Gamma \vdash_c \alpha x : A. M : A \multimap \underline{B}} \\
\\
\frac{\Xi; \Gamma_1 \vdash_c M : A \multimap \underline{B} \quad \Xi; \Gamma_2 \vdash_v N : A}{\Xi; \Gamma_1 * \Gamma_2 \vdash_c M @ N : \underline{B}} \\
\\
\frac{\Xi, X; \Gamma \vdash_c M : \underline{B}}{\Xi; \Gamma \vdash_c \Lambda X. M : \forall X. \underline{B}} \\
\\
\frac{\Xi; \Gamma \vdash_c M : \forall X. \underline{B} \quad \Xi \vdash A}{\Xi; \Gamma \vdash_c M[A] : \underline{B}[A/X]} \\
\\
\frac{\Xi; \Gamma \vdash_v V : A}{\Xi; \Gamma \vdash_c \text{ret } V : FA}
\end{array}$$

$$\begin{array}{c}
\frac{\Xi; \Gamma \vdash_c M : FA \quad \Xi; \Gamma, x : A \vdash_c N : \underline{B}}{\Xi; \Gamma \vdash_c x \leftarrow M; N : \underline{B}} \\
\\
\frac{\Xi; \Gamma \vdash_v V : U\underline{B}}{\Xi; \Gamma \vdash_c \text{force } V : \underline{B}} \\
\\
\frac{\Xi; \Gamma * (\sigma : \text{Case}A) \vdash_c M : \underline{B} \quad \Xi \vdash A}{\Xi; \Gamma \vdash_c \text{newcase}_A x; M : \underline{B}} \\
\\
\frac{\Xi; \Gamma \vdash_v V : \text{OSum} \quad \Xi; \Gamma \vdash_v \sigma : \text{Case } A \quad \Xi; \Gamma, x : A \vdash M : \underline{B} \quad \Xi; \Gamma \vdash_c N : \underline{B}}{\Xi; \Gamma \vdash_c \text{match } V \text{ with } \sigma \{ \text{inj } x.M \parallel N \} : \underline{B}} \\
\\
\frac{\Xi; \Gamma \vdash_v V : A_1 \times A_2 \quad \Xi; \Gamma, x : A_1, y : A_2 \vdash_c M : \underline{B}}{\Xi; \Gamma \vdash_c \text{let } (x, y) = V; M : \underline{B}} \\
\\
\frac{\Xi; \Gamma \vdash_v V : A_1 * A_2 \quad \Xi; \Gamma * x : A_1 * y : A_2 \vdash_c M : \underline{B}}{\Xi; \Gamma \vdash_c \text{let } (x * y) = V; M : \underline{B}} \\
\\
\frac{\Xi \vdash \underline{B} \quad \Xi; \Gamma \vdash_v V : \exists X.A \quad \Xi, X; \Gamma, x : A \vdash_c M : \underline{B}}{\Xi; \Gamma \vdash_c \text{unpack}(X, x) = V; M : \underline{B}}
\end{array}$$

## 2 Logic

### 2.1 Judgments

The relation environment,  $\Theta$  in PE logic contains both value and computation relations. How does this work in the semantics when value relations are denoted as objects of  $Sub_V(A \times B)$  for  $Rel_V[A, B]$  and computation relations are denoted as objects of  $Sub_C(\underline{A} \times \underline{B})$  for  $Rel_C[\underline{A}, \underline{B}]$ ? Maybe we have separate relation environments?

$$\begin{array}{l}
\Xi; \Gamma; \Theta \vdash \phi \text{ VProp} \\
\Xi; \Gamma; \Theta \vdash (x : A, y : B). \phi : Rel_V[A, B] \\
\Xi; \Gamma; \Theta \mid \Phi \vdash \phi \\
\Xi; \Gamma; \Delta; \Theta; \Omega \vdash \underline{\phi} \text{ CProp} \\
\Xi; \Gamma; \Delta; \Theta; \Omega \vdash (x : \underline{A}, y : \underline{B}). \underline{\phi} : Rel_C[\underline{A}, \underline{B}] \\
\Xi; \Gamma; \Delta; \Theta; \Omega \mid \Phi; \underline{\Psi} \vdash \underline{\phi}
\end{array}$$

for type environment  $\Xi$ , term environment  $\Gamma$ , stoup  $\Delta$ , value relation environment  $\Theta$ , computation relation environment  $\Omega$ , value proposition environment  $\Phi$ , and computation proposition environment  $\underline{\Psi}$ .

## 2.2 Formation Rules

### 2.2.1 Value Propositions

$$\begin{array}{c}
\phi := \top | \phi \wedge \phi | t =_A u | R(t, u) \\
\hline
\Xi; \Gamma; \Theta \vdash \top \text{ VProp} \\
\hline
\Xi; \Gamma; \Theta \vdash \phi \text{ VProp} \quad \Xi; \Gamma; \Theta \vdash \psi \text{ VProp} \\
\hline
\Xi; \Gamma; \Theta \vdash \phi \wedge \psi \text{ VProp} \\
\hline
\Xi; \Gamma \vdash_v t : A \quad \Xi; \Gamma \vdash_v u : A \\
\hline
\Xi; \Gamma; \Theta \vdash t =_A u \text{ VProp} \\
\hline
\Xi; \Gamma \vdash_v t : A \quad \Xi; \Gamma \vdash_v u : B \quad R : \text{Rel}_V[A, B] \in \Theta \\
\hline
\Xi; \Gamma; \Theta \vdash R(t, u) \text{ VProp}
\end{array}$$

### 2.2.2 Computation Propositions

$$\underline{\psi} := \top | \underline{\psi} \wedge \underline{\psi} | t =_B u | \phi \implies \underline{\psi} | \underline{R}(t, u) | \forall (x : A). \underline{\psi} | \forall X. \underline{\psi} | \forall \underline{X}. \underline{\psi} | \forall (R : \text{Rel}_V[A, B]). \underline{\psi} | \forall (R : \text{Rel}_C[\underline{A}, \underline{B}]). \underline{\psi}$$

$$\begin{array}{c}
\hline
\Xi; \Gamma; \Delta; \Theta; \Omega \vdash \top \text{ CProp} \\
\hline
\Xi; \Gamma; \Delta; \Theta; \Omega \vdash \underline{\phi} \text{ CProp} \quad \Xi; \Gamma; \Delta; \Theta; \Omega \vdash \underline{\psi} \text{ CProp} \\
\hline
\Xi; \Gamma; \Delta; \Theta; \Omega \vdash \underline{\phi} \wedge \underline{\psi} \text{ CProp} \\
\hline
\Xi; \Gamma \vdash_c t : \underline{B} \quad \Xi; \Gamma \vdash_c u : \underline{B} \\
\hline
\Xi; \Gamma; \Delta; \Theta; \Omega \vdash t =_{\underline{B}} u \text{ CProp} \\
\hline
\Xi; \Gamma; \Theta \vdash \phi \text{ VProp} \quad \Xi; \Gamma; \Delta; \Theta; \Omega \vdash \underline{\psi} \text{ CProp} \\
\hline
\Xi; \Gamma; \Delta; \Theta; \Omega \vdash \phi \implies \underline{\psi} \text{ CProp} \\
\hline
\Xi; \Gamma \vdash_c t : \underline{A} \quad \Xi; \Gamma \vdash_c u : \underline{B} \quad \underline{R} : \text{Rel}_C[\underline{A}, \underline{B}] \in \Omega \\
\hline
\Xi; \Gamma; \Delta; \Theta; \Omega \vdash \underline{R}(t, u) \text{ CProp} \\
\hline
\Xi; \Gamma, x : A; \Delta; \Theta; \Omega \vdash \underline{\psi} \text{ CProp} \\
\hline
\Xi; \Gamma; \Delta; \Theta; \Omega \vdash \forall (x : A). \underline{\psi} \text{ CProp} \\
\hline
\Xi, X; \Gamma; \Delta; \Theta; \Omega \vdash \underline{\psi} \text{ CProp} \\
\hline
\Xi; \Gamma; \Delta; \Theta; \Omega \vdash \forall X. \underline{\psi} \text{ CProp} \\
\hline
\Xi, \underline{X}; \Gamma; \Delta; \Theta; \Omega \vdash \underline{\psi} \text{ CProp} \\
\hline
\Xi; \Gamma; \Delta; \Theta; \Omega \vdash \forall \underline{X}. \underline{\psi} \text{ CProp} \\
\hline
\Xi; \Gamma; \Delta; \Theta, R; \Omega \vdash \underline{\psi} \text{ CProp} \\
\hline
\Xi; \Gamma; \Delta; \Theta; \Omega \vdash \forall R. \underline{\psi} \text{ CProp} \\
\hline
\Xi; \Gamma; \Delta; \Theta; \Omega, \underline{R} \vdash \underline{\psi} \text{ CProp} \\
\hline
\Xi; \Gamma; \Delta; \Theta; \Omega \vdash \forall \underline{R}. \underline{\psi} \text{ CProp}
\end{array}$$

### 2.2.3 Value Relations

$$\frac{\Xi; \Gamma, x : A \vdash_v t : C \quad \Xi; \Gamma, y : B \vdash_v u : C}{\Xi; \Gamma; \Theta \vdash (x : A, y : B).t =_C u : Rel_V[A, B]}$$

$$\frac{\Xi; \Gamma, x : A \vdash_v t : C \quad \Xi; \Gamma, y : B \vdash_v u : D}{\Xi; \Gamma; \Theta, R : Rel_V[C, D] \vdash (x : A, y : B).R(t, u) : Rel_V[A, B]}$$

### 2.2.4 Computation Relations

Something seems off including the stoup,  $\Delta$ , in the computation relation judgment..

$$\frac{\Xi; \Gamma | x : \underline{A} \vdash_c t : \underline{C} \quad \Xi; \Gamma | y : \underline{B} \vdash_c u : \underline{C}}{\Xi; \Gamma; \Delta; \Theta; \Omega \vdash (x : \underline{A}, y : \underline{B}).t =_{\underline{C}} u : Rel_C[\underline{A}, \underline{B}]}$$

$$\frac{\Xi; \Gamma | x : \underline{A} \vdash_c t : \underline{C} \quad \Xi; \Gamma | y : \underline{B} \vdash_c u : \underline{D}}{\Xi; \Gamma; \Delta; \Theta; \Omega, \underline{R} : Rel_C[\underline{C}, \underline{D}] \vdash (x : \underline{A}, y : \underline{B}).\underline{R}(t, u) : Rel_C[\underline{A}, \underline{B}]}$$

## 2.3 Derivation Rules

### 2.3.1 Values

$$\frac{}{\Xi; \Gamma; \Theta | \Phi \vdash \top}$$

$$\frac{\Xi; \Gamma; \Theta | \Phi \vdash \phi \quad \Xi; \Gamma; \Theta | \Phi \vdash \psi}{\Xi; \Gamma; \Theta | \Phi \vdash \phi \wedge \psi} \text{I-}\wedge$$

$$\frac{\Xi; \Gamma; \Theta | \Phi \vdash \phi \wedge \psi}{\Xi; \Gamma; \Theta | \Phi \vdash \phi} \text{E1-}\wedge$$

$$\frac{\Xi; \Gamma; \Theta | \Phi \vdash \phi \wedge \psi}{\Xi; \Gamma; \Theta | \Phi \vdash \psi} \text{E2-}\wedge$$

$$\frac{\Xi; \Gamma \vdash_v t : A}{\Xi; \Gamma; \Theta | \Phi \vdash t =_A t}$$

$$\frac{\Xi; \Gamma; \Theta | \Phi \vdash t =_A u \quad \Xi; \Gamma; \Theta | \Phi \vdash \phi[t/x]}{\Xi; \Gamma; \Theta | \Phi \vdash \phi[u/x]}$$

Rel

$$\frac{\Xi; \Gamma; \Theta | \Phi \vdash \quad \Xi; \Gamma; \Theta | \Phi \vdash}{\Xi; \Gamma; \Theta | \Phi \vdash}$$

### 2.3.2 Computation

$$\begin{array}{c}
\frac{}{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \perp} \\
\\
\frac{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \underline{\phi} \quad \Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \underline{\psi}}{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \underline{\phi} \wedge \underline{\psi}} \text{I-}\wedge \\
\\
\frac{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \underline{\phi} \wedge \underline{\psi}}{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \underline{\phi}} \text{E1-}\wedge \\
\\
\frac{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \underline{\phi} \wedge \underline{\psi}}{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \underline{\psi}} \text{E2-}\wedge \\
\\
\frac{\Xi; \Gamma \vdash_c t : \underline{B}}{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash t =_{\underline{B}} t} \\
\\
\frac{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash t =_{\underline{B}} u \quad \Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \underline{\phi}[t/x]}{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \underline{\phi}[u/x]} \\
\\
\frac{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \phi; \Psi \vdash \underline{\psi}}{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \phi \implies \underline{\psi}} \text{I-}\implies \\
\\
\frac{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \phi \implies \underline{\psi} \quad \Xi; \Gamma; \Theta | \Phi \vdash \phi}{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \underline{\psi}} \text{E-}\implies
\end{array}$$

Rel?

$$\begin{array}{c}
\frac{\Xi; \Gamma, x : A; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \underline{\phi}}{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \forall(x : A).\underline{\phi}} \text{I-}\forall \text{ term , FV constraint?} \\
\\
\frac{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \forall(x : A).\underline{\phi} \quad \Xi; \Gamma \vdash_v t : A}{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \underline{\phi}[t/x]} \text{E-}\forall \text{ term} \\
\\
\frac{\Xi, X; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \underline{\phi}}{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \forall X.\underline{\phi}} \text{I-}\forall \text{ vtype , FV constraint?} \\
\\
\frac{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \forall X.\underline{\phi} \quad \Xi \vdash A}{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \underline{\phi}[A/X]} \text{E-}\forall \text{ vtype} \\
\\
\frac{\Xi, \underline{X}; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \underline{\phi}}{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \forall \underline{X}.\underline{\phi}} \text{I-}\forall \text{ ctype , FV constraint?}
\end{array}$$

$$\begin{array}{c}
\frac{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \forall \underline{X}. \underline{\phi} \quad \Xi \vdash \underline{A}}{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \underline{\phi}[\underline{A}/\underline{X}]} \text{E-}\forall \text{ ctype} \\
\\
\frac{\Xi; \Gamma; \Delta; \Theta; (R : Rel_{\mathcal{V}}[A, B]); \Omega | \Phi; \Psi \vdash \underline{\phi}}{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \forall (R : Rel_{\mathcal{V}}[A, B]). \underline{\phi}} \text{I-}\forall \text{ vrel} \\
\\
\frac{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \forall (R : Rel_{\mathcal{V}}[A, B]). \underline{\phi} \quad \Xi; \Gamma; \Theta, \vdash (x : A, y : B). \psi : Rel_{\mathcal{V}}[A, B]}{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \forall (R : Rel_{\mathcal{V}}[A, B]). \underline{\phi}[\psi[t/x, u/y]/R(t, u)]} \text{E-}\forall \text{ vrel} \\
\\
\frac{\Xi; \Gamma; \Delta; \Theta; (\underline{R} : Rel_{\mathcal{C}}[\underline{A}, \underline{B}]); \Omega | \Phi; \Psi \vdash \underline{\phi}}{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \forall (\underline{R} : Rel_{\mathcal{C}}[\underline{A}, \underline{B}]). \underline{\phi}} \text{I-}\forall \text{ crel} \\
\\
\frac{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \forall (R : Rel_{\mathcal{C}}[\underline{A}, \underline{B}]). \underline{\phi} \quad \Xi; \Gamma; \Delta; \Theta; \Omega, \vdash (x : \underline{A}, y : \underline{B}). \underline{\psi} : Rel_{\mathcal{C}}[\underline{A}, \underline{B}]}{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \forall (R : Rel_{\mathcal{C}}[\underline{A}, \underline{B}]). \underline{\phi}[\underline{\psi}[t/x, u/y]/R(t, u)]} \text{E-}\forall \text{ crel}
\end{array}$$

### 2.3.3 Congruences

$$\frac{\Xi; \Gamma \vdash_c t : \underline{B} \quad \Xi; \Gamma \vdash_c u : \underline{B} \quad \Xi; \Gamma, x : A; \Delta; \Theta; \Omega | \Phi; \Psi \vdash t = u}{\Xi; \Gamma; \Delta; \Theta; \Omega | \Phi; \Psi \vdash \lambda(x : A). t = \lambda(x : A). u} \text{cong-}\lambda$$

## 2.4 Axioms

Beta/Eta/(parametricity schema?)

## 2.5 Logical Interpretation of Types

Let  $\underline{X}$  and  $\underline{X}$  be vectors of value type and computation type variables of length  $n$ . Let  $\underline{\rho}$  be a vector of value relations  $\Xi; \Gamma; \Theta \vdash \rho_i : Rel_{\mathcal{V}}[C_i, C'_i]$  for all  $i \in 1..n$ . Let  $\underline{\rho}$  be a vector of computation relations  $\Xi; \Gamma; \Delta; \Theta; \Omega \vdash \rho_i : Rel_{\mathcal{C}}[\underline{C}_i, \underline{C}'_i]$  for all  $i \in 1..n$ .

Let  $A$  be a **value type** with  $FTV(A) \in \{\underline{X}, \underline{X}\}$ . Define:

$$A[\underline{\rho}/\underline{X}, \underline{\rho}/\underline{X}] : Rel_{\mathcal{V}}[A[\underline{C}/\underline{X}, \underline{C}/\underline{X}], A[\underline{C}'/\underline{X}, \underline{C}'/\underline{X}]]$$

by induction on  $A$ .

$$\begin{aligned}
X_i[\underline{\rho}, \underline{\rho}] &= \rho_i \\
\text{Unit}[\underline{\rho}, \underline{\rho}] &= (x : \text{Unit}, y : \text{Unit}). x =_{\text{Unit}} y \\
\text{CaseA}[\underline{\rho}, \underline{\rho}] &= (x : \text{Case } (A[\underline{C}/\underline{X}, \underline{C}/\underline{X}]), y : \text{Case } (A[\underline{C}'/\underline{X}, \underline{C}'/\underline{X}])). \\
&\quad \text{think exists?} \\
\text{OSum}[\underline{\rho}, \underline{\rho}] &= \text{think exists?} \\
A \times A'[\underline{\rho}, \underline{\rho}] &= ((x, y) : A \times A'[\underline{C}/\underline{X}, \underline{C}/\underline{X}], (x', y') : A \times A'[\underline{C}'/\underline{X}, \underline{C}'/\underline{X}]). \\
&\quad A[\underline{\rho}, \underline{\rho}](x, x') \wedge A'[\underline{\rho}, \underline{\rho}](y, y') \\
A * A'[\underline{\rho}, \underline{\rho}] &= \text{similar to product?} \\
\exists X. A[\underline{\rho}, \underline{\rho}] &= \text{standard} \\
U\underline{B}[\underline{\rho}, \underline{\rho}] &= \text{related thunks?}
\end{aligned}$$

Let  $\underline{B}$  be a **computation type** with  $FTV(\underline{B}) \in \{\underline{X}, \underline{X}\}$ . Define:

$$\underline{B}[\underline{\rho}/\underline{X}, \underline{\rho}/\underline{X}] : \text{Rel}_{\mathcal{C}}[\underline{B}[\underline{C}/\underline{X}, \underline{C}/\underline{X}], \underline{B}[\underline{C}'/\underline{X}, \underline{C}'/\underline{X}]]$$

by induction on  $\underline{B}$ .

$$\begin{aligned}
A \rightarrow \underline{B}[\underline{\rho}, \underline{\rho}] &= \text{Add weakest precondition to the proposition syntax to interpret this?} \\
A * \underline{B}[\underline{\rho}, \underline{\rho}] &= \\
\forall X. \underline{B}[\underline{\rho}, \underline{\rho}] &= \\
FA[\underline{\rho}, \underline{\rho}] &= \text{Could be encoded if we add } \forall \underline{X}. \underline{B}?
\end{aligned}$$

### 3 Goal

Try to prove

$$\begin{aligned}
&\vdash_d \forall A \underline{B}. \\
&\quad \forall (y : \text{OSum}). \\
&\quad \forall (f : U(\forall X. \text{Case } X * \text{OSum} \rightarrow FX)). \\
&\quad \forall (k \ k' : U(A \rightarrow \underline{B})). \\
&\quad \text{newcase}_A \sigma; x \leftarrow (!f)[A]\sigma y; (!k)x \\
&\quad = \\
&\quad \text{newcase}_A \sigma; x \leftarrow (!f)[A]\sigma y; (!k')x
\end{aligned}$$