

OUTPUT: ORGANIZE TESTS WITH SUITES

```
when opts.expectsValue is an object
```

```
  ✓ should throw a TypeError
```

```
when opts.expectsValue is a nonzero number
```

```
  ✓ should throw a TypeError
```

```
when passed a single argument "--foo"
```

```
  ✓ should return an object having property foo: true
```

```
3 passing (7ms)
```

ANSWER: ORGANIZE TESTS WITH SUITES

test/bargs.spec.js

```
const assert = require('assert');
const {parse} = require('bargs');

describe('when opts.expectsValue is an object', function () {
  it('should throw a TypeError', function () {
    assert.throws(() => {
      parse({
        expectsValue: {},
      }),
      {
        name: 'TypeError',
        message: /object is not iterable/,
      };
    });
  });
});

describe('when opts.expectsValue is a nonzero number',
function () {
  it('should throw a TypeError', function () {
    assert.throws(() => {
      parse({
```

```
        expectsValue: 1,
      }),
      {
        name: 'TypeError',
        message: /number 1 is not iterable/,
      };
    });
  });
});

describe('when passed a single argument "--foo"', function () {
  it('should return an object having property foo: true',
function () {
    assert.deepStrictEqual(parse(['--foo']), {_: [], foo:
true});
  });
});
```