

# Principles of AI Planning

## 2. Transition systems and planning tasks

Bernhard Nebel and Robert Mattmüller

Albert-Ludwigs-Universität Freiburg

October 25th, 2011

# Transition systems

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Definition  
Blocks world

Planning tasks

Summary

# Transition systems

## Definition (transition system)

A **transition system** is a 5-tuple  $\mathcal{T} = \langle S, L, T, s_0, S_\star \rangle$  where

- $S$  is a finite set of **states**,
- $L$  is a finite set of (transition) **labels**,
- $T \subseteq S \times L \times S$  is the **transition relation**,
- $s_0 \in S$  is the **initial state**, and
- $S_\star \subseteq S$  is the set of **goal states**.

We say that  $\mathcal{T}$  **has the transition**  $\langle s, \ell, s' \rangle$  if  $\langle s, \ell, s' \rangle \in T$ .

We also write this  $s \xrightarrow{\ell} s'$ , or  $s \rightarrow s'$  when not interested in  $\ell$ .

**Note:** Transition systems are also called **state spaces**.

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems


Definition  
Blocks world

Planning tasks

Summary

# Transition systems: example

Transition systems are often depicted as **directed arc-labeled graphs** with marks to indicate the initial state and goal states.



AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Definition  
Blocks world

Planning tasks

Summary

# Transition system terminology

We use common graph theory terms for transition systems:

- $s'$  **successor** of  $s$  if  $s \rightarrow s'$
- $s$  **predecessor** of  $s'$  if  $s \rightarrow s'$
- $s'$  **reachable** from  $s$  if there exists a sequence of transitions  $s^0 \xrightarrow{\ell_1} s^1, \dots, s^{n-1} \xrightarrow{\ell_n} s^n$  s.t.  $s^0 = s$  and  $s^n = s'$ 
  - **Note:**  $n = 0$  possible; then  $s = s'$
  - $s^0 \xrightarrow{\ell_1} s^1, \dots, s^{n-1} \xrightarrow{\ell_n} s^n$  is called **path** from  $s$  to  $s'$
  - $s^0, \dots, s^n$  is also called **path** from  $s$  to  $s'$
  - **length** of that path is  $n$
- additional terms: **strongly connected**, **weakly connected**, **strong/weak connected components**, ...

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Definition  
Blocks world

Planning tasks

Summary

# Transition system terminology (ctd.)

Some additional terminology:

- $s'$  **reachable** (without reference state) means reachable from initial state  $s_0$
- **solution** or **goal path** from  $s$ : path from  $s$  to some  $s' \in S_\star$ 
  - if  $s$  is omitted,  $s = s_0$  is implied
- transition system **solvable** if a goal path from  $s_0$  exists

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Definition  
Blocks world

Planning tasks

Summary

# Deterministic transition systems

## Definition (deterministic transition system)

A transition system with transitions  $T$  is called **deterministic** if for all states  $s$  and labels  $\ell$ , there is **at most one** state  $s'$  with  $s \xrightarrow{\ell} s'$ .

**Example:** previously shown transition system

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Definition  
Blocks world

Planning tasks

Summary

# Running example: blocks world

- Throughout the course, we will often use the **blocks world** domain as an example.
- In the blocks world, a number of differently coloured blocks are arranged on our table.
- Our job is to rearrange them according to a given goal.

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Definition  
Blocks world

Planning tasks

Summary




# Blocks world rules

Location on the table does not matter.



Location on a block does not matter.



AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems


Definition  
Blocks world

Planning tasks


Summary

# Blocks world rules (ctd.)

At most one block may be below a block.



At most one block may be on top of a block.



AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems


Definition  
Blocks world

Planning tasks

Summary

# Blocks world transition system for three blocks

(Transition labels omitted for clarity.)



AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Definition  
Blocks world

Planning tasks

Summary

# Blocks world computational properties

blocks	states	blocks	states
1	1	10	58941091
2	3	11	824073141
3	13	12	12470162233
4	73	13	202976401213
5	501	14	3535017524403
6	4051	15	65573803186921
7	37633	16	1290434218669921
8	394353	17	26846616451246353
9	4596553	18	588633468315403843

- Finding a solution is polynomial time in the number of blocks (move everything onto the table and then construct the goal configuration).
- Finding a shortest solution is NP-complete (for a compact description of the problem).

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Definition  
Blocks world

Planning tasks

Summary

# Planning tasks

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

**Planning tasks**

State variables

Logic

Operators

Tasks

Summary

# Compact representations

- Classical (i. e., deterministic) planning is in essence the problem of finding solutions in **huge** transition systems.
- The transition systems we are usually interested in are too large to explicitly enumerate all states or transitions.
- Hence, the input to a planning algorithm must be given in a more **concise** form.
- In the rest of chapter, we discuss how to represent planning tasks in a suitable way.

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Planning tasks

State variables

Logic

Operators

Tasks

Summary

# State variables

How to represent huge state sets without enumerating them?

- represent different aspects of the world in terms of different **state variables**
- ⇒ a state is a **valuation of state variables**
- $n$  state variables with  $m$  possible values each induce  $m^n$  different states
- ⇒ **exponentially more compact** than “flat” representations
- **Example:**  $n$  variables suffice for blocks world with  $n$  blocks

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Planning tasks

State variables

Logic

Operators

Tasks

Summary

# Blocks world with finite-domain state variables

Describe blocks world state with three state variables:


- *location-of-A*: {B, C, table}
- *location-of-B*: {A, C, table}
- *location-of-C*: {A, B, table}

## Example

$s(\text{location-of-A}) = \text{table}$

$s(\text{location-of-B}) = A$

$s(\text{location-of-C}) = \text{table}$



Not all valuations correspond to intended blocks world states.

**Example:**  $s$  with  $s(\text{location-of-A}) = B$ ,  $s(\text{location-of-B}) = A$ .

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Planning tasks

State variables

Logic

Operators

Tasks

Summary



# Boolean state variables

Problem:

- How to **succinctly** represent **transitions** and **goal states**?

Idea: Use **propositional logic**

- **state variables**: propositional variables (0 or 1)
- **goal states**: defined by a propositional formula
- **transitions**: defined by **actions** given by
  - **precondition**: when is the action applicable?
  - **effect**: how does it change the valuation?

**Note:** general finite-domain state variables can be compactly encoded as Boolean variables

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Planning tasks

State variables

Logic

Operators

Tasks

Summary

# Blocks world with Boolean state variables

## Example

$$s(A\text{-on-}B) = 0$$

$$s(A\text{-on-}C) = 0$$

$$s(A\text{-on-table}) = 1$$

$$s(B\text{-on-}A) = 1$$


$$s(B\text{-on-}C) = 0$$

$$s(B\text{-on-table}) = 0$$

$$s(C\text{-on-}A) = 0$$

$$s(C\text{-on-}B) = 0$$

$$s(C\text{-on-table}) = 1$$



AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Planning tasks

**State variables**

Logic

Operators

Tasks

Summary

# Syntax of propositional logic

## Definition (propositional formula)

Let  $A$  be a set of **atomic propositions** (here: state variables).

The **propositional formulae** over  $A$  are constructed by finite application of the following rules:

- $\top$  and  $\perp$  are propositional formulae (**truth** and **falsity**).
- For all  $a \in A$ ,  $a$  is a propositional formula (**atom**).
- If  $\varphi$  is a propositional formula, then so is  $\neg\varphi$  (**negation**).
- If  $\varphi$  and  $\psi$  are propositional formulas, then so are  $(\varphi \vee \psi)$  (**disjunction**) and  $(\varphi \wedge \psi)$  (**conjunction**).

**Note:** We often omit the word “propositional”.

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Planning tasks

State variables

Logic

Operators

Tasks

Summary

# Propositional logic conventions

## Abbreviations:

- $(\varphi \rightarrow \psi)$  is short for  $(\neg\varphi \vee \psi)$  (**implication**)
- $(\varphi \leftrightarrow \psi)$  is short for  $((\varphi \rightarrow \psi) \wedge (\psi \rightarrow \varphi))$  (**equivalence**)
- parentheses omitted when not necessary
- $(\neg)$  binds more tightly than binary connectives
- $(\wedge)$  binds more tightly than  $(\vee)$  than  $(\rightarrow)$  than  $(\leftrightarrow)$

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Planning tasks

State variables

Logic

Operators

Tasks

Summary

# Semantics of propositional logic

## Definition (propositional valuation)

A **valuation** of propositions  $A$  is a function  $v : A \rightarrow \{0, 1\}$ .

Define the notation  $v \models \varphi$  ( $v$  **satisfies**  $\varphi$ ;  $v$  is a **model** of  $\varphi$ ;  $\varphi$  is **true** under  $v$ ) for valuations  $v$  and formulae  $\varphi$  by

- $v \models \top$
- $v \not\models \perp$
- $v \models a$  iff  $v(a) = 1$ , for  $a \in A$ .
- $v \models \neg\varphi$  iff  $v \not\models \varphi$
- $v \models \varphi \vee \psi$  iff  $v \models \varphi$  or  $v \models \psi$
- $v \models \varphi \wedge \psi$  iff  $v \models \varphi$  and  $v \models \psi$

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Planning tasks

State variables

Logic

Operators

Tasks

Summary

# Propositional logic terminology

- A propositional formula  $\varphi$  is **satisfiable** if there is at least one valuation  $v$  so that  $v \models \varphi$ .
- Otherwise it is **unsatisfiable**.
- A propositional formula  $\varphi$  is **valid** or a **tautology** if  $v \models \varphi$  for all valuations  $v$ .
- A propositional formula  $\psi$  is a **logical consequence** of a propositional formula  $\varphi$ , written  $\varphi \models \psi$ , if  $v \models \psi$  for all valuations  $v$  with  $v \models \varphi$ .
- Two propositional formulae  $\varphi$  and  $\psi$  are **logically equivalent**, written  $\varphi \equiv \psi$ , if  $\varphi \models \psi$  and  $\psi \models \varphi$ .

**Question:** How to phrase these in terms of **models**?

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Planning tasks

State variables

Logic

Operators

Tasks

Summary

# Propositional logic terminology (ctd.)

- A propositional formula that is a proposition  $a$  or a negated proposition  $\neg a$  for some  $a \in A$  is a **literal**.
- A formula that is a disjunction of literals is a **clause**. This includes **unit clauses**  $l$  consisting of a single literal, and the **empty clause**  $\perp$  consisting of zero literals.

**Normal forms:** NNF, CNF, DNF

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Planning tasks

State variables

Logic

Operators

Tasks

Summary

# Operators

Transitions for state sets described by propositions  $A$  can be concisely represented as **operators** or **actions**  $\langle \chi, e \rangle$  where

- the **precondition**  $\chi$  is a propositional formula over  $A$  describing the set of states in which the transition can be taken (states in which a transition starts), and
- the **effect**  $e$  describes how the resulting successor states are obtained from the state where the transition is taken (where the transition goes).

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Planning tasks

State variables

Logic

Operators

Tasks

Summary



# Example: blocks world operators

## Blocks world operators

To model blocks world operators conveniently, we use auxiliary state variables *A-clear*, *B-clear*, and *C-clear* to denote that there is nothing on top of a given block.

Then blocks world operators can be modeled as:

- $\langle A\text{-clear} \wedge A\text{-on-}T \wedge B\text{-clear}, A\text{-on-}B \wedge \neg A\text{-on-}T \wedge \neg B\text{-clear} \rangle$
- $\langle A\text{-clear} \wedge A\text{-on-}T \wedge C\text{-clear}, A\text{-on-}C \wedge \neg A\text{-on-}T \wedge \neg C\text{-clear} \rangle$
- $\langle A\text{-clear} \wedge A\text{-on-}B, A\text{-on-}T \wedge \neg A\text{-on-}B \wedge B\text{-clear} \rangle$
- $\langle A\text{-clear} \wedge A\text{-on-}C, A\text{-on-}T \wedge \neg A\text{-on-}C \wedge C\text{-clear} \rangle$
- $\langle A\text{-clear} \wedge A\text{-on-}B \wedge C\text{-clear}, A\text{-on-}C \wedge \neg A\text{-on-}B \wedge B\text{-clear} \wedge \neg C\text{-clear} \rangle$
- $\langle A\text{-clear} \wedge A\text{-on-}C \wedge B\text{-clear}, A\text{-on-}B \wedge \neg A\text{-on-}C \wedge C\text{-clear} \wedge \neg B\text{-clear} \rangle$
- ...

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Planning tasks

State variables

Logic

Operators

Tasks

Summary

# Effects (for deterministic operators)

## Definition (effects)

(Deterministic) **effects** are recursively defined as follows:

- If  $a \in A$  is a state variable, then  $a$  and  $\neg a$  are effects (**atomic effect**).
- If  $e_1, \dots, e_n$  are effects, then  $e_1 \wedge \dots \wedge e_n$  is an effect (**conjunctive effect**).

The special case with  $n = 0$  is the empty effect  $\top$ .

- If  $\chi$  is a propositional formula and  $e$  is an effect, then  $\chi \triangleright e$  is an effect (**conditional effect**).

Atomic effects  $a$  and  $\neg a$  are best understood as assignments  $a := 1$  and  $a := 0$ , respectively.

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Planning tasks

State variables

Logic

Operators

Tasks

Summary

# Effect example

$\chi \triangleright e$  means that change  $e$  takes place if  $\chi$  is true in the current state.

## Example

Increment 4-bit number  $b_3b_2b_1b_0$  represented as four state variables  $b_0, \dots, b_3$ :

$$\begin{aligned} & (\neg b_0 \triangleright b_0) \wedge \\ & ((\neg b_1 \wedge b_0) \triangleright (b_1 \wedge \neg b_0)) \wedge \\ & ((\neg b_2 \wedge b_1 \wedge b_0) \triangleright (b_2 \wedge \neg b_1 \wedge \neg b_0)) \wedge \\ & ((\neg b_3 \wedge b_2 \wedge b_1 \wedge b_0) \triangleright (b_3 \wedge \neg b_2 \wedge \neg b_1 \wedge \neg b_0)) \end{aligned}$$

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Planning tasks

State variables

Logic

Operators

Tasks

Summary

# Operator semantics

## Definition (changes caused by an operator)

For each effect  $e$  and state  $s$ , we define the **change set** of  $e$  in  $s$ , written  $[e]_s$ , as the following set of literals:

- $[a]_s = \{a\}$  and  $[\neg a]_s = \{\neg a\}$  for atomic effects  $a$ ,  $\neg a$
- $[e_1 \wedge \dots \wedge e_n]_s = [e_1]_s \cup \dots \cup [e_n]_s$
- $[\chi \triangleright e]_s = [e]_s$  if  $s \models \chi$  and  $[\chi \triangleright e]_s = \emptyset$  otherwise

## Definition (applicable operators)

Operator  $\langle \chi, e \rangle$  is **applicable in a state  $s$**  iff  $s \models \chi$  and  $[e]_s$  is consistent (i. e., does not contain two complementary literals).

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Planning tasks

State variables

Logic

Operators

Tasks

Summary

# Operator semantics (ctd.)

## Definition (successor state)

The **successor state**  $app_o(s)$  of  $s$  with respect to operator  $o = \langle \chi, e \rangle$  is the state  $s'$  with  $s' \models [e]_s$  and  $s'(v) = s(v)$  for all state variables  $v$  not mentioned in  $[e]_s$ .

This is defined only if  $o$  is applicable in  $s$ .

## Example

Consider the operator  $\langle a, \neg a \wedge (\neg c \triangleright \neg b) \rangle$  and the state  $s = \{a \mapsto 1, b \mapsto 1, c \mapsto 1, d \mapsto 1\}$ .

The operator is applicable because  $s \models a$  and  $[\neg a \wedge (\neg c \triangleright \neg b)]_s = \{\neg a\}$  is consistent.

Applying the operator results in the successor state  $app_{\langle a, \neg a \wedge (\neg c \triangleright \neg b) \rangle}(s) = \{a \mapsto 0, b \mapsto 1, c \mapsto 1, d \mapsto 1\}$ .

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Planning tasks

State variables

Logic

Operators

Tasks

Summary

# Deterministic planning tasks

## Definition (deterministic planning task)

A **deterministic planning task** is a 4-tuple  $\Pi = \langle A, I, O, \gamma \rangle$  where

- $A$  is a finite set of **state variables** (propositions),
- $I$  is a valuation over  $A$  called the **initial state**,
- $O$  is a finite set of **operators** over  $A$ , and
- $\gamma$  is a formula over  $A$  called the **goal**.

## Note:

- In the major part of this course, in which we talk about deterministic planning tasks, we usually omit the word “deterministic”.
- When we will talk about nondeterministic planning tasks later, we will explicitly qualify them as “nondeterministic”.

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Planning tasks

State variables

Logic

Operators

Tasks

Summary

# Mapping planning tasks to transition systems

## Definition (induced transition system of a planning task)

Every planning task  $\Pi = \langle A, I, O, \gamma \rangle$  induces a corresponding deterministic transition system  $\mathcal{T}(\Pi) = \langle S, L, T, s_0, S_\star \rangle$ :

- $S$  is the set of all valuations of  $A$ ,
- $L$  is the set of operators  $O$ ,
- $T = \{ \langle s, o, s' \rangle \mid s \in S, o \text{ applicable in } s, s' = \text{app}_o(s) \},$
- $s_0 = I$ , and
- $S_\star = \{ s \in S \mid s \models \gamma \}$

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Planning tasks

State variables

Logic

Operators

Tasks

Summary

# Planning tasks: terminology

- Terminology for transitions systems is also applied to the planning tasks that induce them.
- For example, when we speak of the **states of  $\Pi$** , we mean the states of  $\mathcal{T}(\Pi)$ .
- A sequence of operators that forms a goal path of  $\mathcal{T}(\Pi)$  is called a **plan** of  $\Pi$ .

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Planning tasks

State variables

Logic

Operators

Tasks

Summary



# Planning

By **planning**, we mean the following two algorithmic problems:

## Definition (satisficing planning)

Given: a planning task  $\Pi$

Output: a plan for  $\Pi$ , or **unsolvable** if no plan for  $\Pi$  exists

## Definition (optimal planning)

Given: a planning task  $\Pi$

Output: a plan for  $\Pi$  with minimal length among all plans for  $\Pi$ , or **unsolvable** if no plan for  $\Pi$  exists

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Planning tasks

State variables

Logic

Operators

Tasks

Summary

# Summary

- **Transition systems** are a kind of directed graph (typically huge) that encode how the state of the world can change.
- **Planning tasks** are compact representations for transition systems, suitable as input for planning algorithms.
- Planning tasks are based on concepts from **propositional logic**, suitably enhanced to model state change.
- **States** of planning tasks are propositional valuations.
- **Operators** of planning tasks describe **when** (precondition) and **how** (effect) to change the current state of the world.
- In **satisficing planning**, we must find a solution to planning tasks (or show that no solution exists).
- In **optimal planning**, we must additionally guarantee that generated solutions are of the shortest possible length.

AI Planning

B. Nebel,  
R. Mattmüller

Transition  
systems

Planning tasks

Summary